

used to convey instrument-pointing information to the activity plan. The software allows users to develop a plan of what they would like the rover to accomplish for a given time period. When developing the plan, the user can input constraints between activities or groups of activities. MSLICE will enforce said

constraints and ensure that all mission flight rules are satisfied.

This work was done by Mark W. Powell, Khawaja S. Shams, Michael N. Wallick, Jeffrey S. Norris, Joseph C. Joswig, Thomas M. Crockett, Jason M. Fox, Recaredo J. Torres of Caltech; James A. Kurien, Michael P. McCurdy, and Guy Pyrzak of NASA Ames Re-

search Center; and Arash Agheoli and Andrew G. Bachmann of Stinger Ghaffarian Technologies, Inc. for NASA's Jet Propulsion Laboratory.

This software is available for commercial licensing. Please contact Karina Edmonds of the California Institute of Technology at (626) 395-2322. Refer to NPO-45908.

▶ Telemetry-Enhancing Scripts

NASA's Jet Propulsion Laboratory, Pasadena, California

Scripts Providing a Cool Kit of Telemetry Enhancing Tools (SPACKLE) is a set of software tools that fill gaps in capabilities of other software used in processing downlinked data in the Mars Exploration Rovers' (MER) flight and test-bed operations. SPACKLE tools have helped to accelerate the automatic processing and interpretation of MER mission data, enabling non-experts to understand and/or use MER query and data product command simulation software tools more effectively. SPACKLE has greatly accelerated some operations and provides new capabilities.

The tools of SPACKLE are written, variously, in Perl or the C or C++ language. They perform a variety of search and shortcut functions that include the following:

- Generating text-only, Event Report-annotated, and Web-enhanced views of command sequences;
- Labeling integer enumerations with their symbolic meanings in text messages and engineering channels;
- Systematic detecting of corruption within data products;
- Generating text-only displays of data-product catalogs including downlink status;
- Validating and labeling of commands related to data products;

- Performing of convenient searches of detailed engineering data spanning multiple Martian solar days;
- Generating tables of initial conditions pertaining to engineering, health, and accountability data;
- Simplified construction and simulation of command sequences; and
- Fast time format conversions and sorting.

This program was written by Mark W. Maimone of Caltech for NASA's Jet Propulsion Laboratory.

This software is available for commercial licensing. Please contact Karina Edmonds of the California Institute of Technology at (626) 395-2322. Refer to NPO-45700.

▶ Analog Input Data Acquisition Software

John F. Kennedy Space Center, Florida

DAQ Master Software allows users to easily set up a system to monitor up to five analog input channels and save the data after acquisition. This program was written in LabVIEW 8.0, and requires the LabVIEW runtime engine 8.0 (free download from National Instruments; ni.com) to run the executable. A DAQ card must be installed in the computer for this program to work correctly, and it must have

up to five analog input channels. The user can set the channel configuration, and other channel details, from the setup tab after the program has begun.

A Setup tab holds all information for the channels that will be used for data acquisition, and allows the user to save or upload the settings for future use by writing or reading a configuration file. The Data Acquisition tab is where the

commands to acquire, stop, and save data are located, and where the data will be displayed. The user can choose to display scaled or un-scaled data while acquisition is taking place.

This work was done by Ellen Arens of Kennedy Space Center. For more information, visit http://www.openchannelsoftware.com/projects/Analog_Input_Data_Acquisition for a free download. KSC-13203

▶ Relay Sequence Generation Software

NASA's Jet Propulsion Laboratory, Pasadena, California

Due to thermal and electromagnetic interactivity between the UHF (ultra-high frequency) radio onboard the Mars Reconnaissance Orbiter (MRO), which performs relay sessions with the Martian landers, and the remainder of the MRO payloads, it is required to integrate and

de-conflict relay sessions with the MRO science plan. The MRO relay SASE/PTF (spacecraft activity sequence file/ payload target file) generation software facilitates this process by generating a PTF that is needed to integrate the periods of time during which MRO supports relay

activities with the rest of the MRO science plans. The software also generates the needed command products that initiate the relay sessions, some features of which are provided by the lander team, some are managed by MRO internally, and some being derived.