code with these tools can vary greatly. In each case, however, the tools produce results that would be difficult to realize with human code inspections alone. There is little overlap in the results produced by the different analyzers, and each analyzer used generally increases the effectiveness of the overall effort. The SCRUB tool allows all reports to be accessed through a single, uniform interface (see figure) that facilitates browsing code and reports. Improvements over existing software include significant simplification, and leveraging of a range of commercial, static source code analyzers in a single, uniform framework.

The tool runs as a small stand-alone application, avoiding the security problems related to tools based on Webbrowsers. A developer or reviewer, for instance, must have already obtained access rights to a code base before that code can be browsed and reviewed with the SCRUB tool. The tool cannot open any files or folders to which the user does not already have access. This means that the tool does not need to enforce or administer any additional security policies. The analysis results presented through the SCRUB tool's user interface are always computed off-line, given that, especially for larger projects, this computation can take longer than appropriate for interactive tool use.

The recommended code review process that is supported by the SCRUB tool consists of three phases: Code Review, Developer Response, and Closeout Resolution. In the Code Review phase, all tool-based analysis reports are generated, and specific comments from expert code reviewers are entered into the SCRUB

detep.c	Code Review Mode	Exit	ticituti -	Lines: 412	Search-	_191
	rstTime(int n)	EAR	31011010	Chieferre	obarch.	F
	int i;					ſ
0096	for (I = 0; I < T); I++	1				
0097		p[i] == n)				
8600		return (Specia	al[i] <= 1);			
	return 1;					
0100						
0101	and a second					
	atic void egal(Element *e, ch	ne fintel				
0103 1	адацскеннени е, сл	ar ant				
	printf("illegal operation	tor in 'd step?"	· .			
	comment/stdout, e		10			
0107	printf(""\n");	Ex L				
0108	fatal("%s", str);					
0109 ]						
0110	1000000					
	atic void					
0112 fil 0113 l	terbad(Element *e)					
	switch (e->n->ntyp	11				
	case ASSERT:	/1				
	case PRINT:					
0117	case 'c':					
COLUMN ST	Distance in the local diversion of	analyses:	Care strict coverity	codesonar	Macours: 1	en Late
Intel Date	MARGINESS INTO TRACK	anayses.	a la deservición de la deservi	Constant		-
adaeana	AND dates at 1021	nebooked Para	ameter Dereference illegal			
ouesona	and astebration b	nuneukeu Fala	amerer Derererence medar			
odesona	r001 dstep.c:114 U	nchecked Para	ameter Dereference filterba	d		
odesona	1002 dstep.c:135 U	nreachable Co	de filterbad			- 1
odesona	138 Uastep.c:138	nreachable Co	de filterbad			- 1
odesona	r004 dstep.c:141 U	nreachable Co	de filterbad			
	DOE datas alter D	a house of the local state	nded Loop CollectGuards			

SCRUB User Interface is shown when it is opened in local mode.

tool. In the second phase, Developer Response, the developer is asked to respond to each comment and tool-report that was produced, either agreeing or disagreeing to provide a fix that addresses the issue that was raised. In the third phase, Closeout Resolution, all disagreements are discussed in a meeting of all parties involved, and a resolution is made for all disagreements. The first two phases generally take one week each, and the third phase is concluded in a single closeout meeting.

This work was done by Gerard J. Holzmann of Caltech for NASA's Jet Propulsion Laboratory. Further information is contained in a TSP (see page 1).

This software is available for commercial licensing. Please contact Daniel Broderick of the California Institute of Technology at danielb@caltech.edu. Refer to NPO-46817.

## Diametrical Mean Element Orbital Analysis With Morbiter

NASA's Jet Propulsion Laboratory, Pasadena, California

The Morbiter software numerically averages an osculating orbit's equations of motion (EOM) to arrive at the mean orbit's EOMs, which are then numerically propagated to obtain the long-term orbital ephemerides. The long-term evolution characteristics, and stability, of an orbit are best characterized using a mean element propagation of the perturbed, two-body variational equations of motion. The average process eliminates short period terms, leaving only secular and long period effects. Doing this avoids the Fourier series expansions and truncations required by the traditional analytic methods. The numerical methods require no analytic approximation, and the averaging theory and software implementation work at any solar system body. JPL's Monte mission analysis and navigation software was used as the underlying trajectory system (to the extent possible) for this innovation.

Morbiter is a package of Python scripts that implement the algorithms, and uses Monte for basic astrodynamics constructs and functions such as trajectories, ephemerides, coordinate systems, astrodynamics constants, and, in most cases, the perturbation acceleration methods. Python is an interpreted language that provides an ideal platform for rapid development of algorithms; however, there is a performance penalty for using Python script-based applications. An end-user, future version of Morbiter that is fully compiled will not suffer from this speed penalty; development of this version is planned to begin in late FY '10.

This work was done by Todd A. Ely of Caltech for NASA's Jet Propulsion Laboratory. For more information, contact iaoffice@jpl.nasa.gov.

This software is available for commercial licensing. Please contact Daniel Broderick of the California Institute of Technology at danielb@caltech.edu. Refer to NPO-47212.