



# NASA Composite Cryotank Technology Project Game Changing Program

**Presented by:  
John Vickers  
Project Manager  
NASA Marshall Space Flight Center  
December 1<sup>st</sup>, 2015**



# Overall Project Objective

Composite Cryotank

STMD Game Changing Program

*The fundamental goal of this project was to provide new and innovative cryotank technologies that enable human space exploration to destinations beyond low earth orbit such as the moon, near-earth asteroids, and Mars.*



*The goal ... to mature technologies in preparation for potential system level flight demonstrations through significant ground-based testing and/or laboratory experimentation.*



# Composite Cryotank Project Goals

Composite Cryotank

STMD Game Changing Program



**Objective:** Advance technologies for lightweight cryotanks for heavy lift vehicles + spin-off capabilities for multiple stakeholders - NASA, DOD, and Industry

**Concept:** Develop and demonstrate composite tank critical technologies – **Materials, Structures, and Manufacturing - Out-of-Autoclave**

**Approach:** Focus on achieving affordability, technical performance, verified through agreement between experimental results and analysis predictions

**Goal:** Produce a major advancement in technology readiness; successfully test a 5.5-meter diameter composite hydrogen fuel tank, achieve:


- **25-30% weight savings**
- **20-25% cost savings**



# NASA Project Organization and Key Personnel

Composite Cryotank

STMD Game Changing Program






# Boeing Organization

Composite Cryotank

STMD Game Changing Program



### Boeing Technical Advisory Team

- Dallas Bienhoff, BDS Advanced Space Exploration
- Gail Hahn (TF), Next Gen Materials & Labs
- Brice Johnson (TF), Composites & Non-Metallics
- Don Barnes (ATF), BDS/Exploration Launch Sys
- Al Olsen, Propulsion Technology
- Marc Piehl (TF), Primary Structural Bonding
- Kurtis Willden (ATF), Composite Fabrication
- Richard Bossi (STF), Non-Destructive Evaluation

### Functional Support Team


- Kurt Braaten, Contracts
- Ros Campbell, Schedule
- David Sanchez, Finance
- Mark Mihalco, Supplier Mgmt
- Denise Boss, Data Mgmt
- Roger Smith, Quality
- Charlie Conway, Safety
- Jeff Fukushima, ERB/MRB/CCB



# NASA & Industry Team

Composite Cryotank

STMD Game Changing Program






# Building Block Program Culminated With 5.5m Cryotank

Composite Cryotank


STMD Game Changing Program





**5.5 meter Tank**

Available to support 5.5m Tank


**2.4 meter Precursor Tank**



Precursor




**Manufacturing Demonstration Units**



Joint Testing

**Joint Testing**



Coupon Testing

**Coupon Testing**


**Building block approach essential to successful technology maturation**



# Schedule Overview

Composite Cryotank

STMD Game Changing Program



**Saved 13 months in comparison to typical Serial Development**






# CCTD Key Terminology

Composite Cryotank

STMD Game Changing Program

## Major Components

## Major Joints






# Technologies Matured by CCTD

Composite Cryotank

STMD Game Changing Program






# Major Accomplishments

Composite Cryotank

STMD Game Changing Program

- Large AFP test article using 5320-1/IM7
- 70gsm fiber placed cryotank (hybrid laminate)
- Benefits:
  - Enables Out-of-Autoclave manufacturing
  - Meets material out time
  - Provides permeation barrier





# Major Accomplishments

Composite Cryotank

STMD Game Changing Program

- **Janicki - Large scale, spherical segmented tool**
  - Enables lightweight, 1-piece tank shell
  - Successfully used to fabricate cryotank
  - Successfully extracted







# Major Accomplishments

Composite Cryotank

STMD Game Changing Program

- Large scale, Gr/Ep fluted core sandwich & NDI





# Major Accomplishments

Composite Cryotank

STMD Game Changing Program

- Cold temperature softening strip.
- All composite bolted cover joints.






# Major Accomplishments

## Permeation Reduction:


- Hybrid laminate with thin plies prevented microcracking and reduced permeation levels.
- Design meets upper stage & booster stage calculated permeation allowable.
- To improve performance further:
  - Improve OoA AFP materials & processes
  - Increase number of thin plies
  - Autoclave cure





# Permeation Coupon Measurements


## Composite Cryotank




SRI Permeation Rig 100% In-plane Bonding



## STMD Game Changing Program



MSFC Permeation Rig 10% Mid-plane Bonding



Multiple tests performed using both setups with coupons cut from same parent panel, SRI exhibited no detectable permeation on all tests. MSFC rig detected excessive permeation on all OOA cured hybrid laminates. 100% of autoclave cured laminated had 0% permeation on both tests, and all OOA cured, all thin ply laminates had 0% permeation on both tests.







# In-Situ Permeability Measurement

## Composite Cryotank

## STMD Game Changing Program

- Metallized film bag/Composite bag underneath foam insulation collects permeated hydrogen and helium carrier gas
- Bag effluent gas is collected in bottles at specified times; bottles taken to MSFC chem labs for gc-ms analysis. Measured total effluent flow rate at test site and composition from gas analysis gives permeation rate.
- Same equipment and procedure for 2.4-m and 5.5-m tanks
- Accurate permeability measurements are difficult under ideal conditions. Performing the measurement on an industrial scale offers a unique set of challenges.





# Permeation Results

Composite Cryotank


STMD Game Changing Program

Max. Allowables:

Boost Stage  
4 - 6minutes

Upper Stage / Earth Orbits  
49min – 7.5hrs

Long Duration  
*(i.e. Lunar Lander)*  
8-25days



Allowables depend on:

- Boil off
- Draw off
- Total Allowable Losses
- Leakage through penetrations
- Residuals
- Mission Duration
- Explosive mixture limits




# Implication of OOA on Hybrid Laminate

Composite Cryotank

STMD Game Changing Program

- **Objective:** Determine Effects of OOA vs. Autoclave Cures
- **Approach:** Hybrid laminates fiber-placed panels produced at Boeing and LH2 tested at MSFC
  - Hybrid laminate 12 plies of 5.4mil with 5 plies of 2.5 mil material
  - OOA cured laminates exhibit ~4% porosity

17 ply IM7/5320-1			
Ply ID	Orientation	Thickness	
1	12	0.00545	Thick
2	-12	0.00545	
3	-45	0.00545	
4	45	0.00545	
5	65	0.00545	
6	-65	0.00545	Thin
7	60	0.0025	
8	-60	0.0025	
9	0	0.0025	
10	-60	0.0025	
11	60	0.0025	Thick
12	-65	0.00545	
13	65	0.00545	
14	45	0.00545	
15	-45	0.00545	
16	-12	0.00545	
17	12	0.00545	
Total		0.0779	



Autoclave Cure




Out-of-Autoclave Cure





# Laminate Micro-Cracks

Composite Cryotank

STMD Game Changing Program



- Micro cracks formed in thin plies primarily due to presence of porosity
- To eliminate permeation
  - Increase number of thin plies
  - Reduce porosity
    - Autoclave cure
    - Improved OoA AFP processes





# Permeation Conclusions

## Tank level permeation measurements

- Meet upper stage and booster stage allowable
- Exceed CCTD, lunar lander based, requirement

## Permeation is sensitive to

- Laminate quality
- Number of thin plies

## To eliminate permeation

- Increase number of thin plies
- Reduce porosity
  - Autoclave cure
  - Improved OoA Material Architecture and AFP processes



Microcracks formed in thin plies primarily due to presence of porosity





# 2.4m Test Summary

## Composite Cryotank

## STMD Game Changing Program

- 135 psi achieved with tank filled with LH2
- 20 press./de-press. cycles between 20 psi & 100 psi conducted
- Permeation measurements conducted at multiple test conditions:



2.4m Thermal Image During LH2 Testing




# 5.5m SHM Arrangement

Composite Cryotank

STMD Game Changing Program

- **AE Sensors:**

- Thirty-two (32) acoustic emission sensors uniformly spaced around the circumference of the tank barrel and on both domes
- Identified on Boeing SHM Instrumentation drawing, ZE154071
- Tank barrel – four sensors evenly spaced (at 90 degrees) in forward section of tank; four evenly spaced sensors in aft section of tank offset by 45 degrees from forward sensors






# 5.5m Structural Test Arrangement

Composite Cryotank

STMD Game Changing Program







# 5.5m Test Summary

Composite Cryotank

STMD Game Changing Program

Testing Summary	Date	Type	Details
Ambient pressure test (nitrogen) was successfully conducted	5/22/2014	Ambient (Nitrogen)	Achieved target pressure and reached 80% of target strain
Liquid hydrogen cryogenic pressure test was successfully conducted	7/20/2014	Cryogenic (Liquid Hydrogen)	Achieved pressure and 100% of strain in the forward dome acreage. (Permeation samples taken)
Combined ambient pressure (nitrogen) and load test was successfully conducted	7/30/2014	Ambient (Nitrogen)	Achieved 100% desired pressure with 100% load on the tank
Liquid hydrogen combined cryogenic pressure and load test was performed	8/16/2014	Cryogenic (Liquid Hydrogen)	The test was prematurely stopped at 20% mechanical loads due to mechanical issues with applying the loads in the test facility (Permeation samples taken)
Liquid hydrogen cryogenic pressure cycle test was successfully conducted	8/17/2014	Cryogenic (Liquid Hydrogen)	Achieved our goal of 80 pressure cycles (20% to 90% max pressure) on the tank. (Permeation samples taken)
Permeation with gaseous hydrogen test was conducted	8/22/2014	Ambient (Gaseous Hydrogen)	Achieved desired pressure. Issues with a leak in facility piping and a leak in the bag prevented any useful permeation data.
Permeation with gaseous hydrogen test was conducted	8/28/2014	Ambient (Gaseous Hydrogen)	Achieved desired pressure. Obtained permeation data.



# Critical Safety Factors

Composite Cryotank

STMD Game Changing Program

	Ambient	
Location	Demonstrated 100% target Pressure	Demonstrated Pressure + 100% Flight Load
Fwd Scarf	2.06	2.16
Aft Scarf	2.79	2.76
Y-Joint	6.21	4.64
Acreage	90% max allowable	92% max allowable
Local Buckling (67% of max pressure)		3.70

- Most critical areas are dominated by pressure loads
- At ambient, Y-joint is dominated by combined load case
  - Increased shear across joint



# Critical Safety Factors

Composite Cryotank

STMD Game Changing Program

	Cryo	
Location	Demonstrated LH2 Pressure 100% achieved	Predicted / Not Tested LH2 Pressure + 20% Flight Loads*
Fwd Scarf	1.49	1.68
Aft Scarf	2.16	2.34
Y-Joint	0.53	0.52
Acreage	102% max allowable	94% max allowable
Local Buckling (67% of max pressure)		4.42

- Pressure test limited by acreage strain design limit.
- Not all Joint S.F. are above 2.0
- Buckling is above 1.5 requirement
- Y-joint strength is dominated by thermal load, not pressure or flight loads.
- **By analysis, the addition of Flight Loads do not significantly impact critical safety factors**

\* Achieved 20% due to facility issues



# Major Accomplishments

## Largest Successfully Ground Tested Composite Cryotank

### Ground Test Program

1. Ambient Pressure
2. Cryogenic Pressure
3. Ambient Pressure & Mechanical
4. Cryogenic Cyclic Pressure

### Ground Test Summary

- ✓ 83 pressure cycles
- ✓ 2 thermal cycles
- ✓ 2 max pressure cases
- ✓ 1 combined load cycle

### Data Acquired

- Load/strain response
- Thermal response
- Laminate permeation rate
- Bolted joint performance



Marshall Space Flight Center



# Projected Composite Cryotank Benefits

Composite Cryotank

STMD Game Changing Program

	Reference	Composite	Weight Savings
<b>10 meter</b> (2011, Phase 1)	<b>NASA</b> <b>Al- Li</b> <b>11,000lbs</b>	<b>6,700lbs</b>	<b>39%</b> (4,200lbs)
<b>10 meter</b> (2014, Phase 2)	<b>NASA</b> <b>Al-Li</b> <b>11,000lbs</b>	<b>7319 lbs</b> <b>+ 619lbs for acreage &amp;</b> <b>fwd joint</b>	<b>33%</b> (3,681lbs)
<b>5 meter</b>	Delta IV Al – 2219	CCTD Phase 2 Test Article	<b>33%</b>



# CCTD Overview Summary

Composite Cryotank

STMD Game Changing Program

## Prior Barriers

### .... to Application of Large-Scale Composite LH2 Tanks

- **Manufacturability** – Scalable automated fiber placement & tooling.
- **Strain Limits** – Capable of 5,000 $\mu\epsilon$ .
- **Y-Joint Strength** – Achieved 58psi at LH2 temp, despite low margins.
- **Bolted Joint Seals** – Demonstrated composite joint w/ furon omniseal.
- **Hydrogen Permeability**
  - Out-of-Autoclave – Thin plies significantly reduced permeation.
  - Autoclave – Hybrid laminate coupon did not permeate.



# Summary

Composite Cryotank

STMD Game Changing Program

**Successful culmination of a three-year effort to design and build a large high-performance tank with new materials and new processes and to test it under extreme conditions**

**Credit the NASA's Space Technology Mission Directorate, and Game Changing Development Program with goals for innovating, developing, testing and flying hardware for use in NASA's future missions.**

**This is a significant technology achievement for NASA, Boeing and industry. "We are looking at composite fuel tanks for many aerospace applications."**