Ns G. 711

UNPUBLISHED PRELIMINARY DATA

VIII-U-1

HEAT TRANSFER ACROSS SURFACES IN CONTACT: TRANSIENT EFFECTS OF AMBIENT TEMPERATURES AND PRESSURES

Harold A. Blum*
Clifford J. Moore, Jr.*
Southern Methodist University

ABSTRACT

18445

The time dependent effects of non constant thermal contact conductance systems are considered. In addition to a general discussion of the approach that is to be used on this new project, some results of simulated experiments are presented.

AUTHOR

INTRODUCTION

The recent studies of contact conductance have been concerned primarily with the steady state. It is the purpose of this project to consider various types of time dependent problems when contacts are present during a heat transfer process. This knowledge may help us predict the practical consequences of contact conductance changes as well as having some possible control applications.

At this stage, we are planning and building systems for varying the contact conductance in two ways. In the first, we expect to vary the ambient pressure in a system which is at steady state. In the second method, the contact pressure in a system which is at steady state will be rapidly changed. Another phase of our current work, and in a practical way tied in with our planning of the first phase, is the computer simulation of experiments. It is with this phase of our studies that this progress report is concerned.

*Professor, Mechanical Engineering Department
*National Science Foundation Cooperative Fellow

GPO PRICE $ _____

OTS PRICE(S) $ _____

Hard copy (HC) 1.00

Microfiche (MF) .50

FACILITY FORM 602

N65 18445 (ACCESSION NUMBER)

11 (PAGES)

CR 57137 (NASA CR OR TMX OR AD NUMBER)

(THRU)

1 (CODE)

33 (CATEGORY)

COMPUTER SIMULATED EXPERIMENTS

The purposes of our computer simulated experiments are first to help us better plan the experiments which we will be carrying out and second to study the operating variables that are pertinent to this problem. The computer problem is divided into three parts. The first part (the only one reported in this study) is concerned with a number of one-dimensional heat transfer problems where the contact conductance is suddenly varied. The second part is concerned with the flow of fluids in the interstices of contacts. This work, reported briefly by Aaron and Blum (1), is being modified and expanded. The third phase of the computer work will be concerned with two-dimensional heat transfer problems where contacts are present.

In the one-dimensional experiments, we start with the system at constant temperature, suddenly change the temperature of one end, and print out distance versus temperature at different times. This is done until steady state is almost reached. At this point, the contact conductance is suddenly changed to simulate a decrease in the ambient pressure. In our experiments, this change will not be sudden since it will be limited at least in part by the ability of the vacuum system to reach low pressures. After the contact conductance is changed, the temperature is printed out again as a function of distance at various times until a new steady state condition is reached. At this point, the contact conductance is returned to the original condition which does simulate our experiments inasmuch as when the steady state condition is reached at low pressures, we will allow the gas to enter the system rapidly. When the final steady state condition is reached, the experiment will be considered at an end.

The variables which affect the results are (1) the contact conductance variation, (2) the types of materials used, (3) the length of the materials used, (4) the arrangement of the materials. In our actual experiments, we intend to use cylinders (at least initially). The computer program is a relatively simple one in which we make use of the explicit method for solving numerically the appropriate partial differential equation.

Figure 1 shows the effect of a sudden change in contact conductance on the temperature distribution on an aluminum-thorium contact. Since both the hot and cold materials are of the same length, the effect of material properties is evident. Aluminum in this case represents the higher temperature portion of the system. Figure 2 shows the effect of imposing a sudden temperature change for three systems. The overshoot occurs as would be expected when the aluminum is exposed to the higher temperature. This figure, therefore, shows the effect of materials, the

effect of the placement of the material, and illustrates the existence of the overshoot in temperature drop across the contact. This is a phenomenon which we will be studying carefully during the experimental phases of this work. In figure 3, there are two major pieces of information for a given system (the aluminum-stainless steel system). The time to reach steady state is plotted against the contact conductance and the peak temperature drop across the contact which was just discussed is plotted as a function of the contact conductance. We think that the study of the nature of the peak (for example, the magnitude and the time at which the peak occurs) should prove to be helpful in understanding transient effects

We are in the process of extending this series of simulated experiments to consider the effects of different length samples with the object of obtaining generalized correlations for one-dimensional flow that we can later compare with the experiments.

ACKNOWLEDGMENT

We gratefully acknowledge the financial and other support of this investigation by the National Aeronautics and Space Administration under Grant NSG 711.

REFERENCES

A classification of thirty six papers is presented in Tables I and II in a way which may be useful for investigators in this field.

(1) Aaron, Robert L. and Blum, Harold A., "Heat Transfer Across Surfaces in Contact: Effect of Ambient Pressure Changes," Preprint 1, A.I.Ch.E. Meeting, September 29, 1963.

(2) Barzelay, M. E., Tong, K. N., and Holloway, G. F., "Effect of Pressure on Thermal Conductance of Contact Joints," NACA TN-3295, May, 1955.

(3) Bloom, Mitchell F., "A Review of the Parameters Influencing Thermal Control Conductance Between Interfaces," Douglas Aircraft Report SM-42082, August, 1962.

(4) Clausing, A. M. and Chao, B. T., "Thermal Contact Resistance in a Vacuum Environment," University of Illinois Experimental Station Report, ME-TN-242-1, August, 1963.

(5) Cordier, H., "Experimental Studies of the Influence of Pressure on Thermal Contact Resistance," Redstone Scientific Information Center, Translation RSIC 116, Redstone Arsenal, Alabama.

(6) Fenech, H., and Rohsenow, W. M., "Prediction of Thermal Conductance of Metallic Surfaces in Contact," Jour. Heat Transfer, V. 85, pp. 15-24, February, 1963.

(7) Fried, E., and Costello, F. A., "Interface Thermal Contact Resistance Problem in Space Vehicles," ARS Journal, V. 32, pp. 237-243, 1962.

(8) Fried, E., "Thermal Joint Conductance in a Vacuum," ASME Paper No. AHGT-18, Aviation and Space Hydraulic and Gas Turbine Conference, Los Angeles, March, 1961.

(9) Petri, F. J., "An Experimental Investigation of Thermal Contact Resistance in a Vacuum," ASME Paper 63-WA-156.

(10) Rogers, G.F.C., "Heat Transfer at the Interface of Dissimilar Metals," Int. J. Heat & Mass Transfer, Vol. 2, pp. 150-154, 1961.

(11) Stubstad, W. R., "Measurements of Thermal Contact Conductance in a Vacuum," ASME Paper 63-WA-150.

(12) Adamantiades, A., "Experimental Determination of Contact Conductance for Some Stainless Steel Contacts," AEL Report No. NYO-9458, July, 1962.

(13) Ascoli, A., and Germagnoli, E., "Measurements of the Thermal Resistance of Uranium and Aluminum Flat Surfaces in Contact," Redstone Scientific Information Center, Redstone Arsenal, Alabama. Translation RSIC-99.

(14) Barzelay, M. E., Tong, K. N., and Holloway, G. F., "Thermal Conductance of Contacts in Aircraft Joints," NACA TN-3167, March, 1954.

(15) Barzelay, M. E., and Holloway, G. F., "Interface Conductance of Twenty-Seven Riveted Aircraft Joints," NACA TN-3991, July, 1957.

(16) Barzelay, M. E., "Range of Interface Thermal Conductance for Aircraft Joints," NASA TN-D-426, May, 1960.

(17) Berman, R., "Some Experiments on Thermal Contact at Low Temperatures," Journal of Applied Physics, Vol. 27, No. 4, pp. 318-323, April 1956.

(18) Boeschoten, F., and Van der Held, E., "The Thermal Conductance of Contacts Between Aluminum and Other Metals." Physics, Vol. 23, pp. 37-44, 1957.

(19) Brunot, A. W., and Buckland, F. F., "Thermal Contact Resistance of Laminated and Machined Joints," Trans. ASME, Vol. 71, pp. 37-44, 1957.

(20) Cetinkale, T. N., and Fishenden, M., "Thermal Conductance of Metal Surfaces in Contact." General Discussion on Heat Transfer, Proceedings Institute of Mechanical Engineers, ASME, P. 271, September, 1951.

(21) Fenech, H., and Rohsenow, W. M., "Thermal Conductance of Metallic Surfaces in Contact," AEC Report No. NYO-2136, May, 1959.

(22) Fried, E., "Study of Interface Thermal Contact Conductance, Summary Report," General Electric Report No. 64SD 652, May 1964

(23) Held, W., "Heat Transfer Between Worked Metal Surfaces," Allegmein Warmetechnik, Vol. 8, No. 1, pp. 1-8, 1957.

(24) Holm, R., Electrical Contacts Handbook, 3rd. Ed., Springer Verlag, Berlin, 1958.

(25) Jacobs, R. B., and Starr, C., "Thermal Conductance of Metallic Contacts," Rev. of Scientific Instruments, Vol. 10, pp. 140-141, 1939.

(26) Jansson, R. M. "The Heat Transfer Properties of Structural Elements for Space Instruments," MIT Instrumentation Lab. Report E-1173, June, 1961.

(27) Kouwenhoven, W. B. and Potter, J. H., "Thermal Resistance of Metal Contacts," J. Am. Weld. Soc., Vol. 27, Part 2, pp. 515-520, 1948.

(28) Laming, L. C., "Thermal Conductance of Machined Metal Contacts," 1961 International Heat Transfer Conference, Part 1, No. 8, pp. 65-76, Boulder, Colorado, September, 1961.

(29) Mikesell, R. P., and Scott, R. B., "Heat Conduction Through Insulating Supports in Very Low Temperature Equipment," Journal of Research of the National Bureau of Standards, Vol. 57, No. 6, pp. 371-378, 1956.

(30) Mizushina, T., Iuchi, S., Sasano, T., and Tamurs, H., "Thermal Contact Resistance Between Mercury and a Metal Surface." Int. J. Heat Mass Transfer, Vol. 1, pp. 139-146, 1960.

(31) Sanderson, P. D., "Heat Transfer from the Uranium Fuel to the Magnox Can in a Gas-Cooled Reactor," 1961 International Heat Transfer Conference. Part 1, No. 8, Boulder, Colorado, September, 1961.

(32) Skipper, R. S. G., and Wooton, K. J., "Thermal Resistance Between Uranium and Can," International Conference on Peaceful Uses of Atomic Energy, Proceedings. Vol. 7, pp. 684-690, 1958.

(33) Weills, N. D., and Ryder, E. A., "Thermal Resistance Measurements of Joints Formed Between Stationary Metal Surfaces," Irane ASME, Vol. 71, pp. 259-267, 1949.

(34) Wheeler, R. G., "Thermal Contact Conductance," AEC Report No. HW-53598, November, 1957.

(35) Wheeler, R. G., "Thermal Contact Conductance of Fuel Element Materials," AEC Report No. HW-60343, 1959.

(36) Schmidt, E. H. W., and Jung, E., "Measurements of the Thermal Contact Resistance from Stainless Steel to Liquid Sodium," Modern Developments in Heat Transfer, Academic Press. New York, 1963, pp. 251-263.

TABLE I

CONTACTS IN THE PRESENCE OF CONDUCTING FLUIDS

In air: 2, 3, 10, 14, 15, 16, 18, 19, 20, 27, 28, 33, 36.
In other gases: 18, 27, 31, 32, 34, 35.
With liquids in interfaces: 18, 20, 28, 30, 33, 36.
With solid materials in interface: 2, 14, 19, 31, 32, 33.
With surface roughness data: 2, 3, 14, 18, 19, 20, 27, 28, 33.
With contact pressure data: 2, 3, 5, 18, 19, 20, 27, 28, 33.
With dissimilar metal contacts: 2, 10, 18, 28, 31, 32, 35, 36.
With surface parameter theory or correlations: 3, 6, 12, 20, 21, 23.
With mean temperature level effects: 2, 14, 15, 27, 31, 33.

TABLE II

CONTACTS AT LOW PRESSURES

In air: 1, 4, 7, 8, 9, 11, 22, 25, 29, 34, 35.
In other gases: 13, 18, 31.
With solid material at interface: 4, 7, 13, 17, 20, 25.
With surface roughness data: 4, 7, 9, 11, 22.
With contact pressure data: 4, 5, 7, 8, 9, 11, 22, 29.
With dissimilar metal contacts: 13, 18, 31.
With surface parameter theory or correlations: 4, 7, 18, 22, 34, 35.
With mean temperature level effects: 4, 17, 22, 25, 29.


THE EFFECT OF A SUDDEN CHANGE IN CONTACT CONDUCTANCE ON THE TEMPERATURE DISTRIBUTION IN AN ALUMINUM-THORIUM CONTACT
θ=TIME AFTER CHANGE IN CONDUCTANCE (SEC)
30
1
0
TOTAL ΔT=122°C
L1=L2=2.54CM
0
1
5
15
30
θ
TEMPERATURE-°C
150
140
130
120
110
100
90
80
70
60
50
40
30
20
10
0
INITIAL CONTACT CONDUCTANCE=5.68X10-1 WATT/CM2-°C
FINAL " " =1.70X10-1 "
0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20
AXIAL DISTANCE (X/L) × 10

FIGURE 1


THE EFFECT OF HEAT FLOW DIRECTION AND MATERIALS ON THE TRANSIENT RESPONSE OF THE CONTACT TEMPERATURE DROP
TOTAL ΔT=122°C
L1=L2=2.54CM
UPPER CURVE OF EACH SET IS FOR ALUMINUM ON HOT SIDE
LEGEND:
1 ALUMINUM-THORIUM
2 ALUMINUM-STAINLESS STEEL
3 ALUMINUM-TITANIUM
CONTACT CONDUCTANCE=5.68X10^-1 WATT/CM^2-°C
TEMPERATURE DROP ACROSS CONTACT-°C
TIME-SEC X 10^-1
0
5
10
15
20
25
30
35
0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21
1
2
3

FIGURE 2

THE EFFECT OF CONTACT CONDUCTANCE ON TIME TO REACH STEADY STATE AND PEAK TEMPERATURE DROP ACROSS CONTACT FOR AN ALUMINUM-STAINLESS STEEL CONTACT

TOTAL $\Delta T = 122°C$
$L_1 = L_2 = 2.54 CM$

FIGURE 3