

THE FLASHING BEHAVIOR OF THUNDERSTORMS

by

A. S. Dennis
Institute of Atmospheric Sciences
South Dakota School of Mines & Technology
Rapid City, South Dakota

FACILITY FORM 602

N66-14627	
(ACCESSION NUMBER)	(THRU)
18	1
(PAGES)	(CODE)
CR 69112	20
(NASA CR OR TMX OR AD NUMBER)	(CATEGORY)

GPO PRICE \$ _____

CFSTI PRICE(S) \$ _____

Hard copy (HC) 1.00

Microfiche (MF) .50

ff 653 July 65

Prepared for presentation at the
244th National Meeting of the American Meteorological Society
on

CLOUD PHYSICS AND SEVERE LOCAL STORMS

18-22 October 1965

Reno, Nevada

ABSTRACT

14627

The distribution in time of individual lightning flashes recorded visually during 20 storms in New Mexico and on 23-cm radar screens during several storms in the south-central United States has been analyzed. The logarithms of the intervals between flashes within a given storm are normally distributed with a standard deviation, σ , of approximately one natural-log unit. The available data do not reject the hypothesis that there are no statistically significant variations in σ among storms. The autocorrelation of the intervals between flashes in one storm is very small. The implications of these findings are briefly explored.

Author

I

INTRODUCTION

This paper is an outcome of a study conducted at Stanford Research Institute of the feasibility of observing lightning from satellites (Dennis, 1964). The study differs considerably from others which have been conducted on the same problem (Whiteman and Freyberger, 1961; Hallgren and MacDonald, 1963; and Kirkwood, 1965), in that an attempt was made to find the sampling time necessary for the determination of flashing rates. The required sampling time is obviously related to the flashing behavior of thunderstorms. All available data on flashing rates, whether obtained by visual observations, by lightning counters, or through the recording of lightning channels on radar screens, were taken into account. In addition, radar data were analyzed to determine the extent, duration and distribution of complexes of convective cells in thunderstorm situations.

The results of the analyses can be summarized as follows: Typical thunderstorms are rather small, involving 100 to 200 km² of precipitating cloud. Only one or two cells are electrically active at any one time. The frequency distribution in terms of flashing rates is asymmetric, with the majority of thunderstorms producing less than three or four flashes per minute, but with a few producing over 100 flashes per minute. The storms with high flashing rates do not necessarily involve a large number of cells; some of the highest rates have been recorded in storms which showed only one cell on a weather radar screen (Mackerras, 1963). In those cases where high flashing rates occur in multicelled storms, the flashes are not uniformly distributed among the cells; rather, one or two cells contribute the majority of the flashes during any given five-minute period.

II

STATISTICAL ANALYSIS OF FLASH INTERVALS

A statistical analysis of the times of individual lightning flashes has been made for 20 storms that occurred in New Mexico during 1958, using times of flashes recorded visually to the nearest second at Socorro by personnel of the New Mexico Institute of Mining and Technology. The maximum separation between flashes belonging to the same storm has been set at 15 minutes. The records for daylight hours include only flashes to ground. The nighttime observations include both ground and cloud flashes. Weather radar data in the SRI Film Library from a site about 160 km from Socorro cover some of the 20 storms. They show, in each instance, only one shower complex likely to produce lightning visible from Socorro.

As normal functions are relatively easy to handle, various parameters related to the flashing rates have been tested for normality. The logarithms of the intervals between successive flashes within a given storm are found to possess this property. (The tests used reveal a tendency for observers to record time to the nearest five seconds, rather than to the nearest second.) The log-normal distribution of intervals between flashes is shown, either implicitly or explicitly, in the data of several authors including Brook and Kitagawa (1960), Norinder and Knudson (1961), and Lakshminarayan (1962). If t_i is the i th interval between flashes and if we define

$$x_i = \ln t_i \quad (1)$$

then the x_i 's are normally distributed. The mean x_i 's over individual storms in the sample range from 3.18 to 5.68, corresponding to median flash intervals between 24 and 290 sec. Let the standard deviation of the x_i 's be denoted by σ . The numerical calculations show that σ is approximately one natural-log unit. Although it varies within the range 0.5 to 1.5 for the various storms, the available data do not reject the hypothesis that there are no statistically significant variations in it. Tests with the available data show no correlation between the value of σ and the flashing rate of a particular storm.

Autocorrelation coefficients for the x_i 's have been computed for each storm over various lags from 1 to 20. The autocorrelation for lag 1 averaged over the 20 storms is 0.12; that for lag 2 is 0.11.

In addition, a mean autocorrelation coefficient over all possible lags has been computed for each storm according to the formula

$$\bar{\rho}_k = \frac{2}{k(k-1)} \sum_{\delta=1}^{k-1} (k-\delta) \rho_{\delta} \quad (2)$$

where ρ_{δ} is the autocorrelation of the intervals with lag δ and k is the number of intervals between flashes for the storm. No statistical significance can be attached to the variations in $\bar{\rho}_k$, which ranges from 0 to 0.2 for the different storms. The very low values of $\bar{\rho}_k$ indicate that intervals between flashes throughout a given storm are essentially independent of one another.

The data needed to examine thoroughly the statistics of lightning flashes in areas containing several simultaneously active storms are not available. A limited check has been made, using the times of occurrence of lightning echoes observed on radar in three thunderstorm complexes occurring simultaneously in the south-central United States. The lightning echoes were recorded on 23-cm radar. Consideration of beam width and rates of antenna rotation indicate that approximately one flash in 20 was recorded (Ligda, 1956). The logarithms of the intervals between echoes occurrences in each individual complex satisfy the tests for normality and show a standard deviation near one natural-log unit. The intervals between the occurrence of successive echoes anywhere within the three complexes also follow the log-normal distribution with a standard deviation near one natural-log unit, that is, they are statistically indistinguishable from those of a single storm.

III

IMPLICATIONS OF THE STATISTICAL ANALYSIS

The most reasonable assumptions concerning any sample of lightning observations for a given area, regardless of whether all flashes are recorded or not, are that the flash intervals are drawn from a log-normal distribution with a standard deviation near one natural-log unit and that the observed intervals are statistically independent. Assuming that the Central Limit Theorem applies, it is necessary to observe about 20 flashes in order to specify a flashing rate to within a factor of 2 at the 5% confidence level. This requirement can be significant in cases where sferics equipment is used to plot thunderstorm activity as a function of azimuth from the receiving station (Kohl and Miller, 1963). It also limits the spatial resolution attainable from a low-orbit lightning-detecting satellite, regardless of the type of sensor employed.

Examination of typical flashing rates per unit area in thunderstorm regions shows that it would generally be unrealistic to specify flashing rates for areas less than 150 km on a side on the basis of low-orbit satellite observations (Dennis, 1964).

The low autocorrelations among flash intervals in single-cell storms show that the occurrence of a flash, or of several flashes close together, has little bearing upon the time of the next flash in the same cell. This is, of course, in line with the results of Kuettnner (1950), who identified localized regions of 1 km or so diameter within thunderstorms as the basic discharge units. The local charge concentrations in thunderstorms are undoubtedly related to the small-scale variations in the precipitation rate, but it is probably an oversimplification to expect a one-to-one correspondence between the electrical and precipitation sub-cells. [See, however, Imyanitov and Shifrin (1962).]

In the absence of detailed information on the small-scale distribution of charge within a thunderstorm, the occurrence of an individual flash must be considered as a random phenomenon. It is generally agreed that the initiation of a lightning flash requires a local intensification of the electric field which leads to a dielectric breakdown of the air (e.g., Hagenguth, 1951). As charges are carried about by cloud particles, by precipitation, and by the air itself, it can readily be seen that the electrical conditions inside a cloud, particularly as they relate to the probability of a dielectric breakdown, can change on a time scale of the order of seconds. Conditions outside the cloud are also of some importance; the changing location of a thundercloud with respect to hills, tall buildings, regions of high ground conductivity, and nearby clouds undoubtedly plays a part in the timing of its lightning discharges. For these reasons, little meteorological significance can be attached to details of the time distribution of the flashes in a particular storm.

ACKNOWLEDGMENTS

This paper is based upon work carried out within the Aerophysics Laboratory of Stanford Research Institute under Contract NASr-49(18) with the National Aeronautics and Space Administration. The statistical analysis of flashing rates was done by Dr. W. G. Madow and Mr. R. L. Mancuso using, for the most part, data supplied by the New Mexico Institute of Mining and Technology.

REFERENCES

- Brook, M., and N. Kitagawa, 1960: Some aspects of lightning activity and related meteorological conditions, J. geophys. Res., 65, 1203-1210.
- Dennis, A. S., 1964: Lightning observations from satellites, Final Report, SRI Project 4877, Contract NASr-49(18), Stanford Research Institute, Menlo Park, California. 85 pp.
- Hagenguth, J. H., 1951: The lightning discharge, Compendium of Meteorology, 136-143 (American Meteorological Society, Boston, Mass.).
- Hallgren, R. E., and R. B. MacDonald, 1963: Atmospherics from lightning from 100 to 600 mc., Report No. 63-538-89, Contract Cwb 10341, IBM Federal Systems Division, Owego, New York.
- Imyanitov, I. M., and K. S. Shifrin, 1962: Present state of research on atmospheric electricity, Soviet Physics, 5, 292-322.
- Kirkwood, R. L., 1965: Determination of thunderstorm density by radio observations from a satellite, Memorandum No. RM-4417-NASA, The RAND Corporation, Santa Monica, California. 23 pp.
- Kohl, D. A., and J. E. Miller, 1963: 500-Kc/sec sferics studies in severe storms, Unit III, Final Report, Revised, Contract ARDS-A-176, U. S. Weather Bureau National Severe Storms Project.
- Kuettner, J., 1950: The electrical and meteorological conditions inside thunderclouds, J. Meteor., 7, 322-332.
- Lakshminarayan, K. N., 1962: Short term 'time' characteristics of impulsive atmospheric noise, J. sci. ind. Res., 21D, 228-232.
- Ligda, M. G. H., 1956: The radar observation of lightning, J. atmos. terr. Physics, 2, 346.
- Mackerras, D., 1963: Thunderstorm observations related to lightning flash counter performance, University of Queensland, Brisbane, Australia.
- Norinder, H., and E. Knudsen, 1958: Combined analysis of daylight photographs of lightning paths and simultaneous oscillographic records, Recent Advances in Atmospheric Electricity, 503-524 (Pergamon Press, New York, New York).
- Whiteman, R. A., and D. Fryberger, 1961: Inherent errors in locating electrical storms with a surveillance satellite, IRE International Conv. Rec., 2, Part 5, 157-170.