


N 70 41013

CR 113824



CASE FILE
COPY

EVALUATION PROGRAM
for
SECONDARY SPACECRAFT CELLS

ACCEPTANCE TEST
OF
GULTON INDUSTRIES, INC. & GENERAL ELECTRIC CO.
6.0 AMPERE - HOUR NICKEL - CADMIUM CELLS

prepared for
GODDARD SPACE FLIGHT CENTER
CONTRACT W12,397

QUALITY EVALUATION LABORATORY
NAD CRANE, INDIANA

QUALITY EVALUATION LABORATORY
NAVAL AMMUNITION DEPOT
CRANE, INDIANA

EVALUATION PROGRAM
FOR
SECONDARY SPACECRAFT CELLS

ACCEPTANCE TEST
OF
GULTON INDUSTRIES, INC. AND GENERAL ELECTRIC COMPANY
6.0 AMPERE-HOUR
NICKEL-CADMIUM CELLS

QE/C 70-690

28 AUGUST 1970

PREPARED BY

D. E. Christy

D. E. CHRISTY

PREPARED UNDER THE DIRECTION OF

D. G. Miley

D. G. MILEY
Manager, Electrochemical
Power Sources Branch

APPROVED BY

C. G. Lynch

C. G. LYNCH
By direction

Enclosure (1)

REPORT BRIEF
6.0 AMPERE-HOUR SEALED NICKEL CADMIUM
SECONDARY SPACECRAFT CELLS
DESIGNATED FOR USE IN SMALL ASTRONOMICAL SATELLITE (SAS)
MANUFACTURED BY
GULTON (SAS A) AND GENERAL ELECTRIC (SAS B)

- Ref: (a) National Aeronautics and Space Administration Purchase
Order Number W12-397
(b) NASA ltr BRA/VBK/pad of 25 September 1961 w/BUWEPS first
end FQ-1:WSK of 2 October 1961 to CO NAD Crane
(c) Preliminary Work Statement for Battery Evaluation Program
of 25 August 1961
(d) Work sheet of 2 February 1970

I. TEST ASSIGNMENT BRIEF

A. In compliance with references (a) and (b), evaluation of 6.0 ampere-hour secondary spacecraft cells was begun according to the program outline of reference (c).

B. The object of this evaluation program is to gather information concerning secondary spacecraft cells, in general. More specifically, these cells are being evaluated for their use in the SAS program as specified in reference (d). Information concerning performance characteristics and limitations, including cycle life under various electrical and environmental conditions, will be of interest to power systems designers and users. Cell weaknesses, including causes of failure of present designs, will be of interest to suppliers as a guide to product improvement.

C. Twenty 6.0 ampere-hour cells (manufacturer's rating) were purchased by the Applied Physics Laboratory and were tested by NAD Crane under the direction of NASA Goddard. Ten were manufactured by Gulton Industries; ten were manufactured by General Electric.

II. RESULTS

A. The ceramic seals of these cells are satisfactory as evidenced by no leakers out of the 20 cells tested.

B. The capacity of the 20 cells tested was acceptable. It ranged from 6.84 to 7.65 ampere-hours for both the Gulton and General Electric cells. The respective averages were 7.24 and 7.44 ampere-hours.

C. None of the 20 cells indicated internal shorts. The 24-hour recovery voltage was in the acceptable range of 1.18 to 1.22 volts for both groups of cells. Both groups averaged 1.19 volts on recovery.

D. Both groups gave satisfactory performance on overcharge. There was essentially no variance in end-of-overcharge values at each of the three rates run for both test groups. The average value was 1.43 volts.

E. The internal resistance of the Gulton cells averaged 3.90 milliohms; that of the General Electric cells averaged 4.26 milliohms.

F. The capacity to 1.00 volt following overcharge averaged 6.83 ampere-hours for the Gulton cells and 7.21 ampere-hours for the General Electric cells.

RESULTS OF ACCEPTANCE TESTS
OF
6.0 AMPERE HOUR NICKEL-CADMIUM SECONDARY SPACECRAFT CELLS
EVALUATED FOR USE IN SAS SATELLITE

I. INTRODUCTION

A. On 27 May 1970 acceptance tests were begun on 20 cells-- 10 manufactured by Gulton Industries and 10 manufactured by General Electric. These tests were completed on 10 June 1970.

II. TEST CONDITIONS

A. All acceptance tests were performed at an ambient temperature between 23° C and 27° C at existing relative humidity and atmospheric pressure, and consisted of the following:

1. Physical Inspection: Weighing, Measuring and Phenolphthalein Leak Test.
2. Capacity Tests.
3. Cell Short Test.
4. Leak Test.
5. Overcharge Test.
6. Internal Resistance Measurement.
7. Leak Test.

B. All charging and discharging was done at constant current (± 5 percent). Cells were charged in series but discharged individually.

III. CELL IDENTIFICATION AND DESCRIPTION

A. The cells were identified by the manufacturer's serial numbers. However, there were two packs of ten cells, each manufactured by a different company. The serial numbers of those cells manufactured by Gulton Industries were from 1937 to 1994; those manufactured by General Electric were from 013 to 057. The numbering was not consecutive in either group.

B. The 6.0 ampere-hour cells of each group are rectangular. The average dimensions and weight are included in Table I along with the individual measurements of each cell.

C. The cell containers and covers of each group are made of stainless steel. The positive terminal of each cell in either group is insulated from the cell cover by a ceramic seal which protrudes from the cover as a solder type terminal. The General Electric cells have a solder tab welded to both terminals while the Gulton cells do not. The negative terminals of either group are welded to the cell covers.

D. These cells, rated at 6.0 ampere-hours by their respective manufacturers, were supplied in a discharged condition.

IV. TEST PROCEDURE AND RESULTS

A. Phenolphthalein Leak Test:

1. The phenolphthalein leak test is a determination of the condition of the welds and ceramic seals on receipt of the cells. This test was performed prior to any other tests, with a phenolphthalein spray indicator solution of one-half of one percent concentration.

2. One cell (SN 1940) indicated a leak and some corrosion at the positive terminal. However, no leaks were detected on later leak tests. Thus, electrolyte contamination prior to shipment may account for such results.

B. Capacity Tests:

1. The capacity test is a determination of the cell capacity at the $c/2$ discharge rate, where c is the manufacturer's rated capacity to a cutoff voltage of 1.00 volt per cell. The discharge was made after a 1-hour open circuit period following the 16-hour charge at the $c/10$ rate. A total of three capacity checks was made at this activity. The cells were discharged individually, but were recharged in series.

2. The individual capacities for the cells of both manufacturers ranged from 6.84 to 7.65 ampere-hours. The Gulton cells averaged 7.24 ampere-hours and the General Electric cells averaged 7.44 ampere-hours.

C. Cell Short Test:

1. The cell short test is a means of detecting slight shorting conditions which may exist because of imperfections in the insulating materials, or damage to element in handling or assembly.

2. Following completion of the third capacity discharge test, each cell was loaded with a 0.5 ohm, 3 watt resistor and allowed to stand 16 hours with the resistor acting as a shorting device. At the end of 16 hours, the resistors were removed and the cells were placed on open circuit stand for 24 hours. Any cell whose voltage did not recover to 1.15 volts or higher was considered as failing this portion of the acceptance test.

3. The open circuit voltage, 24 hours after removal of the shorting resistors, ranged from 1.18 to 1.22 volts for an average of 1.19 volts. No cells failed this test.

D. Leak Test

1. The leak test is a means of detecting leakage of a seal or weld. The test was performed before and after the overcharge test sequence to determine the presence of leaks.

2. The cells were placed in a vacuum chamber and exposed to a vacuum of 40 microns of mercury or less for 24 hours. The cells were then removed from the vacuum chamber and sprayed with phenolphthalein. Faintly pink areas were designated as slight leakers. Darker, more obvious, discolorations of pink or red were noted as definite leakers.

3. None of the 20 cells failed this portion of testing.

E. Overcharge Test:

1. The purpose of this test is basically threefold:

a. To determine the degree to which a pack of cells maintain a balanced voltage.

b. To determine the cells capability of reaching a point of chemical equilibrium--oxygen recombination with the negative (cadmium) plate.

c. To test the integrity of the seals as the pressure increases.

2. The overcharge tests were performed to determine the steady state voltage at specified rates. The test specified a series of constant current charges at c/10, c/20 and c/10 for a minimum of 16 hours at each charge rate.

3. The cells were monitored hourly throughout the test. Charging was to be discontinued on cells which exceeded 1.50 volts. No cells were removed from the charging sequence.

4. The steady state voltage of each cell at the end of each 16-hour charge rate is shown in Table I. Characteristic overcharge voltage curves for high, average and low cells are shown in Figure 2.

F. Internal Resistance Test:

1. Immediately following the overcharge test, the internal resistance of each cell was measured with a Hewlett-Packard milliohm-meter (Model 4328A).

2. The internal resistance for each cell is shown in Table I. The resistance values for the Gulton cells ranged from 3.75 to 3.99 milliohms for an average of 3.90 milliohms; the General Electric cells ranged from 3.97 to 4.78 milliohms for an average of 4.26 milliohms.

G. Leak Test:

1. Following the internal resistance measurements, the cells were still in a charged state. The cells were discharged at $c/2$ to 0.00 volts and shorted prior to the final leak test. The capacities to 1.00 volt prior to the 0.00 volt cut-off are shown for each cell in Table I. The shorted cells were then placed in a vacuum chamber and the procedure described in paragraph IV.D.2 was repeated.

2. None of the 20 cells failed this portion of the testing.


TABLE I
6.0 AMPERE-HOUR CELLS EVALUATED FOR USE IN SAS SATELLITE
MANUFACTURED BY GULFON (SAS A) AND GENERAL ELECTRIC (SAS B)

	CELL SERIAL NUMBER	WEIGHT (Grams)	HEIGHT (Inches)	LENGTH (Inches)	WIDTH (Inches)	CAPACITY No. 1 (Amp-Hr)	CAPACITY No. 2 (Amp-Hr)	CAPACITY No. 3 (Amp-Hr)	CELL SHORT TEST	c/10	c/20	c/10	INTERNAL RESISTANCE (Milliohms)	CAPACITY FOLLOWING OVERCHARGE TO 1.0 VOLT (Amp-Hr)
										OVERCHARGE FOR 16 HRS (Volts)	OVERCHARGE FOR 16 HRS (Volts)	OVERCHARGE FOR 16 HRS (Volts)		
E-3-O	1937	271.8	3.710	0.819	2.100	7.35	7.20	6.99	1.22	1.43	1.43	1.45	3.99	6.69
	1939	273.5	3.698	0.823	2.099	7.65	7.50	7.59	1.19	1.43	1.44	1.45	3.85	7.26
	1940	269.8	3.700	0.824	2.090	7.26	6.96	6.90	1.20	1.42	1.43	1.44	3.90	6.42
	1946	273.1	3.700	0.817	2.098	7.35	7.20	7.05	1.19	1.42	1.43	1.43	3.79	6.75
	1965	271.2	3.704	0.835	2.100	7.41	7.20	7.44	1.18	1.42	1.43	1.44	3.94	6.96
	1968	268.2	3.717	0.830	2.100	7.35	7.05	6.84	1.19	1.42	1.43	1.43	3.88	6.66
	1969	272.1	3.694	0.840	2.098	7.50	7.29	7.29	1.18	1.43	1.43	1.44	3.98	7.14
	1987	271.1	3.698	0.829	2.110	7.41	7.05	7.56	1.19	1.43	1.43	1.43	3.99	6.75
	1992	271.2	3.696	0.827	2.100	7.20	6.96	6.84	1.20	1.43	1.43	1.43	3.75	6.60
	1994	273.9	3.685	0.830	2.101	6.69	7.59	7.59	1.19	1.44	1.44	1.45	3.90	7.05
	Avg.	271.6	3.700	0.827	2.100	7.32	7.20	7.21	1.19	1.43	1.43	1.44	3.90	6.83
E-4-O	013	272.7	3.565	0.848	2.145	7.20	7.20	6.84	1.22	1.42	1.43	1.44	4.39	6.66
	038	271.6	3.563	0.832	2.150	7.44	7.56	7.20	1.19	1.43	1.44	1.44	4.18	7.20
	041	271.8	3.545	0.835	2.142	7.44	7.56	7.20	1.20	1.43	1.43	1.43	4.17	7.14
	043	273.8	3.550	0.831	2.140	7.50	7.65	7.56	1.19	1.43	1.43	1.43	3.99	7.44
	044	273.2	3.549	0.830	2.141	7.50	7.56	7.29	1.20	1.43	1.43	1.43	4.22	7.20

QE/C 70-690


TABLE I

CELL SERIAL NUMBER	WEIGHT (Grams)	HEIGHT (Inches)	LENGTH (Inches)	WIDTH (Inches)	CAPACITY	CAPACITY	CAPACITY	CELL SHORT TEST	c/10	c/20	c/10	INTERNAL RESISTANCE (Milliohms)	CAPACITY FOLLOWING
					No. 1 (Amp-Hr)	No. 2 (Amp-Hr)	No. 3 (Amp-Hr)		OVERCHARGE FOR 16 HRS (Volts)	OVERCHARGE FOR 16 HRS (Volts)	OVERCHARGE FOR 16 HRS (Volts)		OVERCHARGE TO 1.0 VOLT (Amp-Hr)
052	272.0	3.551	0.830	2.145	7.56	7.71	7.29	1.18	1.43	1.43	1.42	4.11	7.41
053	274.2	3.548	0.840	2.142	7.44	7.56	7.56	1.19	1.43	1.43	1.42	4.18	7.26
054	273.3	3.559	0.832	2.147	7.56	7.59	7.80	1.19	1.43	1.43	1.43	4.63	7.26
055	271.8	3.550	0.852	2.140	7.44	7.44	7.14	1.19	1.42	1.43	1.42	4.78	7.14
057	271.9	3.548	0.831	2.144	7.56	7.65	7.50	1.19	1.43	1.43	1.44	3.97	7.35
Avg	272.6	3.553	0.836	2.144	7.46	7.53	7.34	1.19	1.43	1.43	1.43	4.26	7.21



CHARACTERISTIC 2-HOUR RATE DISCHARGE CURVES
 6.0 AMPERE-HOUR CELLS EVALUATED FOR USE IN SAS SATELLITE
 MANUFACTURED BY GULTON (SAS A) AND GENERAL ELECTRIC (SAS B)

FIGURE 1



CHARACTERISTIC 16-HOUR OVERCHARGE CURVES
 6.0 AMPERE-HOUR CELLS EVALUATED FOR USE IN SAS SATELLITE
 MANUFACTURED BY GULTON (SAS A) AND GENERAL ELECTRIC (SAS B)

FIGURE 2

DISTRIBUTION LIST

COPY NO.

- 1-6 National Aeronautics and Space Administration, Goddard Space Flight Center (Mr. Thomas Hennigan, Code 716.2), Greenbelt, Maryland 20771
- 7 National Aeronautics and Space Administration (Mr. Ernst M. Cohn, Code RNW), Washington, D. C. 20546
- 8 National Aeronautics and Space Administration (Mr. A. M. Greg Andrus, Code SAC), Washington, D. C. 20546
- 9-11 National Aeronautics and Space Administration, Scientific and Technical Information Center: Input, P. O. Box 33, College Park, Maryland 20740
- 12 National Aeronautics and Space Administration, (Dr. Steven J. Glassman, Code UT), Washington, D. C. 20546
- 13 National Aeronautics and Space Administration, Goddard Space Flight Center (Mr. Joseph Sherfey, Code 735), Greenbelt, Maryland 20771
- 14 National Aeronautics and Space Administration, Goddard Space Flight Center (Mr. Gerald Halpert, Code 735), Greenbelt, Maryland 20771
- 15 National Aeronautics and Space Administration, Goddard Space Flight Center (Mr. Louis Wilson, Code 450), Greenbelt, Maryland 20771
- 16 National Aeronautics and Space Administration, Langley Research Center (Mr. John L. Patterson, MS-472), Hampton, Virginia 23365
- 17 National Aeronautics and Space Administration, Langley Research Center (Mr. M. B. Seyfert, MS-112), Hampton, Virginia 23365
- 18 National Aeronautics and Space Administration, Lewis Research Center (Dr. Louis Rosenblum, MS 302-1), 21000 Brookpark Road, Cleveland, Ohio 44135
- 19 National Aeronautics and Space Administration, Lewis Research Center (Mr. Harvey Schwartz, MS 309-1), 21000 Brookpark Road, Cleveland, Ohio 44135

- 20 National Aeronautics and Space Administration, Lewis Research Center (Dr. J. Stewart Fordyce, MS 6-1), 21000 Brookpark Road, Cleveland, Ohio 44135
- 21 National Aeronautics and Space Administration, George C. Marshall Space Flight Center (Mr. Charles B. Graff, S&E-ASTR-EP), Huntsville, Alabama 35812
- 22 National Aeronautics and Space Administration, Manned Spacecraft Center (Code EP-5, Mr. W. E. Rice), Houston, Texas 77058
- 23 National Aeronautics and Space Administration, Ames Research Center (Code PBS, M.S. 244-2, Mr. Jon A. Rubenzer), Moffett Field, California 94035
- 24 National Aeronautics and Space Administration, Electronics Research Center (Code CPE, Dr. Sol Gilman), 575 Technology Square, Cambridge, Massachusetts 02139
- 25 Jet Propulsion Laboratory (Mr. Paul Goldsmith, M.S. 198-223), 4800 Oak Grove Drive, Pasadena, California 91103
- 26 Jet Propulsion Laboratory (Mr. Alvin A. Uchiyama, M.S. 198-223), 4800 Oak Grove Drive, Pasadena, California 91003
- 27 Jet Propulsion Laboratory (Dr. R. Lutwack, M.S. 198-220), 4800 Oak Grove Drive, Pasadena, California 91103
- 28 Commanding General, U. S. Army Electro Technology Lab., Energy Conversion Research Division (MERDC), Fort Belvoir, Virginia 22060
- 29 Commanding General, U. S. Army Electronics R&D Labs, (AMSEL-KL-P), Fort Monmouth, New Jersey 07703
- 30 Commanding General, U. S. Army Electronics Command (AMSEL-ME-NMP-TB-2, Mr. A. Frink), Fort Monmouth, New Jersey 07703
- 31 U. S. Army Natick Laboratories, Clothing and Organic Materials Division (Mr. Leo A. Spano), Natick, Massachusetts 01762

- 32 Harry Diamond Laboratories (Mr. Nathan Kaplan), Room 300, Building 92, Connecticut Avenue and Van Ness Street, N.W., Washington, D. C. 20438
- 33 Chief of Naval Research (Director, Power Program, Code 473), Navy Department, Washington, D. C. 20360
- 34 Chief of Naval Research (Code 472, Mr. Harry Fox), Navy Department, Washington, D. C. 20360
- 35 Director, Naval Research Laboratory (Code 6160, Dr. J. C. White), 4555 Overlook Avenue, S.W., Washington, D. C. 20360
- 36 Officer in Charge, Annapolis Division, Naval Ship Research and Development Center (Code M760, Mr. J. H. Harrison), Annapolis, Maryland 21402
- 37 Commander, Naval Air Systems Command (Code AIR-340C, Mr. Milton Knight), Department of the Navy, Washington, D. C. 20360
- 38 Commanding Officer, Naval Weapons Center, Corona Laboratories (Code 441, Mr. William C. Spindler), Corona, California 91720
- 39 Commander, U. S. Naval Ordnance Laboratory White Oak (Code 232, Mr. Philip B. Cole), Silver Spring, Maryland 20910
- 40 Commander, Naval Ship Engineering Center (Code 6157D, Mr. C. F. Viglotti), Washington, D. C. 20360
- 41 Superintendent, Naval Observatory (Code STIC, Mr. Robert E. Trumbule, Building 52), 34th and Massachusetts Avenue, N.W., Washington, D. C. 20390
- 42 Commander, Naval Ship Systems Command (Code SHIP-03422, Mr. Bernard B. Rosenbaum), Department of the Navy, Washington, D. C. 20360
- 43 Department of the Air Force Headquarters, Aero Propulsion Laboratory (APIP-1, Mr. James E. Copper), Wright-Patterson Air Force Base, Ohio 45433
- 44 Air Force Cambridge Research Laboratory (CRE, Mr. Francis X. Doherty and Mr. Edward Raskind, Wing F), L. G. Hanscom Field, Bedford, Massachusetts 01731

- 45 Rome Air Development Center (Mr. Frank J. Mollura, Code EMEAM), Griffiss Air Force Base, New York 13442
- 46 National Bureau of Standards (Dr. W. J. Hamer), Washington, D. C. 20234
- 47-66 Director, Defense Documentation Center, Cameron Station, Alexandria, Virginia 22314
- 67 Aerospace Corporation (Library Acquisition Group), P. O. Box 95085, Los Angeles, California 90045
- 68 American Cyanamid Company (Dr. R. A. Haldeman), 1937 W. Main Street, Stamford, Connecticut 06902
- 69 AMF, Inc. (Mr. R. A. Knight), 689 Hope Street, Stamford, Connecticut 06907
- 70 American University, Chemistry Department (Dr. R. T. Foley), Massachusetts and Nebraska Avenues, N.W., Washington, D. C. 20016
- 71 Atomics International Division, North American Aviation, Inc. (Dr. H. L. Recht), 8900 DeSota Avenue, Canoga Park, California 91304
- 72 Autonetics Division, NAR (Mr. F. F. Fogle, GF 16), P. O. Box 4181, Anaheim, California 92803
- 73 Battelle Memorial Institute (Dr. C. L. Faust), 505 King Avenue, Columbus, Ohio 43201
- 74 Bellcomm, Inc. (Mr. B. W. Moss), 955 L'Enfant Plaza North, S.W., Washington, D. C. 20024
- 75 Bell Laboratories (Mr. D. O. Feder), Murray Hill, New Jersey 07974
- 76 Dr. Carl Berger, 13401 Kootenay Drive, Santa Ana, California 92705
- 77 The Boeing Company (Mr. Sidney Gross, 2-7814, MS 85-86) P. O. Box 3999, Seattle, Washington 98124
- 78 Burgess Battery Company (Dr. Howard J. Strauss), Foot of Exchange Street, Freeport, Illinois 61032

- 79 C & D Batteries, Division of Electric Autolite Company
(Dr. Eugene Willihnganz), Conshohocken,
Pennsylvania 19428
- 80 Calvin College (Prof. T. P. Dirkse), 3175 Burton
Street, S. E., Grand Rapids, Michigan 49506
- 81 Catalyst Research Corporation (Dr. H. Goldsmith),
6101 Falls Road, Baltimore, Maryland 21209
- 82 Communications Satellite Corporation (Mr. Robert Strauss),
1835 K Street, N. W., Washington, D. C. 20036
- 83 G. & W. H. Corson, Inc. (Dr. L. J. Minnick), Plymouth
Meeting, Pennsylvania 19462
- 84 Cubic Corporation (Librarian), 9233 Balboa Avenue,
San Diego, California 92123
- 85 Delco-Remy Division, General Motors Corporation
(Mr. J. A. Keralla), 2401 Columbus Avenue, Anderson,
Indiana 46011
- 86 Eagle-Picher Industries, Inc. (Mr. E. P. Broglio),
P. O. Box 47, Joplin, Missouri 64801
- 87 E. I. du Pont Nemours and Company, Engineering Materials
Laboratory, Experimental Station, Building 304, (Mr. J. M.
Williams), Wilmington, Delaware 19898
- 88 ESB, Inc. (Director of Engineering), P. O. Box 11097,
Raleigh, North Carolina 27604
- 89 ESB, Inc., Carl F. Norberg Research Center (Dr. R. A.
Schaefer), 19 West College Avenue, Yardley,
Pennsylvania 19067
- 90 Electrochimica Corporation (Dr. Morris Eisenberg),
1140 O'Brien Drive, Menlo Park, California 94025
- 91 Electromite Corporation (Mr. R. H. Sparks), 2117 South
Anne Street, Santa Ana, California 92704
- 92 Emhart Corporation (Dr. W. P. Cadogan), Box 1620,
Hartford, Connecticut 06102

- 93 Energetics Science, Inc., 4461 Bronx Boulevard,
New York, New York 10470
- 94 Dr. Arthur Fleischer, 466 South Center Street, Orange,
New Jersey 07050
- 95 General Electric Company, Research and Development Center
(Dr. R. C. Osthoff), P. O. Box 43, Schenectady,
New York 12301
- 96 General Electric Company, Spacecraft Department
(Mr. K. L. Hanson, Room M-2614), P. O. Box 8555,
Philadelphia, Pennsylvania 19101
- 97 General Electric Company, Battery Business Section
(Mr. W. H. Roberts), P. O. Box 114, Gainesville,
Florida 32601
- 98 General Electric Company (Whitney Library), P. O. Box 8,
Schenectady, New York 12301
- 99 Globe-Union, Incorporated (Dr. Eugene Y. Weissman),
P. O. Box 591, Milwaukee, Wisconsin 53201
- 100 Gould Ionics, Inc. (Dr. J. E. Oxley), P. O. Box 1377,
Canoga Park, California 91304
- 101 Grumman Aircraft Engineering Corporation, AAP Project-
Future Missions (Mr. J. S. Caraceni, Plant 25), Bethpage,
Long Island, New York 11714
- 102 Gulton Industries, Alkaline Battery Division (Dr. H. N.
Seiger), 1 Gulton Street, Metuchen, New Jersey 08840
- 103 Honeywell, Incorporated, Livingston Electronic Laboratory
(Library), Montgomeryville, Pennsylvania 18936
- 104 Dr. P. L. Howard, Centreville, Maryland 21617
- 105 Hughes Aircraft Corporation (Mr. M. E. Ellion, Bldg. 366,
M.S. 524), El Segundo, California 90245
- 106 ITT Research Institute (Dr. H. T. Francis), 10 West 35th
Street, Chicago, Illinois 60616
- 107 Idaho State University, Department of Chemistry
(Dr. G. Myron Arcand), Pocatello, Idaho 82301

- 108 Institute for Defense Analyses (Mr. R. Hamilton),
400 Army-Navy Drive, Arlington, Virginia 22202
- 109 Institute for Defense Analyses (Dr. R. Briceland),
400 Army-Navy Drive, Arlington, Virginia 22202
- 110 International Nickel Company (Mr. William C. Mearns),
1000-16th Street, N.W., Washington, D. C. 20036
- 111 Johns Hopkins University, Applied Physics Laboratory
(Mr. Richard E. Evans), 8621 Georgia Avenue, Silver
Spring, Maryland 20910
- 112 Leeson Moos Laboratories (Dr. A. Moos), Lake Success
Park, Community Drive, Great Neck, New York 11021
- 113 Arthur D. Little, Incorporated (Dr. James D. Birkett),
Acorn Park, Cambridge, Massachusetts 02140
- 114 Lockheed Missiles and Space Company (Mr. Robert E. Corbett,
Dept. 62-14, Bldg. 154), P. O. Box 504, Sunnyvale,
California 94088
- 115 Mallory Battery Company (Mr. R. R. Clune), So. Broadway and
Sunnyside Lane, Tarrytown, New York 10591
- 116 P. R. Mallory and Co., Inc. (Dr. Per Bro), Northwest
Industrial Park, Burlington, Massachusetts 01801
- 117 P. R. Mallory and Co., Inc. (Technical Librarian),
3029 E. Washington Street, Indianapolis, Indiana 46206
- 118 Marathon Battery Company (Mr. Lou Belove), P. O. Box 247,
Cold Spring, New York 10516
- 119 Martin-Marietta Corporation (Mr. William B. Collins,
M.S. 1620 and Mr. M. S. Imamura, M.S. 8840),
P. O. Box 179, Denver, Colorado 80201
- 120 McDonnell Douglas, Inc. (Mr. A. D. Tonelli, MS 7C),
3000 Ocean Park Boulevard, Santa Monica, California 90406
- 121 McDonnell Douglas, Inc., Astropower Laboratory (Dr. George
Moe), 2121 Campus Drive, Newport Beach, California 92663
- 122 North American Rockwell Corporation, Rocketdyne Division
(Library), 6633 Canoga Avenue, Canoga Park, California 91304

- 123 Philco-Ford Corporation, Space Power and Propulsion
Department (Mr. D. C. Briggs, M.S. W-49), 3825 Fabian
Way, Palo Alto, California 94303
- 124 Portable Power Sources Corporation (Mr. Leon Schulman),
166 Pennsylvania Avenue, Mt. Vernon, New York 10552
- 125 Power Information Center, University City Science
Institute, Room 2107, 3401 Market Street, Philadelphia,
Pennsylvania 19104
- 126 Prime Battery Corporation, 15600 Cornet Street,
Santa Fe Springs, California 90670
- 127 RAI Research Corporation, 36-40 37th Street, Long Island
City, New York 11101
- 128 Southwest Research Institute (Library), 8500 Culebra
Road, San Antonio, Texas 78206
- 129 Stanford Research Institute (Dr. Fritz R. Kalhammer),
820 Mission Street, South Pasadena, California 91030
- 130 Texas Instruments, Inc., Metals and Controls Division
(Dr. E. J. Jost and Dr. J. W. Ross), 34 Forest Street,
Attleboro, Massachusetts 02703
- 131 TRW Systems, Inc. (Dr. W. R. Scott, M 2/2154),
One Space Park, Redondo Beach, California 90278
- 132 TRW Systems, Inc. (Dr. Herbert P. Silverman, R-1/2094),
One Space Park, Redondo Beach, California 90278
- 133 TRW, Inc. (Librarian), 23555 Euclid Avenue, Cleveland,
Ohio 44117
- 134 Tyco Laboratories, Inc. (Dr. A. C. Makrides), Bear Hill,
Hickory Drive, Waltham, Massachusetts 02154
- 135 Union Carbide Corporation, Development Laboratory
Library, P. O. Box 5056, Cleveland, Ohio 44101
- 136 Union Carbide Corporation, Consumer Products Division
(Dr. Robert Powers), P. O. Box 6166, Cleveland,
Ohio 44101

- 137 University of Pennsylvania, Electrochemistry Laboratory
(Prof. John O'M. Bockris), Philadelphia,
Pennsylvania 19104
- 138 Westinghouse Electric Corporation, Research and
Development Center (Dr. C. C. Hein, Contract Admin.),
Churchill Borough, Pittsburg, Pennsylvania 15235
- 139 Whittaker Corporation, Power Sources Division
(Mr. J. W. Reiter), 3850 Olive Street, Denver,
Colorado 80237