

N72-32296

**NASA CONTRACTOR
REPORT**



NASA CR-2134

NASA CR-2134

**CASE FILE
COPY**

**DEVELOPMENT OF EQUILIBRIUM
AIR COMPUTER PROGRAMS SUITABLE
FOR NUMERICAL COMPUTATION
USING TIME-DEPENDENT
OR SHOCK-CAPTURING METHODS**

by John C. Tannehill and Robert A. Mohling

Prepared by
IOWA STATE UNIVERSITY
Ames, Iowa
for Ames Research Center

NATIONAL AERONAUTICS AND SPACE ADMINISTRATION • WASHINGTON, D. C. • SEPTEMBER 1972

1. Report No. NASA CR-2134		2. Government Accession No.		3. Recipient's Catalog No.	
4. Title and Subtitle "Development of Equilibrium Air Computer Programs Suitable for Numerical Computation Using Time-Dependent or Shock-Capturing Methods"				5. Report Date September 1972	
				6. Performing Organization Code	
7. Author(s) J. C. Tannehill and R. A. Mohling				8. Performing Organization Report No.	
				10. Work Unit No.	
9. Performing Organization Name and Address Iowa State University Engineering Research Institute Ames, Iowa				11. Contract or Grant No. NGR 16-002-038	
				13. Type of Report and Period Covered Contractor Report	
12. Sponsoring Agency Name and Address National Aeronautics and Space Administration Washington, D.C. 20546				14. Sponsoring Agency Code	
15. Supplementary Notes					
16. Abstract Computer programs were developed which compute the thermodynamic properties of equilibrium air for use in either the "time-dependent" or "shock-capturing" computational methods. For the "time-dependent" method, the NASA-ARC RGAS computer program was modified to allow internal energy and density to be used as the independent variables. In addition, simplified curve fits for $p = p(e, \rho)$, $a = a(e, \rho)$, and $T = T(p, \rho)$ were devised to reduce computer time. For the "shock-capturing" method a simplified curve fit for $h = h(p, \rho)$ was made. These approximate curve fits may be particularly useful when employed on advanced computers such as the Burrough's ILLIAC IV or the CDC STAR since they avoid the cumbersome table-lookup feature of the RGAS program.					
17. Key Words (Suggested by Author(s)) Computer Program, thermodynamic properties, Illiac				18. Distribution Statement UNCLASSIFIED-UNLIMITED	
19. Security Classif. (of this report) Unclassified		20. Security Classif. (of this page) Unclassified		21. No. of Pages 49	
				22. Price* \$3.00	

TABLE OF CONTENTS

	<u>Page</u>
INTRODUCTION	1
MODIFICATION OF THE NASA RGAS SUBROUTINE	2
Original RGAS Subroutine	2
Generation of Cubic Coefficients for Modified RGAS	4
Modified RGAS Subroutine	6
SIMPLIFIED CURVE FITS FOR EQUILIBRIUM AIR	10
REFERENCES	24
APPENDIX A: Program for Generating Cubic Coefficients	A-1
APPENDIX B: Calling Sequence for Modified RGAS	B-1
APPENDIX C: Listing of Modified RGAS	C-1
APPENDIX D: Equations for Approximate Curve Fits	D-1
APPENDIX E: Subroutine TGAS for $p = p(e, \rho)$, $a = a(e, \rho)$, and $T = T(p, \rho)$	E-1
APPENDIX F: Subroutine TGAS for $h = h(p, \rho)$	F-1

DEVELOPMENT OF EQUILIBRIUM AIR COMPUTER
PROGRAMS SUITABLE FOR NUMERICAL COMPUTATION
USING TIME-DEPENDENT OR SHOCK-CAPTURING METHODS

John C. Tannehill and Robert A. Mohling

INTRODUCTION

This report summarizes the research accomplished under NASA Grant NGR 16-002-038 for the period November 15, 1971 through March 15, 1972. During this period, computer programs were developed which compute the thermodynamic properties of equilibrium air for use in either the "time-dependent" or "shock-capturing" computational methods. For the "time-dependent" method, the NASA-ARC RGAS computer program was modified to allow internal energy and density to be used as the independent variables. In addition, simplified curve fits for $p = p(e, \rho)$, $a = a(e, \rho)$, and $T = T(p, \rho)$ were devised to reduce computer time. For the "shock-capturing" method a simplified curve fit for $h = h(p, \rho)$ was made. These approximate curve fits may be particularly useful when employed on advanced computers such as the Burrough's ILLIAC IV or the CDC STAR since they avoid the cumbersome table-lookup feature of the RGAS program.

MODIFICATION OF THE NASA RGAS SUBROUTINE

The NASA Ames Research Center real gas computer program has been modified to give the user the option of entering with new independent variables, internal energy e and density ρ . Although the calling sequence has been altered in order to transfer e to the modified RGAS subroutine, the logic and other features of the original RGAS subroutine have been retained. The modified subroutine requires new cubic coefficients for e and ρ entry. A short program was written to generate and store the coefficients on tape for air. In order to understand the method of generating the new coefficients and their use in the modified subroutine, a brief discussion of the original RGAS subroutine follows.

Original RGAS Subroutine

Version I of the original RGAS program for real gas calculations is based on the gas properties determined by Bailey¹ for temperatures up to 45,000 °K and densities from 10^{-7} to 10^3 amagats. These properties were used to generate 13 files of information on a tape for use in determining the thermodynamic properties (a, h, T , and s) of 13 different gas mixtures. Each file on the tape contains the cubic spline fit coefficients along with the lowest value of the independent variable F , for each interval on the 11 constant density lines ($R_j = \log_{10} \rho/\rho_0 = -7.0, -6.0, \dots, +3.0$; $j = 1, 11$). F varies between zero and F_M (the maximum value of F) and is defined by

$$F = \frac{\log_{10} (p/p_0) - \log_{10} (\rho/\rho_0) - B}{1 + E \log_{10} (\rho/\rho_0) + D [\log_{10} (\rho/\rho_0)]^2} \quad (1)$$

where B , D , E , FM , p_o , and ρ_o are known constants for each gas.

Subroutine RGAS calls subroutine SERCH which uses F to locate the cubic coefficients required for the calculation of the thermodynamic properties. For example, if h is to be determined with p and ρ known, then R is first calculated ($R = \log_{10} \rho/\rho_o$) to determine the two adjacent R_j lines. Once F is found from Eq. (1), the two sets of cubic coefficients can be located for each R_j line. With these coefficients, the values of h on the two R_j lines are calculated from

$$\begin{aligned} h_1 &= a_1 + b_1 F + c_1 F^2 + d_1 F^3 \\ h_2 &= a_2 + b_2 F + c_2 F^2 + d_2 F^3 \end{aligned} \quad (2)$$

allowing h to be found by linear interpolation:

$$h = h_1 + (h_2 - h_1)(R - R_i) \quad (3)$$

The method is illustrated in Fig. 1.




Fig. 1. Calculation of enthalpy.

Generation of Cubic Coefficients for Modified RGAS

In order to use e and ρ for the independent variables, it was necessary to generate new cubic coefficients for every e interval such that

$$F = a + be + ce^2 + de^3 \quad (4)$$

This was accomplished by subdividing each F interval of the enthalpy curve into three equal parts as shown in Fig. 2 where $F_i = F_1 + i\Delta F/3$, $i = 0, 1, 2, 3$.




Fig. 2. Subdivision of F interval on enthalpy curve.

Equation (1) was then solved for the four values of p .

$$p_i = p_o (10)^{n_i} \quad i = 1, 2, 3, 4 \quad (5)$$

where

$$n_i = F_i \left\{ 1 + E \log_{10}(\rho/\rho_o) + D[\log_{10}(\rho/\rho_o)]^2 \right\} + \log_{10}(\rho/\rho_o) + B$$

The internal energy e_i was found using the definition of enthalpy

$$e_i = h_i - p_i/\rho \quad i = 1, 2, 3, 4 \quad (6)$$

with h_i determined using the original RGAS subroutine knowing p_i and ρ .

Each value of F can be written as

$$F_i = a + be_i + ce_i^2 + de_i^3 \quad i = 1, 2, 3, 4 \quad (7)$$

or in matrix notation

$$\bar{F} = M\bar{x}, \text{ where } \bar{F} = \begin{bmatrix} F_1 \\ F_2 \\ F_3 \\ F_4 \end{bmatrix}, M = \begin{bmatrix} 1 & e_1 & e_1^2 & e_1^3 \\ 1 & e_2 & e_2^2 & e_2^3 \\ 1 & e_3 & e_3^2 & e_3^3 \\ 1 & e_4 & e_4^2 & e_4^3 \end{bmatrix}, \bar{x} = \begin{bmatrix} a \\ b \\ c \\ d \end{bmatrix} \quad (8)$$

An IBM library subroutine GELG was used to solve the system of four equations for a, b, c, and d for each F interval and all eleven constant density lines. These coefficients along with the initial values of the e intervals (e_1 's) were stored on the tape in File 14. A listing of the program which generates the coefficients appears in Appendix A.

The curve generated for $F = F(e, \rho)$ is shown in Fig. 3. The maximum values of e allowed for each of the density ratios are given in Table 1 and plotted in Fig. 4.

Table 1. Maximum values of e for each density ratio

ρ/ρ_0	10^{-7}	10^{-6}	10^{-5}	10^{-4}	10^{-3}	10^{-2}	10^{-1}	10^0	10^1	10^2	10^3
$e_{\max}(10)^{-8} \left[\frac{ft^2}{sec^2} \right]$	43.27	42.66	39.39	32.72	25.40	19.79	17.15	13.40	9.864	7.440	5.878

Modified RGAS Subroutine

The argument list of the calling sequence for the modified RGAS subroutine is located in Appendix B. An e, ρ entry is accomplished by setting the calling argument NTEST equal to 1, which signals a tape read of the newly calculated cubic coefficients. NTEST equal to -1 and 0 are still reserved for the original RGAS subroutine to make real gas and perfect gas calculations, respectively. For the known ρ , subroutine SERCH uses e to locate the two sets of cubic coefficients needed to calculate

$$\begin{aligned}
 F_1 &= a_1 + b_1 e + c_1 e^2 + d_1 e^3 \\
 F_2 &= a_2 + b_2 e + c_2 e^2 + d_2 e^3
 \end{aligned}
 \tag{9}$$




Fig. 3. Curve fit for $F = F(e, \rho)$.




Fig. 4. Allowable range on e .

As illustrated in Fig. 5, a linear interpolation similar to Eq. (3) gives

$$F = F_1 + (F_2 - F_1)(R - R_j) \quad (10)$$




Fig. 5. Calculation of F .

With F known, p can be determined from Eq. (5). The logic of the original RGAS subroutine is then used to determine the other thermodynamic properties requested through the argument code NUMX. A listing of the modified RGAS subroutine is given in Appendix C.

Estimates of the accuracy of the modified RGAS subroutine were obtained by entering with e and ρ data to determine p and subsequently h from

$$h = e + p/\rho \quad (11)$$

For comparison, h was also calculated from the original RGAS subroutine using the newly determined p and ρ from above. 1083 comparisons were made of these two values of h . The numbers in the first line of Table 2 are percentages of compared values with errors greater than the given value. The second line contains percentages of the 2624 comparisons made by Lomax and Inouye² between the original RGAS subroutine and the data by Bailey¹.

Table 2. Accuracy of Modified RGAS.

Error	0.5%	1%	2%	3%	4%	5%	10%
Modified RGAS	13.30	4.80	0.37	0.09	0	0	0
Original RGAS	5.04	0.45	0	0	0	0	0

SIMPLIFIED CURVE FITS FOR EQUILIBRIUM AIR

Simplified curve fits for the thermodynamic properties of equilibrium air have been constructed for use in either the "time-dependent" or "shock-capturing" computational methods. For the "time-dependent" method, correlations were developed for $p = p(e, \rho)$, $a = a(e, \rho)$, and $T = T(p, \rho)$ while for the "shock-capturing" method a correlation was made for $h = h(p, \rho)$. The ranges of validity for these correlation formulas are the same as the NASA RGAS subroutine, namely, temperatures up to 45,000 °K and densities from 10^{-7} to 10^3 amagats.

The simplified curve fits developed here allow the user to reduce computer time and storage while maintaining reasonable accuracy. This may be particularly true in the "time-dependent" method since the simplified

curve fits could be used until near the end of a calculation when the steady-state solution is approached. Then, the modified RGAS subroutine could be used to give more accurate thermodynamic properties for the final steps. Substantial savings in computer time may also result in the "shock-capturing" method since an iterative procedure involving $h = h(p, \rho)$ is required for equilibrium calculations.

The curve fits for $p = p(e, \rho)$ and $h = h(p, \rho)$ were constructed using Grabau-type transistion functions³ in a manner similar to Lewis and Burgess⁴ and Barnwell⁵. A transistion function of this type can be used to smoothly connect two surfaces $f_1(x, y)$ and $f_2(x, y)$. For $y = \text{constant}$, the Grabau-type transistion function (with an inflection point) becomes

$$z = f_1(x) + \frac{f_2(x) - f_1(x)}{1 + \exp [K(x - x_0)]} \quad (12)$$

where K is the parameter which determines the rate at which the curve moves from $f_1(x)$ to $f_2(x)$ and x_0 is the location of the inflection point as shown in Fig. 6.




Fig. 6. Grabau-type transistion with inflection point.

For the present curve fits, two Grabau-type transition functions were joined with the equation for a perfect gas as shown in Fig. 7.




Fig. 7. Correlation curves for $h = h(p, \rho)$.

In addition, the range of the independent variable ρ was subdivided into three separate regions with different coefficients being used in the curve fits for each region (See Fig. 8.) The division lines are located at $\rho/\rho_0 = 5 \times 10^{-5}$ and $\rho/\rho_0 = 0.5$.

The coefficients for $f_1(x, y)$ and $f_2(x, y)$ were determined using a least squares best fit computer program in conjunction with the original NASA RGAS subroutine. The selection of the form of the equations for $f_1(x, y)$ and $f_2(x, y)$ was largely a trial-and-error process. By including more terms, a better curve fit could be achieved. In fact, if a sufficient number of terms are retained in $f_1(x, y)$ and $f_2(x, y)$, the accuracy of these curve fits can be made to approach that of the RGAS program but without any savings in computer time.




Fig. 8. Division of curve fit range by density.

For the correlation of $p = p(e, \rho)$, the ratio $\tilde{\gamma} = h/e$ was curve-fitted as a function of e and ρ so that p could be found from

$$p = \rho e (\tilde{\gamma} - 1) \quad (13)$$

This equation is derived directly from the definition of enthalpy.

Barnwell⁵ has derived the following expression for the speed of sound:

$$a = \left[e \left\{ (\tilde{\gamma} - 1) \left[\tilde{\gamma} + \left(\frac{\partial \tilde{\gamma}}{\partial \log_e e} \right)_{\rho} \right] + \left(\frac{\partial \tilde{\gamma}}{\partial \log_e \rho} \right)_e \right\} \right]^{1/2} \quad (14)$$

In the present study, it was found that a much better correlation for $a = a(e, \rho)$ could be obtained from

$$a = \left[e \left\{ K_1 + (\tilde{\gamma} - 1) \left[\tilde{\gamma} + K_2 \left(\frac{\partial \tilde{\gamma}}{\partial \log_e e} \right)_\rho \right] + K_3 \left(\frac{\partial \tilde{\gamma}}{\partial \log_e \rho} \right)_e \right\} \right]^{1/2} \quad (15)$$

where the coefficients K_1 , K_2 , and K_3 were determined using the least squares best fit program in conjunction with the NASA RGAS program. The curve fit for $T = T(p, \rho)$ uses a Grabau-type transition function without an inflection point⁴ for the upper curve and a non-Grabau-type function for the middle curve.

For the correlation of $h = h(p, \rho)$, the ratio $\tilde{\gamma} = h/e$ was curve-fitted as a function of p and ρ so that h could be found from

$$h = (p/\rho) \left(\frac{\tilde{\gamma}}{\tilde{\gamma} - 1} \right) \quad (16)$$

This equation was derived from the definition of enthalpy.

The equations for all the present curve fits appear in Appendix D. The calling sequence and listing of the subroutine TGAS to find $p = p(e, \rho)$, $a = a(e, \rho)$, and $T = T(p, \rho)$ and the subroutine TGAS to find $h = h(p, \rho)$ appear in Appendix E and F, respectively.

Comparisons of the relative accuracy of the curve fits for $p = p(e, \rho)$, $a = a(e, \rho)$ and $T = T(p, \rho)$ with the original RGAS subroutine are shown in Figs. 9, 10, and 11. Included on these graphs are the curve fits by Barnwell⁵. It should be pointed out that the limits of applicability of

the Barnwell curve fits for $p = p(e, \rho)$ and $a = a(e, \rho)$ are $10^{-4} \leq \rho/\rho_0 \leq 10$ and $e/e_0 \leq 565$. The limits of applicability for $T = T(p, \rho)$ are $6 \times 10^{-2} \leq p/p_0 \leq 20$ and $10^{-3} \leq \rho/\rho_0 \leq 10^{-1}$. A comparison between the present curve fit for $h = h(p, \rho)$ and the original RGAS subroutine is shown in Fig. 12. The deviations between the curve fits for $p = p(e, \rho)$, $a = a(e, \rho)$, $T = T(p, \rho)$, and $h = h(p, \rho)$; and the original RGAS subroutine are plotted in Figs. 13, 14, 15, and 16. In order to make the comparison for $p = p(e, \rho)$ the following procedure was used. First, e and ρ input data was supplied which allowed TGAS to compute $p = p(e, \rho)$. Then, this p and the original ρ were inputted into RGAS to give h and subsequently e from the definition of enthalpy. This e was compared with the original e to determine the accuracy of the curve fit for $p = p(e, \rho)$.

A comparison of the relative computer times required for the TGAS subroutines and the NASA RGAS programs are given in Table 3. The TGAS subroutine for finding $p = p(e, \rho)$, $a = a(e, \rho)$, and $T = T(p, \rho)$ is approximately

Table 3. Comparison of computer time.

Curve Fit	Number of Data Points	TGAS	RGAS
$p = p(e, \rho)$	508	1.434 sec	3.535 sec (0-1) includes tape read 2.367 sec (2-508) 5.902 sec
$a = a(e, \rho)$			
$T = T(p, \rho)$			
$h = h(p, \rho)$	464	1.035 sec	2.434 sec (0-1) includes tape read 1.765 sec (2-464) 4.199 sec

65% faster than the modified NASA RGAS subroutine. This comparison does not include the time spent by the RGAS subroutine in reading the tape. The TGAS subroutine for finding $h = h(p, \rho)$ is approximately 71% faster than the original RGAS program, again excluding the tape read time. If there are not more than a few hundred calls made to these real gas subroutines, then the TGAS subroutines are substantially faster than the RGAS subroutines when the tape read time is included. For instance, if there are 500 calls made to the subroutines to find $p = p(e, \rho)$, $a = a(e, \rho)$ and $T = T(p, \rho)$, then TGAS is 317% faster than the modified RGAS subroutine.

Comparisons of the values obtained using the curve fits at the juncture points A and B (See Fig. 7) are shown in Table 4. The maximum deviation between the curves at the juncture points for the primary variables $p = p(e, \rho)$ and $h = h(p, \rho)$ is 1.1%.

Additional work is being conducted to improve the accuracy and computation times of the simplified curve fits developed in this study. In particular, it has been found that a substantial improvement in accuracy without much increase in computer time can be achieved if four instead of two Grabau-type transition functions are joined with the equation for a perfect gas as in Fig. 7.

Table 4. Comparison of variables at juncture points.

Curve Fit	Density Ratio ρ/ρ_0	Point A		Point B	
		Lower Curve	Middle Curve	Middle Curve	Upper Curve
$p = p(e, \rho)$	10^3	1.400	1.399	1.244	1.243
	10^2	1.400	1.400	1.228	1.225
	10^1	1.400	1.401	1.209	1.207
	10^0	1.400	1.401	1.189	1.190
	10^{-1}	1.400	1.403	1.168	1.172
	10^{-2}	1.400	1.407	1.160	1.158
	10^{-3}	1.400	1.408	1.151	1.143
	10^{-4}	1.400	1.407	1.139	1.127
	10^{-5}	1.400	1.407	1.150	1.163
	10^{-6}	1.400	1.411	1.151	1.156
	10^{-7}	1.400	1.410	1.149	1.149
$a = a(e, \rho)$	10^3	442.9	438.3	326.8	324.7
	10^2	442.9	440.1	313.7	309.2
	10^1	442.9	440.9	298.4	293.6
	10^0	442.9	440.9	281.1	277.8
	10^{-1}	442.9	442.3	261.7	261.7
	10^{-2}	442.9	445.0	256.0	251.2
	10^{-3}	442.9	446.1	248.6	239.6
	10^{-4}	442.9	445.6	239.4	226.8
	10^{-5}	442.9	447.0	241.4	251.5
	10^{-6}	442.9	450.5	244.9	244.9
	10^{-7}	442.9	450.6	244.8	238.1
$T = T(p, \rho)$	10^3	1870.0	1885.0	17039.0	16384.0
	10^2	1871.0	1868.0	13772.0	13818.0
	10^1	1862.0	1838.0	11450.0	11600.0
	10^0	1843.0	1797.0	9727.0	9697.0
	10^{-1}	1849.0	1863.0	8503.0	8629.0
	10^{-2}	1823.0	1815.0	7615.0	7850.0
	10^{-3}	1783.0	1752.0	6815.0	7029.0
	10^{-4}	1730.0	1677.0	6030.0	6162.0
	10^{-5}	1721.0	1718.0	5435.0	5628.0
	10^{-6}	1689.0	1650.0	4965.0	5143.0
	10^{-7}	1620.0	1543.0	4723.0	4699.0
$h = h(p, \rho)$	10^3	1.400	1.396	1.267	1.266
	10^2	1.400	1.396	1.251	1.251
	10^1	1.400	1.396	1.234	1.236
	10^0	1.400	1.395	1.217	1.218
	10^{-1}	1.400	1.395	1.191	1.197
	10^{-2}	1.400	1.396	1.171	1.183
	10^{-3}	1.400	1.397	1.150	1.158
	10^{-4}	1.400	1.399	1.130	1.130
	10^{-5}	1.400	1.401	1.116	1.119
	10^{-6}	1.400	1.404	1.105	1.105
	10^{-7}	1.400	1.406	1.093	1.091




Fig. 9. Comparison of curve fits for $p = p(e, \rho)$.




Fig. 10. Comparison of curve fits for $a = a(e, \rho)$.




Fig. 11. Comparison of curve fits for $T = T(p, \rho)$.




Fig. 12. Comparison of curve fits for $h = h(p, p_0)$.




Fig. 13. Percentage difference between RGAS and TGAS for $p = p(e, \rho)$.




Fig. 14. Percentage difference between RGAS and TGAS for $a = a(e, \rho)$.




Fig. 15. Percentage difference between RGAS and TGAS for $T = T(p, \rho)$.




Fig. 16. Percentage difference between RGAS and TGAS for $h = h(p, \rho)$.

REFERENCES

1. Bailey, Harry E., "Equilibrium Thermodynamic Properties of Carbon Dioxide," SP-3014, 1965, NASA.
2. Lomax, H. and Inouye, M., "Numerical Analysis of Flow Properties about Blunt Bodies Moving at Supersonic Speeds in an Equilibrium Gas," TR R-204, 1964, NASA.
3. Grabau, M., "A Method of Forming Continuous Empirical Equations for the Thermodynamic Properties of Air from Ambient Temperatures to 15,000 °K with Applications," TN-59-102, 1959, AEDC.
4. Lewis, C. H. and Burgess, E. G., "Empirical Equations for the Thermodynamic Properties of Air and Nitrogen to 15,000 °K," TDR-63-138, 1963, AEDC.
5. Barnwell, R. W., "Inviscid Radiating Shock Layers about Spheres Traveling at Hypersonic Speeds in Air," TR R-311, 1969, NASA.

APPENDICES

APPENDIX A

Program for Generating Cubic Coefficients

```

DIMENSION F(4),EE(4),V(4,4),U(4,4),FP(4),P(4),NTT(11),EXT(11,2)
DIMENSION AO(11,22),A1(11,22),A2(11,22),A3(11,22),FEE(11,22)
DIMENSION TZ(3000),C(7),NEZ(89),NDL(4,11),NDU(4,11)
EQUIVALENCE (NDZ,NDL),(NDZ(45),NDU)
READ(9,201) WTMIX,(C(N),N=1,7)
READ(9,200) (NDZ(N),N=1,89)
NMM=NDZ(89)
READ(9,201) (TZ(N),N=1,NMM)
REWIND 9
WRITE(6,2030)
DO 120 N=1,88
120 NDZ(N) = 5*NDZ(N)
CONC = WTMIX/28.566
PO = 2116.
RO = .002458*CONC
B = TZ(NMM-2)
E = TZ(NMM-1)
D = TZ(NMM)
FM = 2.1632 + .3463*CONC
DO 1000 NR =1,11
NL = NDL(2,NR)
NU = NDU(2,NR)
NT = ((NU-NL)/5) + 1
NTT(NR)= NT
WRITE(6,2011) NR,NTT(NR)
RHC = RO*10.**((NR-8)
DO 500 I =1,NT
ND = NL + 5*(I-1)
FMAX = TZ(ND + 5)
IF(I .EQ. NT) FMAX = FM - .00001
F(1) = TZ(ND)
F(2) = ((FMAX - TZ(ND))/3.) + TZ(ND)
F(3) = (FMAX - TZ(ND))*(2./3.) + TZ(ND)
F(4) = FMAX
DO 800 J=1,4
P(J) = PO*10.**((F(J)*(1.+E*ALOG10(RHO/RO)+ D*(ALOG10(RHO/RO))**2 )
1 +ALOG10(RHC/RC) + B)
CALL RGAS(P(J),RHO,A,H,T,S,RR,G,-1,2,2)
EE(J)= H - P(J)/RHO
800 CONTINUE
WRITE(6,2010) (F(K),K=1,4),(EE(K),K=1,4)
DO 20 J=1,4
DO 10 K=1,4
V(K,J) =EE(K)**(J-1)
10 U(K,J) = V(K,J)
20 CONTINUE
EPS = .000001
CALL GELG(F,V,4,1,EPS,IER)
IF(IER)50,60,50
50 WRITE(6,2020) IER
DO 70 J=1,4
SUM = 0.
DO 80 K=1,4
80 SUM = SUM + U(J,K)* F(K)
70 FP(J)= SUM
WRITE(6,2022) FP(1),FP(2),FP(3),FP(4)
60 WRITE(6,2023) F(1),F(2),F(3),F(4),EE(1)
AO(NR,I) = F(1)
A1(NR,I) = F(2)
A2(NR,I) = F(3)
A3(NR,I) = F(4)

```

```

      EEE(NR,I) = EE(1)
900  CONTINUE
      EXT(NR,1) = EEE(1,1)
      EXT(NR,2) = EE(4)
1000 CONTINUE
      REWIND 9
      WRITE(6,44) (EXT(NR,1),NR=1,11),(EXT(NR,2),NR=1,11),B,E,D,WTMIX
      WRITE(10,44)(EXT(NR,1),NR=1,11),(EXT(NR,2),NR=1,11),B,E,D,WTMIX
      NDZ(1) = 1
      NSAVE = 0
      DO 22 II=2,11
      NDZ(II) = NTT(II-1) + 1 + NSAVE
      NDZ(II+10) = NTT(II-1) + NSAVE
      NSAVE = NDZ(II+10)
22  CONTINUE
      NDZ(22) = NTT(11) +      NSAVE
      NDZ(23) = 5*NDZ(22)
      WRITE (6,2) (NDZ(N),N=1,23)
      WRITE(10,2) (NDZ(N),N=1,23)
      DO 42 I=1,11
      NT = NTT(I)
      DO 41 J=1,NT
      WRITE(10,43) AC(I,J),A1(I,J),A2(I,J),A3(I,J),EEE(I,J)
41  WRITE (6,43) AC(I,J),A1(I,J),A2(I,J),A3(I,J),EEE(I,J)
42  CONTINUE
      2  FORMAT(16I8)
43  FORMAT(5E16.8)
44  FORMAT(6E16.8)
200  FORMAT (16I8)
201  FORMAT (8E16.8)
2010 FORMAT(8F15.7)
2011 FORMAT(1H ,5X,'NR=',I5,15X,'NT=',I5)
2020 FORMAT(1H ,3X,'IER=',I4)
2022 FORMAT(1H ,4X,'FP(1)=' ,E15.7,5X,'FP(2)=' ,E15.7,5X,'FP(3)=' ,E15.7,
1      5X,'FP(4)=' ,E15.7)
2023 FORMAT(1H ,4X,'AC=' ,E15.7,5X,'A1=' ,E14.7,5X,'A2=' ,E15.7,5X,'A3=' ,
1      E15.7,5X,'E(1)=' ,E15.7)
2030 FORMAT(1H1,4X,'F(1)',13X,'F(2)',11X,'F(3)',11X,'F(4)',11X,'E(1)',
1      11X,'E(2)',11X,'E(3)',11X,'E(4)')
      STOP
      END
//GO.FT09F001  DD  UNIT=TAPE7,VOLUME=SFR=T2145,DISP=(CLD,KEEP),      X
//              DCB=(DEN=1,TRTCH=ET,RECFM=U,PLKSIZE=132),LABEL=(2,NL)

```

APPENDIX B

CALLING SEQUENCE FOR MODIFIED RGAS

The modified RGAS subroutine is called by the following statement

CALL RGAS(P, R, A, H, T, S, RR, G, NTEST, NUMX, NGAS, E) with

P = Pressure lb/ft²

R = Density, slugs/ft³

A = Speed of sound, ft/sec

H = Enthalpy, ft²/sec²

T = Temperature, °R

S = Entropy, ft²/sec² - °R

RR = Gas constant, ft²/sec² - °R

G = Ratio of specific heats

E = Internal energy in ft²/sec²

NTEST = - 1 enter with P,R or P,S data for real gas

= 0 enter with P,R, or P,S data for perfect gas

= 1 enter with E,R data for real gas

		NTEST = - 1 or 0	NTEST = 1
NUMX = 1	Input =	P, R, RR, G	E, R, RR, G
	Output =	A	P, A
= 2	Input =	Same as NUMX = 1	Same as NUMX = 1
	Output =	A, H	P, A, H
= 3	Input =	Same as NUMX = 1	Same as NUMX = 1
	Output =	A, H, T	P, A, H, T
= 4	Input =	Same as NUMX = 1	Same as NUMX = 1
	Output =	A, H, T, S	P, A, H, T, S
= 5	Input =	P, S, RR, G	
	Output =	R, A, H, T	

NGAS = File number on permanent tape which contains desired gas.

APPENDIX C

Listing of Modified RGAS

```

SUBROUTINE RGAS(PX,RX,AX,HX,TX,SX,RRX,GX,NTEST,NUMX,NGAS,EX)
DIMENSION NLL(10),JXX(10),DZZ(10),TZ(3000),NDZ(89)
DIMENSION TH(5,600),NDL(4,11),NDU(4,11),AN(4),C(7),ANR(17),BN(4)
DIMENSION      TTZ(750),NNDZ(23),DH(5,150),EXT(11,2)
EQUIVALENCE(TZ,TH),(NDZ,NDL),(NDZ(45),NDU),(TTZ,DH)
FIRST = 1.0
DATA KEY,NTIMES/C,0/
DATA WORD1,WORD2/4HNUMH,4HNUML/
DATA NFIRST/0/
DATA NTAPE/9/
DATA MFIRST,MTIMES/0,0/
164 KEY=KEY+1
    P=PX
    S = SX
    R=RX
    NUM=NUMX
    IF(NUM) 1,1,2
    2 IF(NUM-5) 3,3,4
    4 WORD=WORD1
    6 WRITE(6,5) WORD
    5 FORMAT(12H0 ER IN RGAS,3X,A4)
    25 CALL EXIT
    1 WORD=WORD2
    GO TO 6
3    IF(NTEST) 7,8,500
500 E = EX
    IF(MFIRST.GT.0) GO TO 531
    READ(10,499) (EXT(NR,1),NR=1,11),(EXT(NR,2),NR=1,11),B,E1,D,WTMIX
499 FORMAT(6E16.8)
    READ(10,501)(NNDZ(N),N=1,23)
501 FORMAT(16I8)
    NNMM=NNDZ(23)
    READ(10,502)(TTZ(N),N=1,NNMM)
502 FORMAT(5E16.8)
    END FILE 10
    REWIND 10
    DO 503 N=1,22
503 NNDZ(N)=5*NNDZ(N)
    CONC = WTMIX/28.566
    PO = 2116.
    RO = .002458*CONC
531 R = ALOG10(R/RO)
    IF(R) 512,512,513
512 NR = R-1.
    IF(NR+7)516,516,515
516 NR = -7
    GO TO 515
513 NR = R
    IF(NR-3) 515,514,514
514 NR = 2
515 DX = R - FLOAT(NR)
    NR = NR + 8
    IF(E.LT.EXT(NR,1)) GO TO 521
    IF(E.GT.EXT(NR,2)) GO TO 519
525 NL =NNDZ(NR)
    IF(NLL(9)-NL) 601,602,601
602 J = JXX(9)
    DIFF2 = E - DH(5,J)
    IF(DIFF2) 601,608,608
608 IF(DZZ(9)-ABS(DIFF2)) 601,601,603
601 NU = NNDZ(NR+11)

```

```

      CALL SERCH(E,DH,NL,NU,5,J,NER)
      J = J/5
      DZZ(9) = ABS(DH(5,J+1) - DH(5,J))
      JXX(9)=J
      NLL(9) = NL
603  NL = NNDZ(NR+1)
      IF(NLL(10)-NL) 6C5,606,605
606  K = JXX(10)
      DIFF2 = E - DH(5,K)
      IF(DIFF2) 605,6C5,609
609  IF(DZZ(10)-ABS(DIFF2)) 605,605,607
605  NU = NNDZ(NR + 12)
      CALL SERCH(E,CH,NL,NU,5,K,NER)
      K = K/5
      DZZ(10) = ABS(DH(5,K+1) - DH(5,K))
      JXX(10) = K
      NLL(10) = NL
607  F1 = DH(1,J) + E*(DH(2,J) + E*(DH(3,J) +E*DH(4,J)))
      F2 = DH(1,K) + E*(DH(2,K) + E*(DH(3,K) +E*DH(4,K)))
      F = F1 + DX*(F2-F1)
      PX = PO*10.**{(F*(1.+E1*R +D*R*R) +R +B)}
521  IF(E.LT.EXT(NR,1)) PX = RX*EX*.4
      P = PX
      R = RX
      MFIRST = 1
      GO TO 7
519  MTIMES = MTIMES + 1
      WRITE(6,520) E
520  FORMAT(1H0,10X,'OUTSIDE TABLES IN RGAS ENTERING WITH E=',E16.8)
      WRITE(6,523) RX
523  FORMAT(48X,'R=',E16.8)
      IF(MTIMES-10) 525,525,25
       7 IF (NFIRST-NGAS) 10,9,10
      10 NFIRST=NGAS
      CALL LCCATE(NGAS,NTAPE)
C
C                                     FOR TAPE WRITTEN BY FORTRAN 2
C
      READ(9,201) WTMIX,(C(N),N=1,7)
      READ (NTAPE) (NC2(N),N=1,89)
      READ(9,200) (NDZ(N),N=1,89)
200  FORMAT(16I8)
      NMM=NDZ(89)
C
      READ (NTAPE) (TZ(N),N=1,NMM),WTMIX,(C(N),N=1,7)
      READ(9,201) (TZ(N),N=1,NMM),X,X,X,X,X,X,X,X
201  FORMAT(8E16.8)
1190 READ(9,201,END=1200) X,X,X,X,X,X,X,X
      GO TO 1190
1200 CONTINUE
      REWIND 9
      DO 120 N=1,88
120  NDZ(N)=5*NCZ(N)
      CONC=WTMIX/28.566
      PO=2116.
      RO=.002498*CONC
      RRR=1716./CUNC
      RRX=RRR
      RTC=RRR*493.635
      SQPORO=SQRT (RO/PC)
      B=TZ(NMM-2)

```

```

D=TZ(NMM)
FM=2.1632+.3468*CONC
AA=C*FM
BB=E*FM+1.
CCC=B+FM
9 P=ALOG10(P/P0)
E=TZ(NMM-1)
GO TO (40,40,40,40,31,4,4,4),NUM
31 REAL=S/RRR
GG=(REAL-C(1)-C(2)*P)/(C(3)+P*(C(4)+P*C(5)))
110 R=C(6)*GG+C(7)*P
RL=P-B
CC=CCC-P
RH=-CC*(1.+AA*CC/(BB*BB))/BB+.005
IF(RH+7.)183,185,185
183 RH=-7.
185 IF(R-RH) 180,181,181
180 R=RH
181 IF(3.-RL) 184,186,186
184 RL=3.
186 IF(RL-R) 182,163,163
182 R=RL
163 NUMB=0
NIMX=0
35 NUMM=5
NBCT=9-NUM
NUP=NBCT
GO TO 42
40 R=ALOG10(R/R0)
NUMM=5
NBCT=1
NUP=NUM
42 CONTINUE
IF(R) 12,12,13
12 NR=R-1.
IF(NR+7) 16,16,15
16 NR=-7
GO TO 15
13 NR=R
IF(NR-3) 15,14,14
14 NR=2
15 DX=R-FLOAT(NR)
NR=NR+8
F=(P-R-B)/(1.+R*(E+D*R))
IF(NUMM-9+NUM) 22,162,22
162 IF(F-.C00001) 27,161,161
161 IF(FM-F) 44,22,22
22 DO 17 N1=NBCT,NUP
IF(N1-NUMM) 36,81,36
36 NER1=N1
NER2=N1+4
NL=ADL(N1,NR)
IF(NLL(NER1)-NL) 301,302,301
302 J=JXX(NER1)
DIFF2=F-TH(5,J)
IF(DIFF2) 301,308,308
308 IF(DZZ(NER1)-ABS(DIFF2)) 301,301,303
301 NU=ACU(N1,NR)
CALL SERCH(F,TH,NL,NU,5,J,NER)
J=J/5
DZZ(NER1)=ABS(TH(5,J+1)-TH(5,J))

```

```

      JXX(NER1)=J
      NLL(NER1)=NL
303 XYZ=XYZ
      NL=NCL(N1,NR+1)
      IF (NLL(NER2)-NL) 305,306,305
306 K=JXX(NER2)
      DIFF2=F-TH(5,K)
      IF (DIFF2) 305,309,309
309 IF (DZZ(NER2)-ABS(DIFF2)) 305,305,307
305 NU=NDU(N1,NR+1)
      CALL SERCH(F,TH,NL,NU,5,K,NER)
      K=K/5
      DZZ(NER2)=ABS (TH(5,K+1)-TH(5,K))
      JXX(NER2)=K
      NLL(NER2)=NL
307 Y1=TH(1,J)+F*(TH(2,J)+F*(TH(3,J)+F*TH(4,J)))
128 Y2=TH(1,K)+F*(TH(2,K)+F*(TH(3,K)+F*TH(4,K)))
      AN(N1)=Y1+DX*(Y2-Y1)
      GO TO 17
      81 AN(N1)=REAL
17 CONTINUE
      IF (NUM-5) 51,52,52
      51 GO TC (121,122,123,124,124,124,124,124),NUM
      124 SX=AN(4)*RRR
123 TX= AN(3)*1.8
      122 HX=AN(2)*RTO
      121 AX=AN(1)/SQPORO
      GO TO 109
      52 IF (NUMM-9+NUM) 39,108,39
108 RX=RC*10.**R
      GO TC 51
      39 DIFF=ABS ((REAL-AN(NUP))/REAL)
      IF (DIFF-.0001) 37,37,38
      37 NUMM=9-NUM
      NBOT=1
      NUP=4
      GO TC 42
      38 NUMB=NUMB+1
      NIMX=NIMX+1
      IF (NIMX-20) 43,43,44
      43 IF (NUMB-2) 82,83,84
      82 IF (REAL-AN(NUP)) 85,37,86
      85 R1=R
141 S1=AN(NUP)
      R=R+.3
      IF (RL-R) 150,99,99
150 R=RL
      99 R2=R
151 L=C
      GO TO 42
      86 R2=R
153 S2=AN(NUP)
      R=R-.3
      IF (R-RH) 142,102,102
142 R=RH
102 R1=R
143 L=1
      GO TC 42
      83 IF (L) 91,90,91
      90 S2=AN(NUP)
126 R=R2-(S2 -REAL)/(S2-S1)*(R2-R1)

```

```

      IF(RL-R) 187,93,93
187 R=RL
      GO TO 93
      91 S1=AN(NUP)
127 R=(REAL-S1      )/(S2-S1)*(R2-R1)+R1
      IF(R-RH) 188,93,93
188 R=RH
      93 IF(R2-R) 104,37 ,105
104 NUMB=1
      R1=R2
      S1=S2
      L=0
      IF(R2+.3-RL) 210,211,211
211 R2=RL
      R=R2
      GO TO 42
210 R2=R2+.3
      R=R2
      GO TO 42
105 IF(R-R1) 106,37,42
106 NUMB=1
      R2=R1
      S2=S1
      L=1
      IF(RH-R1+.3) 212,213,213
213 R1=RH
      R=R1
      GO TO 42
212 R1=R1-.3
      R=R1
      GO TO 42
      84 IF(REAL-AN(NUP)) 87,87,88
      87 R1=R
      GO TO 91
      88 R2=R
      GO TO 90
      44 IF(F-.000001) 27,444,444
444 NTIMES=NTIMES+1
      WRITE(6,190)
190 FORMAT(1H0,10X,36HOUTSIDE TABLES IN RGAS ENTERING WITH)
      WRITE(6,191) PX
191 FORMAT(11X,2HP=,E13.6)
      IF(NUM-5) 192,193,193
192 WRITE(6,194) RX
194 FORMAT(11X,2HR=E14.6)
      GO TO 196
193 WRITE(6,195) SX
195 FORMAT(11X,2HS=,E13.6)
196 IF(NTIMES-10) 109,197,197
197 WRITE(6,198)
198 FORMAT(20X,28HEXIT CALLED CN TENTH FAILURE)
      GO TO 25
      8 L=0
      IF(GTEST-GX) 64,441,64
64 GTEST= GX
      L1=2
      ANR(1)=RRX
      ANR(2)=GX
      ANR(3)=ANR(1)/(ANR(2)-1.)
      ANR(4)=ANR(1)+ANR(3)
      ANR(8)=49CC8.609-ANR(3)*ALOG(171.6/.0001 **ANR(2))

```

```

26 ANR(L+5)=1./ANR(L+2)
   ANR(L+6)=ANR(L+4)/ANR(L+1)
   ANR(L+7)=ANR(L+6)/ANR(L+2)
441 GO TO (440,440,440,440,69,70,71,72),NUM
440 QUCD=P/R**ANR(L+2)
   QUCT=P/R
   GO TO(65,66,67,68,69,70,71,72),NUM
68 S=ANR(L+8)+ANR(L+3)*ALOG(QUOD)
67 T=QUCT/ANR(L+1)
66 H=QUCT*ANR(L+6)
65 LL=L+L1
   A=SQRT (ANR(LL )*QUOT)
   GO TO 30
69 EX=S-ANR(L+8)
   EX=EXP (EX/ANR(L+3))
   R=(P/EX)**ANR(L+5)
   QUOD=P/R**ANR(L+2)
   QUOT=P/R
   GO TO 67
70 R=P/(T*ANR(L+1))
   QUCD=P/R**ANR(L+2)
   QUCT=P/R
   S=ANR(L+8)+ANR(L+3)*ALOG(QUOD)
   GO TO 66
71 ASSIGN 65 TO NJUMP
73 T=H/ANR(L+4)
   R=P/(T*ANR(L+1))
   QUCD=P/R**ANR(L+2)
   QUOT=P/R
   S=ANR(L+8)+ANR(L+3)*ALOG(QUOD)
   GO TO NJUMP,(65,30)
72 ASSIGN 30 TO NJUMP
   H=ANR(L+7)*A**2
   GO TO 73
30 AX=A
   HX=T
   TX= T
   SX=S
   RX=R
109 RETLRN
27 L=8
   P=PX
   R=RX
   IF (GTESTR-GX) 24,441,24
24 GTESTR=GX
   L1=9
   Z2=R0/10.**7
   PR=-7.+8
   PR=PC*10.**PR
   Z1=PR
   DO 21 N1=1,4
   NL=NDL(N1,1)
   NU=NDU(N1,1)
   F=C.
   CALL SERCH(F,TH,NL,NU,5,J,NER)
   J=J/5
21 BN(N1)=TH(1,J)
   BN(1)=BN(1)/SQPORO
   BN(2)=BN(2)*RTO
   BN(3)=BN(3)*1.8
   BN(4)=BN(4)*RRR

```

```

ANR(9)=PR/(Z2 *BN(3))
RRX=ANR(9)
ANR(12)=BN(2)/BN (3)
ANR(10)=1.+ANR(9)/(ANR(12)-ANR(9))
ANR(11)=ANR(12)/ANR(10)
ANR(17)=BN(1)*BN(1)*Z2/Z1
ANR(16)=BN(4)-ANR(11)*ALOG(Z1/Z2**ANR(10))
LAST = 1
GO TO 26
ENC

```

```

//GO.FT09F001  DD  UNIT=TAPE7,VOLUME=SER=T2145,DISP=(OLD,PASS),      X
//              DCB=(DEN=1,TRTCH=ET,RECFM=U,BLKSIZE=132),LABEL=(2,NL)
//GO.FT10F001  DD  UNIT=TAPE7,VOLUME=SER=T2145,DISP=(NEW,KEEP),      X
//              DCB=(DEN=1,TRTCH=ET,RECFM=U,BLKSIZE=132),LABEL=(14,NL)

```


APPENDIX D

EQUATIONS FOR APPROXIMATE CURVE FITS

$$\underline{p = p(e, \rho)}$$

For the correlation of $p = p(e, \rho)$, the ratio $\tilde{\gamma} = h/e$ was curve-fitted using the following equation:

$$\tilde{\gamma} = a_1 + a_2 Y + a_3 Z + a_4 (Y)(Z) + \frac{a_5 + a_6 Y + a_7 Z + a_8 (Y)(Z)}{1 + \exp(a_9 + a_{10} Y + a_{11} Z)} \quad (D1)$$

where $Y = \log_{10}(\rho/1.292)$ and $Z = \log_{10}(e/78408.4)$. The units of ρ are kg/m^3 and the units of e are m^2/sec^2 . Once $\tilde{\gamma}$ is determined, $p(\text{N/m}^2)$ is found from

$$p = \rho e (\tilde{\gamma} - 1) \quad (D2)$$

The coefficients $a_1, a_2, \dots, a_{11}$ are given in Table 5.

$$\underline{a = a(e, \rho)}$$

The correlation for $a = a(e, \rho)$ is given by Eq. (15). The coefficients K_1, K_2 , and K_3 are listed in Table 5.

$$\underline{T = T(p, \rho)}$$

The temperature is given by the following equations:

$$T = p / (287 \times \rho) \quad Z \leq 1.30 \quad (D3)$$

$$\log_{10} T = b_1 + b_2(Y - RO) + b_3 \frac{\exp[2.(RO - Y) - 3.4]}{RO + 10.} + b_4 |RO|^{2(Z) - 2.18} \quad 1.30 < Z \leq 2.6 \quad (D4)$$

where $RO = \log_{10}(p/1.013 \times 10^5) + 2.42$ and

$$\log_{10} T = c_1 + c_2(RO) + c_3(Y - RO) + c_4 \frac{(Y - RO)}{1. - \exp[-50.25(Y - RO)]} \quad (D5)$$

where $RO = 0.941 \log_{10}(p/1.013 \times 10^5) - 1.97.$ $Z > 2.6$

The units of T are $^{\circ}K$. The coefficients b_1, b_2, b_3, b_4 and c_1, c_2, c_3, c_4 are given in Table 6.

Table 6. Coefficients for curve fit $T = T(p, \rho)$.

Density range	b_1	b_2	b_3	b_4	c_1	c_2	c_3	c_4
$Y > -0.50$	-0.450363	-1.16372	-1.37558	0.000355	4.17976	0.083386	-0.673668	0.071504
$-4.5 < Y \leq -0.50$	-0.022868	-1.03203	-1.02635	0.000441	4.17471	0.06272	-0.537628	-0.052594
$-7 \leq Y \leq -4.5$	0.113084	-0.994532	-0.970778	0.001902	4.12619	0.05437	-0.551836	0.051818

$$\underline{h = h(p, \rho)}$$

For the correlation $h = h(p, \rho)$, the ratio $\tilde{\gamma} = h/e$ was curve-fitted using the following equation:

$$\tilde{\gamma} = d_1 + d_2 Y + d_3 X + d_4 (X)(Y) + \frac{d_5 + d_6 Y + d_7 X + d_8 (X)(Y)}{1 + \exp(d_9 + d_{10} Y + d_{11} X')}$$

where $X' = \log_{10}(p/1.013 \times 10^5)$ and $X = X' - Y$. The units for h are m^2/sec^2 . Once $\tilde{\gamma}$ is determined, h is found from

$$h = (p/\rho)(\tilde{\gamma}/\tilde{\gamma} - 1) \quad (D6)$$

The coefficients $d_1, d_2, \dots, d_{11}$ are listed in Table 7.

APPENDIX E:

SUBROUTINE TGAS FOR $p = p(e, \rho)$, $a = a(e, \rho)$, and $T = T(p, \rho)$

The calling statement for this subroutine is

CALL TGAS(E, RHO, P, T, A)

with

E - Internal energy in m^2/sec^2

RHO - Density in kg/m^3

P - Pressure in $\text{newtons}/\text{m}^2$

T - Temperature in $^{\circ}\text{K}$

A - Speed of sound in m/sec

The following logic can be employed when the English system of units is used:

EI = E * 0.0929

RHO1 = RHO * 515.4

CALL TGAS (EI, RHO1, P1, T1, A1)

P = P1 * 0.02088

T = T1 * 1.80

A = A1 * 3.281

with

E = Internal energy, ft^2/sec^2

RHO = Density, slugs/ft^3

P = Pressure, lbs/ft^2

T = Temperature, $^{\circ}\text{R}$

A = Speed of sound, ft/sec

Listing of TGAS for $p = p(e, \rho)$, $a = a(e, \rho)$, and $T = T(p, \rho)$

```

SUBROUTINE TGAS(E,RHO,P,T,A)
Y2= ALOG10(RHO/1.292)
Z2= ALOG10(E/78408.4)
IF(Y2 .GT. -.50) GO TO 14
IF(Y2 .GT. -4.50) GO TO 7
IF(Z2.GT..650)GO TO 1
GAMM=1.400
SNDSQ= E*.560
GO TO 4
1 IF(Z2.GT.2.02) GO TO 2
GAS1= 1.35397-.0049197*Y2
GAS2= -.0314908+.0733289*Y2
GAS3= .390859-.257944*Y2
GAS4= -.0637166-.0377134*Y2
GAS5= .0049197+.0733289*Z2
GAS6= .257944-.0377134*Z2
GAS7= EXP(-2.*Z2+.064*Y2+3.40)
GAS8= -2.0
GAS9= .064
GAS12= .115520
GAS13= .135562
GAS14= -.00159424
GO TO 3
2 GAS1= 1.38221-.0069761*Y2
GAS2= .0916976-.0068208*Y2
GAS3= .322099-.0054549*Y2
GAS4= .118999-.0037667*Y2
GAS5= .0069761-.0068208*Z2
GAS6= .0054549-.0037667*Z2
GAS7= EXP(-10.*Z2+.320*Y2+27.08)
GAS8= -10.0
GAS9= .320
GAS12= .342076
GAS13= .0236520
GAS14= .007608
3 GAS10=1./((1.+GAS7))
GAS11=(GAS3-GAS4*Z2)*GAS7*GAS10**2
GAMM=GAS1-GAS2*Z2-(GAS3-GAS4*Z2)*GAS10
GAME=2.304*(-GAS2+GAS4*GAS10+GAS11*GAS8)
GAME= GAME*GAS12
GAMR=2.304*(-GAS5+GAS6*GAS10+GAS11*GAS9)
GAMR= GAMR*GAS13
SNDSQ= E*((GAMM-1.)*(GAMM+GAME)+GAMR+GAS14)
4 A= SQRT(AES(SNDSQ))
P= RHO*E*(GAMM-1.0)
IF(Z2 .GT. 1.30) GO TO 5
T= P/(287.*RHO)
GO TO 102
5 IF(Z2 .GT. 2.6) GO TO 6
RO= ALOG10(P/1.013E+05)+2.42
T= .113084-.554532*(Y2-RO)-.970778*(1./(RO+10.))*EXP(2.*((RO-Y2)
1-3.40))+.001902*(ABS(RO))**(2.*Z2-2.18)
GO TO 101
6 RO= 0.941*ALOG10(P/1.013E+05)-1.970
IF (Y2 .EQ. RO) GO TO 100
T= 4.12619+.054370*RO-.551836*(Y2-RO)+.051318*(Y2-RO)/(1.0-
1EXP(-50.25*(Y2-RO)))
GO TO 101
7 IF(Z2.GT..650)GO TO 8
GAMM=1.400
SNDSQ= E*.560

```



```

GO TO 11
8 IF(Z2.GT.2.3)GO TO 9
  GAS1= 2.10606-.0525560*Y2
  GAS2= -1.00142+.0302711*Y2
  GAS3= 5.83208-.132134*Y2
  GAS4= .276381+.0043623*Y2
  GAS5= .0525560+.0302711*Z2
  GAS6= .132134+.0043623*Z2
  GAS7= EXP(-Z2+.032*Y2+1.80)
  GAS8= -1.0
  GAS9= .032
  GAS12= .147174
  GAS13= .428416
  GAS14= -.00605
  GO TO 10
9 GAS1= 1.58945+.0956959*Y2
  GAS2= .174938+.0354141*Y2
  GAS3= .390197+.0455076*Y2
  GAS4= .166956+.0242439*Y2
  GAS5= -.0956959+.0354141*Z2
  GAS6= -.0455076+.0242439*Z2
  GAS7= EXP(-10.0*Z2+.320*Y2+27.08)
  GAS8= -10.0
  GAS9= .320
  GAS12= .259574
  GAS13= -.192579
  GAS14= .014277
10 GAS10=1./(1.+GAS7)
  GAS11=(GAS3-GAS4*Z2)*GAS7*GAS10**2
  GAMM=GAS1-GAS2*Z2-(GAS3-GAS4*Z2)*GAS10
  GAME=2.304*(-GAS2+GAS4*GAS10+GAS11*GAS8)
  GAME= GAME*GAS12
  GAMR=2.304*(-GAS5+GAS6*GAS10+GAS11*GAS9)
  GAMR= GAMR*GAS13
  SNDSQ= E*((GAMM-1.)*(GAMM+GAME)+GAMR+GAS14)
11 A= SQRT(ABS(SNDSQ))
  P= RHO*E*(GAMM-1.0)
  IF(Z2.GT. 1.30) GO TO 12
  T= F/(287.*RHO)
  GO TO 102
12 IF(Z2.GT. 2.6) GO TO 13
  RO= ALOG10(P/1.013E+05)+2.42
  T=-.022868-1.03203*(Y2-RO)-1.02635*(1./(RO+10.))*EXP(2.*((RO-Y2)
1-3.40))+.000441*(ABS(RO))**(2.*Z2-2.18)
  GO TO 101
13 RO= C.541*ALOG10(P/1.013E+05)-1.970
  IF (Y2.EQ. RO) GO TO 100
  T= 4.17471+.062720*RO-.537628*(Y2-RO)-.052594*(Y2-RO)/(1.0-
1EXP(-50.25*(Y2-RO)))
  GO TO 101
14 IF(Z2.GT..650)GO TO 15
  GAMM=1.400
  SNDSQ= E*.560
  GO TO 18
15 IF(Z2.GT.2.3)GO TO 16
  GAS1= 1.8379-.0140959*Y2
  GAS2= -.532783+.0347996*Y2
  GAS3= 3.81752-.0571566*Y2
  GAS4= .274508+.0425175*Y2
  GAS5= .0140959+.0347996*Z2
  GAS6= .0571566+.0425175*Z2

```

```

GAS7= EXP(-1.0*Z2+.032*Y2+1.943)
GAS8= -1.0
GAS9= .032
GAS12= .150553
GAS13= .189652
GAS14= -.0033884
GO TO 17
16 GAS1= 1.53746-.0411865*Y2
   GAS2= .151113-.0256504*Y2
   GAS3= .305574+.0488379*Y2
   GAS4= .135442+.0145258*Y2
   GAS5= .0411865-.0256504*Z2
   GAS6= -.0488379+.0145258*Z2
   GAS7= EXP(-10.0*Z2+.320*Y2+27.08)
   GAS8= -10.0
   GAS9= .320
   GAS12= .198341
   GAS13= .216819
   GAS14= -.0016115
17 GAS10=1./{1.+GAS7)
   GAS11=(GAS3-GAS4*Z2)*GAS7*GAS10**2
   GAMM=GAS1-GAS2*Z2-(GAS3-GAS4*Z2)*GAS10
   GAME=2.304*(-GAS2+GAS4*GAS10+GAS11*GAS8)
   GAME= GAME*GAS12
   GAMR=2.304*(-GAS5+GAS6*GAS10+GAS11*GAS9)
   GAMR= GAMR*GAS13
   SNDSQ= E*{(GAMM-1.)*(GAMM+GAME)+GAMR+GAS14)
18 A= SQRT{APS(SNDSQ))
   P= RHC*E*(GAMM-1.0)
   IF(Z2 .GT. 1.30) GO TO 19
   T= P/(287.*RHC)
   GO TO 102
19 IF(Z2 .GT. 2.6) GO TO 20
   RO= ALOG10(P/1.013E+05)+2.42
   T=-.450363-1.16372*(Y2-RO)-1.37558*(1./{RO+10.))*EXP(2.*{(RO-Y2)
1-3.40))+.000355*(ABS(RO))*{(2.*Z2-2.18)
   GO TO 101
20 RO= 0.941*ALOG10(P/1.013E+05)-1.970
   IF (Y2 .EQ. RC) GO TO 100
   T= 4.17976+.083386*RO-.673668*(Y2-RO)+.071504*(Y2-RO)/(1.0-
1EXP(-50.25*(Y2-RC)))
   GO TO 101
100 T= 4.174+.063*Y2
101 T= 10.**T
102 RETURN
END

```

APPENDIX F

SUBROUTINE TGAS FOR $h = h(p, \rho)$

The calling statement for this subroutine TGAS is

```
CALL TGAS(P, RHO, H)
```

with

P = Pressure, newtons/m²

RHO = Density, kg/m³

H = Enthalpy, m²/sec²

The following logic can be employed when the English system of units is used:

$P1 = P/0.02088$

$RHO1 = RHO * 515.4$

CALL TGAS(P1, RHO1, H1)

$H = H1/0.0929$

with

P - Pressure in lbs/ft²

RHO - Density in slugs/ft³

H - Enthalpy in ft²/sec²

Listing of TGAS for $h = h(p, \rho)$

```

SUBROUTINE TGAS(P,RHO,H)
Y2= ALOG10(RHO/1.292)
X2= ALOG10(P/1.013E+05)
Z3= X2-Y2
IF (Y2 .GT. -.50) GO TO 6
IF (Y2 .GT. -4.50) GO TO 3
IF (Z3 .GT. .250) GO TO 1
H= (P/RHO)*3.50
RETURN
1 IF (Z3 .GT. 1.40) GO TO 2
GAS1= 1.40168+.0025690*Y2
GAS2= .0644343+.0229381*Y2
GAS3= -.0746109-.0148297*Y2
GAS4= -.151756+.0187665*Y2
GAS5=EXP(-10.0*X2+10.31*Y2+9.0)
GO TO 9
2 GAS1= 2.04727+.115191*Y2
GAS2= .631801+.0910350*Y2
GAS3= 1.00382+.114356*Y2
GAS4= .677464+.0542628*Y2
GAS5=EXP(-5.0*X2+5.5*Y2+8.5)
GO TO 9
3 IF (Z3 .GT. .250) GO TO 4
H= (P/RHO)*3.50
RETURN
4 IF (Z3 .GT. 1.40) GO TO 5
GAS1= 1.40668+.0036616*Y2
GAS2= .053836+.0203309*Y2
GAS3= -.0675256-.0121155*Y2
GAS4= -.134637+.0235357*Y2
GAS5=EXP(-10.0*X2+10.31*Y2+9.0)
GO TO 9
5 GAS1= 1.26133-.0084646*Y2
GAS2= .0387273-.0033959*Y2
GAS3= .183174-.0074683*Y2
GAS4= .0784110-.0056930*Y2
GAS5=EXP(-10.0*X2+11.0*Y2+17.0)
GO TO 9
6 IF (Z3 .GT. .250) GO TO 7
H= (P/RHO)*3.50
RETURN
7 IF (Z3 .GT. 1.40) GO TO 8
GAS1= 1.40715+.0020473*Y2
GAS2= .0472791+.0068224*Y2
GAS3= -.0414595+.0325854*Y2
GAS4= -.118581+.0404860*Y2
GAS5=EXP(-10.0*X2+10.31*Y2+9.0)
GO TO 9
8 GAS1= 1.36839-.0032924*Y2
GAS2= .103499-.0124481*Y2
GAS3= .341674+.0228219*Y2
GAS4= .171891+.0089432*Y2
GAS5=EXP(-10.0*X2+11.0*Y2+17.0)
9 GAMM=GAS1-GAS2*Z3-(GAS3-GAS4*Z3)/(1.+GAS5)
10 H= (P/RHO)*(GAMM/(GAMM-1.))
RETURN
END

```