
NASA TECH BRIEF

Lyndon B. Johnson Space Center



NASA Tech Briefs announce new technology derived from the U.S. space program. They are issued to encourage commercial application. Tech Briefs are available on a subscription basis from the National Technical Information Service, Springfield, Virginia 22151. Requests for individual copies or questions relating to the Tech Brief program may be directed to the Technology Utilization Office, NASA, Code KT, Washington, D.C. 20546.

High-Friction Mechanical Grips



The problem:

Mechanical-grip friction surfaces are usually machined to a high-friction finish by multiple serrations. The high-friction finishes produced by this method may be relatively expensive.

The solution:

Plasma-arc spraying offers a method of preparing the required surface at a greatly reduced cost.

How it's done:

A coarse-grained, tungsten carbide bonded-nickel coating is applied by plasma-arc spraying. This coating has been used successfully on wedge-shaped mechanical test grips.

The test grip shown in the illustration demonstrates plasma-arc-sprayed coatings. These grips were proof tested to a 150,000-pound (670,000-newton) pull. This indicates that they may be used for 100,000-pound (450,000-newton) laboratory tests.

Note:

No further documentation is available.

Patent status:

NASA has decided not to apply for a patent.

Source: E. G. Stevens of Rockwell International Corp. under contract to Johnson Space Center (MSC-19260)

Wedge-Shaped Grip With Plasma-Arc-Sprayed Coating