



DATA Management Copy #5
Lee Lauer

NATIONAL AERONAUTICS AND SPACE ADMINISTRATION

DMS-DR-2011
NASA CR-120,089

SPACE SHUTTLE (ATP CONFIGURATION)
ABORT STAGING INVESTIGATION

(NASA-CR-120089) SPACE SHUTTLE (ATP
CONFIGURATION) ABORT STAGING INVESTIGATION
(Chrysler Corp.) 200 p HC \$12.00

N73-21831

CSCL 22B



SPACE SHUTTLE

AEROTHERMODYNAMIC DATA REPORT

MANNED SPACECRAFT CENTER

HOUSTON, TEXAS

DATA MANAGEMENT services

SPACE DIVISION  CHRYSLER
CORPORATION

April, 1973

DMS-DR-2011
NASA CR-120,089

SPACE SHUTTLE (ATP CONFIGURATION)

ABORT STAGING INVESTIGATION

By

J. Rampy, NSI
K. Blackwell, NASA/MSFC
E. Allen, Rockwell
I. Fossler, NASA/MSC

Prepared under NASA Contract Number NAS9-13247

by

Data Management Services
Chrysler Corporation Space Division
New Orleans, La. 70189

for

Aerodynamics Section
Flight Technology Branch
Engineering Analysis Division

Manned Spacecraft Center
National Aeronautics and Space Administration
Houston, Texas

WIND TUNNEL TEST SPECIFICS:

Test Number: MSFC-TWT-558
NASA Series No.: MA9F
NASA CR 120,089
Test Date: November 29 - December 7, 1972

FACILITY COORDINATOR:

Jim Weaver
Marshall Space Flight Center
Mail Stop S&E-AERO-AAE
Huntsville, Alabama 35801

Phone: (205) 453-2512

PROJECT ENGINEERS:

J. Rampy
Northrop Services Inc.
6025 Technology Drive
Huntsville, Alabama 35807

Phone: (205) 837-0580

K. Blackwell
Marshall Space Flight Center
Mail Stop S&E-AERO-AAE
Huntsville, Alabama 35801

Phone: (205) 453-2512

E. Allen
Rockwell International
Suite 142
3322 S. Memorial Parkway
Huntsville, Alabama 35801

Phone: (205) 881-2200

I. Fossler
Manned Spacecraft Center
EOA Flight Technology
Bldg. 16, Code EX24
Houston, Texas 77058

Phone: (713) 483-2983

DATA MANAGEMENT SERVICES

This document has been prepared by:

V. W. Sparks
Liaison Operations

V. W. Sparks

J. Ziler
Data Operations

J. Ziler

This document has been reviewed and is approved for release.

N. D. Kemp
Data Management Services

N. D. Kemp

Chrysler Corporation Space Division assumes no responsibility for the data presented herein other than its display characteristics.

TABLE OF CONTENTS

	Page
ABSTRACT	2
INDEX OF MODEL FIGURES	3
INDEX OF DATA FIGURES	4
NOMENCLATURE	5
MODEL DESCRIPTION AND TUNNEL INSTALLATION	8
CONFIGURATIONS INVESTIGATED	8
TEST FACILITY DESCRIPTION	9
TEST PROCEDURE	10
DATA REDUCTION	10
REFERENCE DIMENSIONS	11
TABLES	
I. TEST GRID	12
II. TEST CONDITIONS	13
III. DATA SET COLLATIONS	14
IV. DIMENSIONAL DATA	20
FIGURES	
MODEL	32
DATA	39
APPENDIX	
TABULATED SOURCE DATA	

SPACE SHUTTLE (ATP CONFIGURATION) ABORT STAGING INVESTIGATION

By J. Ramps*, K. Blackwell**, E. Allen***, and I. Fossler****

ABSTRACT

This report presents results of a wind tunnel test conducted in the MSFC 14-Inch Trisonic Wind Tunnel to determine the force and moment characteristics of the ATP Orbiter and modified ATP External Tank/SRB combination during abort staging conditions. The .004 scale models were previously employed in MSFC Test 545. Figure 6 shows a typical installation of these models. The MSFC TWT staging apparatus was used to move the orbiter to relative horizontal and vertical distances and relative incidence angles to ET/SRB combination. Six component aerodynamic force and moment data were recorded for the orbiter and ET/SRB combination.

Pitch polars were obtained for an angle of attack range from -10 to 10 degrees and orbiter incidence angles (orbiter relative to the ET/SRB combination) of 0 and 2 degrees. A limited amount of yaw data were obtained at 0 degree angle of attack and beta range from -10 to 10 degrees. In addition, orbiter pitch control effectiveness was determined at several grid points. These force and moment data were obtained for Mach numbers of 0.9, 1.2 and 2.0.

* NSI

** NASA/MSFC

*** Rockwell International

**** NASA/MSC

INDEX OF MODEL FIGURES

<u>FIGURE</u>	<u>DESCRIPTION</u>	<u>PAGE</u>
1	Axis systems.	33
2	ATP Orbiter (01).	34
3	Modified ATP ET (T3) and ATP SRB.	35
4	Layout of test grid and sign convention.	36
5	Space Shuttle Parallel Staging System for the MSFC 14 x 14-Inch Trisonic Wind Tunnel.	37
6	Typical installation photograph.	38

INDEX OF DATA FIGURES

<u>TITLE</u>	<u>COEFFICIENT SCHEDULE</u>	<u>PLOT PAGES</u>
EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK/SRB, LONGITUDINAL STABILITY	1	1-47
EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK/SRB, LAT.-DIR STABILITY	2	48-53
LONGITUDINAL STABILITY CHARACTERISTICS - EFFECTS OF VARYING DELX/D	3	54-56
LONGITUDINAL STABILITY CHARACTERISTICS - EFFECTS OF VARYING DELZ/D	4	57-65

COEFFICIENT SCHEDULE

1. CAF, CN, CLM, XCP/L versus ALPHA
2. CBL, CY, CYN, YCP/L versus BETA
3. CAF, CN, CLM versus DELX/D
4. CAF, CN, CLM versus DELZ/D

NOMENCLATURE
General

<u>SYMBOL</u>	<u>PLOT SYMBOL</u>	<u>DEFINITION</u>
e		speed of sound; m/sec, ft/sec
C _p	CP	pressure coefficient; $(p_1 - p_\infty)/q$
M	MACH	Mach number; V/a
p		pressure; N/m ² , psf
q	Q(NSM) Q(PSF)	dynamic pressure; $1/2 \rho V^2$, N/m ² , psf
RN/L	RN/L	unit Reynolds number; per m, per ft
V		velocity; m/sec, ft/sec
α	ALPHA	angle of attack, degrees
β	BETA	angle of sideslip, degrees
ψ	PSI	angle of yaw, degrees
ϕ	PHI	angle of roll, degrees
ρ		mass density; kg/m ³ , slugs/ft ³

Reference & C.G. Definitions

A _b		base area; m ² , ft ²
b	E _{REF}	wing span or reference span; m, ft
c.g.		center of gravity
L _{REF} c	L _{REF}	reference length or wing mean aerodynamic chord; m, ft
S	S _{REF}	wing area or reference area; m ² , ft ²
	MRP	moment reference point
	XMRP	moment reference point on X axis
	YMRP	moment reference point on Y axis
	ZMRP	moment reference point on Z axis

SUBSCRIPTS

b	base
l	local
s	static conditions
t	total conditions
e	free stream

NOMENCLATURE
(Continued)

Body-Axis System

<u>SYMBOL</u>	<u>PLOT SYMBOL</u>	<u>DEFINITION</u>
C_N	C_N	normal-force coefficient; $\frac{\text{normal force}}{qS}$
C_A	C_A	axial-force coefficient; $\frac{\text{axial force}}{qS}$
C_Y	C_Y	side-force coefficient; $\frac{\text{side force}}{qS}$
C_{A_b}	C_{AB}	base-force coefficient; $\frac{\text{base force}}{qS}$ $-A_b(p_b - p_\infty)/qS$
C_{A_f}	C_{AF}	forebody axial force coefficient; $C_A - C_{A_b}$
C_m	C_{LM}	pitching-moment coefficient; $\frac{\text{pitching moment}}{qS_l \text{REF}}$
C_n	C_{YN}	yawing-moment coefficient; $\frac{\text{yawing moment}}{qS_b}$
C_l	C_{BL}	rolling-moment coefficient; $\frac{\text{rolling moment}}{qS_b}$

NOMENCLATURE (concluded)

Additions to Standard List

D	ET Diameter - 318 in.
$\Delta X/D$ DELX/D	Incremental distance in X direction measured relative to nominal launch position (forward is plus). Change in orbiter nose location relative to ET nose. $\Delta X/D = 0$ is launch position.
$\Delta Z/D$ DELZ/D	Incremental distance in Z direction measured relative to nominal launch position (up is negative). Vertical gap distance between bottom of orbiter wing and top of ET surface. $\Delta Z/D = 0$ is launch position.
δ_e ELEVON	Effective elevon deflection angle of the inboard/outboard elevons, positive trailing edge down.
i_o ORBINC	Orbiter incidence angle
X_{cp}/λ XCP/L	Center of pressure location based on body length; $\left[\frac{X_{c.g.}}{\lambda_{Body}} - \frac{C_m}{C_N} \cdot \frac{\lambda_{ref}}{\lambda_{Body}} \right]$
Y_{cp}/λ YCP/L	Center of pressure location based on body length; $\left[\frac{X_{c.g.}}{\lambda_{Body}} - \frac{C_n}{C_Y} \cdot \frac{\lambda_{ref}}{\lambda_{Body}} \right]$

The 0.004 scale modified Rockwell International ATP Orbiter and ET/SRB models were utilized in this test. The External Tank, SRB bodies, and nose cones were made of aluminum while the SRB nozzles were made of brass. All other parts were constructed of stainless steel.

Orbiter and ET/SRB models were mounted on separate stings and balances. The orbiter was mounted on the top sting of the MSFC Parallel Staging Mounting System and the ET/SRB combination on the lower sting. Figures 5 and 6 show the staging system.

CONFIGURATIONS INVESTIGATED

The following configurations were investigated during this test:

<u>SYMBOL</u>	<u>DESCRIPTION</u>
O1	Orbiter consisting of the following components:
B1	Body
C1	Canopy
D1	Manipulator housing
F1	Body flap
M1	QMS pods
W1	Wing
E1	Elevon
V1	Vertical tail
K1	Coolant inlet
R1	Rudder

T3 318-inch diameter External Tank with ogive nose

S1 156-inch diameter solid Rocket Booster

Figures 2 and 3 present the orbiter and ET/SRB combination geometry and moment reference points. Other pertinent dimensional information for each model component is given in Table IV.

Test results reported herein were obtained on model configurations O1, T3, and S1. The data plots present the data according to the following definitions:

(O1)/(T3)(S1) Orbiter data obtained in presence of ET/SRB combination.

(T3)(S1)/(O1) ET/SRB data obtained in presence of orbiter.
ET contains the balance.

TEST FACILITY DESCRIPTION

The Marshall Space Flight Center 14" x 14" Trisonic Wind Tunnel is an intermittent blowdown tunnel which operates by high pressure air flowing from storage to either vacuum or atmospheric conditions. A Mach number range from .2 to 5.85 is covered by utilizing two interchangeable test sections. The transonic section permits testing at Mach 0.20 through 2.50, and the supersonic section permits testing at Mach 2.74 through 5.85. Mach numbers between .2 and .9 are obtained by using a controllable diffuser. The range from .95 to 1.3 is achieved through the use of plenum suction and perforated walls. Mach numbers of 1.44, 1.93 and 2.50 are produced by interchangeable sets of fixed contour nozzle blocks. Above Mach 2.50 a set of fixed contour nozzle blocks are tilted and translated automatically to produce any desired Mach number in .25 increments.

Air is supplied to a 6000 cubic foot storage tank at approximately -40°F dew point and 500 psi. The compressor is a three-stage reciprocating unit driven by a 1500 hp motor.

The tunnel flow is established and controlled with a servo actuated gate valve. The controlled air flows through the valve diffuser into the stilling chamber and heat exchanger where the air temperature can be controlled from ambient to approximately 180°F. The air then passes through the test section which contains the nozzle blocks and test region.

Downstream of the test section is a hydraulically controlled pitch sector that provides a total angle of attack range of 20° ($\pm 10^\circ$). Sting offsets are available for obtaining various maximum angles of attack up to 90°.

TEST PROCEDURE

The orbiter and ET/SRB combination were mounted on their respective balances as shown in Figures 5 and 6. The orbiter was moved horizontally and vertically with respect to the ET/SRB combination. The ΔX and ΔZ grid locations are given in Table 1 and shown in Figure 4. At each X, Z location, data were obtained for relative incidence angles (orbiter relative to the ET/SRB combination) of 0 and 2 degrees.

DATA REDUCTION

All model forces and moments are resolved in the body axis system and are presented in the form of non-dimensional coefficients. See Table IV

for model dimensional data. The data have been corrected for sting and balance deflections and have been interpolated to obtain constant grid locations and relative incidence angles. The moment reference points are shown in Figures 2 and 3. The orbiter nose and tank nose are the XMRP.

REFERENCE DIMENSIONS

PARAMETER	FULL SCALE	MODEL SCALE
Reference area (S_{ref}) (Orbiter wing area)	3220 ft. ²	7.419 in. ²
Reference length (l_{ref}) (Orbiter body length)	1328.0 in.	5.312 in.
Reference span (b_{ref}) (Orbiter body length)	1328.0 in.	5.312 in.
Balance location Orbiter (aft of nose) HO-Tank (forward of base)		3.714 in. 3.113 in.
Moment reference point		
Orbiter XMRP (aft of nose)	0	0
HO Tank XMRP (aft of nose)	0	0
Base area (A_b)		
Orbiter SRB (one)	382 ft. ²	0.878 in. ²
HO Tank	122.8 ft. ²	.306 in. ²
	553 ft. ²	1.271 in. ²

TABLE I

TEST GRID

MACH NUMBER	X/D	X/D
0.9	-D/2, 0, D/2	-D/2, -D, -3D/2
1.2	-D/2, 0, D/2	-D/2, -D, -3D/2
2.0	-D, 0, D, 2D, 3D	-D/2, -D, -3D/2

ΔX and ΔZ are increments measured from the nominal launch position.

D = ET Diameter (318 inches)

TABLE II

TEST TWO-T-558 - DATA SET COLLATION SHEET

TABLE III.

דRAFT

גָּמְנִיתְתַּתְ

INPVAR(1) INPVAR(2) NDV

COEFFICIENTS:

$$\alpha_A = -8^\circ \text{ to } 8^\circ \quad (\Delta\alpha = 3^\circ)$$

$$C_B = -10 \text{ to } 10 \quad (\Delta \beta = 2^\circ)$$

TEST TEST-558 DATA SET COLLATION SHEET

TABLE III. - Continued

PRETEST POSTTEST

COEFFICIENTS:

SCHEDULES

UDVAR(1) UDVAR(z);NDV

COEFFICIENTS:

-5

TEST TWO-T-558 DATA SET COLLATION SHEET

TABLE III. - Continued

ESTATE PLANNING

בונטנרט

TEST TWENTY-SEVEN DATA SET COLLATION SHEET

TABLE III. - Continued

PRETEST
 POSTTEST

DATA SET IDENTIFIER	CONFIGURATION	STANDARD				CONTROL REFLECTIONS	NO. OF RUNS	MEAN / D				MEAN / HISTOGRAMS	
		N	E	S	M			3.0	2.0	1.0	0.5		
R278T01	Φ1T3S1	A	0	0	0.9	0	-0.52	3					2016 2017 2018
	02						-1.0	3					2021 2020 2019
	03						-1.5	4					2036 2037 2040 2041
	04						-0.52	3					2074 2075 2073
	05						-1.0	3					2085 2086 2089
	06						-1.5	3					2049 2050 2051
	07						0	0	-0.52	2			2015 2014
	08						0	0	-1.0	2			2022 2023
	09						-2.0	-0.52	2				2010 2011
	10						0	0	-1.0	2			2025 2024
	11						2	0	-0.52	2			2077 2078
	12						0	0	-1.0	2			2082 2081
	13						0	1.2	0	-0.52	3		2075 2076 2072
	14						0	0	-1.0	5			2095 2084 2087 2088 2094
	15						0	0	-1.5	5			2044 2045 2046 2047 2048
	16						2	0	-0.52	3			2023 2002 2001
	17						2	0	-1.0	5			2033 2026 2017 2028 2034
	18						2	0	-1.5	5			2043 2035 2038 2039 2042

COEFFICIENTS:
 17 α or β
 SCHEDULES:
 $\alpha A = -0.15 \pm 3 (\Delta\alpha = 2^\circ)$

→ IDPVAR(1) IDPVAR(2) NDV

DELYX/D₁
 7576

TEST TWENTY-SIX DATA SET COLLATION SHEET

TABLE III. - Continued

POSTTEST

TEST TEST-552 DATA SET COLLATION SHEET

TABLE III. - Concluded

□ QUEST

בְּרַאשׁ תִּשְׁנָה

REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.

TABLE IV.
NAR ATP BASELINE ORBITER
CONFIGURATION

MODEL COMPONENT: BODY - B1

GENERAL DESCRIPTION: BASIC DELTA WING FUSELAGE PER NAR LINES DRAWING

VL70-000001

MODEL SCALE = .004

DRAWING NUMBER: VL000001

DIMENSIONS:	THEORETICAL		ACTUAL MEASURED	
	FULL-SCALE	MODEL SCALE	MODEL SCALE	MODEL SCALE
Length	1328.33	5.313		
Max. Width	237.96	0.952		
Max. Depth	238.00	0.952		
Fineness Ratio	5.527	5.527		
Area-FT ²				
Max. Cross-Sectional	326.0	.00522		
Planform				
Wetted				
Base				

REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.

TABLE IV. - Continued
NAR ATP BASELINE ORBITER
CONFIGURATION

MODEL COMPONENT: BODY - CANOPY C1

GENERAL DESCRIPTION: CANOPY USED WITH BASIC DELTA WING FUSELAGE PER
NAR LINES DWG VL70-000001

MODEL SCALE = 0.004

DRAWING NUMBER: VL70-000001

<u>DIMENSIONS:</u>	<u>THEORETICAL</u>		<u>ACTUAL MEASURED</u>
	<u>FULL-SCALE</u>	<u>MODEL SCALE</u>	<u>MODEL SCALE</u>
STA FWD BULKHEAD, IN	<u>340.00</u>	<u>1.3600</u>	
STA. TRAILING EDGE, IN	<u>560.00</u>	<u>2.240</u>	
Max. Depth			
Fineness Ratio			
Area			
Max. Cross-Sectional			
Planform			
Wetted			
Base			

REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.

TABLE IV. - Continued
NAR ATP BASELINE ORBITER
CONFIGURATION

MODEL COMPONENT: BODY - MANIPULATOR HOUSING - D1

GENERAL DESCRIPTION: _____

SCALE MODEL = 0.004

DRAWING NUMBER: VL70-000001

DIMENSIONS:	THEORETICAL		ACTUAL MEASURED	
	FULL-SCALE	MODEL SCALE	MODEL SCALE	
Length, IN	967.0	3.8680		
Max. Width, IN	53.32	0.2132		
Max. Depth, IN	20.00	0.080		
Fineness Ratio				
Area				
Max. Cross-Sectional				
Planform				
Wetted				
Base				

TABLE IV. - Continued

MODEL COMPONENT: BODY - FLAP F1

GENERAL DESCRIPTION: FLAP LOCATED ON LOWER AFT PORTION OF BODY AND EXTENDING
AFT OF BODY TRAILING EDGE

SCALE MODEL = 0.004

DRAWING NUMBER:

DIMENSIONS:	<u>THEORETICAL</u>		<u>ACTUAL MEASURED</u>
	<u>FULL-SCALE</u>	<u>MODEL SCALE</u>	<u>MODEL SCALE</u>
Length	<u>83.33</u>	<u>0.333</u>	
Fus. Sta. LE IN.	<u>1528.33</u>	<u>5.113</u>	
Fus. Sta. T.E. In.	<u>1611.67</u>	<u>6.447</u>	
Width (span) In.	<u>229.33</u>	<u>0.917</u>	
Area Ft. ²			
Max. Cross-Sectional	<u>-</u>	<u>-</u>	
Planform	<u>132.72</u>	<u>0.0021</u>	
Wetted			
Base			

REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.

TABLE IV. - Continued
NAR ATP BASELINE ORBITER
CONFIGURATION

MODEL COMPONENT: BODY - ORBITAL MANEUVERING SYSTEM POD-III

GENERAL DESCRIPTION: _____

MODEL SCALE = 0.004

DRAWING NUMBER: VL - 000001

<u>DIMENSIONS:</u>	<u>THEORETICAL</u>		<u>ACTUAL MEASURED</u>
	<u>FULL-SCALE</u>	<u>MODEL SCALE</u>	<u>MODEL SCALE</u>
Length ~IN	<u>290.67</u>	<u>1.1626</u>	_____
Max. Width ~IN	<u>67.33</u>	<u>0.2693</u>	_____
Max. Depth ~IN	<u>104.00</u>	<u>0.416</u>	_____
Fineness Ratio	—	—	_____
Area			
Max. Cross-Sectional	—	—	_____
Planform	—	—	_____
Wetted	—	—	_____
Base	—	—	_____

REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.

TABLE IV. - Continued
NAR ATP BASELINE ORBITER
CONFIGURATION

MODEL COMPONENT: WING - VI

GENERAL DESCRIPTION: DELTA WING WITH -5° TWIST AND ROUNDED WING TIPS. WING
BLENDS INTO BODY. FOLLOWS NAR LINES. V70-000001. EQUIV SPAN IS 78.60% OF
THEORETICAL DELTA WING. MODEL SCALE = 0.004

DRAWING NUMBER: V170-000001

DIMENSIONS:	THEORETICAL		ACTUAL MEASURED
	FULL-SCALE	MODEL SCALE	MODEL SCALE
<u>TOTAL DATA</u>			
Area			
Planform	<u>3221.92</u>	<u>.05155</u>	
Wetted			
Span (equivalent)	<u>1007.8</u>	<u>4.0312</u>	
Aspect Ratio	<u>2.144</u>	<u>2.144</u>	
Rate of Taper	<u>1.191</u>	<u>1.191</u>	
Taper Ratio	<u>0.219</u>	<u>0.219</u>	
Dihedral Angle, degrees	<u>3.500</u>	<u>3.500</u>	
Incidence Angle, degrees	<u>3.000</u>	<u>3.000</u>	
Aerodynamic Twist, degrees	<u>-5.000</u>	<u>-5.000</u>	
Toe-In Angle	<u>3.000</u>	<u>3.000</u>	
Cant Angle	<u>-2.000</u>	<u>-2.000</u>	
Sweep Back Angles, degrees			
Leading Edge	<u>49.910</u>	<u>49.910</u>	
Trailing Edge	<u>-0.183</u>	<u>-0.183</u>	
0.25 Element Line	<u>41.675</u>	<u>41.675</u>	
Chords:			
Root (Wing Sta. 0.0)	<u>760.56</u>	<u>3.0422</u>	
Tip, (equivalent)	<u>159.72</u>	<u>0.6388</u>	
MAC	<u>525.4</u>	<u>2.0976</u>	
Fus. Sta. of .25 MAC	<u>1132.98</u>	<u>4.5319</u>	
W.P. of .25 MAC	<u>304.55</u>	<u>1.2182</u>	
B.L. of .25 MAC	<u>196.09</u>	<u>7843</u>	
Airfoil Section			
Root			
Tip			
<u>EXPOSED DATA</u>			
Area	<u>2203.00</u>	<u>0.03524</u>	
Span, (equivalent)	<u>795.86</u>	<u>3.1834</u>	
Aspect Ratio	<u>1.966</u>	<u>1.966</u>	
Taper Ratio	<u>0.260</u>	<u>0.260</u>	
Chords			
Root	<u>641.57</u>	<u>2.5662</u>	
Tip	<u>166.68</u>	<u>.6667</u>	
MAC	<u>450.63</u>	<u>1.8025</u>	
Fus. Sta. of .25 MAC	<u>1190.82</u>	<u>4.7633</u>	
W.P. of .25 MAC	<u>305.47</u>	<u>1.2219</u>	
B.L. of .25 MAC	<u>260.80</u>	<u>1.0432</u>	
Leading Edge Cuff			
Planform Area (in W.R.P.) Ft. ²		<u>271.39</u>	<u>0043</u>
Leading edge intersects fuselage ML - @ sta. In.		<u>540.00</u>	<u>2.1600</u>

REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.

TABLE IV. - Continued
NAR ATP BASELINE ORBITER
CONFIGURATION

MODEL COMPONENT: ELEVON - EL (DATA FOR 1 of 2 SIDES)

GENERAL DESCRIPTION: FULL SPAN, CONSTANT CHORD ELEVON LOCATED ON
WING WI.

MODEL SCALE = 0.004

DRAWING NUMBER: VL70.000001

<u>DIMENSIONS:</u>	<u>THEORETICAL</u>		<u>ACTUAL MEASURED</u>
	<u>FULL-SCALE</u>	<u>MODEL SCALE</u>	<u>MODEL SCALE</u>
Area (TRUE), FT ²	<u>347.2</u>	<u>.00555</u>	
Span (equivalent)	<u>384.0</u>	<u>1.536</u>	
Inb'd equivalent chord	<u>134.38</u>	<u>.537</u>	
Outb'd equivalent chord	<u>134.38</u>	<u>.537</u>	
Ratio movable surface chord/ total surface chord			
At Inb'd equiv. chord	<u>0.209</u>	<u>0.209</u>	
At Outb'd equiv. chord	<u>0.805</u>	<u>0.805</u>	
Sweep Back Angles, degrees			
Leading Edge	<u>-0.183</u>	<u>-0.183</u>	
Trailing Edge	<u>-0.183</u>	<u>-0.183</u>	
Hingeline	<u>-0.183</u>	<u>-0.183</u>	
Area Moment	<u>4164.40</u>	<u>0.00026</u>	
(Normal to hinge line) (PRODUCT OF AREA & MEAN CHORD)			

REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.

TABLE IV - Continued
NAR ATP BASELINE ORBITER
CONFIGURATION

MODEL COMPONENT: VERTICAL TAIL - VI

GENERAL DESCRIPTION: CENTERLINE VERTICAL ON DELTA WING CONFIGURATION WITH DOUBLE WEDGE AIRFOIL AND ROUNDED LEADING EDGE. TOTAL DATA INCLUDES VOID AREA LISTED BELOW. SCALE MODEL = 0.004

DRAWING NUMBER: VL70-00000

DIMENSIONS:

<u>TOTAL DATA</u>	<u>THEORETICAL</u>		<u>ACTUAL MEASURED</u>
	<u>FULL-SCALE</u>	<u>MODEL SCALE</u>	<u>MODEL SCALE</u>
Area	415.25	.00664	
Planform	1.29	.00002	
Wetted	19.93	.00032	
Span (equivalent)	32.35	1.2956	
Aspect Ratio	1.675	1.675	
Rate of Taper	0.504	0.504	
Taper Ratio	0.424	0.424	
Dihedral Angle, degrees	-	-	
Incidence Angle, degrees	-	-	
Aerodynamic Twist, degrees	-	-	
Toe-In Angle	0.0	0.0	
Cant Angle	0.0	0.0	
Sweep Back Angles, degrees			
Leading Edge	45.000	45.000	
Trailing Edge	26.361	26.361	
0.25 Element Line	41.150	41.150	
Chords:			
Root (Wing Sta. 0.0)	275.52	1.1021	
Tip, (equivalent)	111.4	0.448	
MAC	205.0	0.820	
Fus. Sta. of .25 MAC	1462.2	5.849	
W.P. of .25 MAC	639.0	2.556	
B.L. of .25 MAC	0.0	0.0	
Airfoil Section 5° HALF ANGLE			
Root DOUBLE WEDGE WITH			
Tip ROUNDED L.E. =			

EXPOSED DATA

Area			
Span, (equivalent)			
Aspect Ratio			
Taper Ratio			
Chords			
Root			
Tip			
MAC			
Fus. Sta. of .25 MAC			
W.P. of .25 MAC			
B.L. of .25 MAC			

*Void area located at the lower, aft portion of the surface

TABLE IV. - Continued

MODEL COMPONENT: BODY - COOLANT INLET K1

GENERAL DESCRIPTION: COOLANT INLET PER LINES VL70-000012 AIR COOLANT DUCT
MOLDED INTO 60% ELEMENT LINE OF VERTICAL TAIL.

SCALE MODEL .004

DRAWING NUMBER: VL70-000012

<u>DIMENSIONS:</u>	<u>THEORETICAL</u>		<u>ACTUAL MEASURED</u>
	<u>FULL-SCALE</u>	<u>MODEL SCALE</u>	<u>MODEL SCALE</u>
Length	<u>143.00</u>	<u>0.572</u>	_____
Max. Width	_____	_____	_____
Max. (DIA)	<u>38.00</u>	_____	_____
Fineness Ratio	_____	_____	_____
Area	_____	_____	_____
Max. Cross-Sectional	_____	_____	_____
Planform	_____	_____	_____
Wetted	_____	_____	_____
Base	_____	_____	_____
FS 1307.0 IN. FS	_____	_____	_____
BP = 0.00 IN. FS	_____	_____	_____
WP = 539.00 IN. FS	_____	_____	_____

REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.

TABLE IV. - Continued
NAR ATF BASELINE ORBITER
CONFIGURATION

MODEL COMPONENT: Rudder - VI

GENERAL DESCRIPTION: Rudder on centerline vertical tail, VI

MODEL SCALE = 0.004

DRAWING NUMBER: VL70-000001

<u>DIMENSIONS:</u>	<u>THEORETICAL</u>	<u>ACTUAL MEASURED</u>
	<u>FULL-SCALE</u>	<u>MODEL SCALE</u>
Area ~FT ²	<u>117.7</u>	<u>.00108</u>
Span (equivalent) ~in	<u>226.0</u>	<u>0.9040</u>
Inb'd equivalent chord ~in	<u>97.09</u>	<u>.3884</u>
Outb'd equivalent chord ~in	<u>52.02</u>	<u>.2081</u>
Ratio movable surface chord/ total surface chord		
At Inb'd equiv. chord	<u>0.400</u>	<u>0.400</u>
At Outb'd equiv. chord	<u>0.400</u>	<u>0.400</u>
Sweep Back Angles, degrees		
Leading Edge	<u>34.889</u>	<u>34.889</u>
Tailng Edge	<u>26.361</u>	<u>26.361</u>
Hingeline	<u>34.889</u>	<u>34.889</u>
Area Moment	<u>647.77</u>	<u>00004</u>
(Normal to hinge line) (PRODUCT OF AREA AND MEAN CHORD)		

REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.

TABLE IV. - Continued
NAR ATP BASELINE INTERGRATED LAUNCH
CONFIGURATION

MODEL COMPONENT: BODY - T₃

GENERAL DESCRIPTION: EXTERNAL TANK (BASELINE DIA.) WITH OGIVE NOSE CONE
AND RETRO ROCKET

DRAWING NUMBER: MSFC 80M 32569 (NOSE) & 80M 42575 (body)

<u>DIMENSIONS:</u>	<u>THEORETICAL</u>		<u>ACTUAL MEASURED</u>
	<u>FULL-SCALE</u>	<u>MODEL SCALE</u>	<u>MODEL SCALE</u>
Length	<u>2467.8 in.</u>	<u>9.871 in.</u>	—
Max. Width	<u>318 in.</u>	<u>1.272 in.</u>	—
Max. Depth	<u>318 in.</u>	<u>1.272 in.</u>	—
Fineness Ratio	<u>7.76</u>	<u>7.76</u>	—
Area			
Max. Cross-Sectional	<u>551.54 ft.²</u>	<u>1.271 in.²</u>	—
Planform	—	—	—
Wetted	—	—	—
Base	<u>551.54 ft.²</u>	<u>1.271 in.²</u>	—

REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.

TABLE IV. - Concluded

NAR ATP BASELINE INTERGRATED LAUNCH
CONFIGURATION

MODEL COMPONENT: BODY - S,

GENERAL DESCRIPTION: SOLID ROCKET BOOSTER (BASELINE DIA) WITH HOLD DOWN ARMS

DRAWING NUMBER: MSFC 80M32563-68 & 42574

DIMENSIONS:	THEORETICAL		ACTUAL MEASURED	
	FULL-SCALE	MODEL SCALE	MODEL SCALE	
Length	2217 in.	8.868 in.	—	—
Max. Width	156 in.	0.624 in.	—	—
Max. Depth	156 in.	0.624 in.	—	—
Fineness Ratio	14.21	14.21	—	—
Area				
Max. Cross-Sectional	132.5 ft ²	0.306 in. ²	—	—
Planform	—	—	—	—
Wetted	—	—	—	—
Base	132.5 ft. ²	0.306 in. ²	—	—

MODEL FIGURES




Figure 1. - Axis systems.




Figure 2.- ATP Arbiter (01).




Figure 3.—Modified ATP ET (T3) and ATP SRB.




Figure 4. - Layout of test grid and sign convention.




FIGURE 5.—Space Shuttle Parallel Staging System for the MSFC 14 x 14-Inch Trisonic Wind Tunnel.

REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.





Figure 6. - Typical installation photograph.

DATA FIGURES


REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.



EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LONGITUDINAL STABILITY PAGE


(A) DEL X/B = -.50

REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.



EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LONGITUDINAL STABILITY
 $(\text{CDE}_x/\text{C}) = .00$





REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.



EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LONGITUDINAL STABILITY
 $(C_{\text{DE}} - X_{\text{C}}) = .50$

REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.

DATA SET SYMBOL		CONFIGURATION DESCRIPTION		REFERENCE INFORMATION	
MSPC	558 (MASPI)	NR ATP (O1) / (T3) (S1)		SREF	.3220, .0000 INCHES
(CP602)	X	NR ATP (T3) (S1) / (O1)		LREF	.1326, .0000 INCHES
(CP608)	O	NR ATP (MASPI) (T3) (S1) / (O1)		BREF	.1326, .0000 INCHES
(CP609)	+	NR ATP (O1) / (T3) (S1)		XMRP	.0000, .0000 INCHES
(CP6105)	△	NR ATP (T3) (S1) / (O1)		ZMRP	.0000, .0000 INCHES




EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB. LONGITUDINAL STABILITY
ANGLE X/D = -.50

PAGE 4


REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.

DATA SET SYMBOL CONFIGURATION DESCRIPTION
 MSPC 556 (MA9F) NR ATP (O1) / (T3) (S1)
 MSPC 556 (MA9F) NR ATP (T3) (S1) / (O1)
 MSPC 556 (MA9F) NR ATP (O1) / (T3) (S1)
 MSPC 556 (MA9F) NR ATP (T3) (S1) / (O1)
 MSPC 556 (MA9F) NR ATP (T3) (S1) / (O1)


CRABING MACH ELEVON DELZ/D REFERENCE INFORMATION
 .000 .900 .000 SREF 32.0000 SO. FT.
 .000 .900 .000 LREF. 13.26.0000 INCHES
 2.000 .900 .000 SREF 13.26.0000 INCHES
 2.000 .900 .000 YMRP .0000 INCHES
 ZMRP -.51.5000 PER SCALE 100.0000 INCHES
 SCALE




C_{xCL}



C_{zCL}







C_{xM}



EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LONGITUDINAL STABILITY
 $(C_{xCL} - X/2) = .03$ PAGE 5


REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.

REFERENCE INFORMATION						
DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ORBINC	MACH	ELEVON	DELZ/D	SQ. PT.
(CP6002)	MSPC 558 (MA8P) MR ATP (O1) / (T3) (S1)	.000	.900	.000	-1.000	LREF .3220.0000 INCHES
(CP6002)	MSPC 558 (MA8P) MR ATP (T3) (S1) / (O1)	.000	.900	.000	-1.000	BREF .3226.0000 INCHES
(CP6003)	MSPC 558 (MA8P) MR ATP (O1) / (T3) (S1)	.000	.900	.000	-1.000	XMRP .3226.0000 INCHES
(CP6003)	MSPC 558 (MA8P) MR ATP (T3) (S1) / (O1)	.000	.900	.000	-1.000	ZMRP .0000 .0000 INCHES



EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB. LONGITUDINAL STABILITY PAGE 53

REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.



EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LONGITUDINAL STABILITY
 $C_A \Delta E / D = -1.30$

PAGE 7





REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.

REFERENCE INFORMATION

ORBIT INC	MACH	ELEVON	DELZ/D	SREF	3200.0000
.000	.000	.000	-1.500	LREF	1320.0000
.000	.000	.000	-1.500	BREF	1320.0000
2.000	.000	.000	-1.500	XHLP	.0000
2.000	.000	.000	-1.500	ZHLP	.0000
2.000	.000	.000	-1.500	2MHP	.0000
2.000	.000	.000	-1.500	100.0000	INCHES PER SCALE

DATA SET SYMBOL **CONFIGURATION DESCRIPTION**


DATA SET SYMBOL	ORBIT INC	MACH	ELEVON	DELZ/D	SREF	3200.0000
(C7E003)	MSPC 330 (MASP)	NR ATP	(O1) / (T3) (S1)	.000	.000	1320.0000
(C7E003)	MSPC 330 (MASP)	NR ATP	(T3) (S1) / (O1)	.000	.000	1320.0000
(C7E003)	MSPC 330 (MASP)	NR ATP	(O1) / (T3) (S1)	.000	.000	1320.0000
(C7E003)	MSPC 330 (MASP)	NR ATP	(T3) (S1) / (O1)	.000	.000	1320.0000
(C7E003)	MSPC 330 (MASP)	NR ATP	(O1) / (T3) (S1)	.000	.000	1320.0000
(C7E003)	MSPC 330 (MASP)	NR ATP	(T3) (S1) / (O1)	.000	.000	1320.0000



EFFECT OF INCIDENCE ANGLE ON CRBITER AND TANK / SRB, LONGITUDINAL STABILITY

(3:2E-X/C = -.50)



REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.



EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LONGITUDINAL STABILITY
 CODE - X / O = .30
 PAGE 9

REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.




DATA SET SYMBOL CONFIGURATION DESCRIPTION
 ORB INC MACH ELEVON DELZ/D REFERENCE INFORMATION
 NSPC 256 (MAPT) NR ATP (011)/(173) (S1)
 (CPV03) (MAPT) NR ATP (173) (S11)/(011)
 (CPV03) (MAPT) NR ATP (011)/(173) (S11)
 (CPV03) (MAPT) NR ATP (011)/(173) (S11)
 (CPV03) (MAPT) NR ATP (173) (S11)/(011)
 (CPV03) (MAPT) NR ATP (173) (S11)



EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LONGITUDINAL STABILITY
 CODE-X/D = .50
 PAGE 10

REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.


DATA SET SYMBOL **CONFIGURATION DESCRIPTION**
 (C78013) MSFC 558 (MAF) NR ATP (O1) / (T3) (S1)
 (C78013) MSFC 558 (MAF) NR ATP (T3) (S1) / (O1)
 (C78013) MSFC 558 (MAF) NR ATP (O1) / (T3) (S1)
 (C78016) MSFC 558 (MAF) NR ATP (T3) (S1) / (O1)
 (C78016) MSFC 558 (MAF) NR ATP (T3) (S1) / (O1)



EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LONGITUDINAL STABILITY
 (A25E-X/3= -.52) PAGE 11

REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.

DATA SET SYMBOL	CONFIGURATION DESCRIPTION
(CP-013)	MARC 550 (MAP) MR ATP (O1) / (T3) (S1)
(CP-013)	MARC 550 (MAP) MR ATP (T3) (S1) / (O1)
(CP-013)	MARC 550 (MAP) MR ATP (O1) / (T3) (S1)
(CP-013)	MARC 550 (MAP) MR ATP (T3) (S1) / (O1)
(CP-013)	MARC 550 (MAP) MR ATP (T3) (S1) / (O1)






EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LONGITUDINAL STABILITY
 (3220-X/2) .32
 PAGE :2

REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.

DATA SET SYMBOLS CONFIGURATION DESCRIPTION
 DATA SET SYMBOLS CONFIGURATION DESCRIPTION
 CTPG13 MSFC 550 (MA9F) NR ATP (C11)/(T3) (S1)
 CTPG13 MSFC 550 (MA9F) NR ATP (T3) (S1)/(O1)
 CTPG13 MSFC 550 (MA9F) NR ATP (O1) / (T3) (S1)
 CTPG16 MSFC 550 (MA9F) NR ATP (T3) (S1) / (O1)
 CTPG16 MSFC 550 (MA9F) NR ATP (T3) (S1) / (O1)

CHG INC MACH ELEVON DELZ/D REFERENCE INFORMATION
 .000 1.200 .000 .3220, 0.000 SQ. FT.
 .000 1.200 .000 1.528, 0.000 INCHES
 .000 1.200 .000 1.528, 0.000 INCHES
 .000 1.200 .000 .0000 INCHES
 .000 1.200 .000 .0000 INCHES PER




EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB. LONGITUDINAL STABILITY
 COEFF. X/2 = .50
 PAGE :3


REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.

DATA SET SYMBOL	CONFIGURATION DESCRIPTION	REFERENCE INFORMATION					
		ORIGIN	MACH	ELEVON	DELZ/D	SREF	SRFP
(CP8014)	MSPC 538 (MSPF) NR ATP (O1) / (T3) (S1)	.000	1.200	.000	-1.000	3820.0000	50. FT.
(CP8114)	MSPC 538 (MSPF) NR ATP (T3) (S1) / (O1)	.000	1.200	.000	-1.000	1322.0000	INCHES
(CP8017)	MSPC 538 (MSPF) NR ATP (O1) / (T3) (S1)	.000	1.200	.000	-1.000	1322.0000	INCHES
(CP8117)	MSPC 538 (MSPF) NR ATP (T3) (S1) / (O1)	.000	1.200	.000	-1.000	0.0000	INCHES

Z
SCALE 100.0000 INCHES PER



Z



CLM

EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB. LONGITUDINAL STABILITY
(A) DEL_X/D = -1.00





PAGE 14

DATA SET SYMBOL CONFIGURATION DESCRIPTION

(C78014)	MSPC 556 (MASF) NR ATP (O1) / (T3) (S1)
(C78T14)	MSPC 556 (MASF) NR ATP (T3) (S1) / (O1)
(C78017)	MSPC 556 (MASF) NR ATP (O1) / (T3) (S1)
(C78T17)	MSPC 556 (MASF) NR ATP (T3) (S1) / (O1)

REFERENCE INFORMATION


ORBINC	MACH	ELEVON	CELZ/D	SQ.FT.
.000	1.200	.000	-1.000	SREF 3220.0000
.000	1.200	.000	-1.000	LREF 1320.0000
.200	1.200	.000	-1.000	BREF 1320.0000
.200	1.200	.000	-1.000	XMRP .0000
.200	1.200	.000	-1.000	YMRP .0000
SCALE	100.0000 INCHES PER	ZMRP -.81.5000		



EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LONGITUDINAL STABILITY
 $(\text{C}_z, \text{C}_{PL}, \text{C}_{LM}, \text{C}_{LF}) = -.50$

DATA SET SYMBOL CONFIGURATION DESCRIPTION

(C78014)	MSPC 556 (MA9F) NR ATP (O1) / (T3) (S1)
(C78014)	MSPC 556 (MA9F) NR ATP (T3) (S1) / (O1)
(C78014)	MSPC 556 (MA9F) NR ATP (O1) / (T3) (S1)
(C78017)	MSPC 556 (MA9F) NR ATP (T3) (S1) / (O1)
(C78017)	MSPC 556 (MA9F) NR ATP (T3) (S1) / (O1)




EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LONGITUDINAL STABILITY
CODE-X/C= .00

EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LONGITUDINAL STABILITY
PAGE 16

DATA SET SYMBOL CONFIGURATION DESCRIPTION

(C)PBO14	MSFC 558 (MA9F) NR ATP (O1) / (T3) (S1)
(CPBT14)	MSFC 556 (MA9F) NR ATP (T3) (S1) / (O1)
(CPGT14)	MSFC 556 (MA9F) NR ATP (O1) / (T3) (S1)
(CTAG17)	MSFC 516 (MA9F) NR ATP (T3) (S1) / (O1)
(CTBT17)	MSFC 516 (MA9F) NR ATP (O1) / (T3) (S1)





EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LONGITUDINAL STABILITY
CODE-X/C= .50

PAGE 17

DATA SET SYMBOL CONFIGURATION DESCRIPTION

ORBINC	MACH	ELEVON	DELZ/D	REFERENCE INFORMATION
.000	1.200	.000	-1.000	SREF 3220.0000 SQ. FT.
.000	1.200	.000	-1.000	LREF 1320.0000 INCHES
.000	1.200	.000	-1.000	BREF 1320.0000 INCHES
2.000	1.200	.000	-1.000	XMRP .0000 INCHES
2.000	1.200	.000	-1.000	ZMRP -61.5000 INCHES PER

SCALE 100.0000 INCHES




EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LONGITUDINAL STABILITY
 $(EDELX/D = 1.00)$


PAGE 18

DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (C78013) MSFC 558 (MAFP) NR ATP (O1) / (T3) (S1)
 (C78013) MSFC 559 (MAFP) NR ATP (T3) (S1) / (O1)
 (C78013) MSFC 55A (MAFP) NR ATP (O1) / (T3) (S1)
 (C78013) MSFC 55B (MAFP) NR ATP (T3) (S1) / (O1)


ORBIT INC MACH ELEVON DEL Z/O REFERENCE INFORMATION
 .000 1.200 .000 -1.500 3220.0000
 .000 1.200 .000 -1.500 LREF 1328.0000
 2.000 1.200 .000 -1.500 BREF 1328.0000
 2.000 1.200 .000 -1.500 XMRP .0000
 2.000 1.200 .000 -1.500 YMRP .0000
 2.000 1.200 .000 -1.500 ZMRP -61.5000
 SCALE 100.0000 INCHES PER



C_2



C_{LM}







C_{AF}

EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LONGITUDINAL STABILITY
 $(\Delta \text{ZEL} / \Delta = -1.00)$

DATA SET SYMBOL CONFIGURATION DESCRIPTION

(CP0101)	MSFC 558 (MASP)	NR ATP (O1) / (T3) (S1)
(CP0112)	MSFC 558 (MASP)	NR ATP (T3) (S1) / (O1)
(CP0116)	MSFC 558 (MASP)	NR ATP (O1) / (T3) (S1)
(CP0118)	MSFC 558 (MASP)	NR ATP (T3) (S1) / (O1)

REFERENCE INFORMATION
SQ. FT.
SREF 3220,0000
LREF 1320,0000
BREF 1320,0000
XMRP .0000
YMRP .0000
ZMRP -61,5000
PER 100,0000







EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LONGITUDINAL STABILITY
 $C_{xpl}/L = -.50$

DATA SET SYMBOL CONFIGURATION DESCRIPTION





(CP8015)	NSPC 558 (MA9F) NR ATP (O1)/(T3) (S1)
(CP8115)	NSPC 558 (MA9F) NR ATP (T3)(S1)/(O1)
(CP8016)	NSPC 558 (MA9F) NR ATP (O1)/(T3) (S1)
(CP8017)	NSPC 558 (MA9F) NR ATP (T3)(S1)/(O1)

REFERENCE INFORMATION
 ORB:INC MACH ELEVON DELZ/D SQ.FT.
 .000 1.200 .000 -1.500 SREF 3220.0000
 .000 1.200 .000 -1.500 LREF 1326.0000
 .000 1.200 .000 -1.500 BREF 1326.0000
 2.000 1.200 .000 -1.500 XMRP .0000
 2.000 1.200 .000 -1.500 YMRP -61.5000
 ZMRP 100.0000 INCHES PER
 SCALE



EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LONGITUDINAL STABILITY
 CODE-X/C = .00

DATA SET BY NUMBER CONFIGURATION DESCRIPTION
 (CPAT015) MSPC 938 (MA9F) NR ATP (O1)/(T3) (S1)
 (CPAT015) MSPC 938 (MA9F) NR ATP (T3) (S1) / (O1)
 (CPAT15) MSPC 938 (MA9F) NR ATP (O1)/(T3) (S1)
 (CPAT16) MSPC 938 (MA9F) NR ATP (T3) (S1) / (O1)
 (CPAT18) MSPC 938 (MA9F) NR ATP (T3) (S1) / (O1)



CAB

EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LONGITUDINAL STABILITY
CODE - X/2 = .50




PAGE 22

DATA SET SYMBOLS CONFIGURATION DESCRIPTION

(CPAO13)	MSFC 558 (MAST) NR ATP (O1) / (T3) (S1)
(CPAO15)	MSFC 558 (MAST) NR ATP (O1) / (T3) (S1)
(CPAO16)	MSFC 558 (MAST) NR ATP (O1) / (T3) (S1)
(CPAO17)	MSFC 558 (MAST) NR ATP (O1) / (T3) (S1)
(CPAO18)	MSFC 558 (MAST) NR ATP (O1) / (T3) (S1)

REFERENCE INFORMATION

ORBINC	MACH	ELEVON	DELZ/D	SREF	3220.0000	.59.FT.
.000	1.200	.000	-1.500	LREF	1326.0000	INCHES
.000	1.200	.000	-1.500	BREF	1326.0000	INCHES
2.000	1.200	.000	-1.500	XMRP	.0000	INCHES
2.000	1.200	.000	-1.500	YMRP	.0000	INCHES
				ZMRP	.001 .5000	PER
		SCALE				




EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LONGITUDINAL STABILITY
 $C_{E25} \cdot X/C = .0033$

DATA SET SYMBOL CONFIGURATION DESCRIPTION


(CPAC25)	NSPC 558 (MASP) NR ATP (O1) / (T3) / (S1)
(CPAT25)	NSPC 558 (MASP) NR ATP (T3) (S1) / (O1)
(CPAC26)	NSPC 558 (MASP) NR ATP (O1) / (T3) (C1)
(CPAT26)	NSPC 558 (MASP) NR ATP (T3) (S1) / (O1)

REFERENCE INFORMATION


ORBINC	MACH	ELEVON	DELZ/D	SREF	.520	SQ.FT.
.000	2.000	.000	.000	LREF	13220.0000	INCHES
.000	2.000	.000	.000	BREF	13220.0000	INCHES
2.000	2.000	.000	.000	XMRP	.0000	INCHES
2.000	2.000	.000	.000	ZMRP	-61.0000	INCHES
SCALE	100.0000	PER				




C_{xCL}




C_{LM}



C_{xCP/L}




EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LONGITUDINAL STABILITY
 $(\Delta \alpha = \pm 1^\circ, \alpha_0 = 0^\circ)$



EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LONGITUDINAL STABILITY
 $C_{DE} \cdot X/2 = .30$

DATA SET SYMBOL CONFIGURATION DESCRIPTION





CYR(23)	NSFC 330 (MAF) NM ATP (O11)/(T3) (S1)
CP(123)	NSFC 330 (MAF) NM ATP (T3) (S1)/(C1)
CP(123)	NSFC 330 (MAF) NM ATP (O11)/(T3) (S1)
CP(123)	NSFC 330 (MAF) NM ATP (T3) (S1)/(O1)
CP(123)	NSFC 330 (MAF) NM ATP (T3) (S11)



EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LONGITUDINAL STABILITY
COS(2X/2) = .35
PAGE 26

DATA SET SYMBOL CONFIGURATION DESCRIPTION
 NSPC 550 (MA5P) NR ATP (O1) / (T3) (S1)
 NSPC 550 (MA5P) NP ATP (T3) (S1) / (O1)
 NSPC 550 (MA5P) NP ATP (O1) / (T3) (S1)
 NSPC 550 (MA5P) ATP (T3) (S1) / (O1)

REFERENCE INFORMATION
 ORBINC MACH ELEVON DEL Z/D
 .000 2.000 .000 -.520 SREF 3820.0000 50 FT.
 .000 2.000 .000 -.520 LREF 1326.0000 INCHES
 .000 2.000 .000 -.520 BREF 1326.0000 INCHES
 .000 2.000 .000 -.520 XMRP .0000 INCHES
 .000 2.000 .000 -.520 ZMRP -.61.3000 INCHES
 SCALE 100.0000 INCHES PER



CONF-X/2 = 2.00

EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LONGITUDINAL STABILITY





PAGE 27

DATA SET SYMBOL CONFIGURATION DESCRIPTION

(C7AC25)	MSFC 556 (MA9F) NR ATP (O1) / (T3) (S1)
(C7AT23)	MSFC 556 (MA9F) NR ATP (T3) (S1) / (O1)
(C7AC26)	MSFC 556 (MA9F) NR ATP (O1) / (T3) (S1)
(C7AT23)	MSFC 556 (MA9F) NR ATP (T3) (S1) / (O1)

REFERENCE INFORMATION

ORBITIC	MACH	ELEVON	DELZ/D	SREF	3220.0000	SQ. FT.
.000	.000	.000	-.520	LREF	1328.0000	INCHES
.000	.000	.000	-.520	BREF	1326.0000	INCHES
2.000	2.000	.000	-.520	XMRP	.0000	INCHES
2.000	2.000	.000	-.520	YMRP	.0000	INCHES
2.000	2.000	.000	-.520	ZMRP	.61.5000	INCHES
				SCALE	100.0000	FEET







EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LONGITUDINAL STABILITY
 $\text{CE} \cdot \text{DELX}/\text{C} = 3.00$

DATA SET SYMBOL CONFIGURATION DESCRIPTION


(CP9026)	MSFC 556 (MA9F) NR ATP (O1)/(T3)(S1)
(CP9026)	MSFC 556 (MA9F) NR ATP (T3)(S1)/(O1)
(CP9026)	MSFC 556 (MA9F) NR ATP (O1)/(T3)(S1)
(CP9029)	MSFC 559 (MA9F) NR ATP (O1)/(T3)(S1)
(CP9029)	MSFC 559 (MA9F) NR ATP (T3)(S1)/(O1)

REFERENCE INFORMATION

ORBINC	MACH	ELEVON	DELZ/D	SREF	3220.0000	SQ.FT.
.000	.000	.000	-1.000	LREF	1326.0000	INCHES
.000	.000	.000	-1.000	BREF	1326.0000	INCHES
2.000	2.000	.000	-1.000	XMRP	.0000	INCHES
2.000	2.000	.000	-1.000	YMRP	.0000	INCHES
2.000	2.000	.000	-1.000	ZMRP	-61.3000	PER
SCALE 100.0000 INCHES						



EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LONGITUDINAL STABILITY
 $(\text{ANGLE-X/C} = -1.00)$



EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB. LONGITUDINAL STABILITY
 $C_{ZOE} - X/D = .30$


PAGE 30

DATA SET SYMBOL CONFIGURATION DESCRIPTION


(C79128)	MSPC 55A (MA91) NR ATP (O1) / (T5) (S1)
(C79128)	MSPC 55 (MA9F) NR ATP (O1) / (S1)
(C79128)	MSPC 55B (MA9F) NR ATP (O1) / (T5) (S1)
(C79129)	MSPC 55A (MA9P) NR ATP (T5) (S1) / (O1)
(C79129)	MSPC 55B (MA9P) NR ATP (S1) / (O1)

REFERENCE INFORMATION


ORBINC	MACH	ELEVON	DELZ/D	SQ. FT.
.000	2.000	.000	-1.000	5220.0000
.000	2.000	.000	-1.000	1328.0000
.000	2.000	.000	-1.000	1328.0000
.000	2.000	.000	-1.000	XMRP. .0000
2.000	2.000	.000	-1.000	ZMRP. -61.5000
				SCALE 100.0000 INCHES PER




C_2



CL_M



X_{CP}/L



CA_F




EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LONGITUDINAL STABILITY

CODED X/Z : CC


PAGE 3:

DATA SET SYMBOLS. CONFIGURATION DESCRIPTION
 (CP9026) NSPC 558 (MA9P) NR ATP (O1)/(T3) (S1)
 (CP9026) NSPC 558 (MA9P) NR ATP (T3) (S1)/(O1)
 (CP9026) NSPC 558 (MA9P) NR ATP (O1) / (T3) (S1)
 (CP9026) NSPC 558 (MA9P) NR ATP (T3) (S1) / (O1)

REFERENCE INFORMATION
 ORB INC MACH ELEVON DEL Z/O SREF 5220.0000 SQ.FT.
 .000 .000 .000 1.000 LREF 1328.0000 INCHES
 .2000 .000 .000 -1.000 BREF 1328.0000 INCHES
 .2000 .000 .000 -1.000 XMRP .0000
 .2000 .000 .000 -1.000 YMRP .0000
 .2000 .000 .000 -1.000 ZMRP -61.5000 INCHES
 SCALE 100.0000 PER






EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LONGITUDINAL STABILITY
 $\cos\alpha_{SE_X}/2 = 2.00$ PAGE 32



EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LONGITUDINAL STABILITY
 $\text{C}_{\text{IDE-X/2}} = 3.00$

DATA SET SYMBOLS. CONFIGURATION DESCRIPTION
 DATA NOT AVAILABLE (CP0107)
 (CP0127) DATA NOT AVAILABLE (O1)/(T3)(S1)
 (CP0130) MSFC 938 (MASP) NR ATP (Y3)(S1)/(O1)
 (CP0130) MSFC 938 (MASP) NR ATP (Y3)(S1)/(O1)


REFERENCE INFORMATION
 ORB INC MACH ELEVON DEL Z/D SREF 3220.0000 52. FT.
 .000 .000 .000 -1.500 LREF 1320.0000 INCHES
 .000 .000 .000 -1.500 BREF 1320.0000 INCHES
 .000 .000 .000 -1.500 XMRP .000
 .000 .000 .000 -1.500 YMRP .000
 .000 .000 .000 -1.500 ZMRP -61.5000 INCHES
 SCALE 100.0000 PER



EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LONGITUDINAL STABILITY
 $C_{AF} = -0.33$


DATA SET SYMBOL CONFIGURATION DESCRIPTION

(CPA27)	NSPC 558 (MA9F) NR ATP (O1)/(T3) (S1)
(CPA27)	NSPC 558 (MA9F) NR ATP (T3)(S1)/(O1)
(CPA27)	NSPC 558 (MA9F) NR ATP (O1)/(T3) (S1)
(CPA30)	NSPC 558 (MA9F) NR ATP (T3)(S1)/(O1)
(CPA30)	NSPC 558 (MA9F) NR ATP (T3)(S1)/(O1)



EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LONGITUDINAL STABILITY
(3) D₂, X/2 = .33

PAGE 35




EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LONGITUDINAL STABILITY
CODE: X/Z = .00


PAGE 36

DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (CP80CP) MSC 558 (MA9F) NR ATP (O1)/(T3) (S1)
 (CP81CP) MSC 558 (MA9F) NR ATP (T3) (S1)/(O1)
 (CP82CP) MSC 558 (MA9F) NR ATP (O1) / (T3) (S1)
 (CP83CP) MSC 558 (MA9F) NR ATP (T3) (S1)/(O1)
 (CP84CP) MSC 558 (MA9F) NR ATP (O1) / (T3) (S1)


REFERENCE INFORMATION
 ORB INC MACH ELEVON DEL Z/D SREF SQ.FT.
 .000 2.000 .000 -1.500 SREF 3220.0000
 .000 2.000 .000 -1.500 LREF 1326.0000
 2.000 2.000 .000 -1.500 BREF 1326.0000
 2.000 2.000 .000 .000 XMRP .0000
 2.000 2.000 .000 .000 YMRP -.61.5000
 SCALE 100.0000 INCHES PER




Z



XCP/L




CLM



CAF

EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LONGITUDINAL STABILITY
 CODE: X/Z = 2.00

DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (CPTBZP) DATA NOT AVAILABLE
 (CPTATZP) DATA NOT AVAILABLE
 (MSPFC) MSPFC 538 (MAFP)
 (MSPFC) MSPFC 938 (MAFP) NR ATP (T3) (S1) / (O1)
 (CTATZG) CPTATZG







EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LONGITUDINAL STABILITY
 CEDE_X/Z = 3.00

EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LONGITUDINAL STABILITY

PAGE 38

DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (CPA01) MSFC 556 (MASF) NR ATP (O1)/(T3) (S1)
 (CPA02) MSFC 556 (MASF) NR ATP (T3) (S1)/ (O1)
 (CPA03) MSFC 556 (MASF) NR ATP (O1) / (T3) (S1) / (O1)
 (CPA04) MSFC 556 (MASF) NR ATP (T3) (S1) / (O1)
 (CPA05) MSFC 556 (MASF) NR ATP (T3) (S1) / (O1)

REFERENCE INFORMATION
 ORB INC MACH ELEVON DELZ/D SQ. FT.
 .000 .900 10,000 -.520 LREF 3220,0000
 .000 .900 10,000 -.520 BREF 1328,0000
 2,000 .900 10,000 -.520 XMRP .0000
 2,000 .900 10,000 -.520 YMRP .0000
 ZMRP -.5000 INCHES PER 100,0000 SCALE




EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LONGITUDINAL STABILITY
 $C_d/\alpha = 0.00$


DATA SET SYMBOL CONFIGURATION DESCRIPTION:

NSPC	SSP	(MASP)	MR ATP	(O1) / (T3) / (S1)
(CPAOY)	(CPAT0Y)	(CPAT0Y)	(T3)	(S1) / (O1)
NSPC	SSP	(MASP)	MR ATP	(O1) / (T3) / (S1)
(CPAT0Y)	(CPAT0Y)	(CPAT0Y)	(O1)	(T3) / (S1)
NSPC	SSP	(MASP)	MR ATP	(O1) / (T3) / (S1)
(CPAT11)	(CPAT11)	(CPAT11)	(O1)	(T3) / (S1) / (O1)


REFERENCE INFORMATION
REF. 3220.0000 SQ. FT.
.000 15.000 LREF 1320.0000 INCHES
.000 .500 10.000 BREF 1320.0000 INCHES
2.000 .900 10.000 XMRP .0000
2.000 .900 10.000 YMRP .0000
ZMRP -61.0000 INCHES
SCALE 100.0000 PER




Cz



CLM



CXPL



CAE

CDL - X/C = .5C





EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB. LONGITUDINAL STABILITY

PAGE 40

DATA SET SYMBOL CONFIGURATION DESCRIPTION

(3)	NSPC 550	NR ATP	(O1) / (T3) (S1)
(C)	NSPC 550	NR ATP	(T3) (S1) / (O1)
(O)	NSPC 550	NR ATP	(O1) / (T3) (S1)
(CPAT12)	NSPC 550	NR ATP	(T3) (S1) / (C1)
(CPAT12)	NSPC 550	NR ATP	(T3) (S1) / (C3)

ORBINC MACH ELEVON DELZ/D REFERENCE INFORMATION
 .000 .900 10,000 -1,000 50 FT.
 .000 .900 10,000 1,000 LREF
 2,000 .900 10,000 -1,000 BREF
 2,000 .900 10,000 1,000 1326 INCHES
 2,000 .900 10,000 -1,000 XMRP
 2,000 .900 10,000 1,000 YMRP
 2,000 .900 10,000 -1,000 ZMRP
 100,000 .000 100,000 1,000 1326 INCHES
 100,000 .000 100,000 -1,000 100,000 INCHES
 SCALE




EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LONGITUDINAL STABILITY

INDEX = .CC


PAGE 4:

DATA SET SYMBOL CONFIGURATION DESCRIPTION
 MSFC 559 (MASP) NR ATP (O1) / (T3) (S1)
 MSFC 558 (MASP) NR ATP (T3) (S1) / (O1)
 MSFC 556 (MASP) NR ATP (O1) / (T3) (S1)
 MSFC 555 (MASP) NR ATP (T3) (S1) / (O1)


REFERENCE INFORMATION
 ORB INC MACH ELEVON DELZ/D S.R.F.T.
 .000 .900 10,000 1.000 BREF 3220.0000
 .000 .900 10,000 -1.000 LREF 1326.0000
 2,000 .900 10,000 -1.000 BREP 1328.0000
 2,000 .900 10,000 .000 XMRP .0000
 2,000 .900 10,000 -1.000 THRP .0000
 2,000 .900 10,000 -61.3000 ZMRP 100.0000
 SCALE INCHES PER




C_2



CL_M



$X_{CP/L}$






CA_F

EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LONGITUDINAL STABILITY
 $(300E-X/Z = .50)$

PAGE 42


DATA SET SYMBOL CONFIGURATION DESCRIPTION
 MSFC 559 (MAGF) NR ATP (O1)/(T3) (S1)
 MSFC 558 (MAGF) NR ATP (T3) (S1)/(G1)
 DATA NOT AVAILABLE
 DATA NOT AVAILABLE
 (CPA019) (CPA019)
 (CPA023) (CPA023)

REFERENCE INFORMATION
 ORB INC MACH ELEVON DELZ/D SREF SQ.FT.
 .000 1.200 10.000 -.520 LREF 3220.0000 INCHES
 .000 1.200 10.000 -.520 BREF 1326.0000 INCHES
 2.000 1.200 10.000 -.520 XMRP 1328.0000 INCHES
 .0000 ZMRP .0000 INCHES
 SCALE 100.0000 PER



EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LONGITUDINAL STABILITY
 $(\Delta \text{ZDE} - X/C = -.50)$


DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (C78019) MSFC 558 (MA9) NR ATP (O1)/(T3) (S1)
 (C78019) MSFC 558 (MA9) NR ATP (O1)/(T3) (S1)
 (C78019) MSFC 558 (MA9) NR ATP (O1)/(T3) (S1)
 (C78023) MSFC 558 (MA9) NR ATP (T3) (S1)/(O1)
 (C78023) MSFC 558 (MA9) NR ATP (T3) (S1)/(O1)




EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LONGITUDINAL STABILITY
 (CODE-X/D= .33
 PAGE 44

DATA SET SYMBOL CONFIGURATION DESCRIPTION
 NSFC 556 (MA9F) NR ATP (O1) / (T3) (S1)
 (C78019) NSFC 558 (MA9F) NR ATP (T3) (S1) / (O1)
 (C78A19) NSFC 558 (MA9F) NR ATP (O1) / (T3) (S1)
 (C78C23) NSFC 558 (MA9F) NR ATP (T3) (S1) / (O1)
 (C78T23)


REFERENCE INFORMATION
 ORB INC MACH ELEVON DEL Z/D
 .000 1.200 10.000 -.520
 .000 1.200 10.000 LREF 1320.0000
 .000 1.200 10.000 BREF 1320.0000
 2.000 1.200 10.000 .520
 2.000 1.200 10.000 XMRP .0000
 2.000 1.200 10.000 ZMRP -.61.5000
 SCALE 100.0000




Cz



XCPL



CLM



CAF





EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LONGITUDINAL STABILITY
 CODE-X/C = .50

DATA SET SYMBOL CONFIGURATION DESCRIPTION

(CPAC20)	MSFC 550 (M9F) NR ATP (O1)/(T3) (S1)
(CPAT20)	MSFC 550 (M9F) NR ATP (T3) (S1)/(O1)
(CPAC24)	MSFC 550 (M9F) NR ATP (O1)/(T3) (S1)
(CPAT24)	MSFC 550 (M9F) NR ATP (T3) (S1)/(O1)

REFERENCE INFORMATION

ORB INC	MACH	ELEVON	OCL Z/D	SQ.FT.
.000	1.200	10.000	-1.000	SREF 3220 .0000
.000	1.200	10.000	-1.000	LREF 1328 .0000
.000	1.200	10.000	-1.000	BREF 1328 .0000
2.000	1.200	10.000	-1.000	XMRP .0000
2.000	1.200	10.000	-1.000	ZMRP -.61 .3000
				INCHES PER
			SCALE 100.0000	







EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LONGITUDINAL STABILITY
 $C_{LSE} - X/C = .33$

PAGE 46

DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (CPB20) MSLC 558 (MASF) NR ATP (O1) / (T3) (S1)
 (CPAT20) MSLC 558 (MASF) NR ATP (T3) S1 / (O1)
 (CPA24) MSLC 558 (MASF) NR ATP (O1) / (T3) (S1)
 (CPAT24) MSLC 558 (MASF) NR ATP (T3) (S1) / (O1)

REFERENCE INFORMATION
 ORB INC MACH ELEVON DELZ/D SREF 3220.0000 SQ FT.
 .000 1.200 10.000 -1.000 LREF 1328.0000 INCHES
 .000 1.200 10.000 -1.000 BREF 1328.0000 INCHES
 2.000 1.200 10.000 -1.000 XMRP .0000
 2.000 1.200 10.000 -1.000 YMRP .0000
 ZMRP -81.5000 INCHES
 SCALE 100.0000 PER






EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LONGITUDINAL STABILITY
 (3000 - X/3 = .50)

DATA SET SYMBOLS CONFIGURATION DESCRIPTION

(CTA033)	MSPC 556 (MA9F) NR ATP (O1)/(T3)(S1)
(CTA033)	MSFC 556 (MA9F) NR ATP (T3)/(S1)(O1)
(CTA033)	MSFC 556 (MA9F) NR ATP (O1)/(T3)(S1)
(CTA033)	MSFC 556 (MA9F) NR ATP (T3)(S1)/(O1)
(CTA033)	MSFC 556 (MA9F) NR ATP (S1)/(T3)(O1)

ORB INC MACH ELEVON DFL/Z/D REFERENCE INFORMATION
 .000 .900 .000 -.52U SQ.FT.
 .000 .900 .000 LREF 1322.0000
 .000 .900 .000 RREF 1322.0000
 2.000 .900 .000 XMRP .0000
 2.000 .900 .000 ZMRP -61.5000
 SCALE 100.0000 INCHES PER






EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LAT.-DIR. STABILITY
 $C_{3L} - X/2 = .00$

DATA SET SYMBOL CONFIGURATION DESCRIPTION

(CPA034)	MSPC 558 (MAFP)	NR ATP (O1) / (T3) (S1)
(CPAT34)	MSPC 558 (MAFP)	NR ATP (T3) (S1) / (O1)
(CPA738)	MSPC 558 (MAFP)	NR ATP (O1) / (T3) (S1)
(CPAT38)	MSPC 558 (MAFP)	NR ATP (T3) (S1) / (O1)

REFERENCE INFORMATION

ORB INC	MACH	ELEVN	DELZ/D	SQ.FT.
.000	.000	.000	.000	3220.0000
.000	.900	.000	-1.000	SRBF 1328.0000
.000	.900	.000	-1.000	LREF 1328.0000
.000	.900	.000	-1.000	BRCF 1328.0000
.000	.900	.000	-1.000	XMEP .0000
.000	.900	.000	-1.000	YMRP .0000
.000	.900	.000	-1.000	ZWRP -.61.3000
2.000				INCHES PER
2.000				100.0000






EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LAT.-DIR. STABILITY


$\zeta = 2.25, \chi/2 = .30$

DATA SET SYMBOL CONFIGURATION DESCRIPTION
 MSFC 55A (MA9F1) NR ATP (O1)/(T3) (S1)
 (C7P057)
 MSFC 55B (MA9F1) NR ATP (T3) (S1) / (O1)
 (C7AT57)
 MSFC 55B (MA9F1) NR ATP (O1) / (T3) (S1)
 (C7AO59)
 MSFC 55B (MA9F1) NR ATP (T3) (S1) / (O1)
 (C7ET59)

REFERENCE INFORMATION
 SREF 3220.0000 SO. FT.
 LREF 1328.0000 INCHES
 BREF 1328.0000 TRICHES
 XMRP .0000
 YMRP -.613000 INCHES
 ZMRP 100.0000 PER INCHES




C8L



CYN

EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LAT.-DIR. STABILITY
 CADDET-X/D = .00
 PAGE 50

DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (CP0361) NSPC 558 (MASP) NR ATP (O1)/(T3)/(S1)
 (CPA131) NSPC 558 (MASP) NR ATP (T3)/(S1)/(O1)
 (CPA401) NSFC 558 (MASP) NR ATP (O1)/(T3)/(S1)
 (CPB1401) NSFC 558 (MASP) NR ATP (T3)/(S1)/(O1)






EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LAT.-DIR. STABILITY
 C=2.0E-3, D=.00

PAGE 51

D - SET SYMBOL **CONFIGURATION DESCRIPTION**
 MSPC 556 (MAP) NR ATP (O1) / (T3) .51;
 MSPC 556 (MAP) NR ATP (T3) (S1) / (O1)


REFERENCE INFORMATION
 ORB INC MACH ELEVON Δ EL2/0 SQ.FT.
 2.000 2.000 .000 -.520 3220.0000
 2.000 2.000 .000 -.520 132A.0000
 LREF 132A.0000
 XMRP .0000
 YMRP -.61.3000
 ZMRP 100.0000
 INCHES
 PER
 SCALE



EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB, LAT.-DIR. STABILITY

$X/Z = .00$


PAGE 52



EFFECT OF INCIDENCE ANGLE ON ORBITER AND TANK / SRB. LAT.-DIR. STABILITY
 Cx = X/D₀ .00
 PAGE 53

DATA SET SYMBOL CONFIGURATION DESCRIPTION

(0)	MSFC 558 (MA9F) NR ATP (01) / (T3) (S1)
(077C01)	MSFC 558 (MA9F) NR ATP (01) / (T3) (S1)
(077C02)	MSFC 558 (MA9F) NR ATP (01) / (T3) (S1)
(077C03)	MSFC 558 (MA9F) NR ATP (01) / (T3) (S1)
(07AT01)	MSFC 558 (MA9F) NR ATP (T3) (S1) / (01)
(07AT02)	MSFC 558 (MA9F) NR ATP (T3) (S1) / (01)
(07AT03)	MSFC 558 (MA9F) NR ATP (T3) (S1) / (01)



CLM
DELX/C
DELZ/C
DELX/D



LONGITUDINAL STABILITY CHARACTERISTICS - EFFECTS OF VARYING DELX/D

PAGE 54

DATA SET SYMBOL CONFIGURATION DESCRIPTION

(DPA13)	NSPC 356 (MA5P) NR ATP (O1)/(T3) (S1)
(DPA14)	NSPC 356 (MA5P) DR ATP (O1)/(T3) (S1)
(DPA15)	NSPC 356 (MA5P) ND ATP (O1)/(T3) (S1)
(DPA16)	NSPC 356 (MA5P) NM ATP (O1)/(T3) (S1)
(DPA17)	NSPC 356 (MA5P) NR ATP (T3) (S1)/(O1)
(DPA18)	NSPC 356 (MA5P) DR ATP (T3) (S1)/(O1)
(DPA19)	NSPC 356 (MA5P) ND ATP (T3) (S1)/(O1)
(DPA20)	NSPC 356 (MA5P) NM ATP (T3) (S1)/(O1)

REFERENCE INFORMATION
SREF 3220.0000 SQ. FT.
LREF 1328.0000 INCHES
BREF 1328.0000 INCHES
XMRP .0000 INCHES
YMRP -.0000 INCHES
ZMRP -.81 5000 PER 2
SCALE 100.0000




LONGITUDINAL STABILITY CHARACTERISTICS - EFFECTS OF VARYING DELX/D

$$C_{2A} = .00$$

REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.

DATA SET SYMBOL	CONFIGURATION DESCRIPTION	MACH	DELZ/D	ORBINC	ELEVON	REFERENCE INFORMATION
(DPAT25)	MSFC 558 (MASP) NR ATP (O1) / (T3) (S1)	2.000	.520	.000	.000	3220.0000 INCHES
(DPAT26)	MSFC 558 (MASP) NR ATP (O1) / (T3) (S1)	2.000	-1.000	.000	.000	1326.0000 INCHES
(DPAT27)	MSFC 558 (MASP) NR ATP (O1) / (T3) (S1)	2.000	-1.500	.000	.000	1326.0000 BREW
(DPAT28)	MSFC 558 (MASP) NR ATP (O1) / (T3) (S1)	2.000	-.520	.000	.000	.0000 XMRP
(DPAT29)	MSFC 558 (MASP) NR ATP (T3) (S1) / (O1)	2.000	-1.000	.000	.000	.0000 YMRP
(DPAT30)	MSFC 558 (MASP) NR ATP (T3) (S1) / (O1)	2.000	-1.500	.000	.000	-.61.5000 INCHES
(DPAT31)	MSFC 558 (MASP) NR ATP (T3) (S1) / (O1)	2.000	-.520	.000	.000	10.0000 PER SCALE



LONGITUDINAL STABILITY CHARACTERISTICS - EFFECTS OF VARYING DELX/D

$\text{CDA}_{\text{PA}} = .00$

PAGE 56

REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.

DATA SET SYMBOL **CONFIGURATION DESCRIPTION**

(11PAC01) MAFC 558 (MAFP) MR ATP (O1)/(T3) (S1)

(11PAC02) MAFC 558 (MAFP) NR ATP (T3) (S1)/(O1)

(11PAC03) MAFC 558 (MAFP)

REFERENCE INFORMATION

MACH DELX/D ORBINC ELEVON REFERENCE INFORMATION

.900 -.500 .000 .000 SREF 3220.0000 SQ.FT.




.900 -.500 .000 .000 LREF 1526.0000 INCHES

 .000 .000 .000 BREF 1526.0000 INCHES

 .000 .000 .000 XMRP .0000 INCHES

 .000 .000 .000 ZMRP -.51.5000 INCHES PER

 .000 .000 .000 SCALE 100.0000 INCHES PER




LONGITUDINAL STABILITY CHARACTERISTICS - EFFECTS OF VARYING $\Delta Z/D$

$$C_{AA} \cdot P_A = .00$$

REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.


DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (11PC02) NSFC 550 (MAFP) NR ATP (O1)/(T3) (S1)
 (11PC02) NSFC 550 (MAFP) NR ATP (T3) (S1)/(O1)
 ((11PC02))



LONGITUDINAL STABILITY CHARACTERISTICS - EFFECTS OF VARYING DELZ/D
 $(A_f^2 - D - A = .30)$


PAGE 58

REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.



LONGITUDINAL STABILITY CHARACTERISTICS - EFFECTS OF VARYING DELZ/D
 CASA_P-A = .00
 PAGE 59

REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.





LONGITUDINAL STABILITY CHARACTERISTICS - EFFECTS OF VARYING DELZ/D

PAGE 60

REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.

DATA SET SYMBOL CONFIGURATION DESCRIPTION
 11980141 NSPC 350 (NSPF) NR ATP (01)/(T3) (S1)
 NSPC 350 (NSPF) NR ATP (T3) (S1)/(01)
 (TPAT14)

SREF 3020.0000 SQ.FT.
 LREF 1322.0000 INCHES
 BREF 1326.0000 INCHES
 XMRP .0000 INCHES
 YMRP .0000 INCHES
 ZMRP -61.5000 PER 100.0000 INCHES PER



LONGITUDINAL STABILITY CHARACTERISTICS - EFFECTS OF VARYING $\Delta Z/D$



$C_{IA_D-A} = .00$

PAGE 6:

REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.

DATA SET SYMBOL: CONFIGURATION DESCRIPTION
 (1178015) MSFC 550 (MA5P) NR ATP (01) / (T3) (S1)
 (1178015) MSFC 558 (MA5P) NR ATP (T3) (S1) / (01)

REFERENCE INFORMATION
 MACH DELX/D ORBTINC ELEVON SREF SQ.FT.
 1.200 .900 .000 .000 3220.0000
 1.200 .500 .000 .000 1326.0000
 BREF INCHES
 KMSP .0000
 ZMRP .0000
 VMRP -61.5000
 SCALE 100.0000
 INCHES PER




LONGITUDINAL STABILITY CHARACTERISTICS - EFFECTS OF VARYING $\Delta Z/D$

$$C_{Af} = -0.30$$

PAGE 62

REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.

DATA SET SYMBOL CONFIGURATION DESCRIPTION
 1190251 NSPC 558 (MA5P) NR ATP (01)/(T3) (S1)
 1190252 NSPC 558 (MA5P) NR ATP (T3) (S1),/(O1)
 (1190253)




LONGITUDINAL STABILITY CHARACTERISTICS - EFFECTS OF VARYING $\Delta L/D$

$$C_{M_{\infty}} = .00$$

PAGE 63

REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.


REFERENCE INFORMATION	
SQ.FT.	3880.0000
LREF	1328.0000
BREF	1328.0000
XMRP	.0000
YMRP	.0000
ZMRP	-61.5000
SCALE	100.0000




PAGE 64

LONGITUDINAL STABILITY CHARACTERISTICS - EFFECTS OF VARYING DELZ/D
 $C_{A2,A2-A} = .30$

DATA SET SYMBOL CONFIGURATION DESCRIPTION
 1170260 (1170260) MASP C 130 (MASP) NR ATP (O1)/(T3) (S1)
 1170260 (1170260) X MASP C 330 (MASP) NR ATP (T3) (S1)/(O1)



REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.



LONGITUDINAL STABILITY CHARACTERISTICS - EFFECTS OF VARYING DELZ/D
 $C_{A,A2-A} = .00$

PAGE 65

APPENDIX
TABULATED SOURCE DATA

Plotted data tabulations available
from DMS on request.

PRECEDING PAGE BLANK NOT FILMED

REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.

DATE 29 MAR 73

SOURCE DATA TABULATION, M8FC-TWT-558

PAGE 1

M8FC 558 (M8SF) NR ATP (O1)/(T3)(S1)

(R78001) (29 JAN 73)

PARAMETRIC DATA

REFERENCE DATA

BREF = 3220.0000 SQ.FT.	XMRP = .0000
LREF = 1328.0000 INCHES	YMRP = .0000
BREF = 1328.0000 INCHES	ZMRP = -61.5000 INCHES
SCALE = 100.0000 PER	

BETA = .000	ORGINC = .000
MACH = .900	ELEVON = .000
DELZ/D = -.520	

RUN NO. 1016/0 RNL = 6.21 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLH	CY	CYN	CBL	CAF	CAB
-.500	-8.000	-.35290	.26700	-.00180	.00010	.00190	.03470	.04190
-.500	-4.000	-.27690	.21290	-.00370	.00100	.00100	.03600	.03620
-.500	-4.000	-.21080	.16390	-.00340	.00050	.00060	.03990	.03670
-.500	-2.000	-.14200	.11590	-.00130	-.00090	.00120	.03990	.03700
-.500	.000	-.07170	.06710	-.00230	-.00020	.00110	.03910	.03710
-.500	2.000	.00040	.01620	-.00190	-.00020	.00140	.03730	.03560
-.500	4.000	.07040	-.03360	-.00130	-.00040	.00140	.03390	.03470
-.500	6.000	.15480	-.08310	-.00030	-.00060	.00140	.02920	.03360
-.500	8.000	.23550	-.15140	.00100	-.00180	.00170	.02730	.03290
GRADIENT		.03526	-.02473	.00016	-.00005	.00007	-.00073	-.00087

RUN NO. 1017/0 RNL = 6.20 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLH	CY	CYN	CBL	CAF	CAB
.000	-8.000	-.34960	.28290	-.00360	.00120	.00080	.03360	.03780
.000	-4.000	-.29260	.22650	-.00270	.00090	.00070	.03260	.03710
.000	-4.000	-.21450	.17110	.00000	-.00160	.00080	.03420	.03640
.000	-2.000	-.14370	.11920	-.00110	-.00190	.00100	.03490	.03640
.000	.000	-.07230	.07050	.00080	-.00220	.00100	.03460	.03620
.000	2.000	-.00240	.02220	.00000	-.00190	.00120	.03360	.03590
.000	4.000	.07490	-.03130	-.00040	-.00130	.00130	.02920	.03360
.000	6.000	.15700	-.08000	.00020	-.00170	.00160	.02410	.03360
.000	8.000	.23730	-.14630	.00040	-.00160	.00190	.01810	.03340
GRADIENT		.03620	-.02509	-.00004	.00003	.00003	-.00057	-.00011

RUN NO. 1018/0 RNL = 6.22 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLH	CY	CYN	CBL	CAF	CAB
.500	-8.000	-.38420	.30900	-.00260	.00000	.00080	.03790	.03410
.500	-4.000	-.32720	.26040	-.00200	-.00050	.00090	.03560	.03390
.500	-4.000	-.25270	.20830	-.00120	-.00100	.00030	.03500	.03390
.500	-2.000	-.17670	.15320	-.00040	-.00140	.00050	.03460	.03300
.500	.000	-.09600	.09120	-.00180	-.00100	.00030	.03430	.03280
.500	2.000	-.01340	.03500	-.00020	-.00170	.00060	.03260	.03310
.500	4.000	.06670	-.02120	.00020	-.00160	.00150	.02660	.03260
.500	6.000	.15740	-.06670	-.00020	-.00130	.00060	.02300	.03230
.500	8.000	.23960	-.14540	-.00030	-.00120	.00060	.02030	.03280
GRADIENT		.04050	-.02666	.00019	-.00008	.00013	-.00076	-.00008

PRECEDING PAGE BLANK NOT FILMED

REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.

DATE 29 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 2

MSFC 558 (MAGF) NR ATP (O1)/(T3)(S1)

(RTYC02) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1378.0000 INCHES YMRP = .0000
 BRE = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

BETA = .000 ORBINC = .000
 MACH = .900 ELEVON = .700
 DELZ/D = -1.000

RUN NO. 1019/ D RNL = 6.19 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
-.900	-6.000	-.42360	.31750	.00670	-.00720	.00230	.03110	.03650
-.900	-6.000	-.34130	.25840	.00640	-.00630	.00250	.03250	.03520
-.900	-4.000	-.25650	.19950	.00630	-.00640	.00250	.03470	.03460
-.900	-2.000	-.17420	.14130	.00630	-.00760	.00200	.03650	.03390
-.900	.000	.09780	.06890	.00640	-.00630	.00190	.03460	.03300
-.900	2.000	-.01620	.03310	.00660	-.00760	.00130	.03460	.03260
-.900	4.000	.06420	-.01420	.00610	-.00760	.00120	.03120	.03190
-.900	6.000	.16130	-.06120	.00770	-.00650	.00100	.02420	.03160
-.900	8.000	.29110	-.15390	.00790	-.00640	.00130	.02310	.03140
GRADIENT	.04037	-.02778	.00003	.00008	-.00014	-.00044	-.00038	

RUN NO. 1020/ C RNL = 6.19 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-6.000	-.43730	.32780	.00680	-.00790	.00230	.03230	.03650
.000	-6.000	-.39820	.27130	.00690	-.00490	.00230	.03280	.03510
.000	-4.000	-.27120	.20990	.00790	-.00630	.00190	.03380	.03330
.000	-2.000	-.18790	.15150	.00870	-.00640	.00210	.03440	.03470
.000	.000	-.10810	.09600	.00930	-.00660	.00180	.03610	.03410
.000	2.000	-.03150	.04520	.00850	-.00790	.00170	.03370	.03340
.000	4.000	.05400	-.01920	.00640	-.00760	.00240	.02460	.03300
.000	6.000	.19070	-.06300	.00640	-.00720	.00200	.02760	.03390
.000	8.000	.24470	-.14970	.00600	-.00670	.00200	.01940	.03360
GRADIENT	.04032	-.02792	.00008	.00010	.00013	-.00099	-.00030	

RUN NO. 1021/ D RNL = 6.18 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.900	-6.000	-.49750	.34260	.00690	-.00600	.00300	.03420	.03640
.900	-6.000	-.37040	.26460	.00910	-.00930	.00290	.03120	.03440
.900	-4.000	-.26130	.22050	.00790	-.00790	.00200	.03220	.03240
.900	-2.000	-.20190	.16430	.00790	-.00610	.00140	.03260	.03290
.900	.000	-.11660	.10580	.01090	-.00660	.00190	.03360	.03140
.900	2.000	-.03370	.04810	.00640	-.00600	.00170	.03290	.03120
.900	4.000	.05590	-.01400	.00700	-.00660	.00180	.02780	.03150
.900	6.000	.15870	-.06650	.00640	-.00660	.00170	.02180	.03200
.900	8.000	.25310	-.15300	.00670	-.00660	.00180	.01820	.03270
GRADIENT	.04209	-.02920	-.00003	.00014	-.00001	-.00044	-.00219	

REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.

DATE 29 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 3

MSFC 558 (MADF) NR ATP (01)/(T3) (S1)

(R78003) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

BETA = .000 ORBINC = .000
 MACH = .900 ELEVON = .000
 DELZ/D = -1.500

RUN NO. 1041/0 RN/L = 6.18 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
-1.000	-6.530	-.33520	.30070	-.00130	.00320	-.00050	.11770	.06000
-1.000	-6.290	-.25510	.23130	-.00210	.00460	-.00010	.12260	.07440
-1.000	-4.070	-.17860	.17160	-.00040	.00240	.00010	.12660	.07150
-1.000	-1.890	-.10720	.11160	-.00540	.00760	.00000	.12690	.06690
-1.000	.270	-.02130	.02330	-.00570	.00860	-.00030	.12720	.06490
-1.000	.280	-.01620	.01670	-.00910	.01220	-.00070	.12560	.06570
-1.000	2.480	.06300	-.06360	-.00680	.01060	-.00120	.12310	.06290
-1.000	4.640	.13840	-.13240	-.00850	.01280	-.00230	.12310	.05850
-1.000	6.890	.21540	-.19280	-.00350	.00790	-.00250	.12000	.05560
-1.000	9.050	.29090	-.25590	-.00920	.01210	-.00310	.11210	.05460
GRADIENT		.03691	-.03595	-.00081	.00109	-.00028	-.00033	-.00138

RUN NO. 1040/0 RN/L = 6.19 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
-.500	-8.000	-.46690	.34600	.01860	-.01540	.00260	.03130	.03340
-.500	-8.000	-.37950	.26320	.02010	-.01640	.00260	.03160	.03220
-.500	-4.000	-.29130	.22350	.01970	-.01590	.00230	.03310	.03240
-.500	-2.000	-.19770	.15840	.01870	-.01460	.00210	.03510	.03150
-.500	.000	-.11400	.10170	.01970	-.01520	.00150	.03760	.03040
-.500	2.000	-.02900	.04000	.01830	-.01410	.00040	.03570	.03040
-.500	4.000	.04610	-.02420	.01830	-.01350	.00060	.03060	.03030
-.500	6.000	.16690	-.09320	.01650	-.01220	.00120	.02610	.02930
-.500	8.000	.28280	-.16010	.01500	-.01110	.00160	.02260	.02960
GRADIENT		.04457	-.03089	-.00016	.00027	-.00023	-.00020	-.00027

RUN NO. 1037/0 RN/L = 6.18 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-8.000	-.46160	.34270	.01930	-.01580	.00270	.03110	.03420
.000	-8.000	-.37810	.26400	.02030	-.01640	.00260	.03030	.03310
.000	-4.000	-.28680	.22050	.02030	-.01620	.00230	.03150	.03260
.000	-2.000	-.19470	.15650	.02120	-.01640	.00240	.03270	.03260
.000	.000	-.10660	.09790	.01900	-.01480	.00180	.03370	.03210
.000	2.000	-.01890	.03690	.01710	-.01320	.00160	.03220	.03230
.000	4.000	.07620	-.02910	.01670	-.01240	.00160	.02750	.03180
.000	6.000	.17490	-.09930	.01520	-.01140	.00110	.02170	.03160
.000	8.000	.27350	-.16970	.01400	-.01050	.00150	.01950	.03220
GRADIENT		.04511	-.03094	-.00093	.00054	-.00011	-.00043	-.00013

DATE 26 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-556

PAGE 4

MSFC 556 (MAGF) NR ATP (O1)/(T3)(S1)

(R78003) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
LREF = 1328.0000 INCHES YMRP = .0000
BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
SCALE = 100.0000 PER

BETA = .000 ORBINC = .000
MACH = .000 ELEVON = .000
DELZ/D = -1.500

PARAMETRIC DATA

RUN NO. 1036/0 RN/L = 6.19 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLH	CY	CYN	CBL	CAF	CAB
.500	-6.000	-.47470	.35490	.02020	-.01650	.00290	.03170	.03430
.500	-6.000	-.39460	.29870	.02100	-.01670	.00290	.03080	.03260
.500	-4.000	-.30110	.23270	.02000	-.01600	.00240	.03080	.03170
.500	-2.000	-.20940	.16840	.02030	-.01590	.00220	.03250	.03100
.400	.000	-.12960	.11390	.02050	-.01560	.00170	.03350	.03140
.500	2.000	-.03440	.04650	.01810	-.01380	.00110	.03250	.03060
.500	4.000	.06080	-.01660	.01690	-.01260	.00140	.02620	.03090
.500	6.000	.16260	-.08920	.01610	-.01190	.00150	.02300	.03050
.500	8.000	.26560	-.16230	.01370	-.01030	.00170	.01960	.03100
GRADIENT		.04494	-.03095	-.00042	.00045	-.00015	-.00026	-.00010

DATE 26 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 5

MSFC 558 (MASF) NR ATP (01)/(T3) (81)

(R78004) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

BETA =	.000	ORBINC =	2.000
MACH =	.900	ELEVON =	.000
DELZ/D =	-520		

RUN NO. 1073/0 RN/L = 6.19 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
-.500	-8.000	-.21320	.16880	-.01760	.30'20	-.00010	.04020	.04140
-.500	-6.000	-.14400	.11810	-.00671	.00460	.00000	.04090	.04010
-.500	-4.000	-.07220	.06570	-.01470	.00430	.00000	.04090	.03660
-.500	-2.000	-.00460	.01720	-.00730	.00350	.00030	.04080	.03770
-.500	.000	.05360	-.02430	-.00730	.00360	.00030	.03920	.03630
-.500	2.000	.12980	-.07620	-.00830	.00440	.00020	.03550	.03470
-.500	4.000	.20940	-.13310	-.00970	.00570	.00050	.02950	.03430
-.500	6.000	.29150	-.19230	-.00630	.00440	.00040	.02620	.03430
-.500	8.000	.36120	-.24590	-.00790	.00420	.00090	.02770	.03460
GRADIENT		.03489	-.02455	-.00015	.00018	.00013	-.00150	-.00058

RUN NO. 1070/0 RN/L = 6.16 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-8.000	-.22450	.17950	-.00530	.00250	-.00020	.03380	.03990
.000	-6.000	-.15330	.12750	-.00580	.00260	-.00020	.03380	.03920
.000	-4.000	-.06550	.07900	-.00560	.00250	-.00010	.03450	.03600
.000	-2.000	-.01970	.03380	-.00490	.00160	.00000	.03350	.03640
.000	.000	.04690	-.01250	-.00610	.00260	-.00020	.03180	.03770
.000	2.000	.12150	-.06420	-.00560	.00240	.00010	.02740	.03710
.000	4.000	.20270	-.12190	-.00640	.00330	.00040	.02430	.03630
.000	6.000	.28440	-.18070	-.00730	.00390	.00050	.02190	.03720
.000	8.000	.35460	-.23280	-.00610	.00460	.00090	.02160	.03610
GRADIENT		.03588	-.02499	-.00011	.00011	.00005	-.00133	-.00024

RUN NO. 1074/0 RN/L = 6.18 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.500	-8.000	-.27060	.22490	-.00570	.00210	-.00050	.03790	.03530
.500	-6.000	-.20320	.17610	-.00600	.00230	-.00070	.03650	.03540
.500	-4.000	-.12980	.12270	-.00420	.00250	-.00070	.03520	.03500
.500	-2.000	-.05710	.07070	-.00660	.00290	-.00070	.03500	.03460
.500	.000	.02370	.01320	-.00660	.00270	-.00040	.03320	.03360
.500	2.000	.11260	-.03120	-.00690	.00330	-.00020	.02660	.03360
.500	4.000	.20220	-.11600	-.00610	.00420	-.00010	.02440	.03350
.500	6.000	.27620	-.17020	-.00650	.00450	.00000	.02220	.03540
.500	8.000	.34930	-.22150	-.00690	.00490	.00020	.02220	.03720
GRADIENT		.04168	-.02996	-.00019	.00019	.00006	-.00139	-.00019

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 6

MSFC 558 (MA9F) NR ATP (O1)/(T3)(S1)

(R78005) (29 JAN 73)

REFERENCE DATA

BREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

BETA = .000 ORBINC = 2.000
 MACH = .900 ELEVON = .000
 DELZ/D = -1.000

PARAMETRIC DATA

RUN NO. 1069/0 RN/L = 6.16 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
-.500	-6.000	-.30300	.23210	.00320	-.00480	.00130	.03380	.03780
-.500	-6.000	-.21920	.17250	.00400	-.00530	.00130	.03620	.03660
-.500	-4.000	-.13900	.11620	.00760	-.00750	.00160	.03890	.03620
-.500	-2.000	-.05980	.05990	.00390	-.00470	.00070	.04000	.03900
-.500	.000	.02160	.00350	.00280	-.00360	.00060	.03830	.03510
-.500	2.000	.09960	-.05000	.00220	-.00320	.00070	.03440	.03300
-.500	4.000	.19270	-.11520	.00040	-.00150	.00070	.02880	.03200
-.500	6.000	.28510	-.18010	.00190	-.00170	.00080	.02480	.03290
-.500	8.000	.36650	-.23850	.00100	-.00160	.00120	.02340	.03360
GRADIENT		.04114	-.02863	-.00060	.00067	-.00009	-.00129	-.00052

RUN NO. 1066/0 RN/L = 6.18 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-6.000	-.31280	.24100	.00380	-.00490	.00110	.03370	.03610
.000	-6.000	-.23100	.18280	.00390	-.00510	.00120	.03470	.03570
.000	-4.000	-.14900	.12470	.00340	-.00470	.00120	.03550	.03550
.000	-2.000	-.06980	.07020	.00360	-.00460	.00100	.03460	.03500
.000	.000	.00600	.01790	.00270	-.00370	.00150	.03440	.03490
.000	2.000	.08720	-.03660	.00240	-.00310	.00160	.03100	.03370
.000	4.000	.18670	-.10750	.00070	-.00160	.00130	.02490	.03370
.000	6.000	.27960	-.17290	.00150	-.00210	.00140	.02360	.03330
.000	8.000	.36660	-.23610	.00090	-.00130	.00160	.02300	.03460
GRADIENT		.04142	-.02856	-.00033	.00036	.00004	-.00124	-.00025

RUN NO. 1065/0 RN/L = 6.17 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.900	-6.000	-.33300	.26210	.00390	-.00540	.00110	.03520	.03460
.900	-6.000	-.25150	.20360	.00360	-.00510	.00100	.03460	.03370
.900	-4.000	-.17050	.14590	.00370	-.00500	.00090	.03530	.03290
.900	-2.000	-.08990	.06950	.00250	-.00400	.00050	.03420	.03300
.900	.000	.00010	.08710	.00310	-.00390	.00100	.03360	.03230
.900	2.000	.09290	-.03690	.00000	-.00150	.00080	.02810	.03200
.900	4.000	.18730	-.10520	-.00060	-.00060	.00110	.02510	.03170
.900	6.000	.27620	-.16920	-.00010	-.00070	.00110	.02160	.03300
.900	8.000	.36240	-.22910	.00100	-.00190	.00100	.01800	.03620
GRADIENT		.04490	-.03193	-.00055	.00057	.00003	-.00133	-.00017

DATE 26 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 7

MSFC 558 (MAZF) NR ATP (O1)/(T3)(S1)

(R78006) (29 JAN 73)

REFERENCE DATA

BREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRF = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

BETA = .000 ORBINC = 2.000
 MACH = .900 ELEVON = .000
 DELZ/D = -1.500

PARAMETRIC DATA

RUN NO. 1051/0 RNL = 6.28 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
-.500	-8.000	-.35540	.27010	.01380	-.01220	.00230	.03240	.03490
-.500	-8.000	-.26430	.20580	.01350	-.01310	.00220	.03420	.03380
-.500	-4.000	-.17510	.14350	.01380	-.01290	.00190	.03670	.03340
-.500	-2.000	-.09340	.08660	.01340	-.01090	.00090	.03710	.03300
-.500	.000	-.00290	.02440	.01170	-.00950	.00040	.03650	.03220
-.500	2.000	.06290	-.03440	.00970	-.00770	.00030	.03210	.03190
-.500	4.000	.18960	-.10880	.00990	-.00720	.00090	.02670	.03180
-.500	6.000	.28490	-.17530	.00970	-.00730	.00150	.02350	.03110
-.500	8.000	.37850	-.24090	.00790	-.00560	.00190	.02270	.03280
GRADIENT		.04526	-.03120	-.00378	.00073	-.00013	-.00125	-.00030

RUN NO. 1050/0 RNL = 6.31 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-8.000	-.35750	.27210	.01520	-.01300	.00230	.03230	.03460
.000	-8.000	-.27130	.21120	.01540	-.01280	.00210	.03310	.03370
.000	-4.000	-.18430	.15010	.01370	-.01150	.00180	.03440	.03340
.000	-2.000	-.09720	.09080	.01370	-.01130	.00120	.03530	.03330
.000	.000	-.00560	.02610	.01040	-.00660	.00090	.03370	.03270
.000	2.000	.07650	-.02900	.00990	-.00790	.00090	.02910	.03300
.000	4.000	.18340	-.10260	.00930	-.00720	.00140	.02430	.03240
.000	6.000	.29040	-.17660	.00890	-.00700	.00140	.02020	.03340
.000	8.000	.38960	-.24990	.00670	-.00510	.00190	.01910	.03460
GRADIENT		.04555	-.03127	-.00063	.00060	-.00006	-.00132	-.00011

RUN NO. 1049/0 RNL = 6.29 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.500	-8.000	-.36600	.26020	.01530	-.01310	.00240	.03260	.03320
.500	-8.000	-.27620	.21640	.01420	-.01210	.00200	.03200	.03250
.500	-4.000	-.18460	.15280	.01360	-.01150	.00170	.03310	.03210
.500	-2.000	-.09440	.09310	.01260	-.01050	.00140	.03330	.03160
.500	.000	-.01170	.03310	.01170	-.00950	.00110	.03220	.03190
.500	2.000	.06230	-.03120	.01030	-.00810	.00100	.02750	.03160
.500	4.000	.18900	-.10640	.00790	-.00590	.00130	.02240	.03120
.500	6.000	.28330	-.17260	.00680	-.00490	.00130	.02190	.03240
.500	8.000	.36290	-.24290	.00420	-.00470	.00160	.02120	.03430
GRADIENT		.04642	-.03211	-.00073	.00068	-.00006	-.00134	-.00009

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 8

MSFC 558 (MAGF) NR ATP (O1)/(T3)(S1)

(R78007) (29 JAN 73)

REFERENCE DATA

BREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

BETA = .000 ORBINC = .000
 MACH = .900 ELEVON = 10.000
 DELZ/D = -.520

RUN NO. 1014/0 RNL = 6.21 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-6.000	-.22710	.15290	-.00430	.00310	.00000	.09090	.04130
.100	-6.000	-.14640	.09310	-.00530	.00220	.00000	.05320	.04100
.000	-4.000	-.06560	.03440	-.00450	.00180	-.00040	.05590	.04190
.000	-2.000	.01570	-.02500	-.00340	.00120	-.00020	.05930	.04180
.000	.000	.09030	-.07560	-.00480	.00190	-.00100	.06140	.04100
.000	2.000	.16680	-.13070	-.00470	.00250	-.00040	.06050	.04110
.000	4.000	.25220	-.19020	-.00520	.00330	-.00070	.05770	.04050
.000	6.000	.34790	-.26050	-.00610	.00410	-.00050	.05460	.03960
.000	8.000	.43490	-.32440	-.00640	.00420	-.00050	.05320	.04060
GRADIENT		.03942	-.02714	-.00014	.00021	-.00004	.00024	-.00017

RUN NO. 1015/0 RNL = 6.21 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.900	-6.000	-.25190	.17990	-.00260	.00070	-.00070	.04790	.03920
.900	-6.000	-.15990	.10930	-.00220	.00090	-.00060	.05200	.03870
.900	-4.000	-.07110	.04290	-.00900	.00220	-.00060	.05560	.03840
.900	-2.000	.00530	-.01230	-.00440	.00190	-.00110	.05750	.03930
.900	.000	.09500	-.07670	-.00410	.00160	-.00120	.06050	.03930
.900	2.000	.17610	-.13450	-.00370	.00300	-.00060	.05940	.04060
.900	4.000	.26730	-.20020	-.00590	.00360	-.00140	.05610	.03920
.900	6.000	.36160	-.26930	-.00630	.00460	-.00010	.05190	.04060
.900	8.000	.44240	-.32620	-.00560	.00390	-.00020	.05000	.04120
GRADIENT		.04258	-.03052	-.00019	.00023	-.00004	.00013	.00016

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 8

MSFC 558 (MA9F) NR ATP (O1)/(T3) (S1)

(R78008) (29 JAN 73)

REFERENCE DATA

BREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1326.0000 INCHES YMRP = .0000
 BREF = 1326.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

BETA = .000 ORBINC = .000
 MACH = .800 ELEVON = 10.000
 DELZ/D = -1.000

PARAMETRIC DATA

RUN NO. 1023/0 RNL = 6.21 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLW	CY	CYN	CLL	CAF	CAB
.000	-8.000	-.26800	.17610	.00440	-.00490	.00100	.04810	.04320
.000	-6.000	-.18270	.11640	.00470	-.00490	.00080	.05140	.04210
.000	-4.000	-.09300	.05210	.00490	-.00460	.00080	.05570	.04050
.000	-2.000	-.01200	-.00530	.00570	-.00530	.00010	.05940	.04000
.000	.000	.07800	-.06670	.00500	-.00460	.00000	.06160	.04080
.000	2.000	.16200	-.12780	.00450	-.00370	.00000	.06090	.04110
.000	4.000	.25490	-.19340	.00460	-.00340	.00020	.05920	.03990
.000	6.000	.39340	-.26490	.00430	-.00290	.00060	.05540	.04060
.000	8.000	.45550	-.33610	.00290	-.00110	.00120	.05210	.04180
GRADIENT		.04349	-.03067	-.00005	.00080	-.00004	.00043	-.00000

RUN NO. 1022/0 RNL = 6.22 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLW	CY	CYN	CLL	CAF	CAB
.900	-8.000	-.25400	.16740	-.01360	.01490	.00010	.12080	.06900
.900	-6.000	-.20410	.13610	.00610	-.00610	.00040	.05000	.03920
.900	-4.000	-.10390	.06270	.00620	-.00600	.00010	.05350	.03960
.900	-2.000	-.01120	-.00340	.00670	-.00600	.00000	.05810	.03970
.900	.000	.07850	-.06760	.00580	-.00510	.00000	.06030	.04050
.900	2.000	.16460	-.13050	.00520	-.00430	.00000	.06190	.03970
.900	4.000	.26240	-.19760	.00490	-.00320	.00040	.05620	.04030
.900	6.000	.36860	-.27270	.00390	-.00190	.00100	.05410	.03990
.900	8.000	.46180	-.34010	.00110	-.00010	.00140	.04980	.04020
GRADIENT		.04546	-.03238	-.00024	.00036	.00005	.00046	.00007

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 10

MSFC 558 (MAGF) NR ATP (01)/(T3) (81)

(R78009) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

BETA = .000 ORBINC = .000
 MACH = .900 ELEVON = -20.000
 DELZ/D = -.520

PARAMETRIC DATA

RUN NO. 1011/0 RN/L = 6.21 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	COL	CAF	CAB
.000	-6.540	-.27040	.16110	-.01910	.02200	.00080	.11630	.10460
.000	-6.320	-.20370	.11550	-.01530	.01950	.00100	.12350	.09960
.000	-4.110	-.13910	.07900	-.01400	.02160	.00130	.12640	.09700
.000	-1.940	-.06300	.04050	-.01240	.01950	.00090	.12480	.09700
.000	.200	-.02180	-.00660	-.00430	.01270	.00030	.11750	.09600
.000	.210	-.01810	-.01120	-.01375	.01910	.00010	.11690	.09460
.000	2.360	.04590	-.07130	-.01470	.02110	-.00080	.11910	.09340
.000	4.540	.11560	-.13090	-.01100	.01780	-.00100	.11600	.09120
.000	6.760	.17690	-.17430	-.01260	.01690	-.00150	.11340	.08790
.000	8.920	.24590	-.22630	-.01450	.01970	-.00210	.10930	.08460
GRADIENT		.02952	-.02450	.00017	-.00028	-.00029	-.00141	-.00061

RUN NO. 1010/0 RN/L = 6.20 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	COL	CAF	CAB
.900	-6.310	-.21970	.08020	-.01160	.01700	.00090	.11470	.09730
.900	-6.290	-.14800	.02620	-.00910	.01530	.00140	.11690	.09260
.900	-4.000	-.06720	-.01240	-.00670	.01520	.00140	.12140	.09120
.900	-1.910	-.03610	-.03960	-.00640	.01340	.00100	.11750	.09320
.900	.230	.01990	-.07770	-.00620	.01130	.00060	.11450	.09270
.900	.240	.02390	-.08200	-.00690	.01230	.00060	.11250	.09340
.900	2.400	.07840	-.12900	-.00590	.00810	.00060	.11250	.09030
.900	4.510	.13590	-.17710	-.00970	.01440	-.00040	.11210	.08610
.900	6.730	.19340	-.21300	-.00860	.01210	-.00090	.10600	.08620
.900	8.900	.25590	-.25660	-.01290	.01610	-.00120	.10110	.08590
GRADIENT		.02905	-.01948	.00002	-.00028	-.00019	-.00110	-.00042

DATE 26 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 11

MSFC 558 (MAGF) NR ATP (01)/(T3)(81)

(R78010) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 DREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

BETA = .000 ORBINC = .000
 MACH = .900 ELEVON = -20.000
 DELZ/D = -1.000

RUN NO. 1024/0 RN/L = 0.21 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-8.560	-29390	.20780	-.01120	.01170	.00060	.12130	.10150
.000	-8.330	-21720	.14820	-.00870	.01000	.00120	.12590	.09640
.000	-4.100	-14930	.10450	-.00950	.01250	.00100	.12850	.09080
.000	-1.940	-0.6810	.06210	-.01050	.01440	.00080	.13010	.08730
.000	.230	-0.1920	.00020	-.00780	.01080	.00080	.12190	.08660
.000	.240	-.01660	-.00110	-.00640	.00820	.00080	.11920	.08130
.000	2.430	.05700	-.07410	-.00800	.01220	-.00010	.11690	.08660
.000	4.570	.12080	-.12950	-.00970	.01530	-.00090	.11990	.08230
.000	6.790	.16980	-.18010	-.00680	.01010	-.00140	.11490	.08130
.000	8.940	.25950	-.23320	-.00680	.01040	-.00190	.11030	.07710
GRADIENT		.03157	-.02784	.00010	.00016	-.00022	-.00140	-.00070

RUN NO. 1025/0 RN/L = 0.20 GRADIENT INTERVAL = -3.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.900	-8.510	-24910	.13480	-.00440	.01080	.00080	.11890	.08210
.900	-8.300	-17100	.08680	-.01010	.00990	.00070	.12420	.08620
.900	-4.100	-11150	.03440	-.00990	.01120	.00090	.12660	.08400
.900	-1.900	-.05200	-.00280	-.01120	.01460	.00080	.12280	.08720
.900	.250	.01330	-.05380	-.00770	.00970	.00010	.11930	.08640
.900	2.420	.07990	-.12100	-.00870	.01120	-.00040	.11620	.08690
.900	4.580	.14700	-.17380	-.00900	.00860	-.00080	.11550	.08580
.900	6.790	.20720	-.21430	-.00480	.00960	-.00160	.11120	.08450
.900	8.940	.28420	-.23120	-.00920	.01210	-.00220	.10630	.08270
GRADIENT		.02993	-.02484	.00047	-.00040	-.00020	-.00142	.00015

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 12

MSFC 558 (MASF) NR ATP (O1)/(T3) (S1)

(R78011) (28 JAN 73)

PARAMETRIC DATA

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

BETA = .000 ORBINC = 2.000
 MACH = .900 ELEVON = 10.000
 DELZ/D = -.520

RUN NO. 1076/0 RN/L = 6.17 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-8.000	-.06170	.09030	-.01040	.00680	-.00150	.05640	.04440
.000	-8.000	-.01010	-.00210	-.01070	.00680	-.00150	.05610	.04410
.000	-4.000	.06450	-.05590	-.01190	.00750	-.00190	.05990	.04390
.000	-2.000	.14250	-.11120	-.01110	.00720	-.00200	.06150	.04440
.000	.000	.21500	-.16160	-.01110	.00710	-.00160	.05980	.04420
.000	2.000	.30050	-.22310	-.01230	.00630	-.00120	.05620	.04300
.000	4.000	.39320	-.29110	-.01350	.00930	-.00090	.05620	.04210
.000	6.000	.47550	-.35060	-.01350	.00910	-.00090	.05380	.04380
.000	8.000	.54460	-.40110	-.01330	.00690	-.00070	.05440	.04570
GRADIENT		.04077	-.02911	-.00022	.00023	.00014	-.00053	-.00023

RUN NO. 1077/0 RN/L = 6.17 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.900	-8.000	-.10630	.07660	-.00930	.00590	-.00210	.05470	.04090
.900	-8.000	-.02560	.01650	-.00930	.00560	-.00200	.05670	.04090
.900	-4.000	.05370	-.04250	-.01000	.00600	-.00200	.05680	.04090
.900	-2.000	.13670	-.10320	-.00930	.00590	-.00200	.05990	.04070
.900	.000	.22580	-.16740	-.01140	.00690	-.00180	.05720	.04240
.900	2.000	.32150	-.23660	-.01260	.00670	-.00200	.05570	.04280
.900	4.000	.40910	-.30080	-.01410	.00970	-.00130	.05440	.04260
.900	6.000	.48310	-.35200	-.01410	.00940	-.00140	.05190	.04390
.900	8.000	.54940	-.39680	-.01450	.00970	-.00100	.05140	.04550
GRADIENT		.04478	-.03249	-.00058	.00053	.00007	-.00063	.00026

DATE 29 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 13

MSFC 558 (MADP) NR ATP (O1)/(T3) (S1)

(R78012) (29 JAN 73)

REFERENCE DATA

BREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

BETA = .000 ORBINC = 2.000
 MACH = .900 ELEVON = 10.000
 DELZ/D = -1.000

PARAMETRIC DATA

RUN NO. 1081/0 RN/L = 6.30 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-8.000	-.14440	.09120	.00030	-.00170	.00000	.05330	.04200
.000	-8.000	-.06520	.03450	.00010	-.00190	-.00020	.05600	.04180
.000	-4.000	.01430	-.08230	.00000	-.00120	-.00040	.05670	.04170
.000	-2.000	.10070	-.06330	-.00160	.00020	-.00060	.06070	.04140
.000	.000	.19490	-.14980	-.00170	.00070	-.00020	.06070	.04170
.000	2.000	.28410	-.21280	-.00190	.00090	-.00010	.05770	.04110
.000	4.000	.38650	-.28670	-.00460	.00340	.00060	.05490	.04060
.000	6.000	.48450	-.35600	-.00560	.00450	.00040	.05140	.04120
.000	8.000	.58600	-.41330	-.00610	.00450	.00030	.05040	.04290
GRADIENT		.04639	-.03291	-.00047	.00049	.00008	-.00053	-.00012

RUN NO. 1082/0 RN/L = 6.29 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.900	-8.000	-.16080	.10820	.00130	-.00270	-.00040	.05310	.03980
.900	-8.000	-.07180	.04270	.00140	-.00290	-.00060	.05600	.03990
.900	-4.000	.01490	-.01990	-.00080	-.00060	-.00020	.05990	.04010
.900	-2.000	.11180	-.08900	-.00090	-.00070	-.00040	.05910	.04130
.900	.000	.20430	-.15710	-.00240	.00100	-.00040	.05710	.04120
.900	2.000	.29990	-.22390	-.00380	.00290	-.00040	.05400	.04080
.900	4.000	.40010	-.29510	-.00470	.00340	.00040	.05150	.04220
.900	6.000	.49320	-.36040	-.00500	.00360	.00010	.05070	.04420
.900	8.000	.57430	-.41700	-.00570	.00410	.00010		
GRADIENT		.04797	-.03424	-.00053	.00053	.00014	-.00054	.00010

DATE 29 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 14

MSF 558 (MAZF) NR ATP (O1)/(T3)(S1)

(R78013) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

BETA = .000 ORBTHC = .000
 MACH = 1.800 ELEVON = .000
 DELZ/D = -.520

RUN NO. 1072/0 RMVL = 6.58 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
-.900	-6.000	.21120	.18320	-.00610	.00500	-.00060	.06640	.05280
-.900	-6.000	.12750	.11690	-.00650	.00490	-.00060	.06440	.05400
-.900	-4.000	.04710	.03600	-.00780	.00420	-.00060	.06340	.05510
-.900	-2.000	.03380	.00300	-.00790	.00400	-.00100	.06300	.05390
-.900	0.000	.13040	.07530	-.00600	.00370	-.00060	.06620	.05410
-.900	2.000	.21790	-.1320	-.00620	.00410	-.00060	.06440	.05440
-.900	4.000	.31100	-.2. 40	-.00900	.00520	-.00020	.06490	.05590
-.900	6.000	.39740	-.27920	-.01010	.00660	.00000	.06410	.05530
-.900	8.000	.46900	-.33290	-.01030	.00710	.00020	.06350	.05540
GRADIENT		.04501	-.03411	-.00014	.00011	.00006	.00022	.00011

RUN NO. 1071/0 RMVL = 6.57 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-6.000	.22980	.21030	-.00740	.00480	-.00120	.06940	.05170
.000	-6.000	.15620	.15480	-.00790	.00480	-.00140	.06690	.05260
.000	-4.000	.07670	.09370	-.00640	.00480	-.00120	.06660	.05240
.000	-2.000	.01180	.08530	-.00660	.00510	-.00100	.06680	.05000
.000	0.000	.11080	-.04210	-.00980	.00990	-.00090	.06680	.04740
.000	2.000	.20770	-.12710	-.00990	.00990	-.00070	.06680	.04430
.000	4.000	.30340	-.20020	-.00990	.00820	-.00060	.06430	.04550
.000	6.000	.38420	-.26030	-.01070	.00700	.00000	.06180	.04620
.000	8.000	.43380	-.31190	-.01130	.00740	-.00020	.06030	.04660
GRADIENT		.04781	-.03701	-.00020	.00018	.00007	-.00003	-.00006

RUN NO. 1073/0 RMVL = 6.56 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.900	-6.000	.21200	.19300	-.00570	.00270	-.00140	.06590	.04900
.900	-6.000	.13140	.13310	-.00570	.00290	-.00190	.06390	.05040
.900	-4.000	.04940	.07110	-.00600	.00310	-.00230	.06190	.05090
.900	-2.000	.03540	.00660	-.00740	.00320	-.00180	.06080	.05030
.900	0.000	.13210	-.06740	-.00630	.00400	-.00180	.06490	.05230
.900	2.000	.22110	-.13490	-.00670	.00340	-.00130	.06580	.05300
.900	4.000	.30790	-.20030	-.00960	.00610	-.00130	.06680	.04920
.900	6.000	.34610	-.26010	-.01130	.00740	-.00070	.06420	.04920
.900	8.000	.43460	-.31430	-.01200	.00630	-.00030	.06330	.04930
GRADIENT		.04902	-.03419	-.00050	.00011	.00017	-.00018	-.00009

DATE 20 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 18

MSFC 558 (MASS) NR ATP (O1)/(T3) (S1)

(R78014) (20 JAN 73)

REFERENCE DATA

BREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1326.0000 INCHES YMRP = .0000
 BREF = 1326.0000 INCHES ZMRP = -81.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

BETA = .000 ORBINC = .000
 MACH = 1.200 ELEVON = .000
 DELZ/D = -1.000

RUN NO. 1084/0 RNL = 6.55 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CLL	CAF	CAB
-1.000	-8.000	.28530	.29140	-.00020	-.00180	.00110	.06390	.05400
-1.000	-8.000	-.18510	.15540	.00090	-.00240	.00080	.06410	.05420
-1.000	-4.000	-.06630	.06270	.00000	-.00190	.00040	.06400	.05490
-1.000	-2.000	.00990	.00880	-.00190	-.00060	.00030	.06610	.05430
-1.000	.000	.11660	-.07050	-.00140	-.00120	.00070	.06730	.05550
-1.000	2.000	.21690	-.14470	-.00020	-.00060	.00090	.06660	.05460
-1.000	4.000	.31880	-.21880	-.00240	.00120	.00070	.06620	.05730
-1.000	6.000	.41290	-.28500	-.00330	.00290	.00080	.06600	.05730
-1.000	8.000	.49330	-.34140	-.00420	.00390	.00070	.06600	.05730
GRADIENT		.09106	-.03780	-.00017	.00031	.00008	.00034	.00023

RUN NO. 1085/0 RNL = 6.57 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CLL	CAF	CAB
-.500	-8.000	-.31470	.26380	.00190	-.00310	.00070	.06120	.05200
-.500	-8.000	-.22000	.19330	.00120	-.00290	.00070	.06350	.05000
-.500	-4.000	-.12160	.11780	.00040	-.00210	.00050	.06690	.04670
-.500	-2.000	-.01940	.03980	.00000	-.00140	.00090	.06790	.04500
-.500	.000	.08090	-.04470	-.00100	-.00040	.00040	.06780	.04570
-.500	2.000	.20130	-.12930	-.00080	-.00030	.00060	.06630	.04700
-.500	4.000	.31600	-.21680	-.00160	.00070	.00130	.06480	.04900
-.500	6.000	.42010	-.29460	-.00330	.00290	.00130	.06310	.05100
-.500	8.000	.50990	-.35990	-.00430	.00360	.00110	.06180	.05100
GRADIENT		.03479	-.04191	-.00024	.00033	.00008	-.00031	.00040

RUN NO. 1087/0 RNL = 6.51 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CLL	CAF	CAB
.000	-8.000	-.30390	.29630	.00190	-.00350	.00030	.06130	.05020
.000	-8.000	-.21180	.16720	.00200	-.00350	.00020	.05990	.05100
.000	-4.000	-.11710	.11610	.00140	-.00260	.00010	.05780	.05150
.000	-2.000	-.01790	.04130	.00040	-.00160	.00020	.05610	.05150
.000	.000	.09030	-.04020	.00020	-.00110	.00030	.02480	.05040
.000	2.000	.19410	-.12020	-.00020	-.00040	.00040	.05530	.04900
.000	4.000	.30300	-.20830	-.00130	.00100	.00080	.05660	.04470
.000	6.000	.40420	-.27760	-.00410	.00320	.00110	.05430	.04300
.000	8.000	.49430	-.34300	-.00520	.00480	.00100	.05730	.04320
GRADIENT		.09261	-.03990	-.00032	.00043	.00011	.00004	-.00077

DATE 29 MAR '73

SOURCE DATA TABULATION, MAFC-TWT-550

PAGE 16

MAFC 550 (MAFP) NR ATP (01)/(T3) (81)

(R78014) (29 JAN 73)

REFERENCE DATA

BREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1320.0000 INCHES YMRP = .0000
 BREF = 1320.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

BETA = .000 ORBINC = .000
 MACH = 1.200 ELEVON = .000
 DELZ/D = -1.000

RUN NO. 1084/0 RM/L = 6.74 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.900	-6.000	-.26090	.23170	.00180	-.00370	.00090	.08090	.05240
.900	-6.000	-.18510	.16000	.00180	-.00370	.00040	.05990	.05360
.900	-4.000	-.09130	.09000	.00140	-.00320	.00000	.05760	.05490
.900	-2.000	.00430	.01930	.00110	-.00240	-.00010	.05510	.05500
.900	.000	.10660	-.05630	-.00040	-.00070	.00000	.05520	.05340
.900	2.000	.21090	-.13420	-.00190	.00020	.00000	.05630	.05010
.900	4.000	.31310	-.20940	-.00230	.00190	.00010	.05410	.04910
.900	6.000	.40940	-.28640	-.00420	.00350	.00040	.05220	.04640
.900	8.000	.50020	-.34670	-.00640	.00650	.00080	.05120	.04790
GRADIENT	.05076	-.03765	-.00090	.00080	.00001	-.00029	-.00067	

RUN NO. 1085/0 RM/L = 6.96 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
1.000	-6.000	-.31000	.24970	.00340	-.00900	.00100	.06000	.05540
1.000	-6.000	-.21130	.17480	.00360	-.00910	.00090	.05920	.05430
1.000	-4.000	-.11070	.09910	.00390	-.00910	.00080	.05810	.05600
1.000	-2.000	-.06880	.02130	.00300	-.00440	.00100	.05890	.05460
1.000	.000	.10900	-.06430	.00280	-.00390	.00080	.05900	.05340
1.000	2.000	.21580	-.14750	.00210	-.00270	.00060	.05690	.05310
1.000	4.000	.32640	-.22990	.00080	-.00090	.00060	.05370	.05330
1.000	6.000	.41960	-.29700	-.00120	.00130	.00080	.05090	.05320
1.000	8.000	.51630	-.36740	-.00370	.00360	.00070	.04960	.05290
GRADIENT	.05491	-.04134	-.00034	.00091	-.00004	-.00034	-.00043	

DATE 29 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 17

MSFC 558 (MA9F) NR ATP (O1)/(T3) (S1)

(R78045) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

BETA = .000 ORBINC = .000
 MACH = 1.200 ELEVON = .000
 DELZ/D = -1.500

RUN NO. 1046/0 RN/L = 6.66 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	COL	CAF	CAB
-1.000	-8.000	-.33670	.27530	.01030	-.00930	.00160	.05690	.05090
-1.000	-6.000	-.23090	.19470	.01010	-.00890	.00160	.06060	.04990
-1.000	-4.000	-.12170	.11150	.00920	-.00800	.00150	.06400	.04740
-1.000	-2.000	-.01090	.02710	.00750	-.00640	.00140	.06860	.04410
-1.000	.000	.10690	-.06170	.00610	-.00490	.00140	.07230	.04150
-1.000	2.000	.22080	-.14720	.00520	-.00390	.00130	.06960	.04420
-1.000	4.000	.33460	-.23180	.00450	-.00300	.00100	.06640	.04720
-1.000	6.000	.44590	-.31210	.00360	-.00230	.00130	.06570	.04870
-1.000	8.000	.54550	-.38330	.00200	-.00120	.00130	.06630	.04970
GRADIENT		.05723	-.04304	-.00056	.00063	-.00005	.00029	-.00001

RUN NO. 1047/0 RN/L = 6.69 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	COL	CAF	CAB
-.900	-8.000	-.35230	.29150	.01190	-.01070	.00150	.05720	.05060
-.900	-6.000	-.23140	.21620	.01170	-.01020	.00140	.05710	.05070
-.900	-4.000	-.14740	.13810	.01070	-.00910	.00150	.05810	.04930
-.900	-2.000	-.03880	.05600	.00630	-.00680	.00140	.06020	.04630
-.900	.000	.07730	-.03190	.00720	-.00560	.00150	.06350	.04230
-.900	2.000	.19660	-.12290	.00610	-.00450	.00160	.06260	.04250
-.900	4.000	.31250	-.21080	.00410	-.00240	.00190	.06100	.04320
-.900	6.000	.42120	-.29030	.00240	-.00120	.00110	.05870	.04450
-.900	8.000	.52400	-.36490	.00090	-.00020	.00060	.05670	.04600
GRADIENT		.05777	-.04381	-.00077	.00078	.00002	.00041	-.00060

RUN NO. 1046/0 RN/L = 6.73 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	COL	CAF	CAB
.000	-8.000	-.33650	.27290	.01180	-.01070	.00170	.05870	.05220
.000	-6.000	-.23240	.19570	.01120	-.00990	.00120	.05730	.05370
.000	-4.000	-.12960	.11980	.00980	-.00840	.00100	.05550	.05430
.000	-2.000	-.02780	.04460	.00630	-.00680	.00090	.05500	.05230
.000	.000	.08170	-.03590	.00710	-.00530	.00120	.05980	.04890
.000	2.000	.19310	-.11940	.00560	-.00360	.00130	.05660	.04570
.000	4.000	.31460	-.21150	.00360	-.00160	.00160	.05440	.04460
.000	6.000	.42710	-.29300	.00120	.00010	.00150	.05160	.04470
.000	8.000	.52610	-.36810	-.00070	.00160	.00100	.05000	.04520
GRADIENT		.05546	-.04133	-.00076	.00084	.00008	-.00002	-.00130

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 10

MSFC 558 (MA9F) NR ATP (O1)/(T3) (S1)

(R78015) (29 JAN 73)

REFERENCE DATA

BREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1326.0000 INCHES YMRP = .0000
 BREF = 1326.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

BETA = .000 ORBINC = .000
 MACH = 1.200 ELEVON = .000
 DELZ/D = -1.500

RUN NO. 1045/0 RN/L = 6.69 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.500	-6.000	-.33560	.26790	.01330	-.01190	.00240	.05670	.05460
.500	-6.000	-.22840	.18760	.01260	-.01110	.00200	.05740	.05600
.500	-4.000	-.12230	.10820	.01130	-.00970	.00150	.05620	.05650
.500	-2.000	-.01610	.02950	.00950	-.00780	.00110	.05460	.05590
.500	.000	.09610	-.05340	.00720	-.00570	.00060	.05640	.05200
.500	2.000	.20800	-.13690	.00560	-.00390	.00090	.05550	.04950
.500	4.000	.32090	-.22080	.00410	-.00270	.00070	.05200	.04610
.500	6.000	.43140	-.30250	.00220	-.00170	.00130	.04940	.04720
.500	8.000	.53710	-.37850	-.00020	.00170	.00130	.04600	.04700
GRADIENT		.05552	-.04122	-.00090	.00096	-.00009	-.00038	-.00116

RUN NO. 1044/0 RN/L = 6.69 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
1.000	-6.000	-.36460	.29290	.01400	-.01230	.00210	.05970	.05560
1.000	-6.000	-.25630	.21010	.01340	-.01160	.00190	.05980	.05570
1.000	-4.000	-.14670	.12690	.01220	-.01040	.00160	.05990	.05570
1.000	-2.000	-.03720	.04420	.01100	-.00900	.00170	.06060	.05490
1.000	.000	.07910	-.04330	.00990	-.00770	.00160	.06530	.04920
1.000	2.000	.19930	-.13380	.00840	-.00620	.00140	.06350	.04920
1.000	4.000	.31360	-.21960	.00630	-.00430	.00080	.05840	.05040
1.000	6.000	.42660	-.30290	.00430	-.00250	.00110	.05300	.05050
1.000	8.000	.53660	-.38320	.00190	.00010	.00110	.05080	.04930
GRADIENT		.05765	-.04355	-.00072	.00075	-.00011	-.00000	-.00062

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-556

PAGE 19

MSFC 556 (MA9F) NR ATP (O1)/(T3)(S1)

(R76016) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1326.0000 INCHES YMRP = .0000
 BREF = 1326.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

BETA	=	.000	ORBINC	=	2.000
MACH	=	1.200	ELEVON	=	.000
DELZ/D	=	-.920			

RUN NO. 1001/0 RN/L = 6.58 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
-.500	-8.000	-.38620	.31740	-.00340	.00040	.00060	.06900	.04950
-.500	-6.000	-.29130	.24420	-.00340	.00020	-.00010	.06850	.04920
-.500	-4.000	-.20010	.17400	-.00390	.00040	-.00060	.06780	.05000
-.500	-2.000	-.11210	.10710	-.00410	.00010	-.00070	.06800	.04980
-.500	.000	-.01400	.03190	-.00400	.00040	-.00090	.07030	.04820
-.500	2.000	.07790	-.03630	-.00370	.00030	-.00070	.07110	.04820
-.500	4.000	.16420	-.12060	-.00270	.00000	-.00100	.06940	.05110
-.500	6.000	.26060	-.19420	-.00320	.00060	.00020	.06880	.05220
-.500	8.000	.36130	-.25460	-.00310	.00090	.00040	.06460	.05290
GRADIENT		.04793	-.03673	.00014	-.00003	.00005	.00032	.00003

RUN NO. 1002/0 RN/L = 6.60 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-8.000	-.38490	.30470	-.00410	.00210	-.00020	.07160	.04570
.000	-6.000	-.28650	.24720	-.00360	.00160	-.00040	.06510	.05080
.000	-4.000	-.20630	.16640	-.00370	.00110	-.00030	.06130	.05280
.000	-2.000	-.12470	.12410	-.00400	.00150	-.00010	.06460	.04820
.000	.000	-.02590	.04620	-.00350	.00070	-.00020	.06940	.04300
.000	2.000	.07060	-.02640	-.00360	.00090	-.00010	.07500	.03830
.000	4.000	.16850	-.10220	-.00290	.00070	.00020	.06870	.03940
.000	6.000	.26700	-.17760	-.00330	.00120	.00010	.06430	.04100
.000	8.000	.35920	-.23960	-.00280	.00120	.00020	.06120	.04270
GRADIENT		.04723	-.03638	.00010	-.00007	.00005	.00116	-.00183

RUN NO. 1003/0 RN/L = 6.61 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.500	-8.000	-.38400	.30190	-.00340	.00070	.00040	.06510	.04450
.500	-6.000	-.27470	.23260	-.00310	.00010	-.00040	.06710	.04670
.500	-4.000	-.18500	.16490	-.00260	-.00040	-.00110	.06060	.04800
.500	-2.000	-.09600	.09680	-.00240	-.00060	-.00040	.05970	.04690
.500	.000	.00290	.02490	-.00240	.00000	-.00040	.05900	.04660
.500	2.000	.06910	-.03960	-.00190	-.00030	-.00050	.06190	.04560
.500	4.000	.17970	-.10690	-.00290	.00060	-.00010	.06190	.04560
.500	6.000	.27100	-.17830	-.00360	.00170	.00000	.05930	.04560
.500	8.000	.35460	-.24130	-.00410	.00240	.00000	.05610	.04620
GRADIENT		.04572	-.03426	-.00000	.00013	.00011	-.00001	-.00029

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 20

MSFC 558 (MA9F) NR ATP (O1)/(T3)(S1)

(R78017) (29 JAN 73)

REFERENCE DATA

PARAMETRIC DATA

BREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

BETA = .000 ORBINC = 2.000
 MACH = 1.200 ELEVON = .000
 DELZ/D = -1.000

RUN NO. 1034/0 RN/L = 6.69 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
-1.000	-6.000	.46660	.37470	.00350	-.00520	.00250	.05700	.05050
-1.000	-6.000	.35710	.29090	.00480	-.00600	.00240	.05910	.05020
-1.000	-4.000	.24280	.20200	.00570	-.00660	.00170	.05910	.05180
-1.000	-2.000	.13640	.12190	.00600	-.00650	.00100	.06340	.04980
-1.000	.000	.02910	.03920	.00560	-.00600	.00080	.06750	.04790
-1.000	2.000	.08270	-.04500	.00590	-.00570	.00140	.06950	.04800
-1.000	4.000	.19590	-.13100	.00450	-.00430	.00190	.06920	.04840
-1.000	6.000	.30260	-.21000	.00480	-.00380	.00130	.06720	.05050
-1.000	8.000	.39430	-.27630	.00470	-.00340	.00110	.06560	.05190
GRADIENT		.05492	-.04164	-.00012	.00027	-.00000	.00131	-.00043

RUN NO. 1026/0 RN/L = 6.60 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
-.500	-6.000	.44590	.36370	.00490	-.00630	.00140	.05710	.05050
-.500	-6.000	.34980	.29090	.00530	-.00630	.00160	.06000	.04920
-.500	-4.000	.24680	.21380	.00560	-.00630	.00160	.06510	.04490
-.500	-2.000	.14520	.13460	.00610	-.00630	.00120	.07040	.04010
-.500	.000	.03320	.04790	.00430	-.00490	.00070	.06970	.04100
-.500	2.000	.08160	-.03990	.00420	-.00420	.00130	.06750	.04360
-.500	4.000	.20010	-.12990	.00340	-.00320	.00190	.06460	.04660
-.500	6.000	.30900	-.21170	.00250	-.00200	.00160	.06340	.04720
-.500	8.000	.40340	-.28260	.00160	-.00110	.00130	.06180	.04810
GRADIENT		.05623	-.04309	-.00032	.00042	.00004	-.00020	.00036

RUN NO. 1027/0 RN/L = 6.61 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-6.000	.44680	.36120	.00350	-.00550	.00140	.05740	.05010
.000	-6.000	.35120	.29010	.00520	-.00650	.00120	.05700	.05040
.000	-4.000	.25320	.21670	.00610	-.00670	.00090	.05530	.05140
.000	-2.000	.13210	.14120	.00610	-.00660	.00060	.05440	.05140
.000	.000	.04620	.06260	.00620	-.00620	.00120	.05390	.05070
.000	2.000	.05550	-.01720	.00590	-.00560	.00170	.05360	.05010
.000	4.000	.17660	-.11010	.00420	-.00360	.00190	.06010	.04280
.000	6.000	.28640	-.19420	.00360	-.00290	.00160	.06130	.04090
.000	8.000	.38410	-.26450	.00340	-.00240	.00140	.05990	.04160
GRADIENT		.05336	-.04060	-.00020	.00034	.00014	.00044	-.00093

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 21

MSFC 558 (MA9F) NR ATP (01) / (T3) (S1)

(R78017) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

BETA = .000 ORBINC = 2.000
 MACH = 1.200 ELEVON = .000
 DELZ/D = -1.000

PARAMETRIC DATA

RUN NO. 1026/0 RN/L = 6.61 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CDL	CAF	CAB
.500	-6.000	-.43040	.34050	.00600	-.00750	.00260	.05710	.05350
.500	-6.000	-.32060	.26440	.00580	-.00710	.00240	.05770	.05340
.500	-4.000	-.22740	.18860	.00510	-.00660	.00170	.05640	.05400
.500	-2.000	-.13100	.11740	.00670	-.00780	.00100	.05180	.05660
.500	.000	-.02770	.04240	.00580	-.00610	.00020	.05190	.05540
.500	2.000	.07450	-.03320	.00450	-.00460	.00070	.05610	.04700
.500	4.000	.18010	-.11250	.00490	-.00370	.00120	.05620	.04580
.500	6.000	.29090	-.19570	.00340	-.00240	.00100	.05570	.04430
.500	8.000	.39080	-.26990	.00200	-.00090	.00100	.05410	.04470
GRADIENT	.05102	-.03764	-.00017	.00044	-.00007	.00030		-.00132

RUN NO. 1033/0 RN/L = 6.60 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CDL	CAF	CAB
1.000	-6.000	-.45120	.35470	.00540	-.00690	.00250	.05290	.05690
1.000	-6.000	-.35360	.26080	.00690	-.00600	.00260	.05190	.05680
1.000	-4.000	-.24870	.20140	.00770	-.00650	.00260	.05040	.05900
1.000	-2.000	-.14600	.12420	.00610	-.00650	.00250	.05000	.05820
1.000	.000	-.03690	.04300	.00780	-.00790	.00150	.05090	.05680
1.000	2.000	.07420	-.04090	.00730	-.00690	.00150	.05650	.05020
1.000	4.000	.18800	-.12660	.00560	-.00500	.00130	.05510	.04980
1.000	6.000	.29880	-.20990	.00530	-.00380	.00060	.05180	.05040
1.000	8.000	.40230	-.28480	.00360	-.00180	.00090	.04990	.04970
GRADIENT	.05468	-.04105	-.00025	.00043	-.00017	.00079		-.00132

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-556

PAGE 22

MSFC 556 (MA9F) NR ATP (O1)/(T3)(S1)

(R78018) (29 JAN 73)

REFERENCE DATA

PARAMETRIC DATA

REF = 3220.0000 SQ.FT.	XMRP = .0000	BETA = .000	ORBINC = 2.000
REF = 1326.0000 INCHES	YMRP = .0000	MACH = 1.200	ELEVON = .000
REF = 1326.0000 INCHES	ZMRP = -61.5000 INCHES	DELZ/D = -1.500	
SCALE = 100.0000 PER			

RUN NO. 1042/0 RN/L = 6.61 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
-1.000	-6.000	-.47840	.38540	.01640	-.01400	.00240	.05500	.04630
-1.000	-6.000	-.37510	.30790	.01700	-.01410	.00210	.05610	.04610
-1.000	-4.000	-.26950	.22780	.01580	-.01300	.00210	.05950	.04590
-1.000	-2.000	-.15720	.14270	.01430	-.01140	.00210	.06360	.04210
-1.000	.000	-.03730	.05130	.01310	-.01000	.00210	.06610	.03690
-1.000	2.000	.07900	-.03700	.01070	-.00600	.00210	.06520	.04170
-1.000	4.000	.19630	-.12820	.00360	-.00590	.00190	.06260	.04470
-1.000	6.000	.31710	-.21740	.00690	-.00610	.00150	.06080	.04610
-1.000	8.000	.42680	-.29860	.00680	-.00630	.00120	.05890	.04800
GRADIENT		.05859	-.04458	-.00090	.00068	-.00002	.00039	-.00014

RUN NO. 1039/0 RN/L = 6.59 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
-.500	-6.000	-.47000	.37740	.01620	-.01430	.00200	.05520	.04670
-.500	-6.000	-.36760	.30140	.01720	-.01450	.00200	.05580	.04680
-.500	-4.000	-.26330	.22320	.01690	-.01380	.00190	.05500	.04940
-.500	-2.000	-.15730	.14410	.01510	-.01210	.00160	.05490	.04880
-.500	.000	-.03710	.05310	.01320	-.00990	.00230	.05970	.04430
-.500	2.000	.07860	-.03400	.01240	-.00690	.00250	.06490	.03890
-.500	4.000	.19070	-.11890	.01050	-.00710	.00190	.06230	.03990
-.500	6.000	.29810	-.19920	.00800	-.00540	.00140	.05990	.04120
-.500	8.000	.40220	-.27570	.00650	-.00440	.00120	.05630	.04200
GRADIENT		.05719	-.04311	-.00078	.00043	.00004	.00123	-.00146

RUN NO. 1038/0 RN/L = 6.58 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-6.000	-.46940	.37100	.01560	-.01390	.00300	.05580	.05120
.000	-6.000	-.36170	.29090	.01620	-.01390	.00260	.05640	.05130
.000	-4.000	-.25070	.20890	.01530	-.01290	.00190	.05420	.05310
.000	-2.000	-.14710	.13240	.01430	-.01170	.00110	.05230	.05410
.000	.000	-.03390	.04920	.01310	-.01000	.00150	.05310	.05070
.000	2.000	.07880	-.03460	.01170	-.00830	.00150	.05690	.04290
.000	4.000	.19330	-.12070	.01060	-.00710	.00150	.05630	.04110
.000	6.000	.30990	-.20730	.00810	-.00500	.00220	.05410	.04260
.000	8.000	.41750	-.28720	.00520	-.00290	.00220	.05110	.04360
GRADIENT		.05568	-.04132	-.00080	.00075	-.00002	.00074	-.00176

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 23

MSFC 558 (MA9F) NR ATP (O1)/(T3)(S1)

(RT8016) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

BETA = .000 ORBINC = 2.000
 MACH = 1.200 ELEVON = .000
 DELZ/D = -1.500

PARAMETRIC DATA

RUN NO. 1035/0 RNL = 6.00 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.900	-6.000	-.48200	.37800	.01670	-.01500	.00370	.05370	.05660
.900	-6.000	-.37470	.29710	.01760	-.01540	.00350	.05260	.05700
.900	-4.000	-.26410	.21380	.01820	-.01520	.00300	.05070	.05810
.900	-2.000	-.15280	.13030	.01650	-.01370	.00230	.04670	.05890
.900	.000	-.03560	.04410	.01440	-.01130	.00160	.05000	.05560
.900	2.000	.07350	-.03730	.01320	-.00960	.00150	.05570	.04770
.900	4.000	.16860	-.12330	.01130	-.00740	.00120	.05460	.04470
.900	6.000	.30940	-.21420	.00770	-.00440	.00110	.05170	.04390
.900	8.000	.42190	-.29750	.00480	-.00210	.00120	.04840	.04470
GRADIENT		.05658	-.04209	-.00066	.00098	-.00022	.00074	-.00168

RUN NO. 1043/0 RNL = 6.00 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
1.000	-6.000	-.49650	.39290	.01750	-.01530	.00300	.05620	.05460
1.000	-6.000	-.36950	.31000	.01790	-.01540	.00300	.05620	.05460
1.000	-4.000	-.27620	.22400	.01760	-.01490	.00250	.05670	.05430
1.000	-2.000	-.16600	.14050	.01760	-.01420	.00210	.05620	.05310
1.000	.000	-.05090	.05390	.01620	-.01230	.00210	.06390	.04600
1.000	2.000	.07060	-.03780	.01450	-.01070	.00180	.06320	.04740
1.000	4.000	.16970	-.12720	.01210	-.00900	.00110	.05860	.04900
1.000	6.000	.30550	-.21390	.00970	-.00640	.00100	.05430	.04860
1.000	8.000	.42140	-.30020	.00720	-.00360	.00100	.05150	.04780
GRADIENT		.05643	-.04403	-.00070	.00077	-.00015	.00044	-.00061

DATE 26 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 84

MSFC 558 (MA9F) NR ATP (O1)/(T3)(S1)

(R78019) (29 JAN 73)

REFERENCE DATA

PARAMETRIC DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

BETA = .000 CRBINC = .000
 MACH = 1.200 ELEVON = 10.000
 DEL2/D = -.520

RUN NO. 1006/0 RN/L = 6.61 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
-.500	-6.820	-.34680	.28430	-.00640	.00910	-.00030	.17780	.09500
-.500	-6.510	-.25340	.20250	-.00950	.01150	-.00040	.17950	.08890
-.500	-4.240	-.17760	.14690	-.00790	.01060	.00000	.18170	.06160
-.500	-2.000	-.11150	.10160	-.01060	.01390	-.00030	.16330	.07500
-.500	.240	-.04940	.06490	-.01050	.01360	-.00050	.16060	.06630
-.500	2.320	.02320	.01090	-.00600	.01200	-.00130	.17560	.05870
-.500	4.740	.06950	-.03260	-.00460	.00480	-.00170	.17870	.05190
-.500	7.050	.16430	-.06100	-.00370	.00290	-.00190	.17430	.04760
-.500	9.290	.24430	-.14040	-.00940	.00520	-.00240	.17060	.04350
GRADIENT		.02976	-.02003	.00042	-.00080	-.00020	-.00061	-.00340

RUN NO. 1005/0 RN/L = 6.61 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-6.000	-.23850	.18410	-.00730	.00480	-.00120	.07650	.05550
.000	-6.000	-.15250	.11900	-.00630	.00370	-.00130	.07730	.05700
.000	-4.000	-.06300	.03020	-.00610	.00330	-.00130	.07850	.05710
.000	-2.000	.02640	-.01960	-.00550	.00310	-.00140	.08450	.05240
.000	.000	.13590	-.10520	-.00590	.00370	-.00110	.09310	.04590
.000	2.000	.24410	-.10970	-.00650	.00430	-.00070	.09450	.04600
.000	4.000	.34840	-.20910	-.00690	.00470	-.00090	.09380	.04700
.000	6.000	.43340	-.33230	-.00640	.00480	-.00050	.09240	.04660
.000	8.000	.50790	-.38690	-.00650	.00500	-.00030	.09230	.04660
GRADIENT		.05202	-.04043	-.00013	.00020	.00007	.00197	-.00133

RUN NO. 1004/0 RN/L = 6.60 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.900	-8.000	-.22930	.17340	-.00670	.00960	-.00160	.07190	.05600
.900	-8.000	-.13570	.10200	-.00600	.00490	-.00220	.07270	.05710
.900	.000	.14870	-.11370	-.00640	.00380	-.00280	.08160	.05230
.900	2.000	.24460	-.18600	-.00560	.00330	-.00230	.08580	.05050
.900	4.000	.34300	-.26090	-.00700	.00490	-.00200	.08650	.05130
.900	6.000	.44670	-.34180	-.00720	.00530	-.00160	.08670	.05020
.900	8.000	.53520	-.40440	-.00610	.00620	-.00100	.08540	.05010
GRADIENT		.04657	-.03660	-.00013	.00027	.00020	.00123	-.00029

DATE 28 MAR 73

PAGE 25

SOURCE DATA TABULATION, MSFC-TWT-558

MSFC 558 (MA9F) NR ATP (01)/(T3) (81)

(R78020) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

BETA = .000 ORBINC = .000
 MACH = 1.200 ELEVON = 10.000
 DELZ/D = -1.000

PARAMETRIC DATA

RUN NO. 1029/0 RN/L = 6.61 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-8.000	-.29290	.21790	.00000	-.00160	-.00010	.06150	.06310
.000	-6.000	-.19990	.14830	.00140	-.00260	-.00020	.06270	.06350
.000	-4.000	-.10530	.07700	.00280	-.00340	-.00050	.06380	.06330
.000	-2.000	-.00530	.00180	.00320	-.00340	-.00060	.06900	.05940
.000	.000	.10920	-.06570	.00260	-.00240	-.00040	.07920	.05090
.000	2.000	.22730	-.17680	.00090	-.00050	-.00010	.06530	.04630
.000	4.000	.34050	-.26330	.00030	.00020	-.00030	.06770	.04820
.000	6.000	.44590	-.34240	-.00060	.00140	-.00030	.06850	.04850
.000	8.000	.53980	-.41100	-.00220	.00270	-.00040	.06760	.04930
GRADIENT		.09621	-.04296	-.00034	.00050	.00005	.00321	-.00206

RUN NO. 1030/0 RN/L = 6.61 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.500	-8.000	-.26400	.20440	.00190	-.00300	.00090	.06750	.06130
.500	-6.000	-.16440	.12980	.00310	-.00360	.00040	.06910	.06210
.500	-4.000	-.06640	.05640	.00410	-.00460	-.00030	.06900	.06330
.500	-2.000	.01240	-.01640	.00330	-.00350	-.00060	.07040	.06240
.500	.000	.12310	-.09960	.00190	-.00160	-.00120	.07720	.05530
.500	2.000	.22640	-.17710	.00210	-.00100	-.00090	.07990	.05230
.500	4.000	.33680	-.25990	.00210	-.00040	-.00050	.06020	.05090
.500	6.000	.44360	-.34060	.00020	.00120	-.00080	.06160	.04890
.500	8.000	.54730	-.41770	-.00190	.00310	-.00010	.06240	.04840
GRADIENT		.09302	-.03966	-.00026	.00055	-.00005	.00159	-.00175

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 26

MSFC 558 (MA9F) NR ATP (O1)/(T3) (S1)

(R78021) (29 JAN 73)

REFERENCE DATA

BREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

BETA = .000 CRBINC = .000
 MACH = 1.200 ELEVON = -20.000
 DELZ/D = -.520

PARAMETRIC DATA

RUN NO. 1007/0 RN/L = 6.61 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
-.500	-6.840	-.35360	.29130	-.00680	.00660	-.00060	.18610	.10390
-.500	-6.520	-.25490	.20240	-.00570	.00640	-.00020	.18800	.10010
-.500	-4.250	-.17770	.14390	-.00690	.00640	.00000	.18960	.09490
-.500	-2.010	-.11150	.09630	-.00920	.01130	.00000	.19030	.09040
-.500	.200	-.04960	.05950	-.00940	.01160	-.00040	.18740	.08470
-.500	.220	-.04630	.05770	-.00880	.01130	-.00050	.18750	.08420
-.500	2.500	.02190	.00820	-.00580	.00640	-.00080	.18290	.07620
-.500	4.700	.08450	-.03330	-.00130	.00000	-.00090	.18540	.07280
-.500	7.010	.15730	-.06230	-.00370	.00160	-.00180	.18390	.07020
-.500	9.250	.23860	-.14360	-.00330	.00160	-.00210	.18030	.06890
GRADIENT		.02936	-.01975	.00069	-.00068	-.00012	-.00071	-.00252

RUN NO. 1008/0 RN/L = 6.80 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-6.870	-.32570	.23340	-.01200	.01570	.00040	.17550	.10750
.000	-6.550	-.23320	.15550	-.00960	.01390	.00070	.17860	.10590
.000	-4.260	-.15750	.09990	-.00990	.01400	.00090	.17740	.10340
.000	-2.010	-.09240	.05760	-.00910	.01210	.00060	.17630	.09660
.000	.190	-.03710	.02610	-.00620	.01090	.00050	.17590	.09730
.000	.200	-.03490	.02770	-.00830	.01010	.00030	.17560	.09640
.000	2.470	.02600	-.01260	-.00790	.01190	-.00020	.17220	.08960
.000	4.660	.08570	-.04870	-.00550	.00830	-.00060	.17380	.08270
.000	6.950	.14610	-.08520	-.00520	.00770	-.00120	.17100	.08210
.000	9.170	.22090	-.13750	-.00210	.00360	-.00130	.16860	.08110
GRADIENT		.02710	-.01646	.00049	-.00052	-.00017	-.00080	-.00227

RUN NO. 1009/0 RN/L = 6.61 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.900	-6.830	-.26530	.12690	-.02040	.02810	.00030	.16470	.10960
.900	-6.520	-.18440	.06700	-.01830	.02610	.00090	.16470	.10740
.900	-4.250	-.11490	.01960	-.01680	.02520	.00070	.16560	.10590
.900	-2.010	-.05730	-.01290	-.01700	.02610	.00010	.16430	.10450
.900	.200	.00360	-.04940	-.01330	.02210	.00060	.16310	.10420
.900	2.440	.05670	-.04420	-.01580	.02570	-.00010	.15920	.10310
.900	4.960	.11000	-.11740	-.01500	.02410	-.00050	.16030	.10000
.900	6.860	.17000	-.15260	-.01210	.01940	-.00100	.15770	.09840
.900	9.090	.23910	-.20270	-.01070	.01740	-.00140	.15340	.09690
GRADIENT		.02550	-.01942	.00022	-.00012	-.00014	-.00071	-.00060

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 27

MSFC 558 (MAKF) NR ATP (01)/(T3)(S1)

(078022) (29 JAN 73)

REFERENCE DATA

BREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1326.0000 INCHES YMRP = .0000
 BREF = 1326.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

BETA = .000 ORBINC = .000
 MACH = 1.200 ELEVON = -20.000
 DELZ/D = -1.000

PARAMETRIC DATA

RUN NO. 1032/0 RNL = 6.61 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-8.850	-.34060	.26830	-.00780	.00610	-.00030	.18340	.10260
.000	-8.530	-.24600	.18640	-.00730	.00680	.00010	.18590	.09900
.000	-4.240	-.16600	.12550	-.00660	.00620	.00020	.18590	.09430
.000	-1.990	-.09760	.07540	-.00700	.00640	.00010	.18670	.09290
.000	.230	-.03360	.03560	-.00400	.00390	-.00010	.18420	.08990
.000	.240	-.02930	.03230	-.00290	.00310	.00000	.18310	.08890
.000	2.490	.03480	-.01310	-.00410	.00640	-.00040	.18180	.08310
.000	4.090	.09560	-.04940	-.00220	.00300	-.00100	.18120	.07830
.000	7.010	.15990	-.08710	-.00310	.00280	-.00170	.18050	.07410
.000	9.260	.23790	-.13990	.00040	-.00200	-.00190	.17530	.07050
GRADIENT		.02935	-.01962	.00034	-.00055	-.00013	-.00064	-.00203

RUN NO. 1031/0 RNL = 6.61 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.900	-8.830	-.29880	.19570	-.01340	.01850	.00080	.17570	.10130
.900	-6.490	-.21420	.13010	-.01200	.01540	.00070	.17680	.10220
.900	-4.220	-.13920	.07630	-.00930	.01310	.00080	.17730	.09990
.900	-1.990	-.07620	.03490	-.00800	.01280	.00060	.17680	.09590
.900	.220	-.01690	-.00080	-.00780	.01190	.00040	.17510	.09480
.900	.240	-.01320	-.00130	-.00760	.01180	.00050	.17380	.09520
.900	2.490	.04320	-.03930	-.00680	.01470	.00000	.17220	.09060
.900	4.670	.09650	-.08700	-.00590	.00990	-.00070	.16880	.08960
.900	6.940	.15830	-.10310	-.00510	.00780	-.00110	.16620	.08590
.900	9.170	.22880	-.15170	-.00430	.00590	-.00190	.16440	.08460
GRADIENT		.02634	-.01621	.00031	-.00019	-.00017	-.00099	-.00116

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 20

MSFC 558 (MA9F) NR ATP (01)/(T3)(S1)

(R78023) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.9000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

BETA = .000 ORBINC = 2.000
 MACH = 1.800 ELEVON = 10.000
 DELZ/D = -.520

RUN NO. 1079/0 RN/L = 6.59 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-6.000	-.09350	.07870	-.00920	.00620	-.00270	.08130	.05850
.000	-6.000	-.01240	.01800	-.00920	.00600	-.00290	.08240	.05860
.000	-4.000	.08060	-.05690	-.01000	.00670	-.00220	.08570	.05870
.000	-2.000	.18030	-.13480	-.01040	.00710	-.00200	.08970	.05380
.000	.000	.27990	-.21210	-.01150	.00800	-.00180	.09110	.05290
.000	2.000	.37230	-.28220	-.01160	.00830	-.00130	.09220	.05200
.010	4.000	.48220	-.34990	-.01290	.00930	-.00100	.09290	.05070
.000	6.000	.54200	-.40880	-.01270	.00940	-.00080	.09200	.05100
.000	8.000	.60980	-.45720	-.01290	.00970	-.00060	.09170	.05190
GRADIENT	.04776	-.03667	-.00035	.00034	.00015	.00081	-.00069	

RUN NO. 1078/0 RN/L = 6.58 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.500	-6.000	-.06280	.08950	-.00650	.00510	-.00330	.07350	.05980
.500	-6.000	.00000	.00840	-.00660	.00510	-.00390	.07420	.06040
.500	-4.000	.06910	-.06200	-.00970	.00990	-.00420	.07590	.05950
.500	-2.000	.16420	-.13590	-.01020	.00630	-.00370	.07930	.05710
.500	.000	.28130	-.20940	-.01040	.00670	-.00310	.08260	.05490
.500	2.000	.37650	-.28290	-.01240	.00890	-.00300	.08400	.05500
.500	4.000	.48260	-.34660	-.01350	.01000	-.00180	.08610	.05350
.500	6.000	.57180	-.43330	-.01490	.01130	-.00120	.08500	.05310
.500	8.000	.64900	-.48600	-.01600	.01290	-.00100	.08330	.05320
GRADIENT	.04698	-.03774	-.00049	.00092	.00028	.00126	-.00070	

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 29

MSFC 558 (MA9F) NR ATP (O1)/(T3) (S1)

(R780E4) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

BETA = .000 CRBINC = 2.000
 MACH = 1.200 ELEVON = 10.000
 DELZ/D = -1.000

RUN NO. 1080/0 RN/L = 0.73 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAP	CAB
.000	-8.000	-.15340	.11990	-.00080	-.00070	-.00110	.01010	.00030
.000	-6.000	-.06420	.04840	-.00080	-.00090	-.00130	.07070	.06100
.000	-4.000	.03130	-.02410	-.00120	-.00010	-.00190	.07320	.09970
.000	-2.000	.13820	-.10580	-.00220	.00110	-.00140	.07840	.06910
.000	.000	.24780	-.19980	-.00410	.00290	-.00110	.04370	.05140
.000	2.000	.35660	-.27260	-.00530	.00420	-.00080	.06740	.04980
.000	4.000	.46730	-.35710	-.00650	.00560	-.00040	.06940	.04910
.000	6.000	.56620	-.42080	-.00740	.00650	-.00020	.06930	.04910
.000	8.000	.65410	-.49100	-.00830	.00740	-.00030	.06860	.04980
GRADIENT		.05457	-.04185	-.00068	.00072	.00014	.00209	-.00133

RUN NO. 1083/0 RN/L = 0.71 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAP	CAB
.900	-8.000	-.14020	.10070	.00010	-.00160	-.00070	.07240	.06170
.900	-6.000	-.04650	.03020	-.00040	-.00110	-.00120	.07330	.06250
.900	-4.000	.05100	-.04320	-.00130	-.00020	-.00170	.07490	.06170
.900	-2.000	.13400	-.12100	-.00200	.00060	-.00180	.07670	.05790
.900	.000	.23930	-.20090	-.00260	.00200	-.00180	.08090	.05450
.900	2.000	.34820	-.27740	-.00490	.00390	-.00190	.08130	.05320
.900	4.000	.46660	-.35980	-.00610	.00550	-.00110	.08110	.05200
.900	6.000	.57570	-.43710	-.00790	.00710	-.00090	.08000	.05110
.900	8.000	.67110	-.50570	-.01000	.00800	-.00030	.08260	.05140
GRADIENT		.05196	-.03906	-.00062	.00072	.00007	.00079	-.00120

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 30

MSFC 558 (MAGF) NR ATP (01)/(T3) (S1)

(R78025) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT.	XMRP = .0000	BETA = .000	ORBINC = .000
LREF = 1328.0000 INCHES	YMRP = .0000	MACH = 2.000	ELEVON = .000
BREF = 1328.0000 INCHES	ZMRP = -61.5000 INCHES	DELZ/D = -.520	
SCALE = 100.0000 PER			

PARAMETRIC DATA

RUN NO. 1121/0 RN/L = 6.81 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
-1.000	-6.000	-.18570	.13600	-.00230	.00210	-.00100	.07750	.02330
-1.000	-6.000	-.14070	.12260	-.00250	.00200	-.00090	.07150	.02500
-1.000	-4.070	-.08320	.07770	-.00300	.00200	-.00050	.06610	.02530
-1.000	-2.000	-.02050	.02930	-.00320	.00190	-.00010	.06470	.02590
-1.000	.000	.04290	-.01900	-.00310	.00220	.00070	.06120	.02590
-1.000	2.000	.10950	-.06930	-.00440	.00330	.00080	.06050	.02520
-1.000	4.000	.17850	-.12080	-.00360	.00300	.00090	.06000	.02560
-1.000	6.000	.23650	-.16390	-.00370	.00330	.00110	.06230	.02450
-1.000	8.000	.27090	-.18910	-.00320	.00300	.00100	.06270	.02490
GRADIENT		.03267	-.02476	-.00014	.00017	.00017	-.00102	.00001

RUN NO. 1122/0 RN/L = 6.81 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-6.000	-.13240	.10410	-.00440	.00450	-.00200	.06140	.02440
.000	-6.000	-.10350	.08190	-.00350	.00360	-.00120	.07540	.02560
.000	-4.000	-.05410	.04340	-.00340	.00340	-.00080	.07070	.02600
.000	-2.000	.00270	-.00080	-.00360	.00310	-.00030	.06590	.02670
.000	.000	.05920	-.04200	-.00340	.00270	.00000	.06210	.02730
.000	2.000	.12000	-.08480	-.00360	.00290	.00020	.06110	.02720
.000	4.000	.18980	-.13580	-.00410	.00330	.00000	.05920	.02760
.000	6.000	.25030	-.16040	-.00360	.00310	.00030	.05730	.02780
.000	8.000	.29530	-.21410	-.00350	.00220	.00040	.05570	.02780
GRADIENT		.03025	-.02211	-.00007	-.00002	.00006	-.00139	.00016

RUN NO. 1116/0 RN/L = 3.81 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
1.000	-6.000	-.19080	.14690	-.00170	.00210	-.00040	.05190	.02780
1.000	-6.000	-.14400	.11710	-.00240	.00270	-.00050	.06640	.02700
1.000	-4.000	-.10350	.06380	-.00310	.00290	-.00040	.06230	.02560
1.000	-2.000	-.05280	.04300	-.00360	.00310	-.00020	.07610	.02470
1.000	.000	.00490	-.00410	-.00360	.00310	.00010	.07450	.02410
1.000	2.000	.07260	-.05290	-.00260	.00220	.00040	.07170	.02400
1.000	4.000	.14300	-.11130	-.00270	.00240	.00010	.06850	.02400
1.000	6.000	.22000	-.17080	-.00310	.00250	.00010	.06620	.02340
1.000	8.000	.26240	-.21860	-.00320	.00270	.00020	.06290	.02310
GRADIENT		.03092	-.02449	-.00009	-.00011	.00008	-.00170	-.00014

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 31

MSFC 558 (MA9F) NR ATP (O1)/(T3)(S1)

(R78025) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1320.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

BETA = .000 ORBINC = .000
 MACH = 2.000 ELEVON = .000
 DELZ/D = -.320

RUN NO. 1119/0 RN/L = 6.80 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
2.000	-6.000	-.10590	.08400	.00140	-.00070	-.00080	.09320	.02590
2.000	-6.000	-.07650	.06500	-.00100	.00100	-.00010	.08980	.02510
2.000	-4.000	-.03750	.03750	-.00350	.00260	-.00030	.08410	.02510
2.000	-2.000	-.00090	.01060	-.00340	.00230	-.00070	.07840	.02590
2.000	.000	.03260	-.01360	-.00280	.00190	-.00040	.07490	.02670
2.000	2.000	.07280	-.04230	-.00290	.00220	.00000	.07310	.02650
2.000	4.000	.11930	-.07730	-.00260	.00200	.00000	.07140	.02550
2.000	6.000	.17080	-.11740	-.00260	.00200	.00020	.06920	.02540
2.000	8.000	.22490	-.15970	-.00280	.00220	.00040	.06560	.02540
GRADIENT		.01934	-.01410	.00011	-.00007	.00006	-.00153	.00007

RUN NO. 1120/0 RN/L = 6.81 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
3.000	-6.000	-.09890	.10980	-.00250	.00110	-.00050	.08580	.02340
3.000	-6.000	-.04780	.07050	-.00730	.00530	-.00060	.08300	.02450
3.000	-4.000	.00250	.03190	-.00780	.00660	-.00050	.07940	.02470
3.000	-2.000	.04680	-.00300	-.00670	.00350	-.00030	.07620	.02540
3.000	.000	.09280	-.03590	-.00650	.00470	-.00020	.07510	.02660
3.000	2.000	.14000	-.07130	-.00620	.00460	-.00020	.07500	.02760
3.000	4.000	.19960	-.10630	-.00620	.00450	.00000	.07330	.02660
3.000	6.000	.23920	-.14600	-.00620	.00490	.00000	.07270	.02660
3.000	8.000	.28710	-.18130	-.00490	.00420	.00040	.07020	.02630
GRADIENT		.02327	-.01743	.00019	-.00025	.00005	-.00067	.00051

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 32

MSFC 558 (WAF) NR ATP (O1)/(T3) (S1)

(R78026) (29 JAN 73)

REFERENCE DATA

PARAMETRIC DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

BETA = .000 ORBINC = .000
 MACH = 2.000 ELEVON = .000
 DELZ/D = -1.000

RUN NO. 1126/0 RN/L = 6.81 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
-1.000	-6.000	-.21460	.18240	-.00320	.00250	.00010	.07750	.02350
-1.000	-6.000	-.16260	.12210	-.00250	.00190	.00040	.07300	.02490
-1.000	-4.000	-.10160	.07460	-.00160	.00100	.00070	.06870	.02570
-1.000	-2.000	-.03680	.02550	-.00060	.00010	.00040	.06520	.02610
-1.000	.000	.02900	-.02140	.00030	-.00050	.00040	.06330	.02640
-1.000	2.000	.09820	-.06920	.00160	-.00130	.00050	.06180	.02660
-1.000	4.000	.16550	-.11700	.00090	-.00060	.00030	.06040	.02620
-1.000	6.000	.29030	-.16260	.00110	-.00060	.00030	.05840	.02600
-1.000	8.000	.29310	-.20780	.00130	-.00070	.00060	.05450	.02670
GRADIENT		.03346	-.02389	.00036	-.00023	-.00005	-.00100	.00007

RUN NO. 1125/0 RN/L = 6.83 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-6.000	-.21670	.15690	-.00440	.00410	.00050	.06000	.02360
.000	-6.000	-.17190	.12160	-.00340	.00260	.00070	.07600	.02500
.000	-4.000	-.11620	.07900	-.00250	.00160	.00100	.07200	.02600
.000	-2.000	-.05240	.03070	-.00140	.00090	.00120	.06860	.02670
.000	.000	.01660	-.02160	-.00020	.00030	.00100	.06670	.02660
.000	2.000	.09490	-.07720	.00110	-.00060	.00070	.06570	.02620
.000	4.000	.16740	-.13090	.00100	-.00050	.00080	.06380	.02550
.000	6.000	.23690	-.18190	.00010	.00030	.00080	.06190	.02570
.000	8.000	.29610	-.22520	-.00020	.00040	.00060	.05930	.02630
GRADIENT		.03572	-.02638	.00047	-.00026	-.00005	-.00096	-.00008

RUN NO. 1127/0 RN/L = 6.82 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
1.000	-6.000	-.22360	.17180	-.00250	.00220	.00000	.06650	.02320
1.000	-6.000	-.17280	.13280	-.00160	.00130	.00050	.08250	.02400
1.000	-4.000	-.12000	.09230	-.00040	.00030	.00060	.07810	.02500
1.000	-2.000	-.06430	.04970	-.00020	-.00010	.00060	.07400	.02580
1.000	.000	-.00260	.00310	.00050	.00000	.00090	.07150	.02560
1.000	2.000	.06560	-.04630	.00110	-.00030	.00060	.07000	.02440
1.000	4.000	.13380	-.10010	.00160	-.00050	.00090	.06730	.02480
1.000	6.000	.19630	-.14810	.00090	.00000	.00090	.06490	.02540
1.000	8.000	.25260	-.16800	.00090	.00000	.00070	.06260	.02600
GRADIENT		.03187	-.02414	.00024	-.00009	.00003	-.00128	-.00009

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 33

MSFC 558 (MA9F) NR ATP (O1)/(T3) (S1)

(R78026) (29 JAN 73)

REFERENCE DATA

BREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1326.0000 INCHES YMRP = .0000
 BREF = 1326.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100,0000 PER

PARAMETRIC DATA

BETA = .000 ORBINC = .000
 MACH = 2.000 ELEVON = .000
 DELZ/D = -1.000

RUN NO. 1129/0 RN/L = 6.81 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
2.000	-6.000	-.18060	.15530	-.00120	.00050	.00000	.06670	.02100
2.000	-6.000	-.13550	.12220	-.00050	.00010	.00010	.06340	.02250
2.000	-4.000	-.08630	.08670	.00070	-.00070	.00030	.06010	.02370
2.000	-2.000	-.03840	.04880	.00060	-.00050	.00060	.07850	.02390
2.000	.000	.01360	.00950	-.00050	.00060	.00070	.07640	.02360
2.000	2.000	.06120	-.02570	.00000	.00030	.00100	.07830	.02380
2.000	4.000	.11540	-.06420	-.00040	.00100	.00110	.07600	.02510
2.000	6.000	.16930	-.10600	.00040	.00040	.00130	.07280	.02650
2.000	8.000	.22250	-.14680	.00050	.00050	.00100	.06930	.02680
GRADIENT		.02535	-.01681	-.00014	.00021	.00010	-.00042	.00013

RUN NO. 1128/0 RN/L = 6.81 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
3.000	-6.000	-.09320	.08580	.00030	-.00120	.00080	.06460	.02130
3.000	-6.000	-.03730	.04690	-.00050	.00000	.00060	.06380	.02260
3.000	-4.000	.01270	.01230	.00000	-.00020	.00060	.06110	.02360
3.000	-2.000	.05580	-.01620	.00020	-.00020	.00060	.07660	.02490
3.000	.000	.09760	-.04300	.00020	.00000	.00070	.07760	.02640
3.000	2.000	.14520	-.07560	.00050	.00000	.00090	.07620	.02720
3.000	4.000	.20210	-.11710	-.00070	.00100	.00040	.07430	.02760
3.000	6.000	.25690	-.15590	-.00150	.00180	.00040	.07280	.02860
3.000	8.000	.30530	-.18930	-.00190	.00220	.00050	.07000	.02920
GRADIENT		.02341	-.01591	-.00005	.00013	-.00000	-.00060	.00051

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-T4T-558

PAGE 34

MSFC 558 (MA9F) NR ATP (O1)/(T3)(S1)

(R78C27) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

BETA = .000 ORBINC = .000
 MACH = 2.000 ELEVON = .000
 DELZ/D = -1.500

RUN NO. 1131/0 RN/L = 6.81 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-8.000	-.27050	.20120	.00070	-.00010	.00100	.08310	.02230
.000	-6.000	-.21960	.16340	.00260	-.00170	.00110	.08160	.02360
.000	-4.000	-.16380	.12180	.00390	-.00270	.00100	.07800	.02460
.000	-2.000	-.10160	.07560	.00460	-.00300	.00100	.07410	.02500
.000	.000	-.03630	.02680	.00460	-.00270	.00110	.07170	.02440
.000	2.000	.02980	-.02340	.00440	-.00230	.00110	.06960	.02360
.000	4.000	.10660	-.08270	.00380	-.00170	.00080	.06700	.02410
.000	6.000	.18190	-.14020	.00400	-.00190	.00050	.06620	.02550
.000	8.000	.25140	-.19140	.00360	-.00160	.00070	.06540	.02670
GRADIENT		.03361	-.02540	-.00002	.00013	-.00001	-.00132	-.00012

RUN NO. 1130/0 RN/L = 6.81 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
1.000	-8.000	-.23410	.16820	.00130	-.00090	.00040	.08390	.02080
1.000	-6.000	-.18460	.13270	.00280	-.00180	.00050	.08300	.02230
1.000	-4.000	-.13410	.11600	.00390	-.00260	.00050	.08110	.02360
1.000	-2.000	-.07650	.07510	.00430	-.00270	.00050	.07820	.02450
1.000	.000	-.02210	.03340	.00440	-.00240	.00030	.07560	.02460
1.000	2.000	.02720	-.00290	.00450	-.00230	.00010	.07380	.02470
1.000	4.000	.07360	-.03850	.00470	-.00240	.00000	.07160	.02480
1.000	6.000	.12570	-.07940	.00450	-.00220	.00010	.06740	.02590
1.000	8.000	.17980	-.12240	.00420	-.00210	.00020	.06150	.02680
GRADIENT		.02605	-.01935	.00009	.00004	-.00007	-.00117	.00013

RUN NO. 1132/0 RN/L = 6.80 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
2.000	-8.000	-.17960	.15200	.00360	-.00250	.00060	.08400	.01950
2.000	-6.000	-.12060	.11020	.00510	-.00390	.00070	.08260	.02190
2.000	-4.000	-.06190	.06850	.00630	-.00460	.00080	.08120	.02370
2.000	-2.000	-.00340	.02660	.00560	-.00370	.00070	.07980	.02460
2.000	.000	.05160	-.01190	.00490	-.00250	.00050	.07760	.02570
2.000	2.000	.10170	-.04570	.00360	-.00170	.00060	.07420	.02750
2.000	4.000	.15060	-.07910	.00360	-.00140	.00070	.07140	.02890
2.000	6.000	.19900	-.11150	.00330	-.00110	.00040	.06960	.03010
2.000	8.000	.23970	-.13720	.00270	-.00070	.00010	.07030	.02940
GRADIENT		.02650	-.01838	-.00037	.00042	-.00000	-.00126	.00066

DATE 26 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 35

MSFC 558 (MA9F) NR ATP (O1)/(T3) (S1)

(R76025) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

BETA =	.000	ORBINC =	2.000
MACH =	2.000	ELEVON =	.000
DELZ/D =	-.520		

RUN NO. 1112/0 RN/L = 6.76 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
-1.000	-8.000	-.09650	.09210	-.00520	.0047G	-.00070	.07650	.02300
-1.000	-6.000	-.04490	.04980	-.00590	.00500	-.00050	.07080	.02490
-1.000	-4.000	.01760	-.00080	-.00630	.00490	-.00020	.06670	.02580
-1.000	-2.000	.08420	-.05350	-.00580	.00440	.00010	.06340	.02560
-1.000	.000	.14620	-.10080	-.00630	.00510	.00030	.06120	.02590
-1.000	2.000	.19780	-.13860	-.00700	.00560	.00030	.06240	.02640
-1.000	4.000	.25370	-.17850	-.00720	.00570	.00040	.06440	.02650
-1.000	6.000	.30500	-.21530	-.00760	.00600	.00040	.06630	.02660
-1.000	8.000	.31730	-.22200	-.00690	.00550	.00040	.06920	.02630
GRADIENT		.02929	-.02202	-.00015	.00014	.00007	-.00028	.00006

RUN NO. 1111/0 RN/L = 6.81 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-8.000	-.05630	.06140	-.00450	.00440	-.00200	.07950	.02680
.000	-6.000	-.02860	.03820	-.00480	.00440	-.00120	.07280	.02600
.000	-4.000	.01840	.00140	-.00520	.00460	-.00090	.06730	.02670
.000	-2.000	.07490	-.04210	-.00550	.00440	-.00070	.06250	.02930
.000	.000	.13400	-.06740	-.00600	.00440	-.00040	.05830	.03010
.000	2.000	.18740	-.12700	-.00700	.00500	.00020	.05650	.03010
.000	4.000	.25350	-.17590	-.00650	.00480	.00020	.05910	.02980
.000	6.000	.31370	-.22090	-.00710	.00510	.00030	.05410	.03050
.000	8.000	.35160	-.24890	-.00720	.00510	.00040	.05330	.03100
GRADIENT		.02913	-.02197	-.00021	.00005	.00015	-.00152	.00015

RUN NO. 1110/0 RN/L = 6.82 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
1.000	-8.000	-.08300	.07700	-.00590	.00620	-.00130	.09010	.02390
1.000	-6.000	-.04700	.04730	-.00730	.00670	-.00130	.08420	.02390
1.000	-4.000	-.01500	.01200	-.00630	.00710	-.00110	.07970	.02340
1.000	-2.000	.04690	-.03110	-.00670	.00710	-.00070	.07550	.02280
1.000	.000	.10530	-.07870	-.00780	.00620	-.00040	.07120	.02250
1.000	2.000	.16560	-.12710	-.00650	.00530	.00000	.06690	.02310
1.000	4.000	.23010	-.17780	-.00650	.00510	-.00030	.06490	.02410
1.000	6.000	.30370	-.23460	-.00730	.00570	-.00030	.06210	.02540
1.000	8.000	.36900	-.28390	-.00840	.00660	.00000	.06010	.02580
GRADIENT		.02944	-.02378	-.00029	-.00029	.00011	-.00191	.00008

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-556

PAGE 36

MSFC 556 (MA9F) NR ATP (O1)/(T3)(S1)

(R76026) (29 JAN 73)

REFERENCE DATA

PARAMETRIC DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

BETA = .000 ORBINC = 2.000
 MACH = 2.000 ELEVON = .000
 DELZ/D = -.520

RUN NO. 1109/0 RN/L = 6.76 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
2.000	-6.000	-.03660	.03990	-.00460	.00430	-.00140	.09630	.02580
2.000	-6.000	-.00900	.02150	-.00630	.00540	-.00030	.09280	.02500
2.000	-4.000	.02240	-.00120	-.00690	.00560	-.00100	.08780	.02510
2.000	-2.000	.05560	-.02640	-.00560	.00430	-.00110	.08060	.02640
2.000	.000	.09740	-.05790	-.00470	.00330	-.00070	.07390	.02740
2.000	2.000	.13710	-.08890	-.00570	.00410	-.00060	.07160	.02640
2.000	4.000	.18280	-.12480	-.00400	.00280	-.00020	.06950	.02530
2.000	6.000	.23540	-.16590	-.00430	.00330	.00020	.06680	.02510
2.000	8.000	.29570	-.21340	-.00550	.00440	.00040	.06300	.02560
GRADIENT		.02011	-.01548	.00028	-.00029	.00010	-.00228	.00002

RUN NO. 1108/0 RN/L = 6.77 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
3.000	-6.000	-.01400	.05200	-.00830	.00610	-.00160	.08690	.02330
3.000	-6.000	.03430	.01350	-.01030	.00770	-.00170	.08320	.02430
3.000	-4.000	.08380	-.02540	-.01010	.00790	-.00150	.07960	.02480
3.000	-2.000	.13000	-.06120	-.00960	.00740	-.00130	.07700	.02560
3.000	.000	.17270	-.09370	-.00960	.00700	-.00120	.07610	.02670
3.000	2.000	.21410	-.12520	-.00850	.00620	-.00100	.07590	.02740
3.000	4.000	.25220	-.15330	-.00830	.00580	-.00080	.07340	.02990
3.000	6.000	.29490	-.18740	-.00780	.00580	-.00060	.07150	.02980
3.000	8.000	.33970	-.21630	-.00610	.00610	-.00020	.06810	.02920
GRADIENT		.02104	-.01599	.00023	-.00027	.00008	-.00067	.00060

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 37

MSFC 558 (MA9F) NR ATP (O1)/(T3) (S1)

(R78029) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

BETA = .000 ORBINC = 2.000
 MACH = 2.000 ELEVON = .000
 DELZ/D = -1.000

RUN NO. 1104/0 RN/L = 6.75 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
-1.000	-6.000	-.13390	.10750	-.00290	.00170	.00000	.07620	.02460
-1.000	-6.000	-.08360	.06660	-.00210	.00120	.00010	.07090	.02630
-1.000	-4.000	-.02710	.02460	-.00150	.00070	.00030	.06570	.02720
-1.000	-2.000	.03380	-.02100	-.00100	.00040	.00040	.06160	.02780
-1.000	.000	.09730	-.06750	-.00100	.00060	.00040	.05900	.02760
-1.000	2.000	.16240	-.11410	-.00080	.00050	.00100	.05690	.02790
-1.000	4.000	.23310	-.16410	.00020	-.00010	.00130	.05470	.02650
-1.000	6.000	.29930	-.21110	.00030	-.00010	.00150	.05300	.02670
-1.000	8.000	.36210	-.25670	.00010	.00010	.00160	.05030	.02950
GRADIENT		.03245	-.02932	.00018	-.00007	.00013	-.00133	.00014

RUN NO. 1102/0 RN/L = 6.74 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-6.000	-.11980	.06590	-.00390	.00310	.00000	.06090	.02500
.000	-6.000	-.07540	.05250	-.00360	.00250	.00020	.07590	.02660
.000	-4.000	-.02270	.01210	-.00300	.00190	.00050	.07110	.02780
.000	-2.000	.03690	-.03350	-.00190	.00110	.00060	.06700	.02640
.000	.000	.10130	-.06140	-.00180	.00130	.00040	.06480	.02780
.000	2.000	.17000	-.13090	-.00170	.00140	.00030	.06290	.02770
.000	4.000	.24180	-.18320	-.00200	.00150	.00060	.06110	.02770
.000	6.000	.30690	-.23080	-.00150	.00150	.00070	.05940	.02600
.000	8.000	.36250	-.27200	-.00110	.00160	.00070	.05690	.02850
GRADIENT		.03310	-.02440	.00011	-.00003	-.00001	-.00121	-.00005

RUN NO. 1105/0 RN/L = 6.75 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
1.000	-6.000	-.12270	.09720	-.00280	.00220	.00010	.06660	.02430
1.000	-6.000	-.07910	.06060	-.00290	.00180	.00020	.06160	.02540
1.000	-4.000	-.02770	.02380	-.00130	.00090	.00040	.07640	.02640
1.000	-2.000	.02330	-.01540	-.00020	.00000	.00050	.07160	.02660
1.000	.000	.06300	-.06030	.00000	.00000	.00060	.06790	.02700
1.000	2.000	.14510	-.10420	-.00060	.00090	.00040	.06850	.02620
1.000	4.000	.21100	-.15610	-.00120	.00100	.00050	.06680	.02660
1.000	6.000	.27240	-.20160	-.00060	.00100	.00070	.06520	.02750
1.000	8.000	.32420	-.24010	.00000	.00050	.00060	.06260	.02630
GRADIENT		.02996	-.02233	-.00001	.00004	.00000	-.00111	.00001

DATE 26 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 30

MSFC 558 (MASF) NR ATP (O1)/(T3) (S1)

(R78029) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1326.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

BETA = .000 ORBINC = 2.000
 MACH = 2.000 ELEVON = .000
 DEL2/D = -1.000

RUN NO. 1106/0 RN/L = 6.75 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
2.000	-8.000	-.06670	.08550	-.00150	.00050	-.00030	.08530	.02330
2.000	-6.000	-.04350	.05300	-.00140	.00060	-.00020	.06160	.02450
2.000	-4.000	.00500	.01650	-.00120	.00060	.00000	.07770	.02580
2.000	-2.000	.05490	-.02070	-.00150	.00090	.00000	.07520	.02530
2.000	.000	.09350	-.04970	-.00160	.00110	.00010	.07510	.02530
2.000	2.000	.13370	-.07930	-.00150	.00140	.00080	.07580	.02600
2.000	4.000	.18550	-.11790	-.00270	.00230	.00080	.07410	.02770
2.000	6.000	.24090	-.16020	-.00180	.00170	.00110	.07000	.02890
2.000	8.000	.29390	-.20020	-.00130	.00140	.00120	.06550	.02950
GRADIENT		.02199	-.01637	-.00015	.00019	.00012	-.00033	.00022

RUN NO. 1107/0 RN/L = 6.75 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
3.000	-8.000	-.01640	.03510	-.00230	.00100	.00000	.08400	.02260
3.000	-6.000	.03230	.00000	-.00350	.00210	.00010	.06140	.02430
3.000	-4.000	.07660	-.03290	-.00350	.00230	.00030	.07820	.02540
3.000	-2.000	.12130	-.06240	-.00290	.00190	.00030	.07540	.02650
3.000	.000	.16150	-.08930	-.00270	.00170	.00050	.07440	.02750
3.000	2.000	.20460	-.11760	-.00260	.00190	.00060	.07340	.02920
3.000	4.000	.25690	-.15450	-.00270	.00220	.00060	.07240	.03030
3.000	6.000	.30690	-.18940	-.00350	.00310	.00080	.06930	.03120
3.000	8.000	.35130	-.21910	-.00430	.00390	.00090	.06660	.03190
GRADIENT		.02199	-.01492	.00009	-.00001	.00004	-.00068	.00063

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 39

MSFC 558 (MA9F) NR ATP (O1)/(T3)(S1)

(R78030) (29 JAN 73)

REFERENCE DATA

BREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREY = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

BETA = .000 ORBINC = 2.000
 MACH = 2.000 ELEVON = .000
 DELZ/D = -1.500

RUN NO. 1096/0 RN/L = 6.74 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
-1.000	-9.170	-.47630	.47730	-.00960	.01310	-.00170	.16410	.04460
-1.000	-6.710	-.32710	.31190	-.00260	.00620	-.00090	.18960	.04090
-1.000	-4.360	-.22620	.22340	-.00010	.00240	-.00050	.17220	.03670
-1.000	-2.120	-.14060	.15300	.00270	-.00190	-.00040	.17020	.03780
-1.000	.210	-.05200	.07030	.00410	-.00450	-.00010	.16680	.03730
-1.000	.240	-.03880	.05860	.00370	-.00410	.00000	.16740	.03730
-1.000	2.550	.03950	-.01390	.00500	-.00630	-.00010	.16840	.03650
-1.000	4.820	.12830	-.09050	.00240	-.00400	-.00040	.17030	.03220
-1.000	7.240	.24420	-.19710	.00000	-.00080	-.00060	.16400	.03100
-1.000	9.570	.37490	-.32650	.00050	-.00110	-.00060	.15580	.03190
GRADIENT	.03461	-.03455	.00032	-.00075	.00002	-.00024	-.00062	

RUN NO. 1100/0 RN/L = 6.77 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-8.000	-.16120	.13320	.00190	-.00140	.00110	.08360	.02350
.000	-8.000	-.13180	.09690	.00300	-.00240	.00120	.08040	.02470
.000	-4.000	-.08250	.06020	.00380	-.00290	.00120	.07620	.02590
.000	-2.000	-.03140	.02200	.00440	-.00300	.00130	.07130	.02690
.000	.000	.03990	-.03130	.00460	-.00260	.00130	.08900	.02610
.000	2.000	.11530	-.06930	.00440	-.00260	.00110	.06730	.02610
.000	4.000	.19080	-.14670	.00390	-.00210	.00070	.06700	.02610
.000	6.000	.26610	-.20270	.00410	-.00210	.00110	.06560	.02730
.000	8.000	.33160	-.24950	.00370	-.00180	.00190	.06350	.02660
GRADIENT	.03466	-.02625	.00001	.00010	-.00008	-.00112	-.00002	

RUN NO. 1097/0 RN/L = 6.75 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
1.000	-8.000	-.15640	.12910	.00270	-.00290	.00060	.08330	.02310
1.000	-8.000	-.10910	.09460	.00360	-.00290	.00060	.08060	.02440
1.000	-4.000	-.06170	.05970	.00420	-.00320	.00070	.07780	.02560
1.000	-2.000	-.01220	.02300	.00440	-.00310	.00060	.07420	.02640
1.000	.000	.03900	-.01490	.00370	-.00220	.00060	.07130	.02690
1.000	2.000	.04690	-.05320	.00430	-.00230	.00040	.06870	.02750
1.000	4.000	.15470	-.10310	.00410	-.00230	.00050	.06690	.02750
1.000	6.000	.20470	-.14250	.00320	-.00300	.00070	.06190	.02790
1.000	8.000	.25990	-.18320	.00500	-.00260	.00090	.05500	.02630
GRADIENT	.02669	-.02009	-.00002	.00013	-.00004	-.00137	.00029	

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 4D

MSFC 558 (MA9F) NR ATP (O1)/(T3) (S1)

(R78030) (29 JAN 73)

REFERENCE DATA

PARAMETRIC DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

BETA = .000 ORBINC = 2.000
 MACH = 2.000 ELEVON = .000
 DELZ/D = -1.500

RUN NO. 1098/0 RN/L = 6.76 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
2.000	-6.000	-.10130	.09620	.00360	-.00350	.00080	.06200	.02170
2.000	-6.000	-.04920	.05680	.00420	-.00360	.00080	.07960	.02370
2.000	-4.000	.00260	.02210	.00420	-.00330	.00100	.07730	.02520
2.000	-2.000	.09410	-.01370	.00370	-.00260	.00100	.07520	.02620
2.000	.000	.09960	-.04490	.00320	-.00170	.00110	.07340	.02700
2.000	2.000	.14530	-.07630	.00300	-.00160	.00090	.07190	.02920
2.000	4.000	.19120	-.10780	.00310	-.00130	.00090	.07070	.03070
2.000	6.000	.23570	-.13810	.00300	-.00110	.00080	.06810	.03130
2.000	8.000	.27450	-.16410	.00300	-.00100	.00060	.06600	.03060
GRADIENT		.02340	-.01612	-.00015	.00025	-.00002	-.00082	.00070

RUN NO. 1099/0 RN/L = 6.78 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
3.000	-9.160	-.41620	.36030	-.01210	.01560	-.00100	.15800	.04930
3.000	-6.750	-.29810	.24270	-.00660	.00970	-.00060	.15910	.04960
3.000	-4.440	-.20450	.15910	-.00410	.00670	-.00030	.16170	.04970
3.000	-2.200	-.13150	.10260	-.00260	.00440	-.00030	.16270	.04970
3.000	.100	-.06560	.05980	-.00140	.00320	-.00030	.16230	.04920
3.000	2.330	-.02350	.04000	.00080	.00060	-.00020	.16450	.04910
3.000	4.520	.03080	.00460	.00360	-.00180	-.00030	.16130	.04970
3.000	6.810	.09380	-.03970	.00400	-.00300	.00010	.16280	.04920
3.000	9.040	.17520	-.10490	.00740	-.00720	.00060	.16340	.04810
GRADIENT		.02578	-.01656	.00065	-.00093	.00000	.00005	-.00003

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

(R78051) (29 JAN 73)

MSFC 558 (MASF) NR ATP (O1)/(T3) (S1)

REFERENCE DATA

BREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.9000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

BETA = .000 ORBINC = 2.000
 MACH = 2.000 ELEVON = 10.000
 DELZ/D = -.520

RUN NO. 1103/0 RN/L = 6.02 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-0.290	-0.31950	.52130	-.00400	.00770	-.00160	.16320	.04820
.000	-0.820	-0.37160	.37260	.00010	.00240	-.00090	.16750	.04700
.000	-4.430	-0.26420	.28210	.00220	-.00100	-.00050	.17430	.04530
.000	-2.120	-0.18820	.23080	.00050	-.00070	-.00060	.17630	.04160
.000	.110	-0.13280	.20560	.00190	-.00300	-.00030	.17590	.03770
.000	.140	-0.12580	.19950	.00340	-.00500	-.00060	.17350	.03770
.000	2.360	-0.07930	.17860	.00160	-.00430	-.00100	.17270	.03560
.000	4.670	-0.02290	.15580	.00140	-.00580	-.00090	.17530	.03230
.000	6.980	.05500	.10610	.00320	-.00940	-.00130	.17340	.03190
.000	9.380	.17640	-.01280	-.00070	-.00620	-.00160	.17270	.03220
GRADIENT		.02609	-.01345	-.00002	-.00056	-.00005	-.00016	-.00141

MSFC 558 (MASF) NR ATP (O1)/(T3) (S1)

(R78052) (29 JAN 73)

REFERENCE DATA

BREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.9000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

BETA = .000 ORBINC = 2.000
 MACH = 2.000 ELEVON = 10.000
 DELZ/D = -1.000

RUN NO. 1101/0 RN/L = 6.78 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-0.140	-.45430	.44130	-.01520	.02140	-.00210	.16720	.04930
.000	-0.670	-.31150	.29740	-.00310	.00500	-.00110	.17170	.04330
.000	-4.310	-.20460	.20930	.00030	.00060	-.00070	.17330	.04010
.000	-2.090	-.13780	.15870	-.00020	.00120	-.00090	.17240	.03570
.000	.240	-.06450	.10910	.00360	-.00400	-.00050	.16700	.03250
.000	.250	-.05350	.09340	.00280	-.00260	-.00080	.16530	.03070
.000	2.370	.00240	.06460	.00590	-.00670	-.00040	.16640	.03070
.000	4.600	.07590	.01470	.00620	-.00800	-.00070	.16570	.02940
.000	7.260	.17690	-.04630	.00470	-.00800	-.00110	.16200	.02760
.000	9.340	.29730	-.18570	.00630	-.00690	-.00090	.15640	.02400
GRADIENT		.03099	-.02111	.00076	-.00120	-.00002	-.00093	-.00119

DATE 26 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 42

MSFC 558 (MA9F) NR ATP (O1)/(T3)(S1)

(R78053) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

ALPHA = .000 ORBINC = .000
 MACH = .900 ELEVON = .000
 DELZ/D = -.520

RUN NO. 1066/0 RN/L = 6.19 GRADIENT INTERVAL = -5.00/ 5.00

DLX/D	BETA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-10.220	-.09050	.07600	.19720	-.13600	.01600	.03760	.03760
.000	-6.250	-.09010	.07750	.16400	-.11640	.01660	.03630	.03410
.000	-6.160	-.09020	.07990	.12350	-.06930	.01430	.04210	.03100
.000	-4.090	-.08670	.07860	.06270	-.08090	.01080	.04190	.03050
.000	-2.040	-.08380	.07750	.04080	-.02980	.00560	.03950	.03130
.000	.020	-.07740	.07390	.00040	-.00080	.00150	.03400	.03530
.000	2.090	-.07460	.07210	-.04000	.02880	-.00250	.03320	.03610
.000	4.180	-.06710	.06630	-.06200	.05960	-.00710	.03090	.03630
.000	6.230	-.07040	.06860	-.12380	.09330	-.01210	.03080	.03800
.000	8.300	-.05900	.05910	-.15690	.11210	-.01390	.02750	.03940
.000	10.290	-.05770	.05720	-.19400	.13350	-.01600	.02580	.04410
GRADIENT	.07234	-.00145	-.01985	.01449	-.00212	-.00137	.00079	

MSFC 558 (MA9F) NR ATP (O1)/(T3)(S1)

(R78054) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

ALPHA = .000 ORBINC = .000
 MACH = .900 ELEVON = .000
 DELZ/D = -1.000

RUN NO. 1063/0 RN/L = 6.21 GRADIENT INTERVAL = -5.00/ 5.00

DLX/D	BETA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-10.230	-.09140	.07840	.16900	-.13160	.01440	.03510	.03610
.000	-6.260	-.09270	.08210	.15470	-.11080	.01450	.03900	.03290
.000	-6.150	-.09030	.08200	.11760	-.06570	.01230	.04030	.02930
.000	-4.040	-.08980	.08300	.06140	-.06000	.00950	.04120	.02780
.000	-2.040	-.08310	.07980	.04080	-.03000	.00580	.03880	.03000
.000	.030	-.08290	.08040	.00010	-.00030	.00210	.03340	.03420
.000	2.090	-.07790	.07700	-.03980	.02870	-.00180	.03460	.03330
.000	4.150	-.07020	.07100	-.07790	.05700	-.00580	.03150	.03400
.000	6.220	-.06920	.06610	-.11780	.08580	-.00850	.02850	.03460
.000	8.290	-.05940	.06120	-.15680	.11170	-.01190	.02870	.03700
.000	10.240	-.05360	.05560	-.19970	.13180	-.01290	.02490	.03970
GRADIENT	.00214	-.00130	-.01938	.01482	-.00166	-.00119	.00076	

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 43

MSFC 558 (MASF) NR ATP (O1)/(T3) (S1)

(0780851) (29 JAN 73)

REFERENCE DATA

BREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

ALPHA = .000 ORBINC = 2.000
 MACH = .900 ELEVON = .000
 DELZ/D = -.320

RUN NO. 1091/0 RN/L = 6.17 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	BETA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-10.270	.04560	-.01700	.19030	-.12990	.02420	.03000	.04710
.000	-6.260	.04830	-.01750	.19520	-.10950	.02150	.02920	.04370
.000	-6.190	.04730	-.01450	.11490	-.06290	.01810	.03060	.04230
.000	-4.110	.04780	-.01340	.07520	-.03450	.01290	.03180	.04070
.000	-2.080	.04930	-.01270	.03350	-.02410	.00720	.03260	.03950
.000	.000	.05140	-.01470	-.00420	.00260	.00160	.03230	.03740
.000	2.070	.05070	-.01420	-.04220	.03020	-.00380	.03150	.03710
.000	4.130	.05470	-.01740	-.08260	.09990	-.00980	.02790	.03900
.000	6.200	.05240	-.01620	-.12650	.00560	-.01560	.02690	.03910
.000	8.250	.05460	-.01920	-.16170	.11330	-.01830	.02540	.04190
.000	10.300	.05900	-.02450	-.19770	.13550	-.02060	.02260	.04630
GRADIENT	.00074	-.00046	-.01699	.01374	-.00274	-.00043	-.00026	

MSFC 558 (MASF) NR ATP (O1)/(T3) (S1)

(0780851) (29 JAN 73)

REFERENCE DATA

BREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

ALPHA = .000 ORBINC = 2.000
 MACH = .900 ELEVON = .000
 DELZ/D = -1.000

RUN NO. 1092/0 RN/L = 6.17 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	BETA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-10.230	.01930	.00360	.18480	-.12760	.02010	.02910	.04320
.000	-6.250	.01930	.00600	.19070	-.10720	.01910	.03080	.04040
.000	-6.180	.02070	.00740	.11300	-.08190	.01390	.03180	.03420
.000	-4.110	.01910	.00990	.07340	-.09370	.01190	.03290	.03450
.000	-2.090	.02650	.00550	.03430	-.02490	.00680	.03120	.03600
.000	.000	.02970	.00400	-.00330	.00220	.00230	.03180	.03480
.000	2.060	.03160	.00160	-.04000	.02970	-.00230	.03210	.03350
.000	4.120	.03240	.00130	-.06190	.09990	-.00760	.03070	.03470
.000	6.210	.03560	-.00190	-.12410	.06370	-.01260	.02900	.03620
.000	8.240	.03777	-.00450	-.15600	.11220	-.01460	.02700	.03760
.000	10.290	.03690	-.00370	-.19450	.13460	-.01710	.02430	.04270
GRADIENT	.00159	-.00103	-.01672	.01369	-.00234	-.00017	-.00030	

DATE 29 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 44

MSFC 558 (MAF) NR ATP (O1)/(T3)(S1)

(R76057) (29 JAN 73)

REFERENCE DATA

BREF = 3220.0000 FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

ALPHA = .000 ORBINC = .000
 MACH = 1.200 ELEVON = .000
 DELZ/D = -.520

RUN NO. 1065/0 RN/L = 6.60 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	BETA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-10.400	-.07960	.07820	.19710	-.12980	.02840	.05960	.04960
.000	-8.360	-.06980	.07360	.15570	-.10490	.02580	.06090	.04550
.000	-6.230	-.05890	.06850	.11520	-.07870	.02160	.06340	.04790
.000	-4.140	-.05590	.06680	.07260	-.04970	.01420	.06820	.04430
.000	-2.060	-.05210	.06600	.03430	-.02320	.00750	.07340	.03740
.000	.040	-.04690	.06430	-.00290	.00110	.00040	.07430	.03680
.000	2.140	-.04230	.06080	-.03880	.02500	-.00550	.07310	.03800
.000	4.290	-.03260	.05110	-.06030	.05380	-.01290	.06640	.04250
.000	6.330	-.02240	.04130	-.12030	.06150	-.01580	.06250	.04370
.000	8.450	-.02190	.03780	-.16210	.10780	-.02480	.05630	.04670
.000	10.480	-.02560	.03920	-.20220	.13150	-.02710	.05540	.04790
GRADIENT		.00269	-.00204	-.01806	.01216	-.00320	-.00019	-.00019

MSFC 558 (MAF) NR ATP (O1)/(T3)(S1)

(R76058) (29 JAN 73)

REFERENCE DATA

BREF = 3220.0000 FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

ALPHA = .000 ORBINC = .000
 MACH = 1.200 ELEVON = .000
 DELZ/D = -1.000

RUN NO. 1064/0 RN/L = 6.59 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	BETA	CN	CLM	CY	CYN	CBL	CAF	CAB
.. 0	-10.380	-.07860	.07690	.19310	-.12920	.02220	.05780	.04470
.000	-8.350	-.06740	.07090	.15390	-.10520	.01960	.05890	.04390
.000	-6.220	-.05730	.06560	.11280	.07840	.01630	.05870	.04440
.000	-4.130	-.04980	.05990	.07120	-.04960	.01140	.05700	.04710
.000	-2.060	-.04270	.05810	.03230	-.02240	.00650	.05640	.04760
.000	.030	-.03650	.05420	-.00330	.00170	.00140	.05960	.04380
.000	2.130	-.02670	.04770	-.03740	.02490	-.00380	.06180	.04030
.000	4.290	-.02290	.04120	-.07740	.05310	-.00930	.06430	.03630
.000	6.320	-.01840	.03790	-.11910	.06240	-.01470	.06660	.03760
.000	8.430	-.01930	.03230	-.16040	.10930	-.01880	.05900	.04000
.000	10.450	-.01460	.03000	-.20120	.13390	-.02210	.05490	.04220
GRADIENT		.00246	-.00229	-.01753	.01206	-.00247	.00196	-.00138

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 45

MSFC 558 (MA9F) NR ATP (O1)/(T3) (S1)

(R78039) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

ALPHA = .000 ORBINC = 2.000
 MACH = 1.200 ELEVON = .000
 DELZ/D = -.520

RUN NO. 1090/0 RN/L = 6.57 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	BETA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-10.410	.07850	-.03740	.18840	-.12250	.03380	.06010	.05160
.000	-8.370	.08360	-.03030	.14820	-.09880	.02980	.06060	.05240
.000	-6.230	.09000	-.04080	.10750	-.07270	.02360	.06080	.05220
.000	-4.150	.09400	-.04110	.06700	-.04540	.01650	.06460	.04960
.000	-2.070	.09510	-.04040	.03040	-.02050	.00880	.06830	.04690
.000	.010	.09310	-.03870	-.00530	.00280	.00060	.06970	.04560
.000	2.100	.09690	-.04190	-.04120	.02700	-.00720	.06980	.04460
.000	4.190	.10190	-.04750	-.08050	.05380	-.01550	.06580	.04590
.000	6.320	.10490	-.05210	-.12230	.06230	-.02330	.06250	.04650
.000	8.420	.10760	-.05680	-.16360	.10820	-.02910	.05880	.04920
.000	10.490	.10180	-.05550	-.20520	.13280	-.03250	.05590	.04920
GRADIENT		.00084	-.00069	-.01758	.01179	-.00384	.00019	-.00046

MSFC 558 (MA9F) NR ATP (O1)/(T3) (S1)

(R78040) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

ALPHA = .000 ORBINC = 2.000
 MACH = 1.200 ELEVON = .000
 DELZ/D = -1.000

RUN NO. 1093/0 RN/L = 6.57 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	BETA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-10.380	.06500	-.12910	.18690	-.12340	.02620	.05510	.04800
.000	-8.340	.07880	-.03780	.14680	-.09980	.02370	.05460	.04910
.000	-6.240	.08760	-.04180	.10740	-.07360	.01940	.05390	.05010
.000	-4.150	.09290	-.04380	.06620	-.04540	.01370	.05400	.05100
.000	-2.070	.09620	-.04480	.02940	-.02010	.00750	.05410	.05130
.000	.010	.09880	-.04590	-.00640	.00430	.00170	.05710	.04830
.000	2.090	.10000	-.04720	-.04140	.02790	-.00460	.05880	.04920
.000	4.190	.10430	-.05290	-.08020	.05460	-.01130	.05840	.04380
.000	6.310	.10700	-.05580	-.12070	.06290	-.01690	.05690	.04390
.000	8.380	.10630	-.05740	-.16160	.10910	-.02140	.05360	.04530
.000	10.470	.10050	-.05920	-.20410	.13480	-.02480	.05180	.04630
GRADIENT		.00128	-.00099	-.01743	.01192	-.00298	.00065	-.00098

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 46

MSFC 558 (MA9F) NR ATP (O1)/(T3)(S1)

(R78041) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

ALPHA = .000 ORBINC = 2.000
 MACH = 2.000 ELEVON = .000
 DELZ/D = -.520

RUN NO. 1116/0 RN/L = 6.82 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	BETA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-10.560	-.07570	.11530	.16780	-.18680	.00150	.17920	.04440
.000	-6.520	-.07060	.10650	.14230	-.13930	.00100	.17430	.04200
.000	-6.360	-.06690	.10320	.09960	-.09570	.00080	.17000	.04120
.000	-4.230	-.07170	.11410	.06280	-.05980	.00120	.16930	.03790
.000	-2.120	-.07520	.12170	.02930	-.02800	.00030	.16660	.03750
.000	.010	-.07600	.11870	-.01200	.01310	-.00070	.16490	.03760
.000	.030	-.08220	.12940	-.01090	.01250	-.00080	.16940	.03600
.000	2.130	-.08520	.13730	-.04620	.04800	-.00110	.17360	.03580
.000	4.280	-.08540	.14030	-.08240	.06290	-.00160	.17770	.03740
.000	6.430	-.07790	.12700	-.12490	.12540	-.00220	.17920	.03730
.000	8.590	-.07430	.12190	-.16910	.17010	-.00260	.18240	.03900
.000	10.680	-.08180	.13310	-.21810	.21960	-.00400	.18710	.04120
GRADIENT		-.00176	.00320	-.01720	.01699	-.00033	.00112	-.00013

MSFC 558 (MA9F) NR ATP (O1)/(T3)(S1)

(R78042) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

ALPHA = .000 ORBINC = 2.000
 MACH = 2.000 ELEVON = .000
 DELZ/D = -1.000

RUN NO. 1117/0 RN/L = 6.77 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	BETA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-10.560	-.11000	.15870	.20110	-.20570	-.00220	.17780	.04690
.000	-6.540	-.10490	.15540	.15500	-.15800	-.00240	.17290	.04530
.000	-6.400	-.11010	.16650	.11210	-.11340	-.00190	.17160	.04290
.000	-4.260	-.11420	.17560	.07140	-.07190	-.00110	.16990	.04330
.000	-2.110	-.11860	.18280	.03250	-.03290	-.00040	.16980	.04200
.000	.000	-.12130	.18630	-.00650	.00630	-.00000	.16740	.04170
.000	.020	-.12070	.18300	-.00760	.00840	-.00030	.16930	.04170
.000	2.120	-.11750	.18080	-.04540	.04730	-.00040	.17040	.04180
.000	4.270	-.11750	.18010	-.08460	.08810	-.00110	.17350	.04070
.000	6.420	-.11180	.17080	-.12780	.13260	-.00200	.17790	.04030
.000	8.590	-.10460	.16220	-.17780	.16370	-.00130	.17940	.04180
.000	10.680	-.11060	.16700	-.23020	.23870	-.00010	.18360	.04350
GRADIENT		-.00026	.00033	-.01631	.01660	-.00024	.00037	-.00029

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 47

MSFC 558 (MA9F) NR ATP (T3) (S1) / (O1)

(R78T01) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

BETA = .000 CRBINC = .000
 MACH = .900 ELEVON = .000
 DELZ/D = -.520

RUN NO. 2018/0 RN/L = 6.20 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
-.500	-6.000	-.30340	.24430	-.01210	.01900	.00010	.11630	.09280
-.500	-6.000	-.23790	.19540	-.01230	.01620	.00040	.12090	.06800
-.500	-4.000	-.17420	.15270	-.00580	.01040	.00090	.12230	.06580
-.500	-2.000	-.11820	.11320	-.00710	.01030	.00030	.12350	.06300
-.500	.000	-.05520	.05780	-.00790	.01030	.00000	.12180	.07940
-.500	2.000	.01650	-.01250	-.00810	.01220	-.00080	.11930	.07600
-.500	4.000	.06360	-.07220	-.00660	.01140	-.00140	.12220	.06910
-.500	6.000	.14420	-.11760	-.00630	.01100	-.00170	.12060	.06360
-.500	8.000	.20750	-.16560	-.00780	.01090	-.00230	.11660	.05960
GRADIENT		.03251	-.02877	-.00013	.00019	-.00028	-.00022	-.00202

RUN NO. 2017/0 RN/L = 6.20 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-6.000	-.25470	.16300	-.01110	.01240	.00060	.11670	.06760
.000	-6.000	-.19620	.12740	-.01100	.01450	.00110	.12360	.06090
.000	-4.000	-.14440	.09690	-.01190	.01680	.00080	.12590	.07920
.000	-2.000	-.09120	.06360	-.00970	.01420	.00030	.12380	.07660
.000	.000	-.03420	.01760	-.00980	.01390	.00010	.11920	.07690
.000	2.000	.02920	-.04150	-.01130	.01660	-.00060	.11780	.07680
.000	4.000	.09090	-.09480	-.01000	.01600	-.00120	.11880	.07220
.000	6.000	.14740	-.13170	-.00490	.00840	-.00160	.11250	.07190
.000	8.000	.20560	-.17300	-.00640	.00670	-.00210	.10830	.06940
GRADIENT		.02955	-.02463	-.00011	.00004	-.00024	-.00101	-.00079

RUN NO. 2016/0 RN/L = 6.22 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.500	-6.000	-.21290	.09340	-.01460	.01380	.00060	.11870	.07870
.500	-6.000	-.15740	.06090	-.00970	.01070	.00100	.12370	.07520
.500	-4.000	-.10690	.03610	-.00700	.00970	.00110	.12580	.07230
.500	-2.000	-.05550	.00280	-.00790	.01190	.00090	.12400	.07190
.500	.000	.00050	-.03730	-.00820	.01170	.00040	.12130	.07110
.500	2.000	.03420	-.06560	-.00670	.01280	-.00020	.11780	.07010
.500	4.000	.11050	-.13260	-.00720	.01190	-.00100	.11880	.06770
.500	6.000	.15640	-.15650	-.00770	.01160	-.00170	.11460	.06440
.500	8.000	.21000	-.19040	-.01070	.01440	-.00240	.10940	.06420
GRADIENT		.02722	-.02129	-.00008	.00026	-.00028	-.00103	-.00059

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 48

MSFC 558 (MA9F) NR ATP (T3) (S1) / (O1)

(R76T02) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

BETA = .000 ORBINC = .000
 MACH = .900 ELEVON = .000
 DELZ/D = -1.000

RUN NO. 2019/ 0 RN/L = 6.19 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
-.500	-6.000	-.30470	.25640	-.00630	.01070	-.00020	.11720	.08700
-.500	-6.000	-.23570	.20090	-.00420	.00830	.00000	.12070	.06280
-.500	-4.000	-.17160	.15510	-.00390	.00800	.00010	.12520	.07690
-.500	-2.000	-.10730	.10460	-.00510	.00920	.00020	.12480	.07400
-.500	.000	-.04050	.03570	-.00760	.01170	-.00010	.12490	.07030
-.500	2.000	.03470	-.03620	-.00550	.00930	-.00100	.12410	.06700
-.500	4.000	.10050	-.09560	-.00640	.01120	-.00160	.12460	.06060
-.500	6.000	.17010	-.15140	.00490	.00870	-.00230	.12170	.05800
-.500	8.000	.23650	-.20300	-.00640	.00910	-.00280	.11840	.05460
GRADIENT		.03429	-.03211	-.00027	.00032	-.00023	-.00007	-.00198

RUN NO. 2020/ 0 RN/L = 6.19 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-6.000	-.27190	.19590	-.01200	.01310	.00030	.11690	.08880
.000	-6.000	-.20850	.15110	-.01050	.01280	.00040	.12250	.08310
.000	-4.000	-.14970	.11580	-.00710	.01050	.00030	.12450	.08010
.000	-2.000	-.09370	.07410	-.00600	.01130	.00000	.12330	.07870
.000	.000	-.02740	.01380	-.00840	.01120	-.00030	.12090	.07700
.000	2.000	.04320	-.05660	-.00630	.01010	-.00030	.12300	.07290
.000	4.000	.10750	-.11070	-.00460	.00890	-.00100	.12140	.06660
.000	6.000	.16570	-.15450	-.00570	.00910	-.00210	.11750	.06470
.000	8.000	.22870	-.20110	-.00600	.01090	-.00280	.11310	.06260
GRADIENT		.03256	-.02918	.00033	-.00022	-.00014	-.00033	-.00174

RUN NO. 2021/ 0 RN/L = 6.18 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.500	-6.000	-.24720	.15650	-.00640	.00850	.00020	.12160	.07360
.500	-6.000	-.18140	.10480	-.00920	.01270	.00050	.12200	.07060
.500	-4.000	-.12000	.06170	-.01150	.01620	.00080	.12260	.06870
.500	-2.000	-.06700	.03000	-.00870	.01340	.00050	.12250	.06740
.500	.000	-.00770	-.01920	-.00700	.01030	.00000	.11940	.06950
.500	2.000	.05600	-.06330	-.00740	.01090	-.00070	.12090	.06700
.500	4.000	.12290	-.14010	-.00730	.01120	-.00140	.11840	.06450
.500	6.000	.17680	-.17580	-.00620	.00940	-.00210	.11660	.06140
.500	8.000	.23370	-.21460	-.00670	.00930	-.00270	.11160	.06070
GRADIENT		.03044	-.02984	.00048	-.00063	-.00028	-.00052	-.00044

DATE 26 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 49

MSFC 558 (MA9F) NR ATP (T3) (S1) / (O1)

(R78T03) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

BETA = .000 ORBINC = .000
 MACH = .900 ELEVON = .000
 DELZ/D = -1.500

RUN NO. 2041/0 RN/L = 6.18 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
-1.000	-6.340	-.48780	.36170	.02070	-.01690	.00250	.03140	.03380
-1.000	-6.160	-.39760	.29970	.02120	-.01680	.00260	.03340	.03200
-1.000	-4.010	-.29530	.22830	.02110	-.01680	.00200	.03620	.03040
-1.000	-1.860	-.19450	.15770	.01940	-.01520	.00210	.03750	.03050
-1.000	.250	-.10230	.09450	.01810	-.01390	.00120	.03670	.02980
-1.000	2.400	-.01390	.03340	.01600	-.01350	.00050	.03570	.02960
-1.000	4.550	.08930	-.03700	.01660	-.01230	.00090	.02940	.02900
-1.000	6.740	.19150	-.10790	.01550	-.01150	.00090	.02400	.02780
-1.000	8.830	.27940	-.16900	.01390	-.01050	.00130	.02320	.02800
GRADIENT		.04443	-.03063	-.00049	.00050	-.00018	-.00072	-.00017

RUN NO. 2040/0 RN/L = 6.19 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
-.500	-6.000	-.30250	.25420	-.00780	.00900	-.00040	.11930	.06100
-.500	-6.000	-.23160	.19650	-.00670	.00120	.00000	.12420	.07550
-.500	-4.000	-.16880	.15400	-.00670	.00910	.00000	.12720	.07220
-.500	-2.000	-.10420	.10200	-.00530	.00610	.00020	.12710	.07060
-.500	.000	-.03270	.03150	-.00560	.00770	-.00020	.12500	.06890
-.500	2.000	.04670	-.05240	-.00600	.00940	-.00050	.12650	.06390
-.500	4.000	.11810	-.11850	-.00630	.01020	-.00110	.12590	.05980
-.500	6.000	.18400	-.17200	-.00440	.00730	-.00160	.12110	.05900
-.500	8.000	.25080	-.22510	-.00600	.00830	-.00250	.11570	.05770
GRADIENT		.03623	-.03497	.00001	.00017	-.00014	-.00016	-.00160

RUN NO. 2037/0 RN/L = 6.18 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-6.000	-.28660	.22610	-.00930	.01200	.00000	.12060	.07470
.000	-6.000	-.21940	.17340	-.00630	.01150	.00010	.12390	.07070
.000	-4.000	-.15760	.13090	-.00570	.00910	.00040	.12440	.07030
.000	-2.000	-.09720	.08440	-.00790	.01110	.00000	.12500	.06830
.000	.000	-.02730	.01700	-.00770	.01010	-.00010	.12420	.06630
.000	2.000	.05130	-.06350	-.00680	.00990	-.00050	.12320	.06410
.000	4.000	.11730	-.12240	-.00850	.01260	-.00130	.12360	.06060
.000	6.000	.18110	-.17180	-.00660	.01220	-.00190	.12020	.05910
.000	8.000	.24810	-.22360	-.00720	.00940	-.00250	.11400	.05850
GRADIENT		.03491	-.03273	-.00023	.00029	-.00019	-.00017	-.00118

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 50

MSFC 558 (MA9F) NR ATP (T3) (S1) / (O1)

(R78T03) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
LREF = 1328.0000 INCHES YMRP = .0000
BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
SCALE = 100.0000 PER

PARAMETRIC DATA

BETA = .000 ORBINC = .000
MACH = .900 ELEVON = .000
DELZ/D = -1.500

RUN NO. 2036/0 RN/L = 8.19 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.500	-8.000	-.29540	.17250	-.01120	.01140	.00000	.12010	.06610
.500	-6.000	-.19250	.12530	-.01040	.01150	.00020	.12490	.06220
.500	-4.000	-.13300	.08840	-.00910	.01190	.00050	.12800	.05900
.500	-2.000	-.07380	.04610	-.00800	.01090	.00030	.12540	.06010
.500	.000	-.00970	-.01210	-.00760	.00970	.00000	.12270	.06330
.500	2.000	.06150	-.08580	-.00900	.01220	-.00060	.12400	.06010
.500	4.000	.12650	-.14270	-.00530	.00850	-.00120	.12120	.05930
.500	6.000	.18560	-.18650	-.00550	.00760	-.00170	.11690	.05900
.500	8.000	.24700	-.23110	-.00680	.00680	-.00200	.11360	.05690
GRADIENT		.03271	-.02970	.00033	-.00027	-.00021	-.00075	.00003

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 51

MSFC 558 (MA9F) NR ATP (T3) (S1) / (O1)

(R78T04) (29 MAR 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRF = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

BETA = .000 ORBINC = 2.000
 MACH = .900 ELEVON = .000
 DELZ/D = -.320

RUN NO. 2073/0 RN/L = 6.19 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
-.500	-6.000	-.31240	.26280	-.01040	.01280	.00050	.11680	.09120
-.500	-6.000	-.25150	.22200	-.01020	.01300	.00060	.12200	.06660
-.500	-4.000	-.19060	.18260	-.00810	.01110	.00050	.12340	.06270
-.500	-2.000	-.13330	.14160	-.00330	.00470	.00040	.12540	.07760
-.500	.000	-.07290	.09050	-.00250	.00230	.00030	.12260	.07560
-.500	2.000	.00060	.01490	-.00700	.00960	-.00080	.12470	.06730
-.500	4.000	.06550	-.04150	-.00580	.00900	-.00110	.12930	.06170
-.500	6.000	.12330	-.06400	-.00590	.00900	-.00160	.12120	.05710
-.500	8.000	.18630	-.13550	-.00780	.00970	-.00210	.11940	.05320
GRADIENT		.03230	-.02876	.00004	.00003	-.00022	.00016	-.00262

RUN NO. 2070/0 RN/L = 6.16 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-6.000	-.28750	.21920	-.00390	.00690	.00040	.11690	.08450
.000	-6.000	-.22790	.17870	-.00490	.00900	.00090	.11680	.08220
.000	-4.000	-.17540	.14680	-.00590	.00970	.00090	.11610	.08450
.000	-2.000	-.12420	.11510	-.00580	.00810	.00050	.11710	.08180
.000	.000	-.06610	.06930	-.00490	.00670	.00020	.11620	.07890
.000	2.000	-.00700	.01450	-.00520	.00710	-.00060	.11500	.07550
.000	4.000	.05480	-.03720	-.00340	.00570	-.00110	.11570	.07320
.000	6.000	.11090	-.07720	-.00530	.00780	-.00130	.11320	.06850
.000	8.000	.17170	-.12290	-.00760	.00920	-.00190	.10960	.06540
GRADIENT		.02868	-.02341	.00028	-.00045	-.00025	-.00022	-.00143

RUN NO. 2074/0 RN/L = 6.18 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.500	-6.000	-.24150	.13940	-.00910	.01120	.00120	.12410	.07290
.500	-6.000	-.18460	.10200	-.00860	.01210	.00140	.12620	.06980
.500	-4.000	-.13110	.06950	-.00840	.01260	.00110	.12910	.06630
.500	-2.000	-.07660	.03670	-.00610	.00950	.00090	.12980	.07020
.500	.000	-.02640	.00160	-.00810	.01100	.00040	.12260	.06930
.500	2.000	.02240	-.03690	-.00890	.00960	-.00010	.12160	.06840
.500	4.000	.07740	-.06250	-.00520	.00650	-.00100	.11880	.06590
.500	6.000	.13030	-.11350	-.00610	.00770	-.00140	.11530	.06420
.500	8.000	.18790	-.15810	-.00730	.00770	-.00180	.11060	.06110
GRADIENT		.02590	-.01898	.00028	-.00040	-.00028	-.00124	-.00043

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 52

MSFC 558 (MA9F) NR ATP (T3) (S1)/(O1)

(R78T05) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

BETA = .000 ORBINC = 2.000
 MACH = .900 ELEVON = .000
 DELZ/D = -1.000

PARAMETRIC DATA

RUN NO. 2089/0 RN/L = 6.18 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
-.500	-8.000	-.30970	.26230	-.01270	.01470	-.00020	.11750	.06360
-.500	-6.000	-.24030	.21010	-.01090	.01350	.00030	.12290	.07770
-.500	-4.000	-.18000	.17130	-.01110	.01500	.00020	.12740	.07360
-.500	-2.000	-.11970	.12510	-.00840	.01110	.00000	.12680	.07060
-.500	.000	-.04960	.05730	-.00630	.01050	-.00040	.12640	.06680
-.500	2.000	.02470	-.01850	-.00870	.01360	-.00080	.12870	.06380
-.500	4.000	.09220	-.08020	-.01110	.01760	-.00160	.12550	.05770
-.500	6.000	.15830	-.13250	-.00930	.01450	-.00220	.12300	.05450
-.500	8.000	.22080	-.17900	-.01030	.01370	-.00280	.11810	.05140
GRADIENT		.03444	-.03233	-.00001	.00038	-.00022	-.00010	-.00193

RUN NO. 2086/0 RN/L = 6.18 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
0.000	-8.000	-.27840	.20720	-.01460	.01590	.00000	.12130	.06070
.000	-6.000	-.21550	.16410	-.01240	.01450	.00010	.12510	.07620
.000	-4.000	-.15640	.12780	-.00920	.01290	.00020	.12860	.07360
.000	-2.000	-.09830	.08680	-.00680	.00990	.00010	.12620	.07260
.000	.000	-.03840	.03330	-.00640	.00600	.00000	.12190	.07290
.000	2.000	.03240	-.03690	-.00950	.01280	-.00110	.12050	.07040
.000	4.000	.09490	-.09010	-.00890	.01360	-.00160	.12010	.06370
.000	6.000	.14620	-.12640	-.00900	.01400	-.00190	.12080	.06030
.000	8.000	.20990	-.17500	-.00950	.01320	-.00220	.11600	.05890
GRADIENT		.03166	-.02797	-.00011	.00023	-.00024	-.00093	-.00112

RUN NO. 2085/0 RN/L = 6.17 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.500	-8.000	-.24610	.15620	-.01100	.01140	.00040	.12200	.07420
.500	-6.000	-.18490	.11310	-.01070	.01220	.00050	.12600	.07040
.500	-4.000	-.12850	.06060	-.00990	.01320	.00050	.12700	.06810
.500	-2.000	-.07510	.04440	-.01030	.01440	.00030	.12410	.06960
.500	.000	-.01750	-.00080	-.00890	.01190	-.00020	.12240	.06920
.500	2.000	.04620	-.06220	-.01040	.01430	-.00090	.12060	.06660
.500	4.000	.10420	-.11120	-.00980	.01510	-.00130	.11910	.06290
.500	6.000	.15990	-.15130	-.00860	.01330	-.00190	.11610	.06160
.500	8.000	.21540	-.18920	-.00730	.00910	-.00260	.11090	.06440
GRADIENT		.02933	-.02451	-.00000	.00018	-.00024	-.00097	-.00066

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

(R78T06) (29 JAN 73)

MSFC 558 (MA9F) NR ATP (T3) (S1)/(D1)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

BETA = .000 ORBINC = 2.000
 MACH = .900 ELEVON = .000
 DELZ/D = -1.500

RUN NO. 2031/0 RN/L = 6.28 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
-.900	-6.000	-.29730	.29050	-.01040	.01150	-.00030	.11920	.07900
-.900	-6.000	-.22950	.19860	-.00660	.01020	-.00010	.12390	.07380
-.900	-4.000	-.16330	.19290	-.00590	.00830	.00010	.12500	.07180
-.900	-2.000	-.09950	.10270	-.00240	.00430	.00010	.12560	.06910
-.900	.000	-.02910	.03180	-.00150	.00280	-.00020	.12390	.06670
-.500	2.000	.09050	-.05400	-.00670	.01040	-.00110	.12610	.06090
-.500	4.000	.12060	-.11870	-.00440	.00850	-.00150	.12610	.05510
-.500	6.000	.18550	-.16920	-.00090	.00290	-.00190	.12110	.05440
-.500	8.000	.25310	-.22270	-.00180	.00220	-.00240	.11600	.05320
GRADIENT		.03569	-.03499	-.00007	.00035	-.00022	.00014	-.00204

RUN NO. 2030/0 RN/L = 6.31 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-6.000	-.26780	.20130	-.01090	.01140	-.00010	.12010	.07700
.000	-6.000	-.20140	.15200	-.00920	.01040	.00000	.12470	.07190
.000	-4.000	-.13930	.11120	-.00600	.00660	.00020	.12780	.06850
.000	-2.000	-.08220	.06910	-.00300	.00770	.00000	.12490	.07060
.000	.000	-.01410	.00490	-.00510	.00670	-.00030	.12270	.06970
.000	2.000	.06120	-.07480	-.00730	.01060	-.00090	.12420	.06590
.000	4.000	.13030	-.13680	-.00400	.00600	-.00110	.12110	.06330
.000	6.000	.19300	-.18480	-.00510	.00660	-.00190	.11800	.06090
.000	8.000	.25600	-.23280	-.00610	.00810	-.00250	.11350	.05740
GRADIENT		.03413	-.03200	-.00009	.00006	-.00017	-.00071	-.00077

RUN NO. 2049/0 RN/L = 6.29 GRADIENT INTERVAL = -5.00/ 5.00

VELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.900	-6.000	-.25160	.17070	-.00950	.00920	.00010	.11960	.06860
.900	-6.000	-.18890	.12510	-.01030	.01190	.00030	.12360	.06500
.900	-4.000	-.13050	.09050	-.00750	.01000	.00040	.12590	.06290
.900	-2.000	-.07460	.05070	-.00770	.01100	.00030	.12450	.06350
.900	.000	-.01370	-.00210	-.00650	.00690	-.00010	.12050	.06920
.900	2.000	.05630	-.07690	-.00760	.01130	-.00070	.12140	.06240
.900	4.000	.12640	-.13580	-.00320	.00700	-.00110	.12020	.05940
.900	6.000	.17930	-.17340	-.00110	.00420	-.00190	.11430	.06010
.900	8.000	.23940	-.21930	-.00480	.00730	-.00200	.11090	.06000
GRADIENT		.03254	-.02999	-.00042	-.00029	-.00020	-.00072	-.00041

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 84

MSFC 558 (MA9F) NR ATP (T3) (S1) / (O1)

(RTBTOT) (29 JAN 73)

REFERENCE DATA

BREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

BETA = .000 ORBINC = .000
 MACH = .900 ELEVON = 10.000
 DELZ/D = -.520

RUN NO. 2014/0 RN/L = 6.21 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-6.000	-.27630	.20480	-.01050	.01550	.00050	.11790	.07740
.000	-6.000	-.21670	.16390	-.00860	.01320	.00060	.12110	.07260
.000	-4.000	-.16310	.13250	-.00750	.01260	.00050	.12310	.07090
.000	-2.000	-.10950	.09820	-.00910	.01330	.00030	.12400	.06890
.000	.000	-.05140	.05120	-.01020	.01410	-.00010	.12110	.06640
.000	2.000	.01410	-.01030	-.00880	.01340	-.00060	.12190	.06580
.000	4.000	.07240	-.05930	-.01070	.01710	-.00110	.12250	.05760
.000	6.000	.12680	-.09660	-.00630	.01370	-.00180	.11750	.05580
.000	8.000	.18990	-.14040	-.00990	.01360	-.00250	.11330	.05430
GRADIENT	.02973	-.02460	-.00030	.00046	-.00024	-.00017	-.00159	

RUN NO. 2015/0 RN/L = 6.21 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.500	-6.000	-.24960	.15550	-.01170	.01290	.00040	.11470	.07350
.500	-6.000	-.19870	.13030	-.01060	.01350	.00060	.12150	.06960
.500	-4.000	-.15230	.11260	-.00960	.01400	.00060	.12310	.06560
.500	-2.000	-.09660	.07410	-.01290	.01860	.00060	.12270	.06470
.500	.000	-.04360	.03720	-.01130	.01650	.00010	.12070	.06720
.500	2.000	.01540	-.01640	-.01110	.01720	-.00040	.11640	.06580
.500	4.000	.06640	-.05760	-.01260	.02080	-.00120	.11670	.06160
.500	6.000	.11840	-.06930	-.00440	.00980	-.00110	.11170	.06230
.500	8.000	.17490	-.12910	-.00300	.00660	-.00170	.10700	.06200
GRADIENT	.02748	-.02154	-.00021	.00060	-.00023	-.00115	-.00039	

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 55

MSFC 558 (MASF) NR ATP (T3) (S1) / (O1)

(UR78TDB) (29 JAN 73)

REFERENCE DATA

BREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

BETA = .000 ORBINC = .000
 MACH = .900 ELEVON = 10,000
 DELZ/D = -1.000

PARAMETRIC DATA

RUN NO. 2023/ 0 RN/L = 6.21 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-6.000	-.28530	.21900	-.01220	.01410	.00010	.12110	.07460
.000	-3.000	-.22200	.17620	-.01120	.01390	.00030	.12580	.06820
.000	-4.000	-.16380	.14120	-.00790	.01140	.00090	.12820	.06470
.000	-2.000	-.10510	.09780	-.00630	.01240	.00010	.12710	.06430
.000	.000	-.04200	.04080	-.00610	.00890	.00000	.12820	.06290
.000	2.000	.02640	-.02750	-.00730	.01110	-.00100	.12380	.06050
.000	4.000	.09140	-.08500	-.00730	.01220	-.00100	.12380	.05560
.000	6.000	.14760	-.12390	-.00650	.01100	-.00100	.11950	.05310
.000	8.000	.21120	-.17080	-.00600	.01180	-.00290	.11800	.05060
GRADIENT		.03209	-.02666	.00011	.00001	-.00026	-.00060	-.00108

RUN NO. 2022/ 0 RN/L = 6.22 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.900	-6.000	-.20050	.13850	-.01320	.01570	.00030	.12720	.06170
.900	-4.000	-.14990	.11490	-.01140	.01510	.00030	.13070	.05860
.900	-2.000	-.09180	.07420	-.00630	.01290	.00020	.12560	.05960
.900	.000	-.03370	.02790	-.00520	.00610	.00000	.12360	.06150
.900	2.000	.03040	-.03710	-.00870	.01440	-.00080	.12300	.05820
.900	4.000	.09080	-.08820	-.00810	.01340	-.00100	.12290	.05660
.900	6.000	.14820	-.12680	-.00460	.00870	-.00170	.11560	.05720
.900	8.000	.20410	-.16450	-.00700	.01000	-.00230	.10990	.05430
GRADIENT		.03019	-.02567	.00027	-.00007	-.00024	-.00065	-.00025

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 56

MSFC 558 (MA9F) NR ATP (T3) (S1)/(O1)

(R78T09) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1320.0000 INCHES YMRP = .0000
 BREF = 1320.0000 INCHES ZMRP = -61.3000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

BETA = .000 ORBINC = .000
 MACH = .900 ELEVON = -20.000
 DELZ/D = -.920

RUN NO. 2011/0 RN/L = 6.20 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-8.390	-.73160	.60350	.00480	-.00690	.00110	.09680	.04940
.000	-8.260	-.64880	.54250	.00730	-.00900	.00070	.09970	.04600
.000	-4.150	-.56500	.46430	.00610	-.00790	-.00060	.10140	.04760
.000	-2.040	-.48440	.42230	.00700	-.00660	-.00060	.09950	.04530
.000	.050	-.40150	.36320	.00710	-.00640	-.00060	.09790	.04320
.000	2.180	-.32100	.30480	.00700	-.00610	-.00090	.09320	.04450
.000	4.270	-.24720	.25170	.00700	-.00790	-.00110	.06630	.04320
.000	6.420	-.16590	.19290	.00600	-.00730	-.00100	.06070	.04030
.000	8.470	-.09350	.13720	.00740	-.00660	-.00230	.07810	.03380
GRADIENT	.03622	-.02767	.00009	.00002	.00006	-.00173	-.00046	

RUN NO. 2010/0 RN/L = 6.20 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.900	-8.360	-.66780	.57800	.00320	-.00580	.00020	.09320	.05190
.900	-8.230	-.63530	.53330	.00320	-.00730	.00000	.09530	.04780
.900	-4.130	-.56240	.46170	.00490	-.00720	-.00110	.09570	.04630
.900	-2.030	-.48520	.42560	.00600	-.00790	-.00140	.09580	.04470
.900	.060	-.39620	.36010	.00540	-.00700	-.00040	.08410	.04440
.900	2.200	-.31050	.29710	.00460	-.00680	-.00200	.08950	.04470
.900	4.270	-.23010	.23970	.00460	-.00630	-.00060	.06250	.04370
.900	6.430	-.14200	.17540	.00390	-.00580	-.00150	.07500	.04130
.900	8.520	-.06080	.11360	.00520	-.00680	-.00180	.07180	.03670
GRADIENT	.03991	-.02913	-.00010	.00013	.00002	-.00155	-.00025	

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 57

MSFC 558 (MA9F) NR ATP (T3) (S1) / (O1)

(07810) (29 JAN 73)

REFERENCE DATA

BREF = 3220.0000 SQ.FT. XMAP = .0000
 LREF = 1324.0000 INCHES YMAP = .0000
 BREF = 1328.0000 INCHES ZMAP = -61.5000 INCHES
 SCALE = 100.0000 PER

BETA = .000 ORBINE = .000
 MACH = .900 ELEVON = -20.000
 DELZ/D = -1.000

PARAMETRIC DATA

RUN NO. 2024/0 RNL = 6.21 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-6.510	-.79950	.64960	.01500	-.01480	.00110	.09580	.09070
.000	-6.390	-.72370	.59660	.01690	-.01590	.00160	.10070	.04630
.000	-4.230	-.62860	.52870	.01660	-.01600	.00000	.10310	.04530
.000	-2.120	-.53270	.43950	.01600	-.01590	.00000	.10280	.04460
.000	.000	-.44070	.39280	.01590	-.01500	.00020	.10000	.04340
.000	2.150	-.35440	.33120	.01650	-.01510	.00010	.09540	.04330
.000	4.250	-.26740	.27000	.01540	-.01390	.00000	.08860	.04260
.000	6.410	-.16690	.19430	.01420	-.01290	.00000	.08050	.03970
.000	8.530	-.06320	.11960	.01390	-.01240	-.00060	.07280	.03670
GRADIENT	.04242	-.03041	-.00000	.00022	-.00000	-.00169	-.00030	

RUN NO. 2025/0 RNL = 6.20 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.900	-6.480	-.76760	.62390	.01540	-.01490	.00210	.01240	.09030
.900	-6.360	-.70110	.57890	.01780	-.01640	.00180	.08660	.04640
.900	-4.240	-.62010	.52120	.01690	-.01620	.00060	.09660	.04420
.900	-2.090	-.52360	.45170	.01620	-.01590	.00040	.09620	.04370
.900	.010	-.43640	.39200	.01750	-.01610	.00080	.09610	.04470
.900	2.170	-.34030	.32170	.01790	-.01550	.00080	.08400	.04470
.900	4.270	-.25280	.25940	.01740	-.01510	.00060	.08630	.04220
.900	6.440	-.14980	.18480	.01370	-.01280	-.00110	.08000	.03940
.900	8.570	-.03480	.10210	.01430	-.01290	-.00060	.07050	.03670
GRADIENT	.04314	-.03078	.00011	.00010	.00004	-.00116	-.00014	

DATE 29 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 50

MSFC 558 (MAGF) NR ATP (T3) (S1)/(O1)

(R78T11) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

BETA = .000 JBBINC = 2.000
 MACH = .900 ELEVON = 10.000
 DELZ/D = -.520

PARAMETRIC DATA

RUN NO. 2078/0 RNU/L = 6.17 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-8.000	-.30290	.24820	-.01090	.01500	.00020	.11830	.07390
.000	-6.000	-.24570	.21110	-.01080	.01510	.00050	.11990	.07190
.000	-4.000	-.19170	.18000	-.00830	.01270	.00060	.12140	.06990
.000	-2.000	-.13790	.14650	-.00560	.00820	.00030	.12160	.06780
.000	.000	-.08690	.10630	-.00930	.01090	-.00030	.12210	.06710
.000	2.000	-.02320	.04870	-.00870	.01190	-.00120	.11860	.06530
.000	4.000	.04230	-.00640	-.00670	.01100	-.00130	.11980	.05790
.000	6.000	.09790	-.04900	-.00630	.00960	-.00170	.11680	.05460
.000	8.000	.15700	-.09370	-.00910	.01130	-.00240	.11470	.05200
GRADIENT		.02913	-.02373	.00000	.00003	-.00026	-.00031	-.00133

RUN NO. 2077/0 RNU/L = 6.17 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.900	-8.000	-.26640	.18580	-.01430	.01500	.00060	.12160	.06940
.900	-6.000	-.21460	.15890	-.01230	.01360	.00070	.12560	.06690
.900	-4.000	-.16460	.13560	-.00930	.01260	.00070	.12730	.06530
.900	-2.000	-.11250	.10420	-.00940	.01340	.00060	.12350	.06700
.900	.000	-.06990	.08080	-.00860	.01160	.00010	.12020	.06840
.900	2.000	-.01540	.03560	-.00700	.00960	-.00050	.11620	.06420
.900	4.000	.04000	-.01270	-.00560	.00910	-.00130	.11420	.06620
.900	6.000	.09430	-.05150	-.00470	.00580	-.00140	.11110	.06490
.900	8.000	.15310	-.09650	-.00570	.00560	-.00180	.10630	.06460
GRADIENT		.02531	-.01826	.00049	-.00055	-.00029	-.00164	.00005

DATE 26 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 59

MSFC 558 (MA9F) NR ATP (T3) (S1)/(O1)

(R78T12) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

BETA = .000 ORG. INC = 2.000
 MACH = .900 ELEVON = 10.000
 DELZ/D = -1.000

RUN NO. 2081/0 RN/L = 6.30 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-8.000	-.28230	.22420	-.00900	.01150	.00040	.12000	.07050
.000	-6.000	-.21870	.17720	-.00850	.01060	.00050	.12390	.06720
.000	-4.000	-.16210	.14220	-.00580	.00860	.00070	.12610	.06460
.000	-2.000	-.10370	.10150	-.00520	.00740	.00020	.12420	.06270
.000	.000	-.04560	.05300	-.00550	.00740	-.00010	.12210	.06220
.000	2.000	.02500	-.01850	-.00720	.01100	-.00080	.12370	.05660
.000	4.000	.08640	-.07240	-.00790	.01320	-.00100	.12160	.05270
.000	6.000	.14610	-.11700	-.00850	.01360	-.00170	.12290	.04950
.000	8.000	.20780	-.16120	-.00790	.01110	-.00210	.12000	.04700
GRADIENT		.03128	-.02746	-.00031	.00064	-.00022	-.00052	-.00149

RUN NO. 2082/0 RN/L = 6.23 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.500	-8.000	-.25520	.17760	-.01280	.01320	.00060	.12100	.06620
.500	-6.000	-.19790	.14260	-.01060	.01170	.00070	.12500	.06340
.500	-4.000	-.14460	.11400	-.01070	.01390	.00060	.12800	.06050
.500	-2.000	-.09220	.06040	-.00960	.01340	.00040	.12500	.06280
.500	.000	-.03650	.03690	-.00750	.01000	.00000	.12160	.06440
.500	2.000	.02630	-.02350	-.00940	.01340	-.00060	.12010	.06140
.500	4.000	.08610	-.07450	-.01560	.00990	-.00110	.11770	.05930
.500	6.000	.13970	-.11230	-.00440	.00800	-.00140	.11480	.05930
.500	8.000	.19710	-.15380	-.00600	.00620	-.00160	.10970	.06710
GRADIENT		.02899	-.02404	.00052	-.00040	-.00023	-.00123	-.00019

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 80

MSFC 558 (MA9F) NR ATP (T3) (S2) / (O1)

(R78T13) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

BETA = .000 ORBINC = .000
 MACH = 1.200 ELEVON = .000
 DELZ/D = -.520

RUN NO. 2072/0 RN/L = 6.56 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
-.500	-8.000	-.31340	.2520	-.00840	.00910	.00010	.17380	.10220
-.500	-6.000	-.24020	.19790	-.00860	.00960	.00010	.17710	.09520
-.500	-4.000	-.17650	.15260	-.00800	.00880	.00000	.17950	.08990
-.500	-2.000	-.11820	.11550	-.00760	.00840	.00000	.18260	.08400
-.500	.000	-.06390	.06760	-.00610	.00670	-.00020	.18100	.07790
-.500	2.000	-.00730	.04810	-.00620	.00790	-.00090	.17610	.07230
-.500	4.000	.05130	.00730	-.00480	.00410	-.00110	.17790	.06580
-.500	6.000	.10630	-.02220	-.00260	.00040	-.00140	.17790	.06130
-.500	8.000	.17120	-.06430	-.00190	-.00050	-.00160	.17530	.05620
GRADIENT		.02632	-.01790	.00039	-.00049	-.00015	-.00048	-.00300

RUN NO. 2071/0 RN/L = 6.57 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-8.000	-.29130	.20520	-.01150	.01450	.00040	.16770	.10930
.000	-6.000	-.22100	.15320	-.01100	.01500	.00060	.16990	.10510
.000	-4.000	-.16120	.11720	-.01030	.01490	.00050	.17190	.10140
.000	-2.000	-.11010	.09320	-.00830	.01200	.00040	.17370	.09710
.000	.000	-.06390	.07570	-.00480	.00670	.00020	.17250	.09210
.000	2.000	-.01340	.04560	-.00390	.00840	-.00010	.17140	.08390
.000	4.000	.04090	.01390	-.00320	.00400	-.00050	.17090	.07860
.000	6.000	.09190	-.01240	-.00160	.00130	-.00110	.17110	.07520
.000	8.000	.15280	-.05270	-.00050	-.00020	-.00150	.16970	.07320
GRADIENT		.02504	-.01271	.00063	-.00127	-.00012	-.00022	-.00294

RUN NO. 2073/0 RN/L = 6.58 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.500	-8.000	-.27390	.17610	-.01590	.02090	.00330	.17160	.09450
.500	-6.000	-.20980	.13340	-.01430	.01930	.00040	.17350	.09290
.500	-4.000	-.15180	.09780	-.01160	.01630	.00030	.17370	.09190
.500	-2.000	-.10040	.07100	-.00990	.01310	.00000	.17300	.09090
.500	.000	-.05690	.05390	-.00860	.01360	-.00010	.17010	.09050
.500	2.000	-.00567	.02080	-.00860	.01420	-.00070	.16600	.08640
.500	4.000	.04610	-.01370	-.00740	.01100	-.00140	.16550	.08450
.500	6.000	.10020	-.05050	-.00380	.00520	-.00190	.16150	.08400
.500	8.000	.16120	-.09550	-.00150	.00170	-.00150	.15910	.08330
GRADIENT		.02453	-.01366	.00047	-.00054	-.00020	-.00117	-.00087

DATE 26 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 61

MSFC 558 (MA9F) NR ATP (T3) (S1) / (O1)

(R78T14) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

BETA = .000 ORBINC = .000
 MACH = 1.200 ELEVON = .000
 DELZ/D = -1.000

RUN NO. 2094/0 RN/L = 6.55 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
-1.000	-6.000	-.30760	.25700	-.00720	.00960	-.00040	.18470	.08690
-1.000	-6.000	-.22790	.18600	-.00600	.01120	-.00020	.18520	.08320
-1.000	-4.000	-.15580	.12700	-.00680	.01250	-.00040	.18400	.07820
-1.000	-2.000	-.08720	.07380	-.00890	.01230	-.00040	.18350	.07180
-1.000	.000	-.02110	.02760	-.00660	.00950	-.00010	.17780	.06620
-1.000	2.000	.04720	-.02810	-.00460	.00770	-.00070	.17050	.06170
-1.000	4.000	.10960	-.07070	-.00370	.00490	-.00130	.17060	.05510
-1.000	6.000	.17550	-.11430	-.00570	.00700	-.00160	.16910	.05040
-1.000	8.000	.24680	-.16630	-.00610	.00760	-.00190	.16670	.04550
GRADIENT		.03328	-.02486	.00072	-.00099	-.00010	-.00199	-.00262

RUN NO. 2088/0 RN/L = 6.57 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
-.500	-6.000	-.31670	.26340	-.00620	.00980	-.00020	.18180	.09410
-.500	-6.000	-.24300	.20010	-.00760	.00980	-.00000	.18370	.08890
-.500	-4.000	-.17540	.14940	-.00600	.01060	-.00000	.18540	.08350
-.500	-2.000	-.11380	.10730	-.00650	.01060	-.00020	.18540	.07830
-.500	.000	-.05790	.07320	-.00960	.01270	-.00050	.18300	.07200
-.500	2.000	.00580	.02740	-.00630	.00920	-.00100	.17720	.06540
-.500	4.000	.06790	-.01530	-.00450	.00520	-.00120	.17830	.05790
-.500	6.000	.12870	-.05410	-.00540	.00600	-.00160	.17680	.05270
-.500	8.000	.19780	-.10090	-.00660	.00750	-.00190	.17310	.04840
GRADIENT		.03031	-.02046	.00046	-.00061	-.00016	-.00112	-.00319

RUN NO. 2087/0 RN/L = 6.61 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-6.000	-.30460	.23530	-.00910	.01180	-.00000	.17690	.09810
.000	-6.000	-.22860	.17430	-.00770	.01080	-.00010	.17880	.09380
.000	-4.000	-.16340	.12800	-.00730	.01070	-.00020	.17990	.09030
.000	-2.000	-.10710	.09310	-.00770	.01080	-.00000	.18130	.08630
.000	.000	-.05010	.06040	-.00450	.00610	-.00030	.18030	.08160
.000	2.000	.00510	.02360	-.00390	.00620	-.00100	.17630	.07610
.000	4.000	.06040	-.00910	-.00230	.00310	-.00110	.17820	.07090
.000	6.000	.11390	-.04000	-.00270	.00320	-.00150	.17760	.06560
.000	8.000	.17840	-.07630	-.00260	.00350	-.00200	.17570	.06060
GRADIENT		.02803	-.01719	.00069	-.00098	-.00016	-.00032	-.00245

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 62

MSFC 558 (MASF) NR ATP (T3) (S1) / (O1)

(R78T14) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

BETA = .000 ORBINC = .000
 MACH = 1.200 ELEVON = .000
 DELZ/D = -1.000

RUN NO. 2084/0 RN/L = 6.74 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.500	-8.000	-.27390	.18750	-.01310	.01750	.00020	.17360	.09910
.500	-6.000	-.20360	.13560	-.01170	.01610	.00030	.17470	.09720
.500	-4.000	-.14220	.09450	-.01210	.01660	.00030	.17530	.09520
.500	-2.000	-.08790	.06130	-.01140	.01580	.00010	.17410	.09460
.500	.000	-.03760	.03360	-.00940	.01340	-.00010	.17320	.09150
.500	2.000	.01580	.00040	-.00850	.01350	-.00040	.16980	.08720
.500	4.000	.06680	-.02700	-.00760	.01160	-.00060	.16870	.08420
.500	6.000	.12060	-.05870	-.00480	.00760	-.00090	.16760	.08090
.500	8.000	.17920	-.09610	-.00430	.00600	-.00160	.16550	.07640
GRADIENT		.02608	-.01319	.00059	-.00061	-.00011	-.00088	-.00147

RUN NO. 2095/0 RN/L = 6.56 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
1.000	-8.000	-.22490	.10490	-.01140	.01570	.00000	.18140	.08350
1.000	-6.000	-.16240	.06660	-.01180	.01670	.00000	.18150	.08320
1.000	-4.000	-.10850	.03710	-.01250	.01800	.00000	.18000	.08400
1.000	-2.000	-.06360	.01500	-.01220	.01770	.00000	.17720	.08460
1.000	.000	-.01240	-.01460	-.01180	.01700	-.00020	.17340	.08600
1.000	2.000	.03150	-.03890	-.00850	.01310	-.00050	.16690	.08690
1.000	4.000	.07860	-.06700	-.00730	.01100	-.00100	.16680	.08530
1.000	6.000	.12590	-.09410	-.00530	.00840	-.00120	.16380	.08440
1.000	8.000	.17960	-.12870	-.00360	.00570	-.00140	.16070	.08340
GRADIENT		.02346	-.01310	.00070	-.00093	-.00012	-.00173	.00024

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-556

PAGE 63

MSFC 556 (MA9F) NR ATP (T3) (S1) / (O1)

(R78T15) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRF = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

BETA = .000 ORBINC = .000
 MACH = 1.200 ELEVON = .000
 DELZ/D = -1.500

RUN NO. 2046/0 RN/L = 6.68 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
-1.000	-6.000	-.31630	.27310	-.00370	.00470	-.00060	.18160	.08340
-1.000	-6.000	-.24140	.20680	-.00450	.00640	-.00050	.18270	.07800
-1.000	-4.000	-.17100	.15220	-.00680	.00990	-.00040	.18240	.07370
-1.000	-2.000	-.10410	.10010	-.00580	.00840	-.00020	.18030	.06950
-1.000	.000	-.03590	.05010	-.00260	.00420	-.00010	.17430	.05930
-1.000	2.000	.03320	-.00910	-.00370	.00650	-.00060	.17130	.05860
-1.000	4.000	.10200	-.06100	-.00310	.00540	-.00090	.16830	.05580
-1.000	6.000	.16910	-.10740	-.00220	.00330	-.00150	.16600	.05160
-1.000	8.000	.24270	-.16030	-.00300	.00370	-.00200	.16290	.04700
GRADIENT		.03416	-.02678	.00047	-.00054	-.00007	-.00186	-.00290

RUN NO. 2047/0 RN/L = 6.69 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
-.500	-6.000	-.30490	.25450	-.00570	.00790	-.00050	.18260	.08620
-.500	-6.000	-.22720	.18690	-.00520	.00760	-.00050	.18380	.08360
-.500	-4.000	-.15740	.13070	-.00630	.00890	-.00030	.18510	.07800
-.500	-2.000	-.09240	.08150	-.00620	.00800	-.00030	.18470	.07240
-.500	.000	-.02600	.03440	-.00700	.00940	-.00060	.18150	.06600
-.500	2.000	.04450	-.02380	-.00450	.00760	-.00100	.17490	.06070
-.500	4.000	.11320	-.07640	-.00280	.00400	-.00120	.17390	.05480
-.500	6.000	.17990	-.12250	-.00250	.00290	-.00160	.17190	.05050
-.500	8.000	.25470	-.17580	-.00250	.00250	-.00200	.16750	.04770
GRADIENT		.03390	-.02597	.00044	-.00051	-.00012	-.00161	-.00291

RUN NO. 2046/0 RN/L = 6.73 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-6.000	-.30800	.24790	-.00610	.01100	-.00030	.17900	.09360
.000	-6.000	-.23070	.18350	-.00740	.01060	-.00010	.18120	.08840
.000	-4.000	-.16310	.13220	-.00780	.01100	-.00010	.18260	.08370
.000	-2.000	-.10090	.08780	-.00720	.01020	-.00020	.18400	.07880
.000	.000	-.04010	.04770	-.00540	.00790	-.00010	.18250	.07340
.000	2.000	.02190	.00100	-.00500	.00760	-.00090	.17930	.06790
.000	4.000	.08630	-.04350	-.00200	.00370	-.00090	.17680	.06150
.000	6.000	.14550	-.07600	-.00190	.00260	-.00140	.17600	.05660
.000	8.000	.21030	-.11840	-.00160	.00140	-.00190	.17090	.05630
GRADIENT		.03106	-.02191	.00067	-.00065	-.00011	-.00084	-.00277

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 64

MSFC 558 (MA9F) NR ATP (T3) (S1) / (O1)

(R78715) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

ETTA = .000 ORBINC = .000
 MACH = 1.200 ELEVON = .000
 DELZ/D = -1.500

PARAMETRIC DATA

RUN NO. 2043/0 RN/L = 6.69 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.500	-6.000	-.28700	.20860	-.00990	.01350	.00000	.17390	.09940
.500	-6.000	-.21240	.15080	-.00890	.01300	.00010	.17560	.09590
.500	-4.000	-.14680	.10360	-.00900	.01350	.00010	.17780	.09120
.500	-2.000	-.08760	.06440	-.00850	.01240	.00000	.17830	.08730
.500	.000	-.03270	.03140	-.00680	.01060	-.00020	.17770	.08310
.500	2.000	.02590	-.00820	-.00590	.01090	-.00060	.17580	.07710
.500	4.000	.08070	-.04010	-.00320	.00670	-.00100	.17350	.07300
.500	6.000	.13220	-.06370	-.00200	.00410	-.00150	.17340	.07100
.500	8.000	.19060	-.09650	-.00180	.00290	-.00200	.17010	.06670
GRADIENT		.02642	-.01800	.00071	-.00075	-.00014	-.00036	-.00233

RUN NO. 2044/0 RN/L = 6.69 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
1.000	-6.000	-.25890	.16110	-.00990	.01380	.00000	.17640	.08980
1.000	-6.000	-.19390	.11820	-.00900	.01280	.00010	.17630	.08910
1.000	-4.000	-.13230	.07720	-.00820	.01210	.00020	.17610	.08600
1.000	-2.000	-.07580	.04030	-.00900	.01390	.00000	.17570	.08730
1.000	.000	-.02030	.00520	-.00690	.01160	.00000	.17290	.08610
1.000	2.000	.03340	-.03120	-.00610	.01110	-.00040	.17020	.08590
1.000	4.000	.08330	-.05890	-.00520	.00970	-.00080	.16960	.08280
1.000	6.000	.13430	-.08600	-.00300	.00660	-.00110	.16920	.08000
1.000	8.000	.18610	-.11560	-.00180	.00400	-.00150	.16800	.07740
GRADIENT		.02702	-.01719	.00044	-.00038	-.00012	-.00092	-.00059

DATE 26 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-556

PAGE 63

MSFC 556 (MASF) NR ATP (T3) (S1)/(O1)

(R76116) (29 JAN 73)

REFERENCE DATA

BREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1326.0000 INCHES YMRP = .0000
 BREF = 1326.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

BETA = .000 ORBINC = 2.000
 MACH = 1.200 ELEVON = .000
 DELZ/D = -.520

RUN NO. 2001/0 RN/L = 6.56 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
-.500	-6.000	-.29860	.23340	-.00640	.00630	.00040	.17650	.10540
-.500	-6.000	-.22320	.17160	-.00610	.00630	.00050	.17920	.09760
-.500	-4.000	-.16050	.12550	-.00550	.00560	.00020	.18060	.09250
-.500	-2.000	-.10240	.08750	-.00710	.00860	.00000	.18240	.08760
-.500	.000	-.04680	.05530	-.00520	.00710	-.00020	.18050	.06320
-.500	2.000	.01220	.01180	-.00710	.01330	-.00060	.17740	.07590
-.500	4.000	.07540	-.03250	-.00330	.00520	-.00100	.17940	.06910
-.500	6.000	.13600	-.07160	-.00190	.00170	-.00150	.17750	.06520
-.500	8.000	.20200	-.11580	-.00180	.00080	-.00160	.17380	.06160
GRADIENT		.02932	-.01958	.00022	.00004	-.00016	-.00037	-.00292

RUN NO. 2002/0 RN/L = 6.60 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-6.000	-.27990	.18400	-.01500	.01470	.00050	.17210	.10360
.000	-6.000	-.20760	.13030	-.01200	.01270	.00060	.17410	.10100
.000	-4.000	-.14490	.06960	-.00960	.01140	.00090	.17470	.10030
.000	-2.000	-.09030	.05900	-.00590	.00680	.00020	.17430	.09760
.000	.000	-.03630	.03390	-.00230	.00210	.00030	.17480	.08160
.000	2.000	.01390	.00080	-.00520	.00730	-.00030	.17450	.08420
.000	4.000	.06660	-.02900	-.00360	.00470	-.00080	.17540	.07980
.000	6.000	.12170	-.05920	-.00040	-.00090	-.00090	.17430	.07630
.000	8.000	.18220	-.7.9840	.00230	-.00350	-.00130	.17210	.07370
GRADIENT		.02636	-.01460	.00061	-.00064	-.00013	.00008	-.00272

RUN NO. 2003/0 RN/L = 6.61 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.500	-6.000	-.25490	.19080	-.01810	.02150	.00030	.17000	.09720
.500	-6.000	-.19020	.10640	-.01580	.01970	.00050	.17210	.09470
.500	-4.000	-.12660	.06550	-.01280	.01640	.00050	.17250	.09250
.500	-2.000	-.07650	.03390	-.01340	.01820	.00010	.17160	.09070
.500	.000	-.03130	.01510	-.00950	.01460	.00030	.17030	.08980
.500	2.000	.01920	-.01830	-.01010	.01570	-.00070	.16900	.08640
.500	4.000	.07170	-.09140	-.00640	.01040	-.00060	.16700	.08390
.500	6.000	.12610	-.08560	-.00360	.00810	-.00110	.16410	.08240
.500	8.000	.18460	-.12560	-.00270	.00430	-.00150	.16160	.08060
GRADIENT		.02463	-.01430	.00061	-.00072	-.00017	-.00068	-.00087

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 68

MSFC 558 (MA9F) NR ATP (T3) (S1) / (O1)

(R78T17) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

BETA = .000 ORBINC = 2.000
 MACH = 1.200 ELEVON = .000
 DELZ/D = -1.000

RUN NO. 2034/0 RN/L = 6.69 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
-1.000	-8.000	-.32740	.27390	-.00560	.00540	-.00060	.18750	.09810
-1.000	-6.000	-.24740	.20510	-.00590	.00710	-.00030	.18870	.09080
-1.000	-4.000	-.17620	.14830	-.00670	.01000	-.00020	.18790	.08580
-1.000	-2.000	-.10670	.09290	-.00820	.01160	-.00010	.18540	.08180
-1.000	.000	-.04330	.04700	-.00F 1	.00890	-.00020	.18090	.07590
-1.000	2.000	.02760	-.01240	-.0040	.01040	-.00090	.17610	.06620
-1.000	4.000	.09210	-.05720	-.00520	.00730	-.00140	.17490	.06110
-1.000	6.000	.15680	-.09920	-.00540	.00660	-.00180	.17180	.05720
-1.000	8.000	.23030	-.15130	-.00560	.00650	-.00220	.16720	.05410
GRADIENT		.03354	-.02581	.00024	-.00033	-.00016	-.00176	-.00315

RUN NO. 2028/0 RN/L = 6.60 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
-.500	-8.000	-.31270	.23530	-.00590	.00620	-.00020	.18490	.09630
-.500	-6.000	-.23450	.18640	-.00450	.00600	-.00000	.18580	.09260
-.500	-4.000	-.16440	.13010	-.00590	.00820	-.00000	.18690	.08810
-.500	-2.000	-.09890	.07900	-.00850	.01120	-.00000	.18620	.08300
-.500	.000	-.03860	.03670	-.00760	.01060	-.00020	.18440	.07670
-.500	2.000	.02700	-.00960	-.00780	.01210	-.00090	.17850	.06960
-.500	4.000	.09040	-.05340	-.00460	.00740	-.00110	.17840	.06270
-.500	6.000	.15120	-.09110	-.00390	.00470	-.00180	.17590	.05600
-.500	8.000	.21960	-.13720	-.00460	.00470	-.00230	.17120	.05420
GRADIENT		.03175	-.02278	.00016	-.00003	-.00015	-.00123	-.00321

RUN NO. 2027/0 RN/L = 6.61 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-8.000	-.29640	.22300	-.00500	.00560	-.00000	.17720	.09860
.000	-6.000	-.22000	.16020	-.00570	.00740	-.00000	.17960	.09430
.000	-4.000	-.15440	.11130	-.00670	.00860	-.00000	.18010	.09140
.000	-2.000	-.09170	.06790	-.00430	.00570	-.00010	.18000	.08870
.000	.000	-.03730	.03600	-.00610	.00730	-.00030	.18160	.08250
.000	2.000	.02440	-.00680	-.00390	.00650	-.00060	.17940	.07660
.000	4.000	.06200	-.04390	-.00350	.00510	-.00110	.17830	.07350
.000	6.000	.13630	-.07590	-.00210	.00250	-.00150	.17790	.06840
.000	8.000	.20190	-.11640	-.00140	.00090	-.00200	.17490	.06370
GRADIENT		.02944	-.01933	.00034	-.00033	-.00015	-.00021	-.00226

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 07

MSFC 558 (MASF) NR ATP (T3) (S1) / (O1)

(RTG(17)) (28 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

BETA = .000 ORBINC = 2.000
 MACH = 1.200 ELEVON = .000
 DELZ/D = -1.000

RUN NO. 2026/0 RN/L = 6.61 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.500	-6.000	-.27790	.18420	-.00950	.01310	-.00010	.17570	.10010
.500	-6.000	-.20300	.12660	-.00770	.01140	.00020	.17580	.09650
.500	-4.000	-.13780	.08040	-.00710	.01120	.00040	.17630	.09590
.500	-2.000	-.07940	.04090	-.00700	.01080	.00000	.17550	.09360
.500	.000	-.02960	.01420	-.00570	.00930	.00010	.17630	.09000
.500	2.000	.02810	-.02400	-.00660	.01170	-.00050	.17290	.08590
.500	4.000	.07860	-.04950	-.00620	.01040	-.00110	.17200	.08310
.500	6.000	.13130	-.07790	-.00480	.00620	-.00150	.17020	.07940
.500	8.000	.18920	-.11330	-.00340	.00590	-.00190	.16770	.07690
GRADIENT		.02701	-.01623	.00011	-.00004	-.00017	..00056	-.00167

RUN NO. 2033/0 RN/L = 6.60 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
1.000	-6.000	-.23930	.12240	-.00980	.01310	.00020	.17950	.08760
1.000	-6.000	-.17220	.07800	-.00920	.01270	.00020	.17920	.08730
1.000	-4.000	-.11390	.04170	-.01100	.01610	.00020	.17830	.08660
1.000	-2.000	-.06010	.00690	-.00970	.01500	.00030	.17550	.08750
1.000	.000	-.00950	-.02130	-.00980	.01460	-.00010	.17400	.08710
1.000	2.000	.04420	-.05860	-.00760	.01270	-.00030	.17110	.08670
1.000	4.000	.09200	-.06250	-.00720	.01270	-.00100	.16930	.08500
1.000	6.000	.14070	-.10950	-.00620	.01080	-.00160	.16670	.08340
1.000	8.000	.19380	-.14180	-.00510	.00860	-.00160	.16390	.08230
GRADIENT		.02580	-.01579	.00057	-.00045	-.00015	-.00112	-.00022

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 68

MSFC 558 (MA9F) NR ATP (T3) (S1) / (O1)

(R78T16) (29 JAN 73)

REFERENCE DATA

BREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

BETA = .000 ORBINC = 2.000
 MACH = 1.200 ELEVON = .000
 DELZ/D = -1.500

PARAMETRIC DATA

RUN NO. 2042/0 RN/L = 6.61 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
-1.000	-8.000	.32180	.27620	-.00700	.00900	-.00050	.18430	.08410
-1.000	-6.000	.24480	.20880	-.00820	.01100	-.00040	.18550	.08000
-1.000	-4.000	.17230	.14920	-.00770	.01070	-.00030	.18490	.07620
-1.000	-2.000	.10310	.09410	-.00610	.00830	-.00010	.18240	.07220
-1.000	.000	.03590	.04500	-.00400	.00550	-.00020	.17620	.06800
-1.000	2.000	.03590	.01710	-.00600	.00910	-.00060	.17370	.06140
-1.000	4.000	.10440	.06920	-.00510	.00730	-.00120	.16980	.05920
-1.000	6.000	.17480	.12010	-.00450	.00570	-.00190	.16600	.05600
-1.000	8.000	.25130	.17780	-.00540	.00630	-.00250	.16470	.05250
GRADIENT		.03462	-.02740	.00027	-.00050	-.00011	-.00194	-.00224

RUN NO. 2039/0 RN/L = 6.59 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
-.500	-8.000	.31800	.26730	-.00620	.00670	-.00040	.18420	.08930
-.500	-6.000	.23630	.19850	-.00500	.00680	-.00010	.18520	.08480
-.500	-4.000	.16730	.14130	-.00550	.00780	0.0000	.18620	.07960
-.500	-2.000	.09960	.06800	-.00780	.01010	.00000	.18620	.07340
-.500	.000	.03480	.03960	-.00570	.00760	-.00020	.18250	.06850
-.500	2.000	.03390	.01630	-.00670	.00980	-.00110	.17760	.06190
-.500	4.000	.10330	.07010	-.00700	.00990	-.00100	.17590	.05770
-.500	6.000	.17330	.12070	-.00440	.00960	-.00190	.17200	.05600
-.500	8.000	.25000	.17800	-.00260	.00250	-.00210	.16671	.05340
GRADIENT		.03373	-.02625	-.00010	.00019	-.00015	-.00146	-.00277

RUN NO. 2038/0 RN/L = 6.58 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-8.000	.30510	.24470	-.00830	.01150	.00000	.18100	.09400
.000	-6.000	.22650	.17620	-.00850	.01100	.00000	.18340	.08690
.000	-4.000	.15840	.12260	-.00660	.01150	.00000	.18400	.08500
.000	-2.000	.09620	.07600	-.00810	.01040	.00000	.18410	.08130
.000	.000	.03340	.03420	-.00570	.00760	.00000	.18350	.07440
.000	2.000	.03310	.01610	-.00640	.00970	-.00070	.18150	.06700
.000	4.000	.09650	.06170	-.00410	.00610	-.00100	.17940	.06250
.000	6.000	.15870	.10080	-.00270	.00390	-.00130	.17740	.05820
.000	8.000	.22500	.14430	-.00330	.00420	-.00160	.17260	.05570
GRADIENT		.03195	-.02313	.00053	-.00056	-.00013	-.00039	-.00297

DATE 26 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 69

MSFC 558 (MA9F) NR ATP (T3) (S1) / (O1)

(R78T18) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

BETA = .000 ORBINC = 2.000
 MAOH = 1.200 ELEVON = .000
 DELZ/D = -1.500

PARAMETRIC DATA

RUN NO. 2035/0 RN/L = 6.60 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.900	-6.000	-.26650	.20560	-.00940	.01340	.00000	.17570	.09980
.900	-6.000	-.21300	.14570	-.00930	.01390	.00020	.17700	.09670
.900	-4.000	-.14580	.09580	-.00990	.01450	.00030	.17780	.09320
.900	-2.000	-.08190	.04910	-.00970	.01400	.00020	.17780	.06680
.900	.000	-.02460	.01320	-.00820	.01180	.00000	.17650	.06230
.900	2.000	.03690	-.02980	-.00650	.01120	-.00030	.17690	.07610
.900	4.000	.09470	-.06610	-.00550	.00970	-.00060	.17660	.07050
.900	6.000	.15150	-.09630	-.00600	.00640	-.00160	.17670	.06550
.900	8.000	.21230	-.13380	-.00470	.00360	-.00200	.17350	.06310
GRADIENT		.02999	-.02013	.00060	-.00062	-.00013	-.00016	-.00289

RUN NO. 2043/0 RN/L = 6.60 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
1.000	-6.000	-.26470	.16950	-.01090	.01430	.00000	.17480	.09310
1.000	-6.000	-.19400	.11930	-.01120	.01900	.00000	.17500	.09240
1.000	-4.000	-.13120	.07270	-.01060	.01530	.00000	.17510	.09170
1.000	-2.000	-.07060	.03010	-.01010	.01550	.00000	.17480	.06990
1.000	.000	-.01290	-.00640	-.00690	.01310	.00000	.17380	.06670
1.000	2.000	.04360	-.04700	-.00890	.01200	-.00050	.17280	.06410
1.000	4.000	.09800	-.07870	-.00760	.01250	-.00100	.17310	.06000
1.000	6.000	.15080	-.10660	-.00570	.01000	-.00150	.17240	.07660
1.000	8.000	.21070	-.14280	-.00290	.00620	-.00190	.17070	.07330
GRADIENT		.02864	-.01699	.00048	-.00046	-.00012	-.00030	-.00146

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 70

MSFC 558 (MA9F) NR ATP (T3) (S1) / (O1)

(R78T19) (29 JAN 73)

REFERENCE DATA

BREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1320.0000 INCHES YMRP = .0000
 BREF = 1320.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

BETA = .000 ORBINC = .000
 MACH = 1.200 ELEVON = 1.000
 DELZ/D = -.520

RUN NO. 2006/ 0 RN/L = 6.60 GRADIENT INTERVAL = -5.00/ 5.00

DELZ/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
-.500	-8.070	-.21570	.15720	-.00690	.00430	.00000	.07720	.06260
-.500	-5.910	-.11790	.06170	-.00620	.00360	.00000	.08190	.06190
-.500	-3.760	-.01640	.00390	-.00650	.00390	-.00050	.08370	.06270
-.500	-1.610	.06550	-.07400	-.00690	.00420	-.00150	.08620	.06230
-.500	.530	.20620	-.16660	-.00490	.00320	-.00080	.08990	.05970
-.500	.540	.19500	-.15790	-.00600	.00390	-.00130	.08940	.06120
-.500	2.720	.30020	-.23710	-.00570	.00370	-.00110	.09050	.06160
-.500	4.860	.41040	-.32160	-.00630	.00450	-.00060	.09480	.06060
-.500	7.020	.49800	-.38510	-.00720	.00510	-.00080	.09800	.05740
-.500	9.080	.55350	-.42650	-.00610	.00470	-.00030	.09920	.05650
GRADIENT		.04952	-.03774	.00007	.00003	.00001	.00123	-.00023

RUN NO. 2005/ 0 RN/L = 6.61 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-8.000	.26390	.20570	-.00470	.00610	-.00010	.17660	.08050
.000	-6.000	-.21620	.15710	-.00590	.00630	.00050	.17920	.08670
.000	-4.000	-.16180	.12530	-.00610	.00660	.00030	.18190	.08290
.000	-2.000	-.10820	.09470	-.00570	.00760	.00000	.18390	.07860
.000	.010	-.05570	.07030	-.00600	.00430	-.00010	.18180	.07440
.000	2.000	-.00420	.03660	-.00760	.01140	-.00120	.18140	.06660
.000	4.000	.05170	.00310	-.00430	.00560	-.00140	.18100	.06190
.000	6.000	.10690	-.02930	-.00170	.00160	-.00160	.18120	.05680
.000	8.000	.16770	-.06660	-.00040	.00000	-.00230	.17850	.05390
GRADIENT		.02655	-.01902	.00007	-.00010	-.00023	-.00022	-.00263

RUN NO. 2004/ 0 RN/L = 6.60 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.900	-8.000	-.26480	.18300	-.00720	.00690	.00020	.17820	.08960
.900	-6.000	-.20450	.13890	-.00760	.01060	.00050	.17660	.08740
.900	-4.000	-.14790	.10500	-.01030	.01390	.00090	.17960	.08460
.900	-2.000	-.09370	.07060	-.00790	.01200	.00030	.17920	.08350
.900	.000	-.04440	.04750	-.00590	.01030	.00000	.17660	.08200
.900	2.000	.00260	.01730	-.00920	.01610	-.00100	.17490	.07660
.900	4.000	.05400	-.01390	-.00760	.01260	-.00130	.17160	.07320
.900	6.000	.09610	-.02920	-.00330	.00640	-.00160	.16960	.07250
.900	8.000	.14810	-.05640	-.00100	.00310	-.00210	.16670	.07210
GRADIENT		.02501	-.01455	.00018	.00009	-.00026	-.00102	-.00148

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 71

MSFC 558 (MAST) NR ATP (T3) (S1) / (O1)

(078120) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMPP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

BETA = .000 ORBINC = .000
 MACH = 1.200 ELEVON = 10.000
 DELZ/D = -1.000

RUN NO. 2029/0 RN/L = 6.61 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-6.000	-.29480	.22350	-.00970	.01270	.00010	.17500	.09600
.000	-6.000	-.21960	.16260	-.00940	.01230	.00010	.17610	.09240
.000	-4.000	-.15480	.11520	-.00850	.01120	.00010	.17710	.08790
.000	-2.000	-.09630	.07430	-.00670	.00900	.00020	.17980	.06200
.000	.000	-.03530	.03580	-.150	.00520	.00000	.17780	.07590
.000	2.000	.02190	-.00240	-.00360	.00900	-.00090	.17450	.06990
.000	4.000	.07520	-.03470	-.00630	.00920	-.00120	.17350	.06800
.000	6.000	.13390	-.06570	-.00370	.00520	-.00160	.17430	.06690
.000	8.000	.19710	-.10400	-.00180	.00240	-.00190	.17150	.03170
GRADIENT	.02696	-.01682	.00026	-.00020	-.00018	-.00043	-.00319	

RUN NO. 2030/0 RN/L = 6.61 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.500	-6.000	-.28770	.20970	-.01000	.01370	-.00010	.17670	.09180
.500	-6.000	-.21750	.15660	-.01090	.01500	.00000	.17640	.08880
.500	-4.000	-.15300	.10970	-.01020	.01470	.00000	.17980	.06510
.500	-2.000	-.09380	.06670	-.00940	.01480	.00000	.18090	.06040
.500	.000	-.04000	.04000	-.00720	.01210	-.00010	.18010	.07570
.500	2.000	.01320	.00290	-.00710	.01260	-.30080	.17770	.07120
.500	4.000	.06690	-.02670	-.00500	.00680	-.00110	.17740	.06660
.500	6.000	.12160	-.03690	-.00370	.00670	-.00160	.17650	.06150
.500	8.000	.17540	-.06560	-.00310	.00590	-.00210	.17420	.05840
GRADIENT	.02774	-.01715	.00043	-.00066	-.00015	-.00036	-.00231	

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-55A

PAGE 79

MSFC 55A (M55A) NR ATR (131) (S11-101)

INVESTIGATOR: LEO JANES

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0070
 LREF = 1326.0000 INCHES YMRP = .0000
 BREF = 1326.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

BETA = .000 ORBINC = .000
 MACH = 1.200 ELEVON = -20.000
 DELZ/D = -.920

RUN NO. 2007/0 RN/L = 6.61 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
-.500	-8.400	-.86290	.56290	.00300	-.00670	.00050	.13520	.04510
-.500	-6.250	-.58120	.50290	.00460	-.00690	.00010	.13190	.04620
-.500	-4.110	-.49580	.43640	.00500	-.00740	-.00050	.12860	.04680
-.500	-1.970	-.40720	.37260	.00560	-.00790	-.00100	.12500	.04760
-.500	.130	-.30450	.29880	.00510	-.00750	-.00150	.12240	.04840
-.500	.180	-.30520	.29660	.00640	-.00650	-.00140	.12300	.04840
-.500	2.350	-.21050	.22520	.00500	-.00750	-.00160	.11960	.04970
-.500	4.460	-.10660	.14580	.00760	-.00960	-.00190	.11530	.05020
-.500	6.650	-.00430	.06660	.00630	-.00810	-.00250	.10750	.05040
-.500	8.710	.06130	.01600	.00600	-.00720	-.00200	.10140	.05050
GRADIENT	.04544	-.03414	.00023	-.00019	-.00016	-.00149	.00042	

RUN NO. 2008/0 RN/L = 6.60 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-8.400	-.65910	.56270	.00520	-.00710	-.00020	.13990	.04390
.000	-6.240	-.57440	.50080	.00660	-.00630	-.00040	.13630	.04550
.000	-4.040	-.49190	.44040	.00590	-.00600	-.00140	.13410	.04570
.000	-1.950	-.40830	.37860	.00600	-.00610	-.00170	.12940	.04720
.000	.110	-.31430	.30630	.00660	-.00660	-.00160	.12570	.04740
.000	2.340	-.20670	.22690	.00610	-.00810	-.00190	.11930	.04770
.000	4.490	-.10240	.14640	.00600	-.00820	-.00200	.11250	.04820
.000	6.690	-.00960	.05940	.00510	-.00660	-.00240	.10410	.04870
.000	8.790	.09400	-.00510	.00460	-.00630	-.00220	.09910	.04690
GRADIENT	.04165	-.03448	.00001	-.00002	-.00005	-.00248	.00026	

RUN NO. 2009/0 RN/L = 6.61 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.900	-8.370	-.62960	.53720	.00430	-.00690	.00010	.13920	.04390
.900	-6.210	-.54070	.47050	.00410	-.00720	-.00090	.13640	.04700
.900	-4.040	-.44770	.40190	.00450	-.00670	-.00140	.13270	.04830
.900	-1.900	-.36640	.34310	.00640	-.00910	-.00200	.12860	.05030
.900	.220	-.27040	.27220	.00640	-.00690	-.00220	.12540	.04790
.900	2.420	-.17550	.20190	.00720	-.00920	-.00200	.11900	.05090
.900	4.510	-.07910	.12640	.00590	-.00790	-.00270	.11050	.05210
.900	6.700	.02660	.04610	.00510	-.00700	-.00300	.10070	.05240
.900	8.810	.11760	-.02420	.00480	-.00620	-.00150	.09830	.05200
GRADIENT	.04333	-.03213	-.00004	.00007	-.00012	-.00293	.00036	

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 73

MSFC 558 (MA9F) NR ATP (T3) (S1) / (O1)

(R78T22) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

BETA = .000 ORBINC = .000
 MACH = 1.200 ELEVON = -20.000
 DELZ/D = -1.000

RUN NO. 2032/ D RN/L = 6.61 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-6.540	-.71710	.59640	.01190	-.01250	.00070	.13550	.04410
.000	-6.360	-.62540	.53070	.01270	-.01340	.00040	.13280	.04530
.000	-4.170	-.32460	.45740	.01330	-.01350	.00000	.12890	.04740
.000	-2.000	-.42280	.36270	.01320	-.01330	-.00060	.12430	.04750
.000	.130	-.32120	.30720	.01290	-.01310	-.00080	.12070	.04910
.000	.140	-.31740	.30450	.01460	-.01430	-.00090	.12090	.04920
.000	2.340	-.20600	.22190	.01290	-.01280	-.00040	.11550	.05030
.000	4.460	-.08750	.13310	.01300	-.01270	-.00060	.10980	.05110
.000	6.740	.04210	.03470	.01160	-.01140	-.00130	.10170	.05070
.000	8.880	.15380	-.04930	.00860	-.00840	-.00080	.09430	.05010
GRADIENT	.050-2	-.03741	-.00004	.00010	-.00006	-.00217	.00047	

RUN NO. 2031/ D RN/L = 6.61 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.500	-6.370	-.71860	.59390	.01180	-.01260	.00170	.13630	.04690
.500	-6.370	-.62470	.52570	.01450	-.01490	.00100	.13430	.04700
.500	-4.190	-.52100	.44950	.01560	-.01580	.00100	.12980	.04840
.500	-2.010	-.41320	.37110	.01500	-.01540	.00020	.12340	.04990
.500	.140	-.30420	.23220	.01550	-.01540	-.00030	.11750	.05160
.500	.150	-.29900	.26800	.01700	-.01650	-.00070	.11790	.05100
.500	2.380	-.18640	.20610	.01440	-.01440	-.00080	.11160	.05270
.500	4.510	-.07830	.12550	.01470	-.01390	-.00070	.10470	.05350
.500	6.740	.05770	.02250	.01140	-.01120	-.00110	.09610	.05440
.500	8.910	.17420	-.06420	.00960	-.00890	-.00100	.06930	.05370
GRADIENT	.05095	-.03731	-.00011	.00022	-.00020	-.00264	.00060	

DATE 26 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 74

MSFC 558 (MA9F) NR ATP (T3) (S1)/(O1)

(R78T23) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

BETA = .000 ORBINC = 2.000
 MACH = 1.200 ELEVON = 10.000
 DELZ/D = -.520

RUN NO. 2079/0 RN/L = 6.59 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-8.000	-.32790	.27180	-.00760	.01040	.00000	.17590	.09440
.000	-6.000	-.26030	.22430	-.00850	.01200	.00020	.17900	.08970
.000	-4.000	-.20410	.19230	-.00900	.01270	.00010	.18230	.08420
.000	-2.000	-.15310	.16770	-.00850	.01170	.00000	.18440	.07930
.000	.000	-.10600	.14780	-.00530	.00710	-.00030	.18270	.07490
.000	2.000	-.05380	.11480	-.00600	.00850	-.00090	.18010	.06760
.000	4.000	.00190	.07900	-.00500	.00620	-.00120	.18040	.06050
.000	6.000	.05410	.05010	-.00270	.00230	-.00160	.17910	.05740
.000	8.000	.11430	.00920	-.00160	.00060	-.00200	.17690	.05460
GRADIENT	.32556	-.01397	.00052	-.00081	-.00017	-.00040	-.00296	

RUN NO. 2076/0 RN/L = 6.56 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.00	-8.000	-.29950	.22380	-.01240	.01680	.00010	.17510	.09170
.500	-6.000	-.23340	.17870	-.01250	.01760	.00040	.17600	.09010
.500	-4.000	-.17710	.14460	-.01270	.01820	.00030	.17710	.08780
.500	-2.000	-.13010	.12270	-.01240	.01860	.00000	.17700	.08610
.500	.000	-.08360	.10350	-.01160	.01810	.00000	.17370	.08500
.500	2.000	-.04050	.08210	-.01210	.01950	-.00050	.17030	.07920
.500	4.000	-.00390	.07450	-.00890	.01300	-.00140	.16550	.07970
.500	6.000	.04340	.04720	-.00490	.00720	-.00170	.16220	.07990
.500	8.000	.10390	.00230	-.00240	.00340	-.00180	.15970	.07840
GRADIENT	.02180	-.00904	.00039	-.00048	-.00019	-.00149	-.00119	

DATE 26 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 75

MSFC 558 (MA9F) NR ATP (T3) (S1) / (O1)

(R78T24) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. YMRF = .0000
 LREF = 1328.0000 INCHES YMRF = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

BETA = .000 ORBINC = 2.000
 MACH = 1.200 ELEVON = 10.000
 DELZ/D = -1.000

RUN NO. 2080/0 RN/L = 6.73 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-6.000	-.25970	.23780	-.00930	.01340	.00010	.17630	.09220
.000	-6.000	-.22770	.18060	-.01020	.01460	.00010	.17850	.08770
.000	-4.000	-.16470	.13650	-.01020	.01450	.00000	.18040	.08210
.000	-2.000	-.10600	.09940	-.00740	.01070	.00000	.18200	.07560
.000	.000	-.04960	.06660	-.00670	.00980	-.00020	.18110	.06960
.000	2.000	.30450	.03130	-.00610	.00970	-.00090	.17880	.06250
.000	4.000	.06200	-.00440	-.00430	.00670	-.00100	.17980	.05520
.000	6.000	.11870	-.03650	-.00290	.00420	-.00150	.17910	.04950
.000	8.000	.18080	-.07470	-.00200	.00260	-.00190	.17710	.04370
GRADIENT		.02639	-.01749	.00066	-.00084	-.00014	-.00022	-.00335

RUN NO. 2783/0 RN/L = 6.71 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.500	-6.000	-.25400	.22280	-.01220	.01650	.00010	.17670	.09000
.500	-6.000	-.22360	.17090	-.01240	.01740	.00040	.17810	.08730
.500	-4.000	-.16140	.12490	-.01220	.01770	.00040	.17970	.08390
.500	-2.000	-.10490	.09300	-.01210	.01790	.00020	.18080	.07960
.500	.000	-.05200	.06460	-.01050	.01630	-.00010	.17880	.07600
.500	2.000	-.00030	.03250	-.00890	.01490	-.00070	.17430	.07140
.500	4.000	.05020	.00450	-.00750	.01210	-.00090	.17300	.06780
.500	6.000	.09680	-.01580	-.00640	.01000	-.00130	.17290	.0650
.500	8.000	.15060	-.04470	-.0440	.00680	-.00160	.17100	.06270
GRADIENT		.02639	-.01546	.00063	-.00071	-.00017	-.00099	-.00202

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 76

MSFC 558 (MA9F) NR ATP (T3) (S1) / (O1)

(R78T25) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

BETA = .000 ORBINC = .000
 MACH = 2.000 ELEVON = .000
 DELZ/D = -.520

RUN NO. 2121/0 RN/L = 6.81 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
-1.000	-6.000	-.37670	.36660	-.00740	.01150	.00030	.16930	.05060
-1.000	-6.000	-.28440	.28440	-.00080	.00280	.00030	.17250	.04910
-1.000	-4.000	-.20720	.22270	.00060	.00110	.00030	.17590	.04660
-1.000	-2.000	-.14290	.17560	.00030	.00030	.00040	.17530	.04330
-1.000	.000	-.08090	.12810	.00010	-.00090	.00040	.17160	.04040
-1.000	2.000	-.01440	.07350	-.00110	.00010	.00020	.16990	.03880
-1.000	4.000	.05260	.02160	-.00130	-.00200	.00010	.16920	.03750
-1.000	6.000	.13090	-.04180	-.00310	-.00120	.00000	.16680	.03460
-1.000	8.000	.23260	-.14170	-.00650	.00320	.00000	.16240	.03300
GRADIENT		.03240	-.02522	-.00026	-.00032	-.00003	-.00794	-.00113

RUN NO. 2122/0 RN/L = 6.81 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-6.000	-.32430	.27570	-.01160	.01930	-.00170	.17450	.05200
.000	-6.000	-.24630	.21790	.00230	.00060	-.00080	.17280	.05270
.000	-4.000	-.18300	.17420	.00120	-.00010	-.00050	.17450	.05050
.000	-2.000	-.12880	.14350	.00110	-.00110	-.00020	.17350	.04600
.000	.000	-.07930	.12050	.00290	-.00430	-.00030	.17060	.04620
.000	2.000	-.03211	.09870	.00210	-.00530	-.00070	.17140	.04360
.000	4.000	.02120	.06940	.00410	-.00950	-.00050	.17050	.04170
.000	6.000	.08900	.02250	.00060	-.00650	-.00110	.16920	.03990
.000	8.000	.18100	-.06170	-.00210	-.00310	-.00120	.16640	.03800
GRADIENT		.02525	-.01272	.00034	-.00115	-.00002	-.00050	-.00110

RUN NO. 2118/0 RN/L = 6.81 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
1.000	-6.000	-.31160	.23900	-.00700	.00730	-.00110	.16070	.06230
1.000	-6.000	-.22680	.16730	.00150	-.00260	-.00020	.16180	.06050
1.000	-4.000	-.15530	.10690	-.00010	.00120	.00000	.16260	.05790
1.000	-2.000	-.09260	.06340	-.00310	.00580	.00000	.16600	.05560
1.000	.000	-.04460	.04360	-.00130	.00300	-.00010	.16930	.05420
1.000	2.000	-.00250	.03120	.00230	-.00290	-.00030	.16820	.05240
1.000	4.000	.04540	.00220	.00170	-.00200	-.00050	.16650	.05050
1.000	6.000	.08810	-.00920	.00200	-.00560	-.00050	.16790	.04920
1.000	8.000	.15060	-.04820	.00210	-.00730	-.00050	.16500	.04750
GRADIENT		.02457	-.01208	.00049	-.00075	-.00007	.00070	-.00090

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 77

MSFC 558 (MA9F) NR ATP (T3) (S1) / (O1)

(R78T25) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

BETA = .000 ORBINC = .000
 MACH = 2.000 ELEVON = .000
 DELZ/D = -.520

RUN NO. 2119/0 RN/L = 6.00 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	C	CLM	CY	CYN	CBL	CAF	CAB
2.000	-8.000	-.25270	.15420	-.00140	.00440	.00060	.14120	.07670
2.000	-6.000	-.19240	.11280	-.00510	.01070	.00020	.14510	.07530
2.000	-4.000	-.13040	.06380	-.00150	.00500	.00000	.14750	.06720
2.000	-2.000	-.06960	.01660	-.00020	.00220	-.00010	.15360	.05670
2.000	.000	-.01470	-.02230	.00030	.00170	.00000	.16100	.05160
2.000	2.000	.03380	-.04760	.00360	-.00190	.00030	.16350	.05110
2.000	4.000	.08660	-.08890	.00200	-.00060	.00010	.16360	.04990
2.000	6.000	.12990	-.11380	.00210	-.00140	.00010	.16130	.05070
2.000	8.000	.18110	-.14660	.00070	-.00060	.00010	.15930	.05150
GRADIENT		.02687	-.01868	.00054	-.00076	.00003	.00210	-.00201

RUN NO. 2120/0 RN/L = 6.61 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
3.000	-8.000	-.26880	.17510	-.01230	.02120	-.00030	.17390	.04110
3.000	-6.000	-.19600	.10390	-.01170	.01920	-.00030	.17310	.04080
3.000	-4.000	-.11180	.01930	-.00520	.00870	.00000	.16650	.04120
3.000	-2.000	-.03740	-.05000	.00010	.00090	.00000	.16110	.04200
3.000	.000	.01360	-.08820	.00130	-.00070	-.00010	.16150	.04180
3.000	2.000	.05660	-.11610	.00110	-.00030	-.00010	.16330	.04120
3.000	4.000	.10990	-.16100	.00110	.00010	.00000	.16010	.04170
3.000	6.000	.15400	-.19750	-.00110	.00360	.00000	.15830	.04250
3.000	8.000	.20840	-.24380	-.00050	.00390	.00000	.15290	.04590
GRADIENT		.02687	-.02133	.00068	-.00092	-.00000	-.00053	.00001

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 78

MSFC 558 (MA9F) NR ATP (13)(S1)/(O1)

(R78T26) (29 JAN 73)

REFERENCE DATA

BREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

BETA = .000 ORBINC = .000
 MACH = 2.000 ELEVON = .000
 DELZ/D = -1.000

RUN NO. 2126/0 RN/L = 6.81 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
-1.000	-6.000	.38600	.37690	-.00310	.00710	.00040	.16890	.04990
-1.000	-6.000	.28320	.27960	.00080	.00150	.00020	.17350	.04850
-1.000	-4.000	.19480	.19960	.00070	.00100	.00000	.17460	.04690
-1.000	-2.000	.11170	.13240	.00040	.00020	.00000	.17170	.04470
-1.000	.000	.04470	.07070	.00200	-.00290	.00020	.16860	.04140
-1.000	2.000	.02820	.00540	.00110	-.00240	.00020	.16860	.03900
-1.000	4.000	.10690	-.06410	-.00090	-.00150	.00000	.17000	.03610
-1.000	6.000	.19260	-.13870	-.00170	-.00110	.00030	.16690	.03440
-1.000	8.000	.29760	-.24110	-.00390	.00240	.00030	.16140	.03250
GRADIENT	.03745	-.03272	-.00012	-.00038	.00001	-.00061	-.00135	

RUN NO. 2125/0 RN/L = 6.83 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-6.000	.36750	.34470	.00000	.00450	.00000	.17050	.05310
.000	-6.000	.27200	.25430	-.00260	.00680	.00000	.17600	.05040
.000	-4.000	.19030	.18620	-.00240	.00530	.00000	.17820	.04820
.000	-2.000	.12010	.13360	-.00040	.00160	.00010	.17620	.04550
.000	.000	.05690	.04690	-.00130	.00130	.00010	.17280	.04200
.000	2.000	.01000	.03320	-.00060	.00000	.00000	.16970	.03950
.000	4.000	.07940	-.01960	.00120	-.00370	.00020	.16980	.03670
.000	6.000	.15560	-.07860	-.00060	-.00170	.00030	.16640	.03580
.000	8.000	.25440	-.17190	-.00380	.00270	.00040	.16140	.03360
GRADIENT	.03347	-.02560	.00034	-.00098	.00002	-.00117	-.00145	

RUN NO. 2127/0 RN/L = 6.82 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
1.000	-6.000	.33470	.27760	-.00590	.01140	.00000	.16440	.05930
1.000	-6.000	.23900	.19020	.00010	.00340	.00010	.16920	.05660
1.000	-4.000	.16120	.12740	.00100	.00130	.00010	.17300	.05340
1.000	-2.000	.10090	.06840	.00030	.00100	.00000	.17540	.05010
1.000	.000	.04940	.06100	.00100	-.00100	.00000	.17510	.04680
1.000	2.000	.00230	.03340	.00060	-.00220	.00000	.17150	.04420
1.000	4.000	.05460	.00460	.00270	-.00580	.00020	.17190	.04200
1.000	6.000	.11390	-.02660	.00110	-.00490	.00020	.17110	.04090
1.000	8.000	.19640	-.09230	-.00120	-.00170	.00010	.16680	.03940
GRADIENT	.02674	-.01903	.00019	-.00067	.00001	-.00030	-.00136	

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 79

MSFC 558 (MA9F) NR ATP (T3) (S1) / (O1)

(RT8T26) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

BETA = .000 ORBINC = .000
 MACH = 2.000 ELEVON = .000
 DELZ/D = -1.000

RUN NO. 2129/0 RN/L = 6.81 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
2.000	-8.000	-.30610	.22670	-.00690	.01270	.00020	.16820	.05380
2.000	-6.000	-.22020	.15030	.00090	.00270	.00000	.17230	.05080
2.000	-4.000	-.14630	.08940	.00120	.00100	.00000	.17230	.05020
2.000	-2.000	-.08220	.04180	.00090	.00160	.00000	.17150	.05130
2.000	.000	-.02660	.00770	.00270	-.00070	.00010	.17060	.05100
2.000	2.000	.01990	-.01490	.00300	-.00250	.00030	.16620	.05130
2.000	4.000	.07240	-.05230	.00370	-.00440	.00010	.16640	.05080
2.000	6.000	.12240	-.07860	.00310	-.00510	.00020	.16650	.04810
2.000	8.000	.18220	-.11270	.00110	-.00340	.00020	.17020	.04420
GRADIENT		.02697	-.01700	.00036	-.00073	.00002	-.00076	.00006

RUN NO. 2128/0 RN/L = 6.81 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
3.000	-8.000	-.29900	.21950	-.00370	.00990	.00000	.16810	.04660
3.000	-6.000	-.21130	.13170	-.00120	.00560	.00000	.16740	.04690
3.000	-4.000	-.13060	.05440	.00000	.00330	.00010	.16520	.04740
3.000	-2.000	-.06470	-.00310	.00100	.00160	.00000	.16490	.04780
3.000	.000	-.00950	-.04600	.00240	-.00070	.00000	.16590	.04620
3.000	2.000	.04090	-.08040	.00160	.00050	.00030	.16430	.04890
3.000	4.000	.09110	-.11620	-.00080	.00350	.00010	.16000	.05010
3.000	6.000	.15480	-.14210	.00040	.00160	.00000	.15930	.05100
3.000	8.000	.18330	-.17020	-.00090	.00310	.00020	.15710	.05200
GRADIENT		.02745	-.02092	-.00005	-.00003	.00001	-.00055	.00032

DATE 25 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 80

MSFC 558 (MA9F) NR ATP (T3) (S1) / (O1)

(RT6127) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

BETA = .000 ORBINC = .000
 MACH = 2.000 ELEVON = .000
 DELZ/D = -1.500

RUN NO. 2131/0 RN/L = 6.81 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-8.000	-.39280	.38540	.00270	.00120	.00070	.16780	.05280
.000	-6.000	-.28900	.29520	.01140	-.01070	.00040	.17190	.05060
.000	-4.000	-.19760	.21220	.01060	-.01140	.00020	.17400	.04910
.000	-2.000	-.11770	.13310	.00060	-.00040	.00000	.17320	.04710
.000	.000	-.04430	.06680	.00020	-.00060	.00000	.16790	.04540
.000	2.000	.03650	-.01370	.00230	-.00360	.00010	.16570	.04420
.000	4.000	.11080	-.07610	.00200	-.00440	.00000	.16480	.04430
.000	6.000	.20010	-.15900	-.00120	-.00650	.00000	.16330	.04170
.000	8.000	.30600	-.26640	-.00420	.00250	-.00020	.15930	.03920
GRADIENT		.03855	-.03617	-.00080	.00054	-.00002	-.00130	-.00062

RUN NO. 2130/0 RN/L = 6.81 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
1.000	-8.000	-.36540	.33670	-.00210	.00660	.00040	.16770	.05660
1.000	-6.000	-.26730	.24530	.00120	.00300	.00020	.17420	.05420
1.000	-4.000	-.16900	.16270	.00180	.00040	.00010	.17750	.05160
1.000	-2.000	-.12520	.13890	.00120	-.00040	.00000	.17540	.04920
1.000	.000	-.06480	.09410	.00010	-.00010	.00000	.17020	.04710
1.000	2.000	.00430	.03170	-.00140	.00160	.00000	.16570	.04540
1.000	4.000	.07800	-.02740	.00110	-.00210	.00030	.16350	.04650
1.000	6.000	.16360	-.10360	-.00160	.00010	.00000	.15	.04480
1.000	8.000	.27410	-.22280	-.00490	.00430	.00000	.15460	.04000
GRADIENT		.03317	-.02637	-.00020	-.00014	.00002	-.00189	-.00070

RUN NO. 2132/0 RN/L = 6.80 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
2.000	-8.000	-.34890	.30540	-.00470	.01140	.00020	.16530	.05700
2.000	-6.000	-.25890	.22520	.00190	.00120	.00000	.16250	.06250
2.000	-4.000	-.18880	.17400	.00110	.00160	.00000	.15810	.06990
2.000	-2.000	-.12880	.13740	.00050	.00180	.00010	.15670	.06990
2.000	.000	-.07280	.10350	.00200	-.00050	.00030	.15530	.06540
2.000	2.000	-.01690	.06640	.00350	-.00280	.00040	.15640	.05930
2.000	4.000	.03730	.03260	.00400	-.00470	.00040	.15860	.05340
2.000	6.000	.10470	-.01500	.00070	-.00220	.00030	.17110	.04240
2.000	8.000	.19430	-.09430	-.00240	.00060	.00030	.19460	.04470
GRADIENT		.02610	-.01757	.00044	-.00046	.00005	.00005	-.00194

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 01

MSFC 558 (MA9F) NR ATP (T3) (S1) / (O1)

(R78T28) (29 JAN 73)

REFERENCE DATA

BREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

BETA = .000 ORBINC = 2.000
 MACH = 2.000 ELEVON = .000
 DELZ/D = -.520

RUN NO. 2112/0 RN/L = 6.76 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
-1.000	-6.000	-.42500	.43070	-.00270	.00640	-.00070	.16590	.04540
-1.000	-6.000	-.32650	.34040	.00070	.00100	-.00050	.16940	.04450
-1.000	-4.000	-.24320	.26970	.00220	-.00090	-.00030	.17360	.04190
-1.000	-2.000	-.16960	.20820	.00290	-.00210	-.00010	.17400	.03750
-1.000	.000	-.10990	.16540	.00090	-.00220	-.00010	.16830	.03480
-1.000	2.000	-.04200	.10530	.00000	-.00120	-.00060	.16490	.03240
-1.000	4.000	.02330	.06000	.00120	-.00440	-.00070	.16630	.03160
-1.000	6.000	.09590	.00650	-.00200	-.00160	-.00170	.16440	.02930
-1.000	8.000	.19740	-.09090	-.00500	.00220	-.00240	.16210	.02800
GRADIENT		.03303	-.02612	-.00024	-.00030	-.00007	-.00116	-.00128

RUN NO. 2111/0 RN/L = 6.81 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-6.000	-.40030	.37870	-.00480	.01060	-.00150	.16420	.05310
.000	-6.000	-.31000	.30320	.00580	-.00400	-.00060	.16610	.05250
.000	-4.000	-.29750	.24880	.00430	-.00380	-.00020	.17310	.05070
.000	-2.000	-.18530	.22380	.00140	-.00130	-.00010	.17750	.04980
.000	.000	-.14320	.21210	.00020	-.00160	-.00050	.17670	.04730
.000	2.000	-.08970	.18020	.00080	-.00410	-.00100	.17320	.04440
.000	4.000	-.03770	.15300	.00290	-.00790	-.00050	.17050	.04230
.000	6.000	.02600	.11500	.00310	-.00780	-.00060	.17350	.03960
.000	8.000	.11790	.03360	.00270	-.00740	-.00090	.17150	.03790
GRADIENT		.02476	-.01176	-.00017	-.00055	-.00007	-.00046	-.00111

RUN NO. 2110/0 RN/L = 6.82 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
1.000	-6.000	-.34670	.27720	-.00880	.01420	-.00130	.15590	.05690
1.000	-6.000	-.25730	.19520	-.00240	.00640	-.00060	.15780	.05410
1.000	-4.000	-.16310	.13640	-.00130	.00510	-.00030	.16030	.05200
1.000	-2.000	-.12550	.10140	-.00170	.00520	-.00040	.16270	.05060
1.000	.000	-.07510	.07490	-.00350	.00650	-.00040	.16330	.04940
1.000	2.000	-.03540	.06410	-.00010	.00100	-.00020	.16340	.04790
1.000	4.000	.00240	.05310	.00040	.00040	-.00090	.16160	.04650
1.000	6.000	.03980	.04570	.00070	-.00170	-.00060	.16250	.04910
1.000	8.000	.09500	.01960	.00120	-.00430	-.00060	.16170	.04920
GRADIENT		.02305	-.01019	.00023	-.00064	-.00005	.00016	-.00050

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-556

PAGE 82

MSFC 556 (MA9F) NR ATP (T3) (S1) / (O1)

(R78T26) (29 JAN 73)

REFERENCE DATA

BREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = 0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

BETA = .000 ORBINC = 2.000
 MACH = 2.000 ELEVON = .000
 DELZ/D = -.520

RUN NO. 2109/0 RN/L = 6.76 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
2.000	-6.000	-.31530	.22140	.00050	.00340	-.00030	.15610	.09380
2.000	-6.000	-.24300	.16060	-.00210	.00700	-.00030	.16520	.04630
2.000	-4.000	-.16980	.09750	-.00080	.00460	-.00030	.17090	.03750
2.000	-2.000	-.09950	.03520	-.00190	.00570	-.00010	.17150	.03450
2.000	.000	-.03690	-.01690	.00000	.00310	.00000	.16650	.03720
2.000	2.000	.01310	-.04570	.00150	.00160	.00000	.16460	.04110
2.000	4.000	.06240	-.07760	.00290	-.00050	-.00010	.15610	.04270
2.000	6.000	.10640	-.10540	.00300	-.00140	.00000	.15290	.04650
2.000	8.000	.15210	-.13040	.00240	-.00150	-.00010	.14980	.05080
GRADIENT		.02685	-.02155	.00054	-.00071	.00002	-.00162	.00065

RUN NO. 2108/0 RN/L = 6.77 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
3.000	-6.000	-.33030	.23630	-.00400	.01020	-.00010	.17220	.04020
3.000	-6.000	-.25130	.15940	-.00330	.00630	.00000	.17200	.03940
3.000	-4.000	-.17010	.06020	-.00020	.00300	.00000	.16570	.03910
3.000	-2.000	-.09650	.01230	.00140	.00030	.00000	.16110	.03940
3.000	.000	-.04090	-.03690	.00230	-.00090	.00000	.16410	.04000
3.000	2.000	.01230	-.04030	.00170	-.00040	.00000	.16650	.03950
3.000	4.000	.06410	-.12160	.00250	-.00150	.00010	.16380	.04050
3.000	6.000	.12090	-.17170	.00160	-.00060	.00030	.16090	.04180
3.000	8.000	.18270	-.23140	.00260	-.00170	.00030	.15430	.04340
GRADIENT		.02696	-.02481	.00028	-.00048	.00001	.00008	.00014

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 63

MSFC 558 (MASF) NR ATP (T3) (S1)/(O1)

(R78T29) (29 JAN 73)

REFERENCE DATA

BREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

BETA = .000 ORBINC = 2.000
 MACH = 2.000 LEVON = .000
 DELZ/D = -1.000

RUN NO. 2104/0 RN/L = 6.75 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
-1.000	-6.000	-.39570	.39010	-.00430	.00790	-.00060	.16890	.04520
-1.000	-6.000	-.28980	.16660	-.00060	.00260	-.00050	.17120	.04290
-1.000	-4.000	-.20130	.20640	-.00060	.00230	-.00040	.17330	.03980
-1.000	-2.000	-.12390	.14390	.00070	.00000	-.00010	.17160	.03630
-1.000	.000	-.05220	.07700	.00270	-.00310	.00000	.16660	.03350
-1.000	2.000	.02130	.01270	.00350	-.00510	-.00020	.16750	.03160
-1.000	4.000	.09460	-.04460	.00410	-.00620	-.00040	.16860	.03070
-1.000	6.000	.18140	-.11600	.00430	-.00630	-.00040	.16760	.02860
-1.000	8.000	.29180	-.22340	.00760	-.00920	-.00030	.16430	.02430
GRADIENT		.03697	-.03168	.00061	-.00110	-.00000	-.00067	-.00115

RUN NO. 2102/0 RN/L = 6.74 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-6.000	-.37490	.35140	-.00600	.01030	-.00110	.16880	.04880
.000	-6.000	-.27620	.25940	-.00320	.00610	-.00040	.17230	.04640
.000	-4.000	-.19760	.19790	-.00190	.00390	-.00060	.17460	.04350
.000	-2.000	-.13320	.15410	.00020	.00070	-.00030	.17440	.03960
.000	.000	-.06980	.10550	.00210	-.00160	-.00020	.16950	.03650
.000	2.000	-.01200	.06760	.00350	-.00370	-.00030	.16780	.03400
.000	4.000	.04930	.02970	.00410	-.00380	-.00070	.16910	.03200
.000	6.000	.12410	-.02620	.00500	-.00460	-.00020	.16680	.03020
.000	8.000	.22300	-.11850	.00790	-.00950	-.00010	.16150	.02740
GRADIENT		.03075	-.02114	.00076	-.00119	-.00001	-.00390	-.00145

RUN NO. 2105/0 RN/L = 6.75 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
1.000	-6.000	-.34940	.29590	-.01030	.01570	-.00060	.16350	.05320
1.000	-6.000	-.25690	.21370	-.00370	.00670	-.00030	.16760	.05060
1.000	-4.000	-.18160	.15620	-.00210	.00420	-.00020	.17090	.04780
1.000	-2.000	-.11400	.11460	.00000	.00130	.00000	.17130	.04460
1.000	.000	-.07060	.09350	.00000	.00040	-.00010	.17260	.04270
1.000	2.000	-.02980	.04340	.00140	-.00160	-.00050	.17050	.04090
1.000	4.000	.01970	.06110	.00390	-.00470	-.00020	.17240	.04090
1.000	6.000	.07520	.03440	.00390	-.00770	-.00040	.17090	.03980
1.000	8.000	.15340	-.02840	.00610	-.00750	-.00090	.16780	.03790
GRADIENT		.02434	-.01107	.00063	-.00103	-.00002	.00011	-.00062

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 64

MSFC 558 (MASF) NR ATP (T3)(S1)/(O1)

(R78T29) (29 JAN 73)

REFERENCE DATA

BREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

BETA = .000 ORBINC = 2.000
 MACH = 2.000 ELEVON = .000
 DELZ/D = -1.000

RUN NO. 2106/0 RN/L = 6.75 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
2.000	-6.000	-.32560	.24800	-.00730	.01120	-.00010	.19690	.05860
2.000	-6.000	-.23890	.19940	-.00340	.00580	-.00010	.19600	.05930
2.000	-4.000	-.16070	.10390	-.00160	.00330	.00000	.15420	.05960
2.000	-2.000	-.09180	.04940	.00060	.00060	.00000	.15370	.05790
2.000	.000	-.03430	.00980	.00170	-.00060	.00000	.15630	.05480
2.000	2.000	.00590	-.00490	.00190	-.00120	.00000	.15820	.05290
2.000	4.000	.04940	-.02790	.00260	-.00210	-.00010	.16090	.05120
2.000	6.000	.09310	-.04670	.00420	-.00420	.00000	.16560	.04830
2.000	8.000	.14920	-.07800	.00650	-.00690	.00020	.17130	.04230
GRADIENT		.02569	-.01585	.00049	-.00063	-.00001	.00090	-.00111

RUN NO. 2107/0 RN/L = 6.75 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
3.000	-6.000	-.32950	.24660	-.00770	.01250	-.00040	.16760	.04310
3.000	-6.000	-.24010	.19730	-.00430	.00730	-.00030	.16660	.04250
3.000	-4.000	-.15440	.07420	-.00190	.00350	-.00010	.16320	.04240
3.000	-2.000	-.07750	.00280	-.00030	.00180	.00010	.16110	.04290
3.000	.000	-.01710	-.04710	.00210	-.00090	.00000	.16280	.04320
3.000	2.000	.02830	-.07760	.00190	-.00040	-.00010	.16300	.04410
3.000	4.000	.07280	-.10490	.00390	-.00320	.00000	.15960	.04430
3.000	6.000	.12460	-.14460	.00520	-.00400	.00010	.15680	.04600
3.000	8.000	.17780	-.18310	.00630	-.00520	.00010	.15630	.04720
GRADIENT		.02601	-.02193	.00068	-.00077	.00000	-.00027	.00029

DATE 29 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-338

PAGE 88

MSFC 338 (MAZF) NR ATP (T3) (S1) / (O1)

(R78T30) (29 MAR 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.9000 INCHES
 SCALE = 100.0000 PER

BETA = .000 ORBINC = 2.000
 MACH = 2.000 ELEVON = .000
 DELZ/D = -1.500

RUN NO. 2096/0 RN/L = 6.0 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
-1.000	-8.070	-.18470	.13580	.00630	-.00500	.00130	.06340	.02210
-1.000	-5.920	-.12070	.06780	.00530	-.00400	.00120	.07730	.02370
-1.000	-3.820	-.06260	.04420	.00500	-.00370	.00130	.07220	.02470
-1.000	-1.780	.00180	-.00470	.00430	-.00260	.00130	.06600	.02620
-1.000	.410	.06190	-.06420	.00390	-.00250	.00100	.06350	.02370
-1.000	2.620	.17290	-.12970	.00370	-.00220	.00070	.06150	.02390
-1.000	4.740	.25290	-.18660	.00320	-.00190	.00050	.06090	.02330
-1.000	6.940	.33220	-.24140	.00200	-.00050	.00070	.05830	.02760
-1.000	8.980	.38000	-.27460	.00140	.00010	.00090	.05410	.02600
GRADIENT		.03729	-.02727	-.00019	.00023	-.00010	-.00125	.00013

RUN NO. 2100/0 RN/L = 6.77 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-8.000	-.37540	.36300	-.00670	.01130	-.00060	.16670	.04800
.000	-6.000	-.27440	.28450	-.00190	.00430	-.00050	.17230	.04580
.000	-4.000	-.19200	.19520	-.00030	.00200	-.00030	.17450	.04310
.000	-2.000	-.12070	.13680	.00100	.00080	.00000	.17220	.04010
.000	.000	-.04790	.07000	.00060	.00000	-.00010	.16440	.03480
.000	2.000	.02480	.00440	.00160	-.00190	.00000	.16590	.03480
.000	4.000	.10170	-.06180	.00250	-.00310	-.00020	.16730	.03470
.000	6.000	.19030	-.14300	.00340	-.00460	-.00070	.16470	.03210
.000	8.010	.29400	-.24650	.00430	-.00630	-.00100	.16160	.02910
GRADIENT		.03664	-.03232	.00032	-.00061	.00001	-.00103	-.00101

RUN NO. 2097/0 RN/L = 6.75 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
1.000	-8.000	-.36260	.32990	-.01060	.01640	-.00090	.16720	.05190
1.000	-6.000	-.26330	.24130	-.00430	.00760	-.00040	.17100	.04950
1.000	-4.000	-.18890	.18240	-.00240	.00440	-.00020	.17350	.04720
1.000	-2.000	-.12520	.13760	-.00800	.00370	-.00010	.17330	.04480
1.000	.000	-.06340	.09170	-.00130	.00240	-.00010	.16970	.04320
1.000	2.000	-.00100	.04110	-.00110	.00210	-.00040	.16490	.04290
1.000	4.000	.07040	-.01790	.00090	-.00090	.00000	.16400	.04040
1.000	6.000	.19340	-.09320	.00190	-.00140	-.00050	.16100	.03420
1.000	8.000	.29050	-.19990	.00450	-.00340	-.00040	.15800	.03010
GRADIENT		.03214	-.02482	.00037	-.00061	.00001	-.00139	-.00079

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 86

MSFC 558 (MAS) : NR ATP (T3) (S1)/(O1)

(R70T30) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1320.0000 INCHES YMRP = .0000
 BREF = 1320.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

BETA = .000 ORBINC = 2.000
 MACH = 2.000 ELEVON = .000
 DELZ/D = -1.500

RUN NO. 2098/0 RN/L = 6.76 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	C/N	CBL	CAF	CAB
2.000	-8.000	.34790	.29340	-.01050	.01550	-.00020	.18480	.03260
2.000	-6.000	.25570	.21060	-.00320	.00540	-.00010	.20730	.01100
2.000	-4.000	.18070	.15260	-.00170	.00340	-.00010	.23540	-.01600
2.000	-2.000	.11940	.11210	-.00030	.00160	-.00010	.24830	-.02960
2.000	.000	.06630	.06090	.00070	.00040	.00000	.29180	-.03510
2.000	2.000	-.01950	.05570	.00220	-.00100	-.00010	.24770	-.03330
2.000	4.000	.02940	.02610	.00410	-.00420	.00000	.28430	-.07060
2.000	6.000	.09120	-.01310	.00400	-.00530	.00000	.31420	-.10300
2.000	8.000	.17300	-.06110	.01390	-.02510	-.00040	.34560	-.13950
GRADIENT		.02600	-.01327	.00070	-.00090	.00001	.00483	-.00566

RUN NO. 2099/0 RN/L = 6.76 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
3.000	-7.790	-.00410	-.00020	.00540	-.00430	.00140	.06070	.02100
3.000	-5.800	.05760	-.04260	.00560	-.00410	.00110	.07950	.02430
3.000	-3.450	.12460	-.08580	.00560	-.00420	.00110	.08010	.02560
3.000	-1.360	.16250	-.12450	.00460	-.00310	.00060	.07700	.01740
3.000	.790	.24310	-.16300	.00270	-.00150	.00050	.07460	.02800
3.000	2.980	.29890	-.19740	.00230	-.00130	.00050	.07360	.03070
3.000	5.080	.34180	-.22430	.00210	-.00110	.00070	.07360	.03130
3.000	7.210	.38620	-.25130	.00110	-.00080	.00090	.07460	.03140
3.000	9.290	.43080	-.27960	.00010	-.00040	.00010	.07440	.02940
GRADIENT		.02693	-.01790	-.00059	.00048	-.00010	-.00102	.00074

REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.

DATE 26 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 87

MSFC 558 (MA9F) NR ATP (T3) (S1) / (O1)

(R78T31) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT.	XMRP = .0000
LREF = 1328.0000 INCHES	YMRP = .0000
BREF = 1328.0000 INCHES	ZMRP = -61.5000 INCHES
SCALE = 100.0000 PER	

BETA = .000	ORBINC = 2.000
MACH = 2.000	ELEVON = 10.000
DELZ/D = -.520	

RUN NO. 2103/0 RN/L = 6.82 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-6.410	-.22120	.11540	.00110	.00070	-.00020	.04720	.02590
.000	-6.190	-.15680	.08400	.00190	.00000	.00000	.04960	.02760
.000	-4.000	-.11310	.06620	.00200	-.00040	.00010	.05350	.02880
.000	-1.850	-.07390	.05690	.00090	-.00030	.00000	.05670	.02870
.000	.250	-.05630	.05420	.00090	-.00050	-.00010	.05690	.02900
.000	.260	-.05340	.05300	.00140	-.00090	-.00020	.05550	.02960
.000	2.370	-.3260	.05030	.00040	-.00070	-.00040	.05780	.02860
.000	4.540	-.00620	.04800	-.00010	-.00090	-.00050	.06100	.02830
.000	6.690	.02520	.03980	.00000	-.00150	-.00080	.06330	.02920
.000	8.870	.07790	.01380	-.00200	-.00060	-.00100	.06420	.03000
GRADIENT		.01206	-.00202	-.00022	-.00007	-.00008	.00076	-.00005

MSFC 558 (MA9F) NR ATP (T3) (S1) / (O1)

(R78T32) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT.	XMRP = .0000
LREF = 1328.0000 INCHES	YMRP = .0000
BREF = 1328.0000 INCHES	ZMRP = -61.5000 INCHES
SCALE = 100.0000 PER	

BETA = .000	ORBINC = 2.000
MACH = 2.000	ELEVON = 10.000
DELZ/D = -.520	

RUN NO. 2101/0 RN/L = 6.78 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	ALPHA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-7.930	-.05320	.02160	-.00280	.00250	.00010	.09490	.02460
.000	-9.830	-.00770	-.01210	-.00240	.00200	.00000	.08960	.02660
.000	-3.740	.04520	-.05320	-.00240	.00170	.00020	.06470	.02790
.000	-1.700	.10920	-.10230	-.00180	.00160	.00010	.06090	.02860
.000	.480	.18630	-.16000	-.00110	.00130	.00010	.06010	.02790
.000	.480	.18100	-.15530	-.00120	.00120	.00020	.07960	.02810
.000	2.870	.26410	-.21520	-.00240	.00230	.00000	.07930	.02830
.000	4.750	.34130	-.27180	-.00280	.00300	.00010	.08020	.02790
.000	6.970	.41310	-.32370	-.00360	.00370	.00010	.07910	.02870
.000	8.950	.43400	-.35410	-.00420	.00440	-.00010	.07710	.02900
GRADIENT		.03500	-.02577	-.00007	.00016	-.00001	-.00049	-.00002

REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 68

MSFC 558 (MA9F) NR ATP (T3) (S1) / (O1)

(R78T33) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

ALPHA = .000 ORBINC = .000
 MACH = .900 ELEVON = .000
 DELZ/D = -.520

RUN NO. 2066/ 0 RN/L = 6.19 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	BETA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-10.220	-.02920	.00240	.16060	-.18790	-.00170	.09740	.11120
.000	-8.250	-.02810	.00380	.13220	-.15830	-.00120	.10260	.10300
.000	-6.160	-.03330	.01370	.09910	-.12220	-.00100	.10680	.09640
.000	-4.090	-.03830	.02370	.06450	-.08040	-.00010	.10870	.09150
.000	-2.040	-.04200	.03070	.02960	-.03860	-.00010	.11080	.08710
.000	.020	-.04260	.03420	-.00470	.00530	.00080	.11630	.08060
.000	2.090	-.04370	.03610	-.03990	.04650	.00100	.11840	.07930
.000	4.180	-.03490	.02570	-.07380	.08900	.00130	.11940	.07790
.000	6.230	-.03360	.01970	-.11020	.13070	.00130	.12370	.08120
.000	8.300	-.03370	.01780	-.14240	.19630	.00170	.12000	.08490
.000	10.290	-.05070	.03880	-.17750	.20470	.00140	.11720	.09440
GRADIENT		.00025	.00045	-.01674	.02060	.00019	.00140	-.00169

MSFC 558 (MA9F) NR ATP (T3) (S1) / (O1)

(R78T34) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

ALPHA = .000 ORBINC = .000
 MACH = .900 ELEVON = .000
 DELZ/D = -1.000

RUN NO. 2063/ 0 RN/L = 6.21 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	BETA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-10.230	.01100	-.04130	.14910	-.17240	.00050	.10110	.10190
.000	-8.280	.01790	-.04680	.12420	-.14730	.00090	.10960	.09910
.000	-6.150	.01430	-.03610	.08940	-.10870	.00060	.11090	.08350
.000	-4.040	.01640	-.03740	.05870	-.07230	.00100	.11270	.08090
.000	-2.040	.01150	-.03050	.02680	-.03420	.00080	.11750	.07650
.000	.030	.00710	-.02290	-.00550	.00640	.00030	.12040	.07370
.000	2.090	.00900	-.02270	-.03800	.04580	.00000	.12030	.07270
.000	4.130	.01070	-.02770	-.06740	.06110	.00000	.12350	.06970
.000	6.220	.02070	-.04060	-.10360	.12350	-.00050	.12330	.07160
.000	8.290	.02170	-.04690	-.13270	.19550	-.00090	.12150	.08070
.000	10.240	.00830	-.03230	-.18050	.18280	-.00140	.11780	.08390
GRADIENT		-.00067	.00132	-.01540	.01879	-.00014	.00116	-.00127

REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 69

MSFC 558 (MA9F) NR ATP (T3) (S1)/(O1)

(R78T35) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.9000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

ALPHA =	.000	ORBINC =	2.000
MACH =	.900	ELEVON =	.000
DELZ/D =	-.520		

RUN NO. 2091/0 RN/L = 6.17 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	BETA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-10.270	-.04930	.04140	.17570	-.20890	-.00330	.10510	.10300
.000	-8.260	-.04510	.03770	.13890	-.16870	-.00290	.10750	.09520
.000	-6.190	-.04360	.04050	.10490	-.12940	-.00170	.10810	.09190
.000	-4.110	-.05030	.04950	.06870	-.08740	-.00140	.11100	.08770
.000	-2.060	-.05220	.05500	.03760	-.04950	-.00010	.11380	.08410
.000	.000	-.05440	.06110	.00120	-.00300	.00010	.11930	.07760
.000	2.070	-.05510	.05810	-.03910	.04780	.00080	.12160	.07580
.000	4.130	-.04500	.04650	-.07270	.08690	.00150	.12200	.07610
.000	6.200	-.04110	.04080	-.10770	.12950	.00240	.12460	.07930
.000	8.250	-.04410	.03990	-.14170	.16740	.00290	.11840	.08650
.000	10.300	-.05470	.05400	-.18020	.21010	.00220	.11900	.09090
GRADIENT		.00047	.00005	-.01744	.02183	.00035	.00145	-.00153

MSFC 558 (MA9F) NR ATP (T3) (S1)/(O1)

(R78T36) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.9000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

ALPHA =	.000	ORBINC =	2.000
MACH =	.900	ELEVON =	.000
DELZ/D =	-1.000		

RUN NO. 2092/0 RN/L = 6.17 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	BETA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-10.230	-.02790	.01210	.15740	-.18490	-.00040	.10710	.09360
.000	-8.250	-.02130	.00640	.13030	-.15760	.00000	.11010	.09000
.000	-6.160	-.02360	.01460	.09730	-.11970	.00000	.11210	.08350
.000	-4.110	-.02540	.01690	.06440	-.08110	.00010	.11550	.07920
.000	-2.050	-.02890	.02670	.03360	-.04360	.00040	.11920	.07650
.000	.000	-.02980	.02920	.00070	-.00240	.00030	.12200	.07160
.000	2.060	-.02790	.02660	-.03550	.04390	.00020	.12200	.07020
.000	4.120	-.02690	.02470	-.06960	.08530	.00040	.12160	.07010
.000	6.210	-.01880	.01310	-.10230	.12260	.00030	.12330	.07280
.000	8.240	-.01760	.00720	-.13360	.15710	.00040	.12070	.07990
.000	10.290	-.02400	.01440	-.16840	.19430	-.00040	.11920	.08620
GRADIENT		-.00010	.00064	-.01639	.02043	.00001	.00094	-.00119

REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 90

MSFC 558 (MAGF) NR ATP (T3) (S1) / (O1)

(R78T37) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

ALPHA = .000 ORBINC = .000
 MACH = 1.200 ELEVON = .000
 DELZ/D = -.520

RUN NO. 2065/0 RN/L = 6.60 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	BETA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-10.400	-.02840	-.00040	.17810	-.19930	-.00360	.16820	.10550
.000	-8.360	-.03600	.01200	.13860	-.15860	-.00350	.16830	.10280
.000	-6.230	-.03870	.01670	.10040	-.11680	-.00240	.16630	.09940
.000	-4.140	-.03560	.02040	.06680	-.08010	-.00120	.16750	.09740
.000	-2.060	-.04010	.02870	.03010	-.03780	-.00080	.17040	.09660
.000	.040	-.04390	.03220	-.00620	.00530	.00090	.17060	.09650
.000	2.140	-.04270	.03150	-.04710	.05400	.00070	.16950	.09660
.000	4.250	-.03340	.02310	-.06380	.09700	.00140	.17200	.09600
.000	6.330	-.03250	.02260	-.12070	.13730	.00180	.17450	.09330
.000	8.450	-.02690	.01680	-.15990	.17970	.00190	.17660	.09640
.000	10.480	-.02560	.01660	-.20060	.22130	.00110	.18030	.09520
GRADIENT		.00009	.00039	-.01604	.02126	.00032	.00039	-.00013

MSFC 558 (MAGF) NR ATP (T3) (S1) / (O1)

(R78T38) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA

ALPHA = .000 ORBINC = .000
 MACH = 1.200 ELEVON = .000
 DELZ/D = -1.000

RUN NO. 2064/0 RN/L = 6.59 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	BETA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-10.380	-.01380	-.01410	.16690	-.18570	-.00180	.17310	.09790
.000	-8.350	-.01820	-.00230	.13290	-.15160	-.00180	.17340	.09400
.000	-6.220	-.02380	.00670	.09670	-.11310	-.00110	.17310	.06990
.000	-4.130	-.02150	.01060	.06510	-.07850	-.00020	.17320	.06810
.000	-2.080	-.02160	.01550	.03050	-.03610	.00000	.17660	.06690
.000	.030	-.02680	.02220	-.00730	.00800	.00040	.17960	.06440
.000	2.130	-.02340	.01800	-.04400	.05120	.00040	.16060	.06210
.000	4.230	-.02430	.01890	-.07760	.09000	.00060	.16090	.06340
.000	6.320	-.02180	.01620	-.11100	.12460	.00050	.16200	.06240
.000	8.450	-.01400	.00900	-.14770	.16250	.00000	.16350	.06400
.000	10.490	-.00910	-.00010	-.18710	.20380	-.00070	.18500	.06460
GRADIENT		-.06039	.00091	-.01723	.02039	.00010	.00094	-.00068

REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 91

MSFC 558 (MA9F) NR ATP (T3) (S1) / (O1)

(R78T39) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

ALPHA = .000 ORBINC = 2.000
 MACH = 1.200 ELEVON = .000
 DELZ/D = -.520

RUN NO. 2090/0 RN/L = 6.57 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	BETA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-10.410	-.07430	.07160	.18870	-.21630	-.00590	.16900	.10420
.000	-8.370	-.07310	.07200	.14920	-.17500	-.00530	.16900	.10130
.000	-6.230	-.07610	.07790	.10700	-.12790	-.00440	.16710	.09820
.000	-4.190	-.07380	.07890	.07170	-.08810	-.00250	.16790	.09610
.000	-2.070	-.07600	.08510	.03540	-.04530	-.00090	.17200	.09410
.000	.010	-.07510	.08340	-.00050	-.00200	.00000	.17400	.09460
.000	2.100	-.07110	.07760	-.04450	.05280	.00120	.17360	.09290
.000	4.190	-.06830	.07430	-.08300	.09840	.00230	.17450	.09360
.000	6.320	-.06720	.07440	-.12230	.14270	.00320	.17720	.09160
.000	8.420	-.06560	.07220	-.16520	.18690	.00350	.17950	.09410
.000	10.490	-.06900	.08000	-.20790	.23360	.00310	.18190	.09530
GRADIENT		.00076	-.00060	-.01867	.02260	.00056	.00071	-.00039

MSFC 558 (MA9F) NR ATP (T3) (S1) / (O1)

(R78T40) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

ALPHA = .000 ORBINC = 2.000
 MACH = 1.200 ELEVON = .000
 DELZ/D = -1.000

RUN NO. 2093/0 RN/L = 6.57 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	BETA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-10.380	-.05390	.04920	.17450	-.19790	-.00310	.17550	.09170
.000	-8.340	-.05490	.05010	.13760	-.16010	-.00260	.17430	.09000
.000	-6.240	-.05840	.05860	.10190	-.12120	-.00200	.17350	.08750
.000	-4.150	-.05540	.05940	.06780	-.06350	-.00090	.17400	.08550
.000	-2.070	-.05560	.06440	.03390	-.04340	-.00010	.17610	.08540
.000	.010	-.05520	.06430	-.00530	.00340	.00010	.17960	.08160
.000	2.090	-.05560	.06420	-.04200	.09000	.00040	.18020	.08100
.000	4.190	-.05490	.06300	-.07790	.09150	.00070	.18100	.08120
.000	6.310	-.04920	.05660	-.11380	.12980	.00060	.18260	.07910
.000	8.380	-.04510	.05010	-.14990	.16780	.00060	.18380	.08150
.000	10.470	-.04710	.05270	-.19170	.21150	.00000	.18590	.08200
GRADIENT		.00009	.00034	-.01762	.02120	.00018	.00067	-.00062

REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.

DATE 28 MAR 73

SOURCE DATA TABULATION, MSFC-TWT-558

PAGE 92

MSFC 558 (MA9F) NR ATP (T3) (S1) / (O1)

(R78T41) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA
 ALPHA = .000 ORBINC = 2.000
 MACH = 2.000 ELEVON = .000
 DELZ/D = -.520

RUN NO. 2116/0 RN/L = 6.82 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	BETA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-10.280	-.06740	.06120	.06660	-.03030	.00320	.05930	.03010
.000	-8.310	-.05750	.05250	.05050	-.02230	.00240	.05720	.02930
.000	-6.210	-.04840	.04550	.03540	-.01500	.00170	.05560	.02890
.000	-4.130	-.04340	.04240	.02230	-.00920	.00120	.05420	.02900
.000	-2.060	-.03790	.03860	.01090	-.00430	.00050	.05260	.02920
.000	.000	-.03050	.03120	-.00390	.00230	-.00030	.05240	.02840
.000	.010	-.03350	.03430	-.00350	.00230	-.00030	.05270	.02930
.000	2.060	-.02630	.03110	-.01600	.00810	-.00100	.05370	.03000
.000	4.160	-.02120	.02610	-.02880	.01360	-.00160	.05480	.03100
.000	6.240	-.01000	.01620	-.04380	.02050	-.00240	.05490	.03090
.000	8.330	-.00050	.00840	-.05940	.02790	-.00320	.05660	.03080
.000	10.350	.00520	.00390	-.07670	.03600	-.00430	.05940	.03030
GRADIENT		.00261	-.00194	-.00621	.00260	-.00034	.00011	.00023

MSFC 558 (MA9F) NR ATP (T3) (S1) / (O1)

(R78T42) (29 JAN 73)

REFERENCE DATA

SREF = 3220.0000 SQ.FT. XMRP = .0000
 LREF = 1328.0000 INCHES YMRP = .0000
 BREF = 1328.0000 INCHES ZMRP = -61.5000 INCHES
 SCALE = 100.0000 PER

PARAMETRIC DATA
 ALPHA = .000 ORBINC = 2.000
 MACH = 2.000 ELEVON = .000
 DELZ/D = -1.000

RUN NO. 2117/0 RN/L = 6.77 GRADIENT INTERVAL = -5.00/ 5.00

DELX/D	BETA	CN	CLM	CY	CYN	CBL	CAF	CAB
.000	-10.290	-.06160	.07150	.07150	-.03430	.00230	.05900	.03070
.000	-8.320	-.07160	.06430	.05520	-.02630	.00150	.05740	.03000
.000	-6.240	-.06640	.06120	.04000	-.01670	.00100	.05640	.02970
.000	-4.160	-.06140	.05760	.02550	-.01170	.00060	.05630	.02940
.000	-2.060	-.05620	.05340	.01170	-.00530	.00030	.05600	.02910
.000	.000	-.05020	.04810	-.00240	.00150	-.00020	.05560	.02890
.000	2.060	-.04240	.04170	-.01580	.00600	-.00050	.05520	.02960
.000	4.150	-.03580	.03600	-.02970	.01490	-.00090	.05500	.03030
.000	6.230	-.02600	.02730	-.04500	.02240	-.00120	.05590	.03100
.000	8.330	-.01590	.01800	-.06260	.03090	-.00220	.05630	.03070
.000	10.350	-.00790	.01210	-.08110	.04020	-.00330	.05810	.03100
GRADIENT		.00313	-.00265	-.00663	.00321	-.00016	-.00016	.00011