



NASA CR-

151160

NATIONAL AERONAUTICS AND SPACE ADMINISTRATION

Document No. TR-121-026

WSTF No. _____



Date November 15, 1976

(NASA-CR-151160) DESIGN CERTIFICATION TESTS	N77-16341
HIGH PRESSURE OXYGEN FILTER (HPOF) PROGRAM,	
SUMMARY REPORT (APPENDICES A, B, AND C)	
(Wintec Corp., Los Angeles, Calif.) 353 p	Unclas
HC A16/MF A01	CSCL 13K G3/37 12525

SUMMARY REPORT

DESIGN CERTIFICATION TESTS
HIGH PRESSURE OXYGEN FILTER
(HPOF) PROGRAM

(Appendices A, B, and C)




LYNDON B. JOHNSON SPACE CENTER
WHITE SANDS TEST FACILITY
LAS CRUCES, NEW MEXICO

APPENDIX A

ACCEPTANCE TEST PROCEDURE

TP-259

WINTEC



E323 WEST IMPERIAL HIGHWAY
LOS ANGELES, CALIFORNIA 90045
Telephone (213) 641-4300 Telex. 67-3105

ACCEPTANCE TEST PROCEDURE

TP 259

REVISION *VA*

ACCEPTANCE TEST PROCEDURE TP-259

HIGH PRESSURE OXYGEN FILTER

WINTEC PART NUMBER 9-812

FOR

NATIONAL AERONAUTICS AND SPACE ADMINISTRATION

CONTRACT NAS 9-14466

ORIGINAL PAGE IS
OF POOR QUALITY

APPROVED: *F. B. Jones* DATE: 2-24-76
F. B. Jones, Laboratory Director

APPROVED: *R. Roma* DATE: 2-24-76
R. Roma, Quality Assurance Manager

APPROVED: *B. A. Wilson* DATE: 2-24-76
B. A. Wilson, Chief Engineer

REVISION RECORD

ECL	DESCRIPTION OF CHANGE	DATE	APPROVED
N/C	Initial Release	2-24-76	<i>FB Jones</i>
A	<p>Page 3: Added Figure 5 callout.</p> <p>Page 8: Para 4.1.2: was E.B. Weld Para 4.1.3: Was 2.5 grams Para 4.2.1: Added Figure 5 Para 4.2.3: Was 844 + 14 Kg per sq. cm. (12000 + 800 PSIA)</p> <p>Page 9: Para 4.2.5: Deleted Paragraph Para 4.3.8: Was 1.08 Kg per sq. cm. (20" H₂O) Para 4.3.9: was reduce GN₂ Pressure. Para 4.3.11: was 1.08 Kg per sq. cm. (20" H₂O). ...0.0127 Kg per sq. cm. (5" H₂O).</p> <p>Page 10: Para 4.3.13: Added correction data Para 4.4.1.1: Revised flow rates per Para 4.4.2.1: Nasa letter Aug 3, 1976.</p> <p>Para 11: Para 4.4.2.2: Added max ΔP</p> <p>Page 16: Table 3: Revised Item 3</p> <p>Data Sheets: Revised to conform to latest configuration and new flow requirements.</p>	9-9-76	<i>FB Jones</i>
<p>ORIGINAL PAGE IS OF POOR QUALITY</p>			

TABLE I
TABLE OF CONTENTS

	<u>Description</u>	<u>Page</u>
1.0	Scope	4
2.0	Applicable Documents	4
3.0	Test Conditions	5
4.0	Test Procedures	8
4.1	Inspection of Product	8
4.2	Proof Pressure	8
4.3	Bubble Point	9
4.4	Clean Flow-Differential Pressure	10
4.5	Cleanliness Verification	11
4.6	Drying	11
4.7	Final Inspection	12
5.0	Packaging	12
6.0	Data Package	13
	<u>Figures</u>	
1	Proof Loading Test Set-Up	14
2	Bubble Point Test Set-Up	15
3	Flow-Differential Pressure Set-Up	16
4	Label and Seal	17
A 5	Proof Loading Fixture 4-2498 Cross Section <u>Tables</u>	
1	Table of Contents	3
2	Test Sequence	7
3	Instrumentation and Equipment List	18

1.0 SCOPE

This specification defines the procedures to be used in the Acceptance Testing of the Wintec High Pressure Oxygen Filter, part number 9-812. The objectives of these tests is to provide evidence that the production filters will meet the requirements of the Wintec Detailed Problem Statement SP 3400-103.

2.0 APPLICABLE DOCUMENTS

The following documents and drawings form a part of this specification to the extent specified herein.

2.1. SpecificationsMilitary

MIL-P-27401 B	Propellant Pressurizing Agent, Nitrogen
MIL-C-45662 A	Calibration Standards
MIL-STD-794 B	Parts and Equipment, Procedures for Packaging and Packing of
MIL-STD-834 C	Packaging Data Forms, Instructions for Preparation and Use of.
MIL-P-26514, Type I Class 2, 1.5 lbs. per cubic foot Density	Polyurethane Foam, Rigid or Flexible for Packaging.

NASA

JSC-SN-C-0005	Contamination Control Requirement for the Space Shuttle Program
TT-I-735 A Amendment 2	Isopropyl Alcohol (Isopropanol)
MSFC-SPEC-237 A	Precision Cleaning Agent (PCA)
NH6000-1 (1A)	Requirements for Packaging, Handling and Transport for Aeronautical and Space Systems, Equipment and Associated Components.

Federal

Fed Spec PPP-B-636 Box Fiberboard
 a. Type CF, Class
 Domestic
 b. Type CF, Class
 Weather Resistant

L-P-278, Type II Plastic Sheet and Strip, Thin
 Grade B, Finish I Gage, Polyethylene.

Society of Automotive Engineers

ARP-598 Determination of Particulate Con-
 1 March 1960 tamination of Hydraulic Fluids by
 Particle Count Method.

ARP-599 A Dynamic Test Method for Determin-
 2 Oct. 1972 ing the Degree of Clearliness of
 the Down Stream Side of Filter
 Elements.

ARP-901 Bubble Point Test Method.

Rockwell International

MR096-005 Material Cleanliness, Precision
 Packaging.

MB085-006 Film Transparent Precision Clean
 Packaging (Tinted).

Wintec

SP3400-103 High Pressure Oxygen Filter,
 Detailed Problem Statement of

2.2

Drawings

9-812 High Pressure Oxygen Filter (HPOF)

4-2498 Flow & Proof Fixture

4-2499 Bubble Point Fixture

3.0

TEST CONDITIONS

3.1

Standard Conditions

Unless otherwise specified, all tests will be conducted under
 the following ambient conditions:

Temperature: 70° + 20°F
 Relative Humidity: 80% Maximum
 Barometric Pressure: Local Atmospheric
 -5-

3.2 Test Equipment

The required instrumentation will be as shown in the schematic diagrams of Figure 1 through Figure 3.

Refer to Table 3 for instrument type, accuracy, range and calibration frequency. All instrument calibrations meet the standards of calibration of MIL-C-45662 with traceability to N. B. S.

System cleanliness to conform to the cleanliness requirements of this specification and specification WSQ-005.

3.3 Test Fluids

Nitrogen per MIL-P-27401 or equivalent.
Isopropyl Alcohol per TT-I-735, Grade B.
Precision Cleaning Agent (PCA) per MSFC-SPEC-237 or equivalent.

All test fluids entering the HPOF will be prefiltered through a 2 micron absolute (or finer) filter.

3.4 Data

A continuous test log will be maintained for each test specimen. The log shall contain a record of all operations and tests performed and the resultant data for each test. See Appendix 1 for test log forms.

3.5 Test Discrepancies

3.5.1 The failure of any portion of the test equipment will not constitute failure of the unit being tested. The test sequence may be continued at the discretion of the cognizant test engineer if the failure does not represent a danger to the facility, test personnel, the unit undergoing test, or invalidate the required test objectives.

3.5.2 Failure Notification

In the event that the unit under test exhibits any failure or deviation from the test requirements set forth in this procedure, notify Mr. Irwin Smith, NASA-JSC, White Sands Test Facility, Las Cruces, N. M., that a test failure has occurred as follows:

- a) Notify Mr. I. Smith, Telephone (505) 524-5522 within 24 hours after failure occurrence.
- b) Prepare and submit a written failure report within seven (7) calendar days.

TABLE 2
ACCEPTANCE TEST SEQUENCE

<u>Sequence Number</u>	<u>Description</u>	<u>TP 259 Paragraph</u>
1	Inspection of Product	4.1
2	Proof Pressure	4.2
3	Bubble Point	4.3
4	Flow- Δ P	4.4
5	Cleanliness Verification	4.5
6	Drying	4.6
7	Final Inspection	4.7
8	Packaging	5.0

3.6 Test Notification

The Mr. I. Smith, NASA-JSC, White Sands Test Facility, and the Government Inspector, as required by the applicable purchase order, shall be notified at least 48 hours prior to the performance of any scheduled test so that authorized representatives may witness the test as required.

4.0 TEST PROCEDURE

Unless otherwise specified, the acceptance tests are to be performed on all deliverable HPOF assemblies prior to delivery. The tests are to be performed in the sequence shown in Table 2.

4.1. Inspection of Product

- 4.1.1 Each HPOF assembly (P/N 9-812) shall be inspected for conformance with the drawing requirements. The areas of inspection shall cover:

Finish
Workmanship
Dimensions
Identification
Certified Materials and Processes

- A 4.1.2 Inspect the TIG weld that joins the two 20-1265 rings with a 40X binocular microscope. There shall be no cracks or breaks in the welds.
- A 4.1.3 Measure the weight of each HPOF assembly to the nearest 10 milligram and record the weight. The weight of the HPOF shall not exceed 7.0 grams.
- 4.2 Proof Pressure
- A 4.2.1 Install the HPOF into Fixture 4-2498 as shown in Figure 5.
- 4.2.2 Install the HPOF and 4-2498 fixture into a proof pressure test system as shown in Figure 1.
- A 4.2.3 With the outlet of the 4-2498 Fixture vented to atmosphere, pressurize the inlet of the fixture to 668 ± 0 Kg per sq. cm. (9500 ± 0^{00} psia) with GN₂. Maintain this pressure for 5 ± 1 minutes. Reduce the pressure to atmosphere by venting the inlet side of the HPOF.
- 4.2.4 The HPOF shall not collapse as a result of this test.

- A 4.2.5 DELETED
- 4.3 Bubble Point
- 4.3.1 The 4-2499 fixture and transfer tube shall be flushed with IPA that has been filtered through a 0.8 micron or finer membrane.
- 4.3.2 Install the HPOF into Fixture 4-2499.
- 4.3.3 Measure and record the surface tension and temperature of the Isopropanol (IPA) that will be used..
- 4.3.4 Prefilter Isopropanol (IPA) through a 0.45 micron membrane. Measure and record the surface tension and temperature of the prefiltered IPA. This IPA is to be reserved for bubble point testing of the HPOF assemblies.
- 4.3.5 Attach the HPOF and Fixture 4-2499 to a transfer tube. The transfer tube is a part of the Bubble Point Test system, Figure 2.
- 4.3.6 Using a Hypodermic syringe, fill the transfer tube with IPA (reference paragraph 4.3.4).
- 4.3.7 Attach the transfer tube to the Bubble Point Test System, Figure 2. The 4-2499 Fixture shall be in a vertical position.
- A 4.3.8 Pressurize the HPOF to 1.45 to 1.52 Kg/cm² (8 to 14 in. Hg,) 100 to 190 in. H₂O. The IPA in the transfer tube will be forced through the HPOF to wet all internal surfaces of the HPOF. The IPA will rise in and overflow the open port of the 4-2499 fixture. All bubbles of entrapped air shall cease to emit from the test fixture before proceeding with the next step.
- A 4.3.9 Reduce GN₂ pressure to 1.068 Kg/cm² (1.0 in. Hg, 14 in. H₂O) open valve (A) and allow the excess IPA in the transfer tube to drain out of tube. Close the valve (A).
- 4.3.10 Assure that the open part of Fixture 4-2499 is filled with IPA.
- A 4.3.11 Increase the GN₂ pressure to 1.154 Kg/cm² (3.5 in. Hg, 47.6 in. H₂O) for 2 min. Then increase the pressure at a rate of 1.051 Kg/cm²/minute (0.5 in Hg, 7.0 in. H₂O/minute.) until the first train of bubbles emit from the HPOF. This is the initial (observed) bubble point and shall be recorded. The initial bubble point shall be corrected.

4.3.12 Method for determining surface tension correction factor.

$$ST = C \times R \times D$$

Where:

ST = Surface Tension - Dynes/cm
 C = 16.5 (Capillary Tube Constant)
 R = Difference in Rise of Fluid in cm.
 D = Density of Fluid at Measured Temp.

4.3.13 Method for correcting the observed bubble point to standard conditions.

Where:

$$P_s = (P-dh) \frac{21.15}{ST}$$

P_s = Standard Bubble Point
 P = Observed Bubble Point
 (in. Hg x 13.596 = in. H₂O)
 (PSID x 27.687 = in. H₂O)
 d = Density
 h = Immersion Depth, Inches
 ST = Measured Surface Tension
 21.15 = Standard Surface Tension

4.3.14 The standard bubble point (P_s) shall be greater than (TBD) Kg per sq. cm. (TBD inches of water).4.3.15 Remove the 4-2499 fixture from the bubble point test system and flow prefiltered (0.45 micron) GN₂ through the HPOF to remove all of the residual IPA.

4.3.16 Remove the HPOF from the 4-2499 fixture.

4.4 Clean Flow- Differential Pressure

4.4.1 Install the 4-2498 flow fixture into a flow system as shown in Figure 3.

A 4.4.1.1 Conduct a tare test to measure the system differential pressure (ΔP) at flow rates 0.045, 0.061, and 0.076 ACFM (1.28, 1.71 and 2.14 SCFM) of GN₂ with an inlet pressure of 29.18 Kg per sq. cm. (400 \pm 5 psig). Record the tare ΔP at each flow rate.

4.4.2 Install the HPOF into the 4-2498 fixture.

A 4.4.2.1 Install the HPOF and 4-2498 fixture into the flow system (reference Figure 3) and conduct a flow- ΔP test at flow rates of 0.045, 0.061 and 0.076 ACFM (1.28, 1.71 and 2.14 SCFM) of GN₂ with an inlet pressure of 29.18 Kg per sq. cm. (400 \pm 5 psig). Record the ΔP and temperature at each flow rate. This will be the gross- ΔP at the three noted flow rates.

A

4.4.2.2 Subtract the tare- ΔP from the gross- ΔP for each respective flow rate. The difference will be the net- ΔP for each flow rate. The net- ΔP shall not exceed 300 PSID.

4.4.2.3 Remove the HPOF assembly from the flow system and the 4-2498 flow fixture and set the HPOF aside.

4.5 Cleanliness Verification

4.5.1 Clean the 4-2498 flow fixture by thoroughly flushing with PCA solvent that has been prefiltered through a 0.8 micron or finer filter.

4.5.2 Carefully install the HPOF assembly in the 4-2498 flow fixture. Flush the HPOF in both directions by flowing prefiltered (0.8 micron or finer) PCA through the HPOF.

4.5.3 After flushing the HPOF in both directions, take a sample of the PCA effluent while flowing one direction, then in the other direction. Fifty (50) mil of PCA effluent shall be sampled in each flow direction. The effluent samples may be drawn through a Wintec viewer sampler that has been loaded with a precleaned and pre counted 0.8 micron, 47 min. membrane (Type AA or equivalent). The membrane shall be examined and a particulate count made per the requirements of ARP 598.

4.5.4 The particulate count shall not exceed Table I, Level 25 of JSC-SN-C-0005 as noted below:

<u>Particle Size Range</u>	<u>Particles/100 ml</u>
< 5 microns	no silting
5 - 15 microns	19
16 - 25 microns	4
> 25 microns	0

4.5.5 If the particulate count of paragraph 4.5.4 is exceeded, repeat paragraphs 4.5.2 and 4.5.3 until the HPOF meets the requirements of paragraph 4.5.4.

4.5.6 Remove the HPOF from the 4-2498 fixture.

4.6 Drying

4.6.1 Place the HPOF in a precleaned aluminum dish and place in a vacuum oven. Dry the HPOF at 170 ± 10 degrees F for 15 minutes without a vacuum and 30 to 45 minutes at a pressure of 25 to 28" Hg.

4.7 Final Inspection

- 4.7.1 Visually inspect the HPOF assembly before packaging to assure the unit did not sustain any damage as a result of the acceptance testing and handling. Assure that there are no particles on the exterior surfaces of the unit.

5.0 PACKAGING

5.1 Inner Packaging

NOTE: Inner packaging shall be accomplished in the Clean Room.

- 5.1.1 Insert the unit into a 2 mil tinted nylon "C" Bag (para 2.9) approximately 6 x 3 inches. The inside of the bag shall meet or exceed the requirements of PB095-005, Level 1.
- 5.1.2 Partially seal bag leaving corner open, evacuate air, and final heat seal bag.
- 5.1.3 Attach an Inspection Seal over the final heat sealed ends of bag, Figure 4B.
- 5.1.4 Place the sealed unit into a 6 mil anti-static polyethylene (para 2.10) contamination barrier bag approximately 6 x 3 inches. Insert a Cleanliness/Identification Tag, Figure 4A into bag and partially heat seal bag, evacuate bag, and final heat seal bag. The inside of the bag shall meet or exceed the requirements of PB0295-005, Level 3.

5.2 Unit Packaging

- 5.2.1 Wrap the packaged unit in a 1/2 inch thick sheet of polyurethane foam. Tape overlap using 1/2 inch wide masking tape.
- 5.2.2 Place wrapped unit into box (para 2.7a) and seal using reinforced tape.
- 5.2.3 Stamp side of each box with the following information:

Item Name: High pressure oxygen filter (HPOF)
Manufacturer's Part Number: 9-812
Quantity in Package
Clean Marking: This unit has been cleaned to Table I, Level
25 of JSC-SN-C-0005.
Traceability Identification
Serial Number
Mfg: Wintec Division of Brunswick Corporation
Buyer Purchase Order Number
Date of Packaging

5.3 Shipping Container

5.3.1 Unit packages shall be placed into a Weather Resistance Fiber-board Container.

5.3.2 Test data and associated data shall be enclosed in an envelope and placed inside of the Shipping Container. Close and seal container using gummed reinforced tape.

5.3.3 The container shall be marked with information specified in para 5.2.3.

6.0 DATA PACKAGE

6.1 The data package shall include but not be limited to the following items as applicable:

- a) Statement of Certification
- b) Visual Inspection Characteristics (data sheets)
- c) List of Dimensional Inspection Requirements (data sheets)
- d) Copy of Suppliers Shipping Document.

FIGURE 1
PROOF LOADING TEST SET-UP




FIGURE 2
BUBBLE POINT TEST SET-UP




FIGURE 3
GAS FLOW TEST SYSTEM




FIGURE 4

4A IDENTIFICATION LABEL

WINTEC DIV. - BRUNSWICK CORP.

5223 Imperial Highway
 Los Angeles, Calif. 90045
 Code. 21550

DO NOT OPEN

EXCEPT IN A CONTROLLED ENVIRONMENTAL FACILITY

P/N: 9-812 S/N: _____

PART NAME: HPOF QTY. 1 ea.

CUST. P/N: --

CONTRACT: NAS 9-14466

CUSTOMER: NASA

CLEANED PER: JSC-SN-C-0005

LEVEL: 25 SERVICE: Oxygen

INSP. _____ DATE _____

4B INTEGRITY SEAL






FIGURE 5
PROOF LOADING FIXTURE CROSS SECTION

*Place smaller diameter of plug toward HPOF (9-812).

TABLE 3
EQUIPMENT & INSTRUMENT LIST

Item No.

①	Instrument Manufacturer Size Serial No. Range Accuracy Calibration	Pressure Gage US Gauge 6" Dia. 0018 0-20,000 1% 90 Days
②	Instrument Manufacturer Size Serial No. Range Accuracy Calibration	Pressure Gauge Ashcroft 5" Dia. 0008 0-60 psig 1% 90 Days
③	Instrument Manufacturer Model No. Serial No. Range Accuracy Calibration	Δ P Transducer System Validyne CDIZ 5101 0-100, 0-300, 0-1000 PSID 1% Prior to Use
④	Instrument Manufacturer Model No. Serial No. Range Accuracy Calibration	Temperature Indicator Barber Coleman Type 7 46H 2317 -300°F to +300°F 2°F 90 Days
⑤	Instrument Manufacturer Model No. Serial No. Range Accuracy Calibration	Flow Meter Fischer Proter 1/2-27-G-10180 FMK-004B .2 to 3.4 SCFM GN ₂ 1% Yearly

TABLE 3
EQUIPMENT & INSTRUMENTATION LIST (CON'T)

Item No.

⑥	Instrument	Manometer
	Manufacturer	Meriam
	Model No.	30FB25
	Serial No.	N 24121
	Range	0 to 50 in. H ₂ O
	Accuracy	.003 in. H ₂ O
	Calibration	DNA*

*DNA = Does Not Apply

The noted instruments on instrumentation with the same accuracy shall be used for Acceptance Testing.

APPENDIX 1

TP 259

WİNTEC division
Brunswick Corporation



5223 West Imperial Highway
Los Angeles, California 90045
(213) 641-4300 Telex: 67-3105

S.O. _____

CERTIFICATE OF CONFORMANCE

Date: _____ Part Number _____

Customer P.O. No. _____ P.O. Item Number _____

Number parts delivered with this shipment _____

Shipper No. _____ Serial No (s) _____

1. We hereby certify that the units were processed per the above noted purchase order and specifications. Parts manufactured by Wintec were fabricated from materials of which physical and/or chemical test reports are maintained on file subject to examination.
2. Materials furnished by the customer for the manufacture of parts have been in fact used in their manufacture.
3. All special processes applied to the above parts have been accomplished by approved sources.
4. Units have been cleaned and packaged to the following specifications:

BY: _____
QUALITY ASSURANCE

**ORIGINAL PAGE IS
OF POOR QUALITY**

TP 259



SHIPPER NO.

5223 WEST IMPERIAL HIGHWAY • LOS ANGELES, CALIFORNIA 90045 • PHONE: (213) 641-4300

S
O
L
D

T
O

S
H
I
P

T
O

DATE SHIPPED	SHIPPED VIA	INVOICE NUMBER	SALES ORDER NUMBER
CUSTOMER P.O. NUMBER	CONTRACT NUMBER	F.O.B.	TERMS:

ITEM	QUANTITY				PART NUMBER	DESCRIPTION	UNIT PRICE	EXTENSION
	ORDERED	SHIPPED TO DATE	BACK ORDER	THIS SHIPMENT				

COMPANY INSPECTION

CUSTOMER INSPECTION

GOVERNMENT INSPECTION

WINTEC CORPORATION

ACCEPTANCE TEST DATA SHEET
ATP TDP 259
REVISION

S/O NO.

SHT. 2 OF 3

CUSTOMER	CUST. SPEC.	REV.	CUST. P/N	REV.	WINTEC P/N	REV.
NASA					9-812	

TEST	ALLOWSABLE VALUES	SERIAL NO.
INSPECTION ACCEPTANCE	300 PSID Max.	Gross- Δ P @ 1.28 scfm Para 4.4
		Tare- Δ P @ 1.28 scfm Para 4.4
		Net- Δ P @ 1.28 scfm Para 4.4
		Gross- Δ P @ 1.71 scfm Para 4.4
		Tare- Δ P @ 1.71 scfm Para 4.4
		Net- Δ P @ 1.71 scfm Para 4.4
		Gross- Δ P @ 2.14 scfm Para 4.4
		Tare- Δ P @ 2.14 scfm Para 4.4
		Net- Δ P @ 2.14 scfm Para 4.4
		Gas Temp. OF @1.28 scfm Para 4.4
Gas Temp. OF @ 1.71 scfm Para 4.4		
Gas Temp OF @2.14 scfm Para 4.4		
GOVT.		

ORIGINAL PAGE IS
OF POOR QUALITY

APPENDIX B

RESULTS OF ACCEPTANCE TESTS PERFORMED BY
WINTEC DIVISION, BRUNSWICK CORPORATION

WINTEC CORPORATION

S/O NO. 3400-6

SHT. 1 OF 3

CUSTOMER	CNST. SPLC.	REV.	CNST. P/N	REV.	WHILE C/P/N	REV.
NASA					9-812	

SERIAL NO.	INSPECTION OF PRODUCT	Para 4.1.1	Para 4.1.1	Para 4.1.1	Para 4.1.2	Para 4.1.3	Para 4.2	Para 4.3	Para 4.3	Para 4.3	Para 4.3	Para 4.3	Para 4.3
027	OK	341	4975	OK	6.55	OK		55.233	-	72	7827	21.50	53.998
028	OK	343	4978	OK	6.52	OK		59.483	-	72	7827	21.50	58.129
029	OK	3395	4976	OK	6.54	OK		60.136	-	72	7827	21.50	48.920

ALLOWABLE VALUES

Length

No Cracks or Voids

7.0 gms. Max.

INSPECTION ACCEPTANCE

DATE	4.1.1	4.1.2	4.1.3	4.2	4.3	4.3	4.3	4.3	4.3	4.3	4.3	4.3	4.3
WINTEC													
CUSTOMER													
DATE	7-26-76	7-26-76	8-16-76	8-26-76	8-26-76								

ORIGINAL PAGE IS OF POOR QUALITY

WINTEC CORPORATION

ACCEPTANCE TEST DATA SHEET
ATP TP 259
REVISION

S/O NO.


SHT. 2 OF 3

CUSTOMER	CUST. SPEC.	LEV.	CUST. P/R	REV.	WINTEC P/N	REV.
NASA					9-812	

SERIAL NO.	GROSS-ΔP @		Net-ΔP @		GROSS-ΔP @		Net-ΔP @		GROSS-ΔP @		Net-ΔP @		GROSS-ΔP @	
	1.38 scfm	Para 4.4	1.88 scfm	Para 4.4	1.84 scfm	Para 4.4	2.35 scfm	Para 4.4	1.38 scfm	Para 4.4	1.84 scfm	Para 4.4	2.35 scfm	Para 4.4
017	79	-	79	115	-	115	180	-	180	69	69	69	400	
028	97	-	97	140	-	140	215	-	215	69	69	69	400	
019	102	-	102	158	-	158	235	-	235	69	69	69	400	

ALLOWABLE VALUES

INSPECTOR ACCEPTANCE

WINTEC	914							G.D.V.T.
CUSTOMER								
DATE	8-30-76							

ORIGINAL PAGE IS OF POOR QUALITY

WINTEC CORPORATION

S/O NO. 3900-6

SHT. 1 OF 3

CUSTOMER	CUST. SPEC.	REV.	CUST. P/N	REV.	WINTEC P/N	REV.
NASA					9-812	

SERIAL NO.	Inspection of Product Para 4.1.1	Weight gms	PROOF Pressure	Bubble Point Observed	Rise of Fluid in Capillary	Fluid Temp. of	Density of Fluid	Surface Tension of IPA	Standard	Bubble Point
022	OK	2726	OK	58.51	-	74	7817	2132	58.51	
023	OK	275	OK	55.23	-	74	7817	2133	58.52	
025	OK	2765	OK	62.58	-	74	7817	2132	58.51	P23

ALLOWABLE VALUES

No Cracks or Voids

2.5 gms. Max.

INSPECTION ACCEPTANCE

TEST	1111	1112	1113	112	1125	113	GOVT.
WINTEC							
Q.1, ER	S-2-76	S-2-76	S-2-76	S-2-76	S-2-76	S-2-76	S-2-76

ORIGINAL PAGE IS
 OF POOR QUALITY

WINTEC CORPORATION

S/O NO. 3400-6

SHT. 2 OF 3

CUSTOMER	CUST. SPEC.	REV.	CUST. P/N	HLV.	WINTEC P/N	REV.
NASA					9-812	

SERIAL NO.	Gross-ΔP @ 1.38 SCFM Para 4.4	Net-ΔP @ 1.38 SCFM Para 4.4	Gross-ΔP @ 1.84 SCFM Para 4.4	Net-ΔP @ 1.84 SCFM Para 4.4	Gross-ΔP @ 2.35 SCFM Para 4.4	Net-ΔP @ 2.35 SCFM Para 4.4	Gas Temp. OF @ 1.38 SCFM Para 4.4	Gas Temp. OF @ 1.84 SCFM. Para 4.4	Gas Temp. OF @ 2.35 SCFM Para 4.4
022	95	-	145	-	215	-	68	68	68
023	115	-	170	-	250	-	68	68	68
025	105	-	160	-	235	-	68	68	68

8-2-76

INSPECTION ACCEPTANCE





TEST	4.4								
DATE	8-2-76								

ORIGINAL PAGE IS
 OF POOR QUALITY

WINTEC CORPORATION

S/O NO. 3900-6..

SHT. 3 OF 3

CUSTOMER		CUST. SPEC.		REV.	CUST. P/N		REV.	WINTEC P/N		REV.
NASA								9-812		
SERIAL NO.	Cleanliness Level Para 4.5									
	Particles, Micron/100 ml									
					0	5	16	>		
					4	15	25	25		
022		6.79			8	4	2	0	0.3MG	
023		6.79			8	6	2	0	0.3MG	
025		6.80			8	4	2	0	0.3MG	
ALLOWABLE VALUES					No Silting	19	4	0		
INSPECTION ACCEPTANCE										
TEST										
WINTEC										
CUSTOMER										
	AN 2 74	MC 2 13	RR 2 10							8-02-7-6

ORIGINAL PAGE IS
 OF POOR QUALITY

WINTEG CORPORATION

S/O NO. _____
 SIT. 1 OF 3
 CUSTOMER: NASA
 CUST. SPEC. _____
 REV. _____
 CUST. P/N _____
 H/W. _____
 WAFIC P/N: 9-812
 REV. _____

SERIAL NO.	Inspection of Product	Para 4.1.1	Weight gms	Para 4.1.3	Proof Pres- sure	Para 4.2	Bubble Point Observed	Para 4.3	Rise of Fluid in Capillary	Para 4.3	Fluid Temp. of	Para 4.3	Density of Fluid	Para 4.3	Surface Ten- sion of IPA	Para 4.3	Standard Bubble Point	Para 4.3
022	CI	2282 + .000 C.H.S. = .010	2205 + .002	2498 + .000 Die. = .001	2282 + .000 = .010	2217	21.57	21.45	22.55	22.55	21.45	22.55	21.45	22.55	21.45	22.55	21.45	22.55
024	OK	2282 + .000 C.H.S. = .010	2205 + .002	2498 + .000 Die. = .001	2282 + .000 = .010	2217	21.57	21.45	22.55	22.55	21.45	22.55	21.45	22.55	21.45	22.55	21.45	22.55
025	OK	2282 + .000 C.H.S. = .010	2205 + .002	2498 + .000 Die. = .001	2282 + .000 = .010	2217	21.57	21.45	22.55	22.55	21.45	22.55	21.45	22.55	21.45	22.55	21.45	22.55

No Cracks
or Voids

ALLOWABLE VALUES

LIST

T.C.

CUSTOMER DATE

INSPECTION ACCEPTANCE

GOVT.

ORIGINAL PAGE IS
 OF POOR QUALITY

WINTEC CORPORATION

S/C NO.

SHT. 2 OF 3

CUSTOMER	CUST. SPEC.	REV.	CUST. P/N	REV.	WINTEC P/N	REV.
NASA					9-812	

INLET PRESSURE = 520 PSI.

SERIAL NO.	GROSS-ΔP @ 1.0 scfm Para 4.4	GROSS-ΔP @ 1.0 scfm Para 4.4	NET-ΔP @ 1.0 scfm Para 4.4	GROSS-ΔP @ 2.04 scfm Para 4.4	NET-ΔP @ 2.04 scfm Para 4.4	NET-ΔP @ 2.04 scfm Para 4.4	GROSS-ΔP @ 3.06 scfm Para 4.4	NET-ΔP @ 3.06 scfm Para 4.4	NET-ΔP @ 3.06 scfm Para 4.4	Gas Temp. of @ 1.0 scfm Para 4.4	Gas Temp. of @ 2.04 scfm Para 4.4	Gas Temp. of @ 3.06 scfm Para 4.4	ALLOTTABLE VALUES
073	75	-	75	150	1	125	350	1	350	70	70	70	
026	80	-	70	100	1	200	400	1	400	70	70	70	
125	75	-	75	110	1	125	390	1	390	70	70	70	

INSPECTION ACCEPTANCE

INITIALS	DATE											QNT.	
BR	7-1-50												

ORIGINAL PAGE IS
OF POOR QUALITY

WINTEC CORPORATION

ACCEPTANCE TEST DATA SHEET
ATAP 259
REVISION

S/D NO. 3400-1

SHT. 1 OF 3

CUSTOMER	CUST. SPEC.	REV.	CUST. P/H	REV.	WINTEC P/H	REV.
NASA					9-812	

SERIAL NO.	DESCRIPTION	TEST VALUE	TEST VALUE	TEST VALUE	TEST VALUE	TEST VALUE	TEST VALUE	TEST VALUE	TEST VALUE
021	Inspection Of Product Para 4.1.1	2718	3487	4973	67674	2699	64581	-	74
	Para 4.1.1								
	-282 ± .818								
	C.H.S.								
	Para 4.1.1								
	.285 ± .002								
	Para 4.1.1								
	.498 ± .000								
	Dia.								
	Para 4.1.1								
	Inspect Para Welds 77.6								
	Para 4.1.2								
	Weight gms								
	Para 4.1.3								
	PROF Pres-ure								
	Para 4.2								
	.282 ± .010								
	Para 4.2.5								
	Bubble Point Observed								
	Para 4.3								
	Rise of Fluid in Capillary								
	Para 4.3								
	Fluid Temp. of								
	Para 4.3								
	Density of Fluid								
	Para 4.3								
	Surface Tension of IPA								
	Para 4.3								
	Standard								
	Bubble Point								
	Para 4.3								

INSPECTION ACCEPTANCE									
YES	4.1.1	4.1.2	4.1.3	4.2	4.2.5	4.3			GOV'T.
WINTEC									
CL									
DATE									

ORIGINAL PAGE IS OF POOR QUALITY

S/O NO. 3400-1



SHT. 2 OF 3

WINTEC CORPORATION

CUSTOMER	CUST. SPEC.	REV.	CUST. P/H	REV.	WINTEC P/H	REV.
ASA	—	—	—	—	9-812	

SERIAL NO.	TEST	RESULT	REMARKS
021	Gross- Δ P @ 1.0 scfm Para 4.4	57	
	Tare- Δ P @ 1.0 scfm Para 4.4	—	
	Net- Δ P @ 1.0 scfm Para 4.4	57	
	Gross- Δ P @ 2.04 scfm Para 4.4	145	
	Tare- Δ P @ 2.04 scfm Para 4.4	—	
	Net- Δ P @ 2.04 scfm Para 4.4	146	
	Gross- Δ P @ 3.06 scfm Para 4.4	308	
	Tare- Δ P @ 3.06 scfm Para 4.4	—	
	Net- Δ P @ 3.06 scfm Para 4.4	308	
	Gas Temp. of @ 1.0 scfm Para 4.4	68	
	Gas Temp. of @ 2.04 scfm Para 4.4	68	
	Gas Temp. of @ 3.06 scfm Para 4.4	68	
			@ 400 PSI INLET

INSPECTION ACCEPTANCE

TEST	YES	NO	DATE	WINTEC	GOV'T.
WINTEC					
CHS					
DATE					

ORIGINAL PAGE IS
 OF POOR QUALITY

WINTEC CORPORATION



ACCEPTANCE TEST DATA SHEET
ATP TP 259
REVISION

S/O NO. 3.400-1.

SHT. 3 OF 3

CUSTOMER	CUST. SPEC.	REV.	CUST. P/N	REV.	WINTEC P/N	REV.
NASA	—	—	—	—	9-812	

SERIAL NO.	Cleanliness Level Para 4.5			
	Particles, Micron/100 ml			
		4	5	16
		15	25	25
021	—	3	2	0
ALLOWABLE VALUES	No silting	19	4	0

INSPECTION ACCEPTANCE							
TEST	4/5						
WINTEC							
CU.							
DATE							

WINTEC CORPORATION

S/O NO. **3400-6**

SHT. **1** OF **3**

CUSTOMER	CUST. SPEC.	REV.	CUST. P/N	REV.	WINTEC P/N	REV.
NASA					9-812	

SERIAL NO.	Inspection of Product	Para 4.1.1	Para 4.1.1	Para 4.1.1	Para 4.1.1	Inspect E. B Welds	Para 4.1.2	Weight gms	Para 4.1.3	Proof Pressure	Para 4.2	Para 4.2.5	Bubble Point Observed	Para 4.3	Rise of Fluid in Capillary	Para 4.3	Fluid Temp.	Para 4.3	Density of Fluid	Para 4.3	Surface Tension of IPA	Para 4.3	Standard Bubble Point	Para 4.3
018		2703									2703													
020		2664	2851	4977				5.61			2664	56.93				75			7812		22.7		52.68	
						No Cracks or Voids		2.5 gms. Max.																

INSPECTION ACCEPTANCE

TEST	4.1.1	4.1.2	4.1.3	4.2	4.2.5	4.3	4.4	4.5	GOV'T.
WINTEC									
CR									
DATE	11/15/55	11/15/55	11/15/55	11/15/55	11/15/55	11/15/55	11/15/55		

ORIGINAL PAGE IS OF POOR QUALITY

WINTEC CORPORATION

S/O NO. **3400-6**

SHT. **3** of **3**

CUSTOMER	CUST. SPEC.	REV.	CUST. P/N	REV.	WINTEC P/N	REV.
NASA					9-812	

SERIAL NO.	Cleanliness Level Para 4.5						
	Particles, Micron/100 ml						
	0 4	5 15	16 25	> 25			
020	∞	8	4	0			NUR PARA 4.5
ALLOWABLE VALUES		No Silting	19	4	0		.001 GR / 100 ml

INSPECTION ACCEPTANCE

TEST	4.5							GDM:
WINTEC:								
CUS FR								
D:	SN 18							

ORIGINAL PAGE IS
OF POOR QUALITY

WINTEC CORPORATION

S/O NO.
SHT. 1 OF 3

CUSTOMER	CUST. SPEC.	REV.	CUST. P/N	REV.	WINTEC P/N	REV.
NASA					9-812	

SERIAL NO.	Inspection of Product Para 4.1.1	.282 ± .000 C.H.S. Para 4.1.1	.285 ± .002 Para 4.1.1	.498 ± .001 Dia. Para 4.1.1	Inspect. E. B. Welds Para 4.1.2	Weight gms Para 4.1.3	Proof Pressure Para 4.2	Bubble Point Observed Para 4.3	Rise of Fluid in Capillary Para 4.3	Fluid Temp. OF Para 4.3	Density of Fluid Para 4.3	Surface Tension of IPA para 4.3	Standard Bubble Point Para 4.3	
601		.2712	.2852	.4976			NG.							
002		.2697	.286	.4977			OK	.2696	4.813	1.5	69°	.784	19.41	70.876
005		.2702	.285	.4976			OK	.2702	4.737	1.5	69°	.784	19.41	72.715
004		.274	.286	.4979										
005		.2765	.285	.498										
006		.2738	.285	.4978			OK	.2777	5.250	1.5	69°	.784	19.41	77.358
008		.2746	.2847	.4976										

ALLOWABLE VALUES	NO Cracks OR Voids	2.5 gms. Max.											
------------------	--------------------	---------------	--	--	--	--	--	--	--	--	--	--	--

INSPECTION ACCEPTANCE											
TEST	WHY	CUS	DATE	TEST	WHY	CUS	DATE	TEST	WHY	CUS	DATE

#2 Result at 1200 = 4.911 in.

ORIGINAL PAGE IS OF POOR QUALITY

ORIGINAL PAGE IS
OF POOR QUALITY

APPENDIX C

ORIGINAL

FLOW RATE VERSUS DIFFERENTIAL PRESSURE DATA

TABLE 1
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 1 PART 1C TEST DESCRIPTION

415 psia (nominal) Test Specimen
Inlet Pressure Tare Test

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)
0	45.7	69.0
0	50.1	68.7
0	50.7	68.4
0	52.6	66.7
0	52.0	65.2
0	52.6	64.1
0	52.0	63.6
0	52.0	63.3
0	51.3	63.0
0	51.3	62.7
0	50.1	62.8
0	52.0	63.1
0	52.0	63.6
0	48.2	64.3
0	50.1	64.7
0	52.7	65.3
0	48.8	66.2
0	52.0	66.7
0	52.0	67.4

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)
.16	52.3	70.7
.20	57.4	70.8
.24	57.4	70.8
.29	58.7	69.6
.40	57.4	68.7
.49	58.1	67.8
.59	57.4	67.1
.69	57.4	66.8
.80	56.2	66.2
.90	54.9	65.7
.90	54.9	65.3
.81	54.9	65.4
.71	57.4	65.7
.61	57.4	66.2
.50	54.2	66.8
.41	56.8	67.2
.31	57.4	67.7
.25	54.9	68.5
.21	58.1	68.8
.13	58.1	69.5

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
408.3	69.8	.0206
418.7	69.7	.0278
415.5	69.6	.0333
412.9	68.2	.0418
413.5	66.9	.0551
418.7	65.9	.0683
417.4	65.4	.0817
416.8	65.1	.0954
412.9	64.7	.1082
413.5	64.3	.1198
415.5	64.0	.1193
415.5	64.1	.1072
417.4	64.4	.0973
415.5	64.9	.0848
412.2	65.6	.0664
415.5	66.0	.0566
416.8	66.5	.0430
412.9	67.3	.0333
418.1	67.7	.0286
414.2	68.5	.0189

TABLE 1
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 1 PART 1C TEST DESCRIPTION 415 psia (nominal) Test Specimen
Inlet Pressure Tare Test

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS. (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
408.3	69.8	.0206		0		0	0
418.7	69.7	.0278		0		0	0
415.5	69.6	.0333		0		0	0
412.9	68.2	.0418		.001		0	0.001
413.5	66.9	.0551		.001		0	0.001
418.7	65.9	.0683		.001		0	0.001
417.4	65.4	.0817		.001		0	0.001
416.8	65.1	.0954		.001		0	0.001
412.9	64.7	.1082		.002		0	0.002
413.5	64.3	.1198		.002		0	0.002
415.5	64.0	.1193		.002		0	0.002
415.5	64.1	.1072		.002		0	0.002
417.4	64.4	.0973		.001		0	0.001
415.5	64.9	.0848		.001		0	0.001
412.2	65.6	.0664		0		0	0
415.5	66.0	.0566		0		0	0
416.8	66.5	.0430		0		0	0
412.9	67.3	.0333		0		0	0
418.1	67.7	.0286		0		0	0
414.2	68.5	.0189		0		0	0

COMPUTED EQUATION:

TARE DIFF. PRESS = -0.000034 - 0.000444 (ACFM) + 0.150933 (ACFM)**2 +

0 (ACFM)**3

SIGMA = 0.00034

ORIGINAL PAGE IS
OF POOR QUALITY

ORIGINAL PAGE IS
OF POOR QUALITY

PAGE: 3

DATE: 4/20/76

TABLE 1
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 1		PART 10			TEST DESCRIPTION		415 psia (nominal) Test Specimen		Inlet Pressure Tare Test		NET DIFFERENTIAL PRESS		
TEST SPECIMEN INLET CONDITIONS											*****		
PRESSURE		TEMPERATURE			FLOW RATE							*****	
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID		
28.708	408.3	294.2	21.0	69.8	16.2	.0206	.573	1.128	2.488	0.0000	0.000		
29.438	418.7	294.1	21.0	69.7	22.4	.0278	.792	1.560	3.440	0.0000	0.000		
29.210	415.5	294.0	20.9	69.6	26.6	.0333	.940	1.852	4.083	0.0000	0.000		
29.028	412.9	293.3	20.1	68.2	33.3	.0418	1.177	2.317	5.108	0.0001	0.001		
29.073	413.5	292.6	19.4	66.9	44.1	.0551	1.558	3.069	6.765	0.0001	0.001		
29.438	418.7	292.0	18.8	65.9	55.5	.0683	1.961	3.861	8.512	0.0001	0.001		
29.347	417.4	291.7	18.5	65.4	66.3	.0817	2.340	4.607	10.197	0.0001	0.001		
29.302	416.8	291.5	18.4	65.1	77.3	.0954	2.731	5.378	11.857	0.0001	0.001		
29.028	412.9	291.3	18.2	64.7	86.9	.1082	3.069	6.043	13.323	0.0001	0.002		
29.073	413.5	291.1	18.0	64.3	96.5	.1198	3.408	6.710	14.793	0.0001	0.002		
29.210	415.5	290.9	17.8	64.0	96.6	.1193	3.410	6.714	14.802	0.0001	0.002		
29.210	415.5	291.0	17.8	64.1	86.7	.1072	3.063	6.032	13.298	0.0001	0.002		
29.347	417.4	291.2	18.0	64.4	79.1	.0973	2.792	5.497	12.119	0.0001	0.001		
29.210	415.5	291.4	18.3	64.9	68.5	.0848	2.420	4.765	10.504	0.0001	0.001		
28.982	412.2	291.8	18.6	65.6	53.2	.0664	1.877	3.697	8.150	0.0000	0.000		
29.210	415.5	292.0	18.9	66.0	45.6	.0566	1.611	3.173	6.994	0.0000	0.000		
29.302	416.8	292.3	19.2	66.5	34.8	.0430	1.229	2.419	5.333	0.0000	0.000		
29.028	412.9	292.8	19.6	67.3	26.7	.0333	.941	1.852	4.083	0.0000	0.000		
29.393	418.1	293.0	19.9	67.7	23.2	.0286	.818	1.611	3.551	0.0000	0.000		
29.119	414.2	293.4	20.3	68.5	15.1	.0189	.534	1.051	2.318	0.0000	0.000		
AVG. 29.183	AVG. 415.1	AVG. 292.3	AVG. 19.1	AVG. 65.4									
DEV. .134	DEV. 2.0	DEV. 0.8	DEV. 0.8	DEV. 1.4									

TABLE 2
 FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 1 PART 11 TEST DESCRIPTION

700 psia (nominal) Test Specimen
 Inlet Pressure Tare Test

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP. (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP. (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
0	57.3	74.0	.13	57.5	76.2	697.4	75.1	.0108
"	52.2	72.7	.21	58.8	75.9	697.4	74.3	.0180
"	51.3	71.7	.25	57.5	75.8	697.4	73.8	.0208
0	51.0	70.5	.41	57.5	75.4	689.4	73.0	.0255
"	49.1	69.5	.40	54.9	74.8	689.4	72.1	.0315
0	49.7	68.3	.50	54.9	74.1	685.4	71.2	.0402
0	47.2	66.8	.60	53.0	73.0	693.4	69.9	.0455
0	51.0	65.2	.72	55.6	72.9	697.4	68.1	.0575
"	52.2	64.1	.81	56.2	69.0	709.4	66.5	.0643
0	49.7	63.8	.90	53.7	68.4	691.4	66.1	.0697
0	49.7	63.6	.90	53.7	67.9	693.4	65.7	.0697
"	49.7	63.7	.80	54.3	67.9	709.4	65.8	.0614
0	49.7	64.1	.69	54.9	68.1	697.4	66.1	.0535
0	49.7	64.6	.60	54.9	68.6	697.4	66.6	.0472
0	51.3	65.1	.49	56.2	69.1	701.4	67.1	.0397
0	49.7	65.8	.40	55.6	69.7	705.4	67.8	.0311
0	51.3	66.5	.30	56.9	70.3	701.4	68.4	.0245
"	51.0	67.2	.25	57.5	70.9	709.4	69.1	.0204
0	51.0	68.0	.20	57.5	71.6	697.4	69.8	.0167
0	50.3	69.1	.12	57.5	72.4	701.4	70.8	.0102

ORIGINAL PAGE IS OF POOR QUALITY

TABLE 2
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 1	PART NO	TEST DESCRIPTION	700 psia (nominal) Test Specimen Inlet Pressure Tare Test				
TEST SPECIMEN INLET CONDITIONS							
PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
697.4	75.1	.0108				0	0
697.4	74.3	.0180				0	0
697.4	73.8	.0208				0	0
689.4	73.0	.0255				0	0
689.4	72.1	.0315				0	0
685.4	71.2	.0402				0	0
693.4	69.9	.0458				0	0
697.4	68.1	.0576		.001		0	-0.001
709.4	66.5	.0643		.001		0	0.001
693.4	66.1	.0697		.001		0	0.001
693.4	65.7	.0697		.001		0	0.001
709.4	65.8	.0614		.001		0	0.001
697.4	66.1	.0545				0	0
697.4	66.6	.0472				0	0
701.4	67.1	.0397				0	0
705.4	67.8	.0311				0	0
701.4	68.4	.0245				0	0
709.4	69.1	.0204				0	0
697.4	69.8	.0167				0	0
701.4	70.8	.0102				0	0

COMPUTED EQUATION:

$$\text{TARE DIFF. PRESS} = 0.000360 - 0.033161 (\text{ACFM}) + 0.633359 (\text{ACFM})^2 + 0 (\text{ACFM})^3$$

$$\text{SIGMA} = 0.000184$$

TABLE 2
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 1		PART 10		TEST DESCRIPTION		700 psia (nominal) Test Specimen Inlet Pressure Tare Test						
TEST SPECIMEN INLET CONDITIONS										NET DIFFERENTIAL PRESS		
PRESSURE		TEMPERATURE			FLOW RATE							
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN ₂ KG/HR	GN ₂ LBS/HR	KG/SQ CM DIFFERENTIAL	PSID	
49.033	697.4	297.1	23.9	75.1	14.4	.0108	.509	1.002	2.210	0	0	
49.033	697.4	296.7	23.5	74.3	24.0	.0180	.846	1.667	3.674	0	0	
49.033	697.4	296.4	23.2	73.8	27.8	.0208	.982	1.934	4.263	0	0	
48.469	689.4	295.9	22.8	73.0	33.7	.0255	1.190	2.343	5.166	0	0	
48.469	689.4	295.5	22.3	72.1	41.6	.0315	1.471	2.897	6.387	0	0	
48.188	685.4	294.9	21.8	71.2	53.0	.0402	1.871	3.685	8.123	0	0	
48.751	693.4	294.2	21.1	69.9	61.2	.0458	2.162	4.258	9.387	0	0	
49.033	697.4	293.2	20.0	68.1	77.6	.0576	2.741	5.397	11.899	0.0001	0.001	
49.877	709.4	292.3	19.2	66.5	88.4	.0643	3.122	6.148	13.554	0.0001	0.001	
48.751	693.4	292.1	18.9	66.1	93.8	.0697	3.312	6.521	14.377	0.0001	0.001	
48.751	693.4	291.9	18.7	65.7	93.8	.0697	3.314	6.526	14.388	0.0001	0.001	
49.877	709.4	291.9	18.8	65.8	84.5	.0614	2.985	5.878	12.959	0.0001	0.001	
49.033	697.4	292.1	18.9	66.1	73.7	.0545	2.604	5.127	11.302	0	0	
49.033	697.4	292.4	19.2	66.6	63.9	.0472	2.256	4.442	9.792	0	0	
49.314	701.4	292.7	19.5	67.1	53.9	.0397	1.903	3.747	8.261	0	0	
49.596	705.4	293.0	19.9	67.8	42.5	.0311	1.501	2.955	6.515	0	0	
49.314	701.4	293.4	20.2	68.4	33.2	.0245	1.174	2.311	5.095	0	0	
49.877	709.4	293.7	20.6	69.1	27.9	.0204	.984	1.938	4.272	0	0	
49.033	697.4	294.2	21.0	69.8	22.5	.0167	.794	1.564	3.448	0	0	
49.314	701.4	294.7	21.5	70.8	13.8	.0102	.486	.956	2.108	0	0	
AVG. 49.089	AVG. 698.2	AVG. 293.9	AVG. 20.7	AVG. 69.4								
DEV. .355	DEV. 5.0	DEV. 1.4	DEV. 1.4	DEV. 2.6								

TABLE 3
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 1 PART 1F TEST DESCRIPTION

1000 psia (nominal) Test Specimen
Inlet Pressure Tare Test

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE, (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.12	51.2	67.9	.12	57.4	69.6	982.8	68.8	.0072
.21	51.2	66.1	.21	57.4	69.9	987.7	68.0	.0121
.26	51.2	64.5	.26	57.4	70.2	988.8	67.3	.0151
.31	50.5	63.2	.31	57.4	70.2	992.8	66.7	.0179
.39	51.2	61.3	.39	57.4	70.3	1000.8	65.8	.0220
.49	50.5	60.0	.49	56.2	70.2	980.7	65.1	.0281
.59	49.9	59.0	.59	54.9	70.2	988.8	64.6	.0329
.70	50.5	58.1	.70	55.5	70.2	972.7	64.1	.0400
.81	48.6	57.6	.81	52.9	70.0	984.8	63.8	.0433
.93	51.2	56.3	.93	54.9	69.9	1000.8	63.1	.0510
.93	52.5	55.8	.93	54.2	69.9	992.8	62.9	.0506
.80	47.4	56.7	.80	51.0	69.9	996.8	63.1	.0410
.71	49.9	56.5	.71	54.9	69.9	1000.8	63.2	.0388
.59	49.9	57.7	.59	54.9	70.0	972.7	63.7	.0334
.49	51.2	58.0	.49	57.4	70.0	992.8	64.0	.0286
.40	52.5	59.0	.40	57.4	70.0	988.8	64.5	.0230
.31	51.2	60.2	.31	57.4	70.1	984.8	65.2	.0178
.25	48.6	61.7	.25	54.9	70.2	988.7	66.0	.0142
.20	50.5	62.7	.20	57.4	70.3	1016.8	66.5	.0111
.12	49.9	64.7	.12	56.2	70.4	988.8	67.6	.0071

ORIGINAL PAGE IS
 OF POOR QUALITY

TABLE 3
 FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 1	PART 1F	TEST DESCRIPTION	1000 psia (nominal) Test Specimen Inlet Pressure Tare Test				
TEST SPECIMEN INLET CONDITIONS *****							
PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
984.0	68.8	.0072		-0.000		0	0.000
987.7	68.0	.0121		-0.000		0	0.000
988.8	67.7	.0151		-0.000		0	0.000
992.8	66.7	.0179		-0.000		0	0.000
1021.7	65.8	.0220		.001		0	.001
989.7	65.1	.0281		.001		0	.001
988.8	64.6	.0329		.001		0	.001
972.7	64.1	.0400		.001		0	.001
984.0	63.8	.0433		.001		0	.001
1000.8	63.1	.0510		.001		0	.001
992.8	62.9	.0506		.001		0	.001
996.8	63.1	.0410		.001		0	.001
1000.8	63.2	.0388		.001		0	.001
972.7	63.7	.0374		-0.000		0	0.000
992.8	64.7	.0286		-0.000		0	0.000
988.8	64.5	.0230		-0.000		0	0.000
984.0	65.2	.0178		-0.000		0	0.000
968.7	66.0	.0142		-0.000		0	0.000
1016.8	66.5	.0111		-0.000		0	0.000
988.8	67.6	.0071		-0.000		0	0.000

COMPUTED EQUATION:

$$\text{TARE DIFF. PRESS} = -0.000164 + 0.012693 \cdot (\text{ACFM}) + 0.248070 \cdot (\text{ACFM})^{**2} +$$

$$0 \cdot (\text{ACFM})^{**3}$$

$$\text{SIGMA} = 0.00033$$

TABLE J
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 1		PART ID			TEST DESCRIPTION		1000 psia (nominal) Test Specimen Inlet Pressure Tare Test						
TEST SPECIMEN INLET CONDITIONS													
PRESSURE		TEMPERATURE			FLOW RATE							NET DIFFERENTIAL PRESS	
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN ₂ KG/HR	GN ₂ LBS/HR	KG/SQ CM DIFFERENTIAL	PSID		
69.235	984.8	293.6	21.4	68.8	13.8	.0072	.487	.958	2.113	0.0000	0.000		
68.954	984.7	293.2	20.0	68.0	22.9	.0121	.810	1.594	3.514	0.0000	0.000		
69.517	988.8	292.8	19.6	67.3	28.9	.0151	1.020	2.008	4.426	0.0000	0.000		
69.799	992.0	292.5	19.3	66.7	34.4	.0179	1.216	2.394	5.279	0.0000	0.000		
71.771	1020.4	291.9	18.8	65.8	43.5	.0220	1.537	3.025	6.670	0.0001	.001		
68.954	984.7	291.6	18.4	65.1	53.6	.0281	1.894	3.729	8.222	0.0001	.001		
69.517	988.8	291.3	18.1	64.6	63.3	.0329	2.234	4.399	9.698	0.0001	.001		
68.391	972.7	291.1	17.8	64.1	75.8	.0400	2.675	5.267	11.613	0.0001	.001		
69.235	984.8	291.8	17.7	63.8	83.1	.0433	2.935	5.778	12.739	0.0001	.001		
70.362	1000.6	290.4	17.3	63.1	99.5	.0510	3.515	6.921	15.258	0.0001	.001		
69.799	992.8	291.3	17.1	62.9	98.0	.0506	3.462	6.816	15.027	0.0001	.001		
70.080	996.8	291.4	17.3	63.1	79.8	.0410	2.818	5.549	12.534	0.0001	.001		
70.362	1000.8	290.5	17.4	63.2	75.8	.0388	2.676	5.269	11.616	0.0001	.001		
68.391	972.7	291.8	17.6	63.7	63.4	.0334	2.238	4.407	9.716	0.0000	0.000		
69.799	992.8	290.9	17.8	64.0	55.4	.0286	1.956	3.851	8.489	0.0000	0.000		
69.517	988.8	291.2	18.1	64.5	44.2	.0230	1.561	3.073	6.775	0.0000	0.000		
69.235	984.8	291.6	18.4	65.2	34.2	.0178	1.206	2.375	5.236	0.0000	0.000		
68.108	966.7	292.0	18.9	66.0	26.7	.0142	.944	1.859	4.199	0.0000	0.000		
71.489	1016.8	292.3	19.2	66.5	21.8	.0111	.771	1.518	3.348	0.0000	0.000		
69.517	988.8	292.9	19.8	67.6	13.5	.0071	.477	.939	2.070	0.0000	0.000		
Avg. 69.601	Avg. 990.0	Avg. 291.6	Avg. 18.5	Avg. 65.2									
Dev. 0.665	Dev. 9.4	Dev. 0.8	Dev. 0.8	Dev. 1.5									

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 4
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 1
DATE: 4/23/76

TEST NUMBER F PART IF TEST DESCRIPTION 2900 psia (nominal) Test Specimen
Inlet Pressure Tare Test

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE			FLOWMETER TWO			TEST SPECIMEN INLET CONDITIONS		
FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
0	54.2	78.7	.14	54.0	83.0	2868.0	80.9	.0026
0	45.7	77.3	.21	45.2	82.8	2791.2	80.0	.0034
0	49.5	74.7	.26	45.0	81.9	2859.9	78.3	.0041
0	44.6	71.0	.30	43.9	82.8	2859.9	75.9	.0047
0	44.6	67.5	.40	43.7	79.2	2855.9	73.2	.0061
0	44.2	61.8	.50	43.3	76.4	2851.8	69.1	.0076
0	43.4	57.9	.60	42.2	73.8	2847.8	65.8	.0089
0	42.0	52.0	.70	38.6	68.7	2698.3	60.3	.0100
0	42.0	63.2	.73	47.5	73.7	2868.1	68.5	.0022
0	45.5	62.8	.20	45.2	72.4	2868.0	68.1	.0032
0	45.3	61.9	.26	44.7	72.9	2863.9	67.4	.0040
0	46.6	61.9	.31	46.0	72.3	2863.9	66.6	.0049
0	42.8	59.1	.37	43.1	71.4	2859.9	65.2	.0055
0	45.7	56.9	.45	44.8	70.0	2859.9	63.4	.0071
0	42.4	52.5	.55	42.0	67.6	2855.9	60.6	.0081
0	44.9	52.3	.60	43.5	64.8	2855.9	57.5	.0091
0	44.4	47.9	.65	42.9	62.1	2851.8	55.0	.0099
0	42.4	46.7	.70	42.0	60.4	2847.8	53.6	.0103
0	42.1	45.7	.80	40.5	58.9	2843.7	52.3	.0114
0	41.9	44.5	.91	39.5	57.1	2863.9	50.8	.0125

TABLE 4
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 2
DATE: 4/23/76

TEST NUMBER F	PART IF	TEST DESCRIPTION	2900 psia (nominal) Test Specimen Inlet Pressure Tare Test				
TEST SPECIMEN INLET CONDITIONS							
*****	*****	*****	*****	*****	*****	*****	
PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
2868.0	80.9	.0026	-0.001	-0.000	-0.001	0	-0.001
2791.2	80.0	.0034	-0.001	-0.000	-0.001	0	-0.001
2859.2	78.3	.0041	.000	.001	.001	0	.001
2859.2	75.9	.0047	.000	.001	.001	0	.001
2855.9	73.2	.0061	.000	.001	.001	0	.001
2851.8	69.1	.0076	.000	.001	.001	0	.001
2847.8	65.8	.0089	.000	-0.000	.000	0	.000
2698.3	60.3	.0100	.000	.001	.001	0	.001
2868.0	68.5	.0022	.000	-0.000	.000	0	.000
2868.0	68.1	.0032	.000	-0.000	.000	0	.000
2863.2	67.4	.0040	.000	-0.000	.000	0	.000
2863.2	66.6	.0049	.000	-0.000	.000	0	.000
2859.2	65.2	.0056	.000	-0.000	.000	0	.000
2859.2	63.4	.0071	.000	-0.000	.000	0	.000
2855.9	60.6	.0081	-0.001	-0.000	-0.001	0	-0.001
2855.9	57.5	.0091	-0.001	-0.001	-0.001	0	-0.001
2851.8	55.0	.0099	-0.001	-0.001	-0.001	0	-0.001
2847.8	53.6	.0103	-0.001	-0.001	-0.001	0	-0.001
2843.7	52.3	.0114	-0.001	-0.001	-0.001	0	-0.001
2863.2	50.8	.0125	-0.001	-0.001	-0.001	0	-0.001

COMPUTED EQUATION:

$$\text{TARE DIFF. PRESS} = -0.001246 Q + 0.488453 Q^2 - 40.072254 Q^3$$

SIGMA = 0.000700

TABLE 4
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 3
DATE: 4/23/76

TEST NUMBER F		PART #		TEST DESCRIPTION		2900 psia (nominal) Test Specimen Inlet Pressure Tare Test		TEST SPECIMEN INLET CONDITIONS		NET DIFFERENTIAL PRESS	
PRESSURE		TEMPERATURE		FLOW RATE							
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	SCFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID
201.639	2965.1	300.3	27.1	80.9	13.9	.0026	.491	.467	2.133	-0.0000	-0.001
196.242	2791.2	299.9	26.7	80.0	17.9	.0034	.633	1.246	2.747	-0.0000	-0.001
201.071	2959.9	298.9	25.7	78.3	22.0	.0041	.777	1.530	3.372	.0000	.001
201.071	2959.9	297.6	24.4	75.9	25.4	.0047	.897	1.766	3.893	.0000	.001
200.787	2955.9	296.1	22.9	73.2	33.5	.0061	1.182	2.327	5.130	.0000	.001
200.503	2951.8	293.8	20.6	69.1	42.0	.0076	1.485	2.923	6.445	.0000	.001
200.219	2847.8	292.0	18.8	65.8	49.2	.0089	1.737	3.421	7.541	.0000	.000
189.706	2698.3	288.9	15.7	60.3	52.7	.0100	1.861	3.663	8.077	.0000	.001
201.639	2968.0	293.4	20.3	68.5	12.2	.0022	.431	.842	1.871	.0000	.000
201.639	2968.0	293.2	20.0	68.1	17.7	.0032	.626	1.232	2.717	.0000	.000
201.355	2963.9	292.8	19.7	67.4	22.3	.0040	.786	1.548	3.413	.0000	.000
201.355	2963.9	292.4	19.2	66.6	27.2	.0049	.962	1.894	4.175	.0000	.000
201.071	2959.9	291.6	18.5	65.2	31.1	.0056	1.097	2.161	4.763	.0000	.000
201.071	2959.9	290.6	17.5	63.4	39.4	.0071	1.391	2.732	6.038	.0000	.000
200.787	2955.9	289.0	15.9	60.6	45.2	.0081	1.596	3.144	6.930	-0.0000	-0.001
200.787	2955.9	287.4	14.2	57.5	51.4	.0091	1.815	3.574	7.880	-0.0001	-0.001
200.503	2951.8	285.9	12.8	55.0	55.7	.0099	1.968	3.875	8.542	-0.0001	-0.001
200.219	2847.8	285.1	12.0	53.6	58.3	.0103	2.057	4.051	8.930	-0.0001	-0.001
199.935	2843.7	284.4	11.3	52.3	64.9	.0114	2.291	4.512	9.947	-0.0001	-0.001
201.355	2963.9	283.6	10.5	50.8	71.8	.0125	2.535	4.991	11.004	-0.0001	-0.001
****	****	****	****	****							
200.148	2846.8	291.8	18.7	65.6							
1.456	20.7	4.0	4.0	7.2	DEVIATIONS						

TABLE 5
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 5 PART 22C TEST DESCRIPTION

CLEAN CONDITION - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. TEST SPECIMEN
(S/N 022) INLET PRESSURE = 415 PSIA NOMINAL.

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.70	50.1	81.3	.71	48.7	82.8	420.0	82.0	.0829
.60	50.9	81.2	.60	49.9	82.7	419.4	81.9	.0721
.50	50.7	81.1	.50	49.9	82.5	419.4	81.8	.0603
.41	50.5	80.9	.40	49.9	82.5	418.7	81.7	.0486
.31	50.3	80.9	.30	50.1	82.5	418.7	81.7	.0369
.26	50.3	81.1	.25	49.9	82.6	418.7	81.8	.0306
.21	50.1	81.1	.20	49.9	82.6	418.7	81.8	.0247
.14	50.3	81.3	.13	50.1	82.8	418.7	82.0	.0164
.15	49.5	81.5	.14	49.5	82.8	418.7	82.2	.0169
.22	50.5	81.5	.21	50.2	82.8	418.7	82.2	.0262
.26	50.3	81.3	.25	50.1	82.8	418.7	82.0	.0311
.32	50.3	81.3	.31	49.9	82.8	418.1	82.0	.0374
.41	49.7	81.1	.40	49.3	82.7	418.1	81.9	.0482
.51	50.1	80.9	.51	49.3	82.5	417.4	81.7	.0604
.59	49.9	80.9	.60	48.9	82.4	416.8	81.6	.0704
.69	50.3	81.0	.71	48.9	82.3	416.1	81.6	.0829

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 5
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 5

PART 22C

TEST DESCRIPTION

CLEAN CONDITION - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. TEST SPECIMEN
(S/N 022) INLET PRESSURE = 415 PSIA NOMINAL.

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
420.0	82.0	.0829	295.292	295.292	295.292	.001	295.291
419.4	81.9	.0721	214.385	214.385	214.385	.001	214.384
419.4	81.8	.0603	159.709	159.709	159.709	.000	159.708
418.7	81.7	.0486	115.778	115.778	115.778	.000	115.777
418.7	81.7	.0369	80.239	80.697	80.468	.000	80.467
418.7	81.8	.0306	63.281	63.631	63.456	.000	63.455
418.7	81.8	.0247	48.245	48.776	48.511	.000	48.510
418.7	82.0	.0164	30.476	30.591	30.533	-0.000	30.533
418.7	82.2	.0169	31.578	31.741	31.659	.000	31.658
418.7	82.2	.0262	52.254	52.885	52.569	.000	52.569
418.7	82.0	.0311	64.658	65.211	64.934	.000	64.933
418.1	82.0	.0374	81.476	81.961	81.719	.000	81.718
418.1	81.9	.0482	115.778	115.778	115.778	.000	115.777
417.4	81.7	.0604	161.605	161.605	161.605	.000	161.604
416.8	81.6	.0704	210.276	210.276	210.276	.001	210.275
416.1	81.6	.0829	297.505	297.505	297.505	.001	297.504

TARE DIFF. PRESS = $-3.40000E-05 + -4.44000E-04$ (ACFM) + $1.50933E-01$ (ACFM)**2 + 0 (ACFM)**3

TABLE 5
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 5 PART 22C TEST DESCRIPTION CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE. TEST SPECIMEN (S/N 022) INLET PRESSURE = 415 PSIA NOMINAL.

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESS

PRESSURE		TEMPERATURE			FLOW RATE					NET DIFFERENTIAL PRESS		
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	SCFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID	
29.530	420.0	301.0	27.8	82.0	65.6	.0829	2.317	4.563	10.059	20.7611	295.291	
29.484	419.4	300.9	27.7	81.9	56.7	.0721	2.010	3.958	8.727	15.0727	214.384	
29.484	419.4	300.8	27.7	81.8	47.3	.0643	1.684	3.316	7.311	11.2286	159.708	
29.438	418.7	300.8	27.6	81.7	37.8	.0486	1.353	2.664	5.873	8.1400	115.777	
29.438	418.7	300.8	27.6	81.7	28.7	.0369	1.028	2.123	4.461	5.6574	80.467	
29.438	418.7	300.8	27.7	81.8	23.6	.0300	.854	1.981	3.705	4.4613	63.455	
29.438	418.7	300.8	27.7	81.8	19.1	.0247	.689	1.356	2.989	3.4106	48.510	
29.438	418.7	300.9	27.8	82.0	12.4	.0164	.457	.900	1.985	2.1467	30.533	
29.438	418.7	301.0	27.9	82.2	12.9	.0169	.471	.927	2.044	2.2258	31.658	
29.430	418.7	301.0	27.9	82.2	20.2	.0272	.730	1.438	3.170	3.6959	52.569	
29.438	418.7	301.0	27.8	82.0	24.0	.0311	.866	1.705	3.760	4.5653	64.933	
29.393	418.1	300.9	27.8	82.0	28.9	.0374	1.039	2.146	4.511	5.7453	81.718	
29.393	418.1	300.9	27.7	81.9	37.5	.0492	1.340	2.639	5.818	8.1400	115.777	
29.347	417.4	300.8	27.6	81.7	47.1	.0604	1.677	3.301	7.278	11.3619	161.604	
29.302	416.8	300.7	27.6	81.6	55.1	.0704	1.954	3.847	8.481	14.7838	210.275	
29.256	416.1	300.7	27.6	81.6	65.1	.0829	2.296	4.522	9.969	20.9166	297.504	
*****	*****	*****	*****	*****								
29.419	418.4	300.9	27.7	81.9								
.050	.1	.1	.1	.1	DEVIATIONS							

TABLE 6
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 1
DATE: 8-25-76

TEST NUMBER 5 PART 225 TEST DESCRIPTION

CLEAN CONDITION - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. TEST SPECIMEN
(S/N 022) INLET PRESSURE = 700 PSIA NOMINAL

FLOW TEST CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.87	49.7	83.1	.94	47.6	85.5	719.6	84.2	.0597
.79	49.5	81.3	.93	47.9	85.1	719.6	83.6	.0540
.69	50.2	83.9	.71	48.9	84.7	719.6	83.3	.0481
.61	50.3	81.7	.61	48.9	84.5	719.6	83.1	.0417
.50	49.7	81.7	.5	48.9	84.5	719.6	83.1	.0343
.41	50.1	81.1	.40	49.5	84.7	719.6	83.4	.0282
.32	49.8	82.3	.31	49.3	84.9	719.6	83.6	.0220
.27	49.5	81.7	.26	49.3	85.1	719.6	83.9	.0181
.21	49.7	83.1	.21	49.5	85.4	719.6	84.3	.0144
.14	49.7	83.7	.13	49.5	85.6	719.6	84.7	.0095
.14	50.2	84.4	.13	51.1	86.1	719.6	85.2	.0095
.24	50.1	84.2	.23	49.9	86.	719.6	85.1	.0163
.27	50.1	84.1	.25	49.9	86.	719.6	85.0	.0161
.31	50.2	83.8	.31	49.9	86.	719.6	84.9	.0214
.42	50.2	83.3	.41	49.7	85.8	719.6	84.5	.0287
.51	50.1	82.9	.51	49.3	85.6	719.6	84.2	.0350
.59	50.1	82.4	.59	49.1	85.3	715.7	83.8	.0409
.69	49.9	82.	.71	48.5	85.1	715.7	83.5	.0481
.77	50.2	83.4	.91	48.5	84.4	715.7	82.9	.0544
.84	50.2	83.2	.91	48.3	84.1	715.7	82.6	.0602

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 6
~~FLOW RATE VERSUS DIFFERENTIAL PRESSURE~~

TEST NUMBER 5

PART 228

TEST DESCRIPTION

CLEAN CONDITION - FLOW RATE VERSUS
 DIFFERENTIAL PRESSURE. TEST SPECIMEN
 (S/N 022) INLET PRESSURE = 700 PSIA NOMINAL.

TEST SPECIMEN INLET CONDITIONS

AVG PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
719.6	84.2	.7597	152.565	152.565	152.565	0.000	152.565
719.6	83.6	.7540	133.310	133.310	133.310	0.000	133.310
719.6	83.3	.7481	114.371	114.371	114.371	0.000	114.371
719.6	83.1	.7417	94.404	95.116	94.760	0.001	94.760
719.6	83.1	.7343	73.737	74.283	74.010	0.001	74.010
719.6	83.4	.7282	57.852	58.511	58.177	0.001	58.177
719.6	83.6	.7220	43.648	43.819	43.734	0.001	43.734
719.6	83.9	.7181	34.667	34.726	34.697	0.001	34.697
719.6	84.3	.7144	26.498	26.633	26.566	0.001	26.566
719.6	84.7	.7095	16.591	16.562	16.576	0.001	16.576
719.6	85.2	.7095	16.764	16.915	16.834	0.001	16.834
719.6	85.1	.7063	30.496	30.706	30.601	0.001	30.601
719.6	85.0	.7081	34.494	34.669	34.581	0.001	34.581
719.6	84.9	.7214	42.884	42.321	42.203	0.001	42.203
719.6	84.5	.7287	59.231	59.763	59.497	0.001	59.497
719.6	84.2	.7350	75.853	76.493	76.173	0.001	76.173
715.7	83.8	.7409	91.618	92.591	92.105	0.001	92.105
715.7	83.5	.7481	114.055	114.055	114.055	0.000	114.055
715.7	82.9	.7544	135.520	135.520	135.520	0.000	135.520
715.7	82.6	.7602	157.615	157.615	157.615	0.000	157.615

TARE DIFF. PRESS = 3.60000E-04 + 3.31610E-02 (ACFM) + 6.33359E-01 (ACFM)**2 + 0 (ACFM)**3

TABLE 6
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 3
DATE: 8-25-76

TEST NUMBER 5 PART 22B TEST DESCRIPTION CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE. TEST SPECIMEN (S7N U22) INLET PRESSURE = 700 PSIA NOMINAL.

TEST SPECIMEN INLET CONDITIONS NET DIFFERENTIAL PRESSURE

PRESSURE		TEMPERATURE			FLOW RATE								
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/MIN	ACFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID		
50.594	719.6	302.2	29.0	84.2	80.4	.0597	2.845	5.601	12.349	10.7264	152.565		
50.594	719.6	301.8	28.7	83.6	73.1	.0540	2.579	5.079	11.197	9.3726	133.310		
50.594	719.6	301.7	28.5	83.3	64.8	.0481	2.298	4.524	9.974	8.0411	114.371		
50.594	719.6	301.6	28.4	83.1	55.9	.0417	1.992	3.922	8.647	6.6623	94.760		
50.594	719.6	301.6	28.4	83.1	45.7	.0343	1.638	3.224	7.108	5.2034	74.010		
50.594	719.6	301.7	28.5	83.4	37.3	.0282	1.345	2.649	5.840	4.0902	58.177		
50.594	719.6	301.8	28.7	83.6	29.1	.0220	1.050	2.067	4.558	3.0748	48.734		
50.594	719.6	302.0	28.8	83.9	23.8	.0181	.863	1.699	3.745	2.4394	34.697		
50.594	719.6	302.2	29.0	84.3	19.0	.0144	.688	1.354	2.986	1.8678	26.566		
50.594	719.6	302.4	29.3	84.7	12.3	.0095	.452	.890	1.963	1.1654	16.576		
50.594	719.6	302.7	29.6	85.2	12.3	.0095	.454	.894	1.971	1.1836	16.834		
50.594	719.6	302.7	29.5	85.1	21.5	.0163	.776	1.528	3.368	2.1515	30.601		
50.594	719.6	302.6	29.4	85.0	23.7	.0181	.860	1.693	3.733	2.4313	34.581		
50.594	719.6	302.5	29.4	84.9	28.2	.0214	1.018	2.005	4.421	2.9671	42.203		
50.594	719.6	302.4	29.2	84.5	38.0	.0287	1.367	2.692	5.935	4.1831	59.497		
50.594	719.6	302.2	29.0	84.2	46.7	.0350	1.669	3.287	7.247	5.3555	76.173		
50.318	715.7	302.0	28.8	83.8	54.5	.0409	1.942	3.824	8.430	6.4756	92.105		
50.318	715.7	301.8	28.6	83.5	64.3	.0481	2.282	4.493	9.906	8.0109	114.056		
50.318	715.7	301.5	28.3	82.9	73.6	.0544	2.587	5.094	11.230	9.5280	135.520		
50.318	715.7	301.3	28.1	82.6	82.6	.0602	2.865	5.641	12.436	11.0815	157.615		
50.539	718.8	302.0	28.9	84.0									
.000	1.3	.4	.4	.7	DEVIATIONS								

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 7
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 1
DATE: 8-25-76

TEST NUMBER 5 PART 22A TEST DESCRIPTION

CLEAN CONDITION - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. TEST SPECIMEN
(S/N 022) INLET PRESSURE - 1000 PSIA
NOMINAL. TEST SPECIMEN INLET CONDITIONS

FLOWMETER CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.88	50.2	77.2	.92	48.3	82.2	1011.9	79.7	.0437
.78	50.4	76.5	.81	48.7	81.6	1011.9	79.0	.0390
.69	50.4	76.4	.71	49.1	81.3	1011.9	78.8	.0344
.60	49.7	76.4	.61	48.7	81.2	1015.9	78.8	.0293
.50	49.9	76.6	.50	49.1	81.4	1011.9	79.0	.0246
.41	49.9	77.3	.41	49.3	81.6	1015.9	79.5	.0200
.31	49.7	77.8	.30	49.3	81.9	1015.9	79.9	.0149
.26	50.1	78.3	.25	49.9	82.3	1015.9	80.3	.0126
.22	49.9	78.9	.21	49.7	82.5	1015.9	80.7	.0104
.16	50.1	79.6	.15	49.9	82.9	1015.9	81.2	.0074
.16	50.4	81.0	.15	50.2	83.6	1015.9	82.3	.0075
.23	49.5	81.9	.22	49.3	83.6	1015.9	82.3	.0108
.27	49.7	81.8	.26	49.3	83.6	1015.9	82.2	.0130
.32	49.7	81.6	.31	49.3	83.6	1015.9	82.1	.0151
.41	49.9	81.1	.41	49.3	83.5	1015.9	81.8	.0200
.50	49.9	79.3	.50	49.1	83.2	1015.9	81.2	.0245
.60	50.4	78.5	.61	49.5	82.8	1011.9	80.6	.0298
.69	50.4	77.9	.71	49.1	82.4	1011.9	80.2	.0343
.78	50.4	77.1	.80	48.9	81.8	1011.9	79.4	.0387
.87	50.2	76.4	.91	48.3	81.1	1011.9	78.7	.0434

TABLE 7
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 2
DATE: 8-25-76

TEST NUMBER 5

PART 22A

TEST DESCRIPTION

CLEAN CONDITION - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE, TEST SPECIMEN
(S/N 022) INLET PRESSURE = 1000 PSIA
NOMINAL.

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
1011.9	79.7	.437	111.320	111.320	111.320	-0.000	111.320
1011.9	79.0	.0390	96.484	96.484	96.484	-0.000	96.484
1011.9	78.8	.344	82.095	82.595	82.345	-0.000	82.345
1015.9	78.8	.293	67.535	68.176	67.805	-0.000	67.805
1011.9	79.0	.246	54.132	54.53	54.317	-0.000	54.318
1015.9	79.5	.0700	42.760	42.917	42.838	-0.000	42.839
1015.9	79.9	.0149	30.245	30.381	30.313	-0.000	30.313
1015.9	80.3	.0126	24.914	24.876	24.895	-0.000	24.896
1015.9	80.7	.0104	20.047	20.011	20.029	-0.000	20.029
1015.9	81.2	.0074	13.558	13.611	13.585	-0.000	13.585
1015.9	82.3	.0075	13.732	13.840	13.786	-0.000	13.786
1015.9	82.3	.0138	20.808	20.869	20.835	-0.000	20.835
1015.9	82.2	.0130	25.899	25.965	25.932	-0.000	25.932
1015.9	82.1	.0151	30.824	31.012	30.918	-0.000	30.918
1015.9	81.8	.0200	42.586	42.744	42.665	-0.000	42.665
1015.9	81.2	.0245	54.258	54.818	54.538	-0.000	54.538
1011.9	80.6	.0298	68.410	69.022	68.716	-0.000	68.716
1011.9	80.2	.0343	81.847	82.280	82.064	-0.000	82.064
1011.9	79.4	.387	95.853	95.853	95.853	-0.000	95.853
1011.9	78.7	.434	110.688	110.688	110.688	-0.000	110.688

TARE DIFF. PRESS = $-1.64000E-04 + -1.26930E-02$ (ACFM) + $2.48070E-01$ (ACFM)**2. +

0.1 (ACFM)**3

TABLE 7
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 3
DATE: 8-25-76

TEST UMPREP 5 PART 22A TEST DESCRIPTION

CLEAN CONDITION - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. TEST SPECIMEN
(S/N 022) INLET PRESSURE = 1000 PSIA
NOMINAL. NET DIFFERENTIAL PRESS.

TEST SPECIMEN INLET CONDITIONS

PRESSURE		TEMPERATURE			FLOW RATE						
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITRPS/ MIN	ICFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ.CM DIFFERENTIAL	PSID
71.144	1011.9	299.7	26.5	79.7	83.9	.1437	2.951	5.810	12.809	7.8266	111.320
71.144	1011.9	299.3	26.1	79.0	74.9	.1390	2.641	5.201	11.466	6.7835	96.484
71.144	1011.9	299.7	26.0	78.8	65.9	.1344	2.332	4.591	10.121	5.7894	82.345
71.423	1015.9	299.2	26.0	78.8	56.1	.1293	1.994	3.926	8.655	4.7672	67.805
71.144	1011.9	299.3	26.1	79.0	46.8	.1246	1.668	3.284	7.241	3.8189	54.318
71.423	1015.9	299.5	26.4	79.5	37.9	.1200	1.361	2.680	5.909	3.0119	42.839
71.423	1015.9	299.8	26.6	79.9	28.1	.1149	1.013	1.995	4.399	2.1312	30.313
71.423	1015.9	300.0	26.8	80.3	23.6	.1126	.856	1.686	3.716	1.7503	24.896
71.423	1015.9	300.2	27.0	80.7	19.5	.1104	.706	1.391	3.066	1.4082	20.029
71.423	1015.9	300.5	27.4	81.2	13.7	.1074	.501	.987	2.176	.9551	13.585
71.423	1015.9	301.1	27.9	82.3	13.7	.1075	.504	.993	2.189	.9693	13.786
71.423	1015.9	301.1	27.9	82.3	20.1	.1108	.727	1.431	3.154	1.4648	20.835
71.423	1015.9	301.0	27.9	82.2	24.4	.1130	.881	1.735	3.825	1.8232	25.932
71.423	1015.9	301.8	27.8	82.1	24.4	.1151	1.023	2.014	4.441	2.1738	30.918
71.423	1015.9	300.8	27.7	81.8	37.6	.1200	1.350	2.658	5.860	2.9997	42.665
71.423	1015.9	300.5	27.4	81.2	46.6	.1245	1.661	3.271	7.210	3.8344	54.538
71.144	1011.9	300.2	27.0	80.6	56.6	.1298	2.009	3.956	8.721	4.8312	68.716
71.144	1011.9	299.9	26.8	80.2	65.4	.1343	2.317	4.562	10.058	5.7697	82.064
71.144	1011.9	299.5	26.3	79.4	74.3	.1387	2.619	5.156	11.368	6.7391	95.853
71.144	1011.9	299.1	26.0	78.7	83.4	.1434	2.936	5.781	12.746	7.7822	110.689
*****	*****	*****	*****	*****							
71.311	1014.3	300.0	26.9	80.4							
.134	1.9	.6	.6	1.1	DEVIATIONS						

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 8
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE DATA ACQUIRED AFTER 10 HIGH PRESSURE (10,000 PSIA NOMINAL) CN2 IMPACT CYCLES. FLOW IN FORWARD DIRECTION. TEST SPECIMEN (S/N 023) INLET PRESSURE = 415 PSIA NOMINAL. DATA OBTAINED AFTER PROOF TEST.

TEST NUMBER 5 PART 23C TEST DESCRIPTION

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.79	50.1	81.7	.81	48.3	82.7	413.7	82.2	.0951
.69	49.9	81.7	.71	48.5	82.8	413.0	82.2	.0834
.61	49.9	81.6	.61	48.7	82.9	413.0	82.2	.0727
.51	49.9	81.7	.51	49.1	83.0	412.4	82.3	.0611
.42	49.7	81.7	.41	49.3	83.2	412.4	82.5	.0495
.32	50.2	82.0	.31	49.9	83.4	412.4	82.7	.0382
.27	50.4	82.1	.26	50.0	83.6	412.4	82.8	.0319
.22	50.1	82.3	.21	49.9	83.7	412.4	83.0	.0260
.16	50.4	82.7	.14	50.2	84.0	412.4	83.4	.0183
.16	49.9	82.9	.14	49.9	84.2	412.4	83.6	.0181
.23	50.2	82.7	.22	49.9	84.1	412.4	83.4	.0270
.27	49.9	82.6	.26	49.5	84.1	412.4	83.3	.0318
.32	50.2	82.3	.31	49.9	84.0	412.4	83.2	.0382
.42	50.2	82.0	.41	49.7	83.9	411.7	82.9	.0501
.51	50.1	81.7	.51	49.3	83.6	411.1	82.6	.0613
.60	50.1	81.5	.60	49.1	83.4	410.4	82.4	.0728
.69	49.9	81.4	.71	48.5	83.1	410.4	82.2	.0840
.77	50.4	82.0	.79	48.9	82.9	409.1	82.4	.0944

TABLE 8
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE DATA ACQUIRED AFTER 10 HIGH PRESSURE (10,000 PSIA NOMINAL) GW IMPACT CYCLES. FLOW IN FORWARD DIRECTION. TEST SPECIMEN (S/N 023) INLET PRESSURE = 415 PSIA NOMINAL. DATA OBTAINED AFTER PROOF TEST.

TEST NUMBER 5 PART 23C TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	GARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
413.7	82.2	.0951	303.085	303.085	303.085	.001	303.084
413.0	82.2	.0834	221.545	221.546	221.546	.001	221.545
413.0	82.2	.0727	174.456	174.456	174.456	.001	174.455
412.4	82.3	.0611	133.370	133.370	133.370	.001	133.369
412.4	82.5	.0495	98.922	98.922	98.922	.000	98.920
412.4	82.7	.0382	69.577	70.162	69.869	.000	69.868
412.4	82.8	.0319	55.805	56.572	56.189	.000	56.187
412.4	83.0	.0260	44.112	44.355	44.234	.000	44.232
412.4	83.4	.0183	29.511	29.614	29.563	.000	29.561
412.4	83.6	.0181	29.105	29.327	29.216	.000	29.215
412.4	83.4	.0270	46.545	46.458	46.502	.000	46.501
412.4	83.3	.0318	55.680	56.256	55.968	.000	55.967
412.4	83.2	.0382	70.202	70.794	70.498	.000	70.496
411.7	82.9	.0501	100.818	100.818	100.818	.000	100.816
411.1	82.6	.0613	134.318	134.318	134.318	.001	134.317
410.4	82.4	.0728	175.720	175.720	175.720	.001	175.719
410.4	82.2	.0840	226.919	226.919	226.919	.001	226.918
409.1	82.4	.0944	298.977	298.977	298.977	.001	298.976

GARE DIFF. PRESS = -3.40000E-05 + 4.44000E-04 (ACFM) + 1.50933E-01 (ACFM)**2 + 0 (ACFM)**3.

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 8
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE DATA ACQUIRED AFTER 10 HIGH PRESSURE (10,000 PSIA NOMINAL) GN₂ IMPACT CYCLES. FLOW IN FORWARD DIRECTION. TEST SPECIMEN (S/N 023) INLET PRESSURE = 415 PSIA NOMINAL. DATA OBTAINED AFTER PROOF TEST.

TEST NUMBER 5 PART 23C TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESSURE

PRESSURE		TEMPERATURE			FLOW RATE:							
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN ₂ KG/HR	GN ₂ LBS/HR	KG/SQ CM DIFFERENTIAL	PSID	
29.083	413.7	301.1	27.9	82.2	74.1	.0951	2.616	5.151	11.355	21.3089	303.084	
29.037	413.0	301.1	27.9	82.2	64.9	.0834	2.292	4.512	9.948	15.5702	221.545	
29.037	413.0	301.1	27.9	82.2	56.6	.0727	1.997	3.933	8.670	12.2654	174.455	
28.991	412.4	301.1	28.0	82.3	47.4	.0611	1.675	3.299	7.273	9.3768	133.380	
28.991	412.4	301.2	28.0	82.5	38.4	.0495	1.357	2.673	5.893	6.9548	99.928	
28.991	412.4	301.3	28.2	82.7	29.6	.0382	1.046	2.059	4.539	4.9122	69.848	
28.991	412.4	301.4	28.2	82.8	24.8	.0319	.874	1.722	3.796	3.9506	56.187	
28.991	412.4	301.5	28.3	83.0	20.2	.0260	.712	1.402	3.090	3.1098	44.232	
28.991	412.4	301.7	28.5	83.4	14.2	.0183	.501	.986	2.173	2.0784	29.561	
28.991	412.4	301.8	28.7	83.6	14.0	.0181	.496	.976	2.151	2.0580	29.215	
28.991	412.4	301.7	28.6	83.4	20.9	.0270	.738	1.453	3.204	3.2693	46.581	
28.991	412.4	301.7	28.5	83.3	24.6	.0318	.869	1.712	3.773	3.9348	55.967	
28.991	412.4	301.6	28.4	83.2	29.6	.0382	1.045	2.057	4.535	4.9564	70.496	
28.946	411.7	301.4	28.3	82.9	38.8	.0501	1.369	2.696	5.945	7.0881	100.816	
28.900	411.1	301.3	28.1	82.6	47.4	.0613	1.676	3.299	7.273	9.4434	134.317	
28.855	410.4	301.2	28.0	82.4	56.2	.0728	1.985	3.909	8.618	12.3543	175.719	
28.855	410.4	301.1	27.9	82.2	64.9	.0840	2.292	4.512	9.948	15.9539	226.918	
28.764	409.1	301.2	28.0	82.4	72.7	.0944	2.568	5.057	11.149	21.0201	298.976	
*****	*****	*****	*****	*****								
28.966	412.7	301.4	28.2	82.8								
.057	.5	.2	.2	.4	DEVIATIONS							

ORIGINAL PAGE IS
OF POOR QUALITY

PAGE: 1
DATE: 9-8-76

TABLE 9
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL
PRESSURE DATA ACQUIRED AFTER 10 HIGH PRESSURE
(10,000 PSIA NOMINAL) GN2 IMPACT CYCLES - FLOW
IN FORWARD DIRECTION. TEST SPECIMEN (S/N 023)
INLET PRESSURE = 1000 PSIA NOMINAL. DATA
OBTAINED AFTER PROOF TEST.
TEST SPECIMEN INLET CONDITIONS.

TEST NUMBER 5 PART 23A TEST DESCRIPTION

FLOWMETER CONDITIONS

FLOWMETER ONE			FLOWMETER TWO			AVG	
FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	TEMP (DEG. F)	FLOW RATE (ACFM)
.86	50.1	75.5	.91	47.9	80.4	1011.9	.0429
.78	50.2	75.1	.81	48.5	79.9	1011.9	.0389
.69	49.9	75.1	.71	48.5	79.6	1011.9	.0360
.61	50.1	75.3	.61	48.9	79.6	1011.9	.0298
.51	50.1	75.8	.51	49.3	80.0	1015.9	.0280
.41	49.7	76.4	.41	49.1	80.3	1015.9	.0200
.32	50.1	77.4	.31	49.9	80.8	1015.9	.0154
.27	50.2	78.0	.26	49.9	81.2	1015.9	.0132
.22	50.2	78.6	.21	50.0	81.5	1015.9	.0107
.14	49.7	79.4	.13	49.5	81.9	1015.9	.0068
.14	50.1	80.8	.13	49.9	82.7	1011.9	.0068
.23	49.9	80.8	.23	49.7	82.7	1015.9	.0113
.27	49.9	81.7	.26	49.5	82.9	1015.9	.0131
.32	50.1	80.5	.31	49.9	82.9	1011.9	.0156
.41	50.1	80.0	.41	49.7	82.8	1011.9	.0203
.51	50.6	79.2	.51	49.9	82.5	1015.9	.0250
.60	50.1	78.3	.60	49.1	82.0	1011.9	.0222
.70	50.1	77.5	.71	48.7	81.5	1011.9	.0344
.78	50.4	76.8	.81	48.9	81.0	1011.9	.0321
.87	50.4	76.2	.92	48.3	80.3	1011.9	.0435

TABLE 9
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE DATA ACQUIRED AFTER 10 HIGH PRESSURE (10,000 PSIA NOMINAL) GN₂ IMPACT CYCLES. FLOW IN FORWARD DIRECTION. TEST SPECIMEN (S/N 023) INLET PRESSURE - 1000 PSIA NOMINAL. DATA OBTAINED AFTER PROOF TEST.

TEST NUMBER 5

PART 23A

TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
1011.9	77.9	.0429	93.076	93.865	93.470	=0.000	93.471
1011.9	77.5	.0389	82.300	83.119	82.710	=0.000	82.710
1011.9	77.4	.0340	69.618	70.478	70.048	=0.000	70.048
1011.9	77.5	.0298	59.354	60.048	59.701	=0.000	59.701
1015.9	77.9	.0250	47.952	48.671	48.311	=0.000	48.311
1015.9	78.4	.0200	37.603	37.668	37.636	=0.000	37.636
1015.9	79.1	.0154	27.522	27.547	27.535	=0.000	27.535
1015.9	79.6	.0132	22.944	22.958	22.951	=0.000	22.952
1015.9	80.0	.0107	18.019	17.975	17.997	=0.000	17.997
1015.9	80.7	.0068	10.951	10.944	10.947	=0.000	10.947
1011.9	81.7	.0068	11.009	11.115	11.062	=0.000	11.062
1015.9	81.7	.0113	19.004	19.120	19.062	=0.000	19.062
1015.9	81.8	.0131	22.713	22.843	22.778	=0.000	22.778
1011.9	81.7	.0156	27.869	28.064	27.967	=0.000	27.967
1011.9	81.4	.0203	38.009	38.186	38.098	=0.000	38.098
1015.9	80.8	.0250	47.952	48.671	48.311	=0.000	48.311
1011.9	80.1	.0293	57.976	58.784	58.380	=0.000	58.380
1011.9	79.5	.0344	70.742	71.426	71.084	=0.000	71.084
1011.9	78.9	.0391	83.041	84.067	83.554	=0.000	83.554
1011.9	78.2	.0435	96.393	96.393	96.393	=0.000	96.393

INLET DIFF. PRESS = $-1.64000E-04 + -1.26930E-02 (ACFM) + 2.48070E-01 (ACFM)**2 + 0 (ACFM)**3$

ORIGINAL PAGE IS OF POOR QUALITY

TABLE 9
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE DATA ACQUIRED AFTER 10 HIGH PRESSURE (10,000 PSIA NOMINAL) GN₂ IMPACT CYCLES. FLOW IN FORWARD DIRECTION. TEST SPECIMEN (S/N 023) INLET PRESSURE = 1000 PSIA NOMINAL. DATA OBTAINED AFTER PROOF TEST.

TEST NUMBER 5

PART 23A

TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESS

PRESSURE		TEMPERATURE			FLOW RATE						
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN ₂ KG/HR	GN ₂ LB/HR	KG/SQ CM DIFFERENTIAL	PSIQ
71.144	1011.7	298.7	25.5	77.9	82.4	.0429	2.911	5.734	12.637	6.5716	95.471
71.144	1011.7	298.4	25.3	77.5	74.8	.0389	2.643	5.207	11.474	5.8151	82.710
71.144	1011.7	298.4	25.2	77.4	65.3	.0340	2.307	4.544	10.014	4.9249	70.048
71.144	1011.7	298.4	25.3	77.5	57.4	.0298	2.026	3.987	8.794	4.1974	57.701
71.423	1015.7	298.7	25.5	77.9	48.2	.0250	1.702	3.351	7.387	3.3966	40.311
71.423	1015.7	298.9	25.8	78.4	38.6	.0200	1.362	2.683	5.914	2.6461	37.536
71.423	1015.7	299.3	26.2	79.1	29.7	.0154	1.048	2.063	4.548	1.9359	27.935
71.423	1015.7	299.6	26.4	79.6	25.4	.0132	.896	1.765	3.890	1.6137	22.952
71.423	1015.7	299.8	26.7	80.0	20.6	.0107	.727	1.434	3.156	1.2653	17.277
71.423	1015.7	300.2	27.0	80.7	13.0	.0068	.459	.903	1.991	.7627	10.147
71.144	1011.7	300.8	27.6	81.7	13.1	.0068	.461	.908	2.002	.7777	11.062
71.423	1015.7	300.8	27.6	81.7	21.6	.0113	.761	1.499	3.305	1.3402	19.062
71.423	1015.7	300.8	27.7	81.8	25.0	.0131	.883	1.738	3.833	1.6015	22.178
71.144	1011.7	300.8	27.6	81.7	29.8	.0156	1.054	2.077	4.575	1.9563	27.267
71.144	1011.7	300.6	27.4	81.4	38.8	.0203	1.371	2.699	5.950	2.6785	34.190
71.423	1015.7	300.3	27.1	80.8	48.0	.0250	1.695	3.337	7.356	3.3966	41.1
71.144	1011.7	299.9	26.7	80.1	56.1	.0293	1.980	3.898	8.593	4.1045	51.1
71.144	1011.7	299.6	26.4	79.5	66.0	.0344	2.329	4.587	10.112	4.9277	61.497
71.144	1011.7	299.2	26.0	78.9	74.9	.0391	2.646	5.210	11.487	5.0745	63.174
71.144	1011.7	298.9	25.7	78.2	83.6	.0435	2.952	5.814	12.914	6.1771	76.773
71.270	1013.7	299.6	26.4	79.6							
.138	2.0	.8	.8	1.4	DEVIATIONS						

TABLE 10
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 5 PART 25C

TEST DESCRIPTION

CLEAN CONDITION - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE TEST SPECIMEN
(S/N 025) INLET PRESSURE = 415 PSIA
NOMINAL

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS:

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F.)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F.)	PRESSURE (PSIA)	AVG. TEMP (DEG. F.)	AVG. FLOW RATE (ACFM)
.70	20.8	84.3	.74	49.3	85.5	419.5	84.9	.0859
.69	20.6	84.3	.71	49.3	85.3	418.8	84.8	.0833
.60	20.2	84.1	.61	49.3	85.1	418.2	84.6	.0716
.50	19.9	83.9	.50	49.1	85.0	418.2	84.5	.0596
.41	20.4	83.8	.41	49.9	84.8	418.2	84.3	.0487
.31	20.2	83.8	.30	49.9	84.8	418.2	84.3	.0366
.26	19.9	83.7	.26	49.5	84.7	418.2	84.2	.0309
.22	20.1	83.8	.21	49.9	84.8	418.2	84.3	.0256
.15	20.1	84.0	.14	49.9	85.0	418.2	84.5	.0170
.15	19.9	84.1	.14	49.7	85.1	418.8	84.6	.0168
.21	19.9	84.1	.21	49.9	85.1	418.2	84.6	.0252
.27	20.1	83.9	.26	49.9	84.9	418.2	84.4	.0315
.31	20.1	84.0	.30	49.7	85.1	418.2	84.6	.0366
.41	20.4	83.8	.40	49.9	85.0	417.5	84.4	.0487
.50	20.1	83.6	.50	49.3	84.8	417.5	84.2	.0595
.59	20.6	83.5	.60	49.5	84.7	416.9	84.1	.0717
.68	20.4	83.6	.70	49.3	84.7	416.2	84.2	.0825
.71	20.2	83.9	.74	48.9	84.8	416.2	84.4	.0862

TABLE 10
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 5 PART 25C

CLEAN CONDITION - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE TEST SPECIMEN
(S/N 025) INLET PRESSURE = 415 PSIA
NOMINAL.

TEST SPECIMEN INLET CONDITIONS

INLET PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
419.9	84.9	.0859	308.142	308.142	308.142	.001	308.141
418.8	84.8	.1833	276.222	276.222	276.222	.001	276.221
418.6	84.6	.0716	200.687	200.687	200.687	.001	200.686
418.6	84.5	.0596	147.908	147.908	147.908	.000	147.907
418.6	84.3	.0489	111.247	111.247	111.247	.000	111.246
418.6	84.3	.0364	75.521	75.850	75.685	.000	75.684
418.6	84.2	.0309	60.650	61.312	60.981	.000	60.980
418.6	84.3	.0254	48.515	48.355	48.435	.000	48.434
418.6	84.5	.0170	30.438	30.515	30.476	.000	30.475
418.8	84.6	.0168	30.206	30.400	30.303	.000	30.302
418.6	84.6	.0252	48.226	48.039	48.132	.000	48.131
418.6	84.4	.0315	62.654	63.209	62.931	.000	62.930
418.6	84.6	.0366	75.894	76.482	76.188	.000	76.187
417.5	84.4	.0487	111.247	111.247	111.247	.000	111.246
417.9	84.2	.0595	148.856	148.856	148.856	.000	148.855
416.9	84.1	.0717	203.532	203.532	203.532	.001	203.531
416.6	84.2	.0825	271.481	271.481	271.481	.001	271.480
416.6	84.4	.0862	307.826	307.826	307.826	.001	307.825

TARE DIFF. PRESS = -3.40000E-05 + -4.44000E-04 (ACFM) + 1.50933E-01 (ACFM)**2 + 0 (ACFM)**3

TABLE 10
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 5 PART 25C TEST DESCRIPTION CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE TEST SPECIMEN (S/N 025) INLET PRESSURE = 415 PSIA NOMINAL

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESS: *****

PRESSURE TEMPERATURE FLOW RATE

PRESSURE		TEMPERATURE			FLOW RATE						
KG/SQ. CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN.	ACFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/50 CM DIFFERENTIAL	PSID
29.493	419.3	302.5	29.4	84.9	67.5	0.859	2.384	4.695	10.351	21.665	308.141
29.447	418.6	302.5	29.3	84.8	65.4	0.833	2.308	4.545	10.019	19.4203	275.221
29.402	418.4	302.4	29.2	84.6	56.1	0.716	1.982	3.904	8.606	14.1097	200.680
29.402	418.4	302.3	29.1	84.5	46.7	0.596	1.649	3.268	7.160	10.3889	147.907
29.404	418.4	302.2	29.1	84.3	38.3	0.489	1.354	2.667	5.879	7.8214	111.246
29.402	418.4	302.2	29.1	84.3	28.6	0.364	1.009	1.987	4.380	5.3211	75.884
29.402	418.4	302.2	29.0	84.2	24.3	0.309	0.857	1.687	3.719	4.2873	60.988
29.402	418.4	302.2	29.1	84.3	20.0	0.254	0.705	1.388	3.059	3.4052	48.434
29.402	418.4	302.3	29.2	84.5	13.3	0.170	0.470	0.926	2.042	2.1426	30.478
29.447	418.6	302.4	29.2	84.6	13.2	0.168	0.466	0.917	2.021	2.1304	30.302
29.402	418.4	302.4	29.2	84.6	19.7	0.252	0.697	1.373	3.027	3.3840	48.131
29.402	418.4	302.3	29.1	84.4	24.7	0.315	0.873	1.715	3.788	4.4244	62.220
29.402	418.4	302.4	29.2	84.6	28.7	0.366	1.013	1.995	4.397	5.3555	75.187
29.356	417.3	302.3	29.1	84.4	38.1	0.487	1.346	2.650	5.841	7.8214	111.246
29.356	417.3	302.2	29.0	84.2	46.6	0.595	1.645	3.240	7.142	10.4655	148.855
29.310	416.3	302.1	28.9	84.1	56.1	0.717	1.981	3.901	8.601	14.3095	203.891
29.265	416.4	302.1	29.0	84.2	64.4	0.825	2.275	4.479	9.874	19.0849	271.480
29.265	416.4	302.2	29.1	84.4	77.3	0.862	2.378	4.682	10.322	21.6423	307.825
29.380	418.4	302.3	29.1	84.4							

0.42 0 1 2 DEVIATIONS

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 11
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 5-25 PART 25B TEST DESCRIPTION CLEAN CONDITION - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. TEST SPECIMEN
(S/N 025) INLET PRESSURE = 700 PSIA NOMINAL.

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG. TEMP (DEG. F)	AVG. FLOW RATE (ACFM)
.87	49.9	72.6	.90	47.9	74.0	715.7	73.3	.0604
.78	50.2	72.7	.81	48.5	74.4	707.8	73.5	.0555
.70	49.9	73.0	.71	48.5	74.2	707.8	73.6	.0490
.59	49.9	73.6	.61	48.9	74.7	711.8	74.1	.0416
.50	50.4	74.0	.50	49.7	75.2	707.8	74.6	.0359
.40	49.9	74.7	.41	49.3	75.7	707.8	75.2	.0283
.30	50.2	75.4	.30	49.9	76.4	711.8	75.9	.0213
.26	50.2	75.8	.25	50.0	76.9	711.8	76.3	.0180
.21	50.4	76.2	.20	50.2	77.7	711.8	76.9	.0146
.14	50.4	76.5	.14	50.2	78.5	715.7	77.5	.0099
.14	49.9	77.4	.14	49.9	78.1	715.7	77.8	.0098
.22	50.1	77.4	.22	49.9	77.9	715.7	77.7	.0152
.26	50.1	77.4	.26	49.9	78.0	715.7	77.7	.0184
.31	49.9	77.2	.31	49.5	77.7	715.7	77.4	.0215
.41	49.9	76.8	.41	49.3	77.4	715.7	77.1	.0283
.49	50.1	76.2	.50	49.3	77.6	715.7	76.9	.0345
.58	50.2	75.7	.60	49.3	77.5	715.7	76.6	.0411
.67	50.4	75.2	.70	49.3	77.7	707.8	76.5	.0482
.75	50.6	74.6	.81	49.1	77.4	711.8	76.0	.0545
.85	50.2	74.5	.91	48.3	77.9	711.8	76.2	.0608

TABLE 11
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 5-25 PART 25B

TEST DESCRIPTION

CLEAN CONDITION - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. TEST SPECIMEN
(S/N 025) INLET PRESSURE = 700 PSIA NOMINAL.

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
715.7	73.3	.0604	144.853	144.853	144.853	-0.000	144.853
707.8	73.5	.0555	126.839	126.839	126.839	-0.000	126.839
707.8	73.6	.0490	107.560	107.560	107.560	-0.000	107.560
711.8	74.1	.0416	88.204	88.597	88.401	-0.001	88.401
707.8	74.6	.0353	70.991	71.531	71.261	-0.001	71.261
707.8	75.2	.0283	54.216	54.781	54.498	-0.001	54.498
711.8	75.9	.0213	39.824	40.087	39.956	-0.001	39.956
711.8	76.3	.0180	32.640	32.775	32.708	-0.001	32.708
711.8	76.9	.0146	25.571	25.596	25.583	-0.001	25.583
715.7	77.5	.0099	16.648	16.716	16.682	-0.001	16.682
715.7	77.8	.0098	16.416	16.544	16.480	-0.001	16.480
715.7	77.7	.0152	26.737	26.858	26.794	-0.001	26.794
715.7	77.7	.0184	33.393	33.638	33.516	-0.001	33.516
715.7	77.4	.0215	40.404	40.606	40.505	-0.001	40.505
715.7	77.1	.0283	55.093	55.729	55.411	-0.001	55.411
715.7	76.9	.0345	70.617	71.215	70.916	-0.001	70.916
715.7	76.6	.0411	88.204	88.913	88.559	-0.001	88.559
707.8	76.5	.0482	107.560	107.560	107.560	-0.000	107.560
711.8	76.6	.0545	127.787	127.787	127.787	-0.000	127.787
711.8	76.2	.0608	148.014	148.014	148.014	-0.000	148.014

TARE DIFF. PRESS = $-3.60000E-04 + -3.31610E-02$ (ACFM) + $6.33359E-01$ (ACFM)**2 + 0 (ACFM)**3

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 11
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 5-25		PART 25B		TEST DESCRIPTION		CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE, TEST SPECIMEN (S/N 025) INLET PRESSURE = 700 PSIA NOMINAL.						
TEST SPECIMEN INLET CONDITIONS											NET DIFFERENTIAL PRESS.	
PRESSURE		TEMPERATURE				FLOW RATE						
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID	
50.318	715.7	296.1	23.0	73.3	82.8	.0604	2.925	5.759	12.696	10.1842	144.883	
49.765	707.8	296.2	23.1	73.5	75.2	.0555	2.657	5.232	11.534	8.9176	126.839	
49.765	707.8	296.3	23.1	73.6	66.4	.0490	2.343	4.614	10.172	7.9822	107.589	
50.041	711.8	296.6	23.4	74.1	56.6	.0416	1.997	3.933	8.671	6.2158	88.401	
49.765	707.8	296.8	23.7	74.6	47.7	.0353	1.685	3.318	7.314	5.0102	71.241	
49.765	707.8	297.2	24.0	75.2	38.2	.0283	1.348	2.653	5.850	3.8316	54.488	
50.041	711.8	297.6	24.4	75.9	28.9	.0213	1.022	2.012	4.436	2.8092	39.956	
50.041	711.8	297.8	24.6	76.3	24.5	.0180	.863	1.700	3.748	2.2996	32.788	
50.041	711.8	298.1	25.0	76.9	19.8	.0146	.700	1.378	3.038	1.7987	25.583	
50.318	715.7	298.4	25.3	77.5	13.4	.0099	.474	.934	2.060	1.1729	16.682	
50.318	715.7	298.6	25.4	77.8	13.3	.0098	.470	.925	2.039	1.1587	16.480	
50.318	715.7	298.5	25.4	77.7	20.7	.0152	.730	1.438	3.171	1.8838	26.794	
50.318	715.7	298.6	25.4	77.7	24.9	.0184	.881	1.734	3.823	2.3564	33.516	
50.318	715.7	298.4	25.2	77.4	29.3	.0215	1.034	2.036	4.488	2.8478	40.505	
50.318	715.7	298.2	25.0	77.1	38.5	.0283	1.360	2.678	5.903	3.8958	55.411	
50.318	715.7	298.1	24.9	76.9	47.0	.0345	1.659	3.268	7.204	4.9859	70.916	
50.318	715.7	297.9	24.8	76.6	56.0	.0411	1.978	3.894	8.586	6.2263	88.589	
49.765	707.8	297.9	24.7	76.5	64.9	.0482	2.291	4.510	9.943	7.9622	107.589	
50.041	711.8	297.6	24.5	76.0	73.9	.0545	2.610	5.140	11.331	8.9843	127.787	
50.041	711.8	297.7	24.5	76.2	82.4	.0608	2.910	5.729	12.631	10.4064	148.014	
50.097	712.5	297.6	24.5	76.0								
.199	2.8	.7	.7	1.2	DEVIATIONS							

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 12
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 5-25 PART 25A

TEST DESCRIPTION

CLEAN CONDITION - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE, TEST SPECIMEN
(S/N 025) INLET PRESSURE = 1000 PSIA NOMINAL.

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE			FLOWMETER TWO			TEST SPECIMEN INLET CONDITIONS		
FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	
.84	50.2	68.3	.90	48.3	73.7	1007.9	71.0	.0425
.76	50.6	68.0	.81	48.9	73.3	1007.9	70.6	.0389
.67	49.9	68.0	.71	48.3	73.2	1007.9	70.6	.0334
.58	49.7	68.3	.61	48.5	73.2	1007.9	70.7	.0290
.49	49.7	68.8	.50	48.9	73.5	1007.9	71.1	.0244
.40	49.7	69.4	.40	49.1	73.8	1007.9	71.6	.0197
.30	50.1	70.1	.31	49.9	74.2	1007.9	72.1	.0151
.26	49.7	71.8	.26	49.5	74.6	1007.9	72.7	.0128
.21	49.9	71.4	.21	49.7	74.9	1007.9	73.1	.0103
.14	49.5	72.3	.14	49.1	75.4	1007.9	73.8	.0068
.14	50.1	73.6	.14	49.9	76.2	1007.9	74.9	.0069
.24	50.2	73.7	.24	49.9	76.4	1007.9	75.0	.0116
.27	50.4	73.7	.26	50.2	76.4	1007.9	75.1	.0133
.31	49.9	73.5	.31	49.5	76.6	1007.9	75.0	.0152
.40	50.4	73.0	.40	49.9	76.4	1007.9	74.7	.0198
.48	50.1	72.4	.49	49.3	76.2	1007.9	74.3	.0241
.58	50.2	71.4	.60	49.1	75.6	1007.9	73.5	.0290
.66	50.2	70.5	.70	49.1	75.1	1007.9	72.8	.0336
.75	50.4	70.0	.80	48.7	74.6	1007.9	72.3	.0381
.85	50.4	69.3	.90	48.3	74.0	1007.9	71.7	.0428

TABLE 12
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 5-25 PART 25A

TEST DESCRIPTION

CLEAN CONDITION - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE, TEST SPECIMEN
(S/N 025) INLET PRESSURE = 1000 PSIA NOMINAL.

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
1007.9	71.0	.0425	99.870	99.870	99.870	-0.000	99.870
1007.9	70.6	.0389	88.328	89.124	88.726	-0.000	88.726
1007.9	70.6	.0334	73.735	74.586	74.160	-0.000	74.161
1007.9	70.7	.0290	61.984	62.577	62.280	-0.000	62.280
1007.9	71.1	.0244	49.578	50.251	49.915	-0.000	49.915
1007.9	71.6	.0197	39.168	39.281	39.224	-0.000	39.225
1007.9	72.1	.0151	28.796	28.811	28.804	-0.000	28.804
1007.9	72.7	.0128	23.756	23.761	23.758	-0.000	23.758
1007.9	73.1	.0103	18.425	18.376	18.400	-0.000	18.401
1007.9	73.8	.0068	11.762	11.743	11.753	-0.000	11.753
1007.9	74.9	.0069	11.936	11.972	11.954	-0.000	11.934
1007.9	75.0	.0118	21.554	21.697	21.626	-0.000	21.626
1007.9	75.1	.0133	24.972	25.080	25.026	-0.000	25.026
1007.9	75.0	.0152	29.202	29.328	29.265	-0.000	29.265
1007.9	74.7	.0198	39.342	39.512	39.427	-0.000	39.427
1007.9	74.3	.0241	49.328	49.935	49.631	-0.000	49.632
1007.9	73.5	.0290	61.733	62.261	61.997	-0.000	61.997
1007.9	72.8	.0336	74.233	74.902	74.568	-0.000	74.568
1007.9	72.3	.0381	87.470	88.176	87.823	-0.000	87.823
1007.9	71.7	.0428	101.766	101.766	101.766	-0.000	101.766

TARE DIFF. PRESS = -1.64000E-04 + -1.26930E-02 (ACFM) + 2.48070E-01 (ACFM)**2.0 + 0 (ACFM)**3

TABLE 12
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 5-25 PART 25A

TEST DESCRIPTION CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE TEST SPECIMEN (S/N 025) INLET PRESSURE = 1000 PSIA NOMINAL.

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESS: *****

PRESSURE		TEMPERATURE			FLOW RATE						
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID
70.865	1007.9	294.8	21.7	71.0	82.3	.0425	2.906	5.721	12.614	7.0216	99.870
70.865	1007.9	294.6	21.5	70.6	75.3	.0389	2.661	5.239	11.550	6.2381	88.726
70.865	1007.9	294.6	21.4	70.6	64.8	.0334	2.289	4.507	9.937	5.2140	74.161
70.865	1007.9	294.7	21.5	70.7	56.3	.0290	1.988	3.914	8.628	4.3785	62.288
70.865	1007.9	294.9	21.7	71.1	47.2	.0244	1.667	3.283	7.238	3.5094	49.915
70.865	1007.9	295.2	22.0	71.6	38.1	.0197	1.346	2.650	5.842	2.7978	39.285
70.865	1007.9	295.5	22.3	72.1	29.3	.0151	1.033	2.034	4.484	2.0251	28.804
70.865	1007.9	295.8	22.6	72.7	24.7	.0128	.871	1.715	3.781	1.6704	23.738
70.865	1007.9	296.0	22.9	73.1	19.8	.0103	.700	1.378	3.037	1.2937	18.401
70.865	1007.9	296.4	23.2	73.8	13.2	.0068	.465	.915	2.018	.8293	11.793
70.865	1007.9	297.0	23.8	74.9	13.3	.0069	.470	.926	2.041	.8404	11.954
70.865	1007.9	297.1	23.9	75.0	22.6	.0118	.798	1.572	3.466	1.5204	21.026
70.865	1007.9	297.1	23.9	75.1	25.6	.0133	.903	1.779	3.921	1.7595	25.028
70.865	1007.9	297.1	23.9	75.0	29.2	.0152	1.030	2.028	4.472	2.0575	29.266
70.865	1007.9	296.9	23.7	74.7	38.1	.0198	1.347	2.652	5.848	2.7720	39.427
70.865	1007.9	296.6	23.5	74.3	46.4	.0241	1.639	3.227	7.114	3.4894	49.632
70.865	1007.9	296.2	23.1	73.5	55.9	.0290	1.974	3.887	8.569	4.3588	61.997
70.865	1007.9	295.8	22.7	72.8	64.9	.0336	2.292	4.512	9.948	5.2426	74.588
70.865	1007.9	295.5	22.4	72.3	73.7	.0381	2.602	5.123	11.294	6.1746	87.823
70.865	1007.9	295.2	22.0	71.7	82.9	.0428	2.928	5.765	12.710	7.1549	101.766
70.865	1007.9	295.8	22.7	72.8							
.000	0	.8	.8	1.4	DEVIATIONS						

TABLE-13
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN-CONDITION--FLOW-RATE-VERSUS-DIFFERENTIAL-PRESSURE.
DATA ACQUIRED ON TEST SPECIMEN (S/N 027) PRIOR TO THE
ADDITION OF SYNTHETIC CONTAMINANT. TEST SPECIMEN INLET
PRESSURE = 415 PSIA (NOMINAL).

TEST NUMBER 10 PART-27B TEST DESCRIPTION

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS:

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.75	49.9	69.2	.81	48.4	70.4	413.7	69.8	.0936
.67	50.3	69.2	.71	48.8	70.4	413.0	69.8	.0827
.58	50.5	68.9	.60	49.3	70.4	413.0	69.6	.0718
.49	50.5	68.8	.50	49.5	70.4	412.4	69.6	.0609
.40	50.3	68.7	.40	49.5	70.4	411.7	69.6	.0488
.31	50.3	68.8	.30	49.9	70.5	411.7	69.7	.0370
.26	50.5	68.9	.25	50.1	70.5	411.7	69.7	.0311
.21	50.1	69.1	.21	49.9	70.7	411.7	69.8	.0253
.14	49.7	69.2	.14	49.5	70.8	411.7	70.0	.0169
.14	50.3	69.4	.14	49.9	71.1	411.7	70.2	.0170
.22	50.3	69.2	.22	49.9	70.9	411.1	70.0	.0266
.26	50.5	69.1	.26	50.1	70.9	411.1	70.0	.0320
.31	50.7	68.9	.31	50.1	70.7	411.1	69.8	.0380
.41	49.9	68.6	.41	49.2	70.5	410.4	69.6	.0493
.50	50.1	68.2	.51	49.0	70.4	409.8	69.3	.0614
.58	50.3	68.2	.61	49.2	71.2	409.1	69.2	.0724
.67	50.3	68.0	.70	48.8	69.9	408.5	69.0	.0830
.75	49.9	68.5	.80	48.2	69.8	407.8	69.2	.0934

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 13
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE.
DATA ACQUIRED ON TEST SPECIMEN (S/N 027) PRIOR TO THE
ADDITION OF SYNTHETIC CONTAMINANT. TEST SPECIMEN INLET
PRESSURE = 415 PSIA (NOMINAL).

TEST NUMBER 10 PART 27B TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
413.7	69.8	.0936	302.835	302.835	302.835	.001	302.833
413.0	69.8	.0827	225.939	225.939	225.939	.001	225.938
413.0	69.6	.0718	176.258	176.258	176.258	.001	176.257
412.4	69.6	.0603	133.538	133.538	133.538	.000	133.537
411.7	69.6	.0488	98.413	98.413	98.413	.000	98.412
411.7	69.7	.0370	64.109	68.668	66.389	.000	66.387
411.1	69.7	.0311	50.817	55.694	53.255	.000	53.254
411.1	69.8	.0253	43.026	43.102	43.064	.000	43.062
411.7	70.0	.0169	26.898	26.968	26.933	.000	26.932
411.1	70.2	.0170	27.247	27.371	27.309	.000	27.307
411.1	70.0	.0266	46.802	45.884	46.343	.000	46.342
411.1	70.0	.0320	58.470	57.592	58.031	.000	58.030
411.1	69.8	.0380	72.600	71.832	72.216	.000	72.215
410.4	69.6	.0493	100.628	100.628	100.628	.000	100.627
409.8	69.3	.0614	138.918	138.918	138.918	.001	138.917
409.1	69.2	.0724	179.422	179.422	179.422	.001	179.421
408.5	69.0	.0830	231.002	231.002	231.002	.001	231.001
407.8	69.2	.0934	305.999	305.999	305.999	.001	305.998

TARE DIFF. PRESS = $-3.40000E-05 + -4.44000E-04$ (ACFM) + $1.50933E-01$ (ACFM)**2 + 0 (ACFM)**3.

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 13
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE.
DATA ACQUIRED ON TEST SPECIMEN (S/N 027) PRIOR TO THE
ADDITION OF SYNTHETIC CONTAMINANT. TEST SPECIMEN INLET
PRESSURE = 415 PSIA (NOMINAL).

TEST NUMBER 10 PART 27B TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESS:

PRESSURE		TEMPERATURE			FLOW RATE						
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID
29.083	413.1	294.2	21.0	69.8	74.6	.0936	2.635	5.185	11.437	21.2913	302.833
29.037	413.0	294.1	21.0	69.8	65.8	.0827	2.323	4.574	10.085	15.8850	225.938
29.037	413.0	294.1	20.9	69.6	57.2	.0718	2.020	3.977	8.757	12.3921	175.887
28.992	412.4	294.0	20.9	69.6	48.0	.0603	1.694	3.336	7.354	9.3886	133.517
28.946	411.1	294.0	20.9	69.6	38.7	.0488	1.368	2.694	5.939	6.9191	98.412
28.946	411.1	294.1	20.9	69.7	29.4	.0370	1.037	2.042	4.502	4.6675	66.387
28.946	411.1	294.1	20.9	69.7	24.7	.0311	.873	1.719	3.789	3.7441	53.254
28.946	411.1	294.2	21.0	69.8	20.1	.0253	.709	1.396	3.077	3.0276	43.082
28.946	411.7	294.3	21.1	70.0	13.4	.0169	.472	.930	2.050	1.8935	26.932
28.946	411.1	294.4	21.2	70.2	13.5	.0170	.477	.934	2.069	1.9199	27.307
28.900	411.4	294.3	21.1	70.0	21.1	.0266	.745	1.466	3.233	3.2581	46.342
28.900	411.4	294.3	21.1	70.0	25.4	.0320	.896	1.763	3.888	4.0799	58.030
28.900	411.4	294.2	21.0	69.8	30.1	.0380	1.063	2.093	4.615	5.0772	72.215
28.855	410.4	294.0	20.9	69.6	39.0	.0493	1.378	2.713	5.981	7.0748	100.627
28.809	409.8	293.9	20.7	69.3	48.5	.0614	1.714	3.375	7.440	9.7668	138.917
28.764	409.4	293.8	20.6	69.2	57.1	.0724	2.017	3.971	8.755	12.6146	179.421
28.718	408.5	293.7	20.5	69.0	65.5	.0830	2.312	4.552	10.036	16.2410	231.001
28.673	407.8	293.8	20.6	69.2	73.5	.0934	2.595	5.109	11.264	21.5138	305.998
*****	*****	*****	*****	*****							
28.908	411.4	294.1	20.9	69.7							

DEVIATIONS

0038

TABLE 1-4
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE.
DATA ACQUIRED ON TEST SPECIMEN S/N 027 PRIOR TO THE
ADDITION OF SYNTHETIC CONTAMINANT. TEST SPECIMEN INLET
PRESSURE = 1000 PSIA (NOMINAL).

TEST NUMBER 10 PART 27A TEST DESCRIPTION

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG. TEMP. (DEG. F)	AVG. FLOW RATE (ACFM)
.87	49.9	74.6	.91	47.6	77.7	1009.2	76.1	.0429
.78	50.4	73.5	.81	48.6	77.0	1009.2	75.3	.0390
.69	50.2	73.1	.71	48.8	76.6	1005.3	74.9	.0344
.60	50.1	72.9	.61	49.0	76.4	1005.3	74.7	.0298
.51	50.2	72.8	.50	49.2	76.3	1005.3	74.6	.0249
.41	50.4	73.0	.40	49.5	76.3	1005.3	74.7	.0200
.32	50.2	73.3	.31	49.5	76.5	1005.3	74.9	.0155
.27	50.2	73.5	.26	49.9	76.5	1005.3	75.0	.0132
.22	49.9	73.9	.21	49.3	76.8	1005.3	75.3	.0105
.14	50.6	74.6	.13	50.5	77.0	1005.3	75.8	.0069
.15	50.2	75.2	.13	49.9	77.3	1005.3	76.2	.0070
.22	50.1	75.0	.21	49.7	77.2	1001.3	76.1	.0108
.27	49.7	74.6	.26	49.2	77.1	1001.3	75.9	.0131
.32	49.7	74.1	.31	49.2	77.0	1001.3	75.5	.0155
.42	50.1	73.3	.41	49.2	76.7	1001.3	75.0	.0204
.51	50.1	72.4	.51	49.2	76.3	1001.3	74.3	.0253
.60	50.4	71.3	.60	49.3	75.6	1001.3	73.5	.0299
.69	50.1	71.4	.71	48.6	75.1	1001.3	72.7	.0344
.78	50.2	69.5	.81	48.4	74.4	997.3	71.9	.0392
.87	50.4	68.7	.91	48.2	73.6	997.3	71.1	.0441

ORIGINAL PAGE IS
OF POOR QUALITY

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 14
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE.
DATA ACQUIRED ON TEST SPECIMEN S/N 027 PRIOR TO THE
ADDITION OF SYNTHETIC CONTAMINANT. TEST SPECIMEN INLET
PRESSURE = 1000 PSIA (NOMINAL).

TEST NUMBER 1-1 PART 27A TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
1009.2	76.1	.0429	91.701	92.180	91.940	=0.000	91.941
1009.2	75.3	.0390	81.146	81.435	81.291	=0.000	81.291
1005.3	74.9	.0344	68.952	69.425	69.188	=0.000	69.189
1005.3	74.7	.0298	57.559	58.363	57.961	=0.000	57.961
1005.3	74.6	.0249	46.989	46.986	46.987	=0.000	46.988
1005.3	74.7	.0200	36.039	36.094	36.066	=0.000	36.066
1005.3	74.9	.0156	26.768	26.724	26.746	=0.000	26.747
1005.3	75.0	.0132	22.249	22.136	22.193	=0.000	22.193
1005.3	75.3	.0105	17.150	17.040	17.095	=0.000	17.095
1005.3	75.8	.0069	8.981	8.984	8.982	=0.000	8.982
1005.3	76.2	.0070	10.835	10.924	10.880	=0.000	10.880
1001.3	76.1	.0118	17.672	17.727	17.699	=0.000	17.700
1001.3	75.9	.0131	21.959	22.079	22.019	=0.000	22.019
1001.3	75.5	.0155	26.884	26.954	26.919	=0.000	26.919
1001.3	75.0	.0204	36.850	37.015	36.932	=0.000	36.933
1001.3	74.3	.0253	48.090	48.250	48.170	=0.000	48.170
1001.3	73.5	.0299	58.311	58.995	58.653	=0.000	58.653
1001.3	72.7	.0344	69.827	70.373	70.100	=0.000	70.100
997.3	71.9	.0392	81.765	82.383	82.074	=0.000	82.074
997.3	71.1	.0441	95.657	95.657	95.657	=0.000	95.657

TARE DIFF. PRESS = -1.64000E-04 + -1.26930E-02 (ACFM) + 2.48070E-01 (ACFM)**2 + 0 (ACFM)**3

TABLE 14
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN-CONDITION -- FLOW-RATE VERSUS DIFFERENTIAL PRESSURE.
DATA ACQUIRED ON TEST SPECIMEN S/N 027 PRIOR TO THE
ADDITION OF SYNTHETIC CONTAMINANT. TEST SPECIMEN INLET
PRESSURE = 1000 PSIA (NOMINAL).

TEST NUMBER 10 PART 27A TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESSURE

PRESSURE		TEMPERATURE			FLOW-RATE							NET DIFFERENTIAL PRESSURE
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSIA	
70.956	1009.2	297.7	24.5	76.1	82.5	.429	2.914	5.737	12.648	6.4641	91.941	
70.956	1009.2	297.2	24.4	75.3	75.1	.0390	2.652	5.221	11.510	5.7153	81.291	
70.677	1005.3	297.9	23.8	74.9	66.1	.0344	2.334	4.595	10.131	4.8645	69.189	
70.677	1005.3	296.9	23.7	74.7	57.1	.0298	2.018	3.974	8.761	4.0751	57.961	
70.677	1005.3	296.8	23.6	74.6	47.8	.0249	1.688	3.323	7.326	3.3036	46.988	
70.677	1005.3	296.9	23.7	74.7	38.4	.0200	1.357	2.671	5.889	2.5257	36.066	
70.677	1005.3	297.0	23.8	74.9	29.8	.0156	1.054	2.075	4.574	1.8805	26.747	
70.677	1005.3	297.1	23.9	75.0	25.4	.0132	.897	1.767	3.895	1.5603	22.193	
70.677	1005.3	297.2	24.1	75.3	20.1	.0105	.710	1.398	3.081	1.2019	17.095	
70.677	1005.3	297.5	24.3	75.8	13.3	.0069	.470	.925	2.040	.6315	8.982	
70.677	1005.3	297.7	24.6	76.2	13.3	.0070	.471	.927	2.043	.7649	10.880	
70.398	1001.3	297.6	24.5	76.1	20.7	.0108	.730	1.437	3.169	1.2444	17.700	
70.398	1001.3	297.5	24.4	75.9	25.0	.0131	.884	1.741	3.838	1.5481	22.019	
70.398	1001.3	297.3	24.2	75.5	29.7	.0155	1.048	2.064	4.550	1.8926	26.919	
70.398	1001.3	297.0	23.9	75.0	38.9	.0204	1.374	2.705	5.965	2.5966	36.933	
70.398	1001.3	296.7	23.5	74.3	48.4	.0253	1.708	3.363	7.415	3.3867	48.170	
70.398	1001.3	296.2	23.0	73.5	57.3	.0299	2.024	3.985	8.785	4.1237	58.653	
70.398	1001.3	295.8	22.6	72.7	66.1	.0344	2.334	4.596	10.133	4.9285	70.100	
70.118	997.3	295.3	22.2	71.9	75.1	.0397	2.652	5.222	11.513	5.7704	82.074	
70.118	997.3	294.9	21.7	71.1	84.6	.0441	2.987	5.882	12.967	6.7283	95.687	
****	****	****	****	****								
70.551	1003.7	296.9	23.7	74.7								
.194	2.8	.6	.6	1.0	DEVIATIONS							

TABLE 15
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 12 PART 28D

TEST DESCRIPTION

CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE. DATA ACQUIRED WITH FLOW IN THE FORWARD (S/N SIDE UPSTREAM) DIRECTION. TEST SPECIMEN (S/N U28) INLET PRESSURE = 415 PSIA (NOMINAL).

FLOW METER CONDITIONS

TEST SPECIMEN INLET CONDITIONS:

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.73	49.9	75.1	.75	48.3	75.8	417.5	75.4	.071
.69	50.4	75.1	.71	48.9	75.9	416.9	75.5	.0837
.58	50.4	75.2	.64	49.3	76.0	416.9	75.6	.0709
.49	50.2	75.3	.56	49.3	75.9	416.2	75.6	.0596
.40	50.2	75.3	.46	49.5	75.7	416.2	75.5	.0484
.30	50.1	75.7	.30	49.5	76.1	416.2	75.9	.0360
.26	49.9	75.9	.25	49.3	76.6	416.2	76.3	.0364
.21	50.2	76.1	.20	49.9	77.2	416.2	76.6	.0247
.14	49.9	76.4	.13	49.7	78.0	416.2	77.2	.0164
.14	49.9	76.8	.13	49.5	79.8	416.2	78.3	.0163
.21	49.9	76.8	.21	49.3	79.9	415.6	78.4	.0252
.26	49.7	76.9	.26	49.3	79.9	415.6	78.4	.0307
.30	50.1	76.8	.30	49.5	79.7	415.6	78.2	.0363
.40	50.4	76.5	.46	49.9	79.3	415.6	77.9	.0483
.48	50.8	76.1	.49	49.9	78.9	414.9	77.5	.0592
.58	50.6	76.3	.60	49.3	78.9	414.3	77.6	.0715
.67	50.4	76.8	.70	48.9	78.7	413.7	77.7	.0822
.70	50.6	77.3	.73	48.9	78.5	413.0	77.9	.0862

TABLE 15
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE. DATA ACQUIRED WITH FLOW IN THE FORWARD (S/N SIDE UPSTREAM) DIRECTION. TEST SPECIMEN (S/N 028) INLET PRESSURE = 415 PSIA (NOMINAL).

TEST NUMBER 12 PART 28D TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
417.5	75.4	.0871	309.946	309.946	309.946	.001	309.945
416.9	75.5	.0837	277.662	277.662	277.662	.001	277.661
416.9	75.6	.0709	203.186	203.186	203.186	.001	203.185
416.2	75.6	.0596	153.641	153.641	153.641	.000	153.640
416.2	75.5	.0484	113.686	113.686	113.686	.000	113.685
416.2	75.9	.0360	77.162	77.886	77.524	.000	77.523
416.2	76.3	.0304	62.627	63.502	63.065	.000	63.064
416.2	76.6	.0247	49.118	49.118	49.118	.000	49.118
416.2	77.2	.0164	30.611	30.611	30.611	=0.000	30.611
416.2	78.3	.0163	30.611	30.611	30.611	=0.000	30.611
415.6	78.4	.0252	50.717	50.717	50.717	.000	50.717
415.6	78.4	.0347	63.755	64.461	64.108	.000	64.107
415.6	78.2	.0363	78.414	79.484	78.949	.000	78.948
415.6	77.9	.0483	115.284	115.284	115.284	.000	115.283
414.9	77.5	.0592	152.363	152.363	152.363	.000	152.362
414.3	77.6	.0715	207.341	207.341	207.341	.001	207.340
413.7	77.7	.0822	272.868	272.868	272.868	.001	272.867
413.0	77.9	.0862	309.307	309.307	309.307	.001	309.306

TARE DIFF. PRESS = $-3.40000E-05 + -4.44000E-04$ (ACFM) + $1.50933E-01$ (ACFM)**2 + 0 (ACFM)**3.

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 15
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE. DATA ACQUIRED WITH FLOW IN THE FORWARD (S/N SIDE UPSTREAM) DIRECTION. TEST SPECIMEN (S/N 028) INLET PRESSURE = 415 PSIA (NOMINAL).

TEST NUMBER 12 PART 28D

TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESSURE

PRESSURE		TEMPERATURE			FLOW RATE						
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN2 KG/HR	GN2 LB5/HR	KG/SQ CM DIFFERENTIAL	PSID
29.356	417.9	297.3	24.1	75.4	69.4	0.871	2.450	4.825	10.637	21.7913	309.945
29.311	416.7	297.3	24.2	75.5	66.5	0.837	2.350	4.628	10.202	19.5215	277.661
29.311	416.9	297.4	24.2	75.6	56.3	0.709	1.989	3.917	8.636	14.2853	203.185
29.265	416.2	297.4	24.2	75.6	47.3	0.596	1.670	3.289	7.251	10.8020	153.640
29.265	416.2	297.3	24.2	75.5	38.4	0.484	1.355	2.669	5.883	7.9928	113.685
29.265	416.2	297.6	24.4	75.9	28.5	0.360	1.008	1.985	4.377	5.4504	77.523
29.265	416.2	297.8	24.6	76.3	24.1	0.304	0.851	1.677	3.696	4.4338	63.064
29.265	416.2	297.9	24.8	76.6	19.6	0.247	0.691	1.360	2.999		
29.265	416.2	298.3	25.1	77.2	13.0	0.164	0.458	0.902	1.988		
29.265	416.2	298.9	25.7	78.3	12.8	0.163	0.453	0.893	1.968		
29.219	415.0	298.9	25.8	78.4	19.9	0.252	0.702	1.382	3.047		
29.219	415.0	298.9	25.8	78.4	24.2	0.307	0.855	1.683	3.711	4.5072	64.107
29.219	415.0	298.8	25.7	78.2	28.6	0.363	1.010	1.988	4.382	5.5506	78.948
29.219	415.0	298.7	25.5	77.9	38.1	0.483	1.346	2.650	5.842	8.1052	115.203
29.174	414.9	298.5	25.3	77.5	46.7	0.592	1.649	3.247	7.158	10.7121	152.362
29.128	414.3	298.5	25.3	77.6	56.2	0.715	1.986	3.910	8.620	14.5775	207.340
29.083	413.1	298.6	25.4	77.7	64.6	0.822	2.280	4.490	9.899	19.1844	272.867
29.037	413.0	298.7	25.5	77.9	67.5	0.862	2.385	4.697	10.355	21.7464	309.306
****	****	****	****	****							
29.230	415.1	298.1	25.0	77.0							
0.060	0.8	0.6	0.6	1.0	DEVIATIONS						

TABLE 16
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE.
DATA ACQUIRED WITH FLOW IN THE FORWARD (S/N SIDE UPSTREAM)
DIRECTION. TEST SPECIMEN (S/N 028) INLET PRESSURE =
1000 PSIA (NOMINAL).

TEST NUMBER 12 PART 28C TEST DESCRIPTION:

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS:

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.86	50.2	67.5	.91	48.0	72.9	1009.2	70.2	.0429
.78	50.0	66.6	.81	48.0	72.3	1009.2	69.4	.0395
.69	50.2	66.1	.71	48.6	71.8	1009.2	68.9	.0363
.60	50.4	65.9	.60	49.0	71.5	1009.2	68.7	.0296
.51	50.0	66.1	.51	49.0	71.6	1009.2	69.0	.0288
.41	50.2	66.4	.40	49.5	71.8	1009.2	69.1	.0259
.31	50.2	67.0	.30	49.5	71.9	1009.2	69.4	.0155
.27	50.8	67.3	.26	49.2	71.9	1009.2	69.6	.0128
.21	50.2	67.7	.20	49.7	71.7	1009.2	69.7	.0103
.14	50.4	68.7	.13	49.0	71.5	1009.2	70.1	.0067
.14	50.2	69.9	.13	49.9	72.5	1009.2	71.2	.0068
.22	50.4	69.8	.21	49.9	72.7	1009.2	71.2	.0105
.26	50.6	69.6	.25	49.9	72.9	1009.2	71.2	.0129
.31	50.4	69.6	.30	49.9	73.0	1009.2	71.2	.0154
.41	50.0	69.9	.40	49.2	73.0	1009.2	70.9	.0199
.50	50.2	68.3	.50	49.2	72.8	1009.2	70.5	.0247
.60	50.7	67.3	.60	49.3	72.1	1009.2	69.7	.0298
.69	50.4	66.6	.70	48.8	71.5	1005.3	69.1	.0342
.78	50.0	65.8	.81	48.4	70.8	1005.3	68.2	.0398
.87	50.2	65.0	.91	48.0	70.3	1005.3	67.6	.0434

ORIGINAL PAGE IS
OF POOR QUALITY

PAGE: 2
DATE: 9-15-76

TABLE 16
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE.
DATA ACQUIRED WITH FLOW IN THE FORWARD (S/N SIDE UPSTREAM)
DIRECTION. TEST SPECIMEN (S/N 028) INLET PRESSURE =
1000 PSIA (NOMINAL)

TEST NUMBER 12 PART 28C TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

TEST NUMBER	PART	TEST DESCRIPTION	AVG GROSS DIFF. PRESS. PRIMARY (PSID)	AVG GROSS DIFF. PRESS. SECONDARY (PSID)	AVG GROSS DIFF. PRESS. (PSID)	TARE DIFF. PRESS. (PSID)	NET DIFF. PRESS. (PSID)
1009.2			100.608	100.608	100.608	=0.000	100.608
1009.2			86.805	88.282	87.544	=0.000	87.544
1009.2			75.995	76.905	76.450	=0.000	76.450
1009.2			64.003	64.579	64.291	=0.000	64.291
1009.2			52.054	52.569	52.312	=0.000	52.312
1009.2			39.890	40.478	40.184	=0.000	40.184
1009.2			29.215	29.574	29.395	=0.000	29.395
1009.2			24.597	24.626	24.611	=0.000	24.611
1009.2			19.202	19.225	19.214	=0.000	19.214
1009.2			11.835	11.830	11.832	=0.000	11.833
1009.2			12.067	12.174	12.120	=0.000	12.120
1009.2			19.608	19.742	19.675	=0.000	19.675
1009.2			24.829	24.971	24.900	=0.000	24.900
1009.2			29.968	30.381	30.175	=0.000	30.175
1009.2			40.267	40.825	40.546	=0.000	40.546
1009.2			51.804	52.253	52.029	=0.000	52.029
1009.2			64.868	65.211	65.040	=0.000	65.040
1005.3			76.116	76.905	76.510	=0.000	76.510
1005.3			87.967	89.230	88.599	=0.000	88.599
1005.3			102.820	102.820	102.820	=0.000	102.821

TARE DIFF. PRESS = -1.60000E-04 + -1.26930E-02 (ACFM) + 2.48070E-01 (ACFM)**2.0 + 0 (ACFM)**3.

ORIGINAL PAGE IS
OF POOR QUALITY

DATE: 9-15-76

TABLE 16
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE.
DATA ACQUIRED WITH FLOW IN THE FORWARD (S/N SIDE UPSTREAM)
DIRECTION. TEST SPECIMEN (S/N 028) INLET PRESSURE =
1000 PSIA (NOMINAL).

TEST NUMBER 12 PART 28C

TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS											NET DIFFERENTIAL PRESS	
*****											*****	
PRESSURE		TEMPERATURE			FLOW RATE							
*****											*****	
KG/50 CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/50 CM DIFFERENTIAL	PSID	
70.956	1009.4	294.4	21.2	70.2	83.4	.0429	2.946	5.801	12.789	7.0735	100.800	
70.956	1009.4	293.9	20.8	69.4	74.8	.0385	2.648	5.205	11.475	6.1548	87.566	
70.956	1009.4	293.7	20.5	68.9	66.9	.0343	2.361	4.649	10.250	5.3750	76.050	
70.956	1009.4	293.6	20.4	68.7	57.7	.0296	2.037	4.011	8.842	4.5201	64.291	
70.956	1009.4	293.6	20.5	68.8	48.4	.0248	1.708	3.383	7.414	3.6779	52.312	
70.956	1009.2	293.8	20.6	69.1	38.7	.0199	1.365	2.688	5.927	2.8252	40.184	
70.956	1009.2	294.0	20.8	69.4	29.4	.0151	1.039	2.045	4.508	2.0667	29.395	
70.956	1009.4	294.0	20.9	69.6	25.0	.0128	.882	1.737	3.828	1.7304	24.012	
70.956	1009.4	294.1	20.9	69.7	20.1	.0103	.708	1.395	3.075	1.3509	19.214	
70.956	1009.4	294.3	21.2	70.1	12.9	.0067	.456	.899	1.982	.8319	11.053	
70.956	1009.4	295.0	21.8	71.2	13.1	.0068	.463	.912	2.012	.8521	12.120	
70.956	1009.2	295.0	21.8	71.2	20.3	.0105	.718	1.412	3.114	1.3833	19.675	
70.956	1009.4	295.0	21.8	71.3	25.0	.0129	.884	1.741	3.837	1.7547	24.900	
70.956	1009.4	294.9	21.8	71.2	29.8	.0154	1.053	2.073	4.569	2.1215	30.175	
70.956	1009.4	294.8	21.6	70.9	38.6	.0199	1.364	2.685	5.922	2.8807	40.545	
70.956	1009.4	294.6	21.4	70.5	48.0	.0247	1.695	3.337	7.354	3.6580	52.022	
70.956	1009.4	294.1	20.9	69.7	58.0	.0298	2.049	4.034	8.894	4.5728	65.040	
70.677	1005.3	293.8	20.6	69.1	66.4	.0342	2.346	4.620	10.184	5.3792	76.514	
70.677	1005.3	293.3	20.2	68.3	75.4	.0388	2.662	5.242	11.557	6.2291	88.500	
70.677	1005.3	293.0	19.8	67.6	84.5	.0434	2.984	5.875	12.952	7.2290	102.821	
70.914	1008.9	294.1	21.0	69.8								
.071	1.0	.5	.5	.9	DEVIATIONS							

TABLE 17
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN CONDITION-IMPACT/FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. FLOW RATE VERSUS
DIFFERENTIAL PRESSURE DATA PRIOR TO CN,
IMPACT CYCLES. TEST SPECIMEN (S/N 021)
INLET PRESSURE 415 PSIA (NOMINAL).

TEST NUMBER 6 PART 3C-1 TEST DESCRIPTION

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.72	50.4	78.6	.76	49.1	79.0	417.4	78.8	.0878
.67	50.4	78.9	.70	49.1	79.4	416.1	79.1	.0819
.58	50.4	79.0	.60	49.3	79.4	416.1	79.2	.0708
.49	50.4	78.8	.50	49.9	79.3	415.5	79.0	.0600
.40	50.1	78.6	.40	49.5	79.1	414.8	78.8	.0480
.31	50.1	78.9	.30	49.9	79.1	414.8	79.0	.0368
.26	50.2	78.8	.25	50.1	79.2	414.8	79.0	.0308
.21	50.2	79.4	.20	50.1	79.8	414.8	79.6	.0250
.13	50.2	80.0	.12	50.1	80.2	414.8	80.1	.0154
.13	50.1	80.5	.12	49.9	80.4	414.8	80.5	.0153
.21	50.1	79.9	.20	49.9	80.2	414.8	80.0	.0248
.26	50.2	79.2	.26	49.9	80.5	414.8	79.9	.0315
.31	49.9	78.9	.31	49.7	80.8	414.2	79.8	.0372
.40	49.9	78.8	.40	49.3	82.0	414.2	80.4	.0482
.49	50.2	79.0	.50	49.5	82.5	413.5	80.8	.0600
.58	50.1	78.9	.60	49.1	81.5	412.9	80.2	.0711
.68	50.1	79.2	.71	48.7	81.3	412.2	80.3	.0828
.70	50.4	79.7	.74	49.1	80.9	411.6	80.3	.0868

PAGE: 2
DATE: 8/2/76

TABLE 17
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN CONDITION-IMPACT/FLOW RATE VERSUS
DIFFERENTIAL PRESSURE, FLOW RATE VERSUS
DIFFERENTIAL PRESSURE DATA PRIOR TO ON-
IMPACT CYCLES. TEST SPECIMEN (S/N 021)
INLET PRESSURE 415 PSIA (NOMINAL).

TEST NUMBER 6 PART 3C-1 TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
417.4	78.8	.0878	305.617	305.617	305.617	.001	305.616
416.1	79.1	.0819	251.257	251.257	251.257	.001	251.256
416.1	79.2	.0788	186.467	186.467	186.467	.001	186.466
415.5	79.0	.0600	140.324	140.324	140.324	.000	140.323
414.8	78.8	.0480	100.503	100.503	100.503	.000	100.502
414.8	79.0	.0368	68.620	69.214	68.917	.000	68.916
414.8	79.0	.0308	54.218	54.676	54.447	.000	54.446
414.8	79.6	.0250	41.899	42.178	42.038	.000	42.037
414.8	80.1	.0154	23.544	23.523	23.533	-0.000	23.532
414.8	80.5	.0153	23.312	23.465	23.388	-0.000	23.387
414.8	80.0	.0248	41.725	41.947	41.836	.000	41.835
414.8	79.9	.0315	56.474	56.888	56.681	.000	56.680
414.2	79.8	.0372	69.994	70.794	70.394	.000	70.393
414.2	80.4	.0482	101.135	101.135	101.135	.000	101.134
413.5	80.8	.0600	140.324	140.324	140.324	.000	140.323
412.9	80.2	.0711	188.680	188.680	188.680	.001	188.678
412.2	80.3	.0828	256.945	256.945	256.945	.001	256.944
411.6	80.3	.0868	291.078	291.078	291.078	.001	291.077

TARE DIFF. PRESS = -3.40000E-05 + -4.44000E-04 (ACFM) + 1.50933E-01 (ACFM)**2 +

0 (ACFM)**3

C.2

PAGE: 3
DATE: 8/2/76

TABLE 17
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN CONDITION-IMPACT/FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. FLOW RATE VERSUS
DIFFERENTIAL PRESSURE DATA PRIOR TO GN,
IMPACT CYCLES. TEST SPECIMEN (S/N 021),
INLET PRESSURE 415 PSIA (NOMINAL).

TEST NUMBER 6 PART 3C-1 TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESS

PRESSURE		TEMPERATURE			FLOW RATE					NET DIFFERENTIAL PRESS	
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID
29.347	417.4	299.2	26.0	78.8	70.4	.0878	2.453	4.829	10.647	21.4869	305.616
29.256	416.1	299.3	26.2	79.1	65.3	.0819	2.280	4.490	9.899	17.6650	251.256
29.256	416.1	299.4	26.2	79.2	56.0	.0708	1.969	3.877	8.547	13.1099	186.466
29.210	415.5	299.3	26.1	79.0	47.4	.0600	1.669	3.286	7.244	9.8657	140.323
29.165	414.8	299.2	26.0	78.8	37.5	.0480	1.332	2.623	5.783	7.0660	100.502
29.165	414.8	299.3	26.1	79.0	28.7	.0368	1.020	2.008	4.427	4.8453	68.916
29.165	414.8	299.3	26.1	79.0	24.0	.0308	.854	1.681	3.705	3.8279	54.446
29.165	414.8	299.6	26.4	79.6	19.4	.0250	.694	1.366	3.011	2.9555	42.037
29.165	414.8	299.9	26.7	80.1	11.8	.0154	.427	.841	1.854	1.6545	23.532
29.165	414.8	300.1	26.9	80.5	11.5	.0153	.422	.831	1.833	1.6443	23.307
29.165	414.8	299.8	26.7	80.0	19.3	.0248	.688	1.354	2.985	2.9413	41.835
29.165	414.8	299.7	26.6	79.9	24.5	.0315	.873	1.719	3.791	3.9850	56.680
29.119	414.2	299.7	26.6	79.8	29.0	.0372	1.028	2.025	4.465	4.9491	70.393
29.119	414.2	300.0	26.9	80.4	37.6	.0482	1.332	2.622	5.781	7.1104	101.134
29.073	413.5	300.3	27.1	80.8	46.9	.0600	1.654	3.256	7.179	9.8657	140.323
29.028	412.9	299.9	26.8	80.2	55.8	.0711	1.960	3.859	8.508	13.2654	188.678
28.982	412.2	300.0	26.8	80.3	65.1	.0828	2.278	4.486	9.889	18.0650	256.944
28.937	411.6	300.0	26.8	80.3	68.3	.0868	2.385	4.697	10.354	20.4648	291.077
****	****	****	****	****							
29.147	414.6	299.7	26.5	79.7							
.069	1.0	.3	.3	.6	DEVIATIONS						

PAGE: 1
DATE: 8/2/76

TABLE 18
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 6 PART 3B TEST DESCRIPTION

CLEAN CONDITION-IMPACT/FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. FLOW RATE VERSUS
DIFFERENTIAL PRESSURE DATA PRIOR TO ON
IMPACT CYCLES. TEST SPECIMEN (S/N 021)
INLET PRESSURE 700 PSIA (NOMINAL)

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.84	50.4	70.1	.91	48.5	74.6	711.8	72.3	.0609
.75	50.6	69.6	.81	49.1	74.2	711.8	71.9	.0546
.67	50.2	69.4	.71	48.9	73.9	711.8	71.7	.0479
.58	50.2	69.4	.60	49.3	73.8	707.8	71.6	.0417
.49	50.2	69.6	.50	49.7	73.9	707.8	71.7	.0348
.39	49.7	69.9	.40	49.3	74.1	707.8	72.0	.0276
.30	49.9	70.6	.30	49.5	74.5	707.8	72.5	.0213
.25	50.1	71.0	.25	49.9	74.7	707.8	72.9	.0179
.21	50.1	71.8	.20	49.9	75.3	707.8	73.5	.0144
.14	50.1	72.3	.14	49.9	75.7	707.8	74.0	.0099
.14	49.7	73.6	.14	49.9	76.5	711.8	75.1	.0098
.22	49.7	73.6	.21	49.7	76.5	711.8	75.1	.0149
.26	49.9	74.6	.25	49.7	76.5	711.8	75.0	.0179
.30	50.1	73.3	.31	49.9	76.4	711.8	74.9	.0214
.40	49.7	72.9	.41	49.3	76.3	711.8	74.6	.0281
.49	49.9	72.4	.50	49.3	76.0	707.8	74.2	.0347
.58	49.9	71.9	.60	48.9	75.7	707.8	73.8	.0410
.67	50.1	71.5	.71	48.9	75.2	707.8	73.4	.0491
.76	50.4	71.0	.81	48.9	74.7	707.8	72.9	.0552
.84	50.4	70.7	.91	48.5	74.2	707.8	72.5	.0612

ORIGINAL PAGE IS
OF POOR QUALITY

PAGE: 2
DATE: 8/2/76

TABLE 18
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN CONDITION-IMPACT/FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. FLOW RATE VERSUS
DIFFERENTIAL PRESSURE DATA PRIOR TO CN.
IMPACT CYCLES. TEST SPECIMEN (S/N 021).
INLET PRESSURE 700 PSIA (NOMINAL).

TEST NUMBER 6 PART 3B TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS. (PSID)
711.8	72.3	.0609	148.015	148.015	148.015	-0.000	148.015
711.8	71.9	.0546	126.840	126.840	126.840	-0.000	126.840
711.8	71.7	.0479	105.665	105.665	105.665	-0.000	105.665
707.8	71.6	.0417	86.528	87.018	86.773	-0.001	86.773
707.8	71.7	.0348	67.786	68.371	68.079	-0.001	68.079
707.8	72.0	.0276	50.500	51.305	50.902	-0.001	50.902
707.8	72.5	.0213	37.097	37.226	37.162	-0.001	37.162
707.8	72.9	.0179	30.011	30.093	30.052	-0.001	30.052
707.8	73.5	.0144	22.982	23.034	23.008	-0.001	23.008
707.8	74.0	.0099	14.792	14.734	14.763	-0.001	14.763
711.8	75.1	.0098	14.618	14.734	14.676	-0.001	14.676
711.8	75.1	.0149	24.086	24.239	24.162	-0.001	24.162
711.8	75.0	.0179	29.953	30.151	30.052	-0.001	30.052
711.8	74.9	.0214	37.562	37.687	37.624	-0.001	37.624
711.8	74.6	.0281	51.878	52.569	52.224	-0.001	52.224
707.8	74.2	.0347	67.536	68.371	67.954	-0.001	67.954
707.8	73.8	.0410	85.177	86.070	85.623	-0.001	85.623
707.8	73.4	.0481	106.297	106.297	106.297	-0.000	106.297
707.8	72.9	.0552	128.420	128.420	128.420	-0.000	128.420
707.8	72.5	.0612	148.647	148.647	148.647	-0.000	148.647

TARE DIFF. PRESS = $-3.60000E-04 + -3.31610E-02$ (ACFM) + $6.33359E-01$ (ACFM)**2 +

0 (ACFM)**3

ORIGINAL PAGE IS
OF POOR QUALITY

PAGES: 3
DATE: 8/2/76
CLEAN CONDITION-IMPACT/FLOW RATE VERSUS
DIFFERENTIAL PRESSURE FLOW RATE VERSUS
DIFFERENTIAL PRESSURE DATA PRIOR TO ON,
IMPACT CYCLES TEST SPECIMEN (S/N 021)
INLET PRESSURE 700 PSIA (NOMINAL)?

TABLE 18
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 6 PART 3B TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESS:

PRESSURE		TEMPERATURE			FLOW RATE						
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSIA
50.041	711.8	295.6	22.4	72.3	84.8	.0609	2.933	5.776	12.734	10.4505	148.015
50.041	711.8	295.3	22.2	71.9	76.1	.0546	2.634	5.186	11.433	8.9177	126.840
50.041	711.8	295.2	22.0	71.7	66.5	.0479	2.313	4.554	10.039	7.4290	105.465
49.765	707.8	295.2	22.0	71.6	57.3	.0417	1.999	3.937	8.680	6.1008	86.773
49.765	707.8	295.2	22.1	71.7	47.5	.0348	1.668	3.284	7.240	4.7864	68.079
49.765	707.8	295.4	22.2	72.0	37.5	.0276	1.322	2.603	5.738	3.5708	50.988
49.765	707.8	295.7	22.5	72.5	28.8	.0213	1.021	2.010	4.431	2.6127	37.182
49.765	707.8	295.9	22.7	72.9	24.1	.0179	.857	1.688	3.721	2.1129	30.052
49.765	707.8	296.2	23.1	73.5	19.4	.0144	.690	1.359	2.997	1.6177	23.000
49.765	707.8	296.5	23.3	74.0	13.2	.0099	.474	.933	2.058	1.0379	14.768
50.041	711.8	297.1	23.9	75.1	13.0	.0098	.468	.922	2.033	1.0318	14.676
50.041	711.8	297.1	23.9	75.1	20.0	.0149	.716	1.469	3.167	1.6988	24.162
50.041	711.8	297.1	23.9	75.0	24.1	.0179	.856	1.686	3.717	2.1129	30.052
50.041	711.8	297.0	23.8	74.9	29.1	.0214	1.028	2.024	4.461	2.6459	37.524
50.041	711.8	296.8	23.7	74.6	38.2	.0291	1.347	2.651	5.845	3.6717	52.234
49.765	707.8	296.6	23.5	74.2	47.1	.0347	1.656	3.261	7.189	4.7775	67.954
49.765	707.8	296.4	23.2	73.8	56.1	.0410	1.962	3.862	8.815	6.0199	85.623
49.765	707.8	296.1	23.0	73.4	66.2	.0481	2.304	4.536	10.001	7.4734	106.297
49.765	707.8	295.9	22.7	72.9	76.1	.0552	2.645	5.208	11.401	9.0288	126.420
49.765	707.8	295.6	22.5	72.5	84.6	.0612	2.933	5.774	12.730	10.4509	148.047
*****	*****	*****	*****	*****							
49.876	709.4	296.1	22.9	73.3							
.133	1.9	.6	.6	1.1	DEVIATIONS						

TABLE 19
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 6 PART 3A TEST DESCRIPTION

CLEAN CONDITION-IMPACT/FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. FLOW RATE VERSUS
DIFFERENTIAL PRESSURE DATA PRIOR TO CN.
IMPACT CYCLES. TEST SPECIMEN (S/N 021)
INLET PRESSURE 1000 PSIA (NOMINAL)

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
83	74.3	76.5	90	47.2	81.6	1011.9	79.0	0.012
75	74.2	75.6	80	48.7	80.8	1011.9	78.2	0.0379
67	74.1	75.1	71	48.7	80.1	1011.9	77.6	0.0336
58	74.6	75.1	60	49.3	79.9	1007.9	77.5	0.0290
48	74.4	75.1	50	49.9	79.9	1007.9	77.5	0.0244
39	74.4	75.6	40	49.9	80.1	1007.9	77.9	0.0197
31	74.4	76.0	31	50.1	80.1	1007.9	78.0	0.0185
26	74.8	76.3	26	50.4	80.2	1007.9	78.2	0.0189
21	74.8	76.5	20	50.2	80.3	1007.9	78.4	0.0164
14	74.4	77.3	13	50.2	80.6	1007.9	78.9	0.0088
14	74.9	77.7	13	49.7	80.3	1007.9	79.0	0.0068
11	74.2	77.4	21	50.1	80.1	1007.9	78.7	0.0105
27	74.1	77.0	25	49.5	79.9	1007.9	78.4	0.0124
30	74.4	76.5	30	49.5	79.6	1004.0	78.0	0.0150
40	74.5	75.6	40	49.1	79.2	1004.0	77.4	0.0197
49	74.5	74.7	50	48.7	78.6	1004.0	76.6	0.0243
55	74.4	73.7	61	48.7	77.9	1004.0	75.8	0.0291
66	74.2	72.9	70	48.3	77.3	1000.0	75.1	0.0334
75	74.2	72.0	80	48.5	76.5	1000.0	74.3	0.0384
84	74.4	71.2	91	47.8	75.7	1000.0	73.5	0.0427

TABLE 19
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN CONDITION-IMPACT/FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. FLOW RATE VERSUS
DIFFERENTIAL PRESSURE DATA PRIOR TO GN
IMPACT CYCLES. TEST SPECIMEN (S/N 021)
INLET PRESSURE 1000 PSIA (NOMINAL).

TEST NUMBER 6

PART 3A

TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

INLET PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
1011.2	19.6	.0412	99.009	99.009	99.009	0.000	99.010
1011.2	18.2	.0379	87.853	88.593	88.423	0.000	88.223
1011.2	17.6	.0356	75.012	75.967	75.489	0.000	75.490
1007.2	17.5	.0290	61.656	62.749	62.183	0.000	62.183
1007.2	17.5	.0244	49.391	50.083	49.737	0.000	49.738
1007.2	17.9	.0197	38.540	38.725	38.632	0.000	38.632
1007.2	18.0	.0153	28.387	28.486	28.437	0.000	28.437
1007.2	18.2	.0129	22.992	23.035	23.014	0.000	23.014
1007.2	18.4	.0114	17.597	17.594	17.595	0.000	17.595
1007.2	18.9	.0088	10.810	10.849	10.829	0.000	10.829
1007.2	19.0	.0088	10.694	10.792	10.742	0.000	10.743
1007.2	18.7	.0105	17.887	17.994	17.941	0.000	17.941
1007.2	18.4	.0124	21.890	22.003	21.947	0.000	21.947
1004.2	18.0	.0120	27.575	27.739	27.657	0.000	27.657
1004.2	17.4	.0177	38.360	38.609	38.487	0.000	38.488
1004.2	16.6	.0243	48.891	49.452	49.172	0.000	49.172
1004.2	15.8	.0291	62.407	63.025	62.716	0.000	62.716
1000.2	15.1	.0334	73.892	74.704	74.298	0.000	74.298
1000.2	14.3	.0384	88.342	89.224	88.783	0.000	88.783
1000.2	13.5	.0427	103.744	103.744	103.744	0.000	103.744

TARE DIFF. PRESS = -1.64000E-04 * -1.26930E-02 (ACFM) + 2.48070E-01 (ACFM)**2 + 0 (ACFM)**3

ORIGINAL PAGE IS
OF POOR QUALITY

PAGE: 3
DATE: 8/2/76

TABLE 19
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN CONDITION-IMPACT/FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. FLOW RATE VERSUS
DIFFERENTIAL PRESSURE DATA PRIOR TO GN₂
IMPACT CYCLES. TEST SPECIMEN (S/N 021)
INLET PRESSURE 1000 PSIA (NOMINAL).

TEST NUMBER 6 PART 3A TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESSURE

PRESSURE		TEMPERATURE			FLOW RATE						
KG/CM ²	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN ₂ KG/MIN	GN ₂ LB ₂ /HR	KG/CM ² DIFFERENTIAL	PSID
71.144	1011.7	299.3	26.1	79.0	80.4	0.412	2.787	5.485	12.098	6.9611	99.010
71.144	1011.7	298.8	25.1	78.2	74.2	0.379	2.570	5.060	11.156	6.2027	88.423
71.144	1011.7	298.5	25.3	77.6	65.5	0.336	2.277	4.482	9.884	5.3074	75.490
70.889	1007.2	298.4	25.3	77.5	56.0	0.290	1.959	3.851	8.502	4.3719	62.183
70.889	1007.2	298.4	25.3	77.5	47.1	0.244	1.652	3.256	7.170	3.4969	49.138
70.889	1007.2	298.7	25.3	77.9	37.8	0.197	1.334	2.821	5.792	2.7161	38.832
70.889	1007.2	298.7	25.3	78.0	29.2	0.153	1.037	2.044	4.500	1.9993	28.337
70.889	1007.2	298.8	25.1	78.2	24.5	0.129	0.872	1.711	3.785	1.6180	23.014
70.889	1007.2	298.9	25.8	78.4	19.5	0.104	0.700	1.378	3.037	1.2371	17.396
70.889	1007.2	299.2	26.1	78.9	12.7	0.068	0.459	0.902	1.992	0.7614	10.829
70.889	1007.2	299.3	26.1	79.0	12.5	0.068	0.456	0.892	1.982	0.7553	10.143
70.889	1007.2	299.1	26.4	78.7	19.8	0.105	0.707	1.391	3.067	1.2614	17.741
70.889	1007.2	299.0	25.8	78.4	23.4	0.124	0.834	1.544	3.620	1.5430	21.847
70.889	1004.2	298.7	25.2	78.0	28.4	0.150	1.011	1.990	4.388	1.9445	27.897
70.889	1004.2	298.4	25.6	77.4	37.7	0.197	1.327	2.814	5.759	2.7060	38.488
70.889	1004.2	298.0	24.8	76.6	46.8	0.243	1.637	3.226	7.104	3.4571	49.172
70.889	1004.2	297.5	24.4	75.8	56.2	0.291	1.966	3.871	8.534	4.4094	62.116
70.889	1000.2	297.1	23.2	75.1	64.1	0.334	2.248	4.421	9.760	5.2237	74.498
70.889	1000.2	296.6	23.0	74.3	74.4	0.384	2.589	5.092	11.241	6.2221	88.183
70.889	1000.2	296.2	23.0	73.5	83.4	0.427	2.887	5.682	12.530	7.2240	103.144
70.168	1008.2	298.4	25.2	77.4							
0.211	3.0	0.7	0.7	1.2	DEVIATIONS						

TABLE 20
FLOW RATE VERSUS DIFFERENTIAL-PRESSURE

PAGE: 1
DATE: 8-24-76

TEST NUMBER 6 PART 3G

CLEAN CONDITION - IMPACT/FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. FLOW RATE VERSUS
DIFFERENTIAL PRESSURE DATA AFTER 100 HIGH PRESSURE CO_2 IMPACT
CYCLES. TEST SPECIMEN (S/N 021). INLET PRESSURE 415 PSIA NOMINAL.
TEST SPECIMEN INLET CONDITIONS

FLOWMETER CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP. (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP. (DEG. F)	PRESSURE (PSIA)	AVG TEMP. (DEG. F)	AVG FLOW RATE (ACFM)
0.85	50.2	76.4	0.91	48.3	78.0	420.8	77.2	0.1031
0.76	50.4	76.2	0.80	48.9	77.4	420.1	76.8	0.0923
0.67	50.1	76.1	0.70	48.7	76.6	419.5	76.4	0.0800
0.58	49.9	76.1	0.60	48.9	76.8	419.5	76.5	0.0697
0.49	49.9	76.3	0.49	49.3	77.3	419.5	76.8	0.0579
0.40	50.4	76.6	0.40	49.9	77.8	419.5	77.2	0.0482
0.30	50.4	76.8	0.30	50.1	78.4	419.5	77.6	0.0350
0.26	49.9	77.1	0.25	49.9	78.9	419.5	78.0	0.0302
0.21	50.1	77.3	0.20	49.9	79.2	419.5	78.2	0.0245
0.14	50.2	77.6	0.13	50.1	79.3	420.1	78.5	0.0156
0.13	50.1	78.3	0.13	50.1	79.5	420.8	78.9	0.0155
0.22	49.9	78.4	0.21	49.9	79.9	420.8	79.1	0.0257
0.25	50.2	78.5	0.24	50.1	79.9	420.8	79.2	0.0293
0.32	50.2	78.4	0.31	49.9	80.0	420.1	79.2	0.0375
0.40	50.2	78.2	0.40	49.9	79.9	420.1	79.1	0.0479
0.49	50.4	78.0	0.50	49.7	79.8	419.5	78.9	0.0594
0.58	50.1	77.8	0.60	49.1	79.7	418.8	78.8	0.0698
0.67	50.1	77.6	0.70	48.7	79.5	418.8	78.6	0.0803
0.76	50.2	77.3	0.80	48.5	79.2	418.2	78.3	0.0919
0.84	50.4	77.3	0.90	48.5	79.0	417.5	78.1	0.1031

TABLE 20
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 6 PART 3G TEST DESCRIPTION

CLEAN CONDITION -- IMPACT/FLOW RATE VERSUS DIFFERENTIAL PRESSURE. FLOW RATE VERSUS DIFFERENTIAL PRESSURE DATA AFTER 100 HIGH PRESSURE GN2 IMPACT CYCLES. TEST SPECIMEN (S/N 021) INLET PRESSURE 415 PSIA NOMINAL.

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG. GROSS DIFF. PRESS (PSID)	IARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
420.8	77.2	.1031	135.057	135.057	135.057	.002	135.055
420.1	76.8	.0923	113.250	113.250	113.250	.001	113.248
419.5	76.4	.0800	90.847	91.443	91.145	.001	91.143
419.5	76.5	.0697	74.443	75.008	74.726	.001	74.724
419.5	76.8	.0579	57.184	57.626	57.405	.000	57.404
419.5	77.2	.0482	45.213	45.395	45.304	.000	45.302
419.5	77.6	.0360	31.133	31.224	31.178	.000	31.177
419.5	78.0	.0302	24.876	24.908	24.892	.000	24.890
419.5	78.2	.0245	19.024	19.005	19.014	.000	19.013
420.1	78.5	.0156	11.144	11.172	11.158	.000	11.156
420.8	78.9	.0155	11.144	11.229	11.186	.000	11.185
420.8	79.1	.0257	20.298	20.437	20.368	.000	20.366
420.8	79.2	.0293	24.064	24.162	24.113	.000	24.112
420.1	79.2	.0375	32.755	32.891	32.823	.000	32.822
420.1	79.1	.0479	45.039	45.222	45.130	.000	45.129
419.5	78.9	.0594	59.315	59.838	59.576	.000	59.575
418.8	78.8	.0698	74.816	75.640	75.228	.001	75.227
418.8	78.6	.0803	91.334	92.391	91.862	.001	91.861
418.4	78.3	.0919	112.302	112.302	112.302	.001	112.300
417.5	78.1	.1031	134.741	134.741	134.741	.002	134.739

IARE DIFF. PRESS = $3.40000E=05 \cdot 4.44000E=04 (ACFM) + 1.50993E=01 (ACFM)^{**2} + 0 (ACFM)^{**3}$

0000

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 20
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 3
DATE: 8-24-76

TEST NUMBER 6 PART 3G

CLEAN CONDITION - IMPACT/FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. FLOW RATE VERSUS
DIFFERENTIAL PRESSURE DATA AFTER 100 HIGH PRESSURE GN2 IMPACT
CYCLES. TEST SPECIMEN (S/N 021) INLET PRESSURE 415 PSIA NOMINAL.
NET DIFFERENTIAL PRESSURE

TEST SPECIMEN INLET CONDITIONS

PRESSURE		TEMPERATURE			FLOW RATE						
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	<chem>GN2</chem> KG/HR	<chem>GN2</chem> LBS/HR	KG/SQ CM DIFFERENTIAL	PSID
29.584	420.8	298.3	25.1	77.2	83.7	.1031	2.913	5.735	12.643	9.4953	135.056
29.538	420.1	298.1	24.9	76.8	74.7	.0923	2.605	5.129	11.308	7.9622	113.248
29.493	419.5	297.8	24.7	76.4	64.4	.0800	2.257	4.444	9.798	6.4080	91.143
29.493	419.5	297.9	24.7	76.5	56.0	.0697	1.966	3.871	8.534	5.2536	74.724
29.493	419.5	298.1	24.9	76.8	46.2	.0579	1.631	3.211	7.079	4.0359	57.404
29.493	419.5	298.3	25.1	77.2	38.3	.0482	1.358	2.674	5.895	3.1851	45.302
29.493	419.5	298.5	25.3	77.6	28.4	.0360	1.014	1.997	4.402	2.1920	31.177
29.493	419.5	298.7	25.5	78.0	23.9	.0302	.850	1.674	3.691	1.7500	24.890
29.493	419.5	298.8	25.7	78.2	19.0	.0245	.687	1.353	2.983	1.3367	19.813
29.538	420.1	299.0	25.8	78.5	12.0	.0156	.440	.865	1.909	.7844	11.156
29.584	420.8	299.2	26.1	78.9	11.9	.0155	.436	.858	1.892	.7864	11.185
29.584	420.8	299.3	26.2	79.1	20.3	.0257	.724	1.425	3.144	1.4319	20.266
29.584	420.8	299.4	26.2	79.2	23.0	.0293	.825	1.624	3.580	1.6952	24.112
29.538	420.1	299.4	26.2	79.2	29.5	.0375	1.052	2.072	4.569	2.3076	32.822
29.538	420.1	299.3	26.1	79.1	38.0	.0479	1.345	2.648	5.839	3.1729	45.129
29.493	419.5	299.2	26.1	78.9	47.2	.0594	1.666	3.280	7.232	4.1885	59.375
29.447	418.8	299.2	26.0	78.8	55.8	.0698	1.957	3.852	8.493	5.2690	75.227
29.447	418.8	299.0	25.9	78.6	64.3	.0803	2.251	4.432	9.771	6.4584	91.861
29.402	418.2	298.9	25.7	78.3	73.8	.0919	2.574	5.068	11.174	7.8955	112.300
29.356	417.5	298.8	25.6	78.1	83.1	.1031	2.884	5.680	12.522	9.4731	134.739
29.504	419.6	298.8	25.6	78.1							
.046	.6	.4	.4	.8	DEVIATIONS						

TABLE 21
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 6 PART 3F

TEST DESCRIPTION

CLEAN CONDITION - IMPACT/FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. FLOW RATE VERSUS
DIFFERENTIAL PRESSURE DATA AFTER 100 HIGH
PRESSURE GN2 IMPACT CYCLES. TEST SPECIMEN (S/N 021) INLET
PRESSURE 700 PSIA NOMINAL. TEST SPECIMEN INLET CONDITIONS.

FLOWMETER CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.88	49.5	68.7	.92	47.4	73.4	719.6	71.0	.0663
.78	49.5	67.6	.81	47.8	72.4	715.7	70.0	.0539
.69	49.5	67.4	.70	48.3	72.1	715.7	69.7	.0473
.60	49.5	67.5	.60	48.5	72.0	715.7	69.7	.0409
.50	49.7	67.9	.50	48.9	72.2	715.7	70.1	.0335
.41	49.7	68.4	.40	49.1	72.6	711.8	70.5	.0281
.31	49.9	69.3	.30	49.7	73.2	711.8	71.3	.0215
.26	50.1	69.9	.25	49.9	73.6	711.8	71.8	.0181
.21	49.9	71.8	.20	49.9	74.3	711.8	72.5	.0145
.14	50.4	71.6	.13	50.4	74.8	715.7	73.2	.0095
.14	49.7	72.8	.13	49.5	75.7	715.7	74.2	.0092
.22	50.1	72.7	.21	49.9	75.7	715.7	74.2	.0150
.27	50.4	72.5	.26	50.1	75.7	715.7	74.1	.0180
.32	50.2	72.3	.31	49.9	75.6	715.7	74.0	.0219
.41	50.2	71.8	.40	49.9	75.4	715.7	73.6	.0284
.50	50.1	71.3	.50	49.3	75.2	715.7	73.3	.0350
.60	49.9	70.8	.60	48.9	74.8	715.7	72.8	.0411
.69	50.1	70.2	.70	48.7	74.4	711.8	72.3	.0482
.78	50.2	69.6	.80	48.5	73.8	711.8	71.7	.0549
.87	49.9	69.2	.90	47.9	73.2	711.8	71.2	.0608

TABLE 21
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 6 PART 3F. TEST DESCRIPTION. CLEAN CONDITION - IMPACT/FLOW RATE VERSUS DIFFERENTIAL PRESSURE. FLOW RATE VERSUS DIFFERENTIAL PRESSURE DATA AFTER 100-HIGH PRESSURE GN₂ IMPACT CYCLES. TEST SPECIMEN (S/N 021) INLET PRESSURE 700 PSIA NOMINAL.

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS. (PSID)	TARE DIFF. PRESS. (PSID)	NET DIFF. PRESS. (PSID)
719.6	71.0	.0603	63.110	63.525	63.317	-0.000	63.318
715.7	70.0	.0539	54.327	54.676	54.502	-0.000	54.502
715.7	69.7	.0473	46.159	46.143	46.151	-0.001	46.151
715.7	69.7	.0409	38.269	38.339	38.304	-0.001	38.304
715.7	70.1	.0345	30.727	30.802	30.765	-0.001	30.765
711.8	70.5	.0281	23.476	23.455	23.465	-0.001	23.465
711.8	71.3	.0215	16.804	16.811	16.808	-0.001	16.808
711.8	71.8	.0181	13.556	13.609	13.582	-0.001	13.583
711.8	72.5	.0145	10.249	10.239	10.244	-0.001	10.244
715.7	73.2	.0095	6.304	6.303	6.303	-0.001	6.304
715.7	74.2	.0092	6.13	6.189	6.159	-0.001	6.159
715.7	74.2	.0150	10.829	10.924	10.877	-0.001	10.877
715.7	74.1	.0188	14.310	14.409	14.360	-0.001	14.360
715.7	74.0	.0219	17.384	17.498	17.441	-0.001	17.441
715.7	73.6	.0284	23.882	23.971	23.926	-0.001	23.926
715.7	73.3	.0350	31.307	31.434	31.371	-0.001	31.371
715.7	72.8	.0411	38.617	38.800	38.709	-0.001	38.709
711.8	72.3	.0482	47.087	47.091	47.089	-0.000	47.089
711.8	71.7	.0549	55.457	55.940	55.698	-0.000	55.699
711.8	71.2	.0608	63.611	64.157	63.884	-0.000	63.884

TARE DIFF. PRESS = $-3.60000E-04 + -3.31610E-02$ (ACFM) + $6.33359E-01$ (ACFM)**2 + 0 (ACFM)**3.

TABLE 21
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN CONDITION - IMPACT/FLOW RATE VERSUS DIFFERENTIAL PRESSURE. FLOW RATE VERSUS DIFFERENTIAL PRESSURE DATA AFTER 100 HIGH PRESSURE GN₂ IMPACT CYCLES. TEST SPECIMEN (S/N 021) INLET PRESSURE 700 PSIA NOMINAL.

TEST NUMBER-6- PART-3F-

TEST DESCRIPTION-

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESSURE

PRESSURE		TEMPERATURE			FLOW RATE						
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	CFM	SCFM	GN ₂ KG/HR	GN ₂ LBS/HR	KG/SQ CM DIFFERENTIAL	PSID
50.594	719.6	294.9	21.7	71.0	83.6	.0603	2.947	5.802	12.791	4.4517	63.318
50.318	715.7	294.3	21.1	70.0	74.3	.0539	2.626	5.171	11.401	3.8319	54.502
50.318	715.7	294.1	20.9	69.7	65.2	.0473	2.305	4.538	10.006	3.2447	46.151
50.318	715.7	294.1	21.0	69.7	56.0	.0409	1.991	3.921	8.643	2.6931	38.304
50.318	715.7	294.3	21.1	70.1	47.0	.0345	1.681	3.310	7.297	2.1630	30.765
50.041	711.8	294.5	21.4	70.5	37.8	.0281	1.359	2.676	5.899	1.6498	23.465
50.041	711.8	295.0	21.8	71.3	28.8	.0215	1.039	2.045	4.508	1.1817	16.808
50.041	711.8	295.2	22.1	71.8	24.2	.0181	.873	1.718	3.789	.9549	13.589
50.041	711.8	295.7	22.5	72.5	19.4	.0145	.698	1.375	3.032	.7292	10.244
50.318	715.7	296.1	22.9	73.2	12.5	.0095	.461	.908	2.001	.4432	6.304
50.318	715.7	296.6	23.5	74.2	12.1	.0092	.447	.879	1.939	.4331	6.159
50.318	715.7	296.6	23.4	74.2	20.0	.0150	.723	1.424	3.140	.7647	10.877
50.318	715.7	296.6	23.4	74.1	25.1	.0188	.908	1.788	3.943	1.0096	14.360
50.318	715.7	296.5	23.3	74.0	29.3	.0219	1.056	2.080	4.586	1.2262	17.441
50.318	715.7	296.3	23.1	73.6	38.3	.0284	1.372	2.702	5.956	1.6822	23.926
50.318	715.7	296.1	22.9	73.3	47.5	.0350	1.692	3.332	7.347	2.2056	31.371
50.318	715.7	295.8	22.7	72.8	56.0	.0411	1.992	3.922	8.648	2.7215	38.709
50.041	711.8	295.5	22.4	72.3	65.5	.0482	2.325	4.577	10.091	3.3107	47.089
50.041	711.8	295.2	22.0	71.7	74.9	.0549	2.650	5.218	11.504	3.9160	55.699
50.041	711.8	294.9	21.8	71.2	83.2	.0608	2.937	5.784	12.752	4.4915	63.884
*****	*****	*****	*****	*****							
50.235	714.5	295.4	22.3	72.1							
.135	1.9	.8	.8	1.4	DEVIATIONS						

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 22
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 6 PART 3E

TEST DESCRIPTION

CLEAN CONDITION - IMPACT/FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. FLOW RATE VERSUS
DIFFERENTIAL PRESSURE DATA AFTER 100 HIGH
PRESSURE GN₂ IMPACT CYCLES. TEST SPECIMEN
(S/N 021) INLET PRESSURE 1,000 PSIA NOMINAL.

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE, (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.84	50.1	82.0	.91	47.9	85.9	15.9	83.9	.0420
.75	49.7	81.4	.81	47.9	85.6	15.9	83.5	.0375
.66	49.7	81.1	.70	48.3	85.2	15.9	83.1	.0327
.58	50.2	80.9	.61	49.3	85.0	15.9	83.0	.0291
.49	50.1	81.1	.50	49.3	85.0	15.9	83.0	.0243
.40	49.9	81.2	.40	49.3	84.9	15.9	83.1	.0194
.30	49.5	81.7	.30	49.1	85.2	15.9	83.5	.0146
.25	49.9	82.2	.25	49.5	85.4	15.9	83.8	.0124
.21	50.1	82.6	.21	49.9	85.7	15.9	84.2	.0102
.16	49.7	83.3	.16	49.3	86.0	15.9	84.6	.0079
.17	49.5	84.6	.16	49.3	86.5	15.9	85.6	.0080
.22	49.5	84.7	.22	49.1	86.8	15.9	85.8	.0107
.26	50.1	84.8	.26	49.9	86.9	15.9	85.8	.0127
.30	49.9	84.5	.30	49.5	86.7	15.9	85.6	.0148
.40	50.2	83.9	.40	49.9	86.5	15.9	85.2	.0198
.48	50.4	83.2	.50	49.9	86.2	15.9	84.7	.0242
.58	50.2	82.2	.60	49.1	85.6	15.9	83.9	.0289
.67	50.4	81.4	.70	49.1	85.1	15.9	83.3	.0335
.75	50.4	80.7	.80	48.7	84.6	15.9	82.6	.0379
.84	50.4	80.1	.91	48.3	83.9	15.9	82.0	.0424

TABLE 22
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 6 PART 3E TEST DESCRIPTION

CLEAN CONDITION - IMPACT/FLOW RATE VERSUS DIFFERENTIAL PRESSURE. FLOW RATE VERSUS DIFFERENTIAL PRESSURE DATA AFTER 100 HIGH PRESSURE GN2 IMPACT CYCLES. TEST SPECIMEN (S/N 021) INLET PRESSURE 1,000 PSIA NOMINAL

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TABE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
1015.9	83.9	.0420	45.946	45.769	45.858	-0.000	45.858
1015.9	83.5	.0375	39.689	39.877	39.748	-0.000	39.748
1015.9	83.1	.0327	33.315	33.367	33.341	-0.000	33.341
1015.9	83.0	.0291	28.622	28.612	28.612	-0.000	28.612
1015.9	83.0	.0243	22.777	22.798	22.764	-0.000	22.764
1015.9	83.1	.0194	17.324	17.324	17.324	-0.000	17.324
1015.9	83.5	.0146	12.167	12.128	12.148	-0.000	12.148
1015.9	83.8	.0124	9.908	9.904	9.906	-0.000	9.906
1015.9	84.2	.0102	7.880	7.852	7.866	-0.000	7.866
1015.9	84.6	.0079	5.852	5.859	5.855	-0.000	5.855
1015.9	85.6	.0080	5.852	5.859	5.855	-0.000	5.855
1015.9	85.8	.0117	8.343	8.365	8.354	-0.000	8.354
1015.9	85.8	.0127	10.197	10.246	10.222	-0.000	10.222
1015.9	85.6	.0148	12.341	12.413	12.377	-0.000	12.377
1015.9	85.2	.0198	17.614	17.667	17.640	-0.000	17.640
1015.9	84.7	.0242	22.712	22.758	22.735	-0.000	22.735
1015.9	83.9	.0289	28.564	28.660	28.612	-0.000	28.612
1015.9	83.3	.0335	34.532	34.631	34.581	-0.000	34.581
1015.9	82.6	.0379	40.326	40.440	40.383	-0.000	40.383
1015.9	82.0	.0424	46.873	47.032	46.953	-0.000	46.953

TARE DIFF. PRESS = -1.64000E-04 + -1.28930E-02 (ACFM) + 2.48070E+01 (ACFM) + 0 (ACFM) + 0

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 22
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 6 PART 3E TEST DESCRIPTION

CLEAN CONDITION - IMPACT/FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. FLOW RATE VERSUS
DIFFERENTIAL PRESSURE DATA AFTER 100 HIGH
PRESSURE GN₂ IMPACT CYCLES. TEST SPECIMEN
(S/N 021) INLET PRESSURE 1,000 PSIA NOMINAL.

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESS:

PRESSURE		TEMPERATURE			FLOW RATE						
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN ₂ KG/HR	GN ₂ LBS/HR	KG/SQ CM DIFFERENTIAL	PSID
71.423	1015.9	302.0	28.9	83.9	81.6	0.420	2.827	5.567	12.272	3.2282	45.858
71.423	1015.9	301.8	28.6	83.5	72.9	0.375	2.530	4.981	10.982	2.7946	39.746
71.423	1015.9	301.6	28.4	83.1	63.2	0.327	2.282	4.336	9.566	2.3441	33.341
71.423	1015.9	301.5	28.3	83.0	56.2	0.291	1.962	3.864	8.518	2.0117	28.613
71.423	1015.9	301.5	28.3	83.0	46.6	0.243	1.637	3.223	7.106	1.6005	22.746
71.423	1015.9	301.5	28.4	83.1	37.1	0.194	1.310	2.580	5.489	1.2180	17.324
71.423	1015.9	301.7	28.6	83.5	27.7	0.146	.986	1.942	4.282	.8541	12.148
71.423	1015.9	301.9	28.8	83.8	23.4	0.124	.835	1.644	3.624	.6965	9.906
71.423	1015.9	302.1	29.0	84.2	19.3	0.102	.688	1.354	2.985	.5520	7.866
71.423	1015.9	302.4	29.2	84.6	14.9	0.079	.533	1.049	2.313	.4117	5.856
71.423	1015.9	302.9	29.8	85.6	14.9	0.080	.534	1.051	2.317	.4117	5.856
71.423	1015.9	303.0	29.9	85.8	20.2	0.107	.721	1.412	3.129	.5874	8.358
71.423	1015.9	303.1	29.9	85.8	24.0	0.127	.850	1.674	3.491	.7187	10.222
71.423	1015.9	303.0	29.8	85.6	28.0	0.148	.996	1.960	4.322	.8702	12.377
71.423	1015.9	302.7	29.6	85.2	37.7	0.198	1.329	2.617	5.770	1.2402	17.640
71.423	1015.9	302.4	29.3	84.7	46.3	0.242	1.628	3.205	7.066	1.5985	22.735
71.423	1015.9	302.0	28.8	83.9	55.3	0.289	1.943	3.827	8.436	2.0116	28.612
71.423	1015.9	301.6	28.5	83.3	64.9	0.335	2.262	4.453	9.818	2.4313	34.582
71.423	1015.9	301.3	28.1	82.6	73.4	0.379	2.556	5.033	11.095	2.8393	40.384
71.423	1015.9	300.9	27.8	82.0	82.5	0.424	2.868	5.646	12.448	3.3011	46.959
71.423	1015.9	302.1	28.9	84.0							
0	.0	.5	.5	.9	DEVIATIONS						

TABLE 23
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE. DATA ACQUIRED AFTER THE ADDITION OF 7.9 MG OF SYNTHETIC CONTAMINANT AND PRIOR TO THE GM₂ IMPACT CYCLES. TEST SPECIMEN (S/N 027) INLET PRESSURE = 415 PSIA (NOMINAL).

TEST NUMBER 10 PART 27C TEST DESCRIPTION

00.0

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS:

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG. TEMP (DEG. F)	AVG. FLOW RATE (ACFM)
.65	50.5	69.9	.66	49.2	70.8	414.3	70.3	.0784
.60	50.5	69.9	.61	49.2	70.9	413.7	70.4	.0729
.50	50.5	69.8	.50	49.5	70.9	413.7	70.3	.0607
.41	50.1	69.8	.40	49.3	70.9	413.7	70.3	.0491
.31	50.5	69.9	.30	49.9	71.2	413.7	70.5	.0371
.26	50.3	69.9	.25	49.9	71.2	413.7	70.5	.0307
.21	50.1	70.0	.20	49.9	71.2	413.7	70.6	.0250
.14	51.1	70.2	.13	50.5	71.4	413.7	70.8	.0165
.14	50.3	70.4	.13	49.9	71.7	413.7	71.0	.0162
.22	49.7	70.4	.21	49.3	71.7	413.7	71.0	.0258
.27	49.9	70.3	.26	49.5	71.6	413.7	70.9	.0315
.31	49.9	70.1	.31	49.3	71.6	413.7	70.9	.0374
.41	50.1	69.9	.40	49.3	71.4	413.0	70.6	.0488
.50	50.1	69.7	.51	49.0	71.3	413.0	70.5	.0607
.59	50.3	69.7	.60	49.0	71.1	412.4	70.4	.0717
.62	50.5	69.9	.65	49.2	70.9	411.7	70.4	.0759

00.0

00.0

00.0

00.0

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 23
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE. DATA ACQUIRED AFTER THE ADDITION OF 7.9 MG OF SYNTHETIC CONTAMINANT AND PRIOR TO THE ON₂ IMPACT CYCLES. TEST SPECIMEN (S/N 027) INLET PRESSURE = 415 PSIA (NOMINAL).

TEST NUMBER 10 PART 27C

TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS. (PSID)	NET DIFF. PRESS. (PSID)
414.3	70.3	.0784	304.839	304.839	304.839	.001	304.838
413.7	70.4	.0729	255.157	255.157	255.157	.001	255.157
413.7	70.3	.0607	181.427	181.427	181.427	.000	181.426
413.7	70.3	.0491	132.378	132.378	132.378	.000	132.377
413.7	70.5	.0371	91.144	92.190	91.667	.000	91.666
413.7	70.5	.0307	71.900	72.571	72.236	.000	72.235
413.7	70.6	.0250	55.648	56.432	56.040	.000	56.039
413.7	70.8	.0165	34.827	35.082	34.954	=0.000	34.954
413.7	71.0	.0162	34.189	34.333	34.261	=0.000	34.260
413.7	71.0	.0258	58.030	58.964	58.497	.000	58.496
413.7	70.9	.0315	74.384	75.419	74.901	.000	74.901
413.7	70.9	.0374	92.582	93.772	93.177	.000	93.176
413.0	70.6	.0488	133.960	133.960	133.960	.000	133.959
413.0	70.5	.0607	186.173	186.173	186.173	.000	186.172
412.7	70.4	.0717	253.259	253.259	253.259	.001	253.258
411.7	70.4	.0769	303.257	303.257	303.257	.001	303.256

TARE DIFF. PRESS = -3.40000E-05 + -4.44000E-04 (ACFM) + 1.50933E-01 (ACFM)**2 + 0 (ACFM)**3

1711

1711

1711

1711

1711

TABLE 23
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION -- FLOW RATE VERSUS DIFFERENTIAL PRESSURE. DATA ACQUIRED AFTER THE ADDITION OF 7.9 MG OF SYNTHETIC CONTAMINANT AND PRIOR TO THE GN₂ IMPACT CYCLES. TEST SPECIMEN (S/N 027) INLET PRESSURE = 415 PSIA (NOMINAL).

TEST NUMBER 10 PART 27C TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESS:

PRESSURE TEMPERATURE FLOW RATE

PRESSURE		TEMPERATURE			FLOW RATE						
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID
29.128	414.2	294.5	21.3	70.3	62.6	.0784	2.210	4.351	9.892	21.4322	304.838
29.083	413.1	294.5	21.3	70.4	58.1	.0729	2.051	4.038	8.902	17.9393	255.157
29.083	413.1	294.5	21.3	70.3	48.3	.0607	1.709	3.359	7.406	12.7555	181.426
29.083	413.1	294.5	21.3	70.3	39.1	.0491	1.381	2.719	5.995	9.3070	132.377
29.083	413.1	294.6	21.4	70.5	29.5	.0371	1.043	2.054	4.528	6.4448	91.666
29.083	413.1	294.6	21.4	70.5	24.4	.0307	.862	1.698	3.743	5.0786	72.225
29.083	413.1	294.6	21.4	70.6	19.9	.0250	.702	1.382	3.047	3.9329	56.032
29.083	413.1	294.7	21.6	70.8	13.2	.0165	.465	.915	2.017	2.4575	34.954
29.083	413.1	294.8	21.7	71.0	12.9	.0162	.455	.897	1.977	2.4087	34.260
29.083	413.1	294.8	21.7	71.0	20.5	.0258	.723	1.424	3.140	4.1127	58.496
29.083	413.1	294.8	21.6	70.9	25.0	.0315	.884	1.740	3.836	5.2660	74.901
29.083	413.1	294.8	21.6	70.9	29.7	.0374	1.051	2.069	4.561	6.5509	93.175
29.037	413.0	294.6	21.5	70.6	38.8	.0488	1.369	2.695	5.942	9.4183	133.959
29.037	413.0	294.6	21.4	70.5	48.3	.0607	1.704	3.355	7.397	13.0892	186.172
28.992	412.4	294.5	21.3	70.4	56.9	.0717	2.011	3.954	8.729	17.8058	253.258
28.946	411.1	294.5	21.3	70.4	60.9	.0769	2.151	4.236	9.338	21.3210	303.256
*****	*****	*****	*****	*****							
29.066	413.4	294.6	21.4	70.6							

.031 .4 .1 .1 .2 DEVIATIONS

09

08

08

08

08

9
5

TABLE 24
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE. DATA ACQUIRED AFTER THE ADDITION OF 7.9 MG OF SYNTHETIC CONTAMINANT AND PRIOR TO THE GM₂ IMPACT CYCLES. TEST SPECIMEN (S/N 027) INLET PRESSURE = 1000 PSIA (NOMINAL).

TEST NUMBER 10 PART 270 TEST DESCRIPTION

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS:

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.86	70.1	65.6	.90	47.8	70.2	1013.2	67.9	.0426
.78	70.2	64.0	.81	48.4	69.2	1013.2	66.6	.0387
.69	70.4	63.5	.70	49.0	68.7	1013.2	66.1	.0341
.60	49.9	63.2	.60	48.8	68.4	1013.2	65.8	.0299
.51	70.4	63.1	.50	49.5	68.3	1013.2	65.7	.0249
.41	49.9	63.3	.40	49.2	68.5	1013.2	65.9	.0199
.31	70.4	63.8	.30	49.9	68.7	1013.2	66.2	.0152
.26	70.2	64.2	.25	49.9	68.9	1013.2	66.6	.0127
.22	70.1	64.7	.21	49.9	69.2	1017.2	66.9	.0104
.15	70.2	65.4	.13	49.9	69.5	1017.2	67.4	.0070
.15	70.4	66.6	.13	50.1	70.2	1017.2	68.4	.0070
.22	49.9	66.5	.21	49.5	70.1	1017.2	68.3	.0105
.27	49.7	66.3	.26	49.3	70.0	1017.2	68.2	.0130
.32	70.1	65.9	.31	49.5	69.9	1017.2	67.9	.0154
.42	49.9	65.1	.41	49.2	69.5	1017.2	67.3	.0201
.50	70.4	63.8	.50	49.5	68.7	1017.2	66.3	.0247
.60	70.1	63.0	.60	49.0	68.2	1017.2	65.6	.0299
.69	70.2	62.1	.70	48.8	67.5	1017.2	64.8	.0338
.78	49.7	64.9	.81	48.0	66.3	1013.2	63.6	.0381
.87	70.1	64.2	.91	48.0	65.4	1013.2	62.8	.0430

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 24
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE, DATA ACQUIRED AFTER THE ADDITION OF 7.9 MG OF SYNTHETIC CONTAMINANT AND PRIOR TO THE GN_2 IMPACT CYCLES. TEST SPECIMEN (S/N 027) INLET PRESSURE = 1000 PSIA (NOMINAL).

TEST NUMBER 10 PART 270 TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
1013.4	67.9	.0426	113.603	113.603	113.603	0.000	113.603
1013.4	66.6	.0387	100.628	100.628	100.628	0.000	100.628
1013.4	66.1	.0341	76.592	87.021	81.807	0.000	81.807
1013.4	65.8	.0293	62.171	72.149	67.160	0.000	67.160
1013.4	65.7	.0249	49.674	59.807	54.741	0.000	54.741
1013.4	65.9	.0199	35.624	45.568	40.596	0.000	40.596
1013.4	66.2	.0152	33.547	33.623	33.585	0.000	33.585
1013.4	66.6	.0127	27.464	27.467	27.465	0.000	27.465
1017.4	66.9	.0104	21.959	22.011	21.985	0.000	21.985
1017.4	67.4	.0070	13.964	13.989	13.976	0.000	13.976
1017.4	68.4	.0070	13.906	13.989	13.947	0.000	13.947
1017.4	68.3	.0105	22.017	22.183	22.100	0.000	22.100
1017.4	68.2	.0130	28.101	28.329	28.215	0.000	28.215
1017.4	67.9	.0154	38.133	34.199	36.166	0.000	36.166
1017.4	67.3	.0201	50.552	46.517	48.534	0.000	48.534
1017.4	66.3	.0247	63.166	59.491	61.328	0.000	61.328
1017.4	65.6	.0293	76.105	72.465	74.285	0.000	74.285
1017.4	64.8	.0338	89.397	85.389	87.893	0.000	87.893
1013.2	63.6	.0381	99.996	99.996	99.996	0.000	99.996
1013.2	62.8	.0430	116.451	116.451	116.451	0.000	116.451

TARE DIFF. PRESS = -1.64000E-04 + -1.26930E-02 (ACFM) + 2.48070E+01 (ACFM)**2 + 0 (ACFM)**3

TABLE 24
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE. DATA ACQUIRED AFTER THE ADDITION OF 7.9 MG OF SYNTHETIC CONTAMINANT AND PRIOR TO THE G_{N2} IMPACT CYCLES. TEST SPECIMEN (S/N 027) INLET PRESSURE = 1000 PSIA (NOMINAL).

TEST NUMBER 10 PART 270 TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS											NET DIFFERENTIAL PRESS.	
*****											*****	
PRESSURE		TEMPERATURE			FLOW RATE							
*****											*****	
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	CCM	SCCM	GN2 KG/HR	GN2 LB5/HR	KG/SQ CM DIFFERENTIAL	PSID	
71.235	1013.6	293.1	19.9	67.9	83.5	9426	2.950	5.808	12.804	7.9871	113.603	
71.235	1013.6	292.4	19.2	66.6	76.0	9387	2.685	5.286	11.653	7.0749	100.629	
71.235	1013.6	292.1	19.0	66.1	67.1	9341	2.370	4.666	10.288	5.7516	81.807	
71.235	1013.6	291.9	18.8	65.8	57.6	9293	2.033	4.004	8.826	4.7218	67.160	
71.235	1013.6	291.9	18.7	65.7	49.1	9249	1.733	3.412	7.522	3.8487	54.741	
71.235	1013.6	292.0	18.8	65.9	39.0	9199	1.379	2.715	5.986	2.8542	40.596	
71.235	1013.6	292.2	19.4	66.2	29.8	9152	1.053	2.073	4.569	2.3613	33.585	
71.235	1013.6	292.4	19.2	66.6	25.0	9127	.962	1.736	3.828	1.9310	27.465	
71.514	1017.6	292.6	19.4	66.9	20.6	9104	.726	1.429	3.151	1.5467	21.985	
71.514	1017.6	292.9	19.7	67.4	13.7	9070	.484	.955	2.101	.9826	13.976	
71.514	1017.6	293.4	20.2	68.4	13.7	9070	.485	.955	2.105	.9806	13.947	
71.514	1017.6	293.3	20.2	68.3	20.7	9105	.731	1.440	3.175	1.5538	22.100	
71.514	1017.6	293.2	20.1	68.2	25.6	9130	.903	1.779	3.921	1.9837	28.215	
71.514	1017.6	293.1	19.9	67.9	30.3	9154	1.070	2.101	4.646	2.5427	35.166	
71.514	1017.6	292.8	19.6	67.3	39.6	9201	1.398	2.753	6.070	3.4123	48.535	
71.514	1017.6	292.2	19.1	66.3	49.8	9247	1.722	3.391	7.475	4.3118	61.329	
71.514	1017.6	291.8	18.7	65.6	57.8	9293	2.042	4.020	8.863	5.2228	74.285	
71.514	1017.6	291.4	18.2	64.8	66.9	9338	2.364	4.655	10.262	6.1795	87.893	
71.235	1013.6	290.7	17.6	63.6	75.3	9381	2.659	5.236	11.543	7.0304	99.996	
71.235	1013.6	290.3	17.1	62.8	85.1	9430	3.005	5.911	13.044	8.1873	116.051	
****	****	****	****	****								
71.375	1015.6	292.3	19.1	66.4								
.140	2.0	.6	.6	1.1	DEVIATIONS							

TABLE 25
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 1
DATE: 9-14-76

TEST NUMBER 10 PART 27F

TEST DESCRIPTION

CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE. DATA ACQUIRED AFTER THE ADDITION OF 7.9 MG OF SYNTHETIC CONTAMINANT AND AFTER 10 HIGH PRESSURE (10,000 PSIA NOMINAL) G₂ IMPACT CYCLES. TEST SPECIMEN TEST SPECIMEN INLET CONDITIONS

FLOWMETER CONDITIONS

(S/N 027) **INLET PRESSURE** 1000 PSIA (NOMINAL) **

FLOWMETER ONE			FLOWMETER TWO			PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)			
.85	49.9	62.6	.90	47.6	68.8	1011.9	66.2	.0421
.76	50.2	62.9	.81	48.3	68.1	1011.9	65.5	.0381
.66	50.2	62.5	.70	48.7	67.9	1011.9	65.2	.0333
.57	50.8	62.5	.59	49.5	67.8	1007.9	65.1	.0289
.49	50.2	62.8	.50	49.3	67.9	1007.9	65.4	.0245
.40	50.6	63.4	.40	49.9	68.2	1007.9	65.8	.0200
.30	50.2	63.4	.30	49.7	68.3	1007.9	65.8	.0149
.26	50.2	64.1	.25	49.7	69.7	1007.9	66.9	.0127
.21	50.2	65.4	.20	49.9	70.0	1007.9	67.7	.0103
.14	49.9	66.4	.13	49.5	69.7	1007.9	68.1	.0066
.14	49.9	66.8	.13	49.5	71.9	1011.9	69.4	.0066
.21	49.9	66.6	.20	49.5	72.3	1011.9	69.4	.0100
.26	50.1	66.3	.26	49.5	71.6	1011.9	69.0	.0129
.30	50.1	66.8	.30	49.7	70.2	1007.9	68.5	.0149
.40	49.7	66.6	.41	48.9	70.1	1007.9	68.4	.0197
.49	49.9	65.6	.50	48.9	69.6	1007.9	67.6	.0242
.57	50.1	64.3	.60	48.9	69.5	1007.9	66.9	.0287
.67	49.9	63.1	.71	48.3	69.4	1007.9	66.2	.0337
.75	49.9	62.3	.81	47.9	69.6	1007.9	66.0	.0379
.84	50.1	62.3	.91	47.8	68.6	1007.9	65.4	.0425

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 25
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 2
DATE: 9-14-76

TEST NUMBER		PART 27F		TEST DESCRIPTION			
TEST SPECIMEN INLET CONDITIONS				CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE. DATA ACQUIRED AFTER THE ADDITION OF 7.9 MG OF SYNTHETIC CONTAMINANT AND AFTER 10 HIGH PRESSURE (10,000 PSIA NOMINAL) GN2 IMPACT CYCLES. TEST SPECIMEN (S/N 027) INLET PRESSURE = 1000 PSIA (NOMINAL).			
AVG PRESSURE (PSIA)	TEMP (DEG. F)	AVG FLOW RATE (CFM)	PR SS DIFF. PRESS. PRIMARY (PSID)	SR SS DIFF. PRESS. SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
1011.9	86.2	421	292.659	292.659	292.659	0.000	292.659
1011.9	85.5	381	247.464	247.464	247.464	0.000	247.464
1011.9	85.2	333	197.529	197.529	197.529	0.000	197.529
1007.9	85.1	289	156.127	156.127	156.127	0.000	156.127
1007.9	85.4	245	120.414	120.414	120.414	0.000	120.414
1007.9	85.8	202	86.671	86.671	86.671	0.000	86.671
1007.9	85.8	149	56.617	56.617	56.617	0.000	56.617
1007.9	86.9	127	44.851	44.851	44.851	0.000	44.851
1007.9	87.7	103	32.972	32.972	32.972	0.000	32.972
1007.9	88.1	85	18.085	18.085	18.085	0.000	18.085
1011.9	89.4	66	17.942	18.112	18.027	0.000	18.027
1011.9	89.4	61	31.981	32.72	32.341	0.000	32.341
1011.9	89.6	52	46.675	47.091	46.675	0.000	46.675
1007.9	88.5	140	56.849	57.224	56.849	0.000	56.849
1007.9	88.4	197	86.643	87.545	86.642	0.000	86.642
1007.9	87.6	242	120.414	120.414	120.414	0.000	120.414
1007.9	86.9	27	156.759	156.759	156.759	0.000	156.759
1007.9	86.2	337	202.270	202.270	202.270	0.000	202.270
1007.9	86.0	379	246.832	246.832	246.832	0.000	246.832
1007.9	85.4	425	304.036	304.036	304.036	0.000	304.036

$$\text{TARE DIFF. PRESS} = -1.64000E-04 + -1.25934E-02 (\text{ACFM}) + 2.48070E-01 (\text{ACFM})^{**2} + 0 (\text{ACFM})^{**3}$$

TABLE 25
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 3
DATE: 9-14-76

TEST U: REP 10 PART 27F TEST DESCRIPTION CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE. DATA ACQUIRED AFTER THE ADDITION OF 7.9 MG OF SYNTHETIC CONTAMINANT AND AFTER 10 HIGH PRESSURE (10,000 PSIA NOMINAL) G₂ IMPACT CYCLES. TEST SPECIMEN (S/N 027) INLET PRESSURE = NET DIFFERENTIAL PRESS

TEST SPECIMEN INLET CONDITIONS

1000 PSIA (NOMINAL)

PRESSURE		TEMPERATURE			FLOW RATE						
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	CFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID
71.144	1011.9	292.1	19.4	66.2	74.9	.381	2.645	5.208	11.482	17.3985	247.464
71.144	1011.9	291.8	19.6	65.5	64.4	.333	2.311	4.551	10.432	13.8877	197.529
71.144	1011.9	291.6	19.7	65.2	76.7	.289	2.002	3.942	8.690	10.9768	156.127
70.865	1007.9	291.6	19.4	65.1	47.9	.245	1.691	3.334	7.342	8.4659	120.414
70.865	1007.9	291.7	19.5	65.4	39.1	.200	1.379	2.716	5.987	6.1465	87.424
70.865	1007.9	292.1	18.8	65.8	29.2	.149	1.031	2.031	4.478	4.0124	57.069
70.865	1007.9	292.5	19.4	66.9	24.7	.127	.873	1.720	3.791	3.1534	44.851
70.865	1007.9	293.0	19.8	67.7	21.1	.103	.708	1.395	3.075	2.3181	32.972
70.865	1007.9	293.2	20.1	68.1	12.8	.066	.454	.893	1.969	1.2715	18.085
71.144	1011.9	293.9	20.3	69.4	12.8	.066	.452	.891	1.964	1.2674	18.027
71.144	1011.9	294.4	21.8	69.4	19.6	.111	.692	1.363	3.004	2.2738	32.342
71.144	1011.9	293.7	20.5	69.1	25.3	.129	.892	1.757	3.874	3.2816	46.676
70.865	1007.9	293.5	20.3	68.5	28.9	.140	1.021	2.011	4.434	3.9969	56.849
70.865	1007.9	293.4	20.7	68.4	39.4	.197	1.355	2.668	5.883	6.0916	86.643
70.865	1007.9	292.9	19.8	67.6	47.2	.242	1.669	3.285	7.243	8.4659	120.414
70.865	1007.9	292.6	19.4	66.9	56.7	.287	1.978	3.894	8.585	11.0213	156.759
70.865	1007.9	292.2	19.0	66.2	65.8	.337	2.324	4.576	10.089	14.2210	202.270
70.865	1007.9	292.1	18.9	66.1	74.1	.379	2.617	5.152	11.358	17.3540	246.832
70.865	1007.9	291.7	18.6	65.4	77.3	.425	2.942	5.793	12.771	21.3759	304.037
****	****	****	****	****							
70.949	1009.4	292.6	19.4	66.9							
.117	1.1	.7	.7	1.3	DEVIATIONS						

TABLE 26. CONTAMINATED CONDITION -- FLOW RATE VERSUS DIFFERENTIAL PRESSURE, DATA ACQUIRED AFTER THE ADDITION OF 7.9 MG OF SYNTHETIC CONTAMINANT AND AFTER 10 HIGH PRESSURE (10,000 PSIA NOMINAL) GN₂ IMPACT CYCLES. TEST SPECIMEN (S/N 027) -- INLET PRESSURE -- 415 PSIA (NOMINAL).

TEST NUMBER 10 PART 276

TEST DESCRIPTION

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
------------------	-----------------	---------------	------------------	-----------------	---------------	-----------------	-------------------	----------------------

.38	49.9	73.7	.37	49.2	75.3	413.8	74.5	.0449
.35	50.4	73.8	.35	49.9	75.5	413.1	74.6	.0428
.30	50.6	74.3	.30	50.1	75.7	413.1	75.0	.0367
.26	50.2	74.2	.26	49.9	75.1	413.1	75.0	.0315
.21	50.4	74.4	.21	50.1	76.0	413.1	75.2	.0254
.14	50.2	75.5	.13	49.9	76.3	413.1	75.9	.0167
.14	50.4	75.9	.13	50.1	76.6	413.1	76.3	.0167
.21	49.7	75.7	.21	49.3	76.6	413.1	76.2	.0250
.26	49.7	75.8	.25	49.3	76.8	412.5	76.3	.0305
.31	49.9	75.7	.31	49.3	76.8	412.5	76.3	.0373
.35	49.9	75.8	.35	49.2	76.9	411.8	76.3	.0425
.37	49.9	75.9	.37	49.2	77.0	411.8	76.4	.0441

TABLE 26. CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE, DATA ACQUIRED AFTER THE ADDITION OF 7.9 MG OF SYNTHETIC CONTAMINANT AND AFTER 10 HIGH PRESSURE (10,000 PSIA NOMINAL) GN₂ IMPACT CYCLES. TEST SPECIMEN (S/N-027) INLET PRESSURE = 415 PSIA (NOMINAL).

TEST NUMBER 10 PART 276

TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
413.8	74.5	.0449	303.931	303.931	303.931	.000	303.931
413.1	74.6	.0428	259.685	259.685	259.685	.000	259.685
413.1	75.0	.0367	180.357	180.357	180.357	.000	180.357
413.1	75.0	.0315	133.898	133.898	133.898	.000	133.898
413.1	75.2	.0254	91.487	93.128	92.308	.000	92.308
413.1	75.9	.0167	49.137	49.830	49.483	.000	49.483
413.1	76.3	.0167	48.512	49.198	48.855	.000	48.855
413.1	76.2	.0250	89.294	90.916	90.060	.000	90.060
412.9	76.3	.0305	128.841	128.841	128.841	.000	128.841
412.9	76.3	.0373	190.154	190.154	190.154	.000	190.154
411.8	76.3	.0425	257.788	257.788	257.788	.000	257.788
411.8	76.4	.0441	291.921	291.921	291.921	.000	291.921

$$\text{TARE DIFF. PRESS} = -3.40000\text{E-05} + -4.44000\text{E-04 (ACFM)} + 1.50933\text{E-01 (ACFM)**2} + 0 \text{ (ACFM)**3}$$

ORIGINAL PAGE IS OF POOR QUALITY

TABLE 26
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION -- FLOW RATE VERSUS DIFFERENTIAL PRESSURE. DATA ACQUIRED AFTER THE ADDITION OF 7.9 MG OF SYNTHETIC CONTAMINANT AND AFTER 10 HIGH PRESSURE (10,000 PSIA NOMINAL) GN2 IMPACT CYCLES. TEST SPECIMEN INLET PRESSURE = 415 (NOMINAL).

TEST NUMBER 10 PART 27G

TEST DESCRIPTION(S/N 027)

10

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESSURE

PRESSURE		TEMPERATURE			FLOW RATE							NET DIFFERENTIAL PRESSURE	
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/MIN	SCFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSIA		
29.092	413.9	296.8	23.6	74.5	35.4	.449	1.252	2.465	5.434	21.3685	303.931		
29.046	413.1	296.8	23.7	74.6	33.8	.428	1.194	2.351	5.182	18.2576	259.684		
29.046	413.1	297.1	23.9	75.0	28.9	.367	1.022	2.013	4.437	12.6803	180.357		
29.046	413.1	297.1	23.9	75.0	24.8	.315	.877	1.726	3.805	9.4140	133.888		
29.046	413.1	297.1	24.0	75.2	20.0	.254	.707	1.393	3.071	6.4899	92.308		
29.046	413.1	297.6	24.4	75.9	13.2	.167	.465	.915	2.018	3.4790	49.483		
29.046	413.1	297.8	24.6	76.3	13.1	.167	.463	.913	2.012	3.4348	48.855		
29.046	413.1	297.7	24.5	76.2	19.7	.250	.695	1.369	3.019	6.3318	90.860		
29.001	412.9	297.8	24.6	76.3	23.9	.305	.845	1.663	3.667	9.0584	128.841		
29.001	412.9	297.8	24.6	76.3	29.3	.373	1.035	2.039	4.494	13.3692	190.154		
28.955	411.8	297.8	24.6	76.3	33.3	.425	1.177	2.317	5.109	18.1243	257.788		
28.955	411.8	297.8	24.7	76.4	34.6	.441	1.222	2.406	5.305	20.5241	291.921		
29.028	412.9	297.4	24.3	75.7									
.033	.0	.4	.4	.7	DEVIATIONS								

10

TABLE 27
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE. DATA ACQUIRED AFTER THE ADDITION OF 15.8 MG OF SYNTHETIC CONTAMINANT AND AFTER 20 HIGH PRESSURE (10,000 PSIA NOMINAL) GN₂ IMPACT CYCLES. TEST SPECIMEN (S/N 027) INLET PRESSURE = 1000 PSIA (NOMINAL).

TEST NUMBER 1 PART 27 TEST DESCRIPTION

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.20	56.4	72.1	.19	53.1	74.1	1.15.9	73.1	.0097
.18	54.4	72.2	.18	51.2	74.1	1.15.9	73.0	.0088
.16	50.6	72.1	.15	50.2	74.3	1.15.9	73.1	.0078
.14	50.4	72.1	.13	50.1	74.4	1.15.9	73.3	.0068
.12	50.2	72.4	.11	49.9	74.5	1.15.9	73.5	.0057
.12	50.4	72.5	.11	51.2	73.5	1.15.9	73.0	.0058
.14	49.7	72.1	.13	49.5	73.5	1.15.9	72.8	.0067
.16	56.2	72.1	.15	49.9	75.1	1.15.9	73.5	.0078
.18	49.7	71.8	.18	49.3	74.8	1.15.9	73.3	.0088
.19	56.1	71.8	.19	49.7	73.3	1.11.9	72.5	.0094

TABLE 27
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE. DATA ACQUIRED AFTER THE ADDITION OF 15.8 MG OF SYNTHETIC CONTAMINANT AND AFTER 20 HIGH PRESSURE (10,000 PSIA NOMINAL) GN2 IMPACT CYCLES. TEST SPECIMEN (S/N 027) INLET PRESSURE = 1000 PSIA (NOMINAL).

TEST NUMBER 10 PART 271 TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

TEST NUMBER	TEST DESCRIPTION	TEST SPECIMEN INLET CONDITIONS	AVG PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
1015.9			1015.9	73.1	.0097	302.772	302.772	302.772	-0.000	302.772
1015.9			1015.9	73.0	.0088	260.422	260.422	260.422	-0.000	260.422
1015.9			1015.9	73.1	.0078	214.595	214.595	214.595	-0.000	214.595
1015.9			1015.9	73.3	.0068	173.825	173.825	173.825	-0.000	173.825
1015.9			1015.9	73.5	.0057	134.004	134.004	134.004	-0.000	134.004
1015.9			1015.9	73.0	.0058	134.635	134.635	134.635	-0.000	134.635
1015.9			1015.9	72.8	.0067	168.769	168.769	168.769	-0.000	168.769
1015.9			1015.9	73.5	.0078	210.171	210.171	210.171	-0.000	210.171
1015.9			1015.9	73.3	.0088	259.474	259.474	259.474	-0.000	259.474
1011.9			1011.9	72.5	.0094	290.446	290.446	290.446	-0.000	290.446

NET DIFF. PRESS = -1.64000E-04 + -1.28930E-02 (ACFM) + 2.48070E-01 (ACFM)**2 + 0 (ACFM)**3

TABLE 27
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE. DATA ACQUIRED AFTER THE ADDITION OF 15.8 MG OF SYNTHETIC CONTAMINANT AND AFTER 20 HIGH PRESSURE (10,000 PSIA NOMINAL) GN2 IMPACT CYCLES. TEST SPECIMEN (S/N 027) INLET PRESSURE = 1000 PSIA (NOMINAL).

TEST NUMBER 10 PART 271 TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESS

PRESSURE		TEMPERATURE			FLOW RATE						
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/MIN	CFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID
71.423	1015.4	296.1	22.8	73.1	18.9	0.097	0.666	1.311	2.891	21.2870	302.772
71.423	1015.4	296.2	22.8	73.1	17.2	0.088	0.607	1.194	2.633	18.3095	260.422
71.423	1015.4	296.1	22.9	73.1	15.1	0.078	0.535	1.053	2.321	15.0876	214.596
71.423	1015.4	296.1	22.9	73.3	13.3	0.068	0.469	0.923	2.034	12.2212	173.886
71.423	1015.4	296.2	23.1	73.5	11.2	0.057	0.394	0.775	1.709	9.4214	134.084
71.423	1015.4	295.9	22.8	73.1	11.2	0.058	0.396	0.780	1.720	9.4658	134.696
71.423	1015.4	295.8	22.6	72.3	13.1	0.067	0.463	0.911	2.008	11.8656	168.769
71.423	1015.4	296.2	23.1	73.5	15.1	0.078	0.533	1.050	2.314	14.7765	210.171
71.423	1015.4	296.1	22.9	73.3	17.0	0.088	0.602	1.185	2.611	18.2428	259.474
71.144	1011.4	295.7	22.5	72.5	18.3	0.094	0.647	1.275	2.810	20.4204	290.447
71.395	1015.4	296.1	22.8	73.1							

DEVIATIONS

ORIGINAL PAGE IS
OF POOR QUALITY

PAGE: 1
DATE: 9-10-76

TABLE 28
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 11 PART 22A TEST DESCRIPTION

CONTAMINATED CONDITION - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. TOTAL OR 16.3 MG
OF SYNTHETIC CONTAMINANT ADDED. TEST
SPECIMEN (S/N 022) INLET PRESSURE = 1000
PSIA (NOMINAL).

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.87	50.2	82.4	.91	48.0	86.5	1013.2	84.4	.0433
.78	50.2	81.2	.81	48.4	85.8	1013.2	83.5	.0388
.70	50.2	80.5	.71	48.6	85.2	1009.2	82.8	.0344
.59	50.4	80.2	.60	49.2	84.9	1009.2	82.5	.0295
.50	50.1	80.2	.50	49.0	84.9	1009.2	82.5	.0245
.41	50.2	80.3	.41	49.5	84.9	1009.2	82.6	.0201
.31	50.2	80.7	.31	49.5	85.0	1009.2	82.8	.0151
.26	50.2	80.9	.26	49.7	85.1	1009.2	83.0	.0129
.21	50.6	81.2	.21	50.3	85.2	1009.2	83.2	.0105
.14	50.1	81.9	.14	49.5	85.6	1009.2	83.7	.0069
.14	50.6	82.5	.14	50.1	85.8	1009.2	84.1	.0070
.21	49.7	82.3	.21	49.2	85.7	1009.2	84.0	.0104
.26	49.7	82.4	.26	49.2	85.6	1009.2	83.8	.0129
.31	50.1	81.6	.31	49.3	85.4	1009.2	83.5	.0152
.40	49.9	80.7	.40	49.2	84.9	1005.3	82.8	.0197
.50	49.9	79.8	.50	49.0	84.4	1005.3	82.1	.0246
.59	50.4	78.8	.61	49.2	83.7	1005.3	81.2	.0296
.68	50.1	79.1	.71	48.4	83.0	1005.3	80.5	.0340
.76	49.9	77.2	.80	48.0	82.3	1001.3	79.7	.0381
.85	50.2	76.4	.92	48.0	81.4	1001.3	78.9	.0433

TABLE 28
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE, TOTAL OF 16.3 MG
OF SYNTHETIC CONTAMINANT ADDED. TEST
SPECIMEN (S/N 022) INLET PRESSURE = 1000
PSIA (NOMINAL).

TEST NUMBER 11 PART 22A TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
1013.2	84.4	.0433	133.205	133.205	133.205	-0.000	133.205
1013.2	83.5	.0388	115.213	115.213	115.213	-0.000	115.213
1009.2	82.8	.0344	99.430	99.430	99.430	-0.000	99.430
1009.2	82.5	.0295	82.157	82.71	82.429	-0.000	82.429
1009.2	82.5	.0245	65.243	65.971	65.607	-0.000	65.607
1009.2	82.6	.0201	51.604	52.398	52.001	-0.000	52.001
1009.2	82.8	.0151	37.884	38.081	37.982	-0.000	37.982
1009.2	83.0	.0129	31.345	31.472	31.408	-0.000	31.408
1009.2	83.2	.0115	24.632	24.715	24.668	-0.000	24.668
1009.2	83.7	.0069	15.374	15.381	15.377	-0.000	15.378
1009.2	84.1	.0070	15.675	15.667	15.636	-0.000	15.636
1009.2	84.0	.0104	24.401	24.533	24.467	-0.000	24.467
1009.2	83.8	.0129	31.461	31.644	31.552	-0.000	31.553
1009.2	83.5	.0152	38.058	38.253	38.155	-0.000	38.155
1005.2	82.8	.0197	50.728	51.451	51.089	-0.000	51.090
1005.2	82.1	.0246	66.243	66.918	66.581	-0.000	66.581
1005.2	81.2	.0295	83.513	84.279	83.896	-0.000	83.896
1005.2	80.5	.0340	100.062	100.062	100.062	-0.000	100.062
1001.2	79.7	.0381	115.528	115.528	115.528	-0.000	115.529
1001.2	78.9	.0433	137.308	137.308	137.308	-0.000	137.309

TARE DIFF. PRESS = $-1.64000E-04 + -1.26930E-02$ (ACFM) + $2.48070E-01$ (ACFM)**2 + 0 (ACFM)**3

TABLE 28
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. TOTAL OF 16.3 MG
OF SYNTHETIC CONTAMINANT ADDED. TEST
SPECIMEN (S/N 022) INLET PRESSURE = 1000
PSIA (NOMINAL).

TEST NUMBER 11 PART 22A TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESSURE

PRESSURE		TEMPERATURE			FLOW RATE					NET DIFFERENTIAL PRESSURE		
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID	
71.235	1013.2	302.3	29.1	84.4	82.2	.0433	2.904	5.718	12.605	9.3653	133.205	
71.235	1013.2	301.8	28.6	83.5	73.9	.0388	2.605	5.130	11.310	8.1003	115.213	
70.956	1009.2	301.4	28.2	82.8	65.3	.0344	2.308	4.544	10.018	6.9907	99.430	
70.956	1009.2	301.2	28.1	82.5	56.1	.0295	1.979	3.898	8.593	5.7954	82.429	
70.956	1009.2	301.2	28.1	82.5	46.5	.0245	1.642	3.232	7.126	4.6127	65.607	
70.956	1009.2	301.3	28.1	82.6	38.1	.0201	1.345	2.948	5.838	3.6560	52.001	
70.956	1009.2	301.4	28.2	82.8	28.7	.0151	1.015	1.999	4.408	2.6704	37.983	
70.956	1009.2	301.5	28.4	83.0	24.4	.0129	.862	1.698	3.744	2.2082	31.409	
70.956	1009.2	301.6	28.5	83.2	20.0	.0105	.706	1.389	3.063	1.7344	24.669	
70.956	1009.2	301.9	28.7	83.7	13.2	.0069	.464	.915	2.016	1.0812	15.378	
70.956	1009.2	302.1	29.0	84.1	13.3	.0070	.469	.924	2.038	1.0993	15.636	
70.956	1009.2	302.1	28.9	84.0	19.7	.0104	.696	1.370	3.019	1.7202	24.467	
70.956	1009.2	301.9	28.8	83.8	24.5	.0129	.865	1.704	3.756	2.2184	31.953	
70.956	1009.2	301.8	28.6	83.5	28.8	.0152	1.016	2.000	4.409	2.6826	38.156	
70.677	1005.2	301.4	28.2	82.8	37.2	.0197	1.315	2.588	5.706	3.5920	51.090	
70.677	1005.2	301.0	27.8	82.1	46.6	.0246	1.645	3.240	7.142	4.6811	66.581	
70.677	1005.2	300.5	27.3	81.2	56.2	.0296	1.985	3.908	8.615	5.8985	83.896	
70.677	1005.2	300.1	27.0	80.5	64.5	.0348	2.278	4.486	9.889	7.0350	100.062	
70.398	1001.2	299.7	26.5	79.7	72.2	.0341	2.550	5.021	11.069	8.1225	115.529	
70.398	1001.2	299.2	26.1	78.9	82.0	.0433	2.897	5.705	12.577	9.6538	137.309	
****	****	****	****	****								
70.872	1008.0	301.3	28.1	82.6								
.173	2.5	.6	.6	1.1	DEVIATIONS							

ORIGINAL PAGE IS
OF POOR QUALITY

PAGE: 1
DATE: 9-10-76

TABLE 29
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST UPPER 11 PART 228 TEST DESCRIPTION

CONTAMINATED CONDITION - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE, TOTAL OF 16.3 MG
OF SYNTHETIC CONTAMINANT ADDED. TEST
SPECIMEN (S/N 022) INLET PRESSURE = 415
PSIA (NOMINAL).

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)
.58	49.9	72.9	.60	48.8	74.3
.49	50.2	72.8	.51	49.3	74.3
.40	50.4	72.8	.40	49.9	74.5
.31	50.6	73.0	.30	50.1	74.6
.26	49.7	73.1	.25	49.3	74.7
.21	50.2	73.1	.20	49.9	74.8
.14	50.4	73.5	.13	50.3	75.0
.14	49.9	73.4	.13	49.7	75.4
.22	49.9	73.7	.22	49.5	75.4
.27	49.7	73.0	.26	49.3	75.4
.32	50.2	73.5	.31	49.7	75.3
.41	50.1	73.3	.41	49.3	75.2
.50	50.1	73.1	.51	49.2	74.8
.57	50.6	73.1	.59	49.5	74.2
.57	50.6	73.3	.59	49.5	73.6

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
417.7	73.6	.0702
417.0	73.6	.0597
416.4	73.7	.0485
416.4	73.8	.0368
415.7	73.9	.0304
415.7	74.0	.0250
415.7	74.3	.0164
415.7	74.6	.0161
415.1	74.5	.0265
415.1	74.5	.0317
415.1	74.4	.0378
413.8	74.2	.0488
413.1	73.9	.0602
412.5	73.6	.0703
412.5	73.6	.0703

ORIGINAL PAGE IS
OF POOR QUALITY

PAGE: 2
DATE: 9-10-76

TABLE 29
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. TOTAL OF 16.3 MG
OF SYNTHETIC CONTAMINANT ADDED. TEST
SPECIMEN (S/N 022) INLET PRESSURE = 415
PSIA (NOMINAL).

TEST NUMBER 11 PART 228 TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

AVG PRESSURE (PSIA)	AVG TEMP (DEG. F)	VG FLOW RATE (CFM)	GRSS DIFF. PRESS PRIMARY (PSID)	GR SS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
417.1	73.6	.072	313.240	313.246	303.246	.001	303.246
417.0	73.6	.0597	211.909	211.909	211.909	.000	211.908
416.4	73.7	.0485	150.912	150.912	150.912	.000	150.911
416.4	73.8	.0368	102.557	102.557	102.557	.000	102.556
415.1	73.9	.0304	79.881	79.882	79.882	.000	79.888
415.1	74.0	.0250	61.616	61.616	61.616	.000	61.615
415.1	74.3	.0164	37.856	37.898	37.852	-0.000	37.851
415.1	74.6	.0101	37.111	37.322	37.215	-0.000	37.215
415.4	74.5	.0255	67.278	67.476	67.277	.000	67.276
415.1	74.5	.0317	83.980	84.542	84.264	.000	84.263
415.1	74.4	.0378	106.660	106.666	106.666	.000	106.665
413.0	74.2	.0488	152.492	152.492	152.492	.000	152.492
413.4	73.9	.062	215.385	215.385	215.385	.000	215.385
412.5	73.6	.073	307.039	307.039	307.039	.001	307.038
412.5	73.6	.073	-0.001		-0.000	.001	-0.001

TARE DIFF. PRESS = -3.4000E-05 + -4.4400E-04 (ACF) + 1.50933E-01 (ACF)**2 +

(ACF)**3

TABLE 29
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE, TOTAL OF 16.3 MG
OF SYNTHETIC CONTAMINANT ADDED. TEST
SPECIMEN (S/N 022) INLET PRESSURE = 415
PSIA (NOMINAL).

TEST NUMBER 11 PART 22B TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESS

PRESSURE		TEMPERATURE			FLOW RATE							NET DIFFERENTIAL PRESS	
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GM2 KG/HR	GM2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID		
29.365	417.1	296.3	23.1	73.6	56.1	.0732	1.982	3.905	8.605	21.3203	303.246		
29.320	417.0	296.2	23.1	73.6	47.6	.0597	1.682	3.316	7.301	14.9986	211.908		
29.274	416.4	296.3	23.1	73.7	38.6	.0485	1.364	2.687	5.920	10.6101	150.911		
29.274	416.4	296.4	23.2	73.8	29.3	.0360	1.034	2.037	4.487	7.2104	102.556		
29.229	415.1	296.4	23.3	73.9	24.2	.0314	.855	1.683	3.710	5.6167	79.888		
29.229	415.1	296.5	23.3	74.0	19.8	.0253	.701	1.380	3.043	4.3320	61.615		
29.229	415.1	296.6	23.5	74.3	13.0	.0194	.461	.907	2.000	2.6612	37.851		
29.229	415.1	296.8	23.7	74.6	12.8	.0161	.452	.890	1.963	2.6165	37.215		
29.183	415.1	296.8	23.6	74.5	21.1	.0265	.743	1.464	3.227	4.7300	67.276		
29.183	415.1	296.8	23.6	74.5	25.1	.0317	.888	1.745	3.853	5.9243	84.263		
29.183	415.1	296.7	23.5	74.4	30.0	.0373	1.059	2.087	4.597	7.4993	106.665		
29.092	413.8	296.6	23.5	74.2	38.6	.0488	1.364	2.687	5.920	10.7212	152.492		
29.046	413.1	296.5	23.3	73.9	47.6	.0632	1.680	3.308	7.292	15.1431	215.385		
29.001	412.7	296.3	23.1	73.6	55.5	.0703	1.960	3.859	8.508	21.5869	307.038		
29.001	412.7	296.2	23.1	73.6	55.5	.0703	1.960	3.859	8.509	-0.0001	-0.901		
****	****	****	****	****									
29.189	415.2	296.5	23.3	74.0									
.085	1.2	.2	.2	.3	DEVIATIONS								

ORIGINAL PAGE IS
OF POOR QUALITY

PAGE: 1
DATE: 9-10-76

TABLE 30
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 11 PART 22C TEST DESCRIPTION

CONTAMINATED CONTROL - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. TOTAL OF 32.0 MG
OF SYNTHETIC CONTAMINANT ADDED. TEST
SPECIMEN (S/N 022) INLET PRESSURE = 1000
PSIA (NOMINAL).

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE			FLOWMETER TWO			TEST SPECIMEN INLET CONDITIONS		
FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.84	50.1	68.2	.91	47.8	75.2	115.9	71.7	.0420
.76	50.1	67.4	.81	48.1	74.8	115.9	71.1	.0378
.67	50.4	66.2	.70	48.9	74.1	111.9	70.2	.0336
.58	50.1	65.8	.60	48.7	73.8	111.9	69.9	.0289
.49	50.1	66.3	.50	49.1	74.1	111.9	70.2	.0244
.40	50.2	67.3	.40	49.5	75.1	111.9	71.2	.0198
.30	50.2	69.1	.30	49.7	76.2	115.9	72.6	.0149
.26	49.9	69.7	.25	49.3	76.5	115.9	73.1	.0124
.22	49.9	70.1	.21	49.3	76.6	115.9	73.3	.0105
.14	50.2	71.4	.13	49.9	76.4	115.9	73.9	.0066
.14	50.2	72.5	.13	49.9	76.3	115.9	74.4	.0066
.22	50.1	72.2	.22	49.7	76.2	115.9	74.2	.0110
.26	50.2	72.0	.26	49.9	76.0	115.9	74.0	.0129
.31	50.1	71.6	.31	49.5	75.8	115.9	73.7	.0152
.41	50.2	70.8	.41	49.5	75.2	115.9	73.0	.0200
.49	49.7	70.2	.50	48.7	74.1	115.9	72.1	.0241
.58	50.2	69.5	.60	48.9	73.2	115.9	71.4	.0289
.67	49.9	68.8	.71	48.3	72.3	115.9	70.6	.0334
.76	50.1	67.7	.81	48.3	71.6	115.9	69.7	.0379
.84	50.2	67.2	.91	47.9	70.9	115.9	69.0	.0423

TABLE 30
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONTROL - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. TOTAL OF 32.0 MG
OF SYNTHETIC CONTAMINANT ADDED. TEST
SPECIMEN (S/N 022) INLET PRESSURE = 1000
PSIA (NOMINAL).

TEST NUMBER 11 PART 22C TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSIG)	TARE DIFF. PRESS- (PSID)	NET DIFF. PRESS (PSID)
1015.9	71.7	.0420	137.940	137.940	137.940	-0.000	137.940
1015.9	71.1	.0378	119.632	119.632	119.632	-0.000	119.632
1011.9	70.2	.0336	103.218	103.218	103.218	-0.000	103.218
1011.9	69.9	.0289	84.817	85.542	85.174	-0.000	85.175
1011.9	70.2	.0244	68.661	69.443	69.052	-0.000	69.052
1011.9	71.2	.0198	53.006	53.661	53.333	-0.000	53.334
1015.9	72.6	.0149	38.916	39.117	39.012	-0.000	39.012
1015.9	73.1	.0124	31.326	31.453	31.390	-0.000	31.390
1015.9	73.3	.0105	25.590	25.653	25.622	-0.000	25.622
1015.9	73.9	.0066	15.103	15.115	15.109	-0.000	15.109
1015.9	74.4	.0066	15.103	15.229	15.166	-0.000	15.166
1015.9	74.2	.0110	26.865	26.973	26.919	-0.000	26.919
1015.9	74.0	.0129	32.659	32.833	32.746	-0.000	32.746
1015.9	73.7	.0152	39.554	39.799	39.676	-0.000	39.677
1015.9	73.0	.0200	53.883	54.292	54.088	-0.000	54.088
1015.9	72.1	.0241	67.911	68.496	68.204	-0.000	68.204
1015.9	71.4	.0289	85.300	85.857	85.578	-0.000	85.579
1015.9	70.6	.0334	102.902	102.902	102.902	-0.000	102.903
1015.9	69.7	.0379	121.210	121.210	121.210	-0.000	121.210
1015.9	69.0	.0423	141.728	141.728	141.728	-0.000	141.728

TARE DIFF. PRESS = -1.64000E-04 + -1.26930E-02 (ACFM) + 2.48070E-01 (ACFM)**2 +

0 (ACFM)**3

TABLE 30
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONTROL - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. TOTAL OF 32.0 MG
OF SYNTHETIC CONTAMINANT ADDED. TEST
SPECIMEN (S/N 022) INLET PRESSURE = 1000
PSIA (NOMINAL).

TEST NUMBER 11 PART 22C TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS											NET DIFFERENTIAL PRESS		
*****											*****		
PRESSURE		TEMPERATURE				FLOW RATE							
*****		*****				*****							
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN2 KG/HR	GN2 LB/HR.	KG/SQ CM DIFFERENTIAL	PSID		
71.423	1015.9	295.2	22.1	71.7	82.0	0.0420	2.894	5.699	12.565	9.6981	137.940		
71.423	1015.9	294.9	21.7	71.1	73.8	0.0378	2.606	5.131	11.312	8.4110	119.632		
71.144	1011.9	294.4	21.2	70.2	65.4	0.0336	2.311	4.551	10.034	7.2570	103.218		
71.144	1011.9	294.2	21.1	69.9	56.3	0.0289	1.987	3.913	8.626	5.9884	85.175		
71.144	1011.9	294.4	21.2	70.2	47.5	0.0244	1.676	3.301	7.277	4.8549	69.052		
71.144	1011.9	294.9	21.8	71.2	38.5	0.0195	1.359	2.675	5.897	3.7497	53.334		
71.423	1015.9	295.7	22.6	72.6	29.1	0.0149	1.028	2.023	4.460	2.7428	39.012		
71.423	1015.9	296.0	22.8	73.1	24.1	0.0124	.851	1.676	3.696	2.2069	31.390		
71.423	1015.9	296.1	23.0	73.3	20.4	0.0105	.720	1.418	3.127	1.8014	25.622		
71.423	1015.9	296.4	23.3	73.9	12.8	0.0066	.452	.890	1.962	1.0623	15.109		
71.423	1015.9	296.7	23.6	74.4	12.8	0.0066	.452	.890	1.961	1.0663	15.166		
71.423	1015.9	296.6	23.5	74.2	21.3	0.0110	.752	1.480	3.264	1.8926	26.919		
71.423	1015.9	296.5	23.3	74.0	25.1	0.0129	.887	1.746	3.849	2.3023	32.746		
71.423	1015.9	296.3	23.2	73.7	29.6	0.0152	1.044	2.056	4.533	2.7895	39.677		
71.423	1015.9	295.9	22.8	73.0	38.9	0.0200	1.374	2.709	5.965	3.8028	54.088		
71.423	1015.9	295.5	22.3	72.1	47.0	0.0241	1.660	3.269	7.207	4.7952	68.204		
71.423	1015.9	295.0	21.9	71.4	56.4	0.0289	1.992	3.923	8.648	6.0168	85.579		
71.423	1015.9	294.6	21.4	70.6	65.3	0.0334	2.306	4.541	10.012	7.2348	102.903		
71.423	1015.9	294.1	20.9	69.7	74.3	0.0379	2.624	5.166	11.390	8.5219	121.210		
71.423	1015.9	293.7	20.6	69.0	83.0	0.0423	2.932	5.773	12.728	9.9645	141.728		
****	****	****	****	****									
71.367	1015.1	295.4	22.2	72.0									
.089	1.3	.8	.8	1.5	DEVIATIONS								

TABLE 31
 FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 11 PART 220 TEST DESCRIPTION

CONTAMINATED CONDITION - FLOW RATE VERSUS
 DIFFERENTIAL PRESSURE. TOTAL OF 32.0 MG
 OF SYNTHETIC CONTAMINANT ADDED. TEST
 SPECIMEN (S/N 022) INLET PRESSURE = 415
 PSIA (NOMINAL).

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

***** FLOWMETER ONL *****

***** FLOWMETER T#0 *****

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
0.55	30.4	81.6	0.56	49.2	82.4	416.9	82.0	0.0664
0.50	30.6	81.6	0.51	49.5	82.4	416.2	82.0	0.0606
0.40	30.4	81.0	0.40	49.7	82.5	416.2	82.1	0.0484
0.31	30.2	81.6	0.31	49.7	82.7	415.6	82.1	0.0369
0.26	30.6	81.7	0.25	50.1	82.8	415.6	82.3	0.0308
0.21	30.2	81.9	0.20	49.9	83.1	415.6	82.5	0.0250
0.14	30.1	82.2	0.14	49.9	83.3	415.6	82.8	0.0167
0.14	32.9	82.5	0.14	49.3	83.5	415.6	83.0	0.0166
0.22	32.5	82.5	0.22	49.7	83.5	415.6	83.0	0.0265
0.27	32.9	82.4	0.26	49.3	83.5	415.6	82.9	0.0316
0.31	32.7	82.4	0.31	49.2	83.5	415.6	83.0	0.0366
0.41	32.9	82.3	0.41	49.2	83.5	415.6	82.9	0.0487
0.50	30.1	82.1	0.50	49.2	83.3	414.3	82.7	0.0599
0.54	30.2	82.4	0.55	49.7	83.4	414.3	82.9	0.0653

ORIGINAL PAGE IS
OF POOR QUALITY

PAGE: 2
DATE: 9-10-76

TABLE 31
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE, TOTAL OF 32.0 MG
OF SYNTHETIC CONTAMINANT ADDED. TEST
SPECIMEN (S/N 022) INLET PRESSURE = 415
PSIA (NOMINAL).

TEST NUMBER 11 PART 220 TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
416.7	82.0	.1654	307.129	307.129	307.129	.001	307.128
416.2	82.1	.166	242.730	242.736	242.736	.000	242.735
416.2	82.1	.1484	163.823	163.823	163.823	.000	163.823
415.8	82.1	.1309	111.425	111.425	111.425	.000	111.424
415.8	82.3	.1038	86.935	87.435	87.185	.000	87.185
415.8	82.5	.1250	66.214	66.918	66.561	.000	66.560
415.8	82.8	.107	41.234	41.413	41.324	.000	41.323
415.8	83.0	.1166	40.770	40.952	40.861	.000	40.861
415.8	83.0	.1285	71.576	72.284	71.930	.000	71.930
415.8	82.9	.1316	89.620	90.592	90.109	.000	90.108
415.8	83.0	.1306	110.794	111.794	110.794	.000	110.793
415.8	82.9	.1487	165.086	165.086	165.086	.000	165.085
414.2	82.7	.1599	238.948	238.948	238.948	.000	238.948
414.2	82.9	.1653	295.766	295.766	295.766	.001	295.765

$$\text{TARE DIFF. PRESS} = -3.41000E-05 + -4.44000E-04 (\text{ACFM}) + 1.50933E-01 (\text{ACFM})^{*2} + 0 (\text{ACFM})^{*3}$$

TABLE 31
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. TOTAL OF 32.0 MG
OF SYNTHETIC CONTAMINANT ADDED. TEST
SPECIMEN (S/N 022) INLET PRESSURE = 415
PSIA (NOMINAL).

TEST NUMBER 11 PART 220 TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESS

PRESSURE		TEMPERATURE			FLOW RATE						NET DIFFERENTIAL PRESS	
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ICFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSIA	
29.311	416.2	300.9	27.8	82.1	52.2	0.664	1.842	3.822	7.995	21.5933	307.128	
29.267	416.4	300.9	27.8	82.1	47.5	0.611	1.678	3.303	7.282	17.0660	242.735	
29.267	416.4	301.0	27.8	82.1	38.0	0.404	1.341	2.940	5.820	11.5179	163.823	
29.212	415.8	301.0	27.8	82.1	28.9	0.309	1.019	2.001	4.424	7.8339	111.424	
29.212	415.8	301.1	27.9	82.3	24.1	0.301	0.851	1.977	3.694	6.1297	87.185	
29.212	415.8	301.2	28.1	82.5	19.5	0.250	0.690	1.357	2.997	4.6797	66.260	
29.212	415.8	301.4	28.2	82.8	13.1	0.157	0.462	0.907	2.004	2.9053	41.323	
29.212	415.8	301.5	28.4	83.0	13.0	0.166	0.458	0.901	1.987	2.8728	40.861	
29.212	415.8	301.5	28.4	83.0	20.7	0.205	0.732	1.441	3.178	5.0572	71.930	
29.212	415.8	301.5	28.5	82.9	24.7	0.316	0.873	1.712	3.791	6.3353	90.108	
29.212	415.8	301.5	28.5	83.1	28.6	0.366	1.009	1.988	4.379	7.7895	110.793	
29.212	415.8	301.4	28.5	82.9	33.0	0.447	1.343	2.947	5.831	11.6066	165.085	
29.128	414.3	301.3	28.2	82.7	46.7	0.599	1.648	3.247	7.154	16.7997	238.948	
29.128	414.3	301.4	28.3	82.9	50.9	0.653	1.796	3.538	7.795	20.7943	295.765	
29.212	415.8	301.3	28.1	82.6								
0.026	0.4	0.2	0.4	0.4	DEVIATIONS							

TABLE 32
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 11 PART 22E1 TEST DESCRIPTION

CONTAMINATED CONTROL - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. TOTAL OF 53.2 MG
OF SYNTHETIC CONTAMINANT ADDED. TEST
SPECIMEN (S/N 022) INLET PRESSURE = 1000
PSIA (NOMINAL).

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.87	50.1	66.8	.91	47.8	72.4	1009.2	69.6	.0432
.78	49.9	65.9	.81	48.0	71.6	1009.2	68.8	.0385
.67	50.5	65.6	.71	49.0	71.1	1009.2	68.4	.0338
.58	50.1	65.7	.60	48.8	71.1	1009.2	68.4	.0290
.49	50.3	65.8	.51	49.3	71.1	1009.2	68.5	.0247
.40	50.1	66.3	.40	49.3	71.3	1009.2	68.8	.0197
.30	49.7	67.0	.30	49.2	71.8	1009.2	69.4	.0149
.26	49.9	67.4	.26	49.3	71.8	1009.2	69.6	.0127
.21	50.1	67.9	.20	49.7	71.8	1009.2	69.8	.0103
.14	49.7	68.7	.14	49.3	71.8	1009.2	70.2	.0068
.14	49.7	69.9	.14	49.3	72.8	1009.2	71.3	.0068
.22	49.4	69.5	.22	48.8	72.6	1009.2	71.0	.0108
.27	49.9	69.5	.26	49.3	72.9	1009.2	71.2	.0130
.31	50.1	69.4	.31	49.5	73.1	1009.2	71.2	.0151
.41	49.9	68.8	.41	49.2	73.0	1009.2	70.9	.0201
.49	49.5	68.1	.51	48.6	72.6	1009.2	70.3	.0243
.58	50.1	67.5	.60	48.8	72.2	1009.2	69.8	.0290
.67	50.5	66.6	.71	49.0	71.5	1005.3	69.0	.0341
.76	49.9	65.7	.81	48.2	70.9	1005.3	68.3	.0383
.84	50.3	65.1	.91	48.0	70.2	1005.3	67.7	.0427

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 32
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. TOTAL OF 53.2 MG
OF SYNTHETIC CONTAMINANT ADDED. TEST
SPECIMEN (S/N 022) INLET PRESSURE = 1000
PSIA (NOMINAL).

TEST NUMBER 11 PART 22E1 TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
1009.2	69.6	.0432	148.963	148.963	148.963	-0.000	148.963
1009.2	68.8	.0385	128.104	128.104	128.104	-0.000	128.104
1009.2	68.4	.0338	110.405	110.405	110.405	-0.000	110.405
1009.2	68.4	.0290	90.309	91.127	90.718	-0.000	90.718
1009.2	68.5	.0247	73.371	74.060	73.716	-0.000	73.716
1009.2	68.8	.0197	55.457	56.362	55.909	-0.000	55.909
1009.2	69.4	.0149	40.172	40.426	40.299	-0.000	40.299
1009.2	69.6	.0127	33.277	33.400	33.364	-0.000	33.364
1009.2	69.8	.0103	25.861	25.915	25.888	-0.000	25.888
1009.2	70.2	.0068	16.185	16.164	16.174	-0.000	16.175
1009.2	71.3	.0068	16.011	16.221	16.116	-0.000	16.116
1009.2	71.0	.0108	27.251	27.409	27.330	-0.000	27.330
1009.2	71.2	.0130	34.030	34.257	34.143	-0.000	34.144
1009.2	71.2	.0151	40.867	41.177	41.022	-0.000	41.022
1009.2	70.9	.0201	56.461	56.994	56.727	-0.000	56.727
1009.2	70.3	.0243	71.998	72.480	72.239	-0.000	72.239
1009.2	69.8	.0290	90.309	91.127	90.718	-0.000	90.718
1005.3	69.0	.0341	111.354	111.354	111.354	-0.000	111.354
1005.3	68.3	.0383	129.684	129.684	129.684	-0.000	129.685
1005.3	67.7	.0427	151.491	151.491	151.491	-0.000	151.492

TARE DIFF. PRESS = -1.64000E-04 + -1.26930E-02 (ACFM) + 2.48070E-01 (ACFM)**2 +

0 (ACFM)**3

TABLE 32
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. TOTAL OF 53.2 MG.
OF SYNTHETIC CONTAMINANT ADDED. TEST
SPECIMEN (S/N 022) INLET PRESSURE = 1000.
PSIA (NOMINAL).

TEST NUMBER 11 PART 22E1 TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESS

PRESSURE		TEMPERATURE			FLOW RATE					NET DIFFERENTIAL PRESS	
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ICFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID
70.956	1009.2	294.1	20.9	69.6	84.0	.0432	2.966	5.839	12.874	10.4732	148.963
70.956	1009.2	293.6	20.4	68.8	75.1	.0385	2.652	5.221	11.511	9.0066	128.104
70.956	1009.2	293.4	20.2	68.4	65.9	.0338	2.327	4.581	10.100	7.7623	110.406
70.956	1009.2	293.4	20.2	68.4	56.5	.0290	1.996	3.931	8.667	6.3781	90.718
70.956	1009.2	293.4	20.3	68.5	48.1	.0247	1.697	3.342	7.368	5.1827	73.716
70.956	1009.2	293.6	20.4	68.8	38.3	.0197	1.353	2.665	5.875	3.9308	55.909
70.956	1009.2	293.9	20.8	69.4	29.0	.0149	1.024	2.016	4.445	2.8333	40.299
70.956	1009.2	294.1	20.9	69.6	24.7	.0127	.873	1.719	3.789	2.3457	33.364
70.956	1009.2	294.2	21.0	69.8	20.0	.0103	.705	1.387	3.058	1.8201	25.888
70.956	1009.2	294.4	21.2	70.2	13.2	.0068	.465	.916	2.020	1.1372	16.175
70.956	1009.2	295.0	21.9	71.3	13.2	.0068	.464	.915	2.016	1.1331	16.116
70.956	1009.2	294.8	21.7	71.0	20.9	.0108	.739	1.455	3.208	1.9215	27.330
70.956	1009.2	294.9	21.8	71.2	25.2	.0130	.890	1.753	3.865	2.4005	34.144
70.956	1009.2	295.0	21.8	71.2	29.4	.0151	1.037	2.041	4.501	2.8841	41.022
70.956	1009.2	294.8	21.6	70.9	38.9	.0201	1.374	2.706	5.966	3.9883	56.727
70.956	1009.2	294.5	21.3	70.3	47.2	.0243	1.665	3.279	7.230	5.0789	72.239
70.956	1009.2	294.2	21.0	69.8	56.4	.0290	1.991	3.920	8.643	6.3781	90.718
70.677	1005.3	293.7	20.6	69.0	66.2	.0341	2.339	4.605	10.152	7.8290	111.354
70.677	1005.3	293.3	20.2	68.3	74.3	.0383	2.625	5.170	11.397	9.1177	129.685
70.677	1005.3	293.0	19.8	67.7	83.0	.0427	2.931	5.770	12.722	10.6509	151.492
****	****	****	****	****							
70.914	1008.6	294.1	20.9	69.6							
.071	1.0	.5	.5	.9	DEVIATIONS						

ORIGINAL PAGE IS
OF POOR QUALITY

PAGE: 1
DATE: 9-10-76

TABLE 33
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 11 PART 22F TEST DESCRIPTION

CONTAMINATED CONDITION - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. TOTAL OF 52.2 MG
OF SYNTHETIC CONTAMINANT ADDED. TEST
SPECIMEN (S/N 022) INLET PRESSURE = 415
PSIA (NOMINAL).

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)
.53	50.1	76.2
.50	50.4	76.4
.40	50.4	76.5
.31	50.4	76.7
.26	50.4	76.8
.21	50.4	76.9
.14	50.2	77.2
.14	50.1	77.6
.22	49.9	77.6
.26	50.2	77.6
.31	49.9	77.7
.41	50.1	77.6
.49	50.2	77.6
.53	49.9	77.9

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)
.54	49.0	77.4
.51	49.3	77.5
.40	49.7	77.7
.30	49.9	77.8
.26	50.1	77.9
.20	50.1	78.1
.13	49.9	78.5
.13	49.9	78.8
.21	49.3	78.9
.26	49.9	79.0
.31	49.3	79.2
.41	49.3	79.2
.50	49.2	79.3
.54	49.0	79.4

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
416.2	76.8	.0642
415.6	76.9	.0603
415.6	77.1	.0485
415.6	77.2	.0368
415.6	77.3	.0313
415.6	77.5	.0249
415.6	77.8	.0164
415.6	78.2	.0163
415.6	78.3	.0256
414.9	78.3	.0316
414.3	78.4	.0373
413.7	78.4	.0492
413.0	78.4	.0592
413.0	78.6	.0639

TABLE 33
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE, TOTAL OF 52.2 MG
OF SYNTHETIC CONTAMINANT ADDED. TEST
SPECIMEN (S/N 022) INLET PRESSURE = 415
PSIA (NOMINAL).

TEST NUMBER 11 PART 22F TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
416.2	76.8	.0642	306.919	306.919	306.919	.001	306.918
415.6	76.9	.0603	259.571	259.571	259.571	.000	259.570
415.6	77.1	.0485	172.451	172.451	172.451	.000	172.450
415.6	77.2	.0368	115.634	115.634	115.634	.000	115.633
415.6	77.3	.0313	92.101	92.591	92.346	.000	92.346
415.6	77.5	.0249	68.121	68.602	68.361	.000	68.361
415.6	77.8	.0164	41.562	41.759	41.661	-0.000	41.660
415.6	78.2	.0163	41.273	41.471	41.372	-0.000	41.371
415.6	78.3	.0256	70.619	71.442	71.031	.000	71.030
414.9	78.3	.0316	92.587	93.538	93.062	.000	93.062
414.3	78.4	.0373	117.528	117.528	117.528	.000	117.527
413.7	78.4	.0492	175.292	175.292	175.292	.000	175.291
413.0	78.4	.0599	255.467	255.467	255.467	.000	255.467
413.0	78.6	.0639	306.919	306.919	306.919	.001	306.918

TARE DIFF. PRESS = $-3.40000E-05 + -4.44000E-04$ (ACFM) + $1.50933E-01$ (ACFM)**2 + 0 (ACFM)**3

ORIGINAL PAGE IS
OF POOR QUALITY

PAGE: 3
DATE: 9-10-76

TABLE 33
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. TOTAL OF 52.2 MG
OF SYNTHETIC CONTAMINANT ADDED. TEST
SPECIMEN (S/N Q22) INLET PRESSURE = 415
PSIA (NOMINAL).

TEST NUMBER 11 PART 22F TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESS

PRESSURE		TEMPERATURE			FLOW RATE					NET DIFFERENTIAL PRESS		

KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID	
29.265	416.2	298.0	24.9	76.8	50.8	.0642	1.795	3.534	7.792	21.5785	306.918	
29.219	415.6	298.1	25.0	76.9	47.7	.0603	1.684	3.316	7.310	18.2496	259.570	
29.219	415.6	298.2	25.1	77.1	38.3	.0485	1.353	2.665	5.874	12.1245	172.450	
29.219	415.6	298.3	25.1	77.2	29.1	.0368	1.027	2.022	4.457	8.1298	115.633	
29.219	415.6	298.3	25.2	77.3	24.8	.0313	.874	1.721	3.795	6.4925	92.346	
29.219	415.6	298.4	25.3	77.5	19.6	.0249	.694	1.366	3.011	4.8062	68.361	
29.219	415.6	298.6	25.5	77.8	13.0	.0164	.458	.902	1.988	2.9290	41.660	
29.219	415.6	298.8	25.7	78.2	12.9	.0163	.454	.894	1.971	2.9087	41.371	
29.219	415.6	298.9	25.7	78.3	20.2	.0256	.712	1.401	3.089	4.9939	71.030	
29.174	414.9	298.9	25.7	78.3	24.9	.0316	.878	1.728	3.810	6.5429	93.062	
29.128	414.3	299.0	25.8	78.4	29.3	.0373	1.035	2.038	4.494	8.2630	117.527	
29.083	413.7	298.9	25.8	78.4	38.6	.0492	1.362	2.683	5.914	12.3242	175.291	
29.037	413.0	299.0	25.8	78.4	46.9	.0599	1.656	3.260	7.188	17.9611	255.467	
29.037	413.0	299.1	25.9	78.6	50.0	.0639	1.765	3.476	7.663	21.5785	306.918	
*****	*****	*****	*****	*****								
29.177	415.0	298.6	25.5	77.8								
.061	.9	.3	.3	.6	DEVIATIONS							

TABLE 34
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

FIRST NUMBER 11 PART 22G TEST DESCRIPTION

CONTAMINATED CONDITION - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. TOTAL OF 74.3 MG.
OF SYNTHETIC CONTAMINANT ADDED. TEST
SPECIMEN (S/N 022) INLET PRESSURE = 1000
PSIA (NOMINAL).

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.87	49.7	76.7	.91	47.4	81.7	1013.2	79.2	.0426
.78	50.4	74.7	.81	48.4	76.2	1013.2	77.5	.0388
.69	50.4	74.4	.71	49.0	79.9	1013.2	77.2	.0343
.60	50.2	74.3	.61	49.0	79.7	1013.2	77.0	.0297
.50	50.1	74.5	.50	49.2	79.6	1013.2	77.0	.0246
.41	50.1	74.8	.40	49.3	79.8	1013.2	77.3	.0201
.32	50.4	75.5	.31	49.9	80.3	1017.2	77.9	.0157
.27	49.9	76.2	.25	49.3	80.6	1013.2	78.4	.0128
.22	50.2	76.9	.20	49.9	81.1	1017.2	79.0	.0104
.15	49.9	77.8	.13	49.5	81.6	1017.2	79.7	.0068
.15	49.5	79.7	.13	49.1	82.8	1017.2	81.3	.0068
.22	49.5	79.7	.21	49.0	82.6	1017.2	81.3	.0106
.28	49.9	79.5	.26	49.3	82.6	1017.2	81.1	.0131
.32	50.2	79.1	.31	49.7	82.5	1017.2	80.8	.0154
.42	49.9	78.6	.41	49.2	82.3	1017.2	80.4	.0201
.52	50.2	77.6	.51	49.2	81.7	1013.2	79.7	.0252
.60	50.4	76.9	.61	49.2	81.3	1013.2	79.1	.0298
.70	50.1	75.9	.71	48.4	80.6	1013.2	78.2	.0341
.76	50.2	75.1	.81	48.4	79.8	1013.2	77.4	.0380
.84	50.1	74.5	.91	47.8	79.2	1013.2	76.8	.0423

TABLE 34
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. TOTAL OF 74.3 MG
OF SYNTHETIC CONTAMINANT ADDED. TEST
SPECIMEN (S/N 022) INLET PRESSURE = 1000
PSIA (NOMINAL).

TEST NUMBER 11 PART 226 TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
1013.2	79.2	.0426	153.617	153.617	153.617	-0.000	153.617
1013.2	77.5	.0388	135.941	135.941	135.941	-0.000	135.941
1013.2	77.2	.0343	115.739	115.739	115.739	-0.000	115.739
1013.2	77.0	.0297	96.169	96.169	96.169	-0.000	96.169
1013.2	77.0	.0246	75.314	75.967	75.640	-0.000	75.641
1013.2	77.3	.0201	58.187	58.606	58.396	-0.000	58.397
1017.2	77.9	.0157	43.767	44.009	43.888	-0.000	43.888
1013.2	78.4	.0128	34.103	34.271	34.187	-0.000	34.187
1017.4	79.0	.0104	26.523	26.629	26.576	-0.000	26.576
1017.2	79.7	.0068	16.454	16.544	16.499	-0.000	16.499
1017.2	81.3	.0068	16.164	16.315	16.240	-0.000	16.240
1017.2	81.3	.0106	27.275	27.490	27.382	-0.000	27.383
1017.2	81.1	.0131	35.145	35.422	35.283	-0.000	35.284
1017.2	80.8	.0154	42.552	42.797	42.675	-0.000	42.675
1017.2	80.4	.0201	57.936	58.290	58.113	-0.000	58.114
1013.2	79.7	.0252	76.806	77.229	77.018	-0.000	77.018
1013.2	79.1	.0298	96.169	96.169	96.169	-0.000	96.169
1013.2	78.2	.0341	114.792	114.792	114.792	-0.000	114.792
1013.2	77.4	.0380	135.941	135.941	135.941	-0.000	135.941
1013.2	76.8	.0423	159.299	159.299	159.299	-0.000	159.299

TARE DIFF. PRESS = -1.64000E-04 + -1.26930E-02 (ACFM) + 2.48070E-01 (ACFM)**2 +

0 (ACFM)**3

TABLE 34
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE TOTAL OF 74.3 MG
OF SYNTHETIC CONTAMINANT ADDED. TEST
SPECIMEN (S/N 022) INLET PRESSURE = 1000
PSIA (NOMINAL).

TEST NUMBER 11 PART 226 TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESS

*****										*****	
PRESSURE		TEMPERATURE			FLOW RATE					NET DIFFERENTIAL PRESS	
*****										*****	
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSIA
71.235	1013.2	299.4	26.2	79.2	81.6	.0426	2.883	5.676	12.514	10.8004	153.617
71.235	1013.2	298.4	25.3	77.5	74.6	.0388	2.635	5.189	11.440	9.5576	135.941
71.235	1013.2	298.3	25.1	77.2	66.1	.0343	2.336	4.599	10.139	8.1373	115.799
71.235	1013.2	298.2	25.0	77.0	57.2	.0297	2.019	3.976	8.765	6.7613	96.169
71.235	1013.2	298.2	25.0	77.0	47.4	.0246	1.674	3.296	7.266	5.3181	75.641
71.235	1013.2	298.3	25.2	77.3	38.7	.0201	1.365	2.688	5.925	4.1057	58.397
71.514	1017.2	298.7	25.5	77.9	30.3	.0157	1.071	2.109	4.649	3.0857	43.888
71.235	1013.2	298.9	25.8	78.4	24.5	.0128	.866	1.706	3.761	2.4036	34.187
71.514	1017.2	299.3	26.1	79.0	20.0	.0104	.706	1.390	3.065	1.8685	26.576
71.514	1017.2	299.7	26.5	79.7	13.1	.0068	.464	.914	2.015	1.1600	16.499
71.514	1017.2	300.5	27.4	81.3	13.0	.0068	.458	.903	1.990	1.1418	16.240
71.514	1017.2	300.5	27.4	81.3	20.4	.0106	.719	1.416	3.121	1.9252	27.383
71.514	1017.2	300.4	27.3	81.1	25.2	.0131	.890	1.753	3.864	2.4807	35.284
71.514	1017.2	300.3	27.1	80.8	29.6	.0154	1.047	2.062	4.545	3.0004	42.675
71.514	1017.2	300.1	26.9	80.4	38.6	.0201	1.363	2.684	5.918	4.0858	58.114
71.235	1013.2	299.6	26.5	79.7	48.3	.0252	1.706	3.359	7.405	5.4149	77.018
71.235	1013.2	299.3	26.1	79.1	57.1	.0298	2.016	3.970	8.752	6.7613	96.169
71.235	1013.2	298.8	25.7	78.2	65.6	.0341	2.317	4.563	10.059	8.0707	114.792
71.235	1013.2	298.4	25.2	77.4	73.2	.0380	2.585	5.091	11.223	9.5576	135.941
71.235	1013.2	298.1	24.9	76.8	81.4	.0423	2.876	5.663	12.485	11.1998	159.299
****	****	****	****	****							
71.347	1014.8	299.2	26.0	78.8							
.134	1.9	.7	.7	1.3	DEVIATIONS						

TABLE 35
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 11 PART 22H TEST DESCRIPTION

PAGE: 1
DATE: 9-10-76

CONTAMINATED CONDITION - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. TOTAL OF 74.3 MG
OF SYNTHETIC CONTAMINANT ADDED. TEST
SPECIMEN (S/N 022) INLET PRESSURE = 415
PSIA (NOMINAL).

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE			FLOWMETER TWO			PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)			
.53	49.9	85.6	.52	48.8	83.7	418.8	83.1	.0621
.47	50.1	82.6	.46	49.2	83.7	418.2	83.1	.0553
.42	50.4	82.6	.40	49.5	83.7	418.2	83.1	.0490
.32	50.2	82.5	.30	49.7	83.5	417.5	83.0	.0372
.27	50.2	82.3	.25	49.9	83.4	417.5	82.9	.0313
.22	50.6	82.5	.20	50.1	83.5	416.9	83.0	.0255
.14	50.8	82.6	.13	50.3	83.7	416.9	83.1	.0169
.14	50.2	82.9	.13	49.9	83.9	416.9	83.4	.0166
.22	50.1	82.7	.21	49.7	83.9	416.9	83.3	.0257
.27	50.2	82.6	.25	49.9	83.7	416.2	83.1	.0312
.32	50.1	82.1	.31	49.3	83.5	415.6	82.8	.0378
.42	49.9	81.9	.41	49.2	83.3	415.6	82.6	.0499
.46	50.1	81.6	.45	49.2	83.0	415.6	82.3	.0548
.51	49.9	81.6	.50	48.8	82.9	414.3	82.2	.0602

ORIGINAL PAGE IS
OF POOR QUALITY

PAGE: 2
DATE: 9-10-76

TABLE 35
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE, TOTAL OF 74.3 MG
OF SYNTHETIC CONTAMINANT ADDED. TEST
SPECIMEN (S/N 022) INLET PRESSURE = 415
PSIA NOMINAL.

TEST NUMBER 11 PART 22H TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
418.8	83.1	.0621	307.445	307.445	307.445	.001	307.444
418.2	83.1	.0553	230.741	230.741	230.741	.000	230.741
418.2	83.1	.0490	186.550	186.550	186.550	.000	186.550
417.5	83.0	.0372	122.788	122.788	122.788	.000	122.788
417.5	82.9	.0313	95.958	95.958	95.958	.000	95.958
416.9	83.0	.0255	72.442	73.231	72.836	.000	72.836
416.9	83.1	.0169	43.594	43.894	43.744	.000	43.743
416.9	83.4	.0166	42.841	43.086	42.964	.000	42.963
416.9	83.3	.0257	73.064	74.178	73.621	.000	73.621
416.2	83.1	.0312	95.327	95.327	95.327	.000	95.326
415.6	82.8	.0378	124.682	124.682	124.682	.000	124.682
415.6	82.6	.0499	190.969	190.969	190.969	.000	190.969
415.6	82.3	.0548	228.216	228.216	228.216	.000	228.216
414.3	82.2	.0602	282.508	282.508	282.508	.000	282.508

TARE DIFF. PRESS = $-3.40000E-05 + -4.44000E-04$ (ACFM) + $1.50933E-01$ (ACFM)**2 +

0 (ACFM)**3

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 35
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. TOTAL OF 74.3 MG
OF SYNTHETIC CONTAMINANT ADDED. TEST
SPECIMEN (S/N 022) INLET PRESSURE = 415
PSIA (NOMINAL).

TEST NUMBER 11 PART 22H TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESS

PRESSURE		TEMPERATURE			FLOW RATE					NET DIFFERENTIAL PRESS	
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID
29.447	418.8	301.6	28.4	83.1	48.9	.0621	1.727	3.401	7.497	21.6155	307.444
29.402	418.2	301.6	28.4	83.1	43.5	.0553	1.536	3.025	6.669	16.2227	230.741
29.402	418.2	301.6	28.4	83.1	38.5	.0490	1.361	2.680	5.908	13.1157	186.550
29.356	417.5	301.5	28.3	83.0	29.2	.0372	1.031	2.031	4.478	8.6329	122.788
29.356	417.5	301.4	28.3	82.9	24.6	.0313	.867	1.708	3.766	6.7465	95.958
29.311	416.9	301.5	28.3	83.0	20.0	.0255	.705	1.388	3.060	5.1209	72.836
29.311	416.9	301.6	28.4	83.1	13.2	.0169	.466	.918	2.025	3.0755	43.743
29.311	416.9	301.7	28.6	83.4	13.0	.0166	.459	.903	1.992	3.0206	42.963
29.311	416.9	301.7	28.5	83.3	20.2	.0257	.712	1.402	3.090	5.1760	73.621
29.265	416.2	301.6	28.4	83.1	24.4	.0312	.861	1.696	3.739	6.7021	95.326
29.219	415.6	301.4	28.2	82.8	29.5	.0378	1.043	2.053	4.526	8.7660	124.682
29.219	415.6	301.3	28.1	82.6	39.0	.0499	1.377	2.712	5.979	13.4264	190.969
29.219	415.6	301.1	27.9	82.3	42.8	.0548	1.513	2.979	6.568	16.0452	228.216
29.128	414.3	301.1	27.9	82.2	47.0	.0602	1.659	3.267	7.203	19.8623	282.508
****	****	****	****	****							
29.304	416.8	301.5	28.3	82.9							
.067	1.0	.2	.2	.3	DEVIATIONS						

TABLE 36
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 11 PART 221 TEST DESCRIPTION

CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE. TOTAL OF 105.2 MG OF SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN (S/N 022) INLET PRESSURE - 1000 PSIA (NOMINAL).

FLOW METER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.88	49.9	76.7	.92	47.6	74.8	1-11.9	78.6	.0434
.78	50.2	74.9	.41	48.4	74.9	1-11.9	78.1	.0386
.69	50.1	75.9	.71	48.6	79.7	1-11.9	77.8	.0341
.60	51.0	75.7	.60	49.9	79.1	1-11.9	77.6	.0301
.50	49.7	75.6	.49	48.8	79.7	1-11.9	77.8	.0242
.41	50.4	74.2	.40	49.9	79.9	1-11.9	78.0	.0201
.32	49.7	76.8	.30	49.2	79.1	1-15.9	78.4	.0151
.27	49.9	77.2	.26	49.3	79.4	1-11.9	78.8	.0130
.22	49.9	78.4	.21	49.3	79.2	1-15.9	79.7	.0105
.15	50.2	79.6	.14	49.9	81.5	1-15.9	80.5	.0071
.15	50.2	81.3	.14	49.9	82.4	1-15.9	81.1	.0071
.22	50.8	81.3	.20	50.3	81.9	1-15.9	81.1	.0105
.26	50.4	80.1	.25	49.9	81.9	1-15.9	81.0	.0125
.32	50.4	79.7	.31	49.9	81.8	1-15.9	80.8	.0156
.42	50.1	78.9	.41	49.3	81.6	1-15.9	80.3	.0202
.50	50.4	78.2	.49	49.5	81.4	1-15.9	79.8	.0244
.60	50.2	77.2	.60	49.2	81.9	1-15.9	79.1	.0292
.69	50.2	75.9	.70	48.8	80.1	1-11.9	78.0	.0340
.78	50.2	75.4	.81	48.4	79.5	1-11.9	77.2	.0386
.87	50.1	74.4	.91	47.8	78.8	1-11.9	76.6	.0431

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 36
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE TOTAL OF 105.2 MG
OF SYNTHETIC CONTAMINANT ADDED. TEST
SPECIMEN (S/N 022) INLET PRESSURE = 1000
PSIA (NOMINAL).

TEST NUMBER 11	PART 221	TEST DESCRIPTION					
TEST SPECIMEN INLET CONDITIONS							
PRESSURE (PSIA)	AVG TEMP (DFG, F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
1011.9	78.6	.434	168.453	168.453	168.453	-0.000	168.453
1011.9	78.1	.385	143.232	143.232	143.232	-0.000	143.232
1011.9	77.8	.341	121.479	121.479	121.479	-0.000	121.480
1011.9	77.6	.311	102.564	102.564	102.564	-0.000	102.564
1011.9	77.8	.242	77.29	77.609	77.474	-0.000	77.474
1011.9	78.0	.201	60.449	60.950	60.699	-0.000	60.700
1015.9	78.4	.151	43.594	43.741	43.687	-0.000	43.687
1011.9	78.8	.113	36.171	36.182	36.126	-0.000	36.127
1015.9	79.7	.115	27.796	27.846	27.826	-0.000	27.826
1015.9	80.5	.071	17.843	17.838	17.841	-0.000	17.840
1015.9	81.1	.071	17.785	17.902	17.868	-0.000	17.869
1015.9	81.1	.015	27.622	27.709	27.711	-0.000	27.711
1015.9	81.0	.125	34.161	34.343	34.252	-0.000	34.252
1015.9	80.8	.156	44.444	44.241	44.322	-0.000	44.323
1015.9	80.3	.222	61.075	61.580	61.328	-0.000	61.328
1015.9	79.8	.244	77.538	77.974	77.756	-0.000	77.756
1015.9	79.1	.292	99.096	99.096	99.096	-0.000	99.096
1011.9	78.0	.0341	121.164	121.164	121.164	-0.000	121.164
1011.9	77.2	.0385	143.863	143.863	143.863	-0.000	143.863
1011.9	76.6	.0431	170.029	170.029	170.029	-0.000	170.029

TARE DIFF. PRESS = -1.64000E-04 + -1.26930E-02 (ACFM) + 2.48070E-01 (ACFM)**2 + 0 (ACFM)**3

TABLE 36
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. TOTAL OF 105.2 MG
OF SYNTHETIC CONTAMINANT ADDED. TEST
SPECIMEN (S/N 022) INLET PRESSURE = 1000
PSIA (NOMINAL).

TEST NUMBER 11 PART 221 TEST DESCRIPTION

TEST SPECIMEN INFLT CONDITIONS

NET DIFFERENTIAL PRESS

PRESSURE		TEMPERATURE			FLOW RATE						
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID
71.144	1011.9	299.1	25.9	78.6	83.3	434	2.942	5.792	12.770	11.8434	168.453
71.144	1011.9	298.8	25.6	78.1	74.1	386	2.618	5.156	11.366	10.0702	143.232
71.144	1011.9	298.6	25.4	77.8	65.6	341	2.315	4.558	10.049	8.5409	121.480
71.144	1011.9	298.5	25.3	77.6	57.9	301	2.043	4.023	8.869	7.2110	102.564
71.144	1011.9	298.6	25.4	77.8	46.5	242	1.642	3.234	7.130	5.4470	77.474
71.144	1011.9	298.7	25.5	78.1	38.5	241	1.360	2.678	5.905	4.2676	60.700
71.423	1015.9	299.0	25.5	78.4	29.1	151	1.027	2.022	4.459	3.0715	43.687
71.144	1011.9	299.2	26.1	78.8	24.9	134	.879	1.730	3.315	2.5400	36.127
71.423	1015.9	299.6	26.5	79.7	20.2	111	.712	1.401	3.090	1.9564	27.826
71.423	1015.9	300.1	27.0	80.5	13.7	71	.484	.952	2.100	1.2543	17.840
71.423	1015.9	300.5	27.3	81.1	13.7	71	.483	.951	2.097	1.2563	17.869
71.423	1015.9	300.4	27.3	81.1	20.1	105	.709	1.396	3.079	1.9483	27.711
71.423	1015.9	300.4	27.2	81.0	23.9	125	.846	1.665	3.671	2.4082	34.252
71.423	1015.9	300.2	27.1	80.8	29.9	156	1.055	2.078	4.582	3.1162	44.323
71.423	1015.9	300.0	26.9	80.3	38.9	202	1.373	2.703	5.959	4.3118	61.328
71.423	1015.9	299.7	26.0	79.8	46.9	244	1.656	3.261	7.188	5.4668	77.756
71.423	1015.9	299.3	26.1	79.1	56.3	292	1.987	3.912	8.625	6.9672	99.096
71.144	1011.9	298.7	25.6	78.0	65.4	340	2.309	4.546	10.022	8.5187	121.164
71.144	1011.9	298.3	25.1	77.2	74.1	385	2.617	5.153	11.360	10.1146	143.863
71.144 *****	1011.9 *****	297.9 *****	24.8 *****	76.6 *****	83.0	443	2.930	5.770	12.720	11.9543	170.029
71.283	1013.9	299.3	26.1	79.0							
.139	2.0	.7	.7	1.2	DEVIATIONS						

TABLE 37
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 11 PART 2PJ TEST DESCRIPTION

CONTAMINATED CONDITION - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. TOTAL OF 105.2 MG
OF SYNTHETIC CONTAMINANT ADDED. TEST
SPECIMEN (S/N 022) INLET PRESSURE = 415
PSIA (NOMINAL).

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE			FLOWMETER TWO			TEST SPECIMEN INLET CONDITIONS		
FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.51	50.1	71.6	.51	49.2	71.9	419.5	71.3	.0600
.41	50.3	71.5	.41	49.7	71.9	418.2	71.3	.0493
.31	50.3	71.6	.31	49.9	72.0	418.2	71.3	.0371
.26	50.3	71.7	.25	49.9	72.2	417.5	71.4	.0310
.21	49.9	71.4	.20	49.5	72.3	417.5	71.6	.0246
.14	49.9	71.3	.14	49.7	72.5	417.5	71.6	.0166
.14	49.7	71.4	.13	49.3	72.8	417.5	72.1	.0164
.22	50.3	71.3	.21	49.9	72.8	417.5	72.1	.0258
.27	50.1	71.2	.26	49.5	72.8	416.9	72.0	.0318
.31	49.7	71.1	.31	49.2	72.9	416.9	72.0	.0368
.41	50.3	71.9	.41	49.5	72.7	416.2	71.8	.0492
.50	50.5	71.1	.50	49.5	72.5	415.6	71.7	.0604

TABLE 37
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE TOTAL OF 105.2 MG
OF SYNTHETIC CONTAMINANT ADDED. TEST
SPECIMEN (S/N 022) INLET PRESSURE = 415
PSIA (NOMINAL).

TEST NUMBER 11 PART 22J TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (CFM)	AVG GROSS DIFF. PRESS PRIMARY (PSI)	AVG GROSS DIFF. PRESS SECONDARY (PSI)	AVG GROSS DIFF. PRESS (PSI)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
419.0	71.3	.060	290.81	290.81	290.81	.000	290.809
418.2	71.3	.493	192.713	192.713	192.713	.000	192.712
418.2	71.3	.371	124.678	124.678	124.678	.000	124.678
417.5	71.4	.131	96.515	96.515	96.515	.000	96.514
417.5	71.6	.244	71.665	71.616	71.691	.000	71.090
417.5	71.8	.106	43.761	43.91	43.836	.000	43.835
417.5	72.1	.164	43.355	43.504	43.459	.000	43.459
417.5	72.1	.258	75.159	75.906	75.553	.000	75.552
416.9	72.1	.31	100.312	100.312	100.312	.000	100.312
416.9	72.	.362	123.412	123.412	123.412	.000	123.412
416.2	71.8	.492	193.029	193.09	193.129	.000	193.029
415.6	71.7	.064	302.835	302.835	302.835	.000	302.834

TARE DIFF. PRESS = -3.4000E-05 + -4.4400E-14 (ACF) + 1.50933E-01 (ACF)**2 + 0 (ACFM)**3

ORIGINAL PAGE IS
OF POOR QUALITY

PAGE: 3
DATE: 9-10-76

TABLE 37
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE - TOTAL OF 105.2 MG
OF SYNTHETIC CONTAMINANT ADDED. TEST
SPECIMEN (S/N 022) INLET PRESSURE = 415
PSIA (NOMINAL).

TEST NUMBER 11 PART 2PJ TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESS

PRESSURE		TEMPERATURE			FLOW RATE					NET DIFFERENTIAL PRESS	
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	CFM	SCFM	GM2 KG/HR	GM2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID
29.493	419.5	295.1	21.8	71.3	48.4	0.647	1.708	3.362	7.412	20.4459	290.809
29.402	418.2	295.1	21.8	71.3	39.6	0.493	1.398	2.753	6.469	13.5490	192.712
29.402	418.2	295.1	21.8	71.3	29.8	0.371	1.054	2.75	4.575	8.7657	124.678
29.356	417.5	295.1	21.9	71.4	24.9	0.31	0.878	1.729	3.812	6.7856	96.514
29.356	417.5	295.1	22.0	71.6	19.7	0.240	0.697	1.372	3.024	4.9981	71.090
29.356	417.5	295.3	22.1	71.8	13.3	0.166	0.470	0.925	2.038	3.0819	43.835
29.356	417.5	295.4	22.1	72.1	11.1	0.164	0.464	0.913	2.013	3.0555	43.459
29.356	417.5	295.4	22.3	72.1	20.7	0.253	0.730	1.438	3.170	5.3118	75.552
29.311	416.9	295.4	22.2	72.1	25.4	0.318	0.898	1.768	3.898	7.0526	100.312
29.311	416.9	295.4	22.2	72.1	20.4	0.260	0.739	2.045	4.509	8.6767	123.412
29.265	416.2	295.3	22.1	71.3	39.3	0.492	1.388	2.734	6.027	13.5713	193.029
29.219	415.6	295.2	22.1	71.7	48.2	0.648	1.772	3.351	7.387	21.2914	302.834
****	****	****	****	****	****	****	****	****	****	****	****
29.349	417.4	295.2	22.1	71.7							
0.048	0.1	0.1	0.1	0.3	DEFINITIONS						

TABLE 38
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 12 PART 22F TEST DESCRIPTION

CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE. DATA ACQUIRED IN THE NORMAL FLOW DIRECTION (S/N SIDE UPSTREAM) AFTER THE ADDITION OF 5.2 MG OF SYNTHETIC CONTAMINANT AND AFTER 2 HIGH PRESSURE (10,000 PSIA NOMINAL) GN₂ IMPACT CYCLES. TEST SPECIMEN (S/N 028) INLET PRESSURE = 1000 PSIA (NOMINAL). TEST SPECIMEN INLET CONDITIONS

FLOWMETER CONDITIONS

FLOWMETER ONE

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (L/CM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (L/CM)
.84	42.7	66.6	.91	47.6	69.6	111.9	67.1	.0420
.76	50.4	67.8	.81	48.5	68.9	111.9	66.3	.0382
.67	50.2	67.1	.71	48.7	68.4	111.9	65.7	.0334
.58	50.2	63.7	.60	49.1	68.1	111.9	65.6	.0290
.49	50.6	63.1	.50	49.7	68.1	111.9	65.5	.0246
.40	50.2	63.3	.40	49.5	68.1	111.9	65.7	.0198
.30	50.4	63.9	.30	49.9	68.5	111.9	66.2	.0150
.26	50.2	64.3	.26	49.9	68.7	1011.9	66.5	.0127
.21	50.2	64.8	.21	49.9	69.0	1011.9	66.2	.0102
.14	50.4	65.8	.14	49.1	69.4	1007.9	67.6	.0069
.14	50.2	65.6	.14	49.9	70.0	1011.9	68.3	.0069
.22	50.4	66.5	.22	50.1	69.9	1011.9	68.2	.0108
.26	50.4	66.3	.25	49.9	69.9	1011.9	68.1	.0127
.30	50.6	66.9	.30	50.1	69.8	1011.9	67.9	.0151
.40	50.4	65.1	.40	49.9	69.4	1007.9	67.3	.0199
.49	50.4	64.3	.50	49.5	69.1	1007.9	66.7	.0245
.58	42.9	63.7	.60	48.5	68.6	1007.9	66.1	.0296
.67	49.7	62.7	.71	48.3	67.8	1007.9	65.2	.0335
.75	49.7	62.0	.80	47.8	67.1	1007.9	64.6	.0376
.87	42.7	61.3	.91	47.4	66.4	1007.9	63.9	.0429

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 38
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE. DATA ACQUIRED IN THE NORMAL FLOW DIRECTION (S/N SIDE UPSTREAM) AFTER THE ADDITION OF 5.2 MG OF SYNTHETIC CONTAMINANT AND AFTER 2 HIGH PRESSURE (10,000 PSIA NOMINAL) GN2 IMPACT CYCLES. TEST SPECIMEN (S/N 028) INLET PRESSURE = 1000 PSIA (NOMINAL).

TEST UPPER 12

PART 28F

TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
1011.9	07.1	.1342	151.618	151.618	151.618	0.000	151.618
1011.9	06.3	.1362	133.941	133.941	133.941	0.000	133.942
1011.9	05.7	.1334	112.477	112.477	112.477	0.000	112.477
1011.9	05.6	.0290	94.169	94.169	94.169	0.000	94.170
1011.9	05.5	.0246	76.493	76.493	76.493	0.000	76.490
1011.9	05.7	.0198	58.244	58.244	58.244	0.000	58.244
1011.9	06.2	.0150	42.105	42.105	42.105	0.000	42.105
1011.9	06.5	.0127	34.416	34.416	34.416	0.000	34.491
1011.9	06.9	.0112	26.376	26.376	26.376	0.000	26.379
1007.9	07.0	.0089	16.455	16.455	16.491	0.000	16.491
1011.9	08.0	.0089	16.339	16.339	16.376	0.000	16.376
1011.9	08.2	.0113	28.110	28.110	28.109	0.000	28.110
1011.9	08.1	.0127	33.953	33.953	34.057	0.000	34.057
1011.9	07.9	.0151	41.949	41.949	42.018	0.000	42.018
1007.9	07.7	.0199	57.861	57.861	58.023	0.000	58.023
1007.9	06.7	.0245	75.285	75.285	75.415	0.000	75.416
1007.9	05.1	.0286	92.275	92.275	92.275	0.000	92.276
1007.9	05.2	.0335	111.846	111.846	111.846	0.000	111.846
1007.9	04.0	.0376	129.838	129.838	129.838	0.000	129.838
1007.9	03.9	.0420	150.356	150.356	150.355	0.000	150.356

INLET DIFF. PRESS = $-1.64000E-04 + -1.2693E-02$ (ACFM) + $2.48070E-01$ (ACFM)**2 +

0 (ACFM)**3

TABLE 38
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE. DATA ACQUIRED IN THE NORMAL FLOW DIRECTION (S/N SIDE UPSTREAM) AFTER THE ADDITION OF 5.2 MG OF SYNTHETIC CONTAMINANT AND AFTER 2 HIGH PRESSURE (10,000 PSIA NOMINAL) GN₂ IMPACT CYCLES. TEST SPECIMEN (S/N 028) INLET PRESSURE = 1000 PSIA (NOMINAL). NET DIFFERENTIAL PRESSURE = 1000 PSIA (NOMINAL).

TEST NUMBER 12 FORT PPF TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

PRESSURE		TEMPERATURE			FLOW RATE						
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN ₂ KG/HR	GN ₂ LBS/HR	KG/SQ CM DIFFERENTIAL	PSID
71.144	1011.7	292.7	19.4	67.1	10.3	0.020	2.907	5.724	12.620	10.6598	151.618
71.144	1011.7	292.2	19.1	66.3	7.1	0.034	2.648	5.219	11.496	9.4170	133.942
71.144	1011.7	291.9	18.7	65.7	10.7	0.034	2.321	4.570	10.074	7.9080	112.477
71.144	1011.7	291.8	18.6	65.6	7.6	0.020	2.014	3.965	8.742	6.6208	94.170
71.144	1011.7	291.8	18.6	65.5	4.4	0.020	1.711	3.367	7.422	5.3707	76.390
71.144	1011.7	291.9	18.7	65.7	3.8	0.018	1.372	2.704	5.956	4.0950	58.244
71.144	1011.7	292.2	19.0	66.2	4.5	0.015	1.063	2.054	4.529	2.9603	42.105
71.144	1011.7	292.3	19.2	66.5	2.5	0.0127	.881	1.735	3.826	2.4249	34.491
71.144	1011.7	292.1	19.4	66.9	2.1	0.012	.709	1.397	3.080	1.8546	26.379
70.865	1007.7	292.9	19.8	67.0	13.5	0.069	.477	2.939	2.069	1.1595	16.491
71.144	1011.7	293.3	20.2	68.3	13.4	0.069	.474	2.934	2.059	1.1514	16.376
71.144	1011.7	293.3	20.1	68.2	11.2	0.063	.748	1.473	3.248	1.9763	28.110
71.144	1011.7	293.2	20.1	68.1	14.8	0.071	.875	1.722	3.797	2.3945	34.057
71.144	1011.7	293.1	19.9	67.9	10.5	0.051	1.041	2.050	4.520	2.9542	42.018
70.865	1007.7	292.8	19.8	67.3	10.9	0.059	1.373	2.703	5.959	4.0795	58.023
70.865	1007.7	292.1	19.3	66.7	4.2	0.024	1.694	3.335	7.352	5.3022	75.416
70.865	1007.7	292.1	19.0	66.1	5.0	0.020	1.978	3.594	8.586	6.4876	92.276
70.865	1007.7	291.5	18.5	65.2	6.6	0.034	2.318	4.563	10.164	7.8636	111.846
70.865	1007.7	291.3	18.1	64.5	7.5	0.0376	2.607	5.134	11.318	9.1285	129.838
70.865	1007.7	291.4	17.7	63.9	4.2	0.0424	2.973	5.054	12.907	10.5711	150.356
71.046	1010.5	292.3	19.2	66.5							
.127	1.0	.5	.5	1.0	DEVIATIONS						

ORIGINAL PAGE IS
OF POOR QUALITY

PAGE: 1
DATE: 9-15-76

TABLE 39
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 12 PART 296 TEST DESCRIPTION

CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE. DATA ACQUIRED IN THE NORMAL FLOW DIRECTION (S/N SIDE UPSTREAM) AFTER THE ADDITION OF 5.2 MG OF SYNTHETIC CONTAMINANT AND AFTER 2 HIGH PRESSURE (10,000 PSIA NOMINAL) GN₂ IMPACT CYCLES. TEST SPECIMEN (S/N 028) INLET PRESSURE = 415 PSIA (NOMINAL).

FLOW TEST CONDITIONS

TEST SPECIMEN INLET CONDITIONS

***** FLOWMETER ONE ***** FLOWMETER TWO *****

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.50	51.4	71.7	.50	49.5	72.1	414.3	71.4	.0603
.40	50.4	71.6	.40	49.9	72.1	413.7	71.3	.0490
.30	50.6	71.7	.30	49.1	72.2	413.7	71.4	.0369
.26	49.7	71.7	.26	49.1	72.2	413.0	71.4	.0311
.21	50.2	71.8	.21	49.9	72.3	413.1	71.5	.0247
.14	50.2	71.9	.14	49.9	72.4	413.1	71.7	.0168
.14	49.9	71.1	.14	49.5	72.6	413.0	71.8	.0167
.21	50.1	71.0	.21	49.7	72.6	412.4	71.8	.0256
.26	50.1	71.0	.26	49.7	72.4	412.4	71.6	.0308
.31	50.4	71.1	.31	49.9	72.3	411.7	71.4	.0374
.40	50.2	71.3	.40	49.5	72.2	411.1	71.2	.0489
.49	50.2	71.2	.50	49.1	71.9	410.4	71.0	.0600

TABLE 39
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE. DATA ACQUIRED IN THE NORMAL FLOW DIRECTION (S/N SIDE UPSTREAM) AFTER THE ADDITION OF 5.2 MG OF SYNTHETIC CONTAMINANT AND AFTER 2 HIGH PRESSURE (10,000 PSIA NOMINAL) GN₂ IMPACT CYCLES. TEST SPECIMEN (S/N 028) INLET PRESSURE = 415 PSIA (NOMINAL).

TEST NUMBER PART NO TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
414.2	71.4	259.3	259.460	259.406	259.460	0.000	259.465
413.7	71.3	174.1	174.24	174.24	174.24	0.000	174.239
413.7	71.4	114.3	114.26	114.26	114.266	0.000	114.265
413.0	71.4	90.3	90.32	90.32	90.326	0.000	90.319
413.0	71.5	66.1	66.12	66.14	66.149	0.000	66.149
413.0	71.7	41.0	41.06	41.05	41.09	0.000	41.099
413.0	71.9	40.6	40.50	40.71	40.608	0.000	40.607
412.4	71.4	89.5	89.39	89.75	89.578	0.000	89.577
412.4	71.6	89.5	89.42	89.45	89.534	0.000	89.533
411.7	71.4	175.3	175.42	175.42	175.422	0.000	175.422
411.1	71.2	175.1	175.18	175.17	175.187	0.000	175.186
410.4	71.1	259.7	259.71	259.71	259.781	0.000	259.781

TAKE DIFF. PRESS = $-3.4000E-05 + -4.4400E-04 (ACFM) + 1.50933E-01 (ACFM)^2 + 0 (ACFM)^3$

ORIGINAL PAGE IS
OF POOR QUALITY

PAGE: 3
DATE: 9-15-76

TABLE 39
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST U5EX 12 PART 202

TEST DESCRIPTION

CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE. DATA ACQUIRED IN THE NORMAL FLOW DIRECTION (S/N SIDE UPSTREAM) AFTER THE ADDITION OF 5.2 MG OF SYNTHETIC CONTAMINANT AND AFTER 2 HIGH PRESSURE (10,000 PSIA NOMINAL) GN₂ IMPACT CYCLES. TEST SPECIMEN (S/N 028) INLET PRESSURE = 415 PSIA NET DIFFERENTIAL PRESSURE (NOMINAL) *****

TEST SPECIMEN INLET CONDITIONS

PRESSURE		TEMPERATURE			FLOW RATE						DIFFERENTIAL	
KG/SQ CM	PSI	DEG. K	DEG. C	DEG. F	LITERS/ MIN	CFM	SCFM	GM ³ /HR	GM ³ /HR	KG/SQ CM	PSID	
29.128	414.0	295.1	21.7	71.4	6.00	0.03	1.644	3.339	7.354	18.2422	259.465	
29.083	413.1	295.1	21.9	71.3	32.9	0.47	1.375	2.707	5.967	12.2502	174.239	
29.083	413.1	295.1	21.9	71.4	24.3	0.344	1.035	2.139	4.492	8.0337	114.265	
29.037	412.1	295.1	21.9	71.4	24.7	0.311	.871	1.714	3.779	6.3501	90.319	
29.037	412.1	295.1	22.0	71.5	19.6	0.247	.692	1.352	3.405	4.6507	66.149	
29.037	412.1	295.2	22.1	71.7	17.4	0.144	.477	.922	2.047	2.8895	41.099	
29.037	412.1	295.3	22.1	71.8	13.2	0.147	.408	.921	2.031	2.8550	40.507	
28.992	412.4	295.3	22.1	71.8	11.2	0.250	.715	1.404	3.134	4.8918	69.577	
28.992	412.4	295.2	22.0	71.4	11.4	0.311	.962	1.690	3.740	6.2948	89.533	
28.946	411.7	295.1	21.7	71.4	12.0	0.314	1.045	2.055	4.537	8.2556	117.422	
28.900	411.1	295.0	21.6	71.2	3.0	0.402	1.364	2.080	5.922	12.3168	175.186	
28.855	410.4	294.7	21.7	71.1	7.3	0.061	1.671	3.290	7.254	18.2644	259.781	
*****	*****	*****	*****	*****								
29.011	412.0	295.1	21.9	71.1								
.061	.0	.1	.1	.2	DIVISIONS							

TABLE 40
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE.
DATA ACQUIRED IN THE NORMAL FLOW DIRECTION (S/N SIDE UP-
STREAM) AFTER THE ADDITION OF 5.2 MG OF SYNTHETIC CONTAMINANT
AND AFTER 10 HIGH PRESSURE (10,000 PSIA NOMINAL) GN₂ IMPACT
CYCLES. TEST SPECIMEN (S/N 028) INLET PRESSURE = 1000 PSIA
(NOMINAL).

TEST NUMBER 12 PART 28I

TEST DESCRIPTION

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)
.86	42.9	55.8
.76	50.1	55.2
.67	50.1	54.9
.58	50.8	55.0
.49	50.4	55.4
.40	50.4	56.0
.30	50.1	56.5
.26	42.7	57.0
.21	42.7	57.5
.14	50.4	58.6
.14	50.4	60.1
.21	42.9	60.3
.25	42.7	60.1
.31	50.1	59.9
.40	50.2	59.1
.49	50.2	58.1
.58	50.1	57.5
.67	42.9	56.8
.76	50.1	56.1
.87	50.4	55.4

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)
.91	47.6	61.6
.81	48.3	60.8
.70	48.5	60.5
.60	49.5	60.5
.50	42.5	60.7
.40	49.7	61.0
.30	49.5	61.3
.25	49.3	61.6
.20	49.3	62.0
.13	50.2	62.7
.13	50.2	63.6
.21	49.5	63.7
.25	49.3	63.8
.30	49.5	63.7
.40	49.5	63.4
.50	49.3	63.0
.60	48.9	62.5
.71	48.5	61.9
.81	48.3	61.3
.91	48.3	60.5

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
1007.9	58.7	.0427
1007.9	58.0	.0382
1007.9	57.7	.0335
1007.9	57.7	.0295
1007.9	58.0	.0246
1007.9	58.5	.0198
1007.9	58.9	.0147
1007.9	59.3	.0125
1007.9	59.8	.0101
1007.9	60.6	.0067
1007.9	61.9	.0067
1007.9	62.0	.0104
1007.9	62.0	.0122
1007.9	61.8	.0150
1007.9	61.3	.0198
1007.9	60.6	.0246
1007.9	60.0	.0290
1007.9	59.3	.0337
1007.9	58.7	.0382
1007.9	57.9	.0435

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 40
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE
DATA ACQUIRED IN THE NORMAL FLOW DIRECTION (S/N SIDE UP-
STREAM) AFTER THE ADDITION OF 5.2 MG OF SYNTHETIC CONTAMINANT
AND AFTER 10 HIGH PRESSURE (10,000 PSIA NOMINAL) GN2 IMPACT
CYCLES. TEST SPECIMEN (S/N 028) INLET PRESSURE = 1000 PSIA
(NOMINAL).

TEST NUMBER 12 PART 281

TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

INLET PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
1007.2	56.7	.0427	119.044	119.044	119.044	-0.000	119.044
1007.2	58.0	.0382	104.506	104.506	104.506	-0.000	104.506
1007.2	57.7	.0335	88.200	88.704	88.452	-0.000	88.452
1007.9	57.7	.0295	74.543	74.798	74.670	-0.000	74.670
1007.9	58.0	.0246	59.232	59.627	59.429	-0.000	59.430
1007.2	58.5	.0198	44.863	45.089	44.976	-0.000	44.976
1007.9	58.9	.0147	31.172	31.283	31.228	-0.000	31.228
1007.2	59.3	.0125	25.719	25.756	25.738	-0.000	25.738
1007.9	59.8	.0101	19.686	19.665	19.675	-0.000	19.676
1007.2	60.6	.0067	12.028	12.040	12.034	-0.000	12.034
1007.2	61.9	.0067	11.912	12.040	11.976	-0.000	11.976
1007.9	62.0	.0104	20.266	20.412	20.339	-0.000	20.339
1007.9	62.0	.0122	24.849	25.009	24.929	-0.000	24.929
1007.9	61.8	.0150	31.984	32.147	32.066	-0.000	32.066
1007.2	61.3	.0198	44.863	44.773	44.818	-0.000	44.818
1007.9	60.6	.0246	58.980	58.995	58.988	-0.000	58.988
1007.9	60.0	.0290	73.038	72.901	72.970	-0.000	72.970
1007.2	59.3	.0337	89.076	89.020	89.048	-0.000	89.048
1007.2	58.7	.0382	104.190	104.190	104.190	-0.000	104.190
1007.2	57.9	.0435	122.837	122.837	122.837	-0.000	122.837

TARE DIFF. PRESS = -1.64000E-04 + -1.26930E-02 (ACFM) + 2.48070E-01 (ACFM)**2 +

0 (ACFM)**3

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 40
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE.
DATA ACQUIRED IN THE NORMAL FLOW DIRECTION (S/N SIDE UP-
STREAM) AFTER THE ADDITION OF 5.2 MG OF SYNTHETIC CONTAMINANT
AND AFTER 10 HIGH PRESSURE (10,000 PSIA NOMINAL) GN₂ IMPACT
CYCLES. TEST SPECIMEN (S/N 028) INLET PRESSURE = 1000 PSIA
(NOMINAL).

TEST NUMBER 12 PART 281

TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESS

PRESSURE		TEMPERATURE			FLOW RATE					NET DIFFERENTIAL PRESS	
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN ₂ KG/HR	GN ₂ LBS/HR	KG/SQ CM DIFFERENTIAL	PSID
70.865	1007.2	288.0	14.8	58.7	84.7	.0427	2.992	5.892	12.990	8.3696	119.044
70.865	1007.2	287.6	14.4	58.0	75.8	.0382	2.677	5.271	11.620	7.3475	104.506
70.865	1007.2	287.4	14.3	57.7	66.6	.0335	2.352	4.632	10.211	6.2188	88.452
70.865	1007.2	287.5	14.3	57.7	58.6	.0295	2.068	4.073	8.979	5.2499	74.670
70.865	1007.2	287.6	14.5	58.0	48.9	.0246	1.727	3.400	7.496	4.1783	59.430
70.865	1007.2	287.9	14.7	58.5	39.3	.0198	1.387	2.730	6.019	3.1622	44.276
70.865	1007.2	288.1	14.9	58.9	29.2	.0147	1.032	2.034	4.480	2.1955	31.228
70.865	1007.2	288.3	15.2	59.3	24.8	.0125	.874	1.721	3.795	1.8095	25.738
70.865	1007.2	288.6	15.4	59.8	20.0	.0101	.708	1.394	3.072	1.3833	19.676
70.865	1007.2	289.1	15.9	60.6	13.2	.0067	.466	.911	2.022	.8461	12.034
70.865	1007.2	289.8	16.6	61.9	13.2	.0067	.465	.919	2.017	.8420	11.976
70.865	1007.2	289.8	16.7	62.0	20.4	.0104	.722	1.422	3.134	1.4300	20.339
70.865	1007.2	289.8	16.6	62.0	24.1	.0122	.849	1.673	3.688	1.7527	24.929
70.865	1007.2	289.7	16.6	61.8	29.6	.0150	1.046	2.061	4.543	2.2545	32.066
70.865	1007.2	289.4	16.3	61.3	39.0	.0198	1.377	2.711	5.977	3.1510	44.818
70.865	1007.2	289.0	15.9	60.6	48.6	.0246	1.718	3.382	7.456	4.1473	58.988
70.865	1007.2	288.7	15.5	60.0	57.3	.0290	2.023	3.984	8.783	5.1303	72.970
70.865	1007.2	288.3	15.2	59.3	66.8	.0337	2.358	4.643	10.236	6.2607	89.048
70.865	1007.2	288.0	14.8	58.7	75.7	.0382	2.673	5.263	11.603	7.3253	104.190
70.865	1007.2	287.6	14.4	57.9	86.4	.0435	3.050	6.005	13.240	8.6363	122.837
****	****	****	****	****	****	****	****	****	****	****	****
70.865	1007.2	288.5	15.4	59.6							
.000	.0	.7	.7	1.3							

DEVIATIONS

TABLE 41
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE,
DATA ACQUIRED IN THE NORMAL FLOW DIRECTION (S/N SIDE UPSTREAM)
AFTER THE ADDITION OF 5.2 MG OF SYNTHETIC CONTAMINANT AND
AFTER 10 HIGH PRESSURE (10,000 PSIA NOMINAL) GN₂ IMPACT
CYCLES. TEST SPECIMEN (S/N 028) INLET PRESSURE = 415 PSIA
(NOMINAL).

TEST NUMBER 12 PART 28J TEST DESCRIPTION

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE			FLOWMETER TWO			TEST SPECIMEN INLET CONDITIONS		
FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.59	50.4	69.1	.61	49.3	69.8	414.8	69.5	.0718
.50	50.8	69.1	.50	49.9	69.9	414.2	69.5	.0606
.40	50.4	69.2	.40	49.9	70.1	413.5	69.6	.0487
.31	50.2	69.4	.31	49.9	70.2	413.5	69.8	.0374
.26	49.9	69.7	.25	49.5	70.4	413.5	70.0	.0307
.21	50.1	69.9	.20	49.9	70.6	413.5	70.2	.0250
.14	50.1	70.2	.13	49.9	70.8	413.5	70.5	.0165
.14	49.9	70.7	.13	49.5	71.2	413.5	70.9	.0163
.21	49.7	70.6	.21	49.3	71.2	413.5	70.9	.0251
.26	50.2	70.6	.25	49.9	71.2	413.5	70.9	.0309
.31	50.1	70.6	.31	49.5	71.3	412.9	70.9	.0371
.41	50.2	70.4	.41	49.5	71.4	412.9	70.9	.0491
.50	50.1	70.3	.50	49.2	71.3	412.2	70.8	.0601
.60	50.6	70.4	.60	49.3	71.3	411.6	70.8	.0725

TABLE 41
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE
DATA ACQUIRED IN THE NORMAL FLOW DIRECTION (S/N SIDE UPSTREA.)
AFTER THE ADDITION OF 5.2 MG OF SYNTHETIC CONTAMINANT AND
AFTER 10 HIGH PRESSURE (10,000 PSIA NOMINAL) GN₂ IMPACT
CYCLES. TEST SPECIMEN (S/N 028) INLET PRESSURE = 415 PSIA
(NOMINAL).

TEST NUMBER 12 PART 28J TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
414.8	69.5	.0718	266.831	266.831	266.831	.001	266.830
414.2	69.5	.0606	185.393	185.393	185.393	.000	185.392
413.5	69.6	.0487	129.838	129.838	129.838	.000	129.837
413.5	69.8	.0374	89.505	89.435	89.470	.000	89.469
413.5	70.0	.0347	68.853	69.233	69.143	.000	69.042
413.5	70.2	.0250	51.668	52.188	51.928	.000	51.927
413.5	70.5	.0165	30.998	31.172	31.035	-0.000	31.034
413.5	70.9	.0103	30.650	31.899	30.774	-0.000	30.774
413.5	70.9	.0201	52.798	53.135	52.966	.000	52.966
413.5	70.9	.0309	69.103	69.549	69.325	.000	69.325
412.9	70.9	.0371	88.755	89.119	88.937	.000	88.936
412.9	70.9	.0491	132.995	132.995	132.995	.000	132.994
412.2	70.8	.0601	186.024	186.024	186.024	.000	186.023
411.6	70.8	.0725	266.831	266.831	266.831	.001	266.830

TARE DIFF. PRESS = -3.40000E-05 + -4.44000E-04 (ACFM) + 1.50933E-01 (ACFM)**2 + 0 (ACFM)**3

TABLE 41
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE
DATA ACQUIRED IN THE NORMAL FLOW DIRECTION (S/N SIDE UPSTREAM)
AFTER THE ADDITION OF 5.2 MG OF SYNTHETIC CONTAMINANT AND
AFTER 10 HIGH PRESSURE (10,000 PSIA NOMINAL) GN₂ IMPACT
CYCLES. TEST SPECIMEN (S/N 028) INLET PRESSURE = 415 PSIA
(NOMINAL).

TEST NUMBER 12 PART 28J TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESS

PRESSURE		TEMPERATURE			FLOW RATE					NET DIFFERENTIAL PRESS	
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID
29.165	414.0	294.0	20.8	69.5	57.5	0.714	2.030	3.290	8.810	18.7600	266.830
29.119	414.0	294.1	20.8	69.5	48.4	0.606	1.708	3.364	7.415	13.0344	185.392
29.073	413.9	294.1	20.9	69.6	38.8	0.487	1.371	2.700	5.952	9.1285	129.837
29.073	413.9	294.2	21.0	69.8	29.8	0.374	1.053	2.073	4.571	6.2903	89.469
29.073	413.9	294.3	21.1	70.0	24.5	0.307	.864	1.704	3.751	4.8541	69.042
29.073	413.9	294.4	21.2	70.2	19.9	0.250	.702	1.381	3.046	3.6508	51.927
29.073	413.9	294.5	21.4	70.5	13.1	0.165	.463	.914	2.011	2.1819	31.034
29.073	413.9	294.8	21.0	70.9	13.0	0.163	.457	.901	1.986	2.1636	30.774
29.073	413.9	294.8	21.0	70.9	20.0	0.251	.706	1.382	3.063	3.7239	52.966
29.073	413.9	294.8	21.0	70.9	24.5	0.309	.866	1.709	3.761	4.8740	69.325
29.028	412.9	294.8	21.0	70.9	29.4	0.371	1.039	2.049	4.510	6.2528	88.936
29.028	412.9	294.8	21.0	70.9	39.0	0.491	1.377	2.714	5.979	9.3504	132.994
28.982	412.4	294.7	21.0	70.8	47.7	0.601	1.684	3.319	7.310	13.0787	186.023
28.937	411.0	294.7	21.0	70.8	57.4	0.725	2.028	3.994	8.801	18.7600	266.830
29.060	413.3	294.5	21.3	70.4							
0.038	.5	.3	.3	.5	DEVIATIONS						

TABLE 42
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE.
DATA ACQUIRED IN THE NORMAL FLOW DIRECTION (S/N SIDE UPSTREAM,
AFTER THE ADDITION OF 10.2 MG OF SYNTHETIC CONTAMINANT AND AFTER
20 HIGH PRESSURE (10,000 PSIA NOMINAL) GN₂ IMPACT CYCLES.
TEST SPECIMEN (S/N 028) INLET PRESSURE = 1000 PSIA (NOMINAL).

TEST NUMBER 12

PART 28L

TEST DESCRIPTION

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE			FLOWMETER TWO			TEST SPECIMEN INLET CONDITIONS		
FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
0.86	30.4	64.7	0.90	41.9	69.8	1011.9	67.3	0.429
0.78	30.2	63.5	0.90	48.3	68.2	1011.9	65.8	0.384
0.69	30.1	63.1	0.70	48.5	67.6	1011.9	65.4	0.339
0.60	42.7	62.4	0.60	49.5	67.6	1011.9	65.2	0.291
0.50	42.9	62.5	0.50	48.9	67.6	1011.9	65.0	0.246
0.40	30.8	62.3	0.40	42.9	67.7	1011.9	65.3	0.199
0.32	42.9	63.5	0.30	49.3	68.3	1011.9	65.9	0.152
0.26	42.1	64.5	0.25	49.1	68.8	1011.9	66.7	0.126
0.21	30.4	65.8	0.20	50.1	69.3	1011.9	67.5	0.104
0.14	30.2	65.7	0.13	49.9	69.8	1011.9	67.8	0.069
0.14	42.4	63.0	0.13	49.5	70.7	1011.9	69.4	0.068
0.22	30.2	67.4	0.21	49.9	71.0	1011.9	69.4	0.105
0.27	30.1	67.5	0.20	49.9	71.1	1011.9	69.3	0.129
0.32	30.1	67.3	0.31	49.5	71.0	1011.9	69.1	0.153
0.41	42.4	66.7	0.40	49.3	70.6	1011.9	68.6	0.199
0.50	42.4	63.7	0.50	48.4	70.1	1011.9	67.9	0.246
0.60	42.4	65.0	0.60	48.7	69.6	1011.9	67.3	0.293
0.69	42.4	64.4	0.70	48.3	69.1	1011.9	66.8	0.338
0.78	42.4	63.4	0.81	48.3	68.2	1007.9	66.0	0.386
0.87	30.4	63.2	0.91	48.3	67.6	1007.9	65.4	0.435

TABLE 42
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE.
DATA ACQUIRED IN THE NORMAL FLOW DIRECTION (S/N SIDE UPSTREAM,
AFTER THE ADDITION OF 10.2 MG OF SYNTHETIC CONTAMINANT AND AFTER
20 HIGH PRESSURE (10,000 PSIA NOMINAL) GN_2 IMPACT CYCLES.
TEST SPECIMEN (S/N 028) INLET PRESSURE = 1000 PSIA (NOMINAL).

TEST NUMBER 12

PART 28L

TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

TEST NUMBER	INLET PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GRUSS DIFF. PRESS PRIMARY (PSID)	GRUSS DIFF. PRESS SECONDARY (PSID)	AVG GRUSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
1011.9	07.3	00429	158.971	158.971	158.971	-0.000	158.971	
1011.9	05.8	00384	133.088	133.088	133.088	-0.000	133.088	
1011.9	05.4	00339	109.660	109.660	109.660	-0.000	109.660	
1011.9	05.2	00291	86.441	86.413	86.670	-0.000	86.677	
1011.9	05.0	00246	66.582	67.002	66.642	-0.000	66.642	
1011.9	05.3	00199	48.361	48.071	48.516	-0.000	48.516	
1011.9	05.9	00152	32.659	32.666	32.666	-0.000	32.660	
1011.9	06.7	00105	25.011	25.022	25.016	-0.000	25.017	
1011.9	07.5	00104	18.811	18.893	18.851	-0.000	18.851	
1011.9	07.8	00059	10.931	10.880	10.909	-0.000	10.909	
1011.9	09.4	00008	10.700	10.829	10.764	-0.000	10.765	
1011.9	09.4	00105	19.043	19.177	19.110	-0.000	19.110	
1011.9	09.3	00124	25.474	25.596	25.537	-0.000	25.535	
1011.9	09.1	00103	32.659	32.833	32.746	-0.000	32.746	
1011.9	08.6	00199	48.129	48.139	48.084	-0.000	48.084	
1011.9	07.9	00246	66.557	66.066	66.621	-0.000	66.622	
1011.9	07.3	00243	87.564	87.861	87.713	-0.000	87.713	
1011.9	06.8	00338	109.660	109.668	109.668	-0.000	109.668	
1007.9	06.0	00386	134.952	134.952	134.952	-0.000	134.952	
1007.9	05.4	00435	164.026	164.028	164.028	-0.000	164.028	

TARE DIFF. PRESS = $-1.6+000E-04 + -1.26930E-02$ (ACFM) + $2.48070E-01$ (ACFM)**2 + 0 (ACFM)**3

TABLE 42
FLOW RATE VERSUS DIFFERENTIAL PRESSURE
CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE.
DATA ACQUIRED IN THE NORMAL FLOW DIRECTION (S/N SIDE UPSTREAM)
AFTER THE ADDITION OF 10.2 MG OF SYNTHETIC CONTAMINANT AND AFTER
20 HIGH PRESSURE (10,000 PSIA NOMINAL) GN₂ IMPACT CYCLES.
TEST NUMBER 12 PART 28L TEST DESCRIPTION TEST SPECIMEN (S/N 028) INLET PRESSURE = 1000 PSIA (NOMINAL).

TEST SPECIMEN INLET CONDITIONS											NET DIFFERENTIAL PRESS.	
PRESSURE		TEMPERATURE			FLOW RATE						DIFFERENTIAL	
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN ₂ KG/HR	GN ₂ LBS/HR	KG/SQ CM	PSIA	
71.144	1011.7	292.4	19.0	67.3	84.0	0.0429	2.967	5.841	12.878	11.1768	159.271	
71.144	1011.7	292.0	18.9	65.8	75.5	0.0384	2.667	5.254	11.579	9.3992	133.688	
71.144	1011.7	291.7	18.7	65.4	66.0	0.0339	2.352	4.834	10.211	7.7104	109.668	
71.144	1011.7	291.0	18.5	65.2	57.2	0.0291	2.019	3.970	8.765	6.0940	86.577	
71.144	1011.7	291.0	18.4	65.0	48.3	0.0246	1.707	3.361	7.411	4.6995	66.842	
71.144	1011.7	291.7	18.5	65.3	39.1	0.0199	1.380	2.710	5.988	3.4110	48.516	
71.144	1011.7	292.0	18.0	65.9	29.9	0.0152	1.054	2.070	4.577	2.2962	32.660	
71.144	1011.7	292.4	19.3	66.7	24.8	0.0126	.875	1.724	3.796	1.7588	25.017	
71.144	1011.7	292.9	19.7	67.5	20.3	0.0104	.717	1.411	3.111	1.3254	18.851	
71.144	1011.7	293.0	19.9	67.8	13.4	0.0069	.474	.934	2.059	.7670	10.809	
71.144	1011.7	293.9	20.4	69.4	13.3	0.0068	.469	.924	2.037	.7568	10.765	
71.144	1011.7	294.0	20.8	69.4	20.5	0.0105	.723	1.422	3.138	1.3436	19.110	
71.144	1011.7	293.9	20.7	69.3	25.2	0.0129	.892	1.750	3.870	1.7953	25.535	
71.144	1011.7	293.8	20.0	69.1	29.9	0.0153	1.055	2.071	4.579	2.3023	32.746	
71.144	1011.7	293.5	20.3	68.6	39.0	0.0199	1.376	2.702	5.972	3.3807	48.084	
71.144	1011.7	293.1	19.9	67.9	48.1	0.0240	1.698	3.343	7.370	4.6840	66.822	
71.144	1011.7	292.8	19.0	67.3	57.3	0.0293	2.025	3.981	8.790	6.1668	87.113	
71.144	1011.7	292.5	19.3	66.8	66.3	0.0338	2.340	4.801	10.157	7.7104	109.668	
70.865	1007.7	292.1	18.9	66.4	75.5	0.0380	2.668	5.253	11.581	9.4881	134.252	
70.865	1007.7	291.7	18.0	65.4	85.1	0.0430	3.006	5.920	13.051	11.5323	164.028	
71.119	1011.0	292.6	19.5	67.1								

0.050 .1 .1 .1 1.3 DEVIATIONS

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 43
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE.
DATA ACQUIRED IN THE NORMAL FLOW DIRECTION (S/N SIDE UPSTREAM)
AFTER THE ADDITION OF 10.2 MG OF SYNTHETIC CONTAMINANT AND AFTER
20 HIGH PRESSURE (10,000 PSIA NOMINAL) GN₂ IMPACT CYCLES.
TEST SPECIMEN (S/N 028) INLET PRESSURE = 415 PSIA (NOMINAL).

TEST NUMBER 12 PART 28M TEST DESCRIPTION

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)
.50	50.4	74.7
.41	50.4	74.7
.31	50.4	75.0
.26	50.1	75.1
.21	50.2	75.3
.15	50.2	75.9
.22	50.1	75.9
.26	50.2	75.9
.31	49.9	75.7
.40	50.2	75.6
.45	50.2	75.5
.50	50.1	75.5

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)
.50	49.8	76.7
.40	50.0	76.7
.30	50.0	76.9
.25	49.6	77.0
.20	50.0	77.0
.14	50.0	77.2
.21	49.8	77.2
.25	50.0	77.2
.31	49.4	77.2
.40	49.6	77.1
.45	49.4	76.9
.50	49.2	76.9

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
415.7	75.7	.0608
415.7	75.7	.0489
415.7	76.0	.0370
415.7	76.0	.0309
415.7	76.2	.0250
415.7	76.5	.0170
415.1	76.5	.0256
415.1	76.5	.0310
414.4	76.4	.0370
414.4	76.3	.0486
413.8	76.2	.0544
413.1	76.2	.0599

TABLE 43
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE
DATA ACQUIRED IN THE NORMAL FLOW DIRECTION (S/N SIDE UPSTREAM),
AFTER THE ADDITION OF 10.2 MG OF SYNTHETIC CONTAMINANT AND AFTER
20 HIGH PRESSURE (10,000 PSIA NOMINAL) GN_2 IMPACT CYCLES.
TEST SPECIMEN (S/N 028) INLET PRESSURE = 415 PSIA (NOMINAL).

TEST NUMBER 12

PART 28M

TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

INLET PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
415.7	75.7	.0608	248.628	248.628	248.628	.000	248.628
415.7	75.7	.0489	154.248	154.248	154.248	.000	154.248
415.7	76.0	.0370	94.590	94.590	94.590	.000	94.590
415.7	76.0	.0309	71.062	71.232	71.147	.000	71.146
415.7	76.2	.0250	51.395	51.662	51.528	.000	51.528
415.7	76.5	.0170	29.685	29.912	29.793	.000	29.793
415.1	76.5	.0256	52.900	53.240	53.070	.000	53.069
415.1	76.5	.0310	71.437	71.548	71.492	.000	71.492
414.4	76.4	.0370	95.222	95.222	95.222	.000	95.221
414.4	76.3	.0486	153.301	153.301	153.301	.000	153.301
413.8	76.2	.0544	192.442	192.442	192.442	.000	192.442
413.1	76.2	.0599	244.209	244.209	244.209	.000	244.209

TARE DIFF. PRESS = $-3.40000E-05 + -4.44000E-04$ (ACFM) + $1.50933E-01$ (ACFM)**2 + 0 (ACFM)**3

ORIGINAL PAGE IS
OF POOR QUALITY

PAGE: 3
DATE: 9-20-76

TABLE 43
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE.
DATA ACQUIRED IN THE NORMAL FLOW DIRECTION (S/N SIDE UPSTREAM)
AFTER THE ADDITION OF 10.2 MG OF SYNTHETIC CONTAMINANT AND AFTER
20 HIGH PRESSURE (10,000 PSIA NOMINAL) GN2 IMPACT CYCLES.
TEST SPECIMEN (S/N 028) INLET PRESSURE = 415 PSIA (NOMINAL).

TEST NUMBER 12 PART 28M

TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS											NET DIFFERENTIAL PRESS		
*****											*****		
PRESSURE		TEMPERATURE			FLOW RATE								
*****											*****		
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID		
29.229	415.1	297.5	24.3	75.7	48.1	.0673	1.700	3.347	7.378	17.4803	248.628		
29.229	415.1	297.4	24.3	75.7	38.7	.0489	1.368	2.694	5.940	10.8447	154.248		
29.229	415.1	297.6	24.4	76.6	29.3	.0370	1.036	2.040	4.497	6.6503	94.590		
29.229	415.1	297.6	24.5	76.0	24.5	.0339	.864	1.701	3.749	5.0021	71.146		
29.229	415.1	297.7	24.5	76.2	19.8	.0250	.700	1.379	3.039	3.6228	51.528		
29.229	415.1	297.9	24.7	76.5	13.5	.0170	.476	.931	2.065	2.0946	29.793		
29.183	415.1	297.9	24.7	76.5	20.2	.0256	.714	1.409	3.100	3.7312	53.069		
29.183	415.1	297.9	24.7	76.5	24.5	.0310	.865	1.702	3.755	5.0264	71.492		
29.138	414.4	297.8	24.7	76.4	29.2	.0370	1.032	2.031	4.478	6.6947	95.221		
29.138	414.4	297.8	24.6	76.3	38.3	.0486	1.353	2.665	5.875	10.7781	153.301		
29.092	413.8	297.7	24.6	76.2	42.9	.0544	1.514	2.981	6.571	13.5300	192.442		
29.046	413.1	297.7	24.5	76.2	47.2	.0599	1.665	3.279	7.228	17.1696	244.209		
****	****	****	****	****									
29.179	415.0	297.7	24.6	76.2									
.051	.1	.1	.1	.2	DEVIATIONS								

TABLE 44
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE.
DATA ACQUIRED IN THE REVERSE FLOW DIRECTION (S/N SIDE DOWN
STREAM) AFTER COMPLETION OF THE FORWARD FLOW TESTS AND AFTER THE
ADDITION OF 5.3 MG OF SYNTHETIC CONTAMINANT AND 10 HIGH PRESSURE
(10,000 PSIA NOMINAL) GN₂ IMPACT CYCLES. TEST SPECIMEN
(S/N 028) INLET PRESSURE = 1000 PSIA(NOMINAL).

TEST NUMBER 12 PART 280R

TEST DESCRIPTION

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)
.87	50.1	75.5
.78	50.1	74.4
.69	51.1	73.2
.60	50.2	73.5
.50	50.4	73.5
.41	50.4	73.6
.31	50.2	74.2
.26	50.1	74.6
.21	50.4	75.0
.14	50.2	75.7
.14	49.7	76.7
.22	50.4	76.4
.26	49.7	76.1
.31	50.1	76.7
.41	50.1	74.9
.50	49.9	73.0
.59	50.1	77.1
.69	51.2	72.3
.78	50.2	71.2
.87	49.9	70.5

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)
.91	47.6	80.6
.81	48.4	79.9
.71	48.4	79.3
.61	48.8	79.1
.50	49.5	79.1
.40	49.5	79.1
.30	49.5	79.3
.26	49.5	79.5
.20	49.9	79.6
.13	49.9	79.9
.13	49.2	79.4
.21	49.9	80.3
.26	49.2	79.2
.31	49.3	79.1
.40	49.2	79.6
.50	49.0	79.1
.60	48.8	78.5
.70	48.6	77.9
.81	48.4	77.1
.91	47.6	76.3

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
1017.2	78.0	.0426
1017.2	77.2	.0384
1017.2	76.6	.0339
1017.2	76.3	.0294
1017.2	76.3	.0246
1017.2	76.4	.0198
1017.2	76.7	.0151
1013.2	77.0	.0128
1017.2	77.3	.0103
1017.2	77.8	.0068
1017.2	78.5	.0067
1017.2	78.4	.0105
1017.2	78.2	.0127
1017.2	77.9	.0152
1013.2	77.3	.0199
1013.2	76.5	.0246
1013.2	75.8	.0290
1013.2	75.0	.0339
1013.2	74.1	.0386
1009.2	73.4	.0429

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 44
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE.
DATA ACQUIRED IN THE REVERSE FLOW DIRECTION (S/N SIDE DOWN
STREAM) AFTER COMPLETION OF THE FORWARD FLOW TESTS AND AFTER THE
ADDITION OF 5.3 MG OF SYNTHETIC CONTAMINANT AND 10 HIGH PRESSURE
(10,000 PSIA NOMINAL) CN₂ IMPACT CYCLES. TEST SPECIMEN
(S/N 028) INLET PRESSURE = 1000 PSIA (NOMINAL).

TEST NUMBER 12

PART 280K

TEST DESCRIPTION (S/N 028) INLET PRESSURE = 1000 PSIA (NOMINAL).

TEST SPECIMEN INLET CONDITIONS

TEST SPECIMEN INLET CONDITIONS	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	AVG GROSS DIFF. PRESS PRIMARY (PSID)	AVG GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
1017.2	18.1	1.426	125.840	125.840	125.840	-0.000	125.840
1017.2	17.2	1.384	109.110	109.110	109.110	-0.000	109.110
1017.2	16.6	1.339	92.569	92.569	92.569	-0.000	92.569
1017.2	16.3	1.294	76.722	76.722	76.722	-0.000	76.722
1017.2	15.3	1.246	61.971	61.971	61.971	-0.000	61.971
1017.2	16.4	1.194	46.642	46.642	46.642	-0.000	46.642
1017.2	16.7	1.151	33.084	33.084	33.084	-0.000	33.084
1013.2	17.1	1.128	27.000	27.000	27.000	-0.000	27.000
1017.2	17.3	1.013	20.685	20.685	20.685	-0.000	20.685
1017.2	17.6	1.068	12.510	12.510	12.510	-0.000	12.510
1017.2	18.5	1.067	12.341	12.341	12.341	-0.000	12.341
1017.2	18.4	1.015	21.144	21.144	21.144	-0.000	21.144
1017.2	18.2	1.127	26.711	26.711	26.711	-0.000	26.711
1017.2	17.9	1.152	33.431	33.431	33.431	-0.000	33.431
1013.2	17.3	1.199	46.816	46.816	46.816	-0.000	46.816
1013.2	16.5	1.246	60.721	60.721	60.721	-0.000	60.721
1013.2	15.0	1.294	75.473	75.473	75.473	-0.000	75.473
1013.2	15.1	1.339	92.814	92.814	92.814	-0.000	92.814
1013.2	14.1	1.386	110.373	110.373	110.373	-0.000	110.373
1009.2	13.4	1.429	127.102	127.102	127.102	-0.000	127.102

TARE DIFF. PRESS = -1.64000E-04 + -1.26930E-02 (ACFM) + 2.48070E-01 (ACFM)**2 + 0 (ACFM)**3

TABLE 44
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE.
DATA ACQUIRED IN THE REVERSE FLOW DIRECTION (S/N SIDE DOWN
STREAM) AFTER COMPLETION OF THE FORWARD FLOW TESTS AND AFTER THE
ADDITION OF 5.3 MG OF SYNTHETIC CONTAMINANT AND 10 HIGH PRESSURE
(10,000 PSIA NOMINAL) GN₂ IMPACT CYCLES. TEST SPECIMEN
INLET PRESSURE = 1000 PSIA (NOMINAL).

TEST NUMBER 12

PART 280R

TEST DESCRIPTION(S/N 028) INLET PRESSURE = 1000 PSIA (NOMINAL).

TEST SPECIMEN INLET CONDITIONS										NET DIFFERENTIAL PRESS	
PRESSURE		TEMPERATURE			FLOW RATE					DIFFERENTIAL	
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	CFM	SCFM	GN ₂ KG/HR	GN ₂ LBS/HR	KG/SQ CM	PSID
71.514	1017.2	298.7	25.0	78.4	82.2	0.423	2.902	5.713	12.599	8.8474	125.840
71.514	1017.2	298.2	25.1	77.2	74.3	0.394	2.624	5.166	11.390	7.6712	109.110
71.514	1017.2	297.9	24.8	76.5	65.6	0.339	2.316	4.560	10.052	6.5127	92.633
71.514	1017.2	297.8	24.8	76.3	56.9	0.294	2.009	3.951	8.723	5.4008	76.818
71.514	1017.2	297.8	24.8	76.3	47.7	0.244	1.684	3.316	7.310	4.3034	61.209
71.514	1017.2	297.9	24.7	76.4	38.4	0.198	1.356	2.671	5.888	3.2782	46.627
71.514	1017.2	296.8	24.8	76.7	29.1	0.151	1.029	2.020	4.467	2.3335	33.190
71.235	1013.2	298.2	25.0	77.0	24.7	0.120	0.871	1.715	3.781	1.9012	27.042
71.514	1017.2	298.3	25.2	77.3	19.8	0.103	0.730	1.379	3.040	1.4572	20.727
71.514	1017.2	298.6	25.4	77.8	13.1	0.081	0.463	0.912	2.011	0.8821	12.546
71.514	1017.2	299.0	25.5	78.3	12.9	0.087	0.456	0.899	1.982	0.8740	12.431
71.514	1017.2	298.9	25.8	78.4	2.3	0.105	0.716	1.410	3.108	1.4937	21.245
71.514	1017.2	298.8	25.7	78.2	24.4	0.127	0.862	1.698	3.744	1.8850	26.811
71.514	1017.2	298.7	25.5	77.9	29.3	0.152	1.034	2.039	4.489	2.3599	33.566
71.235	1013.2	298.3	25.1	77.3	38.4	0.199	1.355	2.668	5.883	3.2954	46.871
71.235	1013.2	297.9	24.7	76.5	47.4	0.241	1.673	3.294	7.261	4.2835	60.226
71.235	1013.2	297.5	24.3	75.8	50.0	0.291	1.979	3.891	8.591	5.3236	75.720
71.235	1013.2	297.0	23.4	75.0	62.6	0.339	2.317	4.563	10.059	6.5437	93.073
71.235	1013.2	296.5	23.4	74.1	74.1	0.381	2.638	5.194	11.451	7.7600	110.373
70.956	1009.2	296.2	23.1	73.4	82.5	0.420	2.925	5.759	12.697	8.9362	127.103
****	****	****	****	****							
71.403	1015.2	298.0	24.9	76.7							
0.145	2.1	0.6	0.6	1.0	DEVIATIONS						

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 45
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE.
DATA ACQUIRED IN THE REVERSE FLOW DIRECTION (S/N SIDE DOWN
STREAM) AFTER COMPLETION OF THE FORWARD FLOW TESTS AND AFTER THE
ADDITION OF 5.3 MG OF SYNTHETIC CONTAMINANT AND 10 HIGH PRESSURE
(10,000 PSIA NOMINAL) GN₂ IMPACT CYCLES. TEST SPECIMEN
(S/N 028) INLET PRESSURE = 415 PSIA (NOMINAL).

TEST NUMBER 12 PART 2BPK

TEST DESCRIPTION (S/N 028) INLET PRESSURE = 415 PSIA (NOMINAL).

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)
.58	50.2	78.9
.50	49.9	78.9
.40	50.4	78.9
.31	50.2	79.1
.26	50.4	79.0
.21	49.9	79.0
.14	50.1	79.2
.14	50.2	79.3
.21	50.1	79.2
.26	49.7	78.8
.31	50.1	79.2
.41	50.1	78.4
.50	49.9	78.3
.57	50.1	78.4

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)
.60	49.1	80.2
.50	49.1	80.2
.40	49.7	80.2
.30	49.9	80.3
.25	50.1	80.4
.21	49.5	80.4
.13	49.9	80.5
.13	50.1	80.5
.21	49.7	80.5
.26	49.3	80.4
.31	49.5	80.3
.41	49.3	80.1
.50	48.9	80.0
.58	48.9	79.8

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
415.5	79.6	.0709
415.5	79.6	.0596
414.8	79.6	.0484
414.8	79.7	.0368
414.8	79.7	.0312
414.2	79.7	.0253
414.2	79.9	.0164
414.2	79.9	.0164
414.2	79.8	.0253
413.5	79.6	.0311
413.5	79.5	.0370
412.9	79.3	.0489
412.2	79.1	.0599
411.6	79.1	.0690

TABLE 45
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE.
DATA ACQUIRED IN THE REVERSE FLOW DIRECTION (S/N SIDE DOWN
STREAM) AFTER COMPLETION OF THE FORWARD FLOW TESTS AND AFTER THE
ADDITION OF 5.3 MG OF SYNTHETIC CONTAMINANT AND 10 HIGH PRESSURE
(10,000 PSIA NOMINAL) GN₂ IMPACT CYCLES. TEST SPECIMEN
(S/N 028) INLET PRESSURE = 415 PSIA (NOMINAL).

TEST NUMBER 12 PART 24PR

TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

TEST SPECIMEN INLET CONDITIONS	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	AVG GROSS DIFF. PRESS PRIMARY (PSID)	AVG GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
415.5	19.6	.0719	288.716	288.716	288.716	.001	288.715
415.5	19.6	.0596	196.540	196.546	196.546	.000	196.545
414.8	19.5	.0484	137.519	137.519	137.519	.000	137.519
414.8	19.7	.0368	93.057	93.012	93.034	.000	93.034
414.8	19.7	.0312	73.814	73.757	73.785	.000	73.785
414.2	19.7	.0253	55.417	55.765	55.586	.000	55.585
414.2	19.9	.0184	32.543	32.775	32.659	-0.000	32.659
414.2	19.9	.0184	32.775	32.493	32.633	-0.000	32.632
414.2	19.8	.0253	56.414	56.712	56.561	.000	56.560
413.2	19.6	.0311	73.314	73.442	73.378	.000	73.377
413.2	19.5	.0370	94.275	94.275	94.275	.000	94.274
412.2	19.3	.0489	140.360	140.360	140.360	.000	140.359
412.2	19.1	.0599	199.702	199.702	199.702	.000	199.702
411.2	19.1	.0690	271.355	271.355	271.355	.001	271.354

$$\text{TARE DIFF. PRESS} = -3.40000E-05 + -4.44000E-04 (\text{ACFM}) + 1.50933E-01 (\text{ACFM})^{**2} + 0 (\text{ACFM})^{**3}$$

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 45
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE.
DATA ACQUIRED IN THE REVERSE FLOW DIRECTION (S/N SIDE DOWN
STREAM) AFTER COMPLETION OF THE FORWARD FLOW TESTS AND AFTER THE
ADDITION OF 5.3 MG OF SYNTHETIC CONTAMINANT AND 10 HIGH PRESSURE
(10,000 PSIA NOMINAL) GN₂ IMPACT CYCLES. TEST SPECIMEN
(S/N 028) INLET PRESSURE = 415 PSIA (NOMINAL).

TEST NUMBER 12 PART 28PA

TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS											NET DIFFERENTIAL PRESS	
*****											*****	
PRESSURE		TEMPERATURE			FLOW RATE						NET DIFFERENTIAL PRESS	
*****											*****	
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN ₂ KG/HR	GN ₂ LBS/HR	KG/SQ CM DIFFERENTIAL	PSID	
29.210	415.5	299.5	26.4	79.6	55.7	.0749	1.967	3.873	8.539	20.2987	288.715	
29.210	415.5	299.6	26.4	79.6	46.8	.0590	1.654	3.257	7.182	13.8185	196.545	
29.165	414.8	299.6	26.4	79.6	34.0	.0444	1.342	2.642	5.824	9.6685	137.518	
29.165	414.8	299.6	26.5	79.7	28.9	.0368	1.021	2.011	4.433	6.5409	93.034	
29.165	414.8	299.7	26.5	79.7	24.5	.0312	.866	1.705	3.759	5.1876	73.785	
29.119	414.2	299.7	26.5	79.7	19.3	.0253	.699	1.376	3.033	3.9080	55.585	
29.119	414.2	299.8	26.6	79.9	12.9	.0164	.455	.895	1.974	2.2961	32.659	
29.119	414.2	299.8	26.7	79.9	12.4	.0164	.454	.893	1.969	2.3083	32.832	
29.119	414.2	299.7	26.6	79.8	19.9	.0253	.701	1.381	3.044	3.9766	56.560	
29.073	413.5	299.6	26.5	79.6	24.3	.0311	.859	1.690	3.727	5.1589	73.377	
29.073	413.5	299.5	26.4	79.5	23.9	.0370	1.021	2.011	4.433	6.6281	94.274	
29.028	412.9	299.4	26.3	79.3	38.2	.0489	1.349	2.657	5.857	9.8682	140.359	
28.982	412.2	299.3	26.2	79.1	46.8	.0599	1.652	3.254	7.173	14.0404	199.702	
28.937	411.6	299.3	26.2	79.1	53.8	.0690	1.898	3.738	8.240	19.0781	271.354	
*****	*****	*****	*****	*****								
29.106	414.2	299.6	26.4	79.6								
.062	.2	.1	.1	.2	DEVIATIONS							

TABLE 46
 FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE. DATA ACQUIRED IN THE REVERSE FLOW DIRECTION (S/N SIDE DOWN STREAM) AFTER COMPLETION OF THE FORWARD FLOW TESTS AND AFTER THE ADDITION OF 11.1 MG OF SYNTHETIC CONTAMINANT AND 20 HIGH PRESSURE (10,000 PSIA NOMINAL) GN₂ IMPACT CYCLES. TEST SPECIMEN (S/N 028) INLET PRESSURE = 1000 PSIA (NOMINAL).

TFST NUMBER 12 PART 28RR TEST DESCRIPTION

FLOWMETER CONDITIONS						TEST SPECIMEN INLET CONDITIONS		
FLOWMETER ONE			FLOWMETER TWO			PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)			
.87	49.9	72.6	.91	47.6	76.7	1013.2	74.6	.0427
.78	50.1	71.4	.81	48.1	75.9	1013.2	73.6	.0385
.69	50.4	71.5	.70	48.9	75.1	1009.2	72.8	.0343
.60	50.2	71.1	.60	49.1	74.8	1009.2	72.5	.0295
.50	50.1	71.1	.50	49.1	74.7	1009.2	72.4	.0246
.41	50.1	71.3	.40	49.3	74.7	1009.2	72.5	.0201
.31	51.0	70.9	.30	50.4	75.1	1009.2	73.0	.0154
.26	49.7	71.3	.25	49.3	75.2	1009.2	73.3	.0127
.21	49.9	71.7	.20	49.7	75.5	1009.2	73.6	.0103
.14	49.9	72.4	.13	49.7	75.8	1009.2	74.1	.0068
.14	49.5	73.7	.13	49.3	76.4	1009.2	75.1	.0068
.22	50.4	73.5	.21	50.2	76.4	1009.2	75.0	.0107
.26	49.9	73.3	.25	49.5	76.4	1009.2	74.9	.0127
.31	50.1	73.0	.30	49.7	75.4	1009.2	74.7	.0152
.41	50.2	72.3	.40	49.5	76.1	1005.3	74.2	.0200
.50	50.1	71.5	.50	49.1	75.7	1005.3	73.6	.0247
.59	49.9	71.0	.60	48.7	75.1	1005.3	72.9	.0293
.69	50.1	69.9	.70	48.7	74.6	1005.3	72.3	.0341
.78	49.9	69.2	.81	48.1	74.0	1005.3	71.6	.0386
.87	50.1	68.6	.91	47.9	73.2	1001.3	70.9	.0435

TABLE 46
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE.
DATA ACQUIRED IN THE REVERSE FLOW DIRECTION (S/N SIDE DOWN
STREAM) AFTER COMPLETION OF THE FORWARD FLOW TESTS AND AFTER THE
ADDITION OF 11.1 MG OF SYNTHETIC CONTAMINANT AND 20 HIGH PRESSURE
(10,000 PSIA NOMINAL) GN₂ IMPACT CYCLES. TEST SPECIMEN
(S/N 028) INLET PRESSURE = 1000 PSIA (NOMINAL).

TEST NUMBER 12

PART 2ARR

TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (SCFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GR SS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
1013.2	74.6	.427	226.007	226.007	226.007	-0.000	226.007
1013.2	73.6	.385	190.969	190.969	190.969	-0.000	190.969
1009.2	72.8	.343	158.773	158.773	158.773	-0.000	158.773
1009.2	72.5	.275	125.629	125.629	125.629	-0.000	125.630
1009.2	72.4	.246	95.642	95.642	95.642	-0.000	95.643
1009.2	72.5	.201	70.771	70.771	70.771	-0.000	70.771
1009.2	73.0	.154	48.479	48.479	48.479	-0.000	48.479
1009.2	73.3	.127	36.877	36.877	36.877	-0.000	36.877
1009.2	73.6	.093	27.827	27.827	27.827	-0.000	27.827
1009.2	74.1	.070	15.934	15.934	15.934	-0.000	15.934
1009.2	75.1	.056	15.818	15.818	15.818	-0.000	15.818
1009.2	75.0	.077	29.045	29.045	29.045	-0.000	29.045
1009.2	74.9	.072	36.761	36.761	36.761	-0.000	36.761
1009.2	74.7	.102	47.783	47.783	47.783	-0.000	47.783
1005.2	74.2	.020	70.020	70.020	70.020	-0.000	70.020
1005.2	73.6	.127	96.274	96.274	96.274	-0.000	96.274
1005.2	72.9	.123	125.314	125.314	125.314	-0.000	125.314
1005.2	72.3	.034	158.141	158.141	158.141	-0.000	158.141
1005.2	71.6	.038	193.494	193.494	193.494	-0.000	193.494
1001.2	70.9	.043	233.898	233.898	233.898	-0.000	233.898

TARE DIFF. PRESS = -1.64000E-04 + -1.26930E-02 (ACFM) + 2.48070E-01 (ACFM)**2 +

0 (ACFM)**3

TABLE 46
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE.
DATA ACQUIRED IN THE REVERSE FLOW DIRECTION (S/N SIDE DOWN
STREAM) AFTER COMPLETION OF THE FORWARD FLOW TESTS AND AFTER THE
ADDITION OF 11.1 MG OF SYNTHETIC CONTAMINANT AND 20 HIGH PRESSURE
(10,000 PSIA NOMINAL) GN₂ IMPACT CYCLES. TEST SPECIMEN
(S/N 028) INLET PRESSURE = 1000 PSIA (NOMINAL).

TPST NUMBER 12 PART 28RR TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS										NET DIFFERENTIAL PRESS.	
PRESSURE		TEMPERATURE			FLOW RATE						
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID
71.235	1013.2	296.8	23.7	74.6	82.6	.0427	2.915	5.740	12.656	15.8899	226.007
71.235	1013.2	296.3	23.1	73.6	74.6	.0385	2.633	5.184	11.429	13.4265	190.269
70.956	1009.2	295.8	22.7	72.8	66.4	.0343	2.346	4.612	10.184	11.1629	158.773
70.956	1009.2	295.6	22.5	72.5	57.1	.0295	2.017	3.972	8.756	8.8326	125.230
70.956	1009.2	295.6	22.4	72.4	47.7	.0246	1.683	3.315	7.307	6.7243	95.643
70.956	1009.2	295.7	22.5	72.5	39.0	.0201	1.376	2.702	5.971	4.9845	70.296
70.956	1009.2	295.9	22.8	73.0	29.8	.0154	1.051	2.070	4.563	3.4020	48.387
70.956	1009.2	296.1	22.9	73.3	24.5	.0127	.864	1.700	3.749	2.5965	36.231
70.956	1009.2	296.3	23.1	73.6	20.0	.0103	.705	1.382	3.062	1.9586	27.858
70.956	1009.2	296.6	23.4	74.1	13.1	.0068	.464	.913	2.013	1.1230	15.273
70.956	1009.2	297.1	23.9	75.1	13.1	.0068	.462	.910	2.006	1.1169	15.886
70.956	1009.2	297.0	23.9	75.0	20.6	.0107	.726	1.430	3.152	2.0479	29.128
70.956	1009.2	297.0	23.8	74.9	24.4	.0127	.861	1.699	3.739	2.5924	36.873
70.956	1009.2	296.9	23.7	74.7	29.2	.0152	1.033	2.034	4.484	3.3664	47.881
70.677	1005.3	296.6	23.4	74.2	38.4	.0200	1.357	2.671	5.889	4.9359	70.205
70.677	1005.3	296.3	23.1	73.6	47.5	.0247	1.677	3.302	7.279	6.7687	96.274
70.677	1005.3	295.9	22.7	72.9	56.4	.0293	1.992	3.922	8.647	8.8104	125.314
70.677	1005.3	295.5	22.4	72.3	65.8	.0341	2.323	4.575	10.086	11.1185	158.142
70.677	1005.3	295.2	22.0	71.6	74.5	.0386	2.632	5.183	11.427	13.6040	193.395
70.398	1001.3	294.8	21.6	70.9	83.7	.0435	2.956	5.820	12.832	16.4447	233.898
****	****	****	****	****							
70.886	1008.2	296.1	23.0	73.4							
.154	2.2	.5	.5	1.0	DEVIATIONS						

ORIGINAL PAGE IS
OF POOR QUALITY

PAGE: 1
DATE: 9-20-76

TABLE 47
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION = FLOW RATE VERSUS DIFFERENTIAL PRESSURE.
DATA ACQUIRED IN THE REVERSE SLOW DIRECTION (S/N SIDE DOWN
STREAM) AFTER COMPLETION OF THE FORWARD FLOW TESTS AND AFTER THE
ADDITION OF 11.1 MG OF SYNTHETIC CONTAMINANT AND 20 HIGH PRESSURE
(10,000 PSIA NOMINAL) GN_2 IMPACT CYCLES. TEST SPECIMEN
(S/N 028) INLET PRESSURE = 415 PSIA(NOMINAL).

TEST NUMBER 12 PART 28SR TEST DESCRIPTION

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)
.41	50.6	75.0
.36	50.4	78.1
.31	50.6	73.1
.26	50.4	75.2
.21	50.1	71.3
.14	50.1	74.6
.14	50.1	74.9
.21	49.9	74.9
.26	50.1	74.9
.31	50.1	74.8
.35	50.1	74.8
.41	50.1	78.7

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)
.40	50.1	78.9
.36	50.1	79.0
.30	50.1	79.1
.26	50.1	79.2
.20	49.9	79.4
.13	50.1	79.6
.13	50.1	79.9
.21	49.5	80.0
.25	49.7	80.0
.31	49.7	80.0
.35	49.5	80.0
.41	49.3	79.8

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
419.5	78.5	.0487
418.8	78.5	.0427
418.8	78.6	.0368
418.8	78.7	.0313
418.8	78.9	.0247
418.8	79.1	.0165
418.8	79.4	.0164
418.2	79.5	.0248
418.2	79.5	.0304
417.5	79.4	.0367
417.5	79.4	.0418
416.9	79.2	.0483

TABLE 47
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE.
DATA ACQUIRED IN THE REVERSE SLOW DIRECTION (S/N SIDE DOWN
STREAM) AFTER COMPLETION OF THE FORWARD FLOW TESTS AND AFTER THE
ADDITION OF 11.1 MG OF SYNTHETIC CONTAMINANT AND 20 HIGH PRESSURE
(10,000 PSIA NOMINAL) GN2 IMPACT CYCLES. TEST SPECIMEN
(S/N 028) INLET PRESSURE = 415 PSIA (NOMINAL).

TEST NUMBER 12

PART NUMBER

TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
419.5	78.5	.487	249.575	249.575	249.575	.000	249.575
418.8	78.5	.427	188.023	188.023	188.023	.000	188.023
418.8	78.6	.368	142.254	142.254	142.254	.000	142.253
418.8	78.7	.313	107.532	107.532	107.532	.000	107.532
418.8	78.9	.247	74.565	74.744	74.634	.000	74.634
418.8	79.1	.165	41.987	42.254	42.121	0.000	42.120
418.9	79.4	.154	41.755	42.051	41.918	0.000	41.918
418.2	79.5	.248	75.315	75.051	75.483	.000	75.483
418.2	79.5	.304	103.744	103.744	103.744	.000	103.744
417.5	79.4	.367	141.307	141.307	141.307	.000	141.306
417.5	79.4	.418	180.447	180.447	180.447	.000	180.447
416.9	79.2	.483	245.472	245.472	245.472	.000	245.471

$$\text{TARE DIFF. PRESS} = -3.41000E-05 + -4.44000E-04 (\text{ACFM}) + 1.50933E-01 (\text{ACFM})^{**2} + 0 (\text{ACFM})^{**3}$$

TABLE 47
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE
DATA ACQUIRED IN THE REVERSE SLOW DIRECTION (S/N SIDE DOWN
STREAM) AFTER COMPLETION OF THE FORWARD FLOW TESTS AND AFTER THE
ADDITION OF 11.1 MG OF SYNTHETIC CONTAMINANT AND 20 HIGH PRESSURE
(10,000 PSIA NOMINAL) GN₂ IMPACT CYCLES. TEST SPECIMEN
TEST DESCRIPTION(S/N 028) INLET PRESSURE = 415 PSIA (NOMINAL).

TEST NUMBER 12 PART 28SK

TEST DESCRIPTION(S/N 028) INLET PRESSURE = 415 PSIA (NOMINAL).

TEST SPECIMEN INLET CONDITIONS										NET DIFFERENTIAL PRESS.	
PRESSURE		TEMPERATURE			FLOW RATE					NET DIFFERENTIAL PRESS.	
KG/SQ CM	PSIA	DEG. C	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN ₂ G/HR	GN ₂ LBS/HR	KG/SQ CM DIFFERENTIAL	PSID
29.493	419.5	299.	25.4	78.5	38.7	.437	1.367	2.692	5.935	17.5469	249.575
29.447	418.0	299.0	25.9	78.5	33.9	.427	1.199	2.360	5.204	13.2193	188.023
29.447	418.0	299.1	25.9	78.6	29.2	.368	1.032	2.032	4.481	10.0014	142.253
29.447	416.0	299.1	26.	78.7	24.8	.313	.877	1.729	3.805	7.5602	107.932
29.447	418.8	299.2	26.	78.9	19.6	.247	.693	1.364	3.007	5.2473	74.634
29.447	418.0	299.3	26.2	79.1	13.1	.165	.462	.910	2.006	2.9614	42.120
29.447	418.0	299.5	26.3	79.4	13.0	.164	.459	.904	1.992	2.9471	41.918
29.402	418.2	299.5	26.4	79.5	19.6	.248	.694	1.368	3.012	5.3070	75.483
29.402	418.2	299.5	26.4	79.5	24.0	.304	.849	1.672	3.685	7.2939	103.744
29.356	417.5	299.5	26.3	79.4	29.0	.367	1.024	2.019	4.445	9.9348	141.306
29.356	417.5	299.5	26.3	79.4	33.0	.418	1.166	2.295	5.061	12.6867	186.447
29.311	416.9	299.4	26.2	79.2	38.1	.483	1.347	2.652	5.848	17.2584	245.471
****	****	****	****	****							
29.417	410.4	299.3	26.1	79.1							
.043	.0	.2	.2	.3	DEVIATIONS						

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 48
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 5 PART 25DR TEST DESCRIPTION

CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE. FLOW IN REVERSE DIRECTION. TEST SPECIMEN (S/N 025) INLET PRESSURE = 415 PSIA NOMINAL.

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE			FLOWMETER TWO			PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)			
.54	50.6	84.4	.55	49.9	85.3	415.6	84.8	.0656
.50	50.2	84.3	.50	49.5	85.3	414.9	84.8	.0601
.41	49.7	84.2	.41	49.1	85.3	414.9	84.7	.0485
.31	49.9	84.1	.31	49.5	85.2	414.3	84.7	.0370
.26	50.6	84.1	.26	50.2	85.2	414.3	84.6	.0314
.21	50.2	84.1	.21	50.0	85.2	414.3	84.7	.0252
.13	50.2	84.3	.13	50.0	85.4	414.9	84.8	.0157
.10	50.2	84.5	.09	50.0	85.5	414.9	85.0	.0114
.10	50.1	84.5	.09	49.9	85.4	415.6	84.9	.0114
.13	50.4	84.5	.13	50.2	85.5	415.6	85.0	.0159
.21	50.1	84.4	.21	49.9	85.5	415.6	84.9	.0251
.26	49.9	84.2	.26	49.5	85.5	414.9	84.8	.0310
.31	49.9	84.1	.31	49.5	85.4	414.3	84.7	.0371
.40	50.1	83.9	.40	49.5	85.2	414.3	84.5	.0483
.49	49.7	83.6	.50	48.9	85.1	413.7	84.3	.0593
.54	49.7	83.8	.55	48.7	85.1	413.0	84.4	.0647

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 48
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 5	PART 750R	TEST DESCRIPTION	CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE. FLOW IN REVERSE DIRECTION. TEST SPECIMEN (S/N 025) INLET PRESSURE = 415 PSIA NOMINAL.				
TEST SPECIMEN INLET CONDITIONS							

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
415.0	84.8	.0656	307.299	307.299	307.299	.001	307.299
414.9	84.8	.0601	245.671	245.671	245.671	.000	245.670
414.9	84.7	.0465	169.821	169.821	169.821	.000	169.820
414.9	84.7	.0370	115.777	115.777	115.777	.000	115.777
414.9	84.6	.0314	92.153	93.022	92.603	.000	92.602
414.9	84.7	.0252	69.452	70.267	69.860	.000	69.859
414.9	84.8	.0157	40.520	40.837	40.678	-0.000	40.678
414.9	85.0	.0114	28.642	28.753	28.697	-0.000	28.697
415.0	84.9	.0114	28.526	28.695	28.611	-0.000	28.610
415.0	85.0	.0159	40.925	41.183	41.054	-0.000	41.053
415.0	84.9	.0251	70.202	70.899	70.550	.000	70.550
414.9	84.8	.0310	91.211	92.074	91.643	.000	91.642
414.9	84.7	.0371	117.041	117.041	117.041	.000	117.041
414.9	84.5	.04-3	170.769	170.769	170.769	.000	170.768
413.9	84.3	.0593	242.827	242.827	242.827	.000	242.826
413.9	84.4	.0647	300.346	300.346	300.346	.001	300.346

TARE DIFF. PRESS = -3.40000E-05 + -4.44000E-04 (ACFM) + 1.50933E-01 (ACFM)**2 +

0 (ACFM)**3

TABLE 48
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 5		PART 25DR			TEST DESCRIPTION		CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE. FLOW IN REVERSE DIRECTION. TEST SPECIMEN (S/N 025) INLET PRESSURE = 415 PSIA NOMINAL.					NET DIFFERENTIAL PRESS	
TEST SPECIMEN INLET CONDITIONS												*****	
PRESSURE		TEMPERATURE			FLOW RATE							*****	
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID	*****	
29.219	415.0	302.5	29.4	84.8	51.0	.0656	1.803	3.550	7.826	21.6053	307.299		
29.174	414.7	302.5	29.3	84.8	46.7	.0601	1.650	3.249	7.163	17.2723	245.670		
29.174	414.7	302.5	29.3	84.7	37.7	.0485	1.333	2.624	5.786	11.9395	169.820		
29.128	414.7	302.4	29.3	84.7	28.7	.0370	1.015	1.998	4.404	8.1399	115.777		
29.128	414.3	302.4	29.2	84.6	24.4	.0314	.861	1.699	3.737	6.5106	92.602		
29.128	414.3	302.4	29.3	84.7	19.5	.0252	.690	1.359	2.996	4.9116	69.859		
29.174	414.7	302.5	29.4	84.8	12.2	.0157	.432	.850	1.875	2.8599	40.678		
29.174	414.7	302.6	29.4	85.0	8.9	.0114	.314	.618	1.364	2.0176	28.697		
29.219	415.0	302.6	29.4	84.9	8.9	.0114	.313	.616	1.358	2.0115	28.610		
29.219	415.0	302.6	29.4	85.0	12.4	.0159	.436	.859	1.894	2.8863	41.053		
29.219	415.0	302.6	29.4	84.9	19.5	.0251	.690	1.358	2.995	4.9601	70.550		
29.174	414.7	302.5	29.4	84.8	24.1	.0310	.850	1.674	3.691	6.4431	91.642		
29.128	414.3	302.5	29.3	84.7	28.8	.0371	1.017	2.003	4.416	8.2288	117.041		
29.128	414.3	302.3	29.2	84.5	37.5	.0483	1.324	2.607	5.747	12.0062	170.768		
29.083	413.7	302.2	29.1	84.3	46.0	.0593	1.624	3.198	7.051	17.0724	242.826		
29.037	413.7	302.3	29.1	84.4	50.1	.0647	1.769	3.484	7.681	21.1164	300.346		
*****	*****	*****	*****	*****									
29.157	414.7	302.5	29.3	84.7									
.042	.0	.1	.1	.2	DEVIATIONS								

TABLE 49
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 5 PART 25ER TEST DESCRIPTION

CLEAN CONDITION - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. FLOW IN REVERSE
DIRECTION. TEST SPECIMEN (S/N 025) INLET
PRESSURE = 1000 PSIA NOMINAL.

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.84	49.7	66.3	.90	47.8	71.5	1000.0	68.9	.0423
.76	50.2	65.8	.81	48.5	71.1	1004.0	68.4	.0387
.67	50.2	65.5	.71	48.7	70.5	1000.0	68.0	.0340
.59	49.9	65.6	.61	48.7	70.5	1000.0	68.1	.0294
.49	50.1	65.8	.51	49.3	70.6	1000.0	68.2	.0248
.40	50.2	66.3	.41	49.7	70.9	1000.0	68.6	.0203
.30	50.1	67.0	.30	49.9	71.3	1000.0	69.1	.0152
.26	50.1	67.5	.26	49.9	71.5	1000.0	69.5	.0128
.21	49.7	68.2	.21	49.5	71.8	1000.0	69.9	.0103
.13	49.7	69.2	.13	49.7	72.5	1000.0	70.9	.0065
.13	50.1	70.3	.13	49.9	73.2	1000.0	71.7	.0065
.22	49.9	70.3	.22	49.5	73.2	1000.0	71.7	.0108
.27	49.9	70.0	.27	49.7	73.1	1000.0	71.6	.0134
.31	49.9	69.9	.31	49.5	73.2	1000.0	71.5	.0155
.40	50.1	69.3	.41	49.5	72.9	1000.0	71.1	.0203
.49	49.7	68.8	.51	48.9	72.6	1000.0	70.7	.0247
.58	50.6	68.0	.61	49.5	72.2	1000.0	70.1	.0298
.67	50.1	67.4	.71	48.7	71.8	1000.0	69.6	.0342
.76	50.1	66.8	.81	48.3	71.2	1000.0	69.0	.0386
.85	50.2	66.0	.91	48.3	70.5	1000.0	68.3	.0434

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 49
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST SPECIMEN INLET CONDITIONS		TEST NUMBER 5	PART 25ER	TEST DESCRIPTION			CLEAN CONDITION--FLOW RATE VERSUS DIFFERENTIAL PRESSURE. FLOW IN REVERSE DIRECTION. TEST SPECIMEN (S/N-025) INLET PRESSURE = 1000 PSIA NOMINAL.	
PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)	
1000.0	68.9	.0423	140.007	140.007	140.007	-0.000	140.007	
1004.0	68.4	.0387	125.469	125.469	125.469	-0.000	125.469	
1000.0	68.0	.0340	107.455	107.455	107.455	-0.000	107.455	
1000.0	68.1	.0294	88.734	89.756	89.245	-0.000	89.245	
1000.0	68.2	.0248	72.031	72.690	72.360	-0.000	72.361	
1000.0	68.6	.0203	56.638	57.520	57.079	-0.000	57.079	
1000.0	69.1	.0152	41.138	41.356	41.247	-0.000	41.247	
1000.0	69.5	.0128	33.953	34.099	34.026	-0.000	34.026	
1000.0	69.9	.0113	26.421	26.457	26.439	-0.000	26.439	
1000.0	70.9	.0065	15.702	15.687	15.694	-0.000	15.694	
1000.0	71.7	.0065	15.818	15.915	15.867	-0.000	15.867	
1000.0	71.7	.0108	27.580	27.720	27.650	-0.000	27.650	
1000.0	71.6	.0134	35.575	35.768	35.672	-0.000	35.672	
1000.0	71.5	.0155	42.239	42.394	42.316	-0.000	42.317	
1000.0	71.1	.0203	56.764	57.520	57.142	-0.000	57.142	
1000.0	70.7	.0247	72.031	72.690	72.360	-0.000	72.361	
1000.0	70.1	.0298	90.078	91.020	90.549	-0.000	90.549	
1000.0	69.6	.0342	107.455	107.455	107.455	-0.000	107.455	
1000.0	69.0	.0386	124.837	124.837	124.837	-0.000	124.837	
1000.0	68.3	.0434	144.748	144.748	144.748	-0.000	144.748	

TARE DIFF. PRESS = -1.64000E-04 + -1.26930E-02 (ACFM) + 2.48070E-01 (ACFM)**2 +

0 (ACFM)**3

TABLE 49
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 5 PART 25ER TEST DESCRIPTION

CLEAN CONDITION --- FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. FLOW IN REVERSE
DIRECTION. TEST SPECIMEN (S/N 025) INLET
PRESSURE = 1000 PSIA NOMINAL.

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESS.

PRESSURE		TEMPERATURE			FLOW RATE						NET DIFFERENTIAL PRESS.		
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID		
70.307	1000.0	293.7	20.5	68.9	81.7	.7423	2.884	5.678	12.518	9.8435	140.007		
70.586	1004.0	293.4	20.2	68.4	75.0	.6387	2.649	5.216	11.499	8.8214	125.469		
70.307	1000.0	293.2	20.0	68.0	65.8	.6340	2.324	4.576	10.088	7.5548	107.455		
70.307	1000.0	293.2	20.0	68.1	56.9	.6294	2.008	3.954	8.717	6.2746	89.246		
70.307	1000.0	293.3	20.1	68.2	47.9	.6248	1.693	3.333	7.348	5.0875	72.361		
70.307	1000.0	293.5	20.3	68.6	39.2	.6203	1.384	2.724	6.006	4.0131	57.079		
70.307	1000.0	293.8	20.6	69.1	29.3	.6152	1.033	2.034	4.485	2.9000	41.247		
70.307	1000.0	294.0	20.8	69.5	24.8	.6128	.874	1.722	3.795	2.3923	34.026		
70.307	1000.0	294.2	21.1	69.9	19.9	.6103	.701	1.381	3.044	1.8589	26.439		
70.307	1000.0	294.7	21.6	70.9	12.4	.6065	.439	.865	1.906	1.1034	15.694		
70.307	1000.0	295.2	22.1	71.7	12.4	.6065	.438	.863	1.902	1.1155	15.867		
70.307	1000.0	295.2	22.1	71.7	20.7	.6108	.732	1.441	3.176	1.9440	27.650		
70.307	1000.0	295.1	22.0	71.6	25.7	.6134	.907	1.787	3.939	2.5080	35.672		
70.307	1000.0	295.1	22.0	71.5	29.8	.6155	1.051	2.070	4.563	2.9752	42.317		
70.307	1000.0	294.9	21.7	71.1	39.0	.6203	1.378	2.713	5.981	4.0175	57.142		
70.307	1000.0	294.7	21.5	70.7	47.5	.6247	1.678	3.303	7.282	5.0875	72.361		
70.307	1000.0	294.3	21.2	70.1	57.3	.6298	2.025	3.988	8.792	6.3663	90.549		
70.307	1000.0	294.0	20.9	69.6	66.0	.6342	2.330	4.589	10.116	7.5548	107.455		
70.307	1000.0	293.7	20.5	69.0	74.5	.6386	2.633	5.184	11.428	8.7769	124.837		
70.307	1000.0	293.3	20.1	68.3	84.0	.6434	2.965	5.838	12.870	10.1768	144.748		
70.321	1000.2	294.1	21.0	69.7									
.026	.4	.6	.6	1.2	DEVIATIONS								

C-5

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 50
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 5-25 PART 2SA1 TEST DESCRIPTION

CLEAN CONDITION - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. TEST SPECIMEN
(S/N-025) INLET PRESSURE = 1000 PSIA NOMINAL.
DATA OBTAINED AFTER REVERSE FLOW DATA RUN.

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE			FLOWMETER TWO			AVG		AVG
FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)
.86	49.7	69.8	.91	47.8	73.3	1000.0	71.6	.0432
.78	50.4	69.2	.81	48.7	72.4	1000.0	70.8	.0395
.69	49.9	69.2	.71	48.5	72.1	1000.0	70.6	.0344
.60	49.9	69.2	.61	48.7	71.5	1000.0	70.4	.0297
.51	50.1	69.2	.51	49.3	71.5	1000.0	70.4	.0250
.42	50.2	69.3	.41	49.9	72.3	1000.0	70.8	.0207
.32	50.1	69.8	.31	49.9	73.2	1000.0	71.5	.0155
.27	50.4	70.4	.26	50.2	74.3	1000.0	72.4	.0132
.22	50.2	71.0	.21	50.0	74.5	1000.0	72.7	.0106
.15	49.9	71.6	.14	49.7	75.2	1000.0	73.4	.0071
.15	49.9	73.2	.13	49.9	77.9	1000.0	75.6	.0070
.23	49.9	73.7	.22	49.7	77.9	1000.0	75.6	.0114
.26	50.2	73.1	.25	50.0	77.7	1000.0	75.4	.0129
.32	49.9	72.8	.31	49.5	77.4	1000.0	75.1	.0158
.42	49.9	72.2	.41	49.5	77.1	1000.0	74.6	.0206
.50	50.1	71.6	.50	49.3	75.7	1000.0	74.2	.0250
.60	50.4	70.9	.61	49.5	76.2	1000.0	73.6	.0301
.69	50.4	70.1	.71	49.3	75.5	1000.0	72.7	.0350
.78	50.6	69.4	.81	48.9	74.7	1000.0	72.0	.0396
.87	50.1	68.9	.91	48.1	74.0	1000.0	71.5	.0436

TABLE 50
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 5-25 PART 25A1

TEST DESCRIPTION

CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE. TEST SPECIMEN (S/N 025) INLET PRESSURE = 1000 PSIA NOMINAL. DATA OBTAINED AFTER REVERSE FLOW DATA RUN.

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	VG FLOW RATE (CFM)	AVG GROSS DIFF. PRESS. PRIMARY (PSID)	AVG GROSS DIFF. PRESS. SECONDARY (PSID)	AVG GROSS DIFF. PRESS. (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
1000.0	71.6	.1432	101.766	101.766	101.766	-0.000	101.766
1000.0	70.8	.0395	90.202	91.020	90.611	-0.000	90.611
1000.0	70.6	.0344	75.768	76.482	76.125	-0.000	76.126
1000.0	75.4	.0297	62.777	63.525	63.151	-0.000	63.151
1004.0	70.4	.0250	51.374	52.147	51.760	-0.000	51.761
1000.0	70.8	.0207	40.616	40.722	40.669	-0.000	40.669
1000.0	71.5	.0155	29.202	29.213	29.207	-0.000	29.208
1000.0	72.4	.0132	24.219	24.228	24.219	-0.000	24.220
1000.0	72.7	.0116	18.773	18.834	18.803	-0.000	18.803
1000.0	73.4	.0071	11.994	11.972	11.983	-0.000	11.983
1000.0	75.6	.0076	11.994	12.020	12.011	-0.000	12.011
1000.0	75.6	.0114	20.511	20.666	20.589	-0.000	20.589
1000.0	75.4	.0129	23.598	23.808	23.758	-0.000	23.758
1000.0	75.1	.0158	30.071	31.189	30.130	-0.000	30.130
1000.0	74.6	.0216	40.797	40.953	40.871	-0.000	40.872
1000.0	74.2	.0254	50.998	51.831	51.414	-0.000	51.415
1000.0	73.6	.0301	64.029	64.473	64.251	-0.000	64.251
1000.0	72.7	.0350	77.267	77.747	77.504	-0.000	77.504
1000.0	72.0	.0396	90.324	91.020	90.672	-0.000	90.672
1000.0	71.5	.0436	103.662	103.662	103.662	-0.000	103.662

TAKE DIFF. PRESS = $-1.64000E-04 + -1.26930E-02 (ACFM) + 2.48070E-01 (ACFM)**2 + 0 (ACFM)**3$

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 50
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 5-25 PART 25A1 TEST DESCRIPTION CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE. TEST SPECIMEN (S/N 025) INLET PRESSURE = 1000-PSIA-NOMINAL. DATA OBTAINED AFTER REVERSE FLOW DATA RUN.

TEST SPECIMEN INLET CONDITIONS NET DIFFERENTIAL PRESS

PRESSURE		TEMPERATURE			FLOW RATE						
KG/SQ CM	PSI	DEG. K	DEG. C	DEG. F	LITERS/ MIN	CFM	SCFM	GN2 KG/HR	GN2 LRS/HR	KG/SQ CM DIFFERENTIAL	PSID
70.307	1000.	295.1	22.	71.6	82.9	.432	2.929	5.767	12.714	7.1549	101.766
70.307	1000.	294.7	21.5	70.8	75.9	.395	2.681	5.280	11.639	6.3706	90.611
70.307	1000.	294.6	21.5	70.6	66.2	.344	2.336	4.600	10.141	5.3522	76.126
70.307	1000.	294.5	21.3	70.4	57.2	.297	2.019	3.976	8.765	4.4400	63.151
70.586	1000.	294.5	21.3	70.4	48.4	.250	1.708	3.364	7.416	3.6391	51.761
70.307	1000.	294.7	21.6	70.8	39.7	.207	1.403	2.763	6.092	2.8593	40.669
70.307	1000.	295.1	21.9	71.5	29.8	.155	1.054	2.076	4.576	2.0535	29.208
70.307	1000.	295.6	22.4	72.4	25.4	.132	.896	1.765	3.890	1.7028	24.220
70.307	1000.	295.8	22.6	72.7	20.3	.106	.717	1.412	3.112	1.3220	18.803
70.307	1000.	296.2	23.0	73.4	13.5	.071	.478	.942	2.076	.8425	11.983
70.307	1000.	297.4	24.2	75.6	13.4	.070	.474	.934	2.058	.8445	12.011
70.307	1000.	297.4	24.2	75.6	21.7	.114	.767	1.511	3.331	1.4475	20.589
70.307	1000.	297.3	24.1	75.4	24.7	.129	.871	1.714	3.779	1.6704	23.758
70.307	1000.	297.1	24.0	75.1	30.2	.158	1.066	2.100	4.630	2.1184	30.130
70.307	1000.	296.8	23.7	74.6	39.3	.206	1.388	2.734	6.027	2.8736	40.872
70.307	1000.	296.6	23.4	74.2	47.7	.250	1.685	3.317	7.314	3.6148	51.415
70.307	1000.	296.3	23.1	73.6	57.7	.300	2.037	4.111	8.842	4.5173	64.251
70.307	1000.	295.2	22.0	72.7	67.1	.350	2.370	4.667	10.289	5.4491	77.504
70.307	1000.	295.4	22.2	72.1	76.0	.396	2.682	5.282	11.644	6.3749	90.672
70.307	1000.	295.1	21.9	71.5	83.8	.436	2.958	5.824	12.841	7.2882	103.662
70.321	1000.2	295.3	22.6	72.7							
.026	.4	.9	.9	1.6	DEVIATIONS						

TABLE 51
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE.
DATA ACQUIRED WITH FLOW IN THE REVERSE (S/N SIDE DOWNSTREAM)
DIRECTION. TEST SPECIMEN (S/N 028) INLET PRESSURE =
415 PSIA (NOMINAL).

TEST NUMBER 12 PART 28BR TEST DESCRIPTION

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP. (DEG. F)	AVG. FLOW RATE (ACFM)
.60	24.1	77.0	.60	48.9	78.1	419.5	77.5	.0706
.50	20.4	77.0	.50	49.5	78.0	419.5	77.5	.0599
.41	42.5	77.1	.41	48.7	78.1	418.8	77.6	.0483
.31	24.2	77.3	.30	49.9	78.2	418.8	77.8	.0369
.26	22.4	77.3	.25	50.1	78.3	418.8	77.8	.0308
.21	49.9	77.5	.20	49.5	78.4	418.8	77.9	.0247
.14	42.7	77.7	.13	49.3	78.5	418.8	78.1	.0163
.14	42.5	78.1	.13	49.3	78.6	418.8	78.3	.0163
.22	21.1	78.1	.21	49.7	78.7	418.8	78.4	.0261
.26	21.2	78.1	.25	49.9	78.6	418.2	78.4	.0305
.32	21.4	78.3	.31	49.9	78.6	418.2	78.4	.0374
.41	20.2	78.3	.40	49.5	78.7	417.5	78.5	.0486
.50	24.6	78.3	.50	49.9	78.6	417.5	78.5	.0600
.60	20.6	78.4	.60	49.5	78.7	416.9	78.5	.0722

TABLE 51
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE.
DATA ACQUIRED WITH FLOW IN THE REVERSE (S/N SIDE DOWNSTREAM)
DIRECTION. TEST SPECIMEN (S/N 028) INLET PRESSURE =
415 PSIA (NOMINAL).

TEST NUMBER 12 PART 2888 TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
419.5	77.5	.0716	268.199	268.199	268.199	.001	268.198
419.5	77.5	.0599	200.334	200.334	200.334	.000	200.333
418.8	77.6	.483	144.779	144.779	144.779	.000	144.778
418.8	77.8	.0369	101.850	101.850	101.850	.000	101.850
418.8	77.8	.0318	80.972	81.964	81.468	.000	81.467
418.8	77.9	.247	62.532	63.341	62.936	.000	62.936
418.8	78.1	.0163	38.991	39.800	39.395	=0.000	39.394
418.8	78.3	.1163	38.865	39.627	39.246	=0.000	39.246
418.8	78.4	.261	66.715	67.444	67.080	.000	67.079
418.2	78.4	.0315	79.903	81.017	80.460	.000	80.460
418.2	78.4	.0374	104.060	104.060	104.060	.000	104.059
417.5	78.5	.486	145.726	145.726	145.726	.000	145.725
417.5	78.5	.0600	199.071	199.071	199.071	.000	199.070
416.9	78.5	.722	287.453	287.453	287.453	.001	287.453

TARE DIFF. PRESS = -3.40000E-05 + -4.44000E-04 (ACFM) + 1.50933E-01 (ACFM)**2 + 0 (ACFM)**3

TABLE 51
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE.
DATA ACQUIRED WITH FLOW IN THE REVERSE (S/N SIDE DOWNSTREAM)
DIRECTION. TEST SPECIMEN (S/N 028) INLET PRESSURE =
415 PSIA (NOMINAL).

TEST NUMBER 12 PART 2888 TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESSURE

PRESSURE		TEMPERATURE			FLOW RATE						NET DIFFERENTIAL PRESSURE	
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	CFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID	
29.493	419.0	298.5	25.3	77.5	56.2	.0706	1.985	3.909	8.618	18.8562	268.198	
29.493	419.0	298.4	25.3	77.5	47.8	.599	1.687	3.321	7.322	14.0848	200.333	
29.447	418.0	298.5	25.3	77.6	38.4	.483	1.357	2.671	5.889	10.1789	144.778	
29.447	418.0	298.6	25.4	77.8	29.3	.369	1.035	2.039	4.495	7.1607	101.850	
29.447	418.0	298.6	25.5	77.8	24.5	.308	.866	1.704	3.757	5.7277	81.467	
29.447	418.0	298.7	25.5	77.9	19.6	.247	.692	1.363	3.004	4.4248	62.936	
29.447	418.0	298.8	25.6	78.1	12.9	.163	.457	.900	1.985	2.7697	39.394	
29.447	418.0	298.9	25.7	78.3	12.9	.163	.456	.898	1.980	2.7592	39.245	
29.447	418.0	298.9	25.8	78.4	20.7	.1261	.731	1.439	3.173	4.7161	67.079	
29.402	418.0	298.9	25.8	78.4	24.1	.305	.853	1.679	3.702	5.6569	80.460	
29.402	418.0	298.9	25.8	78.4	29.7	.374	1.047	2.062	4.547	7.3161	104.959	
29.356	417.0	299.	25.8	78.5	38.5	.486	1.358	2.674	5.896	10.2655	145.725	
29.356	417.0	299.	25.8	78.5	47.5	.600	1.676	3.300	7.276	13.9960	199.070	
29.311	416.0	299.	25.8	78.5	57.1	.722	2.016	3.970	8.752	20.2099	287.453	
****	****	****	****	****								
29.425	418.0	298.8	25.6	78.1								
.042	.0	.2	.2	.3	DEVIATIONS							

ORIGINAL PAGE IS
OF POOR QUALITY

PAGE: 1
DATE: 9-15-76

TABLE 52
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE.
DATA ACQUIRED WITH FLOW IN THE REVERSE (S/N SIDE DOWNSTREAM)
DIRECTION. TEST SPECIMEN (S/N 028) INLET PRESSURE
1000 PSIA (NOMINAL).

TEST NUMBER 12 PART 28AR TEST DESCRIPTION

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.86	24.2	72.5	.91	48.2	77.3	1.07.9	74.7	.0430
.78	49.9	71.5	.81	48.0	76.3	1.07.9	73.6	.0385
.69	22.1	71.8	.71	48.6	75.9	1.07.9	73.3	.0341
.60	22.2	71.5	.51	49.1	75.7	1.04.0	73.2	.0297
.50	42.7	71.8	.51	48.8	75.7	1.04.0	73.3	.0246
.40	42.9	71.3	.41	49.2	75.8	1.07.9	73.4	.0197
.31	20.4	71.5	.30	49.9	76.0	1.04.0	73.8	.0152
.26	42.9	72.5	.25	49.5	76.2	1.04.0	74.1	.0127
.21	20.1	72.3	.21	49.7	76.4	1.04.0	74.5	.0103
.14	20.1	73.3	.13	49.7	76.8	1.04.0	75.0	.0069
.14	20.6	74.3	.13	51.3	77.1	1.04.0	75.6	.0069
.22	20.2	73.9	.21	49.9	77.0	1.04.0	75.5	.0107
.26	20.4	73.7	.25	49.9	77.1	1.04.0	75.3	.0127
.31	20.4	73.2	.31	49.9	76.8	1.04.0	75.0	.0155
.40	20.2	72.5	.41	49.7	76.5	1.04.0	74.6	.0199
.49	20.6	72.5	.49	49.3	76.2	1.04.0	74.1	.0245
.59	20.4	71.1	.51	49.2	75.7	1.00.0	73.4	.0296
.69	20.1	71.1	.71	48.8	75.1	1.00.0	72.7	.0343
.77	20.1	62.3	.81	48.4	74.4	1.00.0	71.9	.0388
.87	20.2	62.3	.91	48.2	73.4	1.00.0	70.9	.0437

TABLE 52
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE.
DATA ACQUIRED WITH FLOW IN THE REVERSE (S/N SIDE DOWNSTREAM)
DIRECTION. TEST SPECIMEN (S/N 028) INLET PRESSURE =
1000 PSIA (NOMINAL).

TEST NUMBER 12 PART 2BAR TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

AVG TEMP (DEG. F)	VG FLOW RATE (CFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)	
1007.2	14.7	.0420	120.684	120.684	120.684	0.000	120.684
1007.2	13.6	.385	106.164	106.164	106.164	0.000	106.164
1007.2	13.3	.341	91.544	91.544	91.544	0.000	91.544
1004.0	13.2	.297	77.679	77.679	77.679	0.000	77.679
1004.0	13.3	.246	62.615	62.615	62.615	0.000	62.615
1007.2	13.4	.197	48.949	48.949	48.949	0.000	48.949
1004.0	13.3	.152	36.943	36.943	36.943	0.000	36.943
1004.0	14.1	.127	30.191	30.191	30.191	0.000	30.191
1004.0	14.5	.013	24.567	24.567	24.567	0.000	24.567
1004.0	15.1	.009	15.870	15.870	15.870	0.000	15.870
1004.0	15.6	.009	16.165	16.165	16.165	0.000	16.165
1004.0	15.5	.017	25.321	25.321	25.321	0.000	25.321
1004.0	15.3	.127	30.191	30.191	30.191	0.000	30.191
1004.0	15.1	.135	37.447	37.447	37.447	0.000	37.447
1004.0	14.6	.159	49.573	49.573	49.573	0.000	49.573
1004.0	14.1	.245	62.615	62.615	62.615	0.000	62.615
1000.0	13.4	.296	77.119	77.119	77.119	0.000	77.119
1000.0	12.7	.343	91.713	91.713	91.713	0.000	91.713
1000.0	11.9	.388	106.795	106.795	106.795	0.000	106.795
1000.0	10.9	.437	123.209	123.209	123.209	0.000	123.209

INLET DIFF. PRESS = -1.64000E-04 + -1.26930E-02 (ACFM) + 2.48070E-01 (ACFM)**2 + 0 (ACFM)**3

TABLE 52
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE.
DATA ACQUIRED WITH FLOW IN THE REVERSE (S/N SIDE DOWNSTREAM).
DIRECTION. TEST SPECIMEN (S/N 028) INLET PRESSURE = 1000 PSIA (NOMINAL).

TEST NUMBER 12 PART 28AR TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESSURE

PRESSURE		TEMPERATURE			FLOW RATE						
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN2 KG/HR	GN2 LB5/HR	KG/SQ CM DIFFERENTIAL	PSIDI
70.865	1007.8	296.9	23.7	74.7	82.7	.0430	2.922	5.753	12.683	8.4850	120.584
70.865	1007.8	296.3	23.1	73.6	74.3	.0385	2.624	5.167	11.391	7.4641	106.364
70.865	1007.8	296.1	23.0	73.3	65.7	.0341	2.321	4.571	10.077	6.3824	90.179
70.586	1004.0	296.0	22.9	73.2	57.1	.0297	2.015	3.968	8.749	5.4359	77.317
70.586	1004.0	296.1	22.9	73.3	47.2	.0246	1.667	3.282	7.236	4.4241	62.825
70.865	1007.8	296.2	23.0	73.4	38.0	.0197	1.342	2.662	5.824	3.6777	49.864
70.586	1004.0	296.4	23.2	73.8	29.2	.0152	1.031	2.021	4.477	2.6230	37.307
70.586	1004.0	296.6	23.4	74.1	24.4	.0127	.862	1.698	3.742	2.1488	30.863
70.586	1004.0	296.8	23.5	74.5	19.8	.0103	.700	1.377	3.037	1.7291	24.594
70.586	1004.0	297.1	23.9	75.0	13.1	.0069	.464	.913	2.012	1.1176	15.896
70.586	1004.0	297.4	24.2	75.6	13.3	.0069	.468	.922	2.033	1.1398	16.212
70.586	1004.0	297.3	24.2	75.5	20.4	.0107	.721	1.420	3.130	1.7859	25.401
70.586	1004.0	297.2	24.1	75.3	24.3	.0127	.857	1.688	3.720	2.1468	30.595
70.586	1004.0	297.0	23.9	75.0	29.6	.0155	1.046	2.060	4.542	2.6608	37.845
70.586	1004.0	296.8	23.7	74.6	38.2	.0199	1.349	2.650	5.855	3.5107	49.234
70.586	1004.0	296.5	23.4	74.1	47.1	.0245	1.663	3.279	7.221	4.4352	63.088
70.307	1000.0	296.2	23.0	73.4	56.7	.0296	2.002	3.944	8.620	5.4666	77.353
70.307	1000.0	295.8	22.6	72.7	65.8	.0343	2.323	4.574	10.084	6.4549	91.410
70.307	1000.0	295.3	22.2	71.9	74.5	.0388	2.631	5.180	11.420	7.5085	106.796
70.307	1000.0	294.8	21.6	70.9	84.0	.0437	2.966	5.839	12.874	8.6625	123.210
****	****	****	****	****							
70.586	1004.0	296.4	23.3	73.9							
.112	1.0	.5	.5	.9	DEVIATIONS						

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 53

FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 1
DATE: 7/23/76

TEST NUMBER 6

PART 58

TEST DESCRIPTION

CLEAN CONDITION-FLOW RATE VERSUS
DIFFERENTIAL PRESSURE, BEFORE PROOF TEST,
TEST SPECIMEN (S/N 023) INLET PRESSURE = 415 PSIA (NOMINAL)

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)
.47	50.4	83.5
.45	49.7	83.6
.40	50.4	83.6
.36	50.8	83.6
.31	50.6	83.6
.26	50.2	83.6
.21	50.4	83.7
.16	50.6	83.8
.12	50.2	83.8
.12	50.4	83.8
.16	50.1	83.7
.21	50.1	83.6
.26	49.7	83.5
.31	50.1	83.3
.36	50.1	83.3
.40	49.9	83.3
.44	49.9	83.3
.48	49.9	83.3

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)
.42	49.9	83.5
.45	48.9	83.6
.40	49.9	83.6
.35	50.2	83.7
.31	50.2	83.7
.26	49.9	83.8
.21	50.2	83.7
.15	50.4	83.8
.11	50.1	83.8
.11	50.4	83.9
.16	49.9	83.9
.21	49.9	83.9
.26	49.3	83.8
.31	49.9	83.8
.35	49.5	83.7
.40	49.3	83.7
.44	49.5	83.6
.48	49.7	83.5

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
421.0	83.0	.0567
421.2	83.1	.0527
421.2	83.1	.0476
421.5	83.1	.0425
421.2	83.2	.0368
421.2	83.2	.0306
421.5	83.2	.0249
421.2	83.3	.0188
421.2	83.3	.0132
421.4	83.4	.0133
421.8	83.3	.0189
421.0	83.2	.0251
421.2	83.1	.0306
421.2	83.1	.0361
21.2	83.0	.0419
420.5	83.0	.0475
419.9	82.9	.0520
419.9	82.9	.0565

TABLE 53
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 2
DATE: 7/23/76

TEST NUMBER 6

PART 5B

TEST DESCRIPTION

CLEAN CONDITION-FLOW RATE VERSUS DIFFERENTIAL
PRESSURE..BEFORE PROOF PRESSURE TEST
TEST SPECIMEN (S/N 023) INLET PRESSURE = 415 PSIA (NOMINAL)

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS		AVG GROSS DIFF. PRESS (PSID)	TARE	
			DIFF. PRESS PRIMARY (PSID)	DIFF. PRESS SECONDARY (PSID)		DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
421.8	83.1	.1567	299.869	299.869	299.869	.000	299.869
421.2	83.1	.1577	258.203	258.203	258.203	.000	258.203
421.4	83.1	.1476	213.380	213.380	213.380	.000	213.380
421.2	83.1	.1425	180.553	180.553	180.553	.000	180.553
421.2	83.2	.1468	146.147	146.147	146.147	.000	146.146
421.2	83.2	.1158	115.844	115.844	115.844	.000	115.844
421.2	83.2	.0849	88.899	89.645	89.272	.000	89.271
421.2	83.3	.0818	64.322	65.024	64.673	.000	64.673
421.4	83.3	.0732	44.767	44.921	44.631	-0.000	44.630
421.8	83.4	.0733	43.210	42.945	43.078	-0.000	43.077
421.8	83.3	.0818	63.321	64.077	63.699	.000	63.699
421.4	83.2	.0751	87.429	88.382	87.916	.000	87.916
421.2	83.1	.0706	113.003	113.003	113.003	.000	113.003
421.2	83.1	.0731	144.253	144.253	144.253	.000	144.253
421.4	83.0	.0719	176.765	176.765	176.765	.000	176.765
420.7	83.0	.0745	214.959	214.959	214.959	.000	214.958
419.9	82.9	.0520	252.206	252.206	252.206	.000	252.206
419.9	82.9	.0565	299.869	299.869	299.869	.000	299.869

TARE DIFF. PRESS = $-3.40000E-05 + -4.44000E-04$ (ACFM) + $1.50933E-01$ (ACFM)**2 +

0 (ACFM)**3

TABLE 53
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 3
DATE: 7/23/76

CLEAN CONDITION-FLOW RATE VERSUS DIFFERENTIAL
PRESSURE, BEFORE PROOF PRESSURE TEST
TEST SPECIMEN (S/N 023) INLET PRESSURE = 415 PSIA (NOMINAL)

TEST NUMBER 6 PART 5B TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS										NET DIFFERENTIAL PRESS.	
*****										*****	
PRESSURE		TEMPERATURE			FLOW RATE					NET DIFFERENTIAL PRESS.	
*****										*****	
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	CFM	SCFM	GN ₂ KG/HR	GN ₂ LBS/HR	KG/SQ CM DIFFERENTIAL	PSID
29.658	421.8	311.5	28.3	83.0	45.1	.4567	1.588	3.127	6.894	21.0829	299.869
29.612	421.2	311.5	28.4	83.1	41.6	.4527	1.474	2.982	6.398	18.1934	258.203
29.612	421.2	311.5	28.4	83.1	37.5	.4476	1.330	2.618	5.772	15.0021	213.380
29.612	421.2	311.6	28.4	83.1	33.4	.4425	1.189	2.341	5.161	12.6941	180.552
29.612	421.2	311.6	28.4	83.2	28.9	.4368	1.028	2.025	4.464	10.2751	146.146
29.612	421.2	311.6	28.5	83.2	24.0	.4316	.855	1.684	3.712	8.1446	115.844
29.612	421.2	311.6	28.5	83.2	19.5	.4249	.696	1.371	3.022	6.2764	89.271
29.612	421.2	311.7	28.5	83.3	14.6	.4188	.525	1.034	2.279	4.5470	64.673
29.612	421.2	311.7	28.5	83.3	10.0	.4132	.369	.727	1.603	3.1378	44.630
29.658	421.8	311.7	28.6	83.4	17.1	.4133	.371	.731	1.615	3.0286	43.077
29.658	421.8	311.7	28.5	83.3	14.8	.4189	.530	1.044	2.302	4.4785	63.699
29.658	421.8	311.6	28.5	83.2	19.7	.4251	.702	1.383	3.048	6.1804	87.906
29.612	421.2	311.6	28.4	83.1	24.0	.4306	.857	1.687	3.718	7.9449	113.003
29.612	421.2	311.5	28.4	83.1	28.5	.4367	1.010	1.989	4.386	10.1419	144.252
29.612	421.2	311.5	28.3	83.1	32.9	.4419	1.171	2.306	5.085	12.4278	176.764
29.567	420.5	311.5	28.3	83.0	37.4	.4475	1.326	2.611	5.756	15.1131	214.958
29.521	419.8	311.5	28.3	82.9	40.8	.4520	1.449	2.853	6.291	17.7318	252.205
29.521	419.9	311.5	28.3	82.9	44.5	.4565	1.575	3.102	6.839	21.0829	299.869
****	****	****	****	****							
29.610	421.2	311.6	28.4	83.1							
.025	.3	.1	.1	.1	DEVIATIONS						

TABLE 54

FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 1
DATE: 7/23/76

TEST NUMBER 6

PART 2A

TEST DESCRIPTION

CLEAN CONDITION-FLOW RATE VERSUS DIFFERENTIAL
PRESSURE, BEFORE PROOF PRESSURE TEST
TEST SPECIMEN (S/N 023) INLET PRESSURE = 1000 PSIA (NOMINAL)

FLOWMETER CONDITIONS

FLOWMETER ONE

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)
.83	49.5	76.2
.75	50.2	73.6
.66	50.1	73.4
.58	49.9	72.2
.49	49.9	73.8
.39	49.9	76.
.31	50.2	75.3
.25	49.9	76.2
.21	50.1	77.2
.14	50.2	77.8
.14	50.1	79.5
.22	50.1	78.3
.25	50.1	78.1
.31	50.1	78.6
.40	50.1	78.8
.49	50.2	77.2
.58	50.1	76.2
.67	49.9	75.7
.75	50.2	74.9
.84	49.9	74.2

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)
.90	47.4	72.2
.81	48.5	79.7
.70	48.7	79.1
.60	48.7	78.9
.50	48.9	79.1
.40	49.3	79.4
.31	49.9	79.9
.25	49.5	78.6
.20	79.9	78.9
.13	50.1	77.3
.13	49.9	78.3
.21	49.9	78.2
.25	49.9	78.1
.31	49.9	78.1
.40	49.5	77.9
.51	49.5	77.5
.60	49.1	77.1
.70	48.5	78.6
.81	48.5	79.9
.91	47.9	79.2

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
1011.9	77.2	.0414
1011.9	76.6	.0381
1007.9	76.2	.0335
1007.9	76.1	.0288
1007.9	76.4	.0241
1007.9	77.0	.0194
1007.9	77.6	.0152
1007.9	78.5	.0125
1007.9	79.0	.0102
1007.9	79.5	.0067
1007.9	80.9	.0067
1011.9	80.8	.0106
1011.9	80.6	.0125
1007.9	80.4	.0152
1007.9	80.0	.0198
1007.9	79.3	.0247
1007.9	78.7	.0291
1007.9	78.1	.0334
1007.9	77.4	.0381
1007.9	76.7	.0424

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 54
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 2
DATE: 7/23/76

TEST NUMBER 6 PART 5A TEST DESCRIPTION

CLEAN CONDITION-FLOW RATE VERSUS DIFFERENTIAL
PRESSURE BEFORE PROOF PRESSURE TEST
TEST SPECIMEN (S/N 023) INLET PRESSURE = 1000 PSIA (NOMINAL)

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	IARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
1011.9	77.2	.0414	161.403	161.403	161.403	=0.000	161.403
1011.9	76.6	.0381	145.365	145.365	145.365	=0.000	145.365
1007.9	76.2	.0325	124.472	124.472	124.472	=0.000	124.472
1007.9	76.1	.0288	104.902	104.902	104.902	=0.000	104.902
1007.9	76.4	.0241	84.294	84.294	84.294	=0.000	84.294
1007.9	77.0	.0194	66.653	66.653	66.653	=0.000	66.653
1007.9	77.6	.0152	50.534	50.534	50.534	=0.000	50.534
1007.9	78.5	.0125	41.751	41.751	41.751	=0.000	41.751
1007.9	79.0	.0102	33.356	33.356	33.356	=0.000	33.356
1007.9	79.4	.0067	21.530	21.530	21.530	=0.000	21.530
1007.9	80.9	.0067	21.437	21.437	21.437	=0.000	21.437
1011.9	80.8	.0106	34.975	34.975	34.975	=0.000	34.975
1011.9	80.6	.0125	42.079	42.079	42.079	=0.000	42.079
1007.9	80.4	.0152	50.942	50.942	50.942	=0.000	50.942
1007.9	80.0	.0198	67.847	67.847	67.847	=0.000	67.847
1007.9	79.2	.0247	86.865	86.865	86.865	=0.000	86.865
1007.9	78.7	.0291	106.164	106.164	106.164	=0.000	106.164
1007.9	78.1	.0334	124.788	124.788	124.788	=0.000	124.788
1007.9	77.4	.0381	145.621	145.621	145.621	=0.000	145.621
1007.9	76.7	.0424	166.769	166.769	166.769	=0.000	166.769

IARE DIFF. PRESS = $-1.64000E-04 + -1.26930E-02$ (ACFM) + $2.48070E-01$ (ACFM)**2 +

0 (ACFM)**3

FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN CONDITION-FLOW RATE VERSUS DIFFERENTIAL

PRESSURE: BEFORE PROOF PRESSURE TEST

TEST SPECIMEN (S/N 023) INLET PRESSURE = 1000 PSIA (NOMINAL)

TEST NUMBER 6

PART 5A

TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESS

PRESSURE		TEMPERATURE			FLOW RATE					NET DIFFERENTIAL PRESS			
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN ₂ KG/HR	GN ₂ LBS/HR	KG/SQ CM DIFFERENTIAL	PSID		
71.144	1011.9	298.3	25.1	77.2	81.1	.0414	2.812	5.537	12.206	11.3478	161.403		
71.144	1011.9	297.9	24.8	76.6	74.7	.0381	2.589	5.098	11.240	10.2160	145.305		
70.865	1007.9	297.7	24.6	76.2	65.3	.0335	2.269	4.467	9.848	8.7513	124.472		
70.865	1007.9	297.6	24.5	76.1	55.8	.0280	1.952	3.843	8.472	7.3753	104.902		
70.865	1007.9	297.8	24.7	76.4	46.4	.0241	1.634	3.218	7.894	5.9518	84.655		
70.865	1007.9	298.2	25.0	77.0	37.4	.0194	1.315	2.590	5.710	4.6862	66.653		
70.865	1007.9	298.5	25.4	77.6	29.0	.0152	1.025	2.019	4.451	3.5529	50.534		
70.865	1007.9	299.0	25.8	78.5	23.7	.0125	.842	1.658	3.655	2.9354	41.751		
70.865	1007.9	299.3	26.1	79.1	19.3	.0102	.688	1.354	2.986	2.3452	33.356		
70.865	1007.9	299.6	26.4	79.5	12.6	.0067	.453	.892	1.966	1.5138	21.531		
70.865	1007.9	300.2	27.2	80.9	12.5	.0067	.450	.886	1.954	1.5072	21.437		
71.144	1011.9	300.3	27.1	80.8	20.1	.0106	.714	1.406	3.099	2.4542	34.908		
71.144	1011.9	300.2	27.0	80.6	24.0	.0125	.846	1.667	3.674	2.9585	42.079		
70.865	1007.9	300.0	26.9	80.4	29.0	.0152	1.024	2.016	4.445	3.5816	50.942		
70.865	1007.9	299.8	26.6	80.0	37.8	.0198	1.330	2.612	5.774	4.7701	67.847		
70.865	1007.9	299.5	26.3	79.3	47.3	.0247	1.661	3.271	7.211	6.1073	86.865		
70.865	1007.9	299.1	26.0	78.7	56.3	.0291	1.965	3.869	8.529	7.4641	106.164		
70.865	1007.9	298.8	25.6	78.1	64.8	.0334	2.357	4.445	9.799	8.7735	124.788		
70.865	1007.9	298.4	25.2	77.4	74.2	.0381	2.574	5.068	11.173	10.2382	145.621		
70.865	1007.9	298.0	24.8	76.7	83.0	.0424	2.868	5.647	12.449	11.7251	166.770		
70.921	1008.1	298.0	25.8	78.4									
.089	1.2	.8	.8	1.4	DEVIATIONS								

TABLE 55
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 5 PART 23DR TEST DESCRIPTION

CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL
PRESSURE DATA ACQUIRED AFTER 10 HIGH PRESSURE
(10,000 PSIA NOMINAL) ONE IMPACT CYCLES; FLOW
IN REVERSE DIRECTION. TEST SPECIMEN (S/N 023)
INLET PRESSURE = 415 PSIA NOMINAL.
DATA OBTAINED AFTER PROOF TEST.

FLOW METER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.52	44.9	89.5	.54	48.9	90.9	418.8	90.2	.0624
.50	50.2	89.3	.51	49.5	90.7	418.2	90.0	.0598
.41	50.2	89.2	.42	49.7	90.7	418.2	89.9	.0496
.31	50.4	89.0	.31	50.0	90.4	417.5	89.7	.0369
.26	50.4	88.8	.26	50.0	90.4	417.5	89.6	.0315
.21	50.4	88.8	.21	50.0	90.4	417.5	89.6	.0254
.15	50.2	88.8	.14	50.0	90.5	417.5	89.7	.0174
.15	50.4	89.0	.14	50.2	90.5	417.5	89.7	.0175
.23	50.2	88.7	.23	49.9	90.4	416.9	89.5	.0272
.26	50.4	88.4	.26	50.0	90.2	416.9	89.3	.0315
.31	44.9	88.2	.31	49.5	90.0	416.2	89.1	.0369
.40	50.1	88.1	.40	49.5	89.7	415.6	88.9	.0480
.50	50.2	88.0	.51	49.3	89.5	415.6	88.8	.0600
.52	50.1	88.2	.54	49.1	89.5	414.9	88.8	.0633

ORIGINAL PAGE IS
OF POOR QUALITY

PAGE: 2
DATE: 9-8-76

TABLE 55
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL
PRESSURE DATA ACQUIRED AFTER 10 HIGH PRESSURE
(10,000 PSIA NOMINAL) GN₂ IMPACT CYCLES. FLOW
IN REVERSE DIRECTION. TEST SPECIMEN (S/N 023)
INLET PRESSURE = 415 PSIA NOMINAL. DATA
OBTAINED AFTER PROOF PRESSURE TEST.

TEST NUMBER 5

PART 23DR

TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
418.0	90.2	.0624	291.076	291.076	291.076	.001	291.075
418.2	90.0	.0598	261.684	261.684	261.684	.000	261.683
418.2	89.9	.0496	188.046	188.046	188.046	.000	188.045
417.5	89.7	.0369	125.153	125.153	125.153	.000	125.153
417.5	89.6	.0315	102.398	102.398	102.398	.000	102.397
417.5	89.6	.0254	78.296	79.011	78.653	.000	78.653
417.5	89.7	.0174	50.918	51.515	51.216	.000	51.216
417.5	89.7	.0175	50.793	51.515	51.154	.000	51.153
416.7	89.5	.0272	83.862	84.700	84.281	.000	84.280
416.9	89.3	.0315	102.082	102.082	102.082	.000	102.081
416.2	89.1	.0369	125.785	125.785	125.785	.000	125.785
415.0	88.9	.0480	180.777	180.777	180.777	.000	180.776
415.0	88.8	.0610	266.424	266.424	266.424	.000	266.424
414.9	88.8	.0633	308.774	308.774	308.774	.001	308.774

TARE DIFF. PRESS = $-3.40000E-05 + -4.44000E-04 (ACFM) + 1.50933E-01 (ACFM)**2 +$

$0 (ACFM)**3$

TABLE 55
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL
PRESSURE DATA ACQUIRED AFTER 10 HIGH PRESSURE
(10,000 PSIA NOMINAL) GN₂ IMPACT CYCLES. FLOW
IN REVERSE DIRECTION. TEST SPECIMEN (S/N 023)
INLET PRESSURE = 415 PSIA NOMINAL. DATA
OBTAINED AFTER PROOF PRESSURE TEST.

TEST NUMBER 5 PART 23UR TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESS

PRESSURE		TEMPERATURE			FLOW RATE						
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID
29.441	416.0	305.5	32.4	90.2	48.5	.0624	1.713	3.375	7.436	20.4646	291.075
29.402	416.4	305.4	32.2	90.0	46.4	.0598	1.640	3.230	7.120	18.3982	261.683
29.402	416.4	305.3	32.2	89.9	38.5	.0496	1.361	2.679	5.906	13.2209	188.045
29.356	417.7	305.2	32.1	89.7	28.6	.0369	1.011	1.991	4.390	8.7991	125.153
29.356	417.7	305.2	32.0	89.6	24.5	.0315	.864	1.701	3.749	7.1993	102.397
29.356	417.7	305.2	32.0	89.6	19.7	.0254	.696	1.371	3.023	5.5298	78.653
29.356	417.7	305.2	32.0	89.7	13.5	.0174	.476	.938	2.067	3.6008	51.216
29.356	417.7	305.2	32.1	89.7	13.5	.0175	.478	.941	2.075	3.5964	51.153
29.310	416.2	305.1	32.0	89.5	21.1	.0272	.744	1.467	3.229	5.9255	84.280
29.310	416.2	305.0	31.8	89.3	24.4	.0315	.861	1.690	3.740	7.1770	102.081
29.265	416.4	304.9	31.7	89.1	28.6	.0369	1.009	1.987	4.381	8.8435	125.785
29.219	415.0	304.8	31.6	88.9	37.1	.0480	1.311	2.581	5.689	12.7098	180.776
29.219	415.0	304.7	31.5	88.8	46.4	.0600	1.638	3.227	7.109	18.7315	266.424
29.174	414.9	304.7	31.6	88.8	48.9	.0633	1.727	3.400	7.425	21.7089	308.774
****	****	****	****	****							
29.323	417.1	305.1	31.9	89.5							
.063	.9	.2	.2	.4	DEVIATIONS						

ORIGINAL PAGE IS
OF POOR QUALITY

PAGE: 1
DATE: 9-8-76

TABLE 56
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 5 PART 23ER TEST DESCRIPTION

CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL
PRESSURE DATA ACQUIRED AFTER 10 HIGH PRESSURE
(10,000 PSIA NOMINAL) - GN₂ IMPACT CYCLES. FLOW
IN REVERSE DIRECTION. TEST SPECIMEN (S/N 023)
INLET PRESSURE = 1000 PSIA NOMINAL. DATA
OBTAINED AFTER PROOF PRESSURE TEST
TEST SPECIMEN INLET CONDITIONS.

FLOWMETER CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.85	50.1	83.2	.91	47.9	87.8	1004.0	85.5	.0430
.77	50.1	82.0	.81	48.3	86.9	1004.0	84.5	.0387
.68	50.6	81.2	.71	49.1	86.0	1004.0	83.6	.0345
.59	50.4	80.9	.61	49.3	85.6	1004.0	83.3	.0297
.56	50.1	81.1	.50	49.3	85.7	1004.0	83.4	.0248
.49	50.1	81.5	.41	49.5	85.8	1004.0	83.6	.0200
.31	50.2	82.0	.31	49.9	86.2	1007.9	84.1	.0154
.26	50.4	82.5	.26	50.0	86.2	1004.0	84.4	.0129
.22	50.1	82.9	.21	49.9	86.5	1004.0	84.7	.0106
.15	50.1	83.4	.14	49.9	86.7	1004.0	85.1	.0074
.15	50.2	84.2	.14	50.0	87.3	1004.0	85.8	.0074
.23	49.7	84.2	.22	49.5	87.3	1004.0	85.8	.0112
.26	49.9	84.2	.26	49.5	87.3	1004.0	85.8	.0130
.31	49.9	84.1	.31	49.3	87.2	1004.0	85.6	.0153
.40	50.1	83.4	.40	49.5	86.9	1004.0	85.1	.0200
.50	50.1	82.7	.51	49.3	86.5	1004.0	84.6	.0250
.59	50.4	81.9	.60	49.3	86.0	1004.0	84.0	.0296
.66	50.2	81.2	.70	48.9	85.6	1004.0	83.4	.0338
.76	50.1	80.5	.81	48.3	85.0	1004.0	82.8	.0384
.87	50.2	80.0	.91	48.3	84.4	1004.0	82.2	.0436

TABLE 56
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE DATA ACQUIRED AFTER 10 HIGH PRESSURE (10,000 PSIA NOMINAL) GN₂ IMPACT CYCLES. FLOW IN REVERSE DIRECTION. TEST SPECIMEN (S/N 023)
INLET PRESSURE - 1000 PSIA NOMINAL. DATA OBTAINED AFTER PROOF PRESSURE TEST.

TEST NUMBER 5

PART 73ER

TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
1004.0	85.5	.0439	143.168	143.168	143.168	-0.000	143.168
1004.0	84.5	.0387	126.733	126.733	126.733	-0.000	126.733
1004.0	83.6	.0345	110.615	110.615	110.615	-0.000	110.615
1004.0	83.3	.0297	92.63	93.233	92.931	-0.000	92.932
1004.0	83.4	.0248	75.023	75.534	75.279	-0.000	75.279
1004.0	83.6	.0200	59.522	60.048	59.785	-0.000	59.785
1007.9	84.1	.0154	45.136	45.194	45.165	-0.000	45.165
1004.0	84.4	.0129	37.082	37.265	37.173	-0.000	37.174
1004.0	84.7	.0106	29.665	29.787	29.726	-0.000	29.727
1004.0	85.1	.0074	20.337	20.380	20.358	-0.000	20.359
1004.0	85.8	.0074	20.395	20.551	20.473	-0.000	20.474
1004.0	85.8	.0112	31.635	31.856	31.746	-0.000	31.746
1004.0	85.8	.0130	37.314	37.553	37.433	-0.000	37.433
1004.0	85.6	.0153	44.440	44.703	44.571	-0.000	44.572
1004.0	85.1	.0200	58.895	59.416	59.156	-0.000	59.156
1004.0	84.6	.0250	75.645	76.166	75.906	-0.000	75.906
1004.0	84.0	.0296	92.023	92.917	92.470	-0.000	92.470
1004.0	83.4	.0338	109.983	109.903	109.983	-0.000	109.983
1004.0	82.8	.0384	126.733	126.733	126.733	-0.000	126.733
1004.0	82.2	.0436	146.012	146.012	146.012	-0.000	146.012

TARE DIFF. PRESS = -1.64000E-04 + -1.26930E-02 (ACFM) + 2.48070E-01 (ACFM)**2 + 0 (ACFM)**3

TABLE 56
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL
PRESSURE DATA ACQUIRED AFTER 10 HIGH PRESSURE
(10,000 PSIA NOMINAL) GN₂ IMPACT CYCLES. FLOW
IN REVERSE DIRECTION. TEST SPECIMEN (S/N 023)
INLET PRESSURE - 1000 PSIA NOMINAL. DATA
OBTAINED AFTER PROOF PRESSURE TEST.

TEST NUMBER 5 PART 23ER

TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESS

PRESSURE		TEMPERATURE			FLOW RATE						
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN.	ACFM	SCFM	GN ₂ KG/HK	GN ₂ LBS/HR	KG/SQ CM DIFFERENTIAL	PSID.
70.580	1004.0	302.9	29.7	85.5	80.8	.0430	2.854	5.620	12.389	10.0657	143.168
70.580	1004.0	302.3	29.1	84.5	72.8	.0387	2.572	5.064	11.164	8.9103	126.734
70.580	1004.0	301.8	28.7	83.6	65.0	.0345	2.295	4.518	9.961	7.7770	110.615
70.580	1004.0	301.6	28.5	83.3	56.0	.0297	1.977	3.893	8.583	6.5337	92.932
70.580	1004.0	301.7	28.6	83.4	46.7	.0248	1.651	3.250	7.166	5.2926	75.279
70.580	1004.0	301.9	28.7	83.6	37.8	.0200	1.335	2.628	5.793	4.2033	59.785
70.860	1007.0	302.1	28.9	84.1	29.1	.0154	1.029	2.026	4.467	3.1754	45.165
70.580	1004.0	302.2	29.1	84.4	24.4	.0129	.861	1.699	3.737	2.6136	37.174
70.580	1004.0	302.4	29.3	84.7	19.9	.0106	.704	1.387	3.057	2.0900	29.727
70.580	1004.0	302.7	29.5	85.1	13.9	.0074	.490	.964	2.126	1.4314	20.359
70.580	1004.0	303.0	29.9	85.8	13.9	.0074	.491	.967	2.131	1.4394	20.474
70.580	1004.0	303.0	29.9	85.8	21.0	.0112	.742	1.461	3.221	2.2320	31.746
70.580	1004.0	303.0	29.9	85.8	24.3	.0130	.860	1.699	3.733	2.6318	37.433
70.580	1004.0	302.9	29.8	85.6	28.7	.0153	1.014	1.990	4.400	3.1337	44.572
70.580	1004.0	302.7	29.3	85.1	37.5	.0200	1.325	2.610	5.753	4.1591	59.156
70.580	1004.0	302.4	29.2	84.6	47.0	.0250	1.661	3.271	7.211	5.3367	75.906
70.580	1004.0	302.0	28.9	84.0	55.8	.0296	1.969	3.877	8.547	6.5013	92.470
70.580	1004.0	301.7	28.0	83.4	63.7	.0338	2.248	4.427	9.760	7.7326	109.983
70.580	1004.0	301.4	28.2	82.8	72.5	.0384	2.560	5.041	11.114	8.9103	126.734
70.580	1004.0	301.0	27.9	82.2	82.5	.0436	2.914	5.737	12.649	10.2657	146.012
70.600	1004.0	302.2	29.1	84.3							
.02b	.4	.5	.5	.9	DEVIATIONS						

ORIGINAL PAGE IS
OF POOR QUALITY

PAGE: 1
DATE: 9-8-76

TABLE 57
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 5 PART 23H TEST DESCRIPTION

CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL
PRESSURE DATA ACQUIRED AFTER 10 HIGH PRESSURE
(10,000 PSIA NOMINAL) GN₂ IMPACT CYCLES. TEST
SPECIMEN (S/N 023) INLET PRESSURE = 415 PSIA
NOMINAL. TEST SPECIMEN INLET CONDITIONS

FLOWMETER CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.58	44.9	78.9	.91	47.9	81.3	412.4	80.1	.1059
.78	54.2	79.1	.81	48.5	81.3	411.7	80.2	.0955
.70	54.2	79.3	.71	48.9	81.5	411.1	80.4	.0850
.61	54.4	79.3	.61	49.3	81.4	411.1	80.3	.0736
.51	54.1	79.3	.50	49.1	81.5	411.1	80.4	.0608
.42	54.2	79.5	.41	49.9	81.7	411.1	80.6	.0504
.32	54.2	79.7	.31	49.9	81.8	411.1	80.8	.0380
.27	54.4	79.9	.26	50.0	81.9	411.1	80.9	.0326
.22	54.4	81.1	.21	50.2	82.0	411.1	81.0	.0260
.15	54.2	80.3	.14	50.0	82.1	411.1	81.2	.0173
.15	54.1	80.8	.14	49.9	82.5	411.7	81.6	.0172
.23	44.9	80.9	.22	49.9	82.6	411.1	81.7	.0269
.26	50.1	80.8	.26	49.9	82.5	411.1	81.7	.0328
.32	54.1	80.8	.31	49.7	82.6	411.1	81.7	.0387
.42	44.9	80.6	.41	49.3	82.5	411.1	81.5	.0500
.51	54.2	80.3	.51	49.5	82.4	410.4	81.4	.0620
.61	54.2	80.2	.61	49.3	82.2	410.4	81.2	.0740
.70	54.2	80.1	.71	48.9	82.0	409.8	81.0	.0849
.79	54.1	80.0	.81	48.3	81.8	409.1	80.9	.0962
.87	44.9	80.0	.91	47.9	81.7	408.5	80.9	.1063

TABLE 57
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 5

PART 23H

TEST DESCRIPTION

CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE DATA ACQUIRED AFTER 10 HIGH PRESSURE (10,000 PSIA NOMINAL) GN₂ IMPACT CYCLES. TEST SPECIMEN (S/N 023) INLET PRESSURE = 415 PSIA NOMINAL.

TEST SPECIMEN INLET CONDITIONS

INLET PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
412.4	90.1	.1059	153.386	153.386	153.386	.002	153.385
411.7	90.2	.0955	129.999	129.999	129.999	.001	129.997
411.1	90.4	.0850	108.824	108.824	108.824	.001	108.823
411.1	90.3	.0736	88.569	88.913	88.741	.001	88.740
411.1	90.4	.0678	68.244	68.687	68.465	.000	68.464
411.1	90.6	.0574	52.713	53.211	52.957	.000	52.955
411.1	90.8	.0380	37.758	38.113	37.885	.000	37.884
411.1	90.9	.0326	31.268	31.396	31.332	.000	31.330
411.1	91.0	.0261	23.852	23.932	23.892	.000	23.891
411.1	91.2	.0173	14.871	14.943	14.907	.000	14.906
411.7	91.6	.0172	14.813	14.943	14.878	.000	14.877
411.1	91.7	.0209	24.779	24.977	24.842	.000	24.842
411.1	91.7	.0328	31.558	31.798	31.678	.000	31.677
411.1	91.7	.0387	38.685	38.877	38.781	.000	38.779
411.1	91.5	.0560	52.585	53.211	52.894	.000	52.893
410.4	91.4	.0620	70.368	70.899	70.634	.001	70.632
410.4	91.2	.0741	89.424	90.178	89.801	.001	89.799
409.8	91.0	.0849	109.140	109.140	109.140	.001	109.139
409.1	90.9	.0982	130.947	130.947	130.947	.001	130.946
408.0	90.9	.1063	155.283	155.283	155.283	.002	155.281

TARE DIFF. PRESS = -3.40000E-05 + -4.44000E-04 (ACFM) + 1.50933E+01 (ACFM)**2 + 0 (ACFM)**3

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 57
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL
PRESSURE DATA ACQUIRED AFTER 10 HIGH PRESSURE
(10,000 PSIA NOMINAL) GN₂ IMPACT CYCLES. TEST
SPECIMEN (S/N 023) INLET PRESSURE = 415 PSIA
NOMINAL.

TEST NUMBER 5 PART 23H TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESS

PRESSURE		TEMPERATURE			FLOW RATE							NET DIFFERENTIAL PRESS	
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	CFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID		
28.991	412.4	299.1	26.7	80.1	82.6	.1459	2.916	5.742	12.658	10.7840	153.385		
28.940	411.7	300.0	26.8	80.2	74.3	.1955	2.624	5.167	11.391	9.1397	129.997		
28.900	411.1	300.0	26.9	80.4	66.0	.0880	2.332	4.591	10.121	7.6510	108.823		
28.900	411.1	300.6	26.9	80.3	57.2	.1736	2.019	3.975	8.763	6.2390	88.740		
28.900	411.1	300.1	26.9	80.4	47.2	.0698	1.668	3.289	7.240	4.8135	68.464		
28.900	411.1	300.2	27.0	80.6	39.1	.0504	1.381	2.719	5.994	3.7231	52.955		
28.900	411.1	300.2	27.1	80.8	29.5	.0380	1.041	2.049	4.518	2.6635	37.884		
28.900	411.1	300.3	27.2	80.9	25.3	.0326	.895	1.761	3.883	2.2028	31.330		
28.900	411.1	300.4	27.2	81.0	20.1	.0260	.711	1.401	3.088	1.6797	23.891		
28.900	411.1	300.5	27.3	81.2	13.4	.0173	.475	.935	2.061	1.0480	14.906		
28.946	411.7	300.7	27.6	81.6	13.4	.0172	.473	.931	2.052	1.0459	14.877		
28.900	411.1	300.8	27.0	81.7	20.8	.0259	.735	1.447	3.189	1.7465	24.842		
28.900	411.1	300.8	27.0	81.7	25.4	.0328	.897	1.765	3.892	2.2271	31.677		
28.900	411.1	300.8	27.0	81.7	29.9	.0387	1.058	2.082	4.591	2.7265	38.779		
28.900	411.1	300.7	27.0	81.5	38.7	.0500	1.368	2.694	5.939	3.7187	52.893		
28.855	411.4	300.6	27.4	81.4	48.0	.0620	1.694	3.335	7.355	4.9659	70.632		
28.855	411.3	300.5	27.3	81.2	57.3	.0740	2.023	3.984	8.782	6.3135	89.799		
28.807	409.3	300.4	27.2	81.0	65.6	.0849	2.317	4.563	10.060	7.6732	109.139		
28.764	409.1	300.3	27.2	80.9	74.2	.0962	2.622	5.163	11.383	9.2064	130.946		
28.713	408.5	300.3	27.1	80.9	82.0	.1063	2.895	5.701	12.568	10.9173	155.281		
28.884	410.0	300.4	27.2	81.0									
.042	.0	.2	.2	.4	DEVIATIONS								

TABLE 58
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 5

PART 23F

TEST DESCRIPTION

CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL
PRESSURE DATA ACQUIRED AFTER 10 HIGH PRESSURE
(10,000 PSIA NOMINAL) GN₂ IMPACT CYCLES. FLOW
IN REVERSE DIRECTION. TEST SPECIMEN (S/N 023)
INLET PRESSURE = 1000 PSIA NOMINAL.

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.87	50.1	77.7	.90	47.9	82.7	1005.3	80.2	.0432
.79	49.5	76.8	.82	47.8	81.8	1005.3	79.3	.0388
.69	50.1	76.8	.71	48.5	81.6	1005.3	79.2	.0343
.60	49.7	78.9	.61	48.7	81.6	1005.3	79.2	.0296
.51	49.9	77.3	.51	48.9	81.7	1005.3	79.5	.0250
.42	50.3	77.9	.41	49.9	82.1	1005.3	79.9	.0206
.32	50.5	78.6	.30	50.1	82.4	1005.3	80.5	.0155
.27	49.9	79.3	.26	49.5	82.8	1005.3	81.0	.0130
.22	50.3	79.9	.21	49.9	83.1	1005.3	81.5	.0108
.14	50.1	80.6	.13	49.9	83.5	1005.3	82.0	.0069
.14	50.1	81.6	.13	49.9	83.9	1005.3	82.8	.0069
.22	49.9	81.5	.21	49.7	84.0	1005.3	82.7	.0106
.27	49.9	81.3	.26	49.5	84.1	1005.3	82.6	.0131
.32	49.7	81.1	.31	49.3	84.1	1005.3	82.6	.0156
.42	49.5	80.4	.41	48.9	83.8	1001.3	82.1	.0203
.51	49.9	79.5	.51	49.1	83.5	1001.3	81.5	.0251
.60	50.3	78.7	.60	49.1	82.9	1001.3	80.8	.0298
.69	49.7	77.9	.71	48.3	82.4	1001.3	80.1	.0343
.78	50.3	77.1	.81	48.5	81.8	1001.3	79.4	.0392
.87	50.1	76.3	.91	48.1	81.1	1001.3	78.7	.0437

ORIGINAL PAGE IS
OF POOR QUALITY

PAGE: 2
DATE: 9-8-76

TABLE 58
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL
PRESSURE DATA ACQUIRED AFTER 10 HIGH PRESSURE
(10,000 PSIA NOMINAL) GN2 IMPACT CYCLES. FLOW
IN REVERSE DIRECTION. TEST SPECIMEN (S/N 023)
INLET PRESSURE = 1000 PSIA NOMINAL.

TEST NUMBER 5

PART 03F

TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
1005.3	80.2	.0432	50.498	51.199	50.849	-0.000	50.849
1005.3	79.3	.0388	44.961	44.879	44.920	-0.000	44.920
1005.3	79.2	.0343	38.53	38.628	38.579	-0.000	38.579
1005.3	79.2	.0296	32.099	32.102	32.140	-0.000	32.140
1005.3	79.5	.0250	26.073	26.093	26.083	-0.000	26.083
1005.3	79.9	.0206	20.453	20.475	20.464	-0.000	20.464
1005.3	80.5	.0155	14.659	14.695	14.677	-0.000	14.677
1005.3	81.0	.0130	11.994	12.010	12.002	-0.000	12.002
1005.3	81.5	.0108	9.676	9.669	9.672	-0.000	9.673
1005.3	82.0	.0069	5.852	5.847	5.849	-0.000	5.850
1005.3	82.8	.0069	5.852	5.847	5.849	-0.000	5.850
1005.3	82.7	.0106	9.444	9.497	9.471	-0.000	9.471
1005.3	82.6	.0131	12.157	12.238	12.203	-0.000	12.203
1005.3	82.6	.0156	14.833	14.924	14.878	-0.000	14.879
1001.3	82.1	.0203	20.105	20.303	20.204	-0.000	20.204
1001.3	81.5	.0251	26.247	26.387	26.313	-0.000	26.314
1001.3	80.8	.0290	32.215	32.412	32.313	-0.000	32.313
1001.3	80.1	.0343	38.414	38.628	38.521	-0.000	38.521
1001.3	79.4	.0392	45.193	45.195	45.194	-0.000	45.194
1001.3	78.7	.0437	51.373	52.148	51.760	-0.000	51.760

TARE DIFF. PRESS = $-1.64000E-04 + -1.26930E-02$ (ACFM) + $2.48070E-01$ (ACFM)**2 + 0 (ACFM)**3

TABLE 58
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL
PRESSURE DATA ACQUIRED AFTER 10 HIGH PRESSURE
(10,000 PSIA NOMINAL) GN2 IMPACT CYCLES. FLOW
IN REVERSE DIRECTION. TEST SPECIMEN (S/N 023)
INLET PRESSURE = 1000 PSIA NOMINAL.

TEST NUMBER 5 PART 23F TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESS

PRESSURE		TEMPERATURE			FLOW RATE						NET DIFFERENTIAL PRESS		
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	SCFM	SCFM	GN2 KG/HR	GN2 LB5/HR	KG/SQ CM DIFFERENTIAL	PSID		
70.677	1005.3	299.9	26.8	80.2	82.0	.6432	2.897	5.704	12.574	3.5750	50.849		
70.677	1005.3	299.5	26.3	79.3	73.7	.388	2.608	5.135	11.322	3.1582	44.920		
70.677	1005.3	299.4	25.2	79.2	64.8	.343	2.303	4.535	9.999	2.7124	38.579		
70.677	1005.3	299.4	26.2	79.2	55.9	.296	1.990	3.918	8.639	2.2597	32.140		
70.677	1005.3	299.6	26.4	79.5	46.9	.251	1.678	3.303	7.282	1.8338	26.083		
70.677	1005.3	299.8	26.0	79.9	38.5	.206	1.381	2.720	5.996	1.4388	20.464		
70.677	1005.3	300.1	26.9	80.5	28.7	.155	1.041	2.050	4.519	1.0319	14.677		
70.677	1005.3	300.4	27.2	81.0	24.0	.130	.874	1.721	3.794	.8438	12.002		
70.677	1005.3	300.7	27.5	81.5	19.9	.118	.725	1.427	3.146	.6800	9.673		
70.677	1005.3	301.0	27.8	82.0	12.5	.1069	.461	.909	2.003	.4113	5.850		
70.677	1005.3	301.4	28.2	82.8	12.5	.1069	.461	.907	2.101	.4113	5.850		
70.677	1005.3	301.4	28.2	82.7	19.4	.1100	.708	1.393	3.072	.6659	9.471		
70.677	1005.3	301.3	28.1	82.6	24.1	.1131	.877	1.727	3.807	.8580	12.203		
70.677	1005.3	301.3	28.1	82.6	29.0	.1156	1.044	2.055	4.530	1.0461	14.879		
70.398	1001.3	301.0	27.8	82.1	37.6	.1203	1.352	2.663	5.870	1.4205	20.204		
70.398	1001.3	300.7	27.5	81.5	46.9	.1251	1.675	3.297	7.270	1.8500	26.314		
70.398	1001.3	300.3	27.1	80.8	55.7	.1298	1.986	3.911	8.622	2.2719	32.313		
70.398	1001.3	299.9	26.7	80.1	64.6	.1343	2.292	4.512	9.948	2.7083	38.521		
70.398	1001.3	299.5	26.4	79.4	74.2	.1392	2.623	5.164	11.385	3.1775	45.194		
70.398	1001.3	299.1	26.0	78.7	83.0	.1437	2.927	5.764	12.707	3.6391	51.760		
70.593	1004.1	300.3	27.1	80.8									
.117	1.0	.7	.7	1.2	DEVIATIONS								

TABLE 59
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 5 PART 231R TEST DESCRIPTION

CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL
PRESSURE DATA ACQUIRED AFTER 10 HIGH PRESSURE
(10,000 PSIA NOMINAL) GN₂ IMPACT CYCLES. FLOW
IN REVERSE DIRECTION. TEST SPECIMEN (S/N-023)
INLET PRESSURE = 415 PSIA NOMINAL.

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE			FLOWMETER TWO			PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)			
.83	30.2	83.4	.89	48.3	84.8	416.2	84.1	.1003
.78	30.1	83.2	.81	48.3	84.8	415.6	84.0	.0942
.69	30.1	82.9	.71	48.7	84.7	415.6	83.8	.0831
.60	30.4	82.5	.60	49.3	84.3	414.3	83.4	.0726
.51	49.9	82.2	.50	49.1	84.1	414.3	83.2	.0605
.42	30.2	82.2	.41	49.9	84.3	414.3	83.2	.0497
.31	30.2	82.2	.30	49.9	84.1	414.3	83.2	.0372
.27	30.2	82.2	.26	49.9	84.2	414.3	83.2	.0317
.22	30.2	82.2	.20	49.9	84.2	414.3	83.2	.0254
.14	30.6	82.4	.13	50.4	84.3	414.3	83.3	.0168
.14	30.4	82.5	.13	50.2	84.4	414.3	83.4	.0168
.21	30.1	82.5	.20	49.9	84.3	414.3	83.4	.0253
.27	30.1	82.3	.26	49.9	84.3	414.3	83.3	.0321
.32	30.1	82.2	.31	49.7	84.2	414.3	83.2	.0376
.41	30.1	82.0	.41	49.5	84.4	413.7	83.0	.0494
.51	49.9	81.8	.51	49.1	83.9	413.3	82.8	.0606
.60	30.1	81.7	.60	48.9	83.6	413.3	82.7	.0717
.69	30.1	81.7	.71	48.7	83.5	412.4	82.6	.0837
.76	49.9	81.7	.81	48.3	83.4	411.7	82.5	.0948
.83	30.1	82.1	.87	48.3	83.4	411.7	82.7	.1014

TABLE 59
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE DATA ACQUIRED AFTER 10 HIGH PRESSURE (10,000 PSIA NOMINAL) GN2 IMPACT CYCLES. FLOW IN REVERSE DIRECTION. TEST SPECIMEN (S/N-023) INLET PRESSURE = 415 PSIA NOMINAL.

TEST NUMBER 5

PART 231R

TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
416.2	84.1	.1033	283.912	233.912	283.912	.001	283.911
415.0	84.0	.0942	241.878	241.878	241.878	.001	241.877
415.0	83.8	.0831	190.995	190.995	190.995	.001	190.994
414.3	83.4	.0726	153.702	153.702	153.702	.001	153.701
414.3	83.2	.0615	117.989	117.989	117.989	.000	117.989
414.3	83.2	.0497	89.993	90.178	90.085	.000	90.084
414.3	83.2	.0372	62.697	62.998	62.847	.000	62.846
414.3	83.2	.0317	51.419	51.936	51.678	.000	51.676
414.3	83.2	.0254	39.940	40.687	40.014	.000	40.012
414.3	83.3	.0168	24.818	24.850	24.834	.000	24.832
414.3	83.4	.0168	24.702	24.850	24.775	.000	24.774
414.3	83.4	.0253	39.998	40.260	40.129	.000	40.128
414.3	83.3	.0321	52.797	53.517	53.157	.000	53.156
414.3	83.2	.0376	64.199	64.578	64.389	.000	64.387
413.1	83.0	.0494	89.993	90.010	90.402	.000	90.400
413.0	82.8	.0606	119.886	119.886	119.886	.000	119.884
413.0	82.7	.0717	153.076	153.070	153.070	.001	153.069
412.4	82.6	.0837	195.104	195.104	195.104	.001	195.103
411.1	82.5	.0948	249.779	249.779	249.779	.001	249.778
411.1	82.7	.1014	300.346	300.346	300.346	.001	300.345

TARE DIFF. PRESS = -3.40000E-05 + -4.44000E-04 (ACFM) + 1.50933E-01 (ACFM)²

0 (ACFM)³

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 59
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL
PRESSURE DATA ACQUIRED AFTER 10 HIGH PRESSURE
(10,000 PSIA NOMINAL) GN2 IMPACT CYCLES. FLOW
IN REVERSE DIRECTION. TEST SPECIMEN-(S/N-023)-
INLET PRESSURE = 415 PSIA NOMINAL.

TEST NUMBER 5 PART 23IN TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESS

Pressure		TEMPERATURE				FLOW RATE						NET DIFFERENTIAL PRESS	
KG/50 CM	PSIA	WLG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/50-CM DIFFERENTIAL	PSIA		
29.260	110.2	302.1	28.9	84.1	78.4	0.103	2.767	5.449	12.013	19.9609	283.911		
29.219	110.0	302.1	28.9	84.0	73.0	0.0942	2.596	5.112	11.269	17.0056	241.877		
29.219	110.0	302.1	28.0	83.8	64.9	0.831	2.291	4.511	9.944	13.4282	190.994		
29.128	114.0	301.7	28.0	83.4	56.5	0.720	1.996	3.930	8.665	10.8062	153.701		
29.128	114.0	301.0	28.4	83.2	47.1	0.610	1.664	3.271	7.225	8.2954	117.988		
29.128	114.0	301.0	28.4	83.2	38.7	0.497	1.366	2.689	5.928	6.3335	90.08		
29.128	114.0	301.6	28.4	83.2	28.9	0.372	1.022	2.013	4.437	4.4185	62.846		
29.128	114.0	301.6	28.0	83.2	24.6	0.317	0.870	1.714	3.779	3.6332	51.674		
29.128	114.0	301.0	28.0	83.2	19.8	0.254	0.699	1.370	3.034	2.8131	40.012		
29.128	114.0	301.7	28.0	83.3	13.1	0.168	0.462	0.910	2.007	1.7459	24.837		
29.128	114.0	301.7	28.0	83.4	13.0	0.154	0.460	0.901	1.999	1.7418	24.77		
29.128	114.0	301.7	28.0	83.4	19.7	0.253	0.695	1.368	3.015	2.8213	40.12		
29.128	117.0	301.7	28.0	83.3	25.0	0.321	0.883	1.738	3.832	3.7372	53.15		
29.128	114.0	301.6	28.4	83.2	29.3	0.376	1.035	2.038	4.493	4.5269	64.387		
29.083	113.0	301.0	28.3	83.0	38.4	0.494	1.356	2.669	5.885	6.3558	90.400		
29.131	110.0	301.4	27.2	82.8	47.1	0.606	1.663	3.274	7.218	8.4287	119.88		
29.111	113.0	301.3	28.1	82.7	55.7	0.717	1.966	3.872	8.536	10.7618	153.069		
28.991	112.0	301.3	28.1	82.6	64.9	0.837	2.293	4.510	9.956	13.7171	195.103		
28.940	111.0	301.2	28.1	82.0	73.4	0.944	2.592	5.107	11.254	17.5611	249.77		
28.940	111.0	301.3	28.2	82.7	78.5	1.014	2.772	5.452	12.034	21.1163	300.345		
29.110	114.0	301.6	28.5	83.2									
0.001	0.0	0.0	0.0	0.0									

DEVIATIONS

TABLE 60
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 5 PART 23JR TEST DESCRIPTION

CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE DATA ACQUIRED AFTER 10 HIGH PRESSURE (10,000 PSIA NOMINAL) GN2 IMPACT CYCLES. FLOW IN REVERSE DIRECTION. TEST SPECIMEN (S/N 023) INLET PRESSURE = 1000 PSIA NOMINAL.

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE			FLOWMETER TWO			TEST SPECIMEN INLET CONDITIONS		
FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.87	50.4	76.7	.92	48.3	82.4	1011.9	79.5	.0435
.77	50.2	76.0	.81	48.5	81.7	1007.9	78.9	.0388
.69	50.4	75.7	.71	48.9	81.3	1007.9	78.5	.0345
.60	50.0	75.7	.61	49.5	81.1	1007.9	78.4	.0301
.50	50.4	75.9	.50	49.7	81.2	1007.9	78.6	.0250
.41	50.1	76.6	.40	49.5	81.5	1011.9	79.0	.0200
.32	49.9	77.0	.30	49.5	81.7	1007.9	79.4	.0153
.26	50.2	77.7	.25	49.9	82.1	1011.9	79.9	.0128
.22	50.1	76.4	.21	49.9	82.5	1015.9	80.5	.0104
.15	49.7	79.1	.13	49.5	82.9	1015.9	81.0	.0069
.15	50.4	80.1	.13	50.2	83.4	1015.9	81.7	.0070
.22	50.2	80.1	.20	50.0	83.4	1015.9	81.8	.0104
.28	50.2	80.0	.26	49.9	83.4	1015.9	81.7	.0132
.32	49.9	79.8	.31	49.5	83.4	1015.9	81.6	.0155
.42	50.1	79.3	.41	49.5	83.2	1015.9	81.2	.0203
.51	49.9	78.6	.51	49.1	82.9	1015.9	80.8	.0247
.60	50.4	77.7	.61	49.5	82.4	1015.9	80.1	.0299
.69	50.4	76.9	.70	49.1	81.8	1015.9	79.3	.0341
.78	50.2	76.2	.81	48.7	81.3	1015.9	78.7	.0387
.86	50.2	75.5	.91	48.3	80.5	1007.9	78.0	.0434

ORIGINAL PAGE IS
OF POOR QUALITY

PAGE: 2
DATE: 9-8-76

TABLE 60
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL
PRESSURE DATA ACQUIRED AFTER 10 HIGH PRESSURE
(10,000 PSIA NOMINAL) GN2 IMPACT CYCLES. FLOW
IN REVERSE DIRECTION. TEST SPECIMEN (S/N 023)
INLET PRESSURE = 1000 PSIA NOMINAL.

TEST NUMBER 5 PART 23JR TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
1011.2	79.5	.0435	78.585	79.377	78.956	-0.000	78.956
1007.9	78.9	.0388	68.118	68.897	68.508	-0.000	68.508
1007.9	78.5	.0345	59.479	60.048	59.764	-0.000	59.764
1007.9	78.4	.0301	50.331	51.083	50.607	-0.000	50.607
1007.9	78.6	.0250	40.404	41.401	40.902	-0.000	40.902
1011.2	79.0	.0200	32.002	32.258	32.130	-0.000	32.130
1007.9	79.4	.0153	23.601	23.773	23.652	-0.000	23.652
1011.9	79.9	.0128	19.424	19.520	19.475	-0.000	19.475
1015.9	80.5	.0104	15.250	15.343	15.300	-0.000	15.301
1015.2	81.0	.0089	9.695	9.745	9.720	-0.000	9.720
1015.9	81.7	.0070	9.927	10.030	9.979	-0.000	9.979
1015.9	81.8	.0104	15.431	15.572	15.502	-0.000	15.502
1015.9	81.7	.0132	20.298	20.437	20.367	-0.000	20.368
1015.2	81.6	.0155	24.354	24.506	24.430	-0.000	24.430
1015.9	81.2	.0203	32.871	33.063	32.967	-0.000	32.967
1015.9	80.8	.0247	41.563	41.817	41.690	-0.000	41.690
1015.9	80.1	.0299	51.063	51.531	51.457	-0.000	51.457
1015.2	79.3	.0341	59.479	60.048	59.764	-0.000	59.764
1015.9	78.7	.0387	69.493	70.182	69.827	-0.000	69.827
1007.9	78.0	.0434	78.833	79.643	79.238	-0.000	79.238

TARE DIFF. PRESS = -1.64000E-04 + -1.26930E-02 (ACFM) + 2.48070E-01 (ACFM)**2 +

0 (ACFM)**3

TABLE 60
 FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE DATA ACQUIRED AFTER 10 HIGH PRESSURE (10,000 PSIA NOMINAL) GN₂ IMPACT CYCLES. FLOW IN REVERSE DIRECTION. TEST SPECIMEN (S/N 023) INLET PRESSURE = 1000 PSIA NOMINAL.

TEST NUMBER 5 PART 23JR TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESS

PRESSURE		TEMPERATURE			FLOW RATE						
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID
71.144	1011.7	299.6	26.4	79.5	83.2	.435	2.939	5.781	12.759	5.5512	78.956
70.865	1007.7	299.2	26.0	78.9	74.0	.0388	2.614	5.141	11.346	4.8166	68.508
70.865	1007.7	299.0	25.8	78.5	66.0	.0345	2.330	4.585	10.115	4.2018	59.764
70.865	1007.7	298.9	25.8	78.4	57.5	.0301	2.031	3.999	8.817	3.5581	50.607
70.865	1007.7	299.0	25.9	78.6	47.8	.0250	1.687	3.321	7.322	2.8757	40.902
71.144	1011.7	299.3	26.1	79.0	38.3	.0200	1.351	2.661	5.866	2.2590	32.130
70.865	1007.7	299.5	26.3	79.4	29.2	.0153	1.030	2.025	4.471	1.6629	23.652
71.144	1011.7	299.8	26.6	79.9	24.6	.0128	.867	1.705	3.765	1.3692	19.475
71.423	1015.7	300.1	26.9	80.5	19.9	.0104	.704	1.385	3.056	1.0757	15.301
71.423	1015.7	300.4	27.2	81.0	13.1	.0069	.464	.914	2.014	.6834	9.720
71.423	1015.7	300.8	27.0	81.7	13.4	.0070	.473	.932	2.054	.7016	9.979
71.423	1015.7	300.8	27.7	81.8	19.9	.0104	.702	1.382	3.048	1.0899	15.502
71.423	1015.7	300.8	27.6	81.7	25.4	.0132	.895	1.763	3.887	1.4320	20.368
71.423	1015.7	300.7	27.5	81.6	29.7	.0155	1.048	2.064	4.550	1.7176	24.430
71.423	1015.7	300.5	27.3	81.2	38.8	.0203	1.371	2.700	5.953	2.3178	32.967
71.423	1015.7	300.2	27.1	80.8	47.4	.0247	1.675	3.295	7.271	2.9311	41.690
71.423	1015.7	299.9	26.7	80.1	57.4	.0299	2.027	3.991	8.799	3.6178	51.457
71.423	1015.7	299.5	26.3	79.3	65.5	.0341	2.313	4.555	10.043	4.2018	59.764
71.423	1015.7	299.1	25.7	78.7	74.0	.0387	2.634	5.181	11.435	4.9094	69.827
70.805	1007.7	298.7	25.6	78.0	83.1	.0434	2.934	5.170	12.734	5.5710	79.238
71.214	1012.7	299.8	26.6	79.9							
.230	.3	.6	.6	1.1	DEVIATIONS						

TABLE 61
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 1
DATE: 7/23/76

TEST NUMBER 6 PART 5E TEST DESCRIPTION

CLEAN CONDITION- IMPACT FLOW RATE VERSUS DIFFERENTIAL PRESSURE. PRIOR TO IMPACT DATA. TEST SPECIMEN (S/N 024)
INLET PRESSURE=615 PSIA (NOMINAL)

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.47	49.7	83.1	.48	48.9	84.5	416.6	83.6	.0566
.44	50.4	83.1	.44	49.9	84.0	416.4	83.6	.0529
.40	50.1	83.1	.41	49.5	84.1	416.4	83.6	.0487
.35	50.4	83.1	.35	49.9	84.1	416.2	83.6	.0427
.31	50.2	83.1	.31	49.9	84.5	416.4	83.6	.0368
.26	49.9	83.3	.25	49.5	84.4	416.4	83.8	.0306
.21	50.2	83.5	.20	49.9	84.6	416.4	84.1	.0249
.16	50.4	83.5	.15	50.2	84.6	416.4	84.1	.0190
.12	50.2	83.8	.11	50.1	84.8	416.4	84.3	.0134
.12	50.1	83.7	.11	49.9	84.6	416.6	84.2	.0133
.16	49.9	83.7	.16	49.9	84.7	416.6	84.2	.0195
.21	49.9	83.7	.21	49.7	84.7	416.6	84.2	.0253
.26	49.7	83.6	.26	49.3	84.7	416.4	84.2	.0312
.31	49.7	83.6	.20	49.3	84.8	416.4	84.2	.0363
.35	49.9	83.5	.35	49.3	84.7	416.4	84.1	.0422
.40	49.9	83.5	.41	49.3	84.7	416.4	84.1	.0482
.44	49.7	83.6	.44	49.7	84.7	416.4	84.2	.0523
.48	49.7	83.7	.48	48.9	84.7	415.3	84.2	.0569

TABLE 61
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 2
DATE: 7/23/76

TEST NUMBER 6

PART 3E

TEST DESCRIPTION

SEAN CONDITION- IMPACT/FLOW RATE VERSUS DIFFERENTIAL
PRESSURE, PRIOR TO IMPACT DATA, TEST SPECIMEN (S/N 024)
INLET PRESSURE = 415 PSIA (NOMINAL)

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GRASS DIFF. PRESS PRIMARY (PSID)	GRASS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
416.0	83.6	.1566	296.502	296.502	296.502	.000	296.502
416.0	83.6	.1529	255.152	255.152	255.152	.000	255.151
416.0	83.6	.1487	218.536	218.536	218.536	.000	218.536
416.0	83.6	.1427	179.080	179.080	179.080	.000	179.079
416.0	83.6	.1368	144.674	144.674	144.674	.000	144.673
416.0	83.8	.1306	114.055	114.055	114.055	.000	114.055
416.0	84.1	.1249	87.627	87.627	87.627	.000	87.629
416.0	84.1	.1190	64.498	64.498	64.498	.000	64.499
416.0	84.3	.1134	44.843	44.843	44.729	.000	44.729
416.6	84.2	.1133	44.285	44.096	44.190	.000	44.190
416.6	84.2	.1195	65.429	66.492	65.901	.000	65.900
416.6	84.2	.1253	89.073	90.066	89.570	.000	89.569
416.0	84.2	.1312	116.896	116.896	116.896	.000	116.896
416.0	84.2	.1363	143.411	143.411	143.411	.000	143.411
416.0	84.1	.1422	177.817	177.817	177.817	.000	177.817
416.0	84.1	.1462	217.273	217.273	217.273	.000	217.273
416.0	84.2	.1523	255.152	255.152	255.152	.000	255.151
415.1	84.2	.1569	305.972	305.972	305.972	.000	305.971

TARE DIFF. PRESS = $-3.40000E-05 + -4.44000E-04$ (ACFM) + $1.50933E-01$ (ACFM)**2 + 0 (ACFM)**3

FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN CONDITION-IMPACT/FLOW RATE VERSUS DIFFERENTIAL PRESSURE. PRIOR TO IMPACT DATA. TEST SPECIMEN (S/N 024)
INLET PRESSURE = 415 PSIA (NOMINAL)

TEST NUMBER 6 PART 5E

TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS											NET DIFFERENTIAL PRESS		
PRESSURE		TEMPERATURE			FLOW RATE						DIFFERENTIAL		PSID
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN ₂ KG/HR	GN ₂ LBS/HR	KG/SQ CM DIFFERENTIAL	PSID		
29.293	416.6	301.8	28.7	83.6	44.3	.1566	1.564	3.079	6.788	20.8461	296.502		
29.247	416.0	301.8	28.7	83.6	47.2	.1529	1.460	2.875	6.338	17.9389	255.151		
29.247	416.0	301.8	28.7	83.6	38.0	.1487	1.342	2.643	5.827	15.3646	218.536		
29.247	416.0	301.8	28.7	83.6	39.1	.1427	1.178	2.319	5.112	12.5905	179.079		
29.247	416.0	301.8	28.7	83.6	58.6	.0368	1.015	1.999	4.407	10.1715	144.673		
29.247	416.0	301.9	28.8	83.8	23.6	.0306	.843	1.660	3.660	8.0189	114.055		
29.247	416.0	302.1	28.9	84.1	19.1	.0249	.686	1.351	2.979	6.1792	87.089		
29.247	416.0	302.1	28.9	84.1	14.5	.0190	.523	1.029	2.269	4.5139	64.203		
29.247	416.0	302.2	29.1	84.3	10.0	.0134	.369	.727	1.602	3.1447	44.729		
29.293	416.6	302.2	29.0	84.2	10.0	.0133	.368	.724	1.596	3.1069	44.190		
29.293	416.6	302.2	29.0	84.2	15.1	.0195	.537	1.058	2.333	4.6333	65.200		
29.293	416.6	302.2	29.0	84.2	19.5	.0253	.699	1.376	3.034	6.2973	89.569		
29.247	416.0	302.1	29.0	84.2	24.2	.0312	.859	1.691	4.728	8.2186	116.896		
29.247	416.0	302.2	29.0	84.2	28.1	.0363	1.000	1.969	4.340	10.0828	143.411		
29.247	416.0	302.1	29.0	84.1	32.7	.0422	1.143	2.290	5.049	12.5018	177.817		
29.247	416.0	302.1	28.9	84.1	37.5	.0482	1.328	2.614	5.763	15.2758	217.273		
29.247	416.0	302.1	29.0	84.2	40.7	.0523	1.442	2.839	6.260	17.9389	255.151		
29.201	415.3	302.2	29.0	84.2	44.2	.0569	1.565	3.081	6.793	21.5119	305.271		
29.254	416.1	302.0	28.9	84.0									
.017	.2	.1	.1	.2	DEVIATIONS								

TABLE 62
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 1
DATE: 7/23/76

CLEAN CONDITION-IMPACT/FLOW RATE VERSUS DIFFERENTIAL PRESSURE. PRIOR TO IMPACT DATA, TEST SPECIMEN (S7N 024). INLET PRESSURE = 700 PSIA NOMINAL

TEST NUMBER 6 PART 30 TEST DESCRIPTION

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.84	49.7	77.7	.91	47.8	76.5	700.0	74.1	.0608
.76	50.2	75.4	.81	48.5	75.4	700.0	73.9	.0552
.67	51.4	75.6	.71	49.1	75.5	700.0	74.1	.0489
.58	49.7	77.7	.60	48.7	76.7	700.0	74.2	.0416
.49	49.7	73.0	.50	48.9	76.1	700.0	74.5	.0348
.40	44.9	73.4	.40	40.3	76.2	700.0	74.8	.0280
.31	51.2	73.7	.31	49.9	76.5	700.0	75.1	.0220
.26	50.4	77.1	.25	40.1	76.7	700.0	75.4	.0183
.21	49.9	74.6	.20	49.9	77.0	700.0	75.8	.0147
.14	51.2	75.1	.14	50.1	77.3	700.0	76.2	.0100
.14	50.2	76.4	.14	50.1	78.2	700.9	77.3	.0099
.22	49.7	76.3	.21	49.5	78.2	703.9	77.2	.0151
.26	49.9	76.1	.26	49.7	78.2	703.9	77.1	.0186
.31	49.7	75.9	.31	49.3	78.2	703.9	77.1	.0216
.40	50.4	75.6	.40	49.9	78.2	703.9	76.9	.0284
.49	49.7	75.4	.50	48.9	78.5	700.0	76.5	.0347
.58	49.7	74.5	.61	48.7	77.7	700.0	76.1	.0414
.67	50.1	77.1	.71	48.7	77.9	700.0	76.0	.0484
.76	51.4	73.9	.81	48.7	77.1	700.0	75.4	.0554
.84	51.2	73.4	.91	48.3	76.5	700.0	75.0	.0616

TABLE 62
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 2
DATE: 7/23/76

CLEAN CONDITION-IMPACT/FLOW RATE VERSUS DIFFERENTIAL PRESSURE. PRIOR TO IMPACT DATA. TEST SPECIMEN (S/N 024)
INLET PRESSURE=200 PSIA NOMINAL

TEST NUMBER 6

PART 3D

TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

AVG PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIEG. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
700.0	74.1	.0608	249.360	249.360	249.360	-0.000	249.360
700.0	73.9	.1552	217.440	217.440	217.440	-0.000	217.440
700.0	74.1	.0489	184.887	184.887	184.887	-0.000	184.887
700.0	74.2	.0416	151.070	151.070	151.070	-0.001	151.070
700.0	74.5	.1348	121.362	121.362	121.362	-0.001	121.362
700.0	74.8	.0280	93.917	93.917	93.917	-0.001	93.917
700.0	75.1	.0220	71.700	71.700	71.700	-0.001	71.700
700.0	75.4	.0183	57.054	57.054	57.054	-0.001	57.054
700.0	75.8	.0147	45.999	45.999	45.999	-0.001	45.999
700.0	76.2	.0170	30.541	30.541	30.541	-0.001	30.541
703.9	77.3	.0099	30.353	30.353	30.353	-0.001	30.353
703.9	77.2	.0151	47.548	47.548	47.548	-0.001	47.548
703.9	77.1	.0186	58.811	58.811	58.811	-0.001	58.811
703.9	77.1	.0216	69.941	69.941	69.941	-0.001	69.941
703.9	76.9	.0284	94.611	94.611	94.611	-0.001	94.611
700.0	76.5	.0327	121.046	121.046	121.046	-0.001	121.046
700.0	76.1	.0414	150.122	150.122	150.122	-0.001	150.122
700.0	76.0	.0484	183.623	183.623	183.623	-0.000	183.623
700.0	75.4	.0554	219.652	219.652	219.652	-0.000	219.652
700.0	75.0	.0616	255.049	255.049	255.049	.000	255.049

TARE DIFF. PRESS = $-3.60000E-04 + -3.31610E-02$ (ACFM) + $6.33359E-01$ (ACFM)**2 +

0 (ACFM)**3

TABLE 62
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 3
DATE: 7/23/76

CLEAN, CONDITION-IMPACT/FLOW RATE VERSUS DIFFERENTIAL PRESSURE. PRIOR TO IMPACT DATA. TEST SPECIMEN (S/N 024)
INLET PRESSURE = 700 PSIA(NOMINAL)

TEST NUMBER 6 PART 20 TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS											NET DIFFERENTIAL PRESS:	
*****											*****	
PRESSURE		TEMPERATURE				FLOW RATE						
*****		*****				*****						
KG/50 CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN ₂ KG/HR	GN ₂ LBS/HR	KG/SQ CM DIFFERENTIAL	PSID	
49.212	700.0	296.6	23.4	74.1	82.9	.0608	2.871	5.653	12.463	17.5318	249.360	
49.212	700.0	296.4	23.3	73.9	75.1	.0555	2.611	5.141	11.335	15.2875	217.440	
49.212	700.0	296.5	23.4	74.1	66.4	.0489	2.313	4.553	10.039	12.9989	184.887	
49.212	700.0	296.6	23.4	74.2	56.2	.0416	1.966	3.871	8.534	10.6213	151.070	
49.212	700.0	296.8	24.6	74.5	46.7	.0348	1.645	3.238	7.139	8.5326	121.362	
49.212	700.0	296.9	23.8	74.8	37.2	.0280	1.322	2.603	5.739	6.5661	93.391	
49.212	700.0	297.1	24.0	75.1	29.3	.0220	1.037	2.042	4.502	4.9962	71.063	
49.212	700.0	297.3	24.1	75.4	24.1	.0183	.860	1.694	3.735	4.0389	57.446	
49.212	700.0	297.5	24.3	75.8	19.4	.0147	.694	1.367	3.014	3.2260	45.884	
49.212	700.0	297.7	24.6	76.2	13.0	.0100	.471	.927	2.043	2.1359	30.380	
49.489	703.9	298.3	25.2	77.3	13.0	.0099	.470	.925	2.039	2.1294	30.287	
49.489	703.9	298.3	25.1	77.3	19.9	.0151	.711	1.400	3.086	3.3569	47.319	
49.489	703.9	298.2	25.1	77.1	24.8	.0186	.881	1.734	3.823	4.1672	59.272	
49.489	703.9	298.2	25.4	77.1	28.8	.0216	1.022	2.012	4.435	4.9588	70.531	
49.489	703.9	298.1	24.9	76.9	38.0	.0284	1.341	2.640	5.821	6.6923	95.186	
49.212	700.0	297.9	24.7	76.5	46.4	.0347	1.633	3.219	7.088	8.5104	121.046	
49.212	700.0	297.6	24.5	76.1	55.8	.0414	1.950	3.840	8.466	10.5546	150.122	
49.212	700.0	297.6	24.5	76.0	65.5	.0484	2.281	4.491	9.900	12.9100	183.623	
49.212	700.0	297.3	24.1	75.4	75.1	.0554	2.611	5.141	11.334	15.4431	219.652	
49.212	700.0	297.4	23.9	75.0	83.9	.0616	2.906	5.722	12.614	17.9317	255.049	
****	****	****	****	****								
49.281	700.9	297.4	24.2	75.6								
.104	1.5	.5	.5	1.0	DEVIATIONS							

PAGE: 1
DATE: 7/23/76

TABLE 63
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN CONDITION-IMPACT/FLOW RATE VERSUS DIFFERENTIAL PRESSURE, PRIOR TO IMPACT DATA, TEST SPECIMEN (S/N 024)
INLET PRESSURE = 1000 PSIA (NOMINAL)

TEST NUMBER 6 PART 5C TEST DESCRIPTION

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.83	50.3	67.0	.91	48.3	49.3	1007.9	69.6	.0425
.75	50.5	66.5	.81	48.7	71.9	1007.9	69.2	.0384
.67	50.3	66.3	.71	48.7	71.5	1007.9	68.9	.0338
.58	49.7	66.3	.61	48.3	71.1	996.3	68.7	.0295
.49	49.7	66.5	.50	48.9	71.3	1007.9	68.9	.0243
.40	50.1	67.1	.20	49.5	71.6	1007.9	69.4	.0198
.30	49.7	67.7	.30	49.3	71.9	1007.9	69.8	.0149
.26	49.9	68.5	.55	49.5	72.3	1007.9	70.4	.0125
.21	50.1	69.2	.20	49.9	72.6	1007.9	70.9	.0101
.13	49.9	69.9	.13	49.9	73.1	1007.9	71.4	.0065
.13	49.9	71.6	.13	49.9	73.8	1007.9	72.7	.0065
.21	49.7	71.2	.21	49.5	72.9	1007.9	72.7	.0104
.26	50.1	71.1	.26	49.9	73.9	1007.9	72.5	.0129
.30	49.5	71.7	.21	49.1	74.8	1007.9	72.3	.0149
.40	49.7	72.0	.40	49.1	73.6	1004.0	71.8	.0197
.49	50.1	69.2	.51	49.3	73.2	1004.0	71.2	.0247
.58	50.1	68.3	.60	48.9	72.7	1004.0	70.5	.0292
.67	50.1	67.5	.71	48.7	72.1	1004.0	69.8	.0339
.75	50.5	66.7	.81	48.7	71.3	1004.0	69.0	.0384
.84	50.3	66.2	.91	48.3	70.6	1004.0	68.4	.0429

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 63
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 2
DATE: 7/23/76

TEST NUMBER 6

PART 5C

TEST DESCRIPTION

CLEAN CONDITION- IMPACT FLOW RATE VERSUS DIFFERENTIAL
PRESSURE. PRIOR TO IMPACT DATA. TEST SPECIMEN (S/N 0240)
INLET PRESSURE = 1000 PSIA (NOMINAL)

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS		AVG GROSS DIFF. PRESS (PSID)	TARE		NET	
			DIFF. PRESS PRIMARY (PSID)	DIFF. PRESS SECONDARY (PSID)		DIFF. PRESS (PSID)	DIFF. PRESS (PSID)		
1007.9	69.6	.0425	165.081	165.081	165.081	0.000	165.081		
1007.9	69.2	.384	145.487	145.487	145.487	0.000	145.487		
1007.9	68.9	.0328	125.260	125.260	125.260	0.000	125.260		
996.0	68.7	.0295	104.401	104.401	104.401	0.000	104.401		
1007.9	68.9	.243	84.627	85.122	84.874	0.000	84.874		
1007.9	69.4	.0198	66.699	67.177	66.903	0.000	66.903		
1007.9	69.8	.0149	48.887	49.409	49.148	0.000	49.148		
1007.9	70.4	.0126	41.515	41.226	41.370	0.000	41.371		
1007.9	70.9	.0141	32.696	32.477	32.551	0.000	32.552		
1007.9	71.4	.0065	20.770	20.515	20.628	0.000	20.629		
1007.9	72.7	.0065	20.490	20.515	20.503	0.000	20.503		
1007.9	72.7	.0174	33.442	33.386	33.414	0.000	33.414		
1007.9	72.5	.0129	42.507	42.723	42.415	0.000	42.415		
1007.9	72.3	.0149	48.887	49.409	49.148	0.000	49.148		
1004.0	71.8	.197	66.323	66.797	66.557	0.000	66.557		
1004.0	71.2	.0247	85.613	86.386	85.999	0.000	85.999		
1004.0	70.5	.0292	105.033	105.033	105.033	0.000	105.033		
1004.0	69.8	.339	125.576	125.576	125.576	0.000	125.576		
1004.0	69.0	.0784	146.435	146.435	146.435	0.000	146.435		
1004.0	68.4	.0429	167.610	167.610	167.610	0.000	167.610		

TARE DIFF. PRESS = -1.64000E-04 + -1.26930E-02 (ACFM) + 2.48970E-01 (ACFM)**2 + 0 (ACFM)**3

TABLE 63
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 5
DATE: 7/23/76

CLEAN CONDITION. IMPACT FLOW RATE VERSUS DIFFERENTIAL PRESSURE, PRIOR TO IMPACT DATA. TEST SPECIMEN (S/N 024)
INLET PRESSURE = 1000 PSIA (NOMINAL)

TEST NUMBER 6 PART 20 TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS											NET DIFFERENTIAL PRESS.		
PRESSURE		TEMPERATURE			FLOW RATE								
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID		
70.865	1007.9	294.1	29.9	69.6	84.4	.425	2.913	5.735	12.644	11.6054	168.082		
70.865	1007.9	293.8	29.7	69.5	76.0	.4384	2.636	5.191	11.443	10.2287	145.487		
70.865	1007.9	293.7	29.5	68.9	66.7	.4332	2.322	4.571	10.578	8.8066	125.260		
70.029	996.0	293.6	29.4	68.7	57.3	.4295	2.001	3.940	8.587	7.3401	104.401		
70.865	1007.9	293.7	29.5	68.9	47.5	.4243	1.673	3.293	7.261	5.9673	84.874		
70.865	1007.9	293.9	29.8	69.4	38.4	.4198	1.360	2.678	5.983	4.7038	66.903		
70.865	1007.9	294.2	29.8	69.8	28.9	.4149	1.025	2.012	4.451	3.4555	49.148		
70.865	1007.9	294.5	29.3	70.4	24.2	.4126	.863	1.692	3.745	2.9086	41.371		
70.865	1007.9	294.8	29.6	70.9	19.5	.4101	.694	1.367	3.014	2.2886	32.552		
70.865	1007.9	295.1	29.9	71.4	12.4	.4065	.447	.872	1.939	1.4523	20.528		
70.865	1007.9	295.8	29.6	72.7	12.2	.4065	.442	.871	1.921	1.4415	20.503		
70.865	1007.9	295.8	22.6	72.7	19.9	.4104	.707	1.391	3.667	2.3492	33.414		
70.865	1007.9	295.7	22.5	72.5	24.8	.4129	.881	1.735	3.826	2.9821	42.418		
70.865	1007.9	295.5	22.4	72.3	28.8	.4149	1.020	2.008	4.426	3.4555	49.148		
70.586	1004.0	295.3	22.1	71.8	38.1	.4197	1.343	2.645	5.831	4.6795	66.557		
70.586	1004.0	294.9	21.8	71.2	47.9	.4247	1.681	3.310	7.298	6.0464	85.999		
70.586	1004.0	294.6	21.4	70.5	56.9	.4292	1.990	3.912	8.640	7.3845	105.033		
70.586	1004.0	294.2	21.1	69.8	66.6	.4339	2.313	4.555	10.043	8.8289	125.876		
70.586	1004.0	293.7	20.6	69.1	75.7	.4384	2.628	5.175	11.409	10.2954	146.435		
70.586	1004.0	293.4	20.2	68.4	84.9	.4429	2.940	5.788	12.761	11.7842	167.610		
70.740	1006.2	294.5	21.3	70.4									
.163	2.3	.7	.7	1.2	DEVIATIONS								

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 64
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 1
DATE: 7-26-76

TEST NUMBER 6 PART 2I TEST DESCRIPTION

CLEAN CONDITION - IMPACT/FLOW RATE VERSUS
DIFFERENTIAL PRESSURE AFTER 80 HIGH PRESSURE
(10,000 PSIA) GN₂ IMPACTS. TEST SPECIMEN
(S/N 024) INLET PRESSURE = 415 PSIA NOMINAL.

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE			FLOWMETER TWO			PRESSURE (PSIA)	AVG TEMP. (DEG. F)	AVG. FLOW RATE (ACFM)
FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)			
.81	77.7	78.5	.81	47.9	82.3	416.5	79.4	.0985
.76	77.2	78.3	.81	48.7	82.3	415.2	79.3	.0939
.68	77.4	78.1	.71	49.1	80.2	413.9	79.2	.0836
.59	77.4	78.0	.61	49.7	80.1	413.9	79.1	.0726
.50	77.0	77.9	.51	49.9	80.1	414.9	79.0	.0616
.41	77.0	78.1	.41	50.1	80.1	413.9	79.1	.0494
.31	77.4	78.4	.31	50.2	80.3	413.9	79.4	.0383
.26	77.0	76.6	.26	50.4	80.4	413.9	79.5	.0321
.22	77.7	81.8	.21	49.7	82.7	421.1	82.3	.0254
.15	77.1	81.9	.15	50.1	82.8	421.1	82.4	.0180
.15	77.1	82.0	.15	50.1	82.5	421.1	82.3	.0179
.22	77.1	81.8	.22	49.9	82.3	421.1	82.0	.0264
.27	77.9	81.7	.26	49.9	82.6	420.4	82.2	.0316
.32	77.1	81.7	.32	49.9	82.7	419.8	82.2	.0380
.41	77.9	81.4	.41	49.3	82.7	419.8	82.1	.0487
.50	77.7	81.1	.51	49.1	82.5	419.1	81.8	.0593
.59	77.7	81.9	.61	48.7	82.5	418.5	81.7	.0705
.68	77.7	81.7	.71	48.5	82.2	417.8	81.5	.0819
.76	77.5	81.7	.81	47.9	82.2	416.5	81.5	.0919
.81	77.5	81.1	.87	47.8	82.2	415.9	81.7	.0982

TABLE 64
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 2
DATE: 7-26-76

TEST NUMBER 6

PART 21

TEST DESCRIPTION

CLEAN CONDITION - IMPACT/FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. AFTER 80 HIGH PRESSURE
(10,000 PSIA) GN2 IMPACTS. TEST SPECIMEN
(S/N 024) INLET PRESSURE = 415 PSIA NOMINAL.

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS	GROSS	AVG GROSS DIFF. PRESS (PSID)	TARE	NET
			DIFF. PRESS PRIMARY (PSID)	DIFF. PRESS SECONDARY (PSID)		DIFF. PRESS (PSID)	DIFF. PRESS (PSID)
416.7	19.4	.0905	298.980	298.980	298.980	.001	298.978
417.6	19.3	.0939	260.422	260.422	260.422	.001	260.421
413.7	19.2	.0836	205.430	205.430	205.430	.001	205.429
413.7	19.1	.0725	163.080	163.080	163.080	.001	163.078
413.7	19.0	.0616	127.683	127.683	127.683	.001	127.681
413.7	19.1	.0494	94.080	94.084	94.442	.000	94.447
413.7	19.4	.0383	68.911	69.530	69.220	.000	69.219
413.7	19.5	.0321	56.014	59.572	56.292	.000	56.292
421.1	02.3	.204	43.340	43.526	43.930	.000	43.935
421.1	02.4	.0100	29.858	30.760	30.310	.000	30.309
421.1	02.3	.0179	30.100	30.992	30.542	.000	30.548
421.1	02.0	.0204	45.507	47.091	46.292	.000	46.298
420.7	02.2	.0316	57.142	58.150	57.547	.000	57.546
419.0	02.2	.0380	70.560	71.426	71.042	.000	71.042
417.0	02.1	.0487	96.710	96.710	96.710	.000	96.709
417.0	01.0	.0593	125.154	125.154	125.154	.000	125.153
414.0	01.7	.0700	159.910	159.919	159.910	.001	159.918
411.0	01.5	.0814	201.637	201.637	201.637	.001	201.636
410.0	01.5	.0919	248.412	248.412	248.412	.001	248.411
410.0	01.7	.0902	291.070	291.078	291.070	.001	291.077

$$\text{GROSS DIFF. PRESS} = -3.40000E-05 + -4.44000E-04 (\text{ACFM}) + 1.50933E-01 (\text{ACFM})^{.82} + 0. (\text{ACFM})^{.83}$$

TABLE 64
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 3
DATE: 7-26-76

TEST NUMBER 6

PART 21

TEST DESCRIPTION

CLEAN CONDITION - IMPACT/FLOW RATE VERSUS
DIFFERENTIAL PRESSURE, AFTER 80 HIGH PRESSURE
(10,000 PSIA) GN₂ IMPACTS, TEST SPECIMEN
(S/N 024) INLET PRESSURE = 415 PSIA NOMINAL

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESS

PRESSURE		TEMPERATURE			FLOW RATE							
KG/SQ CM	PSIA	DEG. C	DEG. F	LITERS/ MIN	CFM	SCFM	GN ₂ KG/HR	GN ₂ LB/HR	KG/SQ CM DIFFERENTIAL	PSIA		
29.284	410.0	299.5	26.3	79.4	79.0	0.985	2.742	5.397	11.903	21.0203	298.778	
29.194	410.5	299.4	26.3	79.3	74.9	0.939	2.608	5.132	11.319	18.3094	260.421	
29.111	412.2	299.4	26.2	79.2	66.3	0.836	2.314	4.557	10.043	14.4431	205.429	
29.101	413.2	299.3	26.1	79.1	57.6	0.726	2.010	3.957	8.728	11.4656	163.078	
29.101	413.2	299.3	26.1	79.0	48.4	0.616	1.705	3.251	7.400	8.9769	127.881	
29.101	413.2	299.3	26.2	79.1	38.6	0.474	1.308	2.592	5.938	6.6403	94.447	
29.101	413.2	299.5	26.3	79.4	29.9	0.383	1.059	2.087	4.596	4.8666	69.412	
29.101	413.2	299.6	26.4	79.5	24.7	0.321	0.888	1.747	3.856	3.9577	56.292	
29.004	421.4	301.1	27.4	82.3	19.9	0.224	0.712	1.402	3.091	3.0889	43.735	
29.004	421.4	301.1	28.0	82.4	14.0	0.180	0.505	0.994	2.192	2.1309	30.309	
29.004	421.4	301.1	27.7	82.3	13.9	0.179	0.502	0.987	2.179	2.1477	30.248	
29.004	421.4	301.0	27.8	82.0	20.1	0.264	0.739	1.457	3.208	3.2550	46.428	
29.558	427.2	301.0	27.9	82.2	24.9	0.316	0.884	1.740	3.835	4.0529	57.646	
29.514	419.0	301.1	27.4	82.2	30.0	0.380	1.059	2.080	4.599	4.9947	71.042	
29.514	419.0	301.1	27.8	82.1	38.3	0.467	1.359	2.570	5.901	6.7993	96.102	
29.409	419.4	300.8	27.1	81.8	46.9	0.593	1.653	3.257	7.175	8.7991	125.153	
29.421	419.9	300.7	27.0	81.7	56.0	0.705	1.964	3.860	8.524	11.2434	159.718	
29.377	419.0	300.6	27.5	81.5	65.4	0.819	2.279	4.481	9.892	14.1764	201.836	
29.284	418.9	300.0	27.0	81.5	73.3	0.919	2.549	5.017	11.065	17.4650	248.411	
29.238	415.2	300.0	27.0	81.7	78.2	0.982	2.717	5.347	11.794	20.4648	291.077	
29.243	415.2	300.3	27.1	80.0								
0.103	2.0	0.7	0.1	1.3	DEVIATIONS							

TABLE 65
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 6 PART 2H TEST DESCRIPTION

CLEAN CONDITION - IMPACT/FLOW RATE VERSUS
DIFFERENTIAL PRESSURE, AFTER 80 HIGH PRESSURE
(10,000 PSIA) GN2 IMPACTS. TEST SPECIMEN
(S/N 024) INLET PRESSURE = 700 PSIA NOMINAL.

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESS. (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE, (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.85	22.9	73.7	.91	47.9	76.8	703.9	75.2	.0610
.76	20.2	73.2	.81	48.7	76.3	703.9	74.8	.0550
.67	24.4	74.1	.70	49.1	76.3	703.9	74.7	.0485
.58	21.4	73.1	.60	49.5	76.3	703.9	74.7	.0421
.50	23.4	73.3	.51	49.9	76.3	700.0	74.8	.0359
.41	21.4	73.6	.41	49.9	76.5	700.0	75.1	.0295
.31	42.9	74.2	.31	49.7	76.8	703.9	75.5	.0221
.27	20.1	74.5	.29	49.9	77.0	703.9	75.7	.0189
.22	22.5	74.7	.22	49.3	77.3	703.9	76.1	.0152
.14	42.5	75.5	.13	49.2	77.7	703.9	76.6	.0096
.14	20.1	76.8	.13	50.1	78.3	703.9	77.6	.0098
.22	20.2	76.9	.22	50.1	78.5	703.9	77.7	.0157
.26	24.4	76.8	.26	50.2	78.7	703.9	77.8	.0186
.32	20.2	76.7	.31	50.1	78.7	703.9	77.7	.0225
.41	24.1	76.4	.41	49.7	78.7	703.9	77.5	.0291
.50	22.7	76.1	.51	48.9	78.6	703.9	77.3	.0393
.59	42.9	75.7	.61	48.9	78.5	703.9	77.1	.0418
.68	42.5	75.4	.71	48.3	78.2	703.9	76.8	.0484
.76	22.5	75.1	.81	47.8	78.0	700.0	76.5	.0546
.84	42.7	74.7	.91	47.8	77.7	700.0	76.2	.0610

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 65
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN CONDITION - IMPACT/FLOW RATE VERSUS
DIFFERENTIAL PRESSURE, AFTER 80 HIGH PRESSURE
(10,000 PSIA) GN₂ IMPACTS. TEST SPECIMEN
(S/N 024) INLET PRESSURE = 700 PSIA NOMINAL.

TEST NUMBER 6	PART 2H	TEST DESCRIPTION	TEST SPECIMEN INLET CONDITIONS *****				
TEST SPECIMEN INLET CONDITIONS *****	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
703.9	75.2	.0610	124.206	124.206	124.206	-0.000	124.206
703.2	74.8	.0550	108.720	108.720	108.720	-0.000	108.720
703.9	74.7	.0485	91.746	92.918	92.334	-0.000	92.332
703.2	74.7	.0421	77.344	78.063	77.704	-0.001	77.704
700.2	74.8	.0359	63.486	63.841	63.664	-0.001	63.664
700.9	74.1	.0292	50.581	51.199	50.890	-0.001	50.890
703.9	75.5	.0221	37.999	37.889	37.944	-0.001	37.944
703.9	75.7	.0189	32.095	31.906	32.001	-0.001	32.001
703.9	76.1	.0152	25.496	25.303	25.401	-0.001	25.401
703.2	76.6	.0097	16.268	16.026	16.147	-0.001	16.147
703.2	77.6	.0098	16.393	16.369	16.381	-0.001	16.381
703.2	77.7	.0157	26.993	26.910	26.951	-0.001	26.951
703.2	77.8	.0186	32.469	32.423	32.446	-0.001	32.446
703.2	77.7	.0225	39.923	39.790	39.857	-0.001	39.857
703.2	77.5	.0291	51.832	52.464	52.148	-0.001	52.148
703.2	77.7	.0350	64.613	65.116	64.859	-0.001	64.859
703.2	77.1	.0418	78.461	79.112	78.736	-0.001	78.736
703.2	76.8	.0484	92.961	93.866	93.413	-0.000	93.413
700.9	76.5	.0506	107.140	107.140	107.140	-0.000	107.140
700.9	76.2	.0610	123.890	123.890	123.890	-0.000	123.890

TARE DIFF. PRESS = -3.60000E-04 + -3.31610E-02 (ACFM) + 6.33369E+01 (ACFM)**2 + 0 (ACFM)**3

TABLE 65
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 6 PART 2H TEST DESCRIPTION

CLEAN CONDITION - IMPACT/FLOW RATE VERSUS
DIFFERENTIAL PRESSURE AFTER 80 HIGH PRESSURE
(10,000 PSIA) GN₂ IMPACTS. TEST SPECIMEN
(S/N 024) INLET PRESSURE = 700 PSIA NOMINAL.

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESSURE

PRESSURE		TEMPERATURE			FLOW RATE						NET DIFFERENTIAL PRESSURE		
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	CFM	SCFM	GN ₂ KG/HR	GN ₂ LBS/HR	DIFFERENTIAL	PSID		
49.484	703.7	297.2	24.0	75.2	83.3	0.610	2.891	5.992	12.550	8.7326	124.206		
49.484	703.7	296.9	23.9	74.8	75.2	0.550	2.610	5.138	11.329	7.6438	108.720		
49.484	703.7	296.9	23.7	74.7	65.9	0.485	2.301	4.534	9.987	6.4916	92.332		
49.484	703.7	296.9	23.7	74.7	56.9	0.421	1.997	3.931	8.667	5.4631	77.704		
49.212	700.4	297.0	23.0	74.8	48.2	0.359	1.694	3.333	7.356	4.4760	63.964		
49.212	700.4	297.1	23.9	75.1	39.1	0.295	1.390	2.733	6.034	3.5779	50.890		
49.484	703.7	297.3	24.1	75.5	29.5	0.221	1.046	2.052	4.540	2.6677	37.244		
49.484	703.7	297.5	24.3	75.7	25.0	0.189	0.893	1.758	3.876	2.2499	32.001		
49.484	703.7	297.7	24.5	76.1	20.2	0.152	0.719	1.418	3.121	1.7858	25.401		
49.484	703.7	297.9	24.8	76.6	12.5	0.096	0.455	0.892	1.975	1.1352	16.147		
49.484	703.7	298.5	25.3	77.6	12.7	0.098	0.460	0.902	1.998	1.1517	16.381		
49.484	703.7	298.6	25.4	77.7	20.6	0.157	0.739	1.458	3.209	1.8949	26.251		
49.484	703.7	298.6	25.4	77.8	24.6	0.186	0.879	1.731	3.817	2.2812	32.446		
49.484	703.7	298.5	25.4	77.7	29.9	0.225	1.061	2.082	4.606	2.8022	39.857		
49.484	703.7	298.5	25.3	77.5	38.8	0.291	1.376	2.702	5.972	3.6664	52.148		
49.484	703.7	298.3	25.2	77.3	47.3	0.353	1.669	3.283	7.246	4.5601	64.859		
49.484	703.7	298.2	25.1	77.1	56.5	0.418	1.977	3.894	8.580	5.5357	78.736		
49.484	703.7	298.1	24.9	76.8	65.6	0.484	2.287	4.503	9.928	6.5676	93.413		
49.212	700.4	297.9	24.7	76.5	73.8	0.546	2.567	5.057	11.144	7.5327	107.140		
49.212	700.4	297.7	24.6	76.2	82.8	0.610	2.872	5.657	12.467	8.7103	123.990		
49.433	703.4	297.8	24.6	76.3									
0.088	1.2	.5	.5	1.0	DEVIATIONS								

ORIGINAL PAGE IS
OF POOR QUALITY

PAGE: 1
DATE: 7-26-76

TABLE 66
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 6 PART 20 TEST DESCRIPTION

CLEAN CONDITION -- IMPACT/FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. AFTER 80 HIGH PRESSURE
(10,000 PSIA) GN₂ IMPACTS. TEST SPECIMEN
(S/N 024) INLET PRESSURE = 1000 PSIA NOMINAL.

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE			FLOWMETER TWO			TEST SPECIMEN INLET CONDITIONS		
FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.84	42.5	68.7	.91	47.5	73.8	1007.9	71.2	.0419
.75	39.4	68.7	.81	48.8	73.7	1007.9	71.2	.0384
.67	36.1	69.3	.71	49.0	74.0	1007.9	71.6	.0337
.59	32.6	69.7	.61	49.8	74.3	1007.9	72.0	.0298
.49	29.2	71.6	.51	49.6	74.8	1007.9	72.7	.0248
.40	26.1	71.2	.41	49.6	75.2	1007.9	73.2	.0200
.31	23.4	71.8	.31	50.0	75.5	1007.9	73.7	.0155
.26	20.2	72.6	.26	50.0	76.1	1007.9	74.3	.0131
.22	17.9	73.4	.21	49.8	76.4	1007.9	74.9	.0105
.15	14.2	74.3	.14	50.2	76.9	1007.9	75.6	.0072
.15	14.2	75.7	.14	50.2	77.6	1007.9	76.6	.0072
.22	17.5	75.5	.22	49.2	77.7	1007.9	76.6	.0109
.27	19.5	75.3	.27	49.2	77.7	1007.9	76.5	.0130
.32	19.5	74.8	.31	49.2	77.7	1007.9	76.3	.0154
.41	19.7	74.1	.41	49.2	77.5	1007.9	75.8	.0202
.50	20.1	73.2	.51	49.4	77.2	1007.9	75.2	.0249
.58	19.4	72.1	.61	48.8	76.6	1007.9	74.4	.0291
.67	17.9	71.2	.71	48.5	76.0	1007.9	73.7	.0337
.76	17.5	71.6	.81	47.9	75.5	1004.0	73.0	.0381
.85	17.9	69.7	.92	47.9	74.7	1004.0	72.2	.0429

TABLE 66
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN CONDITION - IMPACT/FLOW RATE VERSUS
DIFFERENTIAL PRESSURE, AFTER 80 HIGH PRESSURE
(1,000 PSIA) GN₂ IMPACTS, TEST SPECIMEN
(S/N 024) INLET PRESSURE = 1000 PSIA NOMINAL.

TEST NUMBER 6 PART 20 TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
1007.2	1.2	.0419	86.653	87.334	86.994	-0.000	86.994
1007.2	1.2	.0384	77.758	78.485	78.121	-0.000	78.122
1007.2	1.6	.0337	66.533	67.117	66.820	-0.000	66.820
1007.2	2.1	.0298	57.139	57.942	57.540	-0.000	57.541
1007.2	2.7	.0248	47.428	48.880	47.154	-0.000	47.154
1007.2	3.2	.0200	37.217	37.988	37.097	-0.000	37.098
1007.2	3.7	.0155	28.389	28.019	28.204	-0.000	28.205
1007.2	4.3	.0131	23.786	23.431	23.608	-0.000	23.609
1007.2	4.9	.0105	18.928	18.677	18.802	-0.000	18.803
1007.2	5.6	.0072	12.941	12.730	12.835	-0.000	12.835
1007.2	6.6	.0072	12.879	12.815	12.862	-0.000	12.862
1007.2	6.6	.0119	19.925	19.879	19.902	-0.000	19.902
1007.2	6.5	.0130	24.161	24.118	24.139	-0.000	24.139
1007.2	6.3	.0154	28.949	28.918	28.943	-0.000	28.944
1007.2	5.8	.022	38.385	38.254	38.320	-0.000	38.320
1007.2	5.2	.0249	48.665	48.144	48.405	-0.000	48.405
1007.2	4.4	.0291	56.888	57.626	57.257	-0.000	57.257
1007.2	3.7	.0337	67.283	67.739	67.511	-0.000	67.511
1004.0	13.1	.0381	76.888	77.437	77.212	-0.000	77.213
1004.0	12.2	.0429	88.737	89.546	89.141	-0.000	89.142

TARE DIFF. PRESS = -1.24000E-04 + -1.24930E-02 (ACFM) + 2.48070E-01 (ACFM)**2 + 0 (ACFM)**3

TABLE 66
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN CONDITION - IMPACT/FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. AFTER 80 HIGH PRESSURE
(10,000 PSIA) GN₂ IMPACTS. TEST SPECIMEN
(S/N 024) INLET PRESSURE = 1000 PSIA NOMINAL.

TEST NUMBER 6 PART 06 TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS										NET DIFFERENTIAL PRESSURE			
*****										*****			
PRESSURE		TEMPERATURE			FLOW RATE					DIFFERENTIAL			
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	CFM	SCFM	GN ₂ KG/HR	GN ₂ LBS/HR	KG/SQ-CM	PSID		
70.865	1007.2	295.1	21.8	71.2	82.8	.419	2.866	5.642	12.441	6.1163	86.994		
70.865	1007.2	294.9	21.8	71.2	75.9	.384	2.630	5.172	11.416	5.4925	78.122		
70.865	1007.2	295.2	22.1	71.6	66.4	.337	2.306	4.540	10.009	4.6979	66.820		
70.865	1007.2	295.4	22.2	72.0	58.4	.298	2.035	4.000	8.834	4.0455	57.341		
70.865	1007.2	295.8	22.0	72.7	48.1	.248	1.691	3.330	7.341	3.3153	47.154		
70.865	1007.2	296.0	22.9	73.2	38.6	.200	1.363	2.682	5.918	2.6082	37.098		
70.865	1007.2	296.3	23.2	73.7	29.8	.155	1.053	2.072	4.571	1.9830	28.205		
70.865	1007.2	296.7	23.5	74.3	25.0	.131	.890	1.752	3.862	1.6599	23.609		
70.865	1007.2	297.6	23.8	74.9	20.0	.105	.716	1.402	3.107	1.3220	18.803		
70.865	1007.2	297.4	24.2	75.6	13.4	.072	.487	.952	2.113	.9025	12.836		
70.865	1007.2	298.1	24.8	76.6	13.4	.072	.486	.952	2.109	.9043	12.862		
70.865	1007.2	298.0	24.8	76.6	20.6	.109	.735	1.441	3.190	1.3993	19.202		
70.865	1007.2	297.9	24.7	76.5	24.8	.130	.884	1.740	3.836	1.6972	24.139		
70.865	1007.2	297.8	24.6	76.3	29.5	.154	1.047	2.061	4.545	2.0349	28.244		
70.865	1007.2	297.5	24.3	75.8	38.7	.202	1.369	2.692	5.943	2.6942	38.320		
70.865	1007.2	297.2	24.0	75.2	48.2	.249	1.691	3.330	7.341	3.4032	48.405		
70.865	1007.2	296.7	23.5	74.4	56.7	.291	1.980	3.892	8.594	4.0256	57.287		
70.865	1007.2	296.3	23.1	73.7	65.9	.337	2.295	4.512	9.962	4.7465	67.511		
70.586	1004.0	295.9	22.8	73.0	74.6	.381	2.588	5.092	11.234	5.4286	77.213		
70.586	1004.0	295.5	22.3	72.2	84.2	.429	2.915	5.732	12.652	6.2673	89.142		
70.837	1007.2	296.5	23.4	74.0									
.050	.1	.9	.9	1.6	DEVIATIONS								

TABLE 67
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

FLOW RATE VERSUS DIFFERENTIAL PRESSURE CHARACTERISTICS OF TEST SPECIMEN S/N 027 AT THE COMPLETION OF TEST 10 AND AFTER THE APPLICATION OF 10 HIGH PRESSURE (10,000 PSIA NOMINAL) GN₂ IMPACT CYCLES TO THE REVERSE SIDE (UP OF SPECIMEN S/N SIDE DOWNSTREAM) OF THE SPECIMEN. DATA ACQUIRED IN THE FORWARD FLOW DIRECTION AT A TEST SPECIMEN INLET PRESSURE = 415 PSIA (NOMINAL).

TEST NUMBER 10 PART 27N

TEST DESCRIPTION

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE			FLOWMETER TWO			TEST SPECIMEN INLET CONDITIONS		
FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.49	50.4	76.7	.49	49.5	76.4	416.2	75.6	.0590
.41	50.4	76.6	.41	49.7	76.4	416.2	75.6	.0491
.30	50.2	76.6	.31	49.9	76.5	416.2	75.7	.0363
.26	50.1	76.2	.25	49.7	76.7	416.2	75.9	.0307
.21	50.4	76.2	.20	50.1	76.7	416.2	75.9	.0250
.14	50.2	76.6	.13	49.9	76.9	416.2	76.2	.0165
.14	50.4	76.2	.13	51.1	77.3	416.2	76.7	.0165
.22	50.1	76.1	.21	49.7	77.1	416.2	76.7	.0259
.26	49.1	76.1	.26	48.6	77.2	415.6	76.6	.0302
.31	50.1	76.0	.31	49.5	77.3	414.9	76.7	.0369
.36	49.9	76.9	.36	49.2	77.3	414.9	76.6	.0425
.40	49.9	76.9	.40	49.2	77.2	414.3	76.5	.0483
.45	49.7	76.9	.45	49.1	77.2	413.7	76.5	.0540
.50	50.1	76.9	.50	49.2	77.2	413.7	76.5	.0600

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 67
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

FLOW RATE VERSUS DIFFERENTIAL PRESSURE CHARACTERISTICS OF TEST SPECIMEN S/N 027 AT THE COMPLETION OF TEST 10 AND AFTER THE APPLICATION OF 10 HIGH PRESSURE (10,000 PSIA NOMINAL) - GN2 IMPACT CYCLES TO THE REVERSE SIDE (HPOF SPECIMEN S/N SIDE DOWNSTREAM) OF THE SPECIMEN. DATA ACQUIRED IN THE FORWARD FLOW DIRECTION AT A TEST SPECIMEN INLET PRESSURE = 415 PSIA (NOMINAL).

TEST NUMBER 10

PART 27N

TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (°F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
416.2	75.6	.0590	250.417	250.417	250.417	.000	250.416
416.2	75.6	.0491	177.817	177.817	177.817	.000	177.817
416.2	75.7	.1363	114.371	114.371	114.371	.000	114.371
416.2	75.9	.0307	92.568	92.591	92.579	.000	92.579
416.2	75.9	.0250	71.224	71.442	71.333	.000	71.333
416.2	76.2	.0165	43.899	43.901	43.940	0.000	43.940
416.2	76.7	.0165	43.957	43.901	43.969	0.000	43.968
416.2	76.7	.0259	74.972	75.230	75.101	.000	75.101
415.6	76.6	.0312	91.820	91.910	91.890	.000	91.889
414.9	76.7	.0369	118.149	118.119	118.159	.000	118.158
414.9	76.6	.0425	144.989	144.909	144.989	.000	144.989
414.3	76.5	.0483	174.029	174.029	174.029	.000	174.029
413.7	76.5	.0540	212.854	212.854	212.854	.000	212.854
413.7	76.5	.0610	269.356	269.316	269.356	.000	269.356

TARE DIFF. PRESS = $-3.40000E-05 + .44400E-04$ (ACFM) + $1.50933E-01$ (ACFM)**2 + $0.$ (ACFM)**3.

TABLE 67
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

FLOW RATE VERSUS DIFFERENTIAL PRESSURE CHARACTERISTICS OF TEST SPECIMEN S/N 027 AT THE COMPLETION OF TEST 10 AND AFTER THE APPLICATION OF 10 HIGH PRESSURE (10,000 PSIA NOMINAL) GN₂ IMPACT CYCLES TO THE REVERSE SIDE (HPOF SPECIMEN S/N SIDE DOWNSTREAM) OF THE SPECIMEN. DATA ACQUIRED IN THE FORWARD FLOW DIRECTION AT A TEST SPECIMEN INLET PRESSURE OF 415 PSIA (NOMINAL).

TEST NUMBER 14 PART 27N TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESSURE

PRESSURE		TEMPERATURE			FLOW RATE							NET DIFFERENTIAL PRESSURE	
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID		
29.265	416.2	297.4	24.2	75.6	46.8	.059	1.653	3.254	7.174	17.6060	250.416		
29.265	416.2	297.4	24.2	75.6	39.0	.0491	1.376	2.710	5.974	12.5018	177.817		
29.265	416.2	297.5	24.3	75.7	28.8	.0353	1.016	2.000	4.408	8.0411	114.371		
29.265	416.2	297.5	24.4	75.9	24.4	.0307	.861	1.999	3.737	6.5089	92.579		
29.265	416.2	297.6	24.4	75.9	19.8	.0250	.701	1.380	3.043	5.0152	71.333		
29.265	416.2	297.7	24.6	76.2	13.1	.0165	.462	.910	2.006	3.0893	43.940		
29.265	416.2	298.0	24.6	76.7	13.0	.0165	.460	.907	1.999	3.0913	43.966		
29.265	416.2	298.1	24.6	76.7	20.5	.0259	.723	1.424	3.140	5.2801	75.101		
29.219	415.0	297.9	24.8	76.6	23.9	.0302	.844	1.663	3.666	6.4605	91.889		
29.174	414.9	298.0	24.8	76.7	29.1	.0369	1.028	2.024	4.462	8.3074	118.158		
29.174	414.9	297.9	24.8	76.6	33.6	.0425	1.186	2.334	5.146	10.1937	144.989		
29.128	414.2	297.9	24.7	76.5	38.1	.0483	1.344	2.646	5.834	12.2354	174.029		
29.083	413.7	297.9	24.7	76.5	42.5	.0540	1.500	2.954	6.512	14.9651	212.854		
29.083	413.7	297.9	24.7	76.5	47.3	.0600	1.669	3.285	7.244	18.9376	269.356		
29.213	415.2	297.8	24.6	76.3									
0.060	.9	.2	.2	.4	DEVIATIONS								

TABLE 68
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

FLOW RATE VERSUS DIFFERENTIAL PRESSURE CHARACTERISTICS OF TEST SPECIMEN S/N 027 AT THE COMPLETION OF TEST 10 AND AFTER THE APPLICATION OF 10 HIGH PRESSURE (10,000 PSIA NOMINAL) GN₂ IMPACT CYCLES TO THE REVERSE SIDE (HPOF SPECIMEN S/N SIDE DOWNSTREAM) OF THE SPECIMEN. DATA ACQUIRED IN THE FORWARD FLOW DIRECTION AT A TEST SPECIMEN INLET PRESSURE = 1000 PSIA (NOMINAL).

TEST NUMBER 10 PART 27M

TEST DESCRIPTION

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.85	50.4	62.4	.91	48.4	73.1	117.2	70.7	.0427
.76	49.5	67.5	.81	48.2	72.2	117.2	69.7	.0377
.67	50.1	66.2	.73	48.6	71.6	117.2	68.9	.0332
.58	50.1	65.9	.61	48.8	71.3	117.2	68.6	.0288
.49	50.2	65.8	.50	49.2	71.2	117.2	68.5	.0243
.40	50.4	64.1	.40	49.9	71.2	117.2	68.6	.0196
.30	49.9	66.4	.30	49.3	71.5	117.2	69.0	.0148
.26	50.4	65.4	.25	49.9	71.8	117.2	69.3	.0126
.21	50.2	67.2	.20	49.9	72.1	117.2	69.6	.0102
.14	47.4	60.1	.14	49.5	72.4	117.2	70.2	.0068
.14	50.0	61.2	.13	51.3	72.8	117.2	71.0	.0069
.21	50.1	64.2	.20	49.7	73.1	117.2	71.1	.0102
.26	50.4	64.1	.25	50.1	72.8	117.2	70.9	.0125
.31	50.4	64.7	.31	49.9	72.7	117.2	70.7	.0152
.41	50.2	62.1	.41	49.5	72.3	117.2	70.2	.0200
.49	50.2	67.2	.50	49.3	71.8	117.2	69.5	.0243
.58	50.2	66.1	.60	49.1	71.3	117.2	68.7	.0289
.67	50.2	65.3	.70	48.8	71.7	113.2	68.0	.0335
.75	50.1	64.4	.81	48.4	69.1	113.2	67.1	.0379
.84	49.9	63.9	.91	47.6	58.7	113.2	66.3	.0419

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 68
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

FLOW RATE VERSUS DIFFERENTIAL PRESSURE CHARACTERISTICS OF TEST SPECIMEN S/N 027 AT THE COMPLETION OF TEST 10 AND AFTER THE APPLICATION OF 10 HIGH PRESSURE (10,000 PSIA NOMINAL) GN₂ IMPACT CYCLES TO THE REVERSE SIDE (HPOF SPECIMEN S/N SIDE DOWNSTREAM) OF THE SPECIMEN. DATA ACQUIRED IN THE FORWARD FLOW DIRECTION AT A TEST SPECIMEN INLET PRESSURE = 1000 PSIA (NOMINAL).

TEST NUMBER 1 PART 271 TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

TEST SPECIMEN INLET PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
1017.2	66.7	0.427	148.251	148.251	148.251	-0.000	148.251
1017.2	69.7	0.377	127.734	127.734	127.734	-0.000	127.734
1017.2	68.9	0.332	108.795	108.795	108.795	-0.000	108.795
1017.2	66.6	0.285	90.99	91.434	91.212	-0.000	91.212
1017.2	66.5	0.243	73.641	74.073	73.857	-0.000	73.857
1017.2	68.6	0.196	57.134	57.559	57.396	-0.000	57.397
1017.2	69.6	0.148	41.871	41.876	41.874	-0.000	41.874
1017.2	69.3	0.126	34.745	34.846	34.795	-0.000	34.796
1017.2	69.6	0.162	27.329	27.375	27.352	-0.000	27.352
1017.2	70.2	0.088	17.537	17.517	17.527	-0.000	17.527
1017.2	71.0	0.069	17.826	17.975	17.900	-0.000	17.901
1017.2	71.1	0.082	27.212	27.375	27.294	-0.000	27.294
1017.2	70.9	0.125	34.745	34.961	34.853	-0.000	34.853
1017.2	70.7	0.132	43.262	43.139	43.200	-0.000	43.201
1017.2	70.2	0.200	58.886	59.237	59.062	-0.000	59.062
1017.2	69.5	0.243	74.140	74.329	74.265	-0.000	74.265
1017.2	68.7	0.289	92.065	92.065	92.065	-0.000	92.065
1013.2	68.0	0.335	109.425	109.426	109.425	-0.000	109.425
1013.2	67.1	0.379	128.996	128.996	128.996	-0.000	128.997
1013.2	66.3	0.419	148.567	148.567	148.567	-0.000	148.567

TARE DIFF. PRESS = -1.64000E-04 + -1.26933E-02 (ACFM) + 2.48070E-01 (ACFM)**2 + 0 (ACFM)**3

TABLE 68
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

FLOW RATE VERSUS DIFFERENTIAL PRESSURE CHARACTERISTICS OF TEST SPECIMEN S/N 027 AT THE COMPLETION OF TEST 10 AND AFTER THE APPLICATION OF 10 HIGH PRESSURE (10,000 PSIA NOMINAL) GN2 IMPACT CYCLES TO THE REVERSE SIDE (HPOF SPECIMEN S/N SIDE DOWNSTREAM) OF THE SPECIMEN. DATA ACQUIRED IN THE FORWARD FLOW DIRECTION AT A TEST SPECIMEN INLET PRESSURE = 1000 PSIA (NOMINAL).

TEST NUMBER 10 PART 27A

TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS										NET DIFFERENTIAL PRESS	
*****										*****	
PRESSURE		TEMPERATURE			FLOW RATE						
*****										*****	
KG/SQ CM	PSIA	LEG. K	DEG. C	DEG. F	LITERS/ MIN	CFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID
71.514	1017.2	294.6	21.5	70.7	43.6	.427	2.953	5.415	12.821	10.4231	148.251
71.514	1017.2	294.1	20.9	69.7	77.9	.377	2.609	5.135	11.328	8.9806	127.734
71.514	1017.2	293.7	20.5	68.9	65.1	.332	2.301	4.530	9.988	7.6490	108.795
71.514	1017.2	293.5	20.3	68.6	56.0	.294	1.999	3.931	8.679	6.4128	91.212
71.514	1017.2	293.4	20.3	68.5	47.7	.243	1.663	3.314	7.306	5.1927	73.857
71.514	1017.2	293.5	20.3	68.6	34.0	.195	1.362	2.082	5.914	4.0354	57.397
71.514	1017.2	293.7	20.5	69.1	24.1	.148	1.027	2.025	4.460	2.9440	41.874
71.514	1017.2	293.9	20.7	69.3	24.7	.126	.874	1.720	3.793	2.4464	34.796
71.514	1017.2	294.0	20.9	69.6	20.0	.107	.707	1.392	3.068	1.9230	27.352
71.514	1017.2	294.4	21.2	70.2	13.4	.064	.472	.930	2.051	1.2323	17.527
71.514	1017.2	294.8	21.7	71.0	13.5	.069	.476	.931	2.066	1.2585	17.901
71.514	1017.2	294.9	21.7	71.1	19.9	.102	.702	1.382	3.048	1.9189	27.294
71.514	1017.2	294.8	21.6	70.9	24.5	.124	.867	1.701	3.763	2.4504	34.853
71.514	1017.2	294.7	21.5	70.7	24.3	.152	1.053	2.074	4.572	3.0373	43.201
71.514	1017.2	294.4	21.2	70.2	39.2	.320	1.385	2.720	6.013	4.1525	59.062
71.514	1017.2	294.0	20.8	69.5	47.6	.423	1.680	3.300	7.293	5.2213	74.265
71.514	1017.2	293.5	20.4	68.7	50.7	.429	2.003	3.940	8.697	6.4728	92.065
71.235	1013.2	293.2	20.1	68.1	65.7	.335	2.319	4.561	10.068	7.6934	109.426
71.235	1013.2	292.7	19.5	67.1	74.5	.379	2.629	5.170	11.415	9.0694	128.997
71.235	1013.2	292.2	19.1	66.3	82.4	.419	2.909	5.720	12.628	10.4453	148.567
*****	*****	*****	*****	*****							
71.472	1010.0	293.9	21.7	69.3							
.071	1.0	.0	.0	1.0	DEVIATIONS						

PAGE: 1
DATE: 10-7-76

TABLE-69
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

FLOW RATE VERSUS DIFFERENTIAL PRESSURE CHARACTERISTICS OF
TEST SPECIMEN S/N 027 AT THE COMPLETION OF TEST 10 AND AFTER
THE APPLICATION OF 10 HIGH PRESSURE (10,000 PSIA NOMINAL)
GN₂ IMPACT CYCLES TO THE REVERSE SIDE (HPOF SPECIMEN S/N
SIDE DOWNSTREAM) OF THE SPECIMEN. DATA ACQUIRED IN THE
REVERSE FLOW DIRECTION AT A TEST SPECIMEN, INLET PRESSURE
415 PSIA (NOMINAL).

TEST NUMBER 10

PART 27LR

TEST DESCRIPTION

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	AVG PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.49	51.2	79.5	.50	49.3	80.9	414.3	80.2	.0597
.40	50.2	79.7	.40	49.3	81.4	414.3	80.4	.0478
.31	50.4	80.0	.31	49.9	81.2	414.3	80.6	.0372
.26	50.4	80.2	.25	49.9	81.4	413.7	80.8	.0311
.21	50.8	80.4	.20	50.3	81.5	413.7	81.0	.0252
.13	50.6	80.7	.13	50.1	81.8	413.7	81.2	.0160
.13	50.8	81.1	.13	50.3	82.2	413.7	81.6	.0159
.22	49.9	81.1	.21	49.3	82.2	413.7	81.7	.0257
.26	50.2	81.1	.25	49.7	82.2	413.7	81.6	.0308
.31	50.2	81.1	.31	49.7	82.2	413.7	81.7	.0373
.40	50.1	81.2	.40	49.2	82.3	413.7	81.8	.0480
.46	49.9	81.4	.46	49.0	82.3	413.7	81.9	.0547

Moore Business Forms, Inc.

ORIGINAL PAGE IS
OF POOR QUALITY

PAGE: 2
DATE: 10-7-76

TABLE 69
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

FLOW RATE VERSUS DIFFERENTIAL PRESSURE CHARACTERISTICS OF TEST SPECIMEN S/N 027 AT THE COMPLETION OF TEST 10 AND AFTER THE APPLICATION OF 10 HIGH PRESSURE (10,000 PSIA NOMINAL) GN₂ IMPACT CYCLES TO THE REVERSE SIDE (HPOF SPECIMEN S/N SIDE DOWNSTREAM) OF THE SPECIMEN. DATA ACQUIRED IN THE REVERSE FLOW DIRECTION AT A TEST SPECIMEN INLET PRESSURE = 415 PSIA (NOMINAL).

TEST NUMBER 10 PART 27LR TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
414.3	80.2	.0597	297.133	297.133	297.133	.000	297.133
414.3	80.4	.0478	188.234	188.234	188.234	.000	188.233
414.3	80.6	.0372	127.628	127.628	127.628	.000	127.628
413.7	80.8	.0311	100.167	100.167	100.167	.000	100.166
413.7	81.0	.0252	76.221	76.177	76.199	.000	76.199
413.7	81.2	.0160	44.768	44.612	44.690	-0.000	44.690
413.7	81.6	.0159	44.710	44.612	44.661	-0.000	44.661
413.7	81.7	.0257	78.344	78.387	78.365	.000	78.365
413.7	81.6	.0304	99.220	99.228	99.220	.000	99.219
413.7	81.7	.0373	129.522	129.522	129.522	.000	129.522
413.7	81.8	.0480	189.496	189.496	189.496	.000	189.496
413.7	81.9	.0547	241.894	241.894	241.894	.000	241.894

INLET DIFF. PRESS = -3.49000E-05 + -4.44000E-04 (ACFM) + 1.50933E-01 (ACFM)**2 + 0 (ACFM)**3

TABLE 69 FLOW RATE VERSUS DIFFERENTIAL PRESSURE CHARACTERISTICS OF TEST SPECIMEN S/N 027 AT THE COMPLETION OF TEST 10 AND AFTER THE APPLICATION OF 10 HIGH PRESSURE (10,000 PSIA NOMINAL) GN2 IMPACT CYCLES TO THE REVERSE SIDE (HPOF SPECIMEN S/N SIDE DOWNSTREAM) OF THE SPECIMEN. DATA ACQUIRED IN THE REVERSE FLOW DIRECTION AT A TEST SPECIMEN INLET PRESSURE = 415 PSIA (NOMINAL).

TEST NUMBER 10 PART 27LK TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESS

PRESSURE		TEMPERATURE			FLOW RATE						
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID
29.128	414.3	299.9	26.8	80.2	46.7	0.597	1.650	3.248	7.161	20.8905	297.133
29.128	414.3	300.0	26.9	80.4	37.4	0.478	1.322	2.604	5.740	13.2341	188.233
29.128	414.3	300.1	27.0	80.6	29.1	0.372	1.028	2.025	4.463	8.9731	127.628
29.083	413.1	300.3	27.1	80.8	24.3	0.311	0.858	1.689	3.724	7.0424	100.166
29.083	413.1	300.4	27.2	81.0	19.7	0.252	0.696	1.370	3.019	5.3573	76.199
29.083	413.1	300.5	27.4	81.2	12.5	0.160	0.440	0.867	1.911	3.1420	44.690
29.083	413.1	300.7	27.6	81.6	12.4	0.159	0.439	0.864	1.904	3.1400	44.661
29.083	413.1	300.8	27.6	81.7	20.0	0.257	0.707	1.392	3.068	5.5095	78.365
29.083	413.1	300.7	27.6	81.6	24.0	0.308	0.848	1.669	3.680	6.9758	99.219
29.083	413.1	300.8	27.6	81.7	29.1	0.373	1.028	2.024	4.462	9.1063	129.522
29.083	413.1	300.8	27.6	81.8	37.4	0.480	1.322	2.604	5.740	13.3229	189.496
29.083	413.1	300.9	27.7	81.9	42.6	0.547	1.505	2.969	6.534	17.0088	241.894
29.094	413.0	300.5	27.3	81.2							
0.017	0.2	0.3	0.3	0.5	DEVIATIONS						

ORIGINAL PAGE IS
OF POOR QUALITY

PAGE: 1
DATE: 10-7-76

TABLE 70
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

FLOW RATE VERSUS DIFFERENTIAL PRESSURE CHARACTERISTICS OF
TEST SPECIMEN S/N 027 AT THE COMPLETION OF TEST 10 AND AFTER
THE APPLICATION OF 10 HIGH PRESSURE (10,000 PSIA NOMINAL)
GN2 IMPACT CYCLES TO THE REVERSE SIDE (HPOF SPECIMEN S/N
SIDE DOWNSTREAM) OF THE SPECIMEN. DATA ACQUIRED IN THE
REVERSE FLOW DIRECTION AT A TEST SPECIMEN INLET PRESSURE =
1000 PSIA (NOMINAL).

TEST NUMBER 1 PART 27KR

TEST DESCRIPTION REVERSE FLOW DIRECTION AT A TEST SPECIMEN INLET PRESSURE =
1000 PSIA (NOMINAL).

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER UNIT

FLOWMETER TAG

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (CFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.78	50.4	77.5	.01	48.5	78.7	1 09.2	78.6	.0388
.69	50.1	75.9	.70	48.7	78.2	1 09.2	78.0	.0341
.60	50.4	74.6	.60	49.1	79.9	1 09.2	77.8	.0296
.51	50.2	75.5	.51	49.3	79.9	1 09.2	77.7	.0250
.41	50.1	75.7	.41	49.3	79.9	1 05.3	77.9	.0200
.31	50.4	75.3	.30	49.1	78.1	1 05.3	78.3	.0153
.27	50.8	76.6	.25	50.4	78.2	1 05.3	78.4	.0131
.21	50.2	75.9	.20	50.1	78.3	1 05.3	78.6	.0104
.14	50.4	77.4	.13	50.2	78.6	1 05.3	79.0	.0070
.14	50.4	77.0	.13	50.2	78.8	1 05.3	79.4	.0070
.22	50.6	77.9	.21	50.2	78.8	1 05.3	79.3	.0107
.26	50.4	77.7	.25	50.1	78.7	1 05.3	79.2	.0128
.32	49.9	77.3	.31	49.5	78.6	1 05.3	79.0	.0154
.41	50.4	78.0	.41	49.9	78.4	1 05.3	78.6	.0204
.51	50.4	78.1	.51	49.5	78.1	1 05.3	78.1	.0251
.59	50.4	78.2	.60	49.5	79.4	1 05.3	77.3	.0295
.68	50.4	78.1	.70	48.9	78.6	1 01.3	76.4	.0342
.75	50.4	77.5	.71	48.5	78.1	1 01.3	75.7	.0384
.84	50.4	77.5	.91	48.5	77.3	1 01.3	74.9	.0432

TABLE 70
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

FLOW RATE VERSUS DIFFERENTIAL PRESSURE CHARACTERISTICS OF TEST SPECIMEN S/N 027 AT THE COMPLETION OF TEST 10 AND AFTER THE APPLICATION OF 10 HIGH PRESSURE (10,000 PSIA NOMINAL) CH_2 IMPACT CYCLES TO THE REVERSE SIDE (HPOF SPECIMEN S/N SIDE DOWNSTREAM) OF THE SPECIMEN. DATA ACQUIRED IN THE REVERSE FLOW DIRECTION AT A TEST SPECIMEN INLET PRESSURE = 1000 PSIA (NOMINAL).

TEST 004 EN 10

PART 2768

TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

TEST SPECIMEN INLET PRESSURE (PSIA)	AVG TEMP (DEG. F)	VS FLOW RATE (CFM)	GR SS DIFF. PRESS PRIMARY (PSID)	GR SS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
1009.2	16.6	.388	138.070	136.476	138.670	-0.000	138.677
1009.2	16.0	.391	117.525	117.128	117.528	-0.000	117.528
1009.2	17.8	.275	98.273	96.173	98.273	-0.000	98.273
1009.2	17.7	.125	79.469	79.942	79.717	-0.000	79.717
1005.3	17.9	.027	60.340	61.126	60.686	-0.000	60.686
1005.3	16.3	.103	44.302	44.270	44.334	-0.000	44.340
1005.3	18.4	.131	37.182	37.118	37.125	-0.000	37.125
1005.3	16.0	.014	28.564	28.599	28.582	-0.000	28.582
1005.3	19.0	.007	18.251	18.250	18.265	-0.000	18.266
1005.3	19.4	.007	18.251	18.452	18.351	-0.000	18.352
1005.3	19.3	.017	29.370	29.518	29.447	-0.000	29.447
1005.3	19.2	.012	35.444	36.651	36.547	-0.000	36.547
1005.3	19.0	.015	44.113	44.920	44.916	-0.000	44.916
1005.3	18.0	.024	52.197	62.004	62.351	-0.000	62.351
1005.3	18.1	.251	80.216	80.912	80.565	-0.000	80.565
1005.3	17.3	.295	98.273	98.273	98.273	-0.000	98.273
1001.3	16.4	.1342	119.100	119.100	119.100	-0.000	119.106
1001.3	15.7	.1384	140.255	140.255	140.255	-0.000	140.255
1001.3	14.9	.1432	164.244	164.244	164.244	-0.000	164.244

TARE DIFF. PRESS = $-1.64000E-04 + -1.2693E-02 (ACFM) + 2.42070E-01 (ACFM)**2 + 0 (ACFM)**3$

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 70
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

FLOW RATE VERSUS DIFFERENTIAL PRESSURE CHARACTERISTICS OF
TEST SPECIMEN S/N 027 AT THE COMPLETION OF TEST 10 AND AFTER
THE APPLICATION OF 10 HIGH PRESSURE (10,000 PSIA NOMINAL)
GN₂ IMPACT CYCLES TO THE REVERSE SIDE (HPOF SPECIMEN S/N
SIDE DOWNSTREAM) OF THE SPECIMEN. DATA ACQUIRED IN THE
REVERSE FLOW DIRECTION AT A TEST SPECIMEN INLET PRESSURE =
1000 PSIA (NOMINAL).

TEST NUMBER		TEST SPECIMEN INLET CONDITIONS			FLOW RATE					NET DIFFERENTIAL PRESS	
PRESSURE		TEMPERATURE			FLOW RATE					DIFFERENTIAL	
KG/SQ CM	PSIA	DEG. C	DEG. F	LITERS/ MIN	CF	SCFM	GN ₂ KG/HR	GN ₂ LBS/HR	KG/SQ CM DIFFERENTIAL	PSID	
70.956	1007.4	299.1	78.6	74.2	.34	2.629	5.159	11.374	9.7499	138.677	
70.956	1007.4	299.7	78.5	66.3	.34	2.337	4.542	10.014	8.2630	117.528	
70.956	1007.4	298.5	78.4	57.7	.24	2.032	3.943	8.692	6.9093	98.273	
70.956	1007.4	298.9	78.4	47.9	.25	1.691	3.327	7.340	5.6047	79.717	
70.677	1005.5	298.7	78.3	38.2	.20	1.359	2.659	5.662	4.2667	60.686	
70.677	1005.5	298.9	78.3	29.1	.15	1.028	2.24	4.463	3.1174	44.340	
70.677	1005.5	298.9	78.4	24.9	.13	.891	1.732	3.423	2.6101	37.125	
70.677	1005.5	299.1	78.7	19.9	.11	.711	1.381	3.044	2.0095	28.582	
70.677	1005.5	299.3	78.1	13.2	.07	.468	.921	2.030	1.2842	18.266	
70.677	1005.5	299.5	78.3	13.2	.07	.467	.920	2.028	1.2902	18.352	
70.677	1005.5	299.5	78.3	11.3	.07	.716	1.413	3.107	2.0703	29.447	
70.677	1005.5	299.4	78.2	24.4	.12	.861	1.690	3.740	2.5695	36.547	
70.677	1005.5	299.2	78.1	24.3	.14	1.035	2.30	4.492	3.1579	44.916	
70.677	1005.5	299.1	78.5	39.4	.12	1.376	2.782	5.973	4.3837	62.351	
70.677	1005.5	298.8	78.1	47.9	.25	1.693	3.333	7.349	5.6643	80.565	
70.677	1005.5	298.3	77.3	56.4	.29	1.991	3.912	8.640	6.9093	98.273	
70.398	1001.5	297.9	78.4	65.2	.34	2.311	4.531	9.990	8.3740	119.106	
70.398	1001.5	297.4	78.5	73.3	.36	2.509	5.098	11.239	9.8609	140.255	
70.398	1001.5	297.1	78.4	81.5	.43	2.914	5.738	12.651	11.5475	164.244	
****	****	****	****	****	****	****	****	****	****	****	
70.691	1005.5	298.7	78.0								
.111	1.0	.5	.5	.9	DEVIATIONS						

TABLE 71
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

FLOW RATE VERSUS DIFFERENTIAL PRESSURE DATA IN THE FORWARD DIRECTION (S/N SIDE UPSTREAM). ACQUIRED ON TEST SPECIMEN S/N 028 AFTER COMPLETION OF NORMAL TEST 12 SEQUENCE TEST SPECIMEN INLET PRESSURE = 415 PSIA.

TEST NUMBER 12 PART 280 TEST DESCRIPTION

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.40	50.4	74.0	.40	49.9	75.4	414.3	75.7	.0485
.36	50.6	74.1	.35	49.9	76.5	414.3	75.8	.0431
.30	50.6	74.1	.30	49.1	76.5	413.7	75.8	.0368
.26	50.2	74.2	.25	49.9	76.7	413.7	75.9	.0308
.21	50.4	74.5	.20	49.0	76.7	413.7	76.1	.0248
.14	50.1	75.7	.13	49.9	76.9	413.7	76.3	.0168
.14	50.1	75.9	.13	49.7	77.1	413.7	76.5	.0167
.21	50.1	75.0	.21	49.7	77.0	413.0	76.5	.0254
.26	49.9	75.9	.25	49.3	77.1	413.0	76.5	.0305
.31	49.5	76.8	.31	49.3	77.1	413.0	76.4	.0368
.36	49.9	75.8	.36	49.2	77.1	412.4	76.4	.0428
.40	50.1	74.0	.40	49.3	77.2	411.7	76.5	.0485

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 71
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

FLOW RATE VERSUS DIFFERENTIAL PRESSURE DATA IN THE FORWARD DIRECTION (S/N SIDE UPSTREAM). ACQUIRED ON TEST SPECIMEN S/N 028 AFTER COMPLETION OF NORMAL TEST 12 SEQUENCE TEST SPECIMEN INLET PRESSURE = 415 PSIA.

TEST NUMBER 12	PORT 26J	TEST DESCRIPTION	TEST SPECIMEN INLET CONDITIONS *****				
AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	AVG GROSS DIFF. PRESS PRIMARY (PSID)	AVG GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)	
414.3	15.7	274.223	274.223	274.223	0.000	274.222	
414.3	15.8	185.731	185.731	185.731	0.000	185.729	
413.7	15.5	130.730	130.730	130.730	0.000	130.737	
413.7	15.9	96.289	96.289	96.289	0.000	96.288	
413.7	16.1	67.570	67.570	67.570	0.000	67.576	
413.7	16.3	39.287	39.287	39.287	0.000	39.287	
413.7	16.5	39.055	39.055	39.055	0.000	39.055	
413.0	16.5	70.783	70.783	70.783	0.000	70.783	
413.0	16.5	95.024	95.024	95.024	0.000	95.024	
413.0	16.4	132.950	132.950	132.950	0.000	132.950	
412.4	16.4	182.885	182.885	182.885	0.000	182.885	
411.7	16.5	279.595	279.595	279.595	0.000	279.595	

$$\text{GROSS DIFF. PRESS} = -3.46000E-05 + -4.44000E-04 (\text{ACFM}) + 1.56933E-01 (\text{ACFM})^{**2} + 0 (\text{ACFM})^{**3}$$

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 71
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

FLOW RATE VERSUS DIFFERENTIAL PRESSURE DATA IN THE FORWARD DIRECTION (S/N SIDE UPSTREAM). ACQUIRED ON TEST SPECIMEN S/N 028 AFTER COMPLETION OF NORMAL TEST 12 SEQUENCE TEST SPECIMEN INLET PRESSURE = 415 PSIA.

TEST NUMBER 12 PART 2811 TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS										NET DIFFERENTIAL PRESS	
PRESSURE		TEMPERATURE			FLOW RATE					DIFFERENTIAL	
KG/SQ CM	PSIA	CEC. K	DEG. C	DEG. F	LITERS/ MIN	CFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID
29.128	414.5	297.4	24.3	75.7	34.3	0.434	1.353	2.664	5.873	19.2798	274.222
29.128	414.5	297.5	24.3	75.8	34.1	0.431	1.273	2.368	5.221	13.0581	185.729
29.083	413.1	297.5	24.3	75.8	29.9	0.364	1.024	2.016	4.446	9.1918	130.737
29.083	413.1	297.6	24.4	75.9	24.3	0.301	0.858	1.690	3.726	6.7697	96.288
29.083	413.1	297.7	24.5	76.1	19.6	0.244	0.691	1.360	2.999	4.7510	67.576
29.083	413.1	297.8	24.6	76.3	13.2	0.164	0.467	0.919	2.026	2.7621	39.287
29.083	413.1	297.9	24.7	76.5	13.1	0.167	0.463	0.912	2.010	2.7459	39.055
29.037	413.0	297.9	24.7	76.5	23.0	0.254	0.796	1.391	3.066	4.9765	70.783
29.037	413.0	297.9	24.7	76.5	24.0	0.317	0.847	1.667	3.675	6.6809	95.024
29.037	413.0	297.7	24.7	76.4	23.9	0.354	1.022	2.011	4.434	9.3473	132.250
28.992	412.4	297.9	24.7	76.4	33.6	0.424	1.186	2.335	5.148	12.8581	182.885
28.946	411.7	297.9	24.7	76.5	38.9	0.485	1.341	2.040	5.820	19.6575	279.595
*****	*****	*****	*****	*****							
29.050	413.2	297.7	24.6	76.2							
0.042	0.0	0.2	0.2	0.3	DEVIATIONS						

ORIGINAL PAGE IS
OF POOR QUALITY

PAGE: 1
DATE: 10-7-76

TABLE 72
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

FLOW RATE VERSUS DIFFERENTIAL PRESSURE DATA IN THE FORWARD
DIRECTION (S/N SIDE UPSTREAM). DATA ACQUIRED ON TEST SPECIMEN
S/N 028 AFTER COMPLETION OF NORMAL TEST 12 SEQUENCE
TEST SPECIMEN INLET PRESSURE = 1000 PSIA.

TEST NUMBER 12 PART DAT TEST DESCRIPTION

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)
.87	50.3	67.3
.78	50.1	67.4
.69	50.5	67.1
.60	50.1	66.1
.51	50.5	66.4
.41	50.1	66.8
.32	49.9	67.3
.26	50.1	67.8
.21	50.3	67.4
.14	49.7	69.3
.14	49.9	71.8
.22	50.3	71.8
.26	50.5	71.9

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)
.91	48.1	72.7
.81	48.4	72.
.71	49.0	71.5
.50	48.8	71.7
.50	49.7	72.2
.40	49.3	72.3
.31	49.3	71.4
.25	49.7	71.9
.20	49.9	72.4
.13	49.5	72.8
.13	49.7	73.8
.21	49.9	73.8
.25	50.1	74.8

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
1005.3	70.5	.0435
1005.3	69.7	.0391
1005.3	69.3	.0346
1005.3	68.8	.0296
1005.3	69.5	.0251
1005.3	69.6	.0202
1005.3	69.3	.0154
1005.3	69.8	.0128
1005.3	70.4	.0104
1005.3	71.1	.0069
1005.3	72.3	.0069
1005.3	72.3	.0108
1005.3	72.4	.0129

TABLE 72
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

FLOW RATE VERSUS DIFFERENTIAL PRESSURE DATA IN THE FORWARD DIRECTION (S/N SIDE UPSTREAM). DATA ACQUIRED ON TEST SPECIMEN S/N 028 AFTER COMPLETION OF NORMAL TEST 12 SEQUENCE TEST SPECIMEN INLET PRESSURE = 1000 PSIA.

TEST NUMBER 12	PART 28T	TEST DESCRIPTION					
TEST SPECIMEN INLET CONDITIONS							

TEST SPECIMEN INLET PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
1005.3	70.5	.435	225.973	225.973	225.973	-0.000	225.973
1005.3	69.7	.3371	185.835	185.835	185.835	-0.000	185.835
1005.3	69.3	.3346	151.070	151.070	151.070	-0.000	151.070
1005.3	68.8	.2296	117.885	117.885	117.885	-0.000	117.885
1005.3	69.5	.2251	90.810	90.810	90.810	-0.000	90.810
1005.3	69.6	.0207	64.786	64.786	64.786	-0.000	64.787
1005.3	69.3	.0154	44.097	43.930	44.097	-0.000	44.097
1005.3	69.8	.0128	33.995	34.034	34.040	-0.000	34.040
1005.3	70.4	.0104	25.534	25.528	25.606	-0.000	25.606
1005.3	71.1	.0069	14.907	14.945	14.967	-0.000	14.907
1005.3	72.3	.0067	14.909	15.19	14.964	-0.000	14.964
1005.3	72.3	.0104	26.918	27.07	26.962	-0.000	26.963
1005.3	72.4	.0129	34.411	34.545	34.473	-0.000	34.473

$$\text{TARE DIFF. PRESS} = -1.04000E-04 + -1.26931E-02 (\text{ACFM}) + 2.48070E-01 (\text{ACFM})^{**2} + 0 (\text{ACFM})^{**3}$$

TABLE 72
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

FLOW RATE VERSUS DIFFERENTIAL PRESSURE DATA IN THE FORWARD DIRECTION (S/N SIDE UPSTREAM). DATA ACQUIRED ON TEST SPECIMEN S/N 028 AFTER COMPLETION OF NORMAL TEST 12 SEQUENCE TEST SPECIMEN INLET PRESSURE = 1000 PSIA.

TEST NUMBER 12 PART 2BT TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS										NET DIFFERENTIAL PRESS	
PRESSURE		TEMPERATURE				FLOW RATE				DIFFERENTIAL	
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	CFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM	PSIA
70.677	1005.3	294.5	21.4	79.5	84.1	.435	2.971	5.849	12.895	15.8875	225.273
70.677	1005.3	294.1	20.9	69.7	75.8	.391	2.676	5.269	11.615	13.0655	185.835
70.677	1005.3	293.9	20.7	69.3	67.0	.346	2.367	4.661	10.276	10.6213	151.070
70.677	1005.3	293.6	20.5	68.8	57.5	.296	2.031	3.998	8.815	8.2882	117.885
70.677	1005.3	294.0	20.8	69.5	48.6	.251	1.716	3.380	7.451	6.3846	90.810
70.677	1005.3	294.0	20.9	69.6	39.1	.202	1.379	2.716	5.987	4.5549	64.787
70.677	1005.3	293.9	20.7	69.3	29.8	.154	1.053	2.073	4.571	3.1003	44.097
70.677	1005.3	294.2	21.0	69.8	24.7	.128	.874	1.721	3.794	2.3932	34.040
70.677	1005.3	294.5	21.3	70.4	20.2	.114	.712	1.401	3.090	1.8003	25.905
70.677	1005.3	294.9	21.7	71.1	13.3	.069	.468	.921	2.032	1.0481	14.207
70.677	1005.3	295.0	22.4	72.3	13.3	.069	.469	.923	2.035	1.0521	14.264
70.677	1005.3	295.6	22.4	72.3	20.9	.108	.738	1.453	3.204	1.8957	26.983
70.677	1005.3	295.6	22.5	72.4	24.8	.129	.876	1.729	3.804	2.4237	34.473
70.677	1005.3	294.5	21.3	70.4							
0	0	0	0	0							

DEVIATIONS

TABLE 73
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

FLOW RATE VERSUS DIFFERENTIAL PRESSURE CHARACTERISTICS OF TEST SPECIMEN S/N 025 AFTER 100 HIGH PRESSURE (10,000 PSIA NOMINAL) GN₂ IMPACT CYCLES AND CONTAMINATED WITH 46 MG OF Fe₂O₃. FLOW DATA ACQUIRED AT AN INLET PRESSURE OF 1,000 PSIA NOMINAL AND IN THE FORWARD (S/N SIDE UPSTREAM) DIRECTION

TEST NUMBER 3 PART 252 TEST DESCRIPTION

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.27	50.6	79.7	.26	50.2	81.5	1009.2	80.6	.0132
.22	50.6	79.7	.21	50.2	81.6	1009.2	80.6	.0106
.16	50.8	79.0	.15	50.4	81.7	1009.2	80.8	.0079
.11	49.5	81.3	.10	49.3	81.8	1009.2	81.0	.0052
.11	49.5	80.6	.10	49.3	82.1	1009.2	81.4	.0052
.17	49.7	81.5	.16	49.5	82.2	1009.2	81.3	.0079
.21	49.7	81.3	.20	49.5	82.1	1009.2	81.2	.0101
.25	49.5	79.9	.24	49.3	82.0	1009.2	80.9	.0120

TABLE 73
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

FLOW RATE VERSUS DIFFERENTIAL PRESSURE CHARACTERISTICS OF TEST SPECIMEN S/N 025 AFTER 100 HIGH PRESSURE (10,000 PSIA NOMINAL) GN2 IMPACT CYCLES AND CONTAMINATED WITH 46 MG OF Fe2O3. FLOW DATA ACQUIRED AT AN INLET PRESSURE OF 1,000 PSIA NOMINAL AND IN THE FORWARD (S/N SIDE UPSTREAM) DIRECTION.

TEST NUMBER PART NOZ TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

TEST NUMBER	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
1009.0	73.0	0.132	264.510	264.510	264.510	-0.000	264.510
1009.2	70.4	0.146	196.967	196.967	196.967	-0.000	196.967
1009.4	71.8	0.0879	136.145	136.145	136.145	-0.000	136.145
1009.6	81.4	0.0132	83.179	83.332	83.178	-0.000	83.179
1009.8	71.4	0.0132	82.404	83.116	82.709	-0.000	82.709
1009.2	81.3	0.0079	136.145	136.145	136.145	-0.000	136.145
1009.2	81.2	0.0121	184.025	184.025	184.025	-0.000	184.025
1009.2	70.9	0.0121	232.951	232.951	232.951	-0.000	232.951

AVG DIFF. PRESS = $-1.64307E-04 + -1.26930E-02 (ACFM) + 2.48070E-01 (ACFM)**2 + U (ACFM)**3$

ORIGINAL PAGE IS
OF POOR QUALITY

PAGE: 3
DATE: 10-7-76

TABLE 73
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

FLOW RATE VERSUS DIFFERENTIAL PRESSURE CHARACTERISTICS OF
TEST SPECIMEN S/N 025 AFTER 100 HIGH PRESSURE (10,000 PSIA
NOMINAL) GN₂ IMPACT CYCLES AND CONTAMINATED WITH 46 MG OF
Fe₂O₃. FLOW DATA ACQUIRED AT AN INLET PRESSURE OF 1,000
PSIA NOMINAL AND IN THE FORWARD (S/N SIDE UPSTREAM) DIRECTION.

TEST NUMBER 8 PART 252 TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS										NET DIFFERENTIAL PRESS	
PRESSURE		TEMPERATURE			FLOW RATE					DIFFERENTIAL	
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	CFM	SCFM	GN ₂ KG/HR	GN ₂ LBS/HR	KG/SQ CM	PSID
70.956	1009.2	300.2	27.0	80.6	25.2	.132	.891	1.754	3.868	18.5973	264.516
70.956	1009.2	300.2	27.0	80.6	20.1	.110	.711	1.401	3.088	13.8431	196.967
70.956	1009.2	300.3	27.1	80.8	15.1	.079	.532	1.048	2.311	9.5650	136.046
70.956	1009.2	300.4	27.2	81.0	10.0	.052	.352	.693	1.527	5.8431	83.179
70.956	1009.2	300.5	27.4	81.4	9.9	.052	.349	.687	1.514	5.8150	82.709
70.956	1009.2	300.6	27.4	81.3	15.1	.079	.532	1.048	2.311	9.5650	136.046
70.956	1009.2	300.5	27.3	81.2	19.1	.101	.676	1.331	2.935	12.9333	184.025
70.956	1009.2	300.3	27.2	80.9	22.0	.120	.805	1.585	3.495	16.3781	232.951
70.956	1009.2	300.4	27.2	81.0							
0.	0.	.1	.1	.2	DEVIATIONS						

TABLE 74
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 1
DATE: 4/29/76

TEST NUMBER 5 PART A TEST DESCRIPTION

Clean Condition - Flow Rate versus
Differential Pressure (Test Specimen
[S/N 6] Inlet Pressure 415 psia (nominal))

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
0	42.2	87.5	.13	47.6	81.4	413.0	82.5	.0149
1	47.4	82.8	.21	49.9	82.0	413.1	82.4	.0254
2	49.9	81.6	.25	49.4	82.5	411.7	82.1	.0303
3	51.4	80.7	.31	49.7	82.8	424.7	81.7	.0362
4	48.5	79.6	.40	47.6	82.8	424.0	81.2	.0450
5	49.5	78.2	.49	48.2	82.5	422.7	80.4	.0564
6	49.5	77.5	.60	48.0	82.1	422.1	79.8	.0682
7	47.0	76.3	.70	45.5	81.3	421.8	78.8	.0786
8	44.0	75.9	.80	44.4	80.9	420.1	78.4	.0846
9	45.7	75.2	.91	43.3	80.2	418.8	77.7	.0942
10	45.3	74.8	1.01	42.7	79.6	417.5	77.2	.1035
11	45.5	74.6	1.11	42.9	78.9	416.2	76.7	.1043
12	44.6	74.7	.91	44.4	78.9	416.0	76.8	.0974
13	49.7	74.7	.81	46.7	78.9	415.6	76.8	.0909
14	51.1	74.7	.71	48.4	79.0	415.6	76.9	.0824
15	51.2	74.9	.60	48.8	79.1	415.6	77.0	.0704
16	51.6	75.1	.50	49.5	79.3	415.6	77.2	.0596
17	51.6	75.4	.41	49.7	79.6	415.6	77.5	.0487
18	51.6	75.9	.30	49.9	80.0	415.6	78.0	.0359
19	51.1	74.4	.25	49.5	81.3	416.2	78.3	.0301

TABLE 74
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 2
DATE: 4/29/76

TEST NUMBER 5 PART A TEST DESCRIPTION

Clean Condition - Flow Rate versus
Differential Pressure (Test Specimen
[S/N 6] Inlet Pressure 415 psia (nominal))

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)
0	57.1	77.1
0	49.1	77.8

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)
0.20	50.5	80.7
0.13	48.6	81.1

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
416.2	78.9	0.0246
416.9	79.4	0.0151

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 74
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 3
DATE: 4/29/76

TEST NUMBER 5	PART A	TEST DESCRIPTION	Clean Condition - Flow Rate versus Differential Pressure (Test Specimen [S/N 6] Inlet Pressure 415 psia (nominal))				
TEST SPECIMEN INLET CONDITIONS *****							
PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (CFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
413.0	82.5	.0149	17.119	17.055	17.087	-0.000	17.087
413.0	82.4	.0254	29.056	29.037	29.096	.000	29.096
411.7	82.1	.0333	36.289	36.161	36.275	.000	36.275
424.7	81.7	.0392	44.411	44.172	44.386	.000	44.386
424.0	81.0	.0450	57.157	57.500	57.339	.000	57.339
422.1	80.4	.0504	74.203	74.903	74.853	.000	74.853
422.1	79.8	.0682	94.012	95.130	95.016	.001	95.016
421.0	78.8	.0756	108.430	108.720	108.720	.001	108.720
421.1	78.4	.0846	126.218	126.418	126.418	.001	126.418
418.8	77.7	.0942	148.054	148.858	148.858	.001	148.858
417.0	77.2	.1035	173.193	173.193	173.193	.002	173.193
416.2	76.7	.1143	173.025	173.825	173.825	.002	173.825
416.2	76.8	.0974	155.195	155.195	155.195	.001	155.195
415.0	76.8	.0909	138.428	138.428	138.428	.001	138.428
415.0	76.9	.0824	120.731	120.731	120.730	.001	120.730
415.0	77.0	.0794	98.184	97.974	98.129	.001	98.129
415.0	77.2	.0596	79.585	79.012	79.148	.000	79.148
415.0	77.5	.0487	61.469	61.629	61.649	.000	61.649
415.0	78.1	.0359	43.084	43.768	43.876	.000	43.876
416.2	78.3	.0311	35.050	35.701	35.829	.000	35.829

TABLE 74
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 4
DATE: 4/29/76

TEST NUMBER 5

PART A

TEST DESCRIPTION

Clean Condition - Flow Rate versus
Differential Pressure (Test Specimen
[S/N 6] Inlet Pressure 415 psia (nominal))

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
416.2	78.9	.0246	28.246	28.757	28.201	.000	28.201
416.9	79.4	.0151	17.215	16.992	17.152	.0000	17.152

$$TARE\ DIFF.\ PRESS = -3.40000E-05 + -4.44200E-04 (ACFM) + 1.50933E-01 (ACFM)**2 + 0 (ACFM)**3$$

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 74
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 5
DATE: 4/29/76

TEST NUMBER 5 PART A TEST DESCRIPTION Clean Condition - Flow Rate versus
Differential Pressure (Test Specimen
[S/N 6] Inlet Pressure 415 psia (nominal))

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESSURE

PRESSURE		TEMPERATURE			FLOW RATE						NET DIFFERENTIAL PRESSURE	
KG/SQ CM	PSI	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID	
29.437	413.7	301.2	26.0	82.5	11.6	0.0140	0.410	1.803	1.781	1.2013	17.087	
29.637	413.7	301.2	26.0	82.4	19.7	0.254	0.696	1.371	3.422	2.1019	29.896	
28.946	411.7	301.1	27.8	82.1	23.5	0.303	0.830	1.633	3.601	2.5504	36.275	
29.857	424.7	304.4	27.6	81.7	29.0	0.362	1.023	2.015	4.443	3.1207	44.386	
29.812	424.7	304.5	27.3	81.2	36.0	0.450	1.271	2.502	5.517	4.0313	57.339	
29.721	422.7	304.1	26.9	80.4	45.1	0.564	1.591	3.133	6.907	5.2627	74.853	
29.675	422.1	299.7	26.5	79.8	54.5	0.682	1.923	3.787	8.349	6.6803	95.016	
29.584	421.4	299.2	26.4	78.8	60.3	0.756	2.129	4.193	9.244	7.6438	108.726	
29.538	421.1	298.9	25.8	78.4	67.4	0.846	2.379	4.684	10.327	8.8881	126.418	
29.447	410.4	298.5	25.4	77.7	74.9	0.947	2.645	5.207	11.480	10.4657	148.858	
29.356	411.5	298.3	25.1	77.2	82.1	1.035	2.901	5.713	12.595	12.1767	173.193	
29.265	410.2	298.0	24.9	76.7	82.6	1.143	2.917	5.743	12.662	12.2211	173.825	
29.265	410.2	298.0	24.9	76.8	77.1	0.974	2.724	5.364	11.825	10.9324	155.495	
29.219	415.5	298.0	24.9	76.8	71.8	0.909	2.537	4.995	11.013	9.7325	138.428	
29.219	415.6	298.1	24.9	76.9	65.1	0.824	2.300	4.531	9.986	8.4881	120.730	
29.219	415.4	298.2	25.0	77.0	55.6	0.704	1.964	3.867	8.525	6.8992	98.129	
29.219	415.6	298.3	25.1	77.2	47.1	0.596	1.663	3.274	7.217	5.5647	79.148	
29.219	415.6	298.4	25.3	77.5	38.5	0.487	1.359	2.676	5.899	4.3343	61.649	
29.219	415.4	298.7	25.5	78.1	28.3	0.359	1.000	1.970	4.342	3.0848	43.876	
29.265	410.2	298.9	25.7	78.3	23.8	0.311	0.839	1.651	3.640	2.5190	35.829	

TABLE 74
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 6
DATE: 4/29/76

TEST NUMBER 5 PART A TEST DESCRIPTION Clean Condition - Flow Rate versus
Differential Pressure (Test Specimen
[S/N 6] Inlet Pressure 415 psia (nominal))

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESS:

PRESSURE		TEMPERATURE			FLOW RATE						
KG/SQ CM	PSI	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID
28.265	410.2	299.2	26.1	78.9	19.4	.0246	.686	1.350	2.976	1.9827	28.201
29.311	419.9	299.5	26.3	79.4	11.9	.151	.421	1.827	1.827	1.2059	17.152
29.350	417.4	299.2	26.1	78.9							
.199	2.6	.9	.9	1.7	DEVIATIONS						

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE '75
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 1
DATE: 4/29/76

TEST NUMBER 5 PART A TEST DESCRIPTION

Clean Condition - Flow Rate versus
Differential Pressure (Test Specimen
[S/N 6] Inlet Pressure 700 psia (nominal))

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
0.13	50.5	75.0	0.13	50.5	75.1	690.3	75.6	0.097
0.20	50.5	74.2	0.20	50.5	76.4	686.4	75.3	0.147
0.25	50.7	72.3	0.25	50.7	76.5	690.3	74.9	0.187
0.29	50.7	72.6	0.29	50.7	76.5	686.4	74.5	0.217
0.39	49.0	70.4	0.39	49.0	76.4	686.4	73.9	0.280
0.49	48.0	70.1	0.49	48.0	75.9	686.4	73.0	0.344
0.59	47.1	68.3	0.59	47.1	75.0	686.4	71.7	0.406
0.69	47.0	66.4	0.69	47.0	73.8	686.4	70.1	0.474
0.80	46.5	64.7	0.80	46.5	72.3	682.5	68.5	0.544
0.90	46.3	62.3	0.90	46.3	71.9	682.5	67.1	0.613
1.01	45.4	61.6	1.01	45.4	68.9	694.3	65.2	0.660
1.01	45.4	61.8	1.01	45.4	67.4	690.3	64.1	0.663
0.90	46.0	61.9	0.90	46.0	67.0	690.3	64.0	0.605
0.80	48.6	61.0	0.80	48.6	67.1	690.3	64.0	0.562
0.70	48.6	61.3	0.70	48.6	67.4	690.3	64.3	0.490
0.60	49.0	61.9	0.60	49.0	67.8	690.3	64.8	0.422
0.49	49.4	62.2	0.49	49.4	68.2	690.3	65.2	0.353
0.39	48.4	62.0	0.39	48.4	68.9	690.3	65.9	0.277
0.30	48.4	64.1	0.30	48.4	69.6	690.3	66.9	0.207
0.25	49.5	64.9	0.25	49.5	70.4	690.3	67.6	0.179

TABLE 75
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 2
DATE: 4/29/76

TEST NUMBER 5 PART B TEST DESCRIPTION

Clean Condition - Flow Rate versus
Differential Pressure (Test Specimen
[S/N 6] Inlet Pressure 700 psia (nominal))

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)
0	44.7	65.8
0	47.4	66.9

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)
.20	48.4	70.9
.13	47.1	77.6

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
490.3	68.4	.0138
697.3	69.2	.0087

TABLE 75
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 3
DATE: 4/29/76

TEST NUMBER 5	PART #	TEST DESCRIPTION	Clean Condition - Flow Rate versus Differential Pressure (Test Specimen [S/N 6] Inlet Pressure 700 psia (nominal))				
TEST SPECIMEN INLET CONDITIONS							

AVG GROSS DIFF. PRESS PRIMARY (PSID)	AVG GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)	AVG TEMP (DEG. F)	AVG FLOW RATE (SCFM)	
10.519	9.970	9.995	-0.001	9.995	75.6	.0097	
15.519	14.997	15.008	+0.001	15.008	75.3	.0147	
19.536	19.516	19.577	-0.001	19.578	74.9	.0187	
23.793	23.009	23.101	+0.001	23.102	74.5	.0217	
30.789	30.641	30.715	+0.001	30.716	73.9	.0280	
38.868	38.580	38.724	+0.001	38.724	73.0	.0344	
47.301	46.885	47.093	+0.001	47.094	71.7	.0406	
56.848	56.116	56.482	+0.001	56.483	70.1	.0474	
67.510	66.242	66.626	+0.000	66.626	68.5	.0544	
78.513	77.001	77.507	+0.000	77.507	67.1	.0613	
85.955	85.861	85.908	.000	85.909	65.2	.0660	
85.955	85.861	85.908	.000	85.909	64.1	.0663	
76.267	76.368	76.318	+0.000	76.318	64.0	.0605	
69.515	69.406	69.210	+0.000	69.211	64.0	.0562	
58.731	58.964	58.847	+0.000	58.848	64.3	.0490	
50.749	49.774	49.961	+0.001	49.962	64.8	.0422	
40.054	40.403	40.639	+0.001	40.639	65.0	.0353	
30.789	30.354	30.572	+0.001	30.572	65.9	.0277	
22.507	22.093	22.300	+0.001	22.300	66.9	.0207	
19.502	18.829	19.015	+0.001	19.016	67.6	.0179	

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 75
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 4
DATE: 4/29/76

TEST NUMBER	PART	TEST DESCRIPTION	Clean Condition - Flow Rate versus Differential Pressure (Test Specimen [S.N 6] Inlet Pressure 700 psia (nominal))				
TEST SPECIMEN INLET CONDITIONS							

AVG PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
690.3	69.4	.0134	14.519	14.254	14.386	-0.001	14.387
694.3	69.2	.0087	9.706	8.886	9.046	-0.001	9.047

$$\text{TARE DIFF. PRESS} = -3.60000\text{E-}04 + -3.3161\text{E-}02 (\text{ACFM}) + 5.33359\text{E-}01 (\text{ACFM})^2 + 0 (\text{ACFM})^3$$

TABLE 75

FLOW RATE VERSUS DIFFERENTIAL PRESSURE

DATE: 4/29/76

TEST NUMBER 5

PART B

TEST DESCRIPTION

Clean Condition - Flow Rate versus
Differential Pressure (Test Specimen
[S/N 6] Inlet Pressure 700 psia (nominal))

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESS

PRESSURE		TEMPERATURE			FLOW RATE					NET DIFFERENTIAL PRESS	
KG/50 CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ICFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID
48.536	890.3	297.4	24.2	75.6	12.8	.0097	.452	.890	1.962	.7027	9.995
48.260	886.4	297.2	24.1	75.3	19.2	.0147	.678	1.334	2.941	1.0552	15.008
48.536	891.3	297.4	23.8	74.9	24.6	.0187	.868	1.710	3.769	1.3764	19.578
48.260	886.4	296.8	23.6	74.5	28.4	.0217	1.003	1.976	4.355	1.6242	23.102
48.260	886.4	296.4	23.3	73.9	36.8	.0280	1.300	2.552	5.642	2.1595	30.716
48.260	886.4	296.0	22.8	73.0	45.3	.0344	1.599	3.142	6.942	2.7226	38.724
48.260	886.4	295.2	22.0	71.7	53.5	.0406	1.889	3.712	8.199	3.3110	47.094
48.260	886.4	294.3	21.1	70.1	62.6	.0474	2.211	4.353	9.597	3.9711	56.483
47.985	882.5	293.4	20.3	68.5	71.8	.0544	2.535	4.991	11.003	4.6843	66.626
47.985	882.5	292.6	19.5	67.1	81.0	.0613	2.861	5.633	12.420	5.4493	77.507
48.811	894.3	291.6	18.5	65.2	89.0	.0660	3.143	6.182	13.644	6.0400	85.909
48.536	890.3	291.0	17.8	64.1	89.2	.0663	3.150	6.202	13.674	6.0400	85.909
48.536	890.3	290.9	17.8	64.0	81.3	.0605	2.872	5.655	12.467	5.3657	76.318
48.536	890.3	291.0	17.8	64.0	75.6	.0562	2.671	5.252	11.595	4.8660	69.211
48.536	890.3	291.1	18.0	64.3	65.8	.0490	2.325	4.572	10.095	4.1374	58.848
48.536	890.3	291.4	18.2	64.8	56.7	.0422	2.003	3.943	8.693	3.5127	49.962
48.536	890.3	291.6	18.5	65.2	47.4	.0353	1.674	3.296	7.267	2.8572	40.639
48.536	890.3	292.0	18.9	65.9	37.1	.0277	1.310	2.572	5.686	2.1494	30.572
48.536	890.3	292.5	19.4	66.9	27.7	.0207	.978	1.925	4.244	1.5679	22.300
48.536	890.3	293.0	19.8	67.6	23.9	.0179	.843	1.660	3.660	1.3369	19.016

TABLE 75
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 6
DATE: 4/29/76

TEST NUMBER 5 PART 3 TEST DESCRIPTION Clean Condition - Flow Rate versus
Differential Pressure (Test Specimen
[S/N 6] Inlet Pressure 700 psia (nominal))

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESS

PRESSURE		TEMPERATURE			FLOW RATE					NET DIFFERENTIAL PRESS	
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	SCFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID
48.536	690.3	203.4	20.2	68.4	18.5	0.138	0.652	1.284	2.832	1.0115	14.387
48.536	690.3	293.0	20.7	69.2	11.6	0.087	0.409	0.809	1.777	0.6361	9.047
48.423	688.7	293.6	20.5	68.8							
0.162	2.4	2.0	2.0	3.5	DEVIATIONS						

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 76
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 1
DATE: 4/29/76

TEST NUMBER 5 PART C TEST DESCRIPTION

Clean Condition - Flow Rate versus
Differential Pressure (Test Specimen
[S/N 6] Inlet Pressure 1000 psia (nominal))

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE, (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE / (ACFM)
0	30.1	71.4	.13	49.7	73.0	1006.7	82.2	.0063
0	35.1	72.3	.21	49.5	73.0	1006.7	81.7	.0102
0	40.7	72.3	.25	49.4	72.1	1006.7	81.2	.0125
0	40.7	72.3	.31	49.2	73.0	1002.7	80.6	.0150
0	51.2	72.4	.41	49.5	72.4	1002.7	79.4	.0200
0	50.9	72.0	.50	49.1	71.4	1002.7	77.7	.0242
0	50.5	71.0	.60	48.0	72.9	1002.7	75.7	.0289
0	40.3	67.1	.70	47.0	72.2	1002.7	73.6	.0335
0	40.9	67.0	.8	47.3	72.3	998.7	71.6	.0379
0	40.0	64.5	.95	47.1	70.7	998.7	69.1	.0427
0	40.9	62.4	1.01	46.3	71.8	994.8	67.4	.0471
0	40.9	61.5	1.1	46.3	69.4	994.8	65.5	.0471
0	30.1	61.5	.91	47.8	69.0	994.8	65.3	.0436
0	40.5	61.8	.80	47.6	69.0	994.8	65.4	.0385
0	40.1	62.2	.71	47.6	69.2	994.8	65.7	.0334
0	40.9	60.8	.60	47.8	69.6	994.8	66.2	.0290
0	40.5	62.3	.50	48.4	70.1	990.8	66.7	.0244
0	40.3	64.5	.4	48.6	71.0	990.8	67.8	.0197
0	40.7	64.8	.3	48.2	72.0	994.8	68.9	.0145
0	40.7	66.7	.25	48.8	72.7	994.8	69.7	.0123

TABLE 76
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 2
DATE: 4/29/76

TEST NUMBER 5 PART C TEST DESCRIPTION

Clean Condition - Flow Rate versus
Differential Pressure (Test Specimen
[S/N 6] Inlet Pressure 1000 psia (nominal))

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG- TEMP (DEG. F)	AVG- FLOW RATE (ACFM)
0	40.5	67.2	.20	49.1	73.4	994.0	70.6	.0096
0	40.3	69.2	.14	48.8	74.4	994.8	71.8	.0067

TABLE 76
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 3
DATE: 4/29/76

TEST NUMBER	S	PART C	TEST DESCRIPTION	Clean Condition - Flow Rate versus Differential Pressure (Test Specimen [S/N 6] Inlet Pressure 1000 psia (nominal))			
TEST SPECIMEN INLET CONDITIONS *****							
PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (CFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
1006.7	82.2	.0063	6.791	6.790	6.891	-0.000	6.891
1006.7	81.7	.0102	11.720	11.112	11.066	-0.000	11.066
1006.7	81.2	.125	13.195	13.711	13.903	-0.000	13.903
1002.7	80.6	.0150	16.437	16.426	16.828	-0.000	16.828
1002.7	79.4	.0206	23.73	23.067	23.099	-0.000	23.099
1002.7	77.7	.022	28.023	28.803	28.863	-0.000	28.863
1002.7	75.7	.0289	35.490	35.241	35.315	-0.000	35.315
1002.7	73.6	.0335	41.900	41.749	41.829	-0.000	41.829
998.7	71.6	.0379	48.416	48.156	48.286	-0.000	48.286
998.7	69.1	.0427	55.984	55.624	55.754	-0.000	55.755
994.8	67.4	.0471	63.413	63.209	63.311	-0.000	63.311
994.8	65.5	.0471	63.464	63.525	63.595	-0.000	63.595
994.8	65.3	.0430	57.490	57.520	57.455	-0.000	57.456
994.8	65.4	.0385	49.24	49.542	49.691	-0.000	49.691
994.8	65.7	.0324	42.280	41.980	42.130	-0.000	42.130
994.8	66.2	.0290	36.735	35.816	35.976	-0.000	35.976
994.8	65.7	.0244	29.794	29.377	29.586	-0.000	29.586
994.8	67.8	.0197	23.655	22.495	23.075	-0.000	23.075
994.8	64.9	.0145	16.705	16.426	16.565	-0.000	16.566
994.8	69.7	.0120	14.182	13.454	13.968	-0.000	13.968

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 76
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 4
DATE: 4/29/76

TEST NUMBER 5	PART C	TEST DESCRIPTION	Clean Condition - Flow Rate versus Differential Pressure (Test Specimen [S/N 6] Inlet Pressure 1000 psia (nominal))				
TEST SPECIMEN INLET CONDITIONS *****							
PRESSURE (PSIA)	AVG TEMP (DEG. F)	VG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
994.2	71.2	.0094	10.432	10.592	10.715	0.000	10.715
994.0	71.8	.0007	7.517	7.347	7.432	0.000	7.432

$$\text{TARE DIFF. PRESS} = -1.6 \times 10^{-04} + -1.2603 \times 10^{-02} (\text{ACFM}) + 2.46070 \times 10^{-01} (\text{ACFM})^{**2} + 0 (\text{ACFM})^{**3}$$

TABLE 76
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 5
DATE: 4/29/76

TEST NUMBER 5		PART C		TEST DESCRIPTION		Clean Condition - Flow Rate versus Differential Pressure (Test Specimen [S/N 6] Inlet Pressure 1000 psia (nominal))					
TEST SPECIMEN INLET CONDITIONS										NET DIFFERENTIAL PRESS	
PRESSURE		TEMPERATURE			FLOW RATE						
KG/SQ CM	PSI	DEG. C	DEG. F	DEG. F	LIT-PS/ MIN	SCFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID
70.775	1000.7	301.0	27.0	82.2	12.0	.0063	.423	.832	1.835	.4845	6.891
70.775	1000.7	310.0	27.0	81.7	19.3	.0102	.680	1.340	2.954	.7780	11.066
70.775	1000.7	311.5	27.4	81.0	23.7	.0115	.837	1.647	3.631	.9775	13.903
70.496	1002.7	300.0	27.0	80.6	28.4	.0150	1.003	1.974	4.352	1.1831	16.828
70.496	1002.7	290.5	26.3	79.4	38.0	.0200	1.343	2.645	5.831	1.6240	23.099
70.496	1000.7	295.5	25.4	77.7	46.2	.0240	1.630	3.210	7.077	2.0293	28.863
70.496	1002.7	297.4	24.3	75.7	55.3	.0289	1.953	3.848	8.479	2.4829	35.315
70.496	1002.7	296.3	23.1	73.6	64.2	.0335	2.266	4.462	9.838	2.9409	41.829
70.218	096.7	295.2	22.0	71.6	72.8	.0379	2.570	5.060	11.155	3.3948	48.286
70.218	096.7	293.4	20.0	69.1	82.3	.0427	2.906	5.722	12.615	3.9199	55.755
69.939	094.8	292.8	19.6	67.4	90.8	.0471	3.205	6.312	13.915	4.4512	63.311
69.939	094.8	291.5	18.0	65.5	91.1	.0471	3.217	6.334	13.965	4.4712	63.595
69.939	094.8	291.6	18.5	65.3	84.2	.0436	2.975	5.858	12.914	4.0395	57.456
69.939	094.8	291.7	18.6	65.4	74.4	.0365	2.627	5.173	11.404	3.4937	49.691
69.939	094.8	291.9	18.7	65.7	64.5	.0334	2.277	4.483	9.883	2.9621	42.130
69.939	094.8	292.2	19.0	66.2	56.0	.0290	1.977	3.892	8.581	2.5294	35.976
69.661	090.8	292.5	19.3	66.7	46.9	.0244	1.657	3.262	7.191	2.0801	29.586
69.661	090.8	293.0	19.9	67.8	37.8	.0197	1.335	2.628	5.795	1.6223	23.075
69.939	094.8	290.0	20.0	68.9	27.8	.0145	.983	1.935	4.265	1.1647	16.566
69.939	094.8	290.1	20.9	69.7	23.6	.0123	.834	1.641	3.618	.9820	13.968

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 76
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 6
DATE: 4/29/76

TEST NUMBER 5		PART C		TEST DESCRIPTION		Clean Condition - Flow Rate versus Differential Pressure (Test Specimen [S/N 6] Inlet Pressure 1000 psia (nominal))					NET DIFFERENTIAL PRESSURE	
TEST SPECIMEN INLET CONDITIONS												
PRESSURE		TEMPERATURE			FLOW RATE							
KG/SQ CM	PSIA	DEG. C	DEG. C	DEG. F	LIT-PS/ MIN	CFM	SCFM	GN2 KG/HR	GN2 LRS/HR	KG/SQ CM DIFFERENTIAL	PSID	
69.939	994.2	244.6	21.5	70.6	18.5	.0006	.652	1.284	2.931	.7534	10.715	
69.939	994.4	295.3	22.1	71.8	12.8	.0067	.452	.890	1.962	.5225	7.432	
****	****	****	****	****								
70.180	994.2	295.4	22.2	72.0								
.313	4.6	2.1	2.2	5.1	DEVIATIONS							

TABLE 77
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 1
DATE: 4/28/76

TEST NUMBER 5 PART D TEST DESCRIPTION

Clean Condition - Flow Rate versus
Differential Pressure (Test Specimen
[S/N 6] Inlet Pressure 2900 psia (nominal)
TEST SPECIMEN INLET CONDITIONS

FLOWMETER CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
0	50.1	78.6	.13	49.7	78.9	2887.8	78.8	.0022
0	51.0	77.2	.20	50.4	78.9	2887.8	78.1	.0035
0	51.0	75.6	.25	50.6	78.8	2891.9	77.2	.0044
0	52.8	73.2	.29	50.2	78.4	2891.9	75.8	.0051
0	40.1	69.8	.40	48.3	77.6	2891.9	73.7	.0066
0	48.9	65.0	.49	47.9	76.0	2891.9	70.6	.0082
0	49.5	58.6	.59	48.1	72.7	2891.9	65.6	.0098
0	42.7	52.7	.69	48.1	68.9	2887.8	60.8	.0116
0	50.6	48.0	.80	48.7	65.1	2887.8	56.6	.0139
0	49.1	45.0	.90	46.8	61.7	2887.8	53.4	.0145
0	40.9	42.6	.90	46.6	58.5	2887.8	50.5	.0149
0	51.2	42.0	.79	48.3	57.0	2883.8	49.5	.0132
0	50.4	43.4	.69	48.7	57.7	2883.8	50.5	.0117
0	40.5	44.1	.59	48.1	58.0	2883.8	51.1	.0098
0	49.1	44.9	.50	47.9	58.6	2883.8	51.7	.0083
0	51.1	46.0	.40	49.3	59.4	2883.8	52.7	.0068
0	49.9	47.6	.29	49.1	60.4	2883.8	54.0	.0049
0	40.5	49.3	.25	48.9	61.7	2887.8	55.5	.0043
0	40.3	51.2	.20	48.7	63.0	2887.8	57.1	.0035
0	40.3	52.2	.13	48.1	64.2	2887.8	58.7	.0022

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 77
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 2
DATE: 4/28/76

TEST NUMBER 6	PART 6	TEST DESCRIPTION	Clean Condition - Flow Rate versus Differential Pressure (Test Specimen [S/N 6] Inlet Pressure 2900 psia (nominal))				
			TEST SPECIMEN INLET CONDITIONS *****	AVG GROSS DIFF. PRESS (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
PRESSURE (PSIA)	INLET TEMP (°C) (°F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
2847.0	73.5	.0022	3.109	3.188	3.148	-0.000	3.148
2847.0	73.1	.0035	4.923	5.010	4.966	-0.000	4.966
2841.4	77.2	.0144	6.794	6.874	6.839	.000	6.839
2841.7	75.2	.0051	7.361	7.462	7.412	.000	7.412
2841.4	75.7	.0066	9.193	9.272	9.285	.000	9.286
2841.7	76.0	.0082	12.343	12.590	12.541	.000	12.541
2841.7	75.5	.0098	15.472	15.571	15.524	-0.000	15.525
2847.0	66.3	.0116	18.783	18.832	18.807	-0.001	18.808
2847.0	56.6	.0135	22.457	22.494	22.478	-0.002	22.478
2847.0	51.4	.0145	24.923	24.648	24.835	-0.003	24.836
2847.0	50.5	.0145	24.947	24.963	24.955	-0.003	24.955
2843.0	49.5	.0132	22.395	22.326	22.361	-0.002	22.361
2843.0	47.5	.0117	19.434	19.576	19.553	-0.001	19.554
2843.0	51.1	.0098	16.764	16.985	16.125	-0.000	16.125
2843.0	51.7	.0083	13.595	13.284	13.289	.000	13.290
2843.0	52.7	.0068	10.611	10.543	10.577	.000	10.577
2843.5	54.1	.0049	7.736	7.576	7.656	.000	7.656
2847.0	55.5	.0043	6.449	6.435	6.492	.000	6.492
2847.0	47.1	.0035	5.135	5.124	5.184	-0.000	5.180
2847.0	46.7	.0022	3.234	3.188	3.211	-0.000	3.211

$$T - 6 \text{ DIFF. PRESS} = -1.24600F - 0.7 + 4.84453 \cdot 10^{-1} (\text{ACFM}) + -4.00723E 01 (\text{ACFM})^2 + 0 (\text{ACFM})^3$$

TABLE 77
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 3
DATE: 4/28/76

TEST NUMBER &		PART 3		TEST DESCRIPTION		Clean Condition - Flow Rate versus Differential Pressure (Test Specimen [S/N 6] Inlet Pressure 2900 psia (nominal) NET DIFFERENTIAL PRESS						
TEST SPECIMEN INLET CONDITIONS												
PRESSURE		TEMPERATURE				FLOW RATE						
KG/SQ CM	PSI	DEG. K	DEG. C	DEG. F	LITERS/ MIN	SCFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID	
203.033	2987.4	299.1	26.0	78.8	12.0	.0022	.425	1.839	1.844	.2213	3.148	
203.033	2967.4	298.4	25.6	78.1	19.1	.0035	.674	1.321	2.926	.3491	4.966	
203.310	2991.4	298.3	25.1	77.2	24.2	.0044	.853	1.672	3.703	.4457	6.339	
203.310	2991.4	297.5	24.3	75.8	28.0	.0051	.988	1.942	4.287	.5211	7.412	
203.310	2991.4	296.3	23.1	73.7	36.6	.0066	1.291	2.541	5.602	.6950	9.886	
203.310	2991.4	294.6	21.5	70.6	45.5	.0082	1.606	3.162	6.972	.8817	12.541	
203.310	2991.4	291.4	18.7	65.6	55.1	.0098	1.945	3.822	8.441	1.0915	15.525	
203.033	2987.4	289.2	16.0	60.8	65.4	.0116	2.311	4.550	10.030	1.3223	18.808	
203.033	2987.4	286.4	13.6	56.6	76.9	.0135	2.714	5.344	11.781	1.5804	22.478	
203.033	2987.4	285.0	11.9	53.4	83.3	.0145	2.943	5.790	12.777	1.7461	24.836	
203.033	2987.4	283.5	10.3	50.5	83.8	.0145	2.959	5.821	12.847	1.7545	24.955	
202.744	2983.4	282.9	9.7	49.5	76.4	.0132	2.699	5.312	11.717	1.5721	22.361	
202.744	2983.4	283.5	10.3	50.5	67.4	.0117	2.379	4.684	10.326	1.3748	19.554	
202.744	2983.4	283.4	10.6	51.1	56.6	.0098	2.000	3.930	8.681	1.1337	16.125	
202.744	2983.4	284.1	11.0	51.7	47.5	.0083	1.677	3.303	7.282	.9344	13.290	
202.744	2983.4	284.7	11.5	52.7	38.8	.0068	1.370	2.691	5.946	.7436	10.577	
202.744	2983.4	285.4	12.2	54.3	28.3	.0049	1.000	1.962	4.341	.5383	7.686	
203.033	2987.4	286.2	13.1	55.5	24.5	.0043	.864	1.702	3.753	.4565	6.492	
203.033	2987.4	287.1	14.0	57.1	19.7	.0035	.695	1.362	3.017	.3642	5.180	
203.033	2987.4	288.0	14.8	58.7	12.3	.0022	.434	1.054	1.882	.2257	3.211	
203.014	2987.4	289.3	16.2	61.1								
.102	2.3	5.1	5.1	9.2	DEVIATIONS							

TABLE 78
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 1
DATE: 7-8-76

TEST NUMBER 50 PART G TEST DESCRIPTION

CLEAN CONDITION - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE- TEST SPECIMEN
[S/N 020] INLET PRESSURE 415 PSIA (NOMINAL)

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.14	49.5	78.5	.13	49.1	79.1	417.4	78.8	.0164
.22	49.1	78.2	.21	48.9	78.9	418.9	78.6	.0261
.28	49.9	77.7	.26	49.5	78.9	416.1	78.3	.0323
.32	49.1	77.5	.21	48.7	78.7	415.5	78.1	.0370
.41	49.7	76.9	.41	49.1	78.4	414.8	77.7	.0489
.51	50.1	76.5	.50	49.1	78.2	413.5	77.4	.0666
.60	49.9	76.1	.60	48.7	77.9	412.9	77.0	.0717
.69	49.5	75.8	.71	48.7	77.6	411.6	76.7	.0830
.79	50.2	74.1	.81	48.5	72.9	416.1	73.5	.0951
.88	49.7	74.2	.91	47.8	73.2	415.5	73.7	.1045
.88	49.7	74.4	.91	47.8	74.6	415.5	74.0	.1048
.79	49.7	74.6	.81	47.9	74.0	415.5	74.3	.0937
.69	50.2	74.8	.70	48.9	74.5	415.5	74.6	.0834
.60	50.2	74.8	.60	49.1	74.5	416.1	74.7	.0720
.51	50.1	75.0	.51	49.3	74.6	416.1	74.8	.0668
.41	50.1	75.2	.40	49.3	74.8	416.8	75.0	.0485
.32	50.1	75.5	.30	49.9	75.0	416.8	75.3	.0372
.27	50.2	75.8	.26	49.9	75.3	417.4	75.5	.0316
.22	49.9	75.9	.21	49.7	75.5	417.4	75.7	.0254
.15	50.1	76.2	.14	49.9	75.5	418.1	75.9	.0174

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 78
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 56	PART G	TEST DESCRIPTION	CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE - TEST SPECIMEN S/N 020 INLET PRESSURE 415 PSIA (NOMINAL)				
TEST SPECIMEN INLET CONDITIONS							
AVG PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (SCFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
411.9	78.8	.1164	17.686	17.663	17.674	-0.000	17.674
410.9	78.6	.0261	29.509	29.342	29.425	.000	29.425
416.1	78.3	.0323	37.620	37.382	37.501	.000	37.501
415.5	78.1	.0370	44.159	43.829	43.994	.000	43.994
414.8	77.7	.0489	59.473	60.786	60.130	.000	60.130
413.5	77.4	.0606	77.218	78.801	78.010	.000	78.010
412.2	77.0	.0717	98.080	98.080	98.080	.001	98.080
411.9	76.7	.0830	118.939	118.939	118.939	.001	118.939
416.1	73.5	.1951	144.538	144.538	144.538	.001	144.538
415.5	73.7	.1046	167.610	167.610	167.610	.002	167.610
415.5	74.0	.1048	167.294	167.294	167.294	.002	167.294
415.5	74.3	.1937	140.746	140.746	140.746	.001	140.746
415.5	74.6	.0834	118.307	118.307	118.307	.001	118.307
416.1	74.7	.0720	96.594	97.448	97.021	.001	97.021
416.1	74.8	.0608	77.591	78.169	77.880	.000	77.880
416.8	75.0	.0485	58.846	59.206	59.026	.000	59.026
416.8	75.3	.0372	43.786	43.484	43.635	.000	43.635
417.2	75.5	.0316	36.561	36.232	36.396	.000	36.396
417.4	75.7	.0254	28.697	28.309	28.503	.000	28.503
418.1	75.9	.0174	19.002	18.691	18.847	.000	18.847

TARE DIFF. PRESS = $-3.40000E-05 + -4.44000E-04$ (ACFM) + $1.50933E-01$ (ACFM)**2 + $0.$ (ACFM)**3

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 78

PAGE: 3
DATE: 7-8-76

FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 50		PART 6		TEST DESCRIPTION		CLEAN CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE - TEST SPECIMEN S/N 020 INLET PRESSURE 415 PSIA (NOMINAL)		NET DIFFERENTIAL PRESS.				
TEST SPECIMEN INLET CONDITIONS												
PRESSURE		TEMPERATURE			FLOW RATE					NET DIFFERENTIAL PRESS.		
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	SCFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID	
28.937	411.0	299.1	26.0	78.8	12.2	.0164	.452	1.890	1.962	1.2426	17.674	
28.891	410.2	299.0	25.9	78.6	19.9	.0261	.718	1.414	3.117	2.0688	29.425	
29.256	416.1	298.9	25.7	78.3	24.8	.0323	.900	1.774	3.907	2.6366	37.901	
29.210	415.2	298.8	25.6	78.1	28.7	.0370	1.031	2.022	4.474	3.0931	43.294	
29.165	414.8	298.5	25.4	77.7	38.1	.0489	1.361	2.681	5.910	4.2275	60.130	
29.073	413.2	298.4	25.2	77.4	47.0	.0606	1.680	3.302	7.293	5.4846	78.010	
29.028	412.2	298.2	25.0	77.0	55.7	.0717	1.988	3.914	8.630	6.0957	98.000	
28.937	411.0	298.0	24.8	76.7	64.9	.0830	2.296	4.521	9.968	8.3622	118.239	
29.256	416.1	296.2	23.1	73.5	75.6	.0951	2.675	5.269	11.611	10.1621	144.538	
29.210	415.2	296.3	23.2	73.7	83.1	.1046	2.937	5.782	12.749	11.7841	167.910	
29.210	415.2	296.5	23.3	74.0	83.2	.1048	2.941	5.790	12.766	11.7619	167.294	
29.210	415.2	296.7	23.5	74.3	74.1	.0937	2.628	5.172	11.409	9.8954	140.746	
29.210	415.2	296.8	23.7	74.6	65.8	.0834	2.336	4.900	10.142	8.3178	118.307	
29.256	416.1	296.9	23.7	74.7	56.5	.0720	2.021	3.972	8.772	6.8212	97.021	
29.256	416.1	296.9	23.8	74.8	47.7	.0608	1.706	3.352	7.404	5.4755	77.880	
29.302	416.8	297.1	23.9	75.0	37.8	.0485	1.362	2.981	5.912	4.1499	59.026	
29.302	416.8	297.2	24.0	75.3	28.9	.0372	1.044	2.052	4.531	3.0678	43.635	
29.347	417.4	297.3	24.2	75.5	24.5	.0316	.889	1.750	3.858	2.5589	36.396	
29.347	417.4	297.4	24.3	75.7	19.7	.0254	.713	1.402	3.096	2.0040	28.503	
29.393	418.1	297.5	24.4	75.9	13.3	.0174	.489	1.964	2.124	1.3250	18.847	
****	****	****	****	****								
29.190	415.4	297.6	24.4	76.0								
.111	1.0	.8	.8	1.5	DEVIATIONS							

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 79
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 1
DATE: 7-8-76

CLEAN CONDITION-FLOW RATE VERSUS DIFFERENTIAL
PRESSURE (TEST SPECIMEN S/N 020) INLET
PRESSURE 700 PSIA (NOMINAL)

TEST NUMBER F5 PART F TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (7CFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
703.9	87.8	.0093	9.422	9.400	9.411	-0.001	9.411
703.9	87.7	.0153	16.026	15.855	15.940	-0.001	15.941
703.9	87.6	.0186	19.909	19.75	19.827	-0.001	19.828
703.9	87.4	.0222	24.219	23.985	24.102	-0.001	24.103
703.9	87.1	.0282	31.351	31.217	31.284	-0.001	31.285
703.9	86.7	.0351	40.493	40.210	40.401	-0.001	40.402
703.9	86.2	.0418	49.797	49.303	49.550	-0.001	49.551
700.0	85.6	.0481	57.331	57.520	57.426	-0.000	57.426
700.0	85.3	.0544	66.602	67.002	66.802	-0.000	66.802
700.0	85.0	.0619	78.458	78.695	78.577	.000	78.577
700.0	84.5	.0613	77.339	77.747	77.543	-0.000	77.544
700.0	84.7	.0542	66.476	67.002	66.739	-0.000	66.740
700.0	84.9	.0486	58.083	58.469	58.276	-0.000	58.276
700.0	85.3	.0418	49.858	49.303	49.581	-0.001	49.581
700.0	85.8	.0350	40.309	39.906	40.108	-0.001	40.108
700.0	86.3	.0282	31.597	31.217	31.407	-0.001	31.408
700.0	86.8	.0220	23.973	23.641	23.807	-0.001	23.808
703.9	87.4	.0179	19.231	18.887	19.059	-0.001	19.060
703.9	87.8	.0150	15.902	15.626	15.764	-0.001	15.765
703.9	88.4	.0098	10.101	9.800	9.950	-0.001	9.951

LARE DIFF. PRESS = -3.60000E-04 + -3.31610E-02 (ACFM) + 6.33359E-01 (ACFM)**2 +

0 (ACFM)**3

C 4

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 79
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 2
DATE: 7-8-76

CLEAN CONDITION-FLOW RATE VERSUS DIFFERENTIAL
PRESSURE (TEST SPECIMEN S/N 020) INLET
PRESSURE 700 PSIA (NOMINAL)

FLOWMETER CONDITIONS			TEST SPECIMEN INLET CONDITIONS					
*****			*****					
FLOWMETER ONE			FLOWMETER TWO					
*****			*****					
FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.14	49.3	87.7	.13	49.1	87.9	703.9	87.8	.0993
.23	48.7	87.4	.22	48.3	88.0	703.9	87.7	.0153
.27	48.9	87.5	.26	48.5	88.0	703.9	87.6	.0186
.32	49.3	86.9	.31	48.7	88.0	703.9	87.4	.0222
.41	49.3	86.2	.40	48.7	87.9	703.9	87.1	.0282
.51	49.3	85.5	.51	48.2	87.9	703.9	86.7	.0351
.60	49.5	84.8	.60	48.3	87.7	703.9	86.2	.0418
.68	49.5	83.9	.70	47.9	87.3	700.0	85.6	.0481
.77	49.1	83.6	.80	47.6	87.0	700.0	85.2	.0544
.87	49.7	83.2	.91	47.6	86.7	700.0	85.0	.0619
.87	49.3	82.7	.91	47.2	86.3	700.0	84.5	.0613
.77	49.1	83.0	.80	47.4	86.4	700.0	84.7	.0542
.69	49.5	83.2	.71	47.9	86.5	700.0	84.9	.0486
.60	49.5	82.7	.60	48.5	87.0	700.0	85.3	.0418
.50	49.3	84.2	.50	48.3	87.4	700.0	85.8	.0350
.41	49.5	84.8	.40	48.9	87.7	700.0	86.3	.0282
.31	49.9	85.5	.31	49.5	88.1	700.0	86.8	.0220
.26	49.5	86.2	.25	49.1	88.6	703.9	87.4	.0179
.22	50.2	86.8	.21	50.1	88.8	703.9	87.8	.0150
.14	49.7	87.6	.13	49.3	89.2	703.9	88.4	.0098

TABLE 79
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 3
DATE: 7-8-76

CLEAN CONDITION-FLOW RATE VERSUS DIFFERENTIAL PRESSURE (TEST SPECIMEN S/N 020) INLET PRESSURE 700 PSIA (NOMINAL)

TEST SPECIMEN INLET CONDITIONS											NET DIFFERENTIAL PRESS	
*****											*****	
PRESSURE		TEMPERATURE			FLOW RATE						DIFFERENTIAL	
*****		*****			*****						*****	
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN ₂ KG/HR	GN ₂ LBS/HR	KG/SQ CM	PSID	
49.489	703.2	304.1	31.0	87.8	11.7	.0093	.432	1.852	1.877	.6617	9.411	
49.489	703.2	304.1	31.0	87.7	19.5	.0150	.707	1.393	3.071	1.1208	15.941	
49.489	703.2	304.0	30.9	87.6	23.9	.0186	.862	1.698	3.743	1.3940	19.828	
49.489	703.2	304.0	30.8	87.4	28.6	.0222	1.031	2.031	4.477	1.6946	24.103	
49.489	703.2	303.7	30.6	87.1	36.4	.0282	1.308	2.572	5.680	2.1995	31.285	
49.489	703.2	303.5	30.4	86.7	45.6	.0351	1.629	3.201	7.071	2.8405	40.402	
49.489	703.2	303.3	30.1	86.2	54.7	.0418	1.942	3.822	8.432	3.4838	49.551	
49.212	700.0	303.0	29.8	85.6	60.7	.0481	2.225	4.380	9.657	4.0375	57.426	
49.212	700.0	302.8	29.6	85.3	71.6	.0544	2.520	4.964	10.939	4.6967	66.802	
49.212	700.0	302.6	29.4	85.0	81.2	.0619	2.868	5.641	12.449	5.5245	78.577	
49.212	700.0	302.3	29.1	84.5	80.5	.0613	2.842	5.591	12.338	5.4819	77.544	
49.212	700.0	302.4	29.3	84.7	71.2	.0542	2.512	4.941	10.905	4.6923	66.740	
49.212	700.0	302.5	29.4	84.9	63.6	.0486	2.253	4.432	9.780	4.0972	58.276	
49.212	700.0	302.8	29.6	85.3	54.5	.0418	1.935	3.811	8.401	3.4859	49.581	
49.212	700.0	303.0	29.9	85.8	45.2	.0350	1.618	3.182	7.022	2.8199	40.108	
49.212	700.0	303.3	30.1	86.3	36.3	.0282	1.304	2.568	5.662	2.2082	31.408	
49.212	700.0	303.6	30.4	86.8	28.2	.0220	1.016	2.001	4.411	1.6738	23.808	
49.489	703.2	303.9	30.8	87.4	23.0	.0179	.832	1.631	3.610	1.3400	19.060	
49.489	703.2	304.2	31.0	87.8	19.2	.0150	.697	1.372	3.026	1.1084	15.765	
49.489	703.2	304.5	31.3	88.4	12.2	.0093	.451	1.882	1.959	.6996	9.951	
*****	*****	*****	*****	*****								
49.350	701.9	303.4	30.2	86.4								
.138	2.0	.6	.6	1.1	DEVIATIONS							

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 80
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 1
DATE: 7-8-76

CLEAN CONDITION-FLOW RATE VERSUS DIFFERENTIAL
PRESSURE (TEST SPECIMEN S/N 020) INLET
PRESSURE 1,000 PSIA (NOMINAL)

TEST NUMBER 5E PART # TEST DESCRIPTION

FLOWMETER CONDITIONS						TEST SPECIMEN INLET CONDITIONS		
FLOWMETER ONE			FLOWMETER TWO			PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (SCFM)
FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE, (PSIA)	TEMP (DEG. F)			
.15	50.4	79.4	.13	50.2	87.7	976.3	88.6	.0072
.22	51.0	82.8	.21	50.6	87.8	976.2	88.3	.0113
.27	50.4	88.1	.26	50.2	87.9	972.3	88.0	.0138
.31	50.4	87.4	.21	50.1	87.9	970.3	87.7	.0160
.41	51.0	85.8	.41	50.2	87.8	972.3	86.8	.0213
.50	50.1	84.4	.50	49.3	87.4	972.3	85.9	.0257
.59	50.1	82.8	.60	48.9	86.7	972.3	84.7	.0304
.69	49.9	81.4	.71	48.5	86.0	968.2	83.7	.0355
.77	49.9	79.7	.81	48.3	84.7	968.3	82.2	.0400
.87	49.5	78.7	.91	47.2	83.9	964.3	81.3	.0445
.87	49.1	77.7	.91	47.0	81.7	964.3	80.2	.0444
.78	48.7	77.8	.81	47.0	82.5	964.3	80.1	.0392
.69	49.5	78.1	.71	48.3	82.5	964.3	80.3	.0352
.60	49.5	79.5	.60	48.3	81.6	964.2	80.5	.0304
.50	49.9	79.3	.50	48.9	83.1	964.3	81.2	.0258
.41	50.2	79.9	.40	49.7	82.5	964.3	81.7	.0209
.31	50.1	80.4	.30	49.5	82.9	964.3	82.2	.0157
.26	50.1	81.3	.25	49.9	84.3	964.3	82.8	.0133
.21	50.2	81.8	.21	49.9	84.6	964.2	83.2	.0109
.14	49.7	82.5	.13	49.3	84.9	964.2	83.7	.0070

TABLE 80

PAGE: 2
DATE: 7-8-76

FLOW RATE VERSUS DIFFERENTIAL PRESSURE

CLEAN CONDITION-FLOW RATE VERSUS DIFFERENTIAL
PRESSURE (TEST SPECIMEN S/M 020) INLET
PRESSURE 1,000 PSIA (NOMINAL)

TEST NUMBER SE PART F TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GRASS DIFF. PRESS PRIMARY (PSID)	GRASS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
976.4	88.6	.0072	7.323	7.613	7.468	-0.000	7.468
976.4	88.3	.113	11.915	12.236	12.075	-0.000	12.076
972.3	88.0	.018	14.752	15.150	14.951	-0.000	14.951
972.3	87.7	.0160	17.467	17.838	17.652	-0.000	17.653
972.3	86.8	.0213	24.095	24.367	24.231	-0.000	24.231
972.3	85.9	.0257	29.990	30.279	30.135	-0.000	30.135
972.3	84.7	.0374	36.597	36.950	36.772	-0.000	36.774
968.3	83.7	.0355	43.731	44.154	43.943	-0.000	43.943
968.3	82.2	.0400	49.981	50.251	50.116	-0.000	50.116
964.3	81.3	.0415	56.998	57.420	57.259	-0.000	57.259
964.3	80.2	.0444	57.248	57.520	57.384	-0.000	57.385
964.3	80.1	.0392	49.619	49.619	49.619	-0.000	49.619
964.3	80.3	.0352	43.312	43.750	43.531	-0.000	43.532
964.3	80.5	.0304	36.357	36.719	36.538	-0.000	36.538
964.3	81.2	.0258	30.231	30.451	30.341	-0.000	30.341
964.3	81.7	.0219	23.794	23.999	23.851	-0.000	23.851
964.3	82.2	.0157	17.407	17.437	17.422	-0.000	17.422
964.3	82.8	.0133	14.451	14.521	14.486	-0.000	14.486
964.3	83.2	.0119	11.734	11.722	11.728	-0.000	11.728
964.3	83.7	.0070	7.323	7.271	7.297	-0.000	7.297

$$\text{GROSS DIFF. PRESS} = -1.64000E-04 + -1.26930E-02 (\text{ACFM}) + 2.48070E-01 (\text{ACFM})^2 +$$

$$0 (\text{ACFM})^3$$

TABLE 80
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 3
DATE: 7-8-76

CLEAN CONDITION-FLOW RATE VERSUS DIFFERENTIAL PRESSURE (TEST SPECIMEN S/N,020) INLET PRESSURE 1,000 PSIA (NOMINAL)

TEST NUMBER SE		PART F		TEST DESCRIPTION		TEST SPECIMEN INLET CONDITIONS				NET DIFFERENTIAL PRESS		

PRESSURE		TEMPERATURE			FLOW RATE							

KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ICFM	SCFM	GN ₂ KG/HR	GN ₂ LRS/HR	KG/SQ CM DIFFERENTIAL	PSID	
68.635	976.2	304.6	31.4	88.6	12.4	.0072	.462	1.902	2.004	.5251	7.468	
68.635	976.2	304.4	31.3	88.3	20.1	.0113	.728	1.434	3.162	.8490	12.076	
68.357	972.2	304.3	31.1	88.0	24.6	.0138	.885	1.742	3.840	1.0512	14.951	
68.357	972.2	304.1	31.0	87.7	28.5	.0160	1.026	2.020	4.454	1.2411	17.053	
68.357	972.2	303.6	30.5	86.8	32.0	.0213	1.366	2.694	5.932	1.7036	24.231	
68.357	972.2	303.1	30.0	85.9	46.2	.0257	1.648	3.249	7.156	2.1187	30.135	
68.357	972.2	302.5	29.3	84.7	55.1	.0304	1.954	3.847	8.480	2.5854	36.774	
68.078	968.2	301.9	28.7	83.7	64.6	.0355	2.280	4.490	9.898	3.0895	43.943	
68.078	968.2	301.0	27.9	82.2	73.3	.0400	2.577	5.072	11.188	3.5235	50.116	
67.800	964.2	300.5	27.4	81.3	81.0	.0445	2.859	5.630	12.411	4.0257	57.259	
67.800	964.2	299.9	26.8	80.2	81.1	.0444	2.859	5.622	12.411	4.0345	57.385	
67.800	964.2	299.9	26.7	80.1	71.5	.0392	2.524	4.971	10.958	1.7444	24.811	
67.800	964.2	300.0	26.8	80.3	64.1	.0352	2.264	4.458	9.828	3.0606	43.532	
67.800	964.2	300.1	27.0	80.5	54.9	.0304	1.954	3.848	8.484	2.5689	36.538	
67.800	964.2	300.5	27.3	81.2	46.3	.0258	1.656	3.261	7.189	2.1332	30.341	
67.800	964.2	300.7	27.6	81.7	37.3	.0209	1.341	2.641	5.823	1.6769	23.851	
67.800	964.2	301.0	27.9	82.2	27.9	.0157	1.004	1.972	4.360	1.2249	17.422	
67.800	964.2	301.4	28.2	82.8	23.5	.0133	.850	1.673	3.689	1.0185	14.486	
67.800	964.2	301.6	28.4	83.2	19.3	.0109	.699	1.372	3.034	.8246	11.728	
67.800	964.2	301.9	28.7	83.7	12.2	.0070	.450	.882	1.952	.5130	7.297	
*****	*****	*****	*****	*****								
68.050	967.2	301.9	28.7	83.7								
.276	3.2	1.4	1.4	2.5	DEVIATIONS							

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 81
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 1
DATE: 7/8/76

TEST NUMBER 11A PART A TEST DESCRIPTION

CONTAMINATED CONDITION-FLOW RATE VERSUS
DIFFERENTIAL PRESSURE, TOTAL OF 4.9 mg OF
SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN
(S/N 020) INLET PRESSURE 1000 PSIA (NOMINAL)
TEST SPECIMEN INLET CONDITIONS

FLOWMETER CONDITIONS

FLOWMETER ONE *****			FLOWMETER TWO *****			TEST SPECIMEN INLET CONDITIONS *****		
FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.87	49.9	74.7	.91	47.8	79.1	992.1	76.9	.0438
.78	49.9	74.4	.81	48.3	78.8	992.1	76.6	.0393
.69	49.7	74.6	.71	48.3	78.8	992.1	76.7	.0345
.60	50.1	75.9	.61	48.9	78.9	992.1	76.9	.0301
.50	50.1	75.6	.50	49.3	79.4	992.1	77.5	.0252
.41	49.5	75.2	.40	48.9	79.7	992.1	78.0	.0200
.31	49.9	77.1	.31	49.3	80.4	992.1	78.7	.0155
.27	49.9	77.8	.26	49.3	80.9	992.1	79.3	.0131
.22	49.9	78.7	.21	49.5	81.3	992.1	80.0	.0106
.14	49.5	79.4	.13	49.3	81.7	992.1	80.5	.0067
.14	49.7	80.5	.13	49.3	82.3	992.1	81.4	.0067
.23	49.3	80.4	.22	48.9	82.5	992.1	81.4	.0110
.26	49.9	81.2	.25	49.5	82.5	992.1	81.4	.0130
.32	49.9	80.0	.31	49.3	82.6	992.1	81.3	.0157
.41	49.9	79.2	.41	49.3	82.5	992.1	80.9	.0204
.51	49.7	78.4	.51	48.7	82.1	992.1	80.3	.0251
.60	49.9	77.6	.60	48.7	81.6	992.1	79.6	.0298
.69	49.5	76.8	.70	48.3	81.1	992.1	78.9	.0343
.78	49.5	75.9	.81	47.8	81.2	992.1	78.0	.0388
.87	50.1	75.2	.91	47.9	79.6	992.1	77.4	.0439

TABLE 81

FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 2
DATE: 7/8/76

CONTAMINATED CONDITION-FLOW RATE VERSUS
DIFFERENTIAL PRESSURE, TOTAL OF 4.9 mg OF
SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN
(S/N 020) INLET PRESSURE 1000 PSIA (NOMINAL)

TEST NUMBER 11A PART A TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (SCFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
992.1	76.9	.0438	56.858	57.449	57.153	-0.000	57.153
992.1	76.6	.0393	49.599	51.189	49.894	-0.000	49.894
992.1	76.7	.0345	43.586	43.253	43.420	-0.000	43.420
992.1	76.9	.0301	37.179	36.922	37.050	-0.000	37.051
992.1	77.5	.0252	31.262	29.973	30.117	-0.000	30.118
992.1	78.0	.0200	23.333	23.030	23.186	-0.000	23.186
992.1	78.7	.0155	17.581	17.320	17.450	-0.000	17.450
992.1	79.3	.0131	14.576	14.407	14.492	-0.000	14.492
992.1	80.0	.0106	11.569	11.384	11.476	-0.000	11.477
992.1	80.5	.0067	7.117	6.996	7.056	-0.000	7.057
992.1	81.4	.0067	6.991	6.996	6.994	-0.000	6.994
992.1	81.4	.0110	11.820	11.840	11.830	-0.000	11.830
992.1	81.4	.0130	14.200	14.266	14.218	-0.000	14.218
992.1	81.3	.0157	17.643	17.663	17.653	-0.000	17.653
992.1	80.9	.0204	23.520	23.497	23.509	-0.000	23.509
992.1	80.3	.0251	29.950	29.808	29.904	-0.000	29.904
992.1	79.6	.0298	36.432	36.290	36.361	-0.000	36.361
992.1	78.9	.0343	42.964	42.792	42.878	-0.000	42.879
992.1	78.0	.0388	48.971	49.557	49.265	-0.000	49.266
992.1	77.4	.0439	56.983	57.440	57.216	-0.000	57.216

TARE DIFF. PRESS = -1.64000E-04 + -1.26930E-02 (ACFM) + 2.48070E-01 (ACFM)**2 + 0 (ACFM)**3

TABLE 81
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 3
DATE: 7/8/76

TEST NUMBER 11A PART A TEST DESCRIPTION

CONTAMINATED CONDITION-FLOW RATE VERSUS
DIFFERENTIAL PRESSURE, TOTAL OF 4.9 mg OF
SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN
(S/N 020) INLET PRESSURE 1000 PSIA (NOMINAL)

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESS

PRESSURE		TEMPERATURE			FLOW RATE					NET DIFFERENTIAL PRESS	
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN2 KG/HR	GN2 LB5/HR	KG/SQ CM DIFFERENTIAL	PSID
69.750	992.1	298.1	24.9	76.9	82.8	.438	2.917	5.742	12.661	4.0183	57.153
69.750	992.1	298.0	24.8	76.6	74.6	.0393	2.621	5.161	11.378	3.5079	49.894
69.750	992.1	298.0	24.8	76.7	65.1	.0345	2.301	4.530	9.988	3.0527	43.420
69.750	992.1	298.1	25.0	76.9	56.4	.0301	2.005	3.948	8.703	2.6049	37.051
69.750	992.1	298.4	25.3	77.5	47.0	.0252	1.677	3.302	7.280	2.1175	30.118
69.750	992.1	298.7	25.5	78.0	37.0	.0200	1.333	2.624	5.786	1.6301	23.186
69.750	992.1	299.1	26.0	78.7	28.6	.0155	1.029	2.027	4.468	1.2269	17.250
69.750	992.1	299.5	26.2	79.3	24.1	.0121	.868	1.710	3.770	1.0189	14.492
69.750	992.1	299.8	26.7	80.0	19.5	.0106	.703	1.382	3.054	.8069	11.477
69.750	992.1	300.1	27.0	80.5	12.1	.0067	.443	.872	1.922	.4961	7.057
69.750	992.1	300.6	27.5	81.4	11.9	.0067	.440	.861	1.910	.4917	6.994
69.750	992.1	300.6	27.5	81.4	20.0	.0110	.724	1.422	3.143	.8317	11.830
69.750	992.1	300.6	27.4	81.4	23.7	.0132	.856	1.682	3.714	.9997	14.218
69.750	992.1	300.6	27.4	81.3	28.9	.0157	1.038	2.042	4.508	1.2411	17.053
69.750	992.1	300.3	27.1	80.9	37.7	.0204	1.350	2.652	5.861	1.6528	23.509
69.750	992.1	300.0	26.8	80.3	46.7	.0251	1.664	3.272	7.223	2.1025	29.904
69.750	992.1	299.6	26.4	79.6	55.6	.0298	1.976	3.891	8.577	2.5564	36.361
69.750	992.1	299.2	26.1	78.9	64.5	.0343	2.276	4.481	9.878	3.0147	42.879
69.750	992.1	298.7	25.6	78.0	73.0	.0388	2.577	5.072	11.188	3.4637	49.266
69.750	992.1	298.4	25.2	77.4	83.0	.0439	2.925	5.760	12.699	4.0227	57.216
*****	*****	*****	*****	*****							
69.750	992.1	299.3	26.2	79.1							
0	.0	.8	.8	1.5	DEVIATIONS						

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 82 PAGE: 1
FLOW RATE VERSUS DIFFERENTIAL PRESSURE DATE: 7/8/76

TEST NUMBER 11B PART B TEST DESCRIPTION

CONTAMINATED CONDITION-FLOW RATE VERSUS
DIFFERENTIAL PRESSURE, TOTAL OF 4.9 mg OF
SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN
(S/N 020) INLET PRESSURE 415 PSIA (NOMINAL)

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE, (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.88	49.5	74.3	.91	47.6	76.1	418.7	75.2	.1035
.72	49.9	73.8	.81	48.3	75.7	417.4	74.7	.0937
.69	49.9	73.7	.71	48.5	75.5	416.8	74.6	.0827
.54	49.9	73.4	.60	48.7	75.3	416.1	74.3	.0713
.50	50.1	73.4	.50	49.3	75.3	416.1	74.3	.0601
.41	50.1	73.6	.40	49.3	75.3	415.5	74.4	.0484
.31	49.9	73.6	.30	49.5	75.3	415.5	74.4	.0368
.31	49.9	73.6	.30	49.3	75.3	415.5	74.4	.0367
.29	50.1	73.7	.25	49.9	75.3	415.5	74.5	.0311
.22	50.1	73.8	.21	49.9	75.3	415.5	74.5	.0254
.15	49.9	73.9	.14	49.9	75.3	416.1	74.6	.0170
.12	49.5	74.4	.14	49.1	75.7	416.1	75.0	.0168
.22	49.5	74.1	.21	49.3	75.3	416.1	74.7	.0259
.27	49.9	73.9	.26	49.5	75.2	416.1	74.5	.0315
.32	50.1	73.8	.31	49.7	75.2	415.5	74.5	.0379
.41	49.9	73.7	.41	49.3	75.2	415.5	74.4	.0489
.51	50.1	73.6	.50	49.3	75.2	415.5	74.4	.0604
.60	49.9	73.6	.61	48.7	75.2	414.2	74.4	.0719
.69	49.7	73.6	.71	48.3	75.0	413.5	74.3	.0830
.78	49.5	73.7	.81	47.9	75.0	412.9	74.4	.0938

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 82
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 2
DATE: 7/8/76

TEST NUMBER 11B PART B TEST DESCRIPTION

CONTAMINATED CONDITION FLOW RATE VERSUS
DIFFERENTIAL PRESSURE TOTAL OF 4.9 mg OF
~~SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN~~
(S/N 020) INLET PRESSURE 4.5 PSIA (NOMINAL)

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)
.88	49.9	73.6

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)
.91	47.8	74.9

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
412.9	74.3	.1055

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 82
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 3
DATE: 7/8/76

TEST NUMBER 11B			PART B		TEST DESCRIPTION		
TEST SPECIMEN INLET CONDITIONS			CONTAMINATED CONDITION-FLOW RATE VERSUS DIFFERENTIAL PRESSURE TOTAL OF 4.9 mg OF SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN (S/N 020) INLET PRESSURE 415 PSIA (NOMINAL)				

AVG PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
418.7	75.2	.1035	168.453	168.453	168.453	.002	168.451
417.4	74.7	.0937	143.169	143.169	143.169	.001	143.167
416.8	74.6	.0827	119.465	119.465	119.465	.001	119.464
416.1	74.3	.0713	97.974	97.974	97.974	.001	97.973
416.1	74.3	.0601	77.882	78.695	78.289	.000	78.287
415.5	74.4	.0484	59.520	60.049	59.784	.000	59.783
415.5	74.4	.0368	-0.001	.000	-0.000	.000	-0.002
415.5	74.4	.0367	44.043	43.788	43.916	.000	43.914
415.5	74.5	.0311	36.172	35.894	36.033	.000	36.032
415.5	74.5	.0254	28.969	28.594	28.781	.000	28.780
416.1	74.6	.0170	18.699	18.448	18.574	.000	18.572
416.1	75.0	.0168	18.201	18.162	18.181	.000	18.180
416.1	74.7	.0259	29.404	29.225	29.315	.000	29.313
416.1	74.5	.0315	36.793	36.527	36.660	.000	36.658
415.5	74.5	.0379	45.405	45.058	45.232	.000	45.230
415.5	74.4	.0489	60.021	60.681	60.351	.000	60.349
415.5	74.4	.0604	78.006	78.695	78.351	.000	78.349
414.2	74.4	.0719	98.922	98.922	98.922	.001	98.921
413.5	74.3	.0830	120.414	120.414	120.414	.001	120.412
412.9	74.4	.0938	143.801	143.801	143.801	.001	143.799

TABLE 82
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 4
DATE: 7/8/76

TEST NUMBER 118

PART B

TEST DESCRIPTION

CONTAMINATED CONDITION-FLOW RATE VERSUS
DIFFERENTIAL PRESSURE, TOTAL OF 4.9 mg OF
SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN
(S/N 020) INLET PRESSURE 415 PSIA (NOMINAL)

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS		AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
			DIFF. PRESS PRIMARY (PSID)	DIFF. PRESS SECONDARY (PSID)			
412.9	74.3	.1055	173.509	173.509	173.509	.002	173.508

$$\text{TARE DIFF. PRESS} = -3.40000\text{E-05} + -4.44000\text{E-04 (ACFM)} + 1.50933\text{E-01 (ACFM)**2} + 0 \text{ (ACFM)**3}$$

TABLE 82
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 5
DATE: 7/8/76

TEST NUMBER 11B PART B TEST DESCRIPTION

CONTAMINATED CONDITION-FLOW RATE VERSUS
DIFFERENTIAL PRESSURE TOTAL OF 4.9 mg OF
SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN
(S/N 020) INLET PRESSURE 415 PSIA (NOMINAL)

TEST SPECIMEN INLET CONDITIONS											NET DIFFERENTIAL PR	
*****											*****	
PRESSURE		TEMPERATURE			FLOW RATE							
*****											*****	
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID	
29.438	418.7	297.2	24.0	75.2	82.7	1.035	2.920	5.750	12.676	11.8433	168.451	
29.347	417.4	296.9	23.7	74.7	74.7	.937	2.636	5.190	11.442	10.0657	143.167	
29.342	416.8	296.8	23.7	74.6	65.6	.827	2.324	4.577	10.090	8.3991	119.464	
29.236	416.1	296.7	23.5	74.3	56.1	.713	2.001	3.940	8.686	6.8882	97.973	
29.256	416.1	296.7	23.5	74.3	47.3	.601	1.687	3.322	7.324	5.5041	78.287	
29.210	415.5	296.7	23.6	74.4	37.7	.484	1.358	2.673	5.893	4.2031	59.783	
29.210	415.5	296.7	23.6	74.4	28.6	.367	1.029	2.026	4.468	3.0875	43.914	
29.210	415.5	296.8	23.6	74.5	24.2	.311	.872	1.716	3.784	2.5333	36.032	
29.210	415.5	296.8	23.6	74.5	19.7	.254	.712	1.402	3.090	2.0234	28.780	
29.256	416.1	296.8	23.7	74.6	13.0	.170	.478	.941	2.075	1.3057	18.572	
29.256	416.1	297.1	23.9	75.0	12.8	.168	.472	.930	2.050	1.2782	18.180	
29.256	416.1	296.9	23.7	74.7	20.1	.259	.726	1.430	3.152	2.0609	29.313	
29.256	416.1	296.8	23.6	74.5	24.5	.315	.884	1.740	3.836	2.5773	36.658	
29.210	415.5	296.8	23.6	74.5	29.7	.379	1.063	2.094	4.616	3.1800	45.230	
29.210	415.5	296.7	23.6	74.4	38.2	.489	1.369	2.696	5.944	4.2430	60.349	
29.210	415.5	296.7	23.6	74.4	47.4	.604	1.693	3.333	7.348	5.5085	78.349	
29.119	414.2	296.7	23.6	74.4	56.5	.719	2.009	3.957	8.723	6.9548	98.921	
29.073	413.5	296.7	23.5	74.3	65.4	.830	2.317	4.562	10.057	8.4658	120.421	
29.028	412.9	296.7	23.5	74.4	73.9	.938	2.614	5.148	11.349	10.1101	143.799	

TABLE 82
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 6
DATE: 7/8/76

TEST NUMBER 118 PART B

TEST DESCRIPTION

CONTAMINATED CONDITION-FLOW RATE VERSUS
DIFFERENTIAL PRESSURE TOTAL OF 4.9 mg OF
SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN
(S/N 020) INLET PRESSURE 415 PSIA (NOMINAL)
NET DIFFERENTIAL PR

TEST SPECIMEN INLET CONDITIONS

PRESSURE		TEMPERATURE			FLOW RATE						
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PS
29.028	412.9	296.6	23.5	74.3	83.0	1.055	2.939	5.788	12.760	12.1988	173.
****	****	****	****	****							
29.217	415.6	296.8	23.6	74.5							
.064	.9	.1	.1	.2	DEVIATIONS						

TABLE 83
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 1
DATE: 7/8/76

TEST NUMBER 11C PART C TEST DESCRIPTION

CONTAMINATED CONDITION-FLOW RATE VERSUS
DIFFERENTIAL PRESSURE, TOTAL OF 11.3 mg OF
SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN
(S/N 020) INLET PRESSURE 1000PSIA (NOMINAL)
TEST SPECIMEN INLET CONDITIONS

FLOWMETER CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.86	42.7	75.7	.91	47.6	78.7	1004.0	75.7	.0428
.78	42.9	77.9	.81	48.1	77.7	1004.0	74.8	.0389
.69	40.1	77.7	.71	48.7	77.1	1004.0	74.4	.0343
.60	44.9	77.9	.61	48.7	77.3	1004.0	74.6	.0298
.50	40.1	72.2	.50	49.1	77.3	1000.0	74.8	.0250
.41	40.2	73.4	.41	49.5	77.7	1000.0	75.3	.0204
.31	40.1	73.7	.30	49.5	78.2	1000.0	75.9	.0153
.26	42.9	74.2	.26	49.7	78.4	1000.0	76.3	.0130
.22	42.5	75.0	.21	49.1	78.8	1000.0	76.9	.0105
.15	42.5	76.1	.14	49.2	79.6	1000.0	77.9	.0070
.15	40.2	77.8	.14	49.9	80.7	1004.0	79.2	.0070
.23	45.3	77.8	.22	47.9	80.9	1004.0	79.4	.0107
.26	42.5	78.0	.26	49.1	81.1	1004.0	79.6	.0128
.32	42.9	77.9	.31	49.3	81.1	1004.0	79.5	.0155
.41	42.5	77.6	.40	48.9	81.1	1004.0	79.3	.0199
.50	42.9	76.8	.50	49.1	80.6	1004.0	78.7	.0248
.60	40.1	75.8	.60	49.1	80.6	1000.0	77.9	.0297
.69	42.5	74.7	.71	48.2	79.2	1000.0	76.9	.0342
.78	42.9	74.0	.81	48.3	78.7	1000.0	76.3	.0388
.87	42.7	72.4	.91	47.6	78.1	1000.0	75.7	.0433

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 83
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 2
DATE: 7/8/76

CONTAMINATED CONDITION-FLOW RATE VERSUS
DIFFERENTIAL PRESSURE, TOTAL OF 11.3 mg OF
SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN
(S/N 020) INLET PRESSURE 1000PSIA (NOMINAL)

TEST NUMBER 11C	PART C	TEST DESCRIPTION	TEST SPECIMEN INLET CONDITIONS *****				
PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
1004.0	15.7	.0428	55.940	56.817	56.379	-0.000	56.379
1004.0	14.8	.0389	49.683	50.514	50.094	-0.000	50.094
1004.0	14.4	.0393	43.919	43.599	43.754	-0.000	43.754
1004.0	14.6	.0298	37.274	36.922	37.098	-0.000	37.098
1000.0	14.8	.0250	30.32	29.973	30.148	-0.000	30.147
1000.0	15.3	.0274	23.971	23.611	23.791	-0.000	23.791
1000.0	15.9	.0153	17.425	17.26	17.315	-0.000	17.316
1000.0	16.3	.0130	14.520	14.243	14.400	-0.000	14.407
1000.0	16.9	.0115	11.480	11.271	11.379	-0.000	11.379
1004.0	17.9	.0070	7.463	7.138	7.400	-0.000	7.400
1004.0	19.2	.0070	7.463	7.451	7.457	-0.000	7.457
1004.0	19.4	.017	11.674	11.726	11.700	-0.000	11.700
1004.0	19.6	.0128	14.272	14.293	14.283	-0.000	14.283
1004.0	19.5	.0155	17.611	17.616	17.608	-0.000	17.608
1004.0	19.3	.0199	23.292	23.268	23.280	-0.000	23.280
1004.0	18.7	.0248	29.951	29.818	29.904	-0.000	29.905
1000.0	17.9	.0297	36.844	36.750	36.797	-0.000	36.797
1000.0	16.9	.0342	43.541	43.426	43.482	-0.000	43.484
1000.0	16.2	.0388	49.433	5.189	49.811	-0.000	49.811
1000.0	15.7	.0433	56.942	57.764	57.352	-0.000	57.353

$$\text{TARE DIFF. PRESS} = -1.64000E-04 + -1.26930E-02 (\text{ACFM}) + 2.48070E-01 (\text{ACFM})^{**2} + 0 (\text{ACFM})^{**3}$$

TABLE 83
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 3
DATE: 7/8/76

CONTAMINATED CONDITION-FLOW RATE VERSUS
DIFFERENTIAL PRESSURE, TOTAL OF 11.3 mg OF
SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN
(S/N 020) INLET PRESSURE 1000 PSIA (NOMINAL)

TEST NUMBER 11C PART C TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESS

PRESSURE		TEMPERATURE			FLOW RATE						NET DIFFERENTIAL PRESS		
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LIT-RS/ MIN	CFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID		
70.586	1004.0	297.4	24.3	75.7	82.1	.428	2.892	5.094	12.554	3.9638	56.379		
70.586	1004.0	296.9	23.8	74.8	74.7	.389	2.633	5.182	11.432	3.5219	50.094		
70.586	1004.0	296.7	23.6	74.4	65.7	.344	2.323	4.574	10.083	3.0762	43.154		
70.586	1004.0	296.8	23.7	74.6	56.6	.298	2.015	3.961	8.745	2.6083	37.098		
70.307	1000.0	296.9	23.8	74.8	47.2	.251	1.685	3.512	7.317	2.1195	30.247		
70.307	1000.0	297.2	24.1	75.3	38.3	.204	1.375	2.701	5.968	1.6727	23.191		
70.307	1000.0	297.6	24.4	75.9	28.7	.153	1.030	2.122	4.472	1.2174	17.216		
70.307	1000.0	297.8	24.6	76.3	24.2	.113	.871	1.712	3.781	1.0129	14.207		
70.307	1000.0	298.1	24.9	76.9	19.4	.085	.712	1.384	3.048	.8000	11.279		
70.586	1004.0	298.6	25.5	77.9	12.8	.071	.471	.921	2.043	.5203	7.200		
70.586	1004.0	299.4	26.2	79.2	12.9	.07	.473	.931	2.053	.5243	7.257		
70.586	1004.0	299.5	26.3	79.4	19.8	.107	.715	1.402	3.106	.8226	11.700		
70.586	1004.0	299.6	26.4	79.6	23.8	.128	.858	1.682	3.723	1.0042	14.283		
70.586	1004.0	299.6	26.4	79.5	28.8	.155	1.039	2.142	4.510	1.2380	17.208		
70.586	1004.0	299.4	26.3	79.3	37.2	.199	1.335	2.622	5.796	1.6367	23.280		
70.586	1004.0	299.1	25.9	78.7	46.7	.248	1.664	3.271	7.224	2.1025	29.205		
70.307	1000.0	298.7	25.5	77.9	56.2	.297	1.994	3.922	8.654	2.5871	36.197		
70.307	1000.0	298.1	25.1	76.9	65.0	.347	2.298	4.522	9.976	3.0572	43.284		
70.307	1000.0	297.8	24.6	76.3	74.1	.388	2.611	5.141	11.334	3.5021	49.211		
70.307	1000.0	297.4	24.3	75.7	82.6	.433	2.917	5.742	12.664	4.0323	57.253		
*****	*****	*****	*****	*****									
70.461	1002.0	298.1	25.0	77.0									
.138	.05	.9	.9	1.6	DEVIATIONS								

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 84
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 1
DATE: 7-8-76

TEST NUMBER 110 \ PART 0 TEST DESCRIPTION

CONTAMINATED CONDITION - FLOW RATE versus
DIFFERENTIAL PRESSURE. TOTAL OF 11.3 mg
OF SYNTHETIC CONTAMINANT ADDED. TEST
SPECIMEN (S/N 020) INLET PRESSURE 415 PSIA (NOMINAL)
TEST SPECIMEN INLET CONDITIONS

FLOWMETER CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.88	49.5	86.9	.92	47.4	82.2	412.9	81.5	.1051
.78	50.4	87.9	.81	48.7	82.2	412.2	81.6	.0957
.69	50.2	87.9	.70	48.9	82.3	411.6	81.6	.0835
.60	50.1	87.9	.61	49.1	82.4	410.9	81.7	.0730
.51	49.9	86.9	.51	48.9	82.5	410.9	81.7	.0610
.41	50.4	87.9	.41	49.9	82.5	410.9	81.7	.0499
.32	49.9	87.2	.31	49.5	82.6	410.9	81.9	.0379
.27	49.9	87.4	.26	49.3	82.8	411.6	82.1	.0315
.22	49.9	87.8	.21	49.7	83.0	411.6	82.4	.0258
.15	50.1	88.1	.13	49.9	83.3	411.6	82.7	.0170
.15	49.5	87.4	.13	49.3	83.5	412.2	82.9	.0188
.21	50.2	87.5	.20	49.9	83.7	412.2	83.1	.0254
.27	49.9	87.7	.26	49.5	83.5	411.6	82.8	.0319
.32	49.5	87.9	.31	48.9	83.3	411.6	82.6	.0374
.41	49.9	87.5	.40	49.1	83.2	410.9	82.3	.0492
.51	49.9	87.3	.50	49.1	83.0	410.9	82.2	.0609
.60	49.7	87.1	.60	48.5	82.8	410.3	82.0	.0721
.69	50.2	87.1	.71	48.7	82.7	409.6	81.9	.0847
.78	50.2	87.1	.81	48.5	82.5	418.7	81.8	.0937
.87	49.9	87.1	.91	47.8	82.4	418.1	81.8	.1041

TABLE 84
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 2

DATE: 7-8-76

TEST NUMBER IID	PART D	TEST DESCRIPTION	CONTAMINATED CONDITION - FLOW RATE versus DIFFERENTIAL PRESSURE. TOTAL OF 11.3 mg OF SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN (S/N 020) INLET PRESSURE 415 PSIA (NOMINAL).				
TEST SPECIMEN INLET CONDITIONS			*****				
PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GRASS DIFF. PRESS PRIMARY (PSID)	GRASS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
412.2	81.5	.1051	183.709	183.709	183.702	.002	183.708
412.2	81.6	.0957	155.616	155.616	155.616	.001	155.615
411.0	81.6	.0835	127.208	127.208	127.208	.001	127.206
410.2	81.7	.0730	105.428	105.428	105.428	.001	105.426
410.2	81.7	.0610	82.199	82.116	82.608	.001	82.606
410.2	81.7	.0499	63.533	64.393	63.963	.000	63.961
410.2	81.9	.0379	46.785	46.597	46.691	.000	46.689
411.0	82.1	.0315	38.144	37.842	37.943	.000	37.942
411.0	82.4	.0258	30.148	29.915	30.032	.000	30.030
411.0	82.7	.0170	19.111	18.863	19.002	.000	19.000
412.2	82.9	.0168	18.787	18.749	18.728	.000	18.726
412.2	83.1	.0254	29.654	29.456	29.555	.000	29.554
411.0	82.8	.0319	38.414	38.310	38.358	.000	38.357
411.0	82.6	.0374	46.232	46.020	46.126	.000	46.124
410.2	82.3	.0492	62.657	63.446	63.052	.000	63.050
410.2	82.2	.0609	82.446	83.332	82.882	.000	82.887
410.2	82.0	.0721	103.849	103.849	103.842	.001	103.848
409.0	81.9	.0847	129.733	129.733	129.732	.001	129.731
418.1	81.8	.0937	149.934	149.934	149.934	.001	149.933
418.1	81.8	.1041	178.659	178.659	178.652	.002	178.657

TARE DIFF. PRESS = -3.40000E-05 + -4.42000E-04 (ACFM) + 1.50933E-01 (ACFM)**2 +

0 (ACFM)**3

TABLE 84
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 3
DATE: 7-8-76

TEST NUMBER 110		PART D			TEST DESCRIPTION		CONTAMINATED CONDITION - FLOW RATE versus DIFFERENTIAL PRESSURE. TOTAL OF 11.3 mg OF SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN (S/N 020) INLET PRESSURE 415 PSIA (NOMINAL). NET DIFFERENTIAL PRESSURE				
TEST SPECIMEN INLET CONDITIONS											
PRESSURE		TEMPERATURE			FLOW RATE						
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID
29.028	412.2	300.7	27.5	81.5	81.7	.1951	2.890	5.690	12.544	12.9159	183.70
28.982	412.2	300.7	27.5	81.6	74.3	.0957	2.626	5.171	11.400	10.9408	155.61
28.937	411.0	300.7	27.6	81.6	64.6	.0835	2.288	4.504	9.930	8.9435	127.20
28.891	410.2	300.7	27.6	81.7	56.1	.0730	1.996	3.922	8.663	7.4122	105.42
28.891	410.2	300.8	27.6	81.7	46.6	.0610	1.668	3.284	7.239	5.8078	82.00
28.891	410.2	300.8	27.6	81.7	38.1	.0499	1.366	2.682	5.928	4.4969	63.26
28.891	410.2	300.9	27.7	81.9	28.8	.0379	1.036	2.032	4.496	3.2826	46.08
28.937	411.0	301.0	27.8	82.1	23.9	.0315	.864	1.700	3.749	2.6676	37.24
28.937	411.0	301.2	28.0	82.4	19.6	.0258	.707	1.392	3.068	2.1113	30.03
28.937	411.0	301.3	28.2	82.7	12.7	.0170	.466	.911	2.022	1.3359	19.00
28.982	412.2	301.5	28.3	82.9	10.5	.0168	.460	.900	1.998	1.3166	18.72
28.982	412.2	301.5	28.4	83.1	19.2	.0254	.696	1.370	3.021	2.0778	29.55
28.937	411.0	301.4	28.2	82.8	24.2	.0319	.872	1.710	3.787	2.6967	38.35
28.937	411.0	301.3	28.1	82.6	28.5	.0374	1.022	2.014	4.436	3.2429	46.12
28.891	410.2	301.1	28.0	82.3	37.3	.0492	1.343	2.647	5.830	4.4329	63.05
28.891	410.2	301.0	27.9	82.2	46.6	.0609	1.664	3.270	7.223	5.8276	82.08
28.845	410.2	300.9	27.8	82.0	55.1	.0721	1.967	3.874	8.537	7.3012	103.84
28.800	409.0	300.9	27.7	81.9	65.0	.0847	2.308	4.544	10.018	9.1210	129.73
29.438	416.1	300.8	27.6	81.8	73.8	.0937	2.612	5.142	11.339	10.5413	149.93
29.393	416.1	300.8	27.6	81.8	81.9	.1041	2.897	5.704	12.575	12.5609	178.65
*****	*****	*****	*****	*****							
28.971	412.1	301.0	27.8	82.1							
.098	1.4	.2	.2	.4	DEVIATIONS						

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 85
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 1
DATE: 7-8-76

TEST NUMBER 11E PART F TEST DESCRIPTION

CONTAMINATED CONDITION - FLOW RATE versus
DIFFERENTIAL PRESSURE. TOTAL OF 16.7 mg
OF SYNTHETIC CONTAMINANT ADDED. TEST
SPECIMEN (S/N 020) INLET PRESSURE 1000 PSIA (NOMINAL).
TEST SPECIMEN INLET CONDITIONS

FLOWMETER CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.86	50.1	67.3	.91	47.9	75.8	992.1	70.0	.0437
.78	50.4	66.8	.81	48.5	72.2	992.1	69.5	.0397
.68	50.2	66.6	.70	48.9	71.8	992.1	69.2	.0344
.60	50.4	66.8	.60	49.3	71.8	992.1	69.3	.0302
.50	49.5	67.2	.51	48.7	71.9	992.1	69.6	.0249
.41	49.9	67.8	.40	49.3	72.2	992.1	70.0	.0204
.31	49.1	68.7	.31	48.7	72.8	992.1	70.7	.0151
.27	50.2	69.5	.26	49.9	73.2	992.1	71.3	.0133
.22	50.2	70.2	.21	49.9	73.5	992.1	71.6	.0107
.15	49.9	70.9	.14	49.9	74.0	992.1	72.4	.0072
.15	49.7	72.2	.14	49.5	74.7	992.1	73.4	.0072
.22	49.5	72.2	.21	49.1	74.9	992.1	73.5	.0107
.27	49.5	72.1	.26	49.3	75.0	992.1	73.6	.0136
.32	50.2	71.9	.31	49.9	75.1	992.1	73.8	.0157
.41	50.1	71.4	.41	49.5	75.0	992.1	73.2	.0204
.51	49.5	71.7	.51	48.5	74.7	992.1	72.7	.0250
.60	49.5	69.7	.60	48.3	74.1	992.1	71.9	.0296
.69	49.9	69.0	.71	48.5	73.6	988.1	71.3	.0348
.78	49.5	68.2	.81	47.6	73.1	988.1	70.6	.0390
.87	49.5	67.5	.91	47.4	72.3	988.1	69.9	.0436

TABLE 85
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 2
DATE: 7-8-76

TEST NUMBER 11E PART E TEST DESCRIPTION

CONTAMINATED CONDITION - FLOW RATE versus DIFFERENTIAL PRESSURE. TOTAL OF 16.7 mg OF SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN (S/N 020) INLET PRESSURE 1000 PSIA (NOMINAL).

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
992.1	70.0	.0437	58.641	59.417	59.029	-0.000	59.029
992.1	69.5	.0397	51.874	52.464	52.169	-0.000	52.169
992.1	69.2	.0344	44.799	44.420	44.659	-0.000	44.659
992.1	69.3	.0312	38.372	38.163	38.217	-0.000	38.217
992.1	69.6	.0249	30.570	30.240	30.405	-0.000	30.406
992.1	70.0	.0204	24.244	23.927	24.086	-0.000	24.086
992.1	70.7	.0151	17.409	17.170	17.290	-0.000	17.290
992.1	71.3	.0133	15.146	14.826	14.936	-0.000	14.936
992.1	71.8	.0117	11.933	11.711	11.837	-0.000	11.837
992.1	72.4	.0172	7.821	7.637	7.729	-0.000	7.727
992.1	73.4	.0172	7.696	7.637	7.664	-0.000	7.664
992.1	73.4	.0107	11.684	11.683	11.684	-0.000	11.684
992.1	73.6	.0130	14.672	14.654	14.663	-0.000	14.663
992.1	73.5	.0157	17.969	17.914	17.941	-0.000	17.942
992.1	73.2	.0206	24.306	24.214	24.260	-0.000	24.260
992.1	72.7	.0250	30.694	30.527	30.611	-0.000	30.611
992.1	71.9	.0296	37.444	37.199	37.321	-0.000	37.322
988.1	71.3	.0348	45.169	44.866	45.018	-0.000	45.018
988.1	70.6	.0390	50.621	51.199	50.910	-0.000	50.910
988.1	69.9	.0436	58.391	59.417	58.904	-0.000	58.904

TARE DIFF. PRESS = $-1.64000E-04 + -1.24937E-02$ (ACFM) + $2.48070E-01$ (ACFM)**2 + 0 (ACFM)**3

TABLE 85

FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 11E PART F TEST DESCRIPTION

CONTAMINATED CONDITION - FLOW RATE versus DIFFERENTIAL PRESSURE. TOTAL OF 16.7 mg OF SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN (S/N 020) INLET PRESSURE 1000 PSIA (NOMINAL). NET DIFFERENTIAL PRESSURE

TEST SPECIMEN INLET CONDITIONS

PRESSURE		TEMPERATURE			FLOW RATE						
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	CFM	SCFM	GN ₂ KG/HR	GN ₂ LBS/HR	KG/SQ CM DIFFERENTIAL	PSID
69.750	992.1	294.3	21.1	70.0	83.9	.0437	2.949	5.806	12.800	4.1502	59.029
69.750	992.1	294.0	20.8	69.5	75.9	.0397	2.680	5.275	11.632	3.6678	52.169
69.750	992.1	293.8	20.7	69.2	65.8	.0344	2.325	4.579	10.095	3.1399	44.959
69.750	992.1	293.9	20.7	69.3	57.5	.0305	2.041	4.015	8.859	2.6869	38.217
69.750	992.1	294.0	20.9	69.6	47.1	.0249	1.680	3.305	7.293	2.1377	30.406
69.750	992.1	294.3	21.1	70.0	38.3	.0204	1.375	2.707	5.969	1.6934	24.086
69.750	992.1	294.7	21.5	70.7	28.3	.0151	1.017	2.002	4.414	1.2156	17.290
69.750	992.1	295.0	21.8	71.3	24.9	.0133	.896	1.764	3.889	1.0501	14.936
69.750	992.1	295.3	22.1	71.8	19.9	.0117	.723	1.423	3.137	.8322	11.837
69.750	992.1	295.6	22.5	72.4	13.2	.0072	.486	.959	2.109	.5432	7.727
69.750	992.1	296.2	23.0	73.4	13.1	.0072	.482	.949	2.093	.5389	7.664
69.750	992.1	296.2	23.1	73.5	19.7	.0107	.715	1.405	3.104	.8215	11.684
69.750	992.1	296.2	23.1	73.6	24.3	.0130	.875	1.722	3.796	1.0309	14.663
69.750	992.1	296.2	23.0	73.5	29.3	.0157	1.055	2.075	4.580	1.2614	17.942
69.750	992.1	296.0	22.9	73.2	38.6	.0206	1.381	2.719	5.993	1.7057	24.260
69.750	992.1	295.8	22.6	72.7	47.2	.0250	1.681	3.310	7.298	2.1522	30.511
69.750	992.1	295.3	22.2	71.9	56.0	.0296	1.989	3.915	8.634	2.6240	37.322
69.471	988.1	295.0	21.8	71.3	66.0	.0348	2.333	4.594	10.128	3.1651	45.018
69.471	988.1	294.6	21.4	70.6	74.0	.0390	2.617	5.152	11.360	3.5794	50.910
69.471	988.1	294.2	21.1	69.9	83.2	.0436	2.932	5.773	12.728	4.1414	58.904
****	****	****	****	****							
69.708	991.2	295.0	21.9	71.4							
.071	1.0	.8	.8	1.4	DEVIATIONS						

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 86
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 1
DATE: 7-8-76

TEST NUMBER 11F PART F TEST DESCRIPTION

CONTAMINATED CONDITION - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. TOTAL OF 16.7 mg
OF SYNTHETIC CONTAMINANT ADDED. TEST
SPECIMEN (S/N Q20) INLET PRESSURE 415 PSIA (NOMINAL).
TEST SPECIMEN INLET CONDITIONS

FLOWMETER CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.88	49.5	77.4	.91	47.5	78.9	412.0	78.1	.1050
.79	51.4	77.5	.81	48.7	79.	411.3	78.2	.0959
.70	56.1	77.5	.71	48.5	79.1	410.7	78.3	.0842
.61	49.9	77.7	.61	48.7	79.3	410.7	78.5	.0734
.51	51.2	77.7	.51	49.2	79.4	410.7	78.6	.0615
.41	50.1	77.9	.40	49.4	79.6	410.7	78.8	.0496
.31	50.1	78.2	.30	49.8	79.7	410.7	79.0	.0375
.26	50.1	78.4	.25	49.8	79.9	410.7	79.1	.0313
.21	50.4	78.6	.20	50.0	80.2	410.7	79.4	.0255
.15	50.1	78.9	.13	49.8	80.2	411.3	79.6	.0170
.15	49.1	78.4	.13	48.8	80.7	412.0	80.1	.0166
.22	50.1	79.4	.21	49.8	80.8	412.0	80.1	.0258
.27	49.9	78.4	.26	49.4	80.8	411.3	80.1	.0321
.32	49.7	79.2	.31	49.2	80.8	411.3	80.0	.0380
.42	50.1	79.1	.41	49.7	80.7	411.3	79.9	.0496
.51	50.1	79.0	.51	49.0	80.7	410.7	79.9	.0617
.60	50.4	78.9	.60	49.2	80.7	410.0	79.8	.0730
.70	49.5	78.4	.71	48.2	80.7	410.0	79.9	.0838
.79	50.2	79.1	.81	48.5	80.7	410.0	79.9	.0959
.88	51.2	79.4	.91	48.3	80.8	419.1	80.1	.1052

TABLE 86
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE 2
DATE 7-8-76

TEST NUMBER 11F

PART F

TEST DESCRIPTION

CONTAMINATED CONDITION - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. TOTAL OF 16.7 mg
OF SYNTHETIC CONTAMINANT ADDED. TEST
SPECIMEN (S/N 020) INLET PRESSURE 415 PSIA (NOMINAL).

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
412.0	78.1	.1058	189.496	189.496	189.496	.002	189.495
411.2	78.2	.0959	160.456	160.456	160.456	.001	160.455
410.1	78.3	.0842	132.048	132.048	132.048	.001	132.046
410.1	78.5	.0734	108.374	108.374	108.374	.001	108.372
410.1	78.6	.0615	84.707	84.707	84.707	.001	84.706
410.1	78.8	.0496	64.498	64.498	64.498	.000	64.498
410.7	79.1	.0375	46.535	46.535	46.535	.000	46.535
410.1	79.1	.0313	37.800	37.800	37.800	.000	37.800
410.1	79.4	.0205	29.74	29.74	29.74	.000	29.74
411.3	79.6	.0171	19.174	19.174	19.174	.000	19.174
412.0	80.1	.0166	18.552	18.552	18.552	.000	18.552
412.0	80.1	.0258	30.298	30.298	30.298	.000	30.298
411.2	80.1	.031	38.915	38.915	38.915	.000	38.915
411.3	80.0	.0380	47.512	47.512	47.512	.000	47.512
411.2	79.9	.0496	64.112	64.112	64.112	.000	64.112
410.7	79.9	.0617	85.138	85.138	85.138	.001	85.137
410.0	79.8	.0730	107.427	107.427	107.427	.001	107.426
410.0	79.9	.0838	131.101	131.101	131.101	.001	131.099
410.0	79.9	.0959	161.403	161.403	161.403	.001	161.402
419.1	80.1	.1052	188.234	188.234	188.234	.002	188.232

TARE DIFF. PRESS = -3.40000E-05 + -4.44006E-04 (ACFM) + 1.50933E-01 (ACFM)**2 +

0 (ACFM)**3

TABLE 86

FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 11F PART F TEST DESCRIPTION

CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE. TOTAL OF 16.7 mg OF SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN (S/N 020) INLET PRESSURE 415 PSIA (NOMINAL). NET DIFFERENTIAL PRESS

TEST SPECIMEN INLET CONDITIONS

PRESSURE		TEMPERATURE			FLOW RATE						
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID
28,963	412.0	298.8	25.6	78.1	82.0	.105	2.899	5.702	12.586	13.3228	189.495
28,918	411.0	298.8	25.7	78.2	74.5	.0959	2.642	5.202	11.470	11.2811	160.455
28,872	410.0	298.9	25.7	78.3	65.0	.0842	2.317	4.564	10.057	9.2838	132.046
28,872	410.0	299.0	25.8	78.5	56.5	.0734	2.019	3.970	8.762	7.6193	108.372
28,872	410.0	299.0	25.9	78.6	47.1	.0615	1.690	3.322	7.337	5.9554	84.706
28,872	410.0	299.1	26.0	78.8	37.8	.0496	1.362	2.682	5.914	4.5122	64.178
28,872	410.0	299.3	26.1	79.0	28.5	.0375	1.030	2.022	4.473	3.2654	46.445
28,872	410.0	299.3	26.2	79.1	23.7	.0313	.861	1.690	3.736	2.6485	37.070
28,872	410.0	299.5	26.3	79.4	19.0	.0255	.700	1.372	3.041	2.0801	29.586
28,918	411.0	299.6	26.4	79.6	12.7	.0170	.469	.922	2.034	1.3358	19.000
28,963	412.0	299.9	26.7	80.1	12.3	.0166	.456	.892	1.981	1.3039	18.546
28,963	412.0	299.9	26.7	80.1	19.6	.0258	.710	1.490	3.081	2.1240	30.210
28,918	411.0	299.9	26.7	80.1	24.4	.0321	.882	1.730	3.830	2.7302	38.832
28,918	411.0	299.8	26.7	80.0	28.9	.0380	1.044	2.050	4.531	3.3305	47.370
28,918	411.0	299.8	26.6	79.9	37.8	.0496	1.363	2.682	5.915	4.5321	64.461
28,872	410.0	299.8	26.6	79.9	47.2	.0617	1.691	3.330	7.341	6.0036	85.391
28,826	410.0	299.7	26.6	79.8	56.0	.0733	1.999	3.930	8.679	7.5527	107.425
28,826	410.0	299.8	26.6	79.9	64.8	.0834	2.295	4.520	9.964	9.2172	131.099
28,826	410.0	299.8	26.6	79.9	74.1	.0959	2.627	5.174	11.403	11.3477	161.402
29,466	419.0	299.9	26.7	80.1	80.2	.1052	2.943	5.794	12.774	13.2340	188.232
****	****	****	****	****							
28,920	411.0	299.5	26.3	79.4							
.068	.4	.4	.4	.6	DEVIATIONS						

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 87
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 1
DATE: 7-8-76

TEST NUMBER 116 PART G TEST DESCRIPTION

CONTAMINATED CONDITION - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. TOTAL OF 24.1 mg
OF SYNTHETIC CONTAMINANT ADDED. TEST
SPECIMEN (S/N 020) INLET PRESSURE 1000 PSIA (NOMINAL).
TEST SPECIMEN INLET CONDITIONS

FLOWMETER CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.86	49.7	75.8	.91	47.6	81.5	1004.0	78.7	.0429
.78	49.9	75.4	.81	48.1	81.7	1004.0	78.2	.0388
.69	49.5	75.7	.71	47.9	80.6	1004.0	77.9	.0339
.60	49.5	75.3	.60	48.3	80.6	1000.0	78.0	.0295
.51	50.1	75.6	.51	49.1	80.6	1000.0	78.1	.0251
.41	49.5	76.1	.41	48.9	80.8	1000.0	78.5	.0202
.31	49.7	76.7	.30	49.3	81.0	1000.0	78.9	.0153
.27	49.5	77.3	.26	49.1	81.3	1000.0	79.3	.0130
.22	49.7	78.0	.21	49.3	81.7	1000.0	79.8	.0107
.15	49.5	78.6	.13	49.3	82.2	1000.0	80.3	.0070
.15	49.1	79.9	.13	48.7	80.6	1000.0	81.2	.0069
.23	49.1	79.8	.22	48.7	82.6	1000.0	81.2	.0108
.27	49.9	79.6	.26	49.7	82.6	1000.0	81.1	.0133
.32	49.7	79.4	.31	49.3	82.6	1000.0	81.0	.0156
.41	49.5	78.8	.41	48.7	82.4	1000.0	80.6	.0201
.50	49.1	78.1	.50	48.3	82.2	1000.0	80.1	.0246
.60	49.7	77.2	.60	48.5	81.7	1000.0	79.5	.0295
.69	49.7	76.0	.71	48.3	80.8	1000.0	78.4	.0343
.78	50.2	74.9	.81	48.5	79.8	996.0	77.4	.0394
.87	49.7	74.0	.91	47.6	78.9	996.0	76.5	.0435

TABLE 87

PAGE: 2
DATE: 7-8-76

FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 116	PART 6	TEST DESCRIPTION	CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE. TOTAL OF 24.1 mg OF SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN (S/N 020) INPUT PRESSURE 1000 PSIA (NOMINAL).				
TEST SPECIMEN INLET CONDITIONS			*****				
PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
1004.0	78.7	.0429	59.694	60.214	59.954	-0.000	59.954
1004.0	78.2	.0388	52.559	53.279	52.919	-0.000	52.919
1004.0	77.9	.0339	45.697	45.329	45.468	-0.000	45.468
1000.0	78.0	.0295	38.579	38.254	38.382	-0.000	38.382
1000.0	78.1	.0251	31.777	31.482	31.629	-0.000	31.627
1000.0	78.4	.0202	24.524	24.211	24.367	-0.000	24.367
1000.0	78.9	.0153	17.947	17.698	17.822	-0.000	17.822
1000.0	79.3	.0134	14.844	14.617	14.729	-0.000	14.729
1000.0	79.8	.0107	12.177	11.939	12.053	-0.000	12.053
1000.0	80.3	.0070	7.562	7.442	7.502	-0.000	7.502
1000.0	81.2	.0069	7.438	7.385	7.411	-0.000	7.412
1000.0	81.2	.0108	12.10	12.110	12.107	-0.000	12.108
1000.0	81.1	.0133	15.151	15.188	15.169	-0.000	15.170
1000.0	81.0	.0156	18.195	18.154	18.175	-0.000	18.175
1000.0	80.6	.0201	24.276	24.211	24.243	-0.000	24.243
1000.0	80.1	.0246	30.842	30.737	30.790	-0.000	30.790
1000.0	79.5	.0295	38.448	38.254	38.351	-0.000	38.351
1000.0	78.4	.0343	46.038	45.789	45.914	-0.000	45.914
996.0	77.4	.0394	53.185	54.224	53.705	-0.000	53.705
996.0	76.5	.0435	60.570	61.475	61.023	-0.000	61.023

$$\text{TARE DIFF. PRESS} = -1.64000\text{E-04} + -1.26930\text{E-02 (ACFM)} + 2.48070\text{E-01 (ACFM)**2} + \dots \text{(ACFM)**3}$$

TABLE 87
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 3
DATE: 7-8-76

TEST NUMBER 11G PART G TEST DESCRIPTION

CONTAMINATED CONDITION - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. TOTAL OF 24.1 mg
OF SYNTHETIC CONTAMINANT ADDED. TEST
SPECIMEN (S/N 020) INPUT PRESSURE 1000 PSIA (NOMINAL).
NET DIFFERENTIAL PRESS

TEST SPECIMEN INLET CONDITIONS

PRESSURE		TEMPERATURE			FLOW RATE				DIFFERENTIAL PRESSURE			
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	CFM	SCFM	GN2 KG/HR	GN2 LBS/HR	PSID		
70.586	1004.0	299.1	25.9	78.7	87.9	.7429	2.882	5.674	72.509	4.2152	59.254	
70.586	1004.0	298.8	25.7	78.2	74.0	.6388	2.611	5.141	11.334	3.7206	52.919	
70.586	1004.0	298.7	25.5	77.9	64.4	.5339	2.282	4.494	9.907	3.1967	45.468	
70.307	1000.0	298.7	25.5	78.0	55.5	.4795	1.975	3.882	8.574	2.6985	38.382	
70.307	1000.0	298.8	25.6	78.1	47.1	.40251	1.681	3.302	7.295	2.2236	31.827	
70.307	1000.0	299.0	25.8	78.5	37.6	.3202	1.351	2.661	5.866	1.7132	24.367	
70.307	1000.0	299.2	26.0	78.9	28.4	.24153	1.024	2.011	4.446	1.2530	17.822	
70.307	1000.0	299.4	26.3	79.3	24.0	.20130	.866	1.709	3.761	1.0356	14.729	
70.307	1000.0	299.7	26.4	79.8	19.7	.17107	.718	1.413	3.116	.8474	12.053	
70.307	1000.0	300.0	26.8	80.3	12.6	.1070	.466	.911	2.021	.5275	7.502	
70.307	1000.0	300.5	27.4	81.2	12.4	.1069	.458	.901	1.986	.5211	7.412	
70.307	1000.0	300.5	27.3	81.2	19.9	.17108	.721	1.421	3.132	.8512	12.108	
70.307	1000.0	300.4	27.3	81.1	24.5	.21133	.883	1.732	3.833	1.0665	15.170	
70.307	1000.0	300.4	27.2	81.0	28.8	.24156	1.037	2.044	4.501	1.2778	18.175	
70.307	1000.0	300.1	27.0	80.6	37.3	.32021	1.341	2.640	5.820	1.7045	24.243	
70.307	1000.0	299.9	26.7	80.1	46.0	.39246	1.640	3.222	7.119	2.1547	30.790	
70.307	1000.0	299.5	26.4	79.5	55.6	.4795	1.974	3.882	8.571	2.6964	38.351	
70.307	1000.0	298.9	25.8	78.4	65.0	.55343	2.299	4.527	9.981	3.2281	45.214	
70.029	996.0	298.4	25.2	77.4	74.7	.6394	2.635	5.182	11.440	3.7758	53.705	
70.029	996.0	297.9	24.7	76.5	82.5	.70435	2.910	5.730	12.634	4.2903	61.023	
70.321	1000.0	299.4	26.2	79.2								
.079	1.1	.7	.7	1.2	DEVIATIONS							

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 88
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 1
DATE: 7/8/76

CONTAMINATED CONDITION-FLOW RATE VERSUS F
DIFFERENTIAL PRESSURE, TOTAL OF 24.1 mg OF
SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN
(S/N 020) INLET PRESSURE 415 PSIA (NOMINAL)

TEST NUMBER 11H PART H TEST DESCRIPTION

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE			FLOWMETER TWO			TEST SPECIMEN INLET CONDITIONS		
FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.88	49.7	77.9	.92	47.5	79.4	418.1	78.6	.1045
.78	50.4	77.8	.81	48.7	79.3	417.4	78.5	.0941
.70	51.4	77.7	.71	49.7	79.3	416.8	78.5	.0836
.60	50.1	77.6	.60	49.0	79.4	416.8	78.5	.0718
.51	49.5	77.8	.51	48.7	79.6	416.8	78.7	.0597
.41	49.9	78.0	.40	49.2	79.8	414.8	78.9	.0486
.32	49.7	78.3	.31	49.2	80.0	416.8	79.2	.0367
.27	50.1	79.5	.26	49.8	80.1	416.8	79.3	.0316
.22	50.4	78.8	.21	50.0	80.3	416.8	79.6	.0256
.15	49.5	79.1	.14	49.0	80.6	416.8	79.8	.0171
.15	49.1	79.7	.14	48.8	81.1	417.4	80.3	.0169
.22	49.9	79.7	.21	49.4	81.1	417.4	80.4	.0251
.26	49.9	79.8	.25	49.4	81.2	417.4	80.5	.0305
.32	49.7	79.6	.31	49.2	81.7	417.4	80.4	.0368
.42	49.7	79.5	.41	49.0	81.1	417.4	80.3	.0487
.51	49.5	79.0	.51	48.7	81.1	416.8	80.1	.0597
.60	50.2	79.2	.60	49.0	80.9	416.1	80.0	.0719
.69	49.7	79.2	.70	48.3	80.9	415.5	80.0	.0823
.79	49.9	79.2	.81	48.3	80.8	415.5	80.0	.0942
.88	50.2	79.2	.91	48.3	80.7	415.5	80.0	.1062

TABLE 88
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 2
DATE: 7/8/76

CONTAMINATED CONDITION-FLOW RATE VERSUS
DIFFERENTIAL PRESSURE, TOTAL OF 24.1 mg OF
SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN
(S/N 020) INLET PRESSURE 415 PSIA (NOMINAL)

TEST NUMBER 11H PART # TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
418.1	78.6	.1045	198.019	198.019	198.019	.002	198.017
417.2	78.5	.0941	163.928	163.928	163.928	.001	163.927
416.8	78.5	.0836	135.835	135.835	135.835	.001	135.834
416.8	78.5	.0718	109.636	109.636	109.636	.001	109.635
416.8	78.7	.0597	84.458	85.15	84.737	.000	84.735
416.8	78.9	.0486	64.576	65.445	65.010	.000	65.009
416.8	79.2	.0369	47.327	46.827	47.077	.000	47.075
416.8	79.3	.0316	39.162	38.648	38.905	.000	38.903
416.8	79.6	.0256	30.608	30.317	30.463	.000	30.461
416.8	79.8	.0171	19.403	19.706	19.314	.000	19.313
417.4	80.3	.0169	19.174	19.192	19.133	.000	19.131
417.2	80.4	.0251	29.802	29.743	29.772	.000	29.771
417.2	80.5	.0305	37.490	37.380	37.435	.000	37.435
417.2	80.4	.0368	46.894	46.654	46.774	.000	46.773
417.2	80.3	.0487	64.326	65.129	64.727	.000	64.726
416.8	80.1	.0597	84.335	85.331	84.833	.000	84.831
416.1	80.0	.0719	109.636	109.636	109.636	.001	109.635
415.0	80.0	.0823	133.626	133.626	133.626	.001	133.624
415.0	80.0	.0942	164.244	164.244	164.244	.001	164.242
415.0	80.0	.1062	203.700	203.700	203.700	.002	203.699

TARE DIFF. PRESS = -3.40000E-05 + -4.44000E-04 (ACFM) + 1.50933E-01 (ACFM)**2 + 0 (ACFM)**3

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 88
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 3
DATE: 7/8/76

CONTAMINATED CONDITION-FLOW RATE VERSUS
DIFFERENTIAL PRESSURE, TOTAL OF 24.1 mg OF
SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN
(S/N 020) INLET PRESSURE 415 PSIA (NOMINAL)

TEST NUMBER 11H PART H TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESS

PRESSURE		TEMPERATURE			FLOW RATE					NET DIFFERENTIAL PRESS		

KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID	
29.393	418.1	299.1	25.9	78.6	82.6	.145	2.923	5.757	12.688	13.9220	198.017	
29.347	417.4	299.1	25.8	78.5	74.3	.0941	2.631	5.180	11.419	11.5252	163.927	
29.302	416.0	299.0	25.8	78.5	65.6	.0836	2.334	4.590	10.132	9.5501	135.834	
29.302	416.0	299.1	25.8	78.5	56.2	.0718	2.003	3.944	8.696	7.7081	109.635	
29.302	416.0	299.1	25.9	78.7	46.6	.0597	1.666	3.281	7.233	5.9575	84.735	
29.302	416.0	299.2	26.1	78.9	37.7	.0486	1.356	2.670	5.887	4.5706	65.009	
29.302	416.0	299.4	26.2	79.2	28.5	.0369	1.028	2.022	4.463	3.3097	47.075	
29.302	416.0	299.5	26.3	79.3	24.3	.0316	.880	1.736	3.819	2.7352	38.903	
29.302	416.0	299.6	26.4	79.6	19.6	.0256	.712	1.402	3.093	2.1416	30.461	
29.302	416.0	299.7	26.6	79.8	12.8	.0171	.476	.931	2.066	1.3578	19.313	
29.347	417.4	300.0	26.8	80.3	12.8	.0169	.470	.925	2.040	1.3451	19.131	
29.347	417.4	300.1	26.9	80.4	19.3	.0251	.699	1.377	3.035	2.0931	29.771	
29.347	417.4	300.1	26.9	80.5	23.4	.0305	.850	1.674	3.691	2.6319	37.435	
29.347	417.4	300.0	26.9	80.4	28.4	.0368	1.026	2.020	4.452	3.2884	46.773	
29.347	417.4	300.0	26.8	80.3	27.7	.0487	1.356	2.670	5.886	4.5507	64.726	
29.302	416.0	299.9	26.7	80.1	46.5	.0597	1.662	3.276	7.214	5.9642	84.831	
29.256	416.1	299.9	26.7	80.1	55.9	.0719	1.998	3.937	8.674	7.7081	109.635	
29.210	415.0	299.9	26.7	80.0	64.3	.0827	2.283	4.490	9.912	9.3947	133.624	
29.210	415.0	299.8	26.7	80.0	73.8	.0942	2.613	5.144	11.341	11.5474	164.242	
29.210	415.0	299.8	26.7	80.0	83.3	.1062	2.947	5.802	12.794	14.3215	203.699	
****	****	****	****	****	****	****	****	****	****	****	****	
29.304	416.0	299.6	26.4	79.6								
.035	.05	.4	.4	.6	DEVIATIONS							

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 89
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 1
DATE: 7/8/76

TEST NUMBER 111 PART I TEST DESCRIPTION

CONTAMINATED CONDITION-FLOW RATE VERSUS
DIFFERENTIAL PRESSURE, TOTAL OF 38.9 mg OF
SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN
(S/N 020) INLET PRESSURE 1000 PSIA (NOMINAL)

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.87	49.1	77.5	.91	46.9	83.1	1000.0	80.3	.0426
.78	50.4	76.4	.81	48.7	87.9	996.0	79.2	.0397
.69	50.4	76.7	.71	49.0	81.6	996.0	78.9	.0349
.60	50.2	76.6	.61	49.0	87.5	996.0	79.1	.0301
.51	49.9	77.2	.51	49.1	81.8	996.0	79.5	.0251
.41	49.5	77.8	.40	48.8	82.2	996.0	80.0	.0201
.32	49.9	77.5	.31	49.4	82.6	996.0	80.6	.0155
.27	50.2	77.3	.26	49.8	82.9	996.0	81.1	.0133
.21	49.5	79.9	.20	49.0	83.2	996.0	81.6	.0104
.15	49.5	80.7	.14	49.0	83.7	996.0	82.2	.0073
.15	50.1	81.8	.14	49.8	84.2	996.0	83.1	.0074
.22	48.9	81.8	.21	48.7	84.4	996.0	83.1	.0107
.26	49.7	80.6	.25	49.4	84.4	996.0	83.0	.0128
.32	50.1	81.3	.31	49.6	84.4	996.0	82.9	.0155
.41	50.1	80.6	.40	49.4	84.1	996.0	82.4	.0203
.50	49.9	79.9	.50	49.7	83.9	996.0	81.9	.0249
.60	50.2	77.1	.60	49.0	82.4	996.0	81.2	.0299
.69	49.9	78.2	.71	48.5	82.7	996.0	80.5	.0344
.78	50.4	77.3	.81	48.7	82.7	996.0	79.6	.0396
.87	49.9	76.5	.91	47.7	81.3	996.0	78.9	.0436

TABLE 89
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 2
DATE: 7/8/76

CONTAMINATED CONDITION-FLOW RATE VERSUS
DIFFERENTIAL PRESSURE, TOTAL OF 38.9 mg OF
SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN
(S/N 020) INLET PRESSURE 1000 PSIA (NOMINAL)

TEST NUMBER III	PART I	TEST DESCRIPTION	TEST SPECIMEN INLET CONDITIONS				
PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (SCFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
1000.0	80.3	.0426		62.106	62.106	-0.000	62.106
996.0	79.2	.0347	55.829	56.116	55.972	-0.000	55.973
996.0	78.9	.0349	48.747	47.919	48.333	-0.000	48.334
996.0	79.1	.0301	40.640	40.259	40.452	-0.000	40.454
996.0	79.5	.0251	32.718	32.343	32.550	-0.000	32.551
996.0	80.0	.0201	24.206	24.871	25.039	-0.000	25.039
996.0	80.6	.0155	18.863	18.577	18.720	-0.000	18.720
996.0	81.1	.0133	15.687	15.435	15.561	-0.000	15.561
996.0	81.6	.0111	11.886	11.724	11.806	-0.000	11.806
996.0	82.2	.0073	8.016	7.907	7.963	-0.000	7.963
996.0	83.1	.0074	8.081	8.078	8.079	-0.000	8.079
996.0	83.1	.0107	12.251	12.239	12.249	-0.000	12.250
996.0	83.0	.0128	14.940	14.921	14.930	-0.000	14.931
996.0	82.9	.0155	18.552	18.521	18.536	-0.000	18.536
996.0	82.4	.0203	25.216	25.170	25.153	-0.000	25.153
996.0	81.9	.0249	32.222	32.030	32.130	-0.000	32.130
996.0	81.2	.0299	40.211	39.971	40.093	-0.000	40.093
996.0	80.5	.0344	47.821	46.973	47.397	-0.000	47.397
996.0	79.6	.0396	55.704	56.116	55.910	-0.000	55.910
996.0	78.9	.0436	63.728	63.997	63.663	-0.000	63.663

$$\text{TARE DIFF. PRESS} = -1.64000\text{E-04} + -1.26930\text{E-02 (ACFM)} + 2.48070\text{E-01 (ACFM)**2} + 0 \text{ (ACFM)**3}$$

TABLE 89
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 3
DATE: 7/8/76

CONTAMINATED CONDITION-FLOW RATE VERSUS
DIFFERENTIAL PRESSURE, TOTAL OF 38.9 MG OF
SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN
(S/N 020) INLET PRESSURE 1000 PSIA (NOMINAL)

TEST NUMBER 111 PART 1 TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESSURE

PRESSURE		TEMPERATURE			FLOW RATE					NET DIFFERENTIAL PRESSURE	
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GM2 KG/HR	GM2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSIA
70.307	1000.0	300.0	26.8	80.3	88.7	.7426	2.842	5.590	12.338	2.1833	31.054
70.029	996.0	299.4	26.2	79.2	75.0	.6397	2.646	5.210	11.487	3.9353	55.973
70.029	996.0	299.2	26.1	78.9	65.7	.5349	2.325	4.579	10.594	3.3982	48.334
70.029	996.0	299.3	26.2	79.1	56.3	.4301	2.004	3.945	8.698	2.8442	40.454
70.029	996.0	299.6	26.4	79.5	46.9	.3251	1.670	3.288	7.250	2.2885	32.551
70.029	996.0	299.8	26.7	80.0	37.3	.2201	1.337	2.632	5.803	1.7604	25.039
70.029	996.0	300.1	27.0	80.6	28.7	.1555	1.031	2.031	4.478	1.3162	18.720
70.029	996.0	300.4	27.3	81.1	24.4	.1133	.881	1.734	3.824	1.0941	15.561
70.029	996.0	300.7	27.5	81.6	18.9	.0704	.686	1.352	2.980	.8300	11.806
70.029	996.0	301.0	27.9	82.2	13.1	.0473	.482	.949	2.093	.5598	7.963
70.029	996.0	301.5	28.4	83.1	13.3	.0474	.488	.960	2.117	.5680	8.079
70.029	996.0	301.5	28.4	83.1	19.7	.0167	.708	1.394	3.074	.8612	12.250
70.029	996.0	301.5	28.3	83.0	23.5	.0128	.847	1.668	3.677	1.0497	14.931
70.029	996.0	301.4	28.3	82.9	28.5	.0155	1.028	2.029	4.464	1.3032	18.536
70.029	996.0	301.2	28.0	82.4	37.4	.0203	1.343	2.649	5.832	1.7685	25.153
70.029	996.0	300.9	27.7	81.9	46.4	.0249	1.651	3.252	7.169	2.2590	32.130
70.029	996.0	300.5	27.4	81.2	55.8	.0299	1.984	3.907	8.614	2.6188	40.093
70.029	996.0	300.1	26.9	80.5	64.6	.0344	2.286	4.502	9.925	3.3324	47.397
70.029	996.0	299.6	26.5	79.6	74.6	.0396	2.635	5.189	11.440	3.9309	55.910
70.029	996.0	299.2	26.0	78.9	82.4	.0436	2.906	5.722	12.615	4.4766	63.603
****	****	****	****	****							
70.043	996.0	300.4	27.2	80.0							
.026	.4	.7	.7	1.3	DEVIATIONS						

TABLE 90
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 1
DATE: 7/8/76

TEST NUMBER 11J PART J TEST DESCRIPTION

CONTAMINATED CONDITION-FLOW RATE VERSUS
DIFFERENTIAL PRESSURE, TOTAL OF 38.9 MG TO
SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN
(S/N 020) INLET PRESSURE 415 PSIA (NOMINAL)

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.88	42.5	85.2	.92	47.4	87.0	418.9	86.4	.1058
.78	46.2	85.3	.81	48.5	86.6	419.4	85.9	.0936
.69	46.4	85.1	.7	49.1	86.5	418.7	85.8	.0830
.60	42.7	85.0	.60	48.7	86.5	418.7	85.7	.0710
.51	46.4	85.2	.51	49.5	86.7	418.7	85.9	.0605
.41	42.9	85.5	.40	49.3	87.1	418.7	86.2	.0481
.31	42.7	85.8	.30	49.3	87.2	418.7	86.5	.0364
.26	46.2	86.3	.25	49.9	87.6	419.4	86.9	.0308
.22	42.7	86.5	.21	49.5	87.8	419.4	87.2	.0250
.15	42.7	86.8	.14	49.5	87.9	420.0	87.4	.0168
.15	42.9	87.1	.13	49.9	88.0	420.7	87.5	.0167
.22	42.9	86.8	.21	49.5	88.1	420.7	87.4	.0256
.27	46.1	86.5	.25	49.7	87.9	421.7	87.2	.0308
.32	42.7	86.7	.31	49.1	87.8	420.7	87.0	.0370
.42	42.7	85.9	.41	49.1	87.6	420.0	86.7	.0483
.52	42.9	85.6	.51	49.1	87.4	419.4	86.5	.0603
.60	46.4	85.4	.61	49.7	87.1	418.7	86.2	.0721
.70	46.4	85.4	.71	49.1	86.8	418.1	86.1	.0836
.79	46.1	85.5	.81	48.3	86.8	417.4	86.2	.0940
.88	42.9	85.8	.91	47.8	86.8	417.4	86.3	.1045

TABLE 90
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 2
DATE: 7/8/76

TEST NUMBER 11J

PART J

TEST DESCRIPTION

CONTAMINATED CONDITION-FLOW RATES VERSUS
DIFFERENTIAL PRESSURE, TOTAL OF 38.9 mg OF
SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN
(S/N 020) INLET PRESSURE 415 PSIA (NOMINAL)

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (CFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
410.2	86.4	.1058	237.179	237.179	237.179	.002	237.177
419.4	85.9	.0936	183.585	183.585	183.585	.001	183.584
418.1	85.6	.0800	150.168	150.168	150.168	.001	150.166
418.1	85.7	.0716	118.327	118.327	118.327	.001	118.325
418.1	85.9	.0655	93.489	94.267	93.928	.000	93.928
418.1	86.2	.0481	68.699	67.147	68.923	.000	68.921
418.1	86.5	.0384	48.433	48.970	48.702	.000	48.700
419.2	86.9	.0318	40.609	41.323	40.468	.000	40.464
419.4	87.2	.0250	31.77	31.482	31.628	.000	31.625
420.0	87.4	.0168	19.119	19.867	19.993	.000	19.992
420.1	87.5	.0167	20.119	20.038	20.079	.000	20.077
420.1	87.4	.0256	32.637	32.514	32.576	.000	32.574
420.1	87.2	.0208	40.609	40.161	40.495	.000	40.493
420.1	87.0	.0370	49.309	49.916	49.612	.000	49.611
420.2	86.7	.0483	68.948	69.462	69.205	.000	69.203
419.4	86.5	.0603	92.642	93.421	93.032	.000	93.030
418.1	86.2	.0721	120.534	120.534	120.534	.001	120.532
418.1	86.1	.0836	152.059	152.50	152.59	.001	152.058
417.4	86.1	.0940	184.846	184.846	184.846	.001	184.845
417.4	86.3	.1145	229.613	229.613	229.613	.002	229.611

TARE DIFF. PRESS = $-3.0000E-05 + -4.4400E-04$ (ACFM) + $1.50933E-01$ (ACFM)**2 + 0 (ACFM)**3

TABLE 90
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE:3
DATE:7/8/76

TEST NUMBER 11J PART J TEST DESCRIPTION

CONTAMINATED CONDITION-FLOW RATE VERSUS
DIFFERENTIAL PRESSURE, TOTAL OF 38.9 mg OF
SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN
(S/N 020) INLET PRESSURE 415 PSIA (NOMINAL)

TEST SPECIMEN INLET CONDITIONS										NET DIFFERENTIAL PRESS.	
PRESSURE		TEMPERATURE			FLOW RATE						
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	CFM	SCFM	GN2 KG/HR	GN2 LRS/HR	KG/SQ CM DIFFERENTIAL	PSID
28.891	413.7	303.4	30.2	86.4	81.1	.1753	2.868	5.640	12.448	16.6752	237.177
29.484	419.4	303.1	30.1	85.9	73.2	.0936	2.593	5.100	11.258	12.9072	183.584
29.438	418.1	303.0	29.9	85.8	64.7	.0830	2.295	4.510	9.961	10.5577	150.156
29.438	418.1	303.	29.9	85.7	55.1	.0710	1.964	3.861	8.526	8.3191	118.325
29.438	418.1	303.1	30.0	85.9	46.8	.0605	1.673	3.294	7.262	6.6037	93.226
29.438	418.1	303.3	30.1	86.2	36.9	.0481	1.330	2.610	5.772	4.8456	68.221
29.438	418.1	303.5	30.3	86.5	27.8	.0364	1.006	1.981	4.366	3.4240	48.700
29.484	419.4	303.7	30.5	86.9	17.5	.0390	.852	1.670	3.700	2.8449	40.454
29.484	419.4	303.6	30.6	87.2	19.1	.0250	.692	1.360	3.004	2.2234	31.025
29.530	420.0	303.9	30.8	87.4	12.6	.0166	.464	.910	2.013	1.4056	19.292
29.575	420.1	304.0	30.9	87.5	10.5	.0167	.463	.912	2.011	1.4116	20.077
29.575	420.1	304.0	30.8	87.4	19.5	.0256	.710	1.391	3.080	2.2902	32.574
29.575	420.1	303.8	30.7	87.2	23.6	.0306	.854	1.680	3.708	2.8470	40.423
29.575	420.1	303.7	30.6	87.0	28.3	.0370	1.025	2.010	4.450	3.4880	49.011
29.530	420.0	303.6	30.4	86.7	37.2	.0483	1.337	2.630	5.804	4.8655	69.203
29.484	419.4	303.4	30.3	86.5	46.5	.0603	1.669	3.280	7.245	6.5407	93.030
29.438	418.1	303.3	30.1	86.2	55.9	.0721	1.992	3.920	8.647	8.4742	120.532
29.393	418.1	303.2	30.1	86.1	65.0	.0836	2.307	4.540	10.016	10.6907	152.058
29.347	417.4	303.2	30.1	86.2	73.1	.0940	2.591	5.100	11.246	12.9959	184.045
29.347	417.4	303.3	30.2	86.3	81.4	.1045	2.879	5.670	12.499	15.1433	229.011
*****	*****	*****	*****	*****							
29.445	418.0	303.5	30.3	86.6							
.084	.10	.3	.3	.5	DEVIATIONS						

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 91
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 1
DATE: 7/8/76

TEST NUMBER 11K PART K TEST DESCRIPTION

CONTAMINATED CONDITION-FLOW RATE VERSUS
DIFFERENTIAL PRESSURE, TOTAL OF 53.9 mg OF
SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN
(S/N 020) INLET PRESSURE 1000 PSIA (NOMINAL)

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.86	50.4	65.7	.90	48.3	70.7	107.9	68.2	.0431
.78	50.4	65.7	.81	48.7	71.6	107.9	68.2	.0392
.69	50.4	66.2	.71	48.9	71.9	107.9	68.5	.0344
.60	50.7	65.6	.60	49.1	71.	107.9	68.9	.0297
.50	52.9	67.4	.50	49.1	71.7	107.9	69.5	.0247
.41	42.7	68.1	.41	49.2	72.2	107.9	70.1	.0201
.31	50.1	68.9	.31	49.7	72.7	107.9	70.8	.0153
.26	42.7	69.8	.25	49.3	73.3	107.9	71.5	.0127
.21	42.9	70.8	.20	49.7	73.9	107.9	72.4	.0103
.15	42.5	71.7	.14	49.3	74.5	107.9	73.1	.0070
.15	50.4	73.2	.14	50.2	75.6	107.9	74.4	.0071
.22	50.1	73.3	.21	49.9	75.7	107.9	74.5	.0106
.27	42.5	73.7	.26	49.1	75.8	107.9	74.5	.0129
.32	42.7	73.9	.31	49.3	76.	107.9	74.5	.0153
.42	42.9	72.4	.41	49.3	75.9	107.9	74.2	.0203
.50	50.2	71.7	.50	49.5	75.7	107.9	73.7	.0249
.60	42.9	71.4	.60	48.7	75.	107.9	73.2	.0294
.69	50.2	69.9	.70	48.9	74.8	107.9	72.4	.0342
.78	42.9	69.1	.81	48.3	74.1	107.9	71.6	.0386
.87	50.2	68.5	.91	48.1	73.5	107.9	71.0	.0435

TABLE 91
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 2
DATE: 7/8/76

TEST NUMBER 11K	PART 1	TEST DESCRIPTION	CONTAMINATED CONDITION-FLOW RATE VERSUS DIFFERENTIAL PRESSURE, TOTAL OF 53.9 mg OF SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN (S/N 020) INLET PRESSURE 1000 PSIA (NOMINAL)				
TEST SPECIMEN INLET CONDITIONS			*****				
PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
1007.2	88.2	.431	66.657	67.318	66.987	-0.000	66.987
1007.4	88.2	.392	58.767	59.417	59.092	-0.000	59.092
1007.2	88.5	.0344	49.619	50.251	49.935	-0.000	49.935
1007.2	88.9	.0297	42.247	41.924	42.086	-0.000	42.086
1007.2	89.5	.247	33.629	33.186	33.457	-0.000	33.457
1007.4	70.1	.0201	26.234	25.975	26.084	-0.000	26.084
1007.2	70.8	.0153	19.011	18.772	18.892	-0.000	18.892
1007.2	71.5	.0127	15.457	15.226	15.342	-0.000	15.342
1007.2	72.4	.013	12.213	11.969	12.091	-0.000	12.091
1007.2	73.1	.0070	7.91	7.746	7.828	-0.000	7.828
1007.2	74.4	.0071	7.965	7.974	7.970	-0.000	7.970
1007.2	74.5	.016	12.40	12.426	12.413	-0.000	12.413
1007.2	74.5	.0129	15.457	15.97	15.427	-0.000	15.428
1007.4	74.5	.0153	18.762	18.715	18.738	-0.000	18.739
1007.2	74.2	.023	26.233	26.164	26.198	-0.000	26.199
1007.4	73.7	.0244	33.628	33.516	33.572	-0.000	33.572
1007.2	73.2	.0294	41.318	41.116	41.217	-0.000	41.218
1007.4	72.4	.342	48.992	49.019	49.306	-0.000	49.306
1007.4	71.6	.0386	57.112	57.806	57.424	-0.000	57.424
1007.2	71.0	.0435	67.157	67.950	67.554	-0.000	67.554

$$\text{GROSS DIFF. PRESS} = -1.64000E-04 + -1.24930E-02 (\text{ACFM}) + 2.48070E-01 (\text{ACFM})^{**2} + 0 (\text{ACFM})^{**3}$$

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 91
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 3
DATE: 7/8/76

TEST NUMBER 11K PART K TEST DESCRIPTION

CONTAMINATED CONDITION-FLOW RATE VERSUS
DIFFERENTIAL PRESSURE, TOTAL OF 53.9 mg OF
SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN
(S/N 020) INLET PRESSURE 1000 PSIA (NOMINAL)

TEST SPECIMEN INLET CONDITIONS											NET DIFFERENTIAL PRESS	
PRESSURE		TEMPERATURE			FLOW RATE					DIFFERENTIAL		PSID
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID	
70.865	1007.2	293.3	20.1	68.2	84.1	.431	2.968	5.847	12.886	4.7097	66.787	
70.865	1007.2	293.2	20.1	68.2	76.4	.393	2.699	5.312	11.715	4.1546	59.092	
70.865	1007.2	293.5	20.3	68.5	66.7	.344	2.366	4.652	10.272	3.5108	49.935	
70.865	1007.2	293.7	20.5	68.9	57.3	.297	2.042	4.020	8.863	2.9589	42.086	
70.865	1007.2	294.0	20.9	69.5	47.3	.247	1.692	3.331	7.344	2.3523	33.457	
70.865	1007.2	294.4	21.2	71.1	38.3	.201	1.377	2.711	5.977	1.8339	26.084	
70.865	1007.2	294.7	21.6	71.3	29.1	.153	1.047	2.066	4.546	1.3282	18.892	
70.865	1007.2	295.1	22.0	71.5	20.1	.127	.870	1.712	3.779	1.0786	15.342	
70.865	1007.2	295.6	22.4	72.4	19.3	.103	.703	1.382	3.052	.8501	12.091	
70.865	1007.2	296.0	22.8	73.1	12.9	.070	.475	.932	2.060	.5501	7.825	
70.865	1007.2	296.7	23.6	74.4	13.1	.071	.487	.950	2.095	.5603	7.970	
70.865	1007.2	296.7	23.6	74.5	20.9	.106	.723	1.422	3.138	.8727	12.413	
70.865	1007.2	296.8	23.6	74.5	24.2	.129	.876	1.722	3.804	1.0847	15.428	
70.865	1007.2	296.7	23.6	74.5	28.8	.153	1.038	2.042	4.505	1.3175	18.739	
70.865	1007.2	296.6	23.4	74.2	38.5	.213	1.383	2.722	6.005	1.8420	26.199	
70.865	1007.2	296.3	23.2	73.7	47.7	.249	1.697	3.346	7.369	2.3604	33.772	
70.865	1007.2	296.0	22.9	73.2	56.4	.294	2.007	3.956	8.713	2.8979	41.418	
70.865	1007.2	295.6	22.4	72.4	65.9	.340	2.333	4.592	10.109	3.4666	49.306	
70.865	1007.2	295.1	22.0	71.6	74.8	.386	2.636	5.182	11.441	4.0373	57.424	
70.865	1007.2	294.8	21.7	71.7	84.4	.435	2.976	5.860	12.918	4.7495	67.554	
****	****	****	****	****								
70.865	1007.2	295.2	22.1	71.8								
0.000	0.0	1.1	1.1	1.9	DEVIATIONS							

TABLE 92
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 1
DATE: 7/8/76

CONTAMINATED CONDITION-FLOW RATE VERSUS
DIFFERENTIAL PRESSURE, TOTAL OF 53.9 mg OF
SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN
(S/N 020) INLET PRESSURE 415 PSIA (NOMINAL)

TEST NUMBER 11L PART L TEST DESCRIPTION

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.88	44.5	78.0	.91	47.5	79.8	419.4	79.2	.1034
.79	44.1	78.7	.81	48.3	79.9	418.7	79.3	.0937
.69	44.2	78.7	.71	48.8	80.1	418.7	79.4	.0828
.60	44.1	78.9	.60	49.0	80.1	418.1	79.4	.0717
.51	44.9	78.8	.50	49.0	80.2	418.1	79.5	.0597
.41	44.9	78.9	.40	49.2	80.3	418.1	79.6	.0483
.31	44.2	79.0	.30	49.8	80.5	418.7	79.8	.0367
.27	44.5	79.2	.26	49.2	80.6	418.7	79.9	.0313
.22	44.4	79.4	.21	49.2	80.8	418.7	80.1	.0255
.14	44.4	79.6	.13	50.2	80.8	418.7	80.2	.0166
.14	44.9	79.9	.13	49.6	81.1	419.4	80.5	.0164
.22	44.2	79.9	.21	50.0	81.1	419.4	80.5	.0260
.27	44.9	79.8	.26	49.4	81.1	419.4	80.4	.0314
.32	44.2	79.5	.31	49.8	81.1	418.7	80.3	.0376
.42	44.1	79.3	.41	49.4	80.8	418.7	80.1	.0489
.51	44.9	79.2	.50	48.8	80.8	418.1	80.0	.0598
.60	44.1	79.1	.60	49.4	80.8	418.1	79.9	.0719
.70	44.2	79.2	.71	48.8	80.7	417.4	79.9	.0835
.78	44.1	79.2	.81	48.3	80.6	416.8	79.9	.0939
.88	44.7	79.7	.91	47.7	80.6	416.1	80.1	.1044

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 92
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 2
DATE: 7/8/76

CONTAMINATED CONDITION-FLOW RATE VERSUS
DIFFERENTIAL PRESSURE TOTAL OF 53.9 mg OF
SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN
(S/N 020) INLET PRESSURE 415 PSIA (NOMINAL)

TEST NUMBER 11L

PART L

TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
419.4	19.2	.1034	257.256	257.256	257.256	.002	257.254
418.1	19.3	.0937	206.752	206.752	206.752	.001	206.750
418.1	19.4	.088	165.086	165.086	165.086	.001	165.084
418.1	19.4	.0717	130.364	130.364	130.364	.001	130.363
418.1	19.5	.0597	99.430	99.430	99.430	.000	99.429
418.1	19.6	.0483	73.063	73.063	73.063	.000	73.063
418.1	19.8	.0367	51.311	51.311	51.311	.000	51.311
418.1	19.9	.0313	43.177	43.177	43.177	.000	43.177
418.1	20.1	.0255	33.441	33.441	33.441	.000	33.441
418.1	20.2	.0166	20.444	20.444	20.444	.000	20.444
419.4	20.5	.0164	20.008	19.949	19.979	-0.000	19.977
419.4	20.5	.0260	34.248	34.166	34.177	.000	34.176
419.4	20.4	.0314	42.805	42.562	42.683	.000	42.682
418.1	20.3	.0376	52.312	53.029	52.671	.000	52.669
418.1	20.1	.0489	73.813	74.494	74.152	.000	74.150
418.1	20.0	.0598	98.483	98.483	98.483	.000	98.482
418.1	19.9	.0719	130.048	130.048	130.048	.001	130.047
417.4	19.9	.0835	166.033	166.033	166.033	.001	166.031
416.8	19.9	.0939	207.067	207.067	207.067	.001	207.066
416.1	20.1	.1044	271.776	271.776	271.776	.002	271.774

TARE DIFF. PRESS = -2.40000E-05 + -4.44000E-04 (ACFM) + 1.50933E-01 (ACFM)**2 + 0 (ACFM)**3

TABLE 92
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 3
DATE: 7/8/76

TEST NUMBER 11L PART L TEST DESCRIPTION

CONTAMINATED CONDITION-FLOW RATE VERSUS
DIFFERENTIAL PRESSURE, TOTAL OF 53.9 mg OF
SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN
(S/N 020) INLET PRESSURE 415 PSIA (NOMINAL)

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESS

*****											*****	
*****											*****	
PRESSURE		TEMPERATURE			FLOW RATE						NET DIFFERENTIAL PRESS	
*****											*****	
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN2 KG/HR	GN2 LB/HR	KG/SQ CM DIFFERENTIAL	PSIA	
29.484	419.4	299.4	26.2	79.2	82.0	.1034	2.899	5.701	12.582	18.0668	257.254	
29.438	418.1	299.4	26.3	79.3	74.1	.0937	2.622	5.162	11.383	14.5360	206.750	
29.438	418.1	299.5	26.3	79.4	65.3	.0828	2.317	4.562	10.059	11.6066	165.084	
29.393	418.1	299.5	26.4	79.4	56.3	.0717	2.004	3.942	8.699	9.1654	130.363	
29.393	418.1	299.5	26.4	79.5	46.6	.0597	1.667	3.282	7.237	6.9905	99.422	
29.393	418.1	299.6	26.5	79.6	37.3	.0483	1.348	2.652	5.851	5.1537	73.303	
29.438	418.1	299.7	26.5	79.8	28.3	.0367	1.027	2.022	4.457	3.6345	51.095	
29.438	418.1	299.8	26.6	79.9	24.2	.0313	.876	1.722	3.805	3.0261	43.041	
29.438	418.1	299.9	26.7	80.1	19.6	.0255	.711	1.401	3.088	2.3441	33.341	
29.438	418.1	299.9	26.8	80.2	12.6	.0166	.465	.912	2.020	1.4279	20.209	
29.484	419.4	300.1	26.9	80.5	11.5	.0164	.460	.902	1.996	1.4045	19.977	
29.484	419.4	300.1	26.9	80.5	20.0	.0260	.728	1.432	3.160	2.4028	34.176	
29.484	419.4	300.1	26.9	80.4	24.2	.0314	.878	1.722	3.811	3.0008	42.082	
29.438	418.1	300.0	26.4	80.3	29.1	.0376	1.051	2.070	4.563	3.7030	52.069	
29.438	418.1	299.9	26.7	80.1	27.9	.0489	1.366	2.690	5.930	5.2133	74.150	
29.393	418.1	299.9	26.7	80.0	46.5	.0598	1.668	3.282	7.240	6.9240	98.482	
29.393	418.1	299.8	26.6	79.9	56.2	.0719	2.006	3.950	8.708	9.1432	130.047	
29.347	417.4	299.8	26.6	79.9	65.5	.0835	2.326	4.580	10.098	11.6732	166.031	
29.302	416.9	299.8	26.6	79.9	73.8	.0939	2.613	5.142	11.345	14.5582	207.066	
29.256	416.1	299.9	26.7	80.1	82.0	.1044	2.899	5.702	12.585	19.1076	271.774	
****	****	****	****	****								
29.416	418.4	299.8	26.6	79.9								
.046	.9	.2	.2	.3	DEVIATIONS							

TABLE 93
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 1
DATE: 7/8/76

CONTAMINATED CONDITION-FLOW RATE VERSUS
DIFFERENTIAL PRESSURE, TOTAL OF 67.3 MG OF
SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN
(S/N 020) INLET PRESSURE 1000 PSIA (NOMINAL)

TEST NUMBER 11M PART M TEST DESCRIPTION

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.87	42.7	74.6	.91	47.5	82.1	1007.9	79.3	.0427
.78	30.2	76.1	.81	48.5	81.5	1004.0	78.8	.0391
.69	31.4	75.9	.71	48.8	81.2	1004.0	78.5	.0346
.60	30.1	76.1	.60	49.0	81.3	1004.0	78.7	.0296
.50	30.1	76.7	.50	49.0	81.5	1004.0	79.1	.0248
.41	30.4	77.3	.40	49.0	81.8	1004.0	79.6	.0203
.31	32.9	78.3	.30	49.4	82.4	1004.0	80.3	.0152
.26	32.5	79.1	.25	49.0	82.7	1004.0	80.8	.0126
.22	32.5	79.5	.21	49.2	83.1	1004.0	81.3	.0105
.14	32.5	81.4	.13	49.2	83.5	1007.9	81.9	.0067
.14	30.4	81.6	.13	50.2	84.3	1007.9	83.0	.0069
.23	32.5	81.5	.22	49.2	84.3	1007.9	82.9	.0109
.26	32.5	81.3	.25	49.2	84.4	1007.9	82.8	.0125
.32	30.1	81.1	.31	49.8	84.4	1007.9	82.7	.0154
.41	32.7	81.4	.40	49.0	84.1	1007.9	82.3	.0200
.50	32.5	79.4	.50	48.5	83.7	1007.9	81.6	.0244
.60	30.1	78.5	.60	49.0	83.2	1004.0	80.8	.0295
.69	30.4	77.4	.71	48.8	82.4	1004.0	79.9	.0346
.78	30.2	76.8	.81	48.5	81.8	1004.0	79.3	.0390
.87	32.7	76.0	.91	47.5	81.2	1004.0	78.6	.0431

TABLE 93
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 2
DATE: 7/8/76

CONTAMINATED CONDITION-FLOW RATE VERSUS
DIFFERENTIAL PRESSURE, TOTAL OF 67.3 mg OF
SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN
(S/N 020) INLET PRESSURE 1000 PSIA (NOMINAL)

TEST NUMBER 114 PART M TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GRASS DIFF. PRESS PRIMARY (PSID)	GRASS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
1007.7	79.3	.0427	71.193	71.774	71.483	-0.000	71.484
1004.0	78.8	.0391	63.174	63.577	63.325	-0.000	63.326
1004.0	78.5	.0346	53.562	54.119	53.841	-0.000	53.841
1004.0	78.7	.0296	45.096	44.867	44.981	-0.000	44.982
1004.0	79.1	.0248	36.172	35.887	36.030	-0.000	36.030
1004.0	79.6	.0203	28.111	27.918	28.034	-0.000	28.035
1004.0	80.3	.0152	20.008	19.835	19.921	-0.000	19.922
1004.0	80.8	.0126	16.081	15.835	15.958	-0.000	15.958
1004.0	81.3	.0105	12.962	12.810	12.886	-0.000	12.886
1007.7	81.9	.0057	7.965	7.795	7.879	-0.000	7.880
1007.7	83.0	.0069	7.903	7.917	7.905	-0.000	7.905
1007.7	82.9	.0109	13.395	13.308	13.389	-0.000	13.390
1007.7	82.8	.0125	15.717	15.665	15.685	-0.000	15.685
1007.7	82.7	.0154	19.946	19.892	19.919	-0.000	19.919
1007.7	82.3	.0200	27.166	27.148	27.107	-0.000	27.107
1007.7	81.6	.0244	34.931	34.853	34.892	-0.000	34.892
1004.0	80.8	.0295	44.167	43.945	44.056	-0.000	44.056
1004.0	79.9	.0346	53.061	53.814	53.433	-0.000	53.433
1004.0	79.3	.0391	62.448	62.947	62.697	-0.000	62.698
1004.0	78.6	.0411	72.065	72.720	72.392	-0.000	72.393

TARE DIFF. PRESS = -1.64000E-04 + -1.26930E-02 (ACFM) + 2.48070E-01 (ACFM)**2 + 0 (ACFM)**3

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 93
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 3
DATE: 7/8/76

CONTAMINATED CONDITION-FLOW RATE VERSUS
DIFFERENTIAL PRESSURE, TOTAL OF 67.3 mg OF
SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN
(S/N 020) INLET PRESSURE 1000 PSIA (NOMINAL)

TEST NUMBER 114 PART 4 TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS										NET DIFFERENTIAL PRESS			
*****										*****			
PRESSURE		TEMPERATURE				FLOW RATE							
*****										*****			
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MI	SCFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID		
70.865	1007.7	299.4	26.3	79.3	81.7	.427	2.879	5.668	12.496	5.0258	71.984		
70.586	1004.4	299.2	26.0	78.8	74.5	.0391	2.626	5.171	11.401	4.4522	63.326		
70.586	1004.4	299.0	25.8	78.5	65.5	.0346	2.323	4.572	10.082	3.7854	53.541		
70.586	1004.	299.1	25.9	78.7	55.9	.296	1.987	3.914	8.625	3.1625	44.982		
70.586	1004.4	299.3	26.2	79.1	46.6	.0048	1.666	3.280	7.232	2.5332	36.030		
70.586	1004.4	299.6	26.4	79.6	37.9	.0213	1.363	2.687	5.919	1.9710	28.035		
70.586	1004.4	300.0	26.8	80.3	28.2	.0152	1.018	2.002	4.419	1.4006	19.922		
70.586	1004.4	300.3	27.1	80.8	23.2	.0126	.840	1.652	3.647	1.1220	15.258		
70.586	1004.4	300.5	27.4	81.3	19.1	.0105	.699	1.271	3.035	.9060	12.886		
70.865	1007.7	300.9	27.7	81.9	12.3	.0067	.452	.890	1.963	.5540	7.580		
70.865	1007.7	301.5	28.3	83.0	12.6	.0069	.460	.900	1.997	.5558	7.605		
70.865	1007.7	301.4	28.3	82.9	20.2	.0109	.730	1.438	3.171	.9414	13.390		
70.865	1007.7	301.4	28.2	82.8	23.1	.0125	.837	1.548	3.634	1.1028	15.685		
70.865	1007.7	301.3	28.2	82.7	28.6	.0154	1.030	2.022	4.473	1.4004	19.919		
70.865	1007.7	301.1	27.9	82.3	37.3	.0200	1.339	2.521	5.813	1.9058	27.107		
70.865	1007.7	300.7	27.5	81.6	45.8	.0244	1.639	3.228	7.116	2.4532	34.892		
70.586	1004.4	300.3	27.1	80.8	55.5	.0295	1.973	3.882	8.567	3.0975	44.056		
70.586	1004.4	299.8	26.6	79.9	65.4	.0346	2.319	4.561	10.069	3.7567	53.433		
70.586	1004.4	299.4	26.3	79.3	74.1	.0390	2.615	5.150	11.353	4.4081	62.598		
70.586	1004.4	299.0	25.9	78.6	82.1	.0431	2.896	5.702	12.573	5.0897	72.393		
****	****	****	****	****									
70.698	1005.0	300.2	27.0	80.6									
.134	1.7	.8	.8	1.4	DEVIATIONS								

TABLE 94
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 1
DATE: 7-8-76

TEST NUMBER 11N PART N TEST DESCRIPTION

CONTAMINATED CONDITION-FLOW RATE VERSUS
DIFFERENTIAL PRESSURE TOTAL OF 67.3 mg OF
SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN
(S/N 020) INLET PRESSURE 415 PSIA (NOMINAL)

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.83	34.2	85.5	.86	48.3	84.3	416.8	85.9	.0997
.79	34.4	85.6	.81	48.7	86.5	416.1	86.0	.0952
.70	36.4	85.4	.71	49.	86.5	416.1	86.0	.0840
.61	42.9	85.4	.61	48.7	86.7	416.1	86.0	.0717
.51	34.2	85.4	.50	49.4	86.7	416.8	86.1	.0605
.41	34.2	85.5	.40	49.4	87.0	416.8	86.2	.0488
.31	42.9	85.9	.30	49.4	87.2	416.8	86.6	.0364
.27	42.9	86.	.25	49.4	87.4	416.8	86.7	.0309
.22	34.2	85.	.21	50.0	87.6	417.4	86.9	.0254
.15	34.4	86.6	.14	50.2	87.9	417.4	87.2	.0172
.15	36.2	87.	.13	50.0	88.2	418.1	87.6	.0169
.23	42.7	86.9	.21	49.	88.1	418.1	87.5	.0260
.27	42.7	86.7	.25	49.2	88.1	418.1	87.4	.0309
.32	42.9	86.5	.31	49.	88.	418.1	87.2	.0376
.42	42.9	86.2	.40	49.2	87.9	417.4	87.0	.0486
.51	42.9	85.9	.50	48.8	87.7	417.4	86.8	.0598
.61	42.7	85.8	.61	48.7	87.5	416.8	86.6	.0715
.70	42.9	85.7	.71	48.5	87.4	416.1	86.6	.0830
.78	42.9	85.9	.81	48.3	87.3	415.5	86.6	.0939
.83	42.7	86.3	.86	47.7	87.2	415.5	86.7	.0993

ORIGINAL PAGES
OF POOR QUALITY

TABLE 94
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 2
DATE: 7-8-76

CONTAMINATED CONDITION-FLOW RATE VERSUS
DIFFERENTIAL PRESSURE TOTAL OF 67.3 mg OF
SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN
(S/N 020) INLET PRESSURE 415 PSIA (NOMINAL)

TEST NUMBER 11N	PART N	TEST DESCRIPTION	TEST SPECIMEN INLET CONDITIONS				
PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSIA)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
416.0	05.9	.0997	292.875	292.875	292.875	.001	292.873
416.1	06.1	.0952	255.674	255.674	255.674	.001	255.673
416.1	06.0	.0840	195.145	195.145	195.145	.001	195.143
416.1	06.0	.0717	147.541	147.541	147.541	.001	147.539
416.0	06.1	.0655	112.547	112.547	112.547	.000	112.546
416.0	06.2	.0588	82.116	82.242	82.192	.000	82.198
416.0	06.6	.0364	55.566	55.811	55.683	.000	55.682
416.0	06.7	.0309	46.024	45.732	45.878	.000	45.877
417.4	06.9	.0254	35.924	35.657	35.791	.000	35.789
417.4	07.2	.0172	22.686	22.452	22.512	.000	22.517
418.1	07.6	.0169	22.312	22.237	22.275	.000	22.273
418.1	07.5	.0261	36.793	36.635	36.714	.000	36.712
418.1	07.4	.0309	45.467	45.113	45.340	.000	45.339
418.1	07.2	.0376	57.319	57.692	57.505	.000	57.504
417.4	07.0	.0486	80.263	80.716	80.489	.000	80.483
417.4	06.8	.0598	109.710	109.710	109.710	.000	109.708
416.0	06.6	.0715	145.964	145.964	145.964	.001	145.963
416.1	06.6	.0831	189.785	189.785	189.785	.001	189.784
415.0	06.6	.0939	245.586	245.546	245.580	.001	245.585
415.0	06.7	.0993	296.342	296.342	296.342	.001	296.341

TARE DIFF. PRESS = -3.40000E-05 + -4.44000E-04 (ACFM) + 1.50933E-01 (ACFM)**2 + 0 (ACFM)**3

TABLE 94
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 3
DATE: 7-8-76

CONTAMINATED CONDITION-FLOW RATE VERSUS
DIFFERENTIAL PRESSURE TOTAL OF 67.3 mg OF
SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN
(S/N 020) INLET PRESSURE 415 PSIA (NOMINAL)

TEST NUMBER 11N PART N TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESS

PRESSURE		TEMPERATURE			FLOW RATE						
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	SCFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID
29.302	415.0	303.1	29.9	85.9	77.4	.997	2.745	5.402	11.914	20.5910	292.873
29.256	415.1	303.0	30.0	86.0	73.8	.0952	2.615	5.150	11.354	17.9756	255.873
29.256	415.1	303.1	30.0	86.0	64.9	.0840	2.309	4.541	10.024	13.7199	195.143
29.256	415.1	303.2	30.1	86.1	55.2	.0717	1.971	3.881	8.557	10.3730	147.539
29.302	415.0	303.2	30.0	86.1	46.5	.0605	1.665	3.272	7.229	7.9127	112.545
29.302	415.0	303.3	30.1	86.2	37.1	.0488	1.342	2.642	5.826	5.7791	82.198
29.302	415.0	303.5	30.3	86.6	27.6	.0364	1.001	1.970	4.344	3.9148	55.882
29.302	415.0	303.6	30.4	86.7	3.3	.0319	.848	1.071	3.683	3.2254	45.877
29.347	417.4	303.7	30.5	86.9	19.3	.0254	.700	1.378	3.038	2.5162	35.189
29.347	417.4	303.8	30.7	87.2	12.8	.0172	.473	.934	2.055	1.5831	22.517
29.393	418.1	304.1	30.9	87.6	1.6	.0169	.466	.911	2.021	1.5660	22.273
29.393	418.1	304.0	30.8	87.5	19.6	.0261	.715	1.401	3.102	2.5811	36.712
29.393	418.1	303.9	30.8	87.4	23.4	.0309	.850	1.672	3.689	3.1876	45.339
29.393	418.1	303.8	30.7	87.2	28.7	.0376	1.036	2.040	4.498	4.0429	57.504
29.347	417.4	303.7	30.6	87.0	7.1	.0480	1.338	2.632	5.808	5.6585	80.483
29.347	417.4	303.6	30.4	86.8	45.9	.0598	1.647	3.242	7.151	7.7133	109.708
29.302	415.0	303.5	30.4	86.6	55.1	.0715	1.965	3.870	8.531	10.2622	145.263
29.256	415.1	303.5	30.3	86.6	64.1	.0830	2.277	4.482	9.886	13.3431	189.184
29.210	415.0	303.5	30.3	86.6	72.8	.0939	2.574	5.068	11.172	17.2663	245.585
29.210	415.0	303.6	30.4	86.7	76.7	.0993	2.720	5.352	11.807	20.8349	296.341
****	****	****	****	****							
29.311	415.0	303.5	30.4	86.7							
.047	.1	.2	.2	.4	DEVIATIONS						

TABLE 95
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 1
DATE: 7-8-76

TEST NUMBER 110 PART 0

TEST DESCRIPTION

CONTAMINATED CONDITION - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. TOTAL OF 83.5 mg
OF SYNTHETIC CONTAMINANT ADDED. TEST
SPECIMEN (S/N 020) INLET PRESSURE 1000 PSIA (NOMINAL)
TEST SPECIMEN INLET CONDITIONS

FLOWMETER CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.86	90.1	71.3	.91	47.9	76.1	1015.9	73.2	.0427
.78	90.2	71.0	.81	48.5	75.7	1015.9	72.8	.0386
.69	90.2	70.1	.73	48.7	75.5	1015.9	72.8	.0338
.60	90.1	70.4	.61	49.1	75.5	1015.9	72.9	.0296
.50	92.9	70.9	.50	49.1	75.8	1011.9	73.3	.0246
.41	92.9	71.6	.40	49.3	76.2	1011.9	73.9	.0200
.31	92.9	72.6	.3	49.5	76.7	1011.9	74.6	.0150
.27	90.2	73.1	.26	50.1	77.0	1011.9	75.0	.0129
.22	90.1	73.8	.21	49.9	77.4	1011.9	75.6	.0104
.15	92.5	74.5	.14	49.3	77.8	1015.9	76.1	.0071
.15	92.7	76.1	.14	49.5	78.9	1015.9	77.6	.0071
.22	90.1	76.2	.21	49.9	79.0	1015.9	77.6	.0108
.27	92.7	76.0	.26	49.3	79.1	1015.9	77.5	.0128
.32	92.5	75.7	.31	49.2	79.1	1015.9	77.4	.0151
.41	92.7	75.1	.40	49.1	78.8	1015.9	76.9	.0198
.51	90.2	74.2	.51	49.5	78.5	1011.9	76.4	.0250
.60	90.2	73.4	.61	49.1	77.9	1011.9	75.6	.0296
.69	90.2	72.2	.71	48.9	77.2	1011.9	74.7	.0344
.78	90.2	71.4	.81	48.5	76.5	1011.9	73.9	.0386
.87	90.1	70.5	.91	47.9	75.7	1011.9	73.1	.0430

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 95
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 2
DATE: 7-8-76

TEST NUMBER 110	PART 2	TEST DESCRIPTION	TEST SPECIMEN INLET CONDITIONS *****						
TEST NUMBER 110	PART 2	TEST DESCRIPTION	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)	GRASS DIFF. PRESS PRIMARY (PSID)	GRASS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
1015.2			13.2	.0427	77.951	78.597	78.274	-0.000	78.274
1015.2			12.8	.0386	67.491	68.496	67.993	-0.000	67.993
1015.2			12.8	.0328	56.607	57.449	57.028	-0.000	57.028
1015.2			12.9	.0296	48.645	48.295	48.470	-0.000	48.470
1011.2			13.3	.0246	38.192	37.891	38.041	-0.000	38.041
1011.2			13.9	.0200	29.388	29.114	29.211	-0.000	29.211
1011.2			14.6	.0150	20.688	20.490	20.589	-0.000	20.589
1011.2			15.0	.0129	17.327	17.113	17.220	-0.000	17.220
1011.2			15.6	.0114	13.413	13.226	13.314	-0.000	13.314
1015.2			16.1	.0071	8.788	8.669	8.723	-0.000	8.723
1015.2			17.6	.0071	8.725	8.716	8.720	-0.000	8.721
1015.2			17.6	.0118	13.911	13.911	13.906	-0.000	13.906
1015.2			17.5	.0128	17.014	17.056	17.036	-0.000	17.036
1015.2			17.4	.0151	20.875	20.891	20.883	-0.000	20.883
1015.2			16.9	.0198	28.891	28.814	28.848	-0.000	28.848
1011.2			16.4	.0250	38.750	38.639	38.694	-0.000	38.694
1011.2			15.6	.0296	48.089	47.663	47.876	-0.000	47.876
1011.2			14.7	.0344	57.484	58.396	57.940	-0.000	57.940
1011.2			13.9	.0386	67.740	68.496	68.118	-0.000	68.118
1011.2			13.1	.0430	79.066	79.860	79.463	-0.000	79.463

CONTAMINATED CONDITION - FLOW RATE VERSUS
DIFFERENTIAL PRESSURE. TOTAL OF 83.5 mg
OF SYNTHETIC CONTAMINANT ADDED. TEST
SPECIMEN (S/N 020) INLET PRESSURE 1000 PSIA
(NOMINAL)

TARE DIFF. PRESS = -1.64000E-04 + -1.26930E-02 (ACFM) + 2.48070E-01 (ACFM)**2 + 0 (ACFM)**3

FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 110 PART 0 TEST DESCRIPTION

CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE. TOTAL OF 83.5 MG OF SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN (S/N 020) INLET PRESSURE 1000 PSIA (NOMINAL)

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESS

PRESSURE		TEMPERATURE			FLOW RATE				NET DIFFERENTIAL PRESS		
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID
71.423	1015.2	296.1	22.9	73.2	83.5	.427	2.936	5.781	12.746	5.5732	78.274
71.423	1015.2	295.9	22.7	72.8	75.4	.386	2.655	5.221	11.523	4.7804	67.923
71.423	1015.2	295.8	22.7	72.8	65.7	.338	2.326	4.572	10.095	4.0095	57.028
71.423	1015.2	295.9	22.7	72.9	57.2	.296	2.033	4.002	8.824	3.4078	48.270
71.144	1011.2	296.1	23.0	73.3	47.2	.246	1.682	3.311	7.300	2.6746	38.041
71.144	1011.2	296.4	23.3	73.9	38.1	.200	1.366	2.694	5.930	2.0538	29.211
71.144	1011.2	296.8	23.7	74.6	28.4	.150	1.021	2.010	4.432	1.4476	20.789
71.144	1011.2	297.1	23.9	75.0	24.5	.129	.882	1.732	3.827	1.2107	17.220
71.144	1011.2	297.4	24.2	75.6	19.6	.094	.710	1.391	3.080	.9361	13.314
71.423	1015.2	297.7	24.5	76.1	13.2	.071	.483	.951	2.097	.6133	8.723
71.423	1015.2	298.5	25.0	77.6	12.2	.071	.484	.956	2.099	.6131	8.721
71.423	1015.2	298.5	25.3	77.6	20.4	.108	.735	1.442	3.192	.9777	13.906
71.423	1015.2	298.5	25.3	77.5	24.1	.128	.871	1.719	3.783	1.1978	17.036
71.423	1015.2	298.4	25.2	77.4	28.8	.151	1.032	2.032	4.481	1.4682	20.883
71.423	1015.2	298.1	25.0	76.9	37.7	.198	1.350	2.652	5.862	2.0282	28.848
71.144	1011.2	297.8	24.6	76.4	47.8	.251	1.702	3.356	7.390	2.7205	38.594
71.144	1011.2	297.4	24.2	75.6	56.8	.296	2.015	3.968	8.747	3.3660	47.876
71.144	1011.2	296.9	23.7	74.7	66.3	.344	2.345	4.911	10.179	4.0736	57.240
71.144	1011.2	296.5	23.3	73.9	74.7	.386	2.637	5.192	11.449	4.7892	68.118
71.144	1011.2	296.0	22.8	73.1	83.5	.430	2.945	5.792	12.784	5.5868	79.263
*****	*****	*****	*****	*****	*****	*****	*****	*****	*****	*****	*****
71.283	1013.2	297.1	23.0	75.1							
.139	2.0	.3	.3	1.5	DEVIATIONS						

TABLE 96
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

Page: 1
Date: 7/8/76

TEST NUMBER 11P PART P TEST DESCRIPTION

CONTAMINATED CONDITION—FLOW RATE VERSUS
DIFFERENTIAL PRESSURE, TOTAL OF 83.5 mg OF
SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN (S/N
020) INLET PRESSURE 41.5 PSIA (NOMINAL)

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.82	42.9	81.0	.85	47.9	82.8	417.4	82.2	.0976
.79	42.2	81.5	.81	48.5	82.5	415.5	82.0	.0948
.70	41.2	81.3	.71	48.9	82.5	415.5	81.9	.0897
.60	40.2	81.1	.60	49.3	82.5	415.5	81.8	.0723
.51	39.7	81.1	.51	48.9	82.5	415.5	81.8	.0606
.42	39.1	81.1	.40	49.5	82.5	415.5	81.8	.0491
.32	38.9	81.1	.31	49.5	82.5	415.5	81.8	.0374
.27	38.1	81.2	.25	49.7	82.7	415.5	81.9	.0311
.22	37.2	81.3	.20	49.9	82.7	415.5	82.0	.0253
.15	36.4	81.5	.14	50.2	82.7	415.5	82.1	.0173
.15	36.4	81.6	.14	50.2	82.9	416.1	82.3	.0173
.22	36.2	81.6	.21	49.9	82.9	416.1	82.2	.0262
.27	35.7	81.4	.26	49.3	82.7	416.1	82.0	.0311
.32	35.9	81.3	.31	49.5	82.7	416.1	82.0	.0376
.42	36.2	81.0	.41	49.9	82.6	415.5	81.8	.0501
.51	35.7	81.8	.50	48.9	82.5	415.5	81.6	.0598
.60	35.9	82.7	.60	48.7	82.2	414.8	81.5	.0715
.70	36.1	81.7	.71	48.7	82.1	414.2	81.4	.0835
.79	35.9	81.3	.81	48.3	82.2	413.5	81.8	.0949
.79	36.4	82.1	.81	48.7	82.7	412.9	82.4	.0962

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 96
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 2
DATE: 7/8/76

CONTAMINATED CONDITION-FLOW RATE VERSUS
DIFFERENTIAL PRESSURE, TOTAL OF 83.5 mg OF
SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN
(S/N 020) INLET PRESSURE 415 PSIA (NOMINAL)

TEST NUMBER 11P PART 0 TEST DESCRIPTION

TEST SPECIMEN INLET CONDITIONS

PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (CFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
417.5	82.2	.0976	310.180	310.180	310.180	.001	310.179
415.5	82.	.0948	280.825	280.825	280.825	.001	280.823
415.5	81.9	.0837	209.172	209.172	209.172	.001	209.170
415.5	81.8	.0723	158.983	158.983	158.983	.001	158.982
415.5	81.8	.066	119.211	119.211	119.211	.000	119.210
415.5	81.6	.0491	87.791	87.791	87.791	.000	87.790
415.5	81.0	.0374	59.697	60.184	59.940	.000	59.939
415.5	81.9	.0311	47.986	47.558	47.772	.000	47.771
415.5	82.0	.0253	37.198	36.730	36.914	.000	36.913
415.5	82.1	.0173	23.445	23.171	23.318	.000	23.317
416.1	82.3	.0173	23.321	23.36	23.315	.000	23.312
416.1	82.2	.0202	38.151	38.053	38.102	.000	38.101
416.1	82.0	.0311	47.615	47.084	47.500	.000	47.499
416.1	82.0	.0376	59.321	60.184	59.753	.000	59.751
415.5	81.8	.051	86.913	87.962	87.437	.000	87.436
415.5	81.6	.0598	115.739	115.739	115.739	.000	115.738
414.5	81.5	.0715	154.880	154.880	154.880	.001	154.878
414.5	81.4	.0835	206.647	206.647	206.647	.001	206.645
413.5	81.8	.0949	284.612	284.612	284.612	.001	284.611
412.5	82.4	.0962	298.817	298.817	298.817	.001	298.815

TARE DIFF. PRESS = -3.4000E-05 + -4.44000E-04 (ACFM) + 1.50933E-01 (ACFM)**2 +

0 (ACFM)**3

FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 11P PART P TEST DESCRIPTION

CONTAMINATED CONDITION-FLOW RATE VERSUS DIFFERENTIAL PRESSURE, TOTAL OF 83.5 mg OF SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN (S/N 020) INLET PRESSURE 415 PSIA (NOMINAL)

TEST SPECIMEN INLET CONDITIONS

NET DIFFERENTIAL PRESS

PRESSURE		TEMPERATURE			FLOW RATE						NET DIFFERENTIAL PRESS	
KG/SQ CM	PSIA	DEG. C	DEG. C	DEG. F	LITERS/ MIN	ACFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID	
29.347	417.4	31.1	27.9	82.2	76.5	.976	2.710	5.330	11.764	21.8077	310.179	
29.210	415.0	30.9	27.8	82.0	74.1	.948	2.621	5.161	11.377	19.7438	280.823	
29.210	415.0	30.9	27.7	81.9	65.2	.837	2.314	4.550	10.044	14.7061	209.170	
29.210	415.0	30.8	27.7	81.8	56.0	.723	1.998	3.930	8.674	11.1775	158.982	
29.210	415.0	30.8	27.7	81.8	46.7	.606	1.674	3.490	7.267	8.3813	119.210	
29.210	415.0	30.8	27.6	81.8	37.7	.491	1.357	2.870	5.890	6.1209	87.059	
29.210	415.0	30.8	27.7	81.8	28.7	.374	1.035	2.030	4.494	4.2141	59.939	
29.210	415.0	30.9	27.7	81.9	24.6	.311	.860	1.690	3.732	3.3586	47.771	
29.210	415.0	30.9	27.8	82.0	19.2	.253	.700	1.370	3.037	2.5952	36.913	
29.210	415.0	31.1	27.8	82.1	12.9	.173	.478	.940	2.076	1.6393	23.317	
29.256	416.4	30.1	27.9	82.3	12.9	.173	.478	.940	2.075	1.6390	23.312	
29.256	416.4	30.1	27.9	82.2	19.9	.262	.725	1.420	3.146	2.6787	38.101	
29.256	416.4	30.1	27.8	82.0	23.8	.311	.861	1.690	3.739	3.3395	47.499	
29.256	416.4	30.9	27.8	82.0	24.8	.336	1.040	2.040	4.517	4.2009	59.791	
29.210	415.0	30.8	27.7	81.8	38.4	.501	1.384	2.720	6.009	6.1474	87.436	
29.210	415.0	30.7	27.6	81.6	46.3	.658	1.655	3.250	7.185	8.1372	115.738	
29.165	414.0	30.6	27.5	81.5	55.2	.715	1.975	3.880	8.573	10.8890	154.878	
29.119	414.0	30.6	27.4	81.4	64.8	.835	2.304	4.530	10.001	14.5286	206.645	
29.073	413.0	30.8	27.6	81.8	73.8	.949	2.612	5.140	11.341	20.0102	284.811	
29.028	412.0	31.1	28.0	82.4	74.5	.960	2.640	5.190	11.462	21.0088	298.815	
****	****	****	****	****								
29.203	415.0	30.9	27.7	81.9								
.043	.02	.1	.1	.2	DEVIATIONS							

ORIGINAL PAGE IS OF POOR QUALITY

TABLE 97
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 1
DATE: 7-8-76

TEST NUMBER 110 PART A TEST DESCRIPTION

CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE. TOTAL OF 100.2 MG OF SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN (S/N 020) INLET PRESSURE 1000 PSIA (NOMINAL).

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.85	42.7	77.2	.91	47.2	81.7	1 11.9	79.3	.0425
.78	42.9	76.2	.81	48.3	81.2	1 11.9	78.7	.0387
.69	42.9	76.1	.71	48.5	81.1	1 11.9	78.6	.0338
.60	42.7	75.2	.60	48.5	81.1	1 11.9	78.6	.0291
.50	42.7	74.6	.50	48.9	81.2	1 11.9	78.9	.0245
.41	42.5	74.1	.41	49.3	81.4	1 11.9	79.2	.0198
.32	42.5	73.9	.30	49.9	81.8	1 11.9	79.9	.0153
.27	42.5	72.9	.25	49.1	83.2	1 15.9	81.6	.0127
.22	42.1	72.2	.21	49.9	83.4	1 15.9	81.8	.0104
.15	42.9	81.2	.14	49.9	81.7	1 15.9	82.3	.0070
.15	42.9	81.8	.13	49.7	84.3	1 15.9	83.1	.0069
.23	42.5	82.6	.21	49.3	84.2	1 15.9	82.9	.0107
.27	42.9	81.2	.25	49.5	84.1	1 15.9	82.7	.0127
.32	42.7	81.8	.31	49.3	84.1	1 15.9	82.4	.0153
.42	42.5	81.1	.41	48.9	83.7	1 15.9	81.9	.0199
.51	42.7	79.2	.51	48.9	83.4	1 15.9	81.3	.0246
.60	42.4	78.2	.61	49.3	82.7	1 15.9	80.4	.0296
.69	42.5	77.1	.71	49.1	81.8	1 15.9	79.4	.0343
.78	42.9	76.4	.81	48.3	81.2	1 11.9	78.8	.0385
.87	42.1	75.7	.91	47.9	80.6	1 11.9	78.1	.0430

FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 110

PART Q

TEST DESCRIPTION

CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE. TOTAL OF 100.2 mg OF SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN (S/N 020) INLET PRESSURE 1000 PSIA (NOMINAL).

TEST SPECIMEN INLET CONDITIONS

TEST NUMBER	AVG TEMP (DEG. F)	AVG FLOW RATE (CFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
1011.7	79.3	.425	81.911	82.711	82.300	-0.000	82.306
1011.7	78.7	.4387	71.733	72.610	72.160	-0.000	72.167
1011.7	78.6	.4338	59.737	60.605	60.171	-0.000	60.171
1011.7	78.6	.291	48.973	49.873	49.423	-0.000	49.423
1011.7	78.9	.4245	40.141	39.798	39.970	-0.000	39.970
1011.7	79.2	.4198	30.460	30.145	30.300	-0.000	30.303
1011.7	79.9	.4153	22.180	21.494	22.041	-0.000	22.041
1015.7	81.6	.4127	17.827	17.666	17.710	-0.000	17.716
1015.7	81.8	.4114	14.022	13.780	13.901	-0.000	13.901
1015.7	82.1	.4070	8.800	8.702	8.801	-0.000	8.801
1015.7	83.1	.4009	8.715	8.762	8.738	-0.000	8.739
1015.7	82.9	.4117	14.272	14.293	14.283	-0.000	14.283
1015.7	82.7	.4127	17.640	17.660	17.651	-0.000	17.651
1015.7	82.4	.4153	21.939	21.894	21.910	-0.000	21.917
1015.7	81.9	.4199	30.400	30.317	30.389	-0.000	30.389
1015.7	81.3	.4246	40.141	39.971	40.050	-0.000	40.050
1015.7	81.4	.4296	49.724	50.514	50.114	-0.000	50.114
1015.7	79.4	.4343	60.860	61.552	61.407	-0.000	61.208
1011.7	78.8	.4385	71.483	72.284	71.884	-0.000	71.884
1011.7	78.1	.4430	84.007	84.910	84.459	-0.000	84.459

TARE DIFF. PRESS = -1.64000E-04 + -1.26930E-02 (ACFM) + 2.48070E-01 (ACFM)**2 +

0 (ACFM)**3

ORIGINAL PAGE IS OF POOR QUALITY

TABLE 97
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

TEST NUMBER 110 PART 3 TEST DESCRIPTION CONTAMINATED CONDITION - FLOW RATE VERSUS DIFFERENTIAL PRESSURE. TOTAL OF 100.2 mg OF CONTAMINANT ADDED. TEST SPECIMEN (S/N 020) INLET PRESSURE 1000 PSIA (NOMINAL). NET DIFFERENTIAL PRESS

TEST SPECIMEN INLET CONDITIONS

PRESSURE		TEMPERATURE			FLOW RATE								
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	CFM	SCFM	GN2 KG/HR	GN2 LBS/HR	KG/SQ CM DIFFERENTIAL	PSID		
71.144	1011.2	299.5	26.3	79.3	81.6	.425	2.874	5.660	12.478	5.7867	82.206		
71.144	1011.2	299.1	25.9	78.7	74.4	.387	2.619	5.151	11.369	5.0738	72.167		
71.144	1011.2	299.0	25.9	78.6	64.6	.338	2.287	4.502	9.929	4.2304	60.171		
71.144	1011.2	299.1	25.9	78.6	55.5	.291	1.972	3.882	8.561	3.4748	49.223		
71.144	1011.2	299.2	26.1	78.9	46.5	.245	1.658	3.262	7.197	2.8102	39.270		
71.144	1011.2	299.4	26.2	79.2	37.2	.198	1.338	2.632	5.810	2.1305	30.203		
71.144	1011.2	299.8	26.6	79.9	28.7	.153	1.036	2.032	4.496	1.5496	22.041		
71.423	1015.2	300.7	27.5	81.6	23.7	.127	.859	1.691	3.728	1.2456	17.716		
71.423	1015.2	300.8	27.7	81.8	19.4	.104	.704	1.381	3.057	.9774	13.201		
71.423	1015.2	301.1	27.9	82.3	12.8	.071	.471	.921	2.043	.6188	8.801		
71.423	1015.2	301.5	28.4	83.1	12.6	.069	.466	.912	2.024	.6144	8.732		
71.423	1015.2	301.5	28.3	82.9	19.9	.107	.723	1.422	3.136	1.0042	14.282		
71.423	1015.2	301.3	28.2	82.7	23.7	.127	.858	1.690	3.725	1.2410	17.651		
71.423	1015.2	301.2	28.1	82.4	28.5	.153	1.030	2.022	4.472	1.5409	21.217		
71.423	1015.2	300.9	27.7	81.9	37.5	.199	1.447	2.854	5.846	2.1365	30.389		
71.423	1015.2	300.6	27.4	81.3	46.8	.246	1.667	3.282	7.239	2.8162	40.056		
71.423	1015.2	300.1	26.9	80.4	56.3	.296	2.005	3.941	8.702	3.5234	50.114		
71.423	1015.2	299.5	26.3	79.4	65.8	.343	2.328	4.582	10.104	4.3033	61.208		
71.144	1011.2	299.2	26.0	78.8	74.1	.385	2.610	5.132	11.330	5.0540	71.884		
71.144	1011.2	298.8	25.6	78.1	82.8	.431	2.918	5.742	12.665	5.9381	84.452		
71.297	1014.1	300.1	26.9	80.5									
.138	2.2	.9	.9	1.5	DEVIATIONS								

TABLE 98
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 1
DATE: 7/8/76

TEST NUMBER 11R PART R TEST DESCRIPTION

CONTAMINATED CONDITION-FLOW RATE VERSUS
DIFFERENTIAL PRESSURE, TOTAL OF 100.2 mg OF
SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN
(S/N 020) INLET PRESSURE 415 PSIA (NOMINAL)

FLOWMETER CONDITIONS

TEST SPECIMEN INLET CONDITIONS

FLOWMETER ONE

FLOWMETER TWO

FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	FLOW RATE (ACFM)	PRESSURE (PSIA)	TEMP (DEG. F)	PRESSURE (PSIA)	AVG TEMP (DEG. F)	AVG FLOW RATE (ACFM)
.81	47.7	75.3	.83	47.9	77.5	417.9	76.9	.0958
.78	46.3	76.1	.81	48.5	77.3	416.6	76.7	.0944
.70	46.5	75.8	.71	48.9	77.3	416.6	76.5	.0839
.60	46.3	75.6	.61	49.3	77.3	416.6	76.5	.0724
.51	47.7	75.6	.50	48.9	77.4	416.6	76.5	.0599
.42	47.9	75.7	.41	49.3	77.5	416.6	76.6	.0492
.32	46.3	75.7	.30	49.9	77.6	416.6	76.6	.0373
.27	46.3	75.6	.26	49.9	77.7	416.6	76.7	.0315
.22	46.3	76.6	.21	54.1	77.8	416.6	76.9	.0256
.15	47.9	76.3	.14	49.9	78.1	416.6	77.2	.0173
.15	47.7	76.8	.14	49.5	78.4	417.3	77.6	.0172
.22	47.9	76.8	.21	49.5	78.4	417.3	77.5	.0258
.27	47.4	76.7	.26	49.5	78.4	417.3	77.5	.0317
.32	47.4	76.6	.31	49.5	78.4	416.6	77.5	.0373
.42	47.9	76.4	.41	49.3	78.7	416.6	77.3	.0489
.51	47.5	76.3	.51	49.3	77.9	412.1	77.1	.0615
.60	46.1	76.3	.60	49.1	78.1	16.5	77.2	.0719
.70	46.1	76.3	.71	48.7	77.9	415.3	77.1	.0838
.78	47.9	76.8	.81	48.3	78.1	414.7	77.5	.0941
.79	46.1	77.4	.81	48.3	78.3	414.0	77.8	.0950

ORIGINAL PAGE IS
OF POOR QUALITY

TABLE 98
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 2
DATE: 7/8/76

CONTAMINATED CONDITION-FLOW RATE VERSUS
DIFFERENTIAL PRESSURE, TOTAL OF 100.2 mg OF
SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN
(S/N 020) INLET PRESSURE 415 PSIA (NOMINAL)

TEST NUMBER 11P	PART P	TEST DESCRIPTION	TEST SPECIMEN INLET CONDITIONS *****				
INLET PRESSURE (PSIA)	AVG INLET P (DEG. F)	AVG FLOW RATE (ACFM)	GROSS DIFF. PRESS PRIMARY (PSID)	GROSS DIFF. PRESS SECONDARY (PSID)	AVG GROSS DIFF. PRESS (PSID)	TARE DIFF. PRESS (PSID)	NET DIFF. PRESS (PSID)
417.3	16.9	.0958	309.725	309.725	309.725	.001	309.724
416.0	16.7	.0944	297.083	297.083	297.083	.001	297.082
416.0	16.5	.0899	218.388	218.388	218.388	.001	218.387
416.1	16.5	.0724	164.976	164.976	164.976	.001	164.975
416.0	16.5	.0599	120.414	120.414	120.414	.000	120.412
416.0	16.6	.0492	89.252	89.252	89.505	.000	89.503
416.0	16.6	.0373	60.641	61.513	60.977	.000	60.976
416.0	16.7	.0315	48.471	48.987	48.722	.000	48.728
416.0	16.9	.0256	38.156	37.745	37.951	.000	37.950
416.0	17.2	.0173	24.056	23.709	23.882	.000	23.881
417.2	17.6	.0172	23.495	23.536	23.516	.000	23.515
417.2	17.6	.0258	37.599	37.631	37.615	.000	37.613
417.3	17.5	.0717	48.471	48.987	48.722	.000	48.728
416.0	17.5	.0373	59.763	60.081	60.222	.000	60.221
416.0	17.3	.0489	86.554	87.545	87.050	.000	87.048
417.1	17.1	.0615	118.517	118.517	118.517	.001	118.516
416.0	17.2	.0719	161.816	161.816	161.816	.001	161.814
415.2	17.1	.0838	217.124	217.124	217.124	.001	217.122
414.1	17.5	.0941	298.031	298.031	298.031	.001	298.030
414.0	17.8	.0950	310.673	310.673	310.673	.001	310.672

INLET DIFF. PRESS = $-3.40000E-05 + -4.44000E-04 (ACFM) + 1.50933E-01 (ACFM)^2 + 0 (ACFM)^3$

ORIGINAL PAGE IS OF POOR QUALITY

TABLE 98
FLOW RATE VERSUS DIFFERENTIAL PRESSURE

PAGE: 3
DATE: 7/8/76

CONTAMINATED CONDITION-FLOW RATE VERSUS DIFFERENTIAL PRESSURE, TOTAL OF 100.2 mg OF SYNTHETIC CONTAMINANT ADDED. TEST SPECIMEN (S/N 020) INLET PRESSURE 415 PSIA (NOMINAL)

TEST SPECIMEN INLET CONDITIONS											NET DIFFERENTIAL PRESSURE	
*****											*****	
PRESSURE		TEMPERATURE			FLOW RATE							
*****		*****			*****						*****	
KG/SQ CM	PSIA	DEG. K	DEG. C	DEG. F	LITERS/ MIN	SCFM	SCFM	GN2 KG/HR	GN2 LRS/HR	KG/SQ CM DIFFERENTIAL	PSID	
29.384	417.2	298.1	24.9	76.9	75.8	.958	2.688	5.292	11.670	21.7758	309.724	
29.293	416.9	298.0	24.8	76.7	74.6	.944	2.643	5.204	11.472	20.8869	297.082	
29.247	416.2	297.9	24.7	76.5	65.9	.839	2.345	4.618	10.182	15.3541	216.387	
29.247	416.	297.9	24.7	76.5	56.8	.724	2.025	3.981	8.790	11.5989	164.975	
29.247	416.4	297.9	24.7	76.5	46.8	.599	1.674	3.298	7.267	8.4658	120.512	
29.247	416.2	297.9	24.8	76.6	38.2	.492	1.376	2.702	5.972	6.2927	89.503	
29.247	416.2	298.0	24.8	76.6	28.9	.373	1.044	2.059	4.531	4.2870	60.276	
29.247	416.2	298.0	24.8	76.7	24.3	.315	.882	1.738	3.827	3.4259	48.728	
29.247	416.2	298.1	24.9	76.9	19.7	.256	.715	1.401	3.102	2.6682	37.250	
29.293	416.9	298.3	25.1	77.2	13.1	.173	.485	.954	2.103	1.6790	23.881	
29.338	417.2	298.5	25.3	77.6	13.0	.171	.481	.948	2.090	1.6532	23.515	
29.338	417.2	298.5	25.3	77.6	19.7	.258	.721	1.420	3.130	2.6445	37.913	
29.338	417.2	298.5	25.3	77.5	24.4	.317	.888	1.748	3.853	3.4259	48.728	
29.293	416.9	298.4	25.3	77.5	28.8	.373	1.043	2.052	4.526	4.2339	60.221	
29.293	416.9	298.3	25.2	77.3	38.0	.489	1.368	2.694	5.940	6.1201	87.948	
28.973	412.1	298.2	25.0	77.1	48.2	.615	1.702	3.350	7.386	8.3325	118.916	
29.247	416.	298.3	25.1	77.2	56.4	.719	2.009	3.959	8.720	11.3767	161.814	
29.201	415.2	298.2	25.1	77.1	65.8	.838	2.335	4.598	10.138	15.2652	217.122	
29.155	414.1	298.4	25.3	77.5	74.0	.941	2.618	5.158	11.366	20.9536	298.030	
29.110	414.2	298.6	25.5	77.8	74.3	.956	2.636	5.190	11.441	21.8424	310.872	
*****	*****	*****	*****	*****								
29.246	416.2	298.2	25.0	77.1								
.058	.0	.2	.2	.4	DEVIATIONS							