

General Disclaimer

One or more of the Following Statements may affect this Document

- This document has been reproduced from the best copy furnished by the organizational source. It is being released in the interest of making available as much information as possible.
- This document may contain data, which exceeds the sheet parameters. It was furnished in this condition by the organizational source and is the best copy available.
- This document may contain tone-on-tone or color graphs, charts and/or pictures, which have been reproduced in black and white.
- This document is paginated as submitted by the original source.
- Portions of this document are not fully legible due to the historical nature of some of the material. However, it is the best reproduction available from the original submission.

SILICON WEB PROCESS DEVELOPMENT

SECOND QUARTERLY REPORT

July 1, 1977 - September 30, 1977

C. S. Duncan, R. G. Seidensticker,
J. P. McHugh, P. D. Blais, and J. R. Davis, Jr.
Westinghouse Research & Development Center
Pittsburgh, Pennsylvania 15235

Contract No. NAS 954654

This work was performed for the Jet Propulsion Laboratory,
California Institute of Technology, under NASA Contract
NAS7-100 for the U. S. Energy Research and Development
Administration, Division of Solar Energy.

The JPL Low-Cost Silicon Solar Array Project is funded
by ERDA and forms part of the ERDA Photovoltaic
Conversion Program to initiate a major effort toward
the development of low-cost solar arrays.


(NASA-CR-157098) SILICON WEB PROCESS
DEVELOPMENT Quarterly Report, 1 Jul. - 30
Sep. 1977 (Westinghouse Electric Corp.)
73 p HC A04/MF A01

CSCI 10A

N78-24646

Unclass
20702

G3/44



Westinghouse R&D Center
1310 Beulah Road
Pittsburgh, Pennsylvania 15235

TECHNICAL CONTENT STATEMENT

This report contains information prepared by WESTINGHOUSE ELECTRIC CORPORATION under JPL subcontract. Its content is not necessarily endorsed by the Jet Propulsion Laboratory, California Institute of Technology, National Aeronautics and Space Administration or the U. S. Energy Research and Development Administration, Division of Solar Energy.

ABSTRACT

Thirty-five (35) furnace runs were carried out during this quarter, of which 25 produced a total of 120 web crystals. Lengths in excess of two meters and widths over 27 mm were achieved. A variety of lid and susceptor configurations have been used to modify the thermal geometry of the system in an effort to grow wider and longer web crystals of high quality.

The two main thermal models for the dendritic growth process have been completed and are being used to assist the design of the thermal geometry of the web growth apparatus. The first model, a finite element representation of the susceptor and crucible, has been refined to give greater precision and resolution in the critical central region of the melt. The second thermal model, which describes the dissipation of the latent heat to generate thickness-velocity data, has been completed. Both models have been validated by comparison of predicted results with experimental data; both are in excellent agreement with reality. The second model also gives temperature distributions in the growing web so that it can be applied to the evaluation of thermally generated stress in the crystal.

Width versus length data generated for dendritic web crystals indicate that the widening rates of the crystal are related to the lid design, however, the differences between most of the lid configurations are relatively small. More importantly, the data indicates that even in the current system which has only a 76 mm diameter crucible, ultimate widths of dendritic web crystals should be in the 30 to 40 mm range. Thickness measurements on the crystals being grown are in excellent agreement with the predictions of the thermal model, and modifications of the lid designs to increase the growth velocity are being investigated.

As longer and wider web is being grown, strain in some crystals has been noted. In these cases growth runs are intentionally terminated because of crystal warpage, rather than because of temperature fluctuations as in the past. Residual stress measurements based on crystal splitting are being made in some of the crystals being grown and these results will be correlated with predictions of the thermal models. The models will then be used to generate susceptor lid configurations producing smaller thermal stresses in the growing crystal.

In addition to the residual stress measurements, both x-ray topographic and etching examinations have been made on web crystals. To date, the results confirm earlier conclusions that most dislocations are generated in either the initial button or in the bounding dendrites. These studies are being continued to correlate crystal perfection with the growth conditions and with solar cell performance.

Dendritic web samples have been fabricated into solar cells using a standard cell configuration and a standard process for a N^+-P-P^+ configuration. The data indicates that web material can make very good solar cells with AM1 efficiencies greater than 14%. In a given fabrication run, cells made from a given crystal have almost identical characteristics. Further, analysis of the cell characteristics indicates that N^+-P junction on web cells is of extremely high quality. Work is presently in progress to correlate the cell performance with the material quality. Studies are also underway to develop improved processing techniques for dendritic web material.

The detailed engineering design was completed for a new dendritic web growth facility of greater width capability than previous facilities. Fabrication of component parts and assembly have begun.

TABLE OF CONTENTS

	<u>Page</u>
1. INTRODUCTION	1
2. TECHNICAL DISCUSSION	3
Experimental Web Growth	3
Thermal Modeling Related to Dendritic Web Growth	4
Mechanical and Dimensional Characterization	10
Web Thickness	15
Residual Stress	15
Crystal Perfection Studies	18
Solar Cell Studies	18
Facility Design and Construction	25
3. PLANS FOR THE NEXT PERIOD	26
4. NEW TECHNOLOGY	27
5. REFERENCES	28
6. APPENDIX	29
6.1 Growth Run Detail Summary for this Reporting Period	30
6.2 Complete Set of Design Drawings for Silicon Web Growth Facility	37

LIST OF ILLUSTRATIONS

	<u>Page</u>
Figure 1 Lid Slot Geometries	5
Figure 2 Calculated Temperatures on Melt Surface	7
Figure 3 Thickness-Velocity Behavior	9
Figure 4 Typical Dendritic Web Widening	14
Figure 5 Standard Solar Cell and Test Pattern Design	19
Figure 6 Dendritic Web and Baseline Czochralski Cells	20
Figure 7 Solar Cell Run Sheet	22
Figure 8 Sample Data Print-Out	23

LIST OF TABLES

Table 1 Dendritic Web Widening Rates	11
Table 2 Stress Data for Web Samples	17

1. INTRODUCTION

The overall intent of this program is to further develop the dendritic web crystal growth process to the extent that it supports the economic goals of the Large Area Silicon Sheet Task of the Low-Cost Silicon Solar Array Project.

The ability of this process to produce crystals for high efficiency solar cells, 14 percent AM-1 or higher, is well known and has been demonstrated in pilot production and in this program. The prior state of development of the process did not, however, have sufficient throughput to satisfy the cost goals of the LSSA Project.

Consequently, a key goal of this program is to increase the throughput of the process in terms of greater width (to 7.5 cm), greater speed (to 7.5 cm/min) and greater length (to >10 meters) within the web thickness range of 100 to 200 μm . These goals are being sought via two growth facilities: an existing facility which is undergoing continued development and a new facility now in the construction and assembly phase.

The existing facility has produced crystals to 2.7 cm width and 3 meters length. Growth rates for useful material in the range of 100 to 200 μm thickness have reached 2.5 cm/min although some experimental growth at rates as high as 10 cm/min have been achieved for very thin web. The goal of this phase of the program is to achieve a growth width equal to the 5 cm dimensional capacity of the facility and a growth rate of 5 cm/minute. Both facilities have provision for adding polycrystalline silicon feed material to the melt for achieving a quasi-continuous growth.

The new facility, when completed, will have capacity to meet the full throughput goals stated above. The growth run experiments with both facilities will be used to identify the necessary on-line process parameter measurements and control.

Computer thermal models are a critical factor in the successful development of the process. The models are verified and refined initially by temperature measurements of sensors located in the thermal system and subsequently by correlation with actual web growth results. As the program progresses, a large volume of data is being generated and related to growth conditions, crucible system geometry, crystal quality, etc.

During the process development period with both facilities the web crystals grown will be used for several purposes. The growth is routinely selected and evaluated in terms of its dimensional, crystalline, electronic, and solar cell properties. For solar cell evaluation a "standard" fabrication procedure suitable for web crystals is used. Crystals are also provided for another program goal which is developing improved solar cell fabrication techniques especially suited to web crystals. Finally, selected web crystals and solar cells are being sent to JPL.

Growth runs will also be performed to determine the interaction of controlled amounts of selected impurities with growth conditions and parameters. This evaluation will be performed in a third web growth facility which is also used for other web programs.

As the program progresses, an economic analysis will be developed and updated in response to continued process development.

2. TECHNICAL DISCUSSION

Experimental Web Growth

The major objectives of the work during this reporting period have been (1) to improve the thermal geometry as required to increase web width, (2) to gather baseline thermal data both for system characterization and for input to the thermal modeling, (3) to verify experimentally the results of the thermal modeling, and (4) to grow web material for evaluation and solar cell processing.

During this reporting period, 35 furnace runs were made, of which 25 were productive web growth runs. A total of 120 identified web crystals were grown. Pertinent data for each is tabulated in Section 6.1. Continuous lengths of over two meters and widths over 27 mm were obtained.

The experimental procedures in the web growth runs have involved systematic variations in lid and susceptor configurations so as to alter heat losses and thus refine the thermal geometry of the melt in an effort to grow wider web crystals. In order to strengthen the data base, configurational features, e.g., slot geometry, are sometimes used which are not necessarily expected to be productive from a web throughput point of view, but provide valuable information as part of a systematic series of changes. We feel that this approach provides an extended data base which will be very beneficial in the long run. In addition, this approach permits us to test and verify the results of the thermal modeling. Thus, we have established a consistency between experiment and modeling results which give confidence in the usefulness of the modeling for guidance in future design changes.

As longer and wider web crystals have been grown, we have observed in some cases crystal deformation due to thermally induced strain. This has resulted in prematurely terminating the crystal


growth while the web was still widening. Thus the full width capabilities of our experimental configurations have not yet been realized. This factor introduces an extra thermal requirement in the design of experimental configurations in addition to maximizing web width. The origin of the thermally induced strain and strategies for minimizing its harmful effects are discussed in more detail later in this report.

Crucibles fabricated by Amersil Corp. have been obtained and used during this period. These have substantially improved run-to-run reproducibility by minimizing the variations in fit between crucible and susceptor which had plagued us previously.

Thermal Modeling Related to Dendritic Web Growth

In the present development program two separate thermal models are being developed as design tools to facilitate the development of appropriate crucible and susceptor configurations. The first model, which calculates the three dimensional temperature distribution in the susceptor and melt, has as its goal the development of a temperature distribution conducive to the growth of wide dendritic web. The second model, which analyzes the dissipation of the latent heat of fusion both to the web itself and to the supercooled melt, has as its main goal the development of a slot geometry conducive to increased growth velocity. This model also provides the basic temperature data necessary for an analysis of any thermally induced stress in the growing ribbon.

During this quarter, the first model was completed and temperature distributions were calculated for a series of lid slot geometries, some of which are shown in Fig. 1. These initial results showed considerable scatter in the temperature plot, a "grain" which was attributed to the rather coarse net of connections used to model the radiation transfer from the melt surface. The melt surface was modeled as a rather large number of elements, and several elements were grouped to a single radiation link. Initially, it was thought that the "grain"



Dimensions in mm

Fig. 1 — Lid slot geometries

in the output could be tolerated and reasonable results obtained by averaging the points. In one instance, however, the calculations showed an unmistakable temperature minimum in the temperature profile when there was no physical reason for such a minimum to occur. Since a modest amount of precision if not accuracy was desired, especially near the center of the melt, the model was refined by making radiation links to every surface node. These three links represented the radiation transfer to the slot, to the lid, and to the wall of the susceptor above the melt. When this modified version of the model was run, the scatter in the temperature profiles was essentially eliminated and the unexpected minimum was not observed. Two typical melt surface temperature profiles are shown in Fig. 2. One of the profiles is for the lid geometry with slot 1, and the other profile is for slot 5, a modification of slot 2 where the total length has been increased to 70 mm. Also shown in Fig. 2 is the temperature profile along a radius perpendicular to the slot. This profile is essentially the same for both slots. It can be seen that the temperature profile parallel to the slot is essentially flat for 1 to 1.5 cm either side of center, which is consistent with the observation that the web continues to widen even at 27 mm total width.

It should be noted that the temperatures plotted in Fig. 2 are "adjusted temperatures;" the computed temperatures have been adjusted to give 1685°K at the center of the slot. Although measured temperatures in the susceptor wall have been used as the boundary conditions for the model there is some uncertainty in the actual thermocouple calibrations, etc. and the actual calculated temperatures differ by about 6° from the measured temperatures in a system. From a thermal model standpoint, this differential is not significant, and considering the uncertainties in the thermal constants of the materials, especially the heat transfer from the molybdenum susceptor to the silicon melt, this agreement seems excellent.




Fig. 2 — Calculated temperatures on melt surface

These results seem to validate the thermal model and it can now be used as a design tool for further development of susceptor and lid configurations. Two extensions of the model are presently under development. The first is a circular crucible and susceptor similar to the present design but with a 106 mm diameter crucible instead of the present 79 mm crucible; the susceptor dimensions are unchanged (see Drawings 1689B31, items 1 and 2, and Drawing 8520D49). In addition, an elongated crucible and susceptor are being modeled (Drawings 8520D52 and 1691B62).

The second thermal model describes the modes of dissipation of the latent heat of freezing in order to develop thermal designs for faster growth. As with any ribbon growth technique, part of the latent heat is dissipated through the growing ribbon itself. In addition, since dendritic web grows from a supercooled melt, some of the latent heat is dissipated to the liquid silicon. Both heat loss modes have been modeled, and a thickness-velocity curve has been generated for a lid configuration which has actually been used to grow web. A comparison of the experimentally observed thickness-velocity data with the predictions of the model is shown in Fig. 3. It can be seen that the agreement between theory and experiment is excellent, which gives a high degree of confidence both for the overall model and for the individual components of the model.

The particular lid design for the case shown in Fig. 3 was the starting geometry in a series of experiments on the effect of beveling the edges of the slot. The lid was relatively thick (8 mm) and had no bevel on the slot. As can be seen, this low heat loss condition gave relatively slow growth, e.g., a 150 μ m web would grow at only 1.3 cm/min. A 3 mm x 3 mm bevel on the slot increased this velocity to about 2 cm/min, and a 6 mm x 6 mm bevel increased the velocity to about 3.5 cm/min. In addition to such parameters as the effective lid thickness (slot bevel), the thermal model also indicates that other parameters such as lid temperature, top shield temperature, slot width, melt level below lid, etc. can be used to tailor the temperature profile in the growing web.




Fig. 3 — Thickness - velocity behavior

Since these factors all produce a multitude of other interactions in the growth behavior, continued study and development is necessary to arrive at a configuration which could be considered optimum.

Mechanical and Dimensional Characterization

In keeping with the program emphasis on the growth of wide dendritic web, much of the material characterization has been dimensional. The widening rate of the crystals is of particular interest, as well as the steady state width for a given system configuration. The widening rate data for the crystals grown during the quarter is shown in Table 1, both in terms of dW/dL and dW/dt . There is a moderate amount of scatter in the data, but some trends can be discerned. First, the first crystals pulled during a run tend to have the fastest widening rates. This apparently has to do with the level of the melt below the crucible lid which in turn affects the heat loss from the meniscus. Second, crystals pulled from melts having beveled slots in the lid widen faster than crystals pulled through unbeveled slots. This apparently is the result of modification of the heat loss from the meniscus at the edges of the dendritic web. The variations in slot geometry should have little effect on the temperature distribution near the center of the melt as a whole, but could have a somewhat greater effect on the heat loss from the meniscus regions. A variety of slot designs are being considered for other reasons and the effect on the widening rate will be studied.

Perhaps more important than the widening rate itself, is the tendency for the crystals to reach a steady state width. In most instances, the dendritic webs are continuing to widen when growth is purposely terminated. Although in some instances a tendency for steady state width is seen, most widening behavior is exemplified by the width-length curve shown in Fig. 4 for crystals R172-4 and R172-6. This result is consistent with the calculated melt temperature profile for slot 5 shown in Fig. 2. Even with a 76 mm diameter crucible, the

Table 1
Dendritic Web Widening Rates

Crystal Number	Widening Rate $10^3 \times \frac{dW}{dL}$	Thickness μm	Widening Rate $10^3 \times \frac{dW}{dt}$ cm/min	Remarks
140-1	7.25	210	16.0	
140-6	6.45	152	13.4	
141-1	7.35	315	15.3	
141-2	6.68	215	13.9	
141-4	7.40	203	15.4	
147-3	7.05	127	11.7	7.9 mm thick lid with 6.4 x 57.2 mm straight slot; no bevel in slot.
147-4	6.15	130	9.5	"
147-5	5.50	116	8.36	"
149-1	6.65	127	12.9	12.7 mm dia. holes added to above slot.
149-4	5.70	125	9.5	"
150-6	7.67	121	16.1	"
151-5	8.95	124	16.1	"
151-7	9.10	114	16.4	"
151-9	7.90	124	13.1	"
152-1	9.20	193	17.7	Lid as above with 3 x 3 mm beveled slot.
152-2	8.35	175	16.1	"
153-1	8.25	188	16.0	"
153-3	8.16	132	15.8	"

Table 1 (cont.)
Dendritic Web Widening Rates

Crystal Number	Widening Rate $10^3 \times \frac{dW}{dL}$	Thickness μm	Widening Rate $10^3 \times \frac{dW}{dt}$ cm/min	Remarks
154-1	8.14	150	15.0	
154-2	7.92	150	14.3	
154-3	6.14	155	11.9	
154-6	5.76	165	9.6	
156-1	6.90	160	13.4	Dogbone slotted lid; 6.3 mm wide terminated by 12.7 mm dia. holes on 44.5 mm centers; 3 x 3 mm bevel. (oxide problems)
156-2	4.80	168	9.3	
156-3	5.54	150	10.5	
157-1	7.78	165	15.1	"
157-3	7.78	140	15.1	
157-4	4.80	122	8.7	
160-1	8.65	210	18.0	"
160-2	8.67	165	16.8	
160-3	7.80	170	14.0	
163-1	8.30	146	15.6	Straight slot, 6.4 mm wide by 66.6 mm long. No level.
163-2	7.00	120	12.6	
165-1	7.80	145	15.1	
165-2	6.40	162	11.5	"

Table 1 (cont.)
Dendritic Web Widening Rates

Crystal Number	Widening Rate $10^3 \times \frac{dW}{dL}$	Thickness μm	Widening Rate $10^3 \times \frac{dW}{dt}$ cm/min	Remarks
170-1	7.76	173	15.1	Straight slot, 6.4 mm wide by 66.6 long. No bevel.
170-2	6.67	130	12.9	
170-3	7.30	128	13.1	
171-2	6.10	148	11.8	Slot as above, but beveled at ends.
171-3	6.10	150	11.8	
172-4	7.00	160	14.0	Straight slot, 7.4 mm wide by 66.6 mm long, beveled at slot ends only.
172-6	8.10	150	14.6	
173-2	7.70	165	15.0	
173-4	7.10	113	15.6	"
173-5	7.06	113	13.5	




Fig. 4 - Typical dendritic web widening

ultimate steady state width for dendritic web has not yet been reached. Data from runs where some curvature is seen in the W-L curve leads to an estimate of 30 to 40 mm as the steady state width for the present system. This would be consistent with the calculated thermal profiles.

Web Thickness

The thickness of a web crystal growing at a given velocity depends on the supercooling of the melt and on the ability of the web itself to radiate heat. Both of these factors were included in the thermal modeling for the velocity-thickness calculations, and it was found that such factors as the lid thickness and bevel on the slot should have a strong effect. Web thickness measurements have, therefore, been directed toward validating the thermal model; specific data is given in Table 1 with the widening rate data and in the run summary, Appendix 6.1. For practical reasons, the growth velocity for most runs is adjusted to give crystal thicknesses between 100 and 200 μm .

Residual Stress

Strain in dendritic web crystals is becoming an increasingly important consideration as longer and wider crystals are being grown. Early in the program, the growth of many crystals terminated spontaneously because of what we believe to be convectively generated temperature fluctuations in the melt. With improvement in thermal conditions, this phenomenon has become rare and instead some crystals develop a warp and twist after several meters of growth and the pull must be terminated in order to remove the crystal through the withdrawal duct. This behavior is suggestive of the thermally generated stress found by people working with other ribbon growth techniques in that the problem is accentuated in wider crystals. An excellent general discussion of the phenomenon is given in the Mobil-Tyco Annual Progress Report of September, 1976.⁽¹⁾

Briefly, a non-linear temperature profile along the length of the growing ribbon can cause stresses which in turn can produce both plastic and elastic deformations in the ribbon. These stresses are functions of both the ribbon width and the higher derivatives of the temperature profile. For example, a major component of the axial stress is given by

$$\sigma_{zz} = \frac{\alpha Y W^2}{6} \left(1 - 3 \frac{y^2}{W^2} \right) \frac{d^2 T}{dz^2}$$

where α is the thermal expansivity, Y is Young's modulus, W is the half width of the ribbon, the z coordinate is along the length of the ribbon and the y coordinate is in the plane of the ribbon perpendicular to z . Other stress components depend on higher derivatives and also have a higher power in the width dependence. Thus as wider ribbons are grown, thermal stresses should become of increasing importance. In order to reduce the stress in the growing crystal, the curvature of the temperature profile must be reduced. Other ribbon growth techniques accomplish this flattening of the temperature gradient by the use of after heaters; in the dendritic web technique, the thermal analysis developed for increasing the velocity also shows that a great deal of control over the temperature profile is possible by careful design of the susceptor cover. In fact, in some instances, the second derivative, $d^2 T/dz^2$ is actually negative over a portion of the crystal near the melt; the hot slotted lid actually is heating the web.

The experimental study of the residual stress in dendritic web crystals has only recently been started. The technique which has been used to characterize any residual stress in the dendritic web is the well known method of measuring the curvature of a ribbon which has been split down the center. The relevant equation is

$$\sigma = \frac{Y W}{4} b_2$$

where σ is the stress (before splitting, the ribbon has a tension σ at the edges, and a compression $-\sigma$ at the center), Y is Young's modulus, W is the total width of the ribbon and b_2 is the coefficient in quadratic expression for the width of the split as a function of length

$$y = b_0 + b_1x + b_2x^2$$

Here y is the separation between the two halves of the crystal and x is a coordinate along the length of the crystal. Fitting the experimental data to this quadratic form removes a variety of experimental uncertainties such as the origin of the crack, and any possible tilt in the x axis or constant separation of the two pieces of the crystal. In practice, the actual data shows a coefficient of determination of 0.998 or better, indicating an excellent agreement of the experiment to the assumed model. Data for some of the web samples is shown in Table 2. The stress values seem to be generally smaller than reported for other ribbon growth techniques. Although it may be a fortuitous result, the crystal with the lowest residual stress was grown with a lid which should have had a smaller d^2T/dz^2 than the other lids. Further design studies and experiments along this direction are being undertaken.

Table 2

Crystal No.	Width cm	Thickness μm	Growth Speed cm/min	Residual Stress $\times 10^8$ dynes/cm ²	Residual Stress psi
R136-9	1.60	188	1.94	2.4×10^8	3480
R153-1	1.65	170	1.94	2.0×10^8	2915
R160-2	2.28	165	1.94	2.1×10^8	3090
R165-4	1.52	84	1.94	1.9×10^8	2712
R172-5	1.46	173	1.80	1.0×10^8	1522

Crystal Perfection Studies

To date, only a limited amount of study has been given to the crystalline perfection of the dendritic web crystals. A limited number of x-ray topographs and etching studies have been done, however, and so far the results are in agreement with the observations of earlier investigators.⁽²⁻⁶⁾ Dislocations apparently arise primarily from two sources: the button portion of the crystal, and as bursts in the bounding dendrites. Various possible techniques will be investigated for reducing these imperfections in the crystal. Although the thermal stress may be a significant factor in the degeneration of the web crystals, other mechanisms involving dislocations cannot be ruled out, and these studies will be continued at an accelerated pace.

Solar Cell Studies

Since solar cells are the anticipated end product of a dendritic web crystal growth process, solar cell studies are being conducted as part of the overall growth program. Two general tasks are being undertaken in the solar cell area: 1) the use of a standard cell design and fabrication process to provide an evaluation of the material on a semi-routine basis and 2) an investigation of techniques for improving the efficiency of solar cells made on dendritic web.

The solar cell design chosen as a standard for material evaluation is one that has been in use for some while in other studies.⁽⁷⁾ The general design of the test device is shown in Fig. 5. This design was originally intended for making standard test cells on Czochralski material, and contains a number of test devices in addition to the 1 cm square cell in the center of the pattern. When this mask is used for fabricating devices on dendritic web material, only the central portion of the patterns is used. A typical dendritic web cell and a "baseline" cell on a Czochralski wafer are shown in Fig. 6.

Technical drawing of a mechanical part with dimensions in centimeters.

Dimensions in Centimeters

View A (Front View): Shows a rectangular block with a central slot. The total width is 0.050. The slot width is 0.025. The slot depth is 0.025. The block is divided into four quadrants by a central vertical line.

View B (Top View): Shows a circular cross-section with a central slot. The outer diameter is 0.150. The slot width is 0.025. The slot depth is 0.064. The block is divided into four quadrants by a central vertical line.

View C (Side View): Shows a circular cross-section with a central slot. The outer diameter is 0.140. The slot width is 0.050. The slot depth is 0.025. The block is divided into four quadrants by a central vertical line.

View E (Detail View): Shows a detail of the central slot, which is a rectangular block with a central slot. The total width is 0.050. The slot width is 0.025. The slot depth is 0.025. The block is divided into four quadrants by a central vertical line.

19

ORIGINAL PAGE IS
OF POOR QUALITY




Fig. 6 Dendritic Web and Baseline Czoehralski Cells

The device processing technique being used for cell fabrication is also very similar to that being used for other studies, with several small changes appropriate to the web material being processed. First, the web surface is in a highly perfect condition as grown, so no other surface preparation other than an oxide removing rinse is done. More importantly, since the material being grown on this program is of the order of 150 μm thick (6 mils), the cell structure includes a P^+ layer on the back surface to provide a minority carrier reflecting back surface field (BSF). The entire process is summarized in the sample run sheet shown as Fig. 7. In a given fabrication run, the individual cell blanks are identified so that material from several crystals can be run and separately identified. Also included in every run are five Czochralski wafers run as baseline material to give a check on the processing reproducibility.

Once the cells are fabricated, they are measured under simulated AM1 illumination and the data fed to a computerized data bank for reduction and printout of the device characteristics. A typical printout is shown in Fig. 8. The Baseline cells are identified by a "B" in their ID, and dendritic web cells by an "R" (except for 1R^* which is a standard cell for calibrating the light source). An asterisk by the ID means that sample was not used in calculating the group averages. ISC is the short circuit current; VOC the open circuit voltage; IP the peak power; FF the fill factor, EFF is the efficiency and OCD is a lifetime measured from the diode decay of the device. The other data, $\text{LOG}(\text{IO})$, N, and R are parameters used in fitting the data to a standard model. The computer program computes the parameter averages and standard deviations for the baseline cells and the experiment cells and also gives percent of baseline for the experiment cell averages.

Generally, the solar cells fabricated on this program are measured without an anti-reflectance (AR) coating; if an AR coating is used, it is noted on the data printout. Several sets of cells have

Web grown silicon N+/P/P+ Solar Cells (Back Side, P+ identified by number)

Start Date:		PROCESSING LOG	Run or Sample RIBON	
Material:				
Quantity:	Engr. P. Blais			
		9C40 RIBON 77		
Date Tech.	Process	Special Instructions, Measurements, etc.	Disp.	
	Identification	Scribe serial numbers on either side of web near one end to identify P+ side of structure	C	E
	CLEAN (1)	HF:H ₂ O (1 to 10 ratio) dip 15 sec. H ₂ O ₂ - NH ₄ , H ₂ O ₂ - HCl		
	BORON (2) DIFF.	Boron Deposition, BBr ₃ @ 960°C 2-20-2 min. Numbered side up. Very slow pull (5 min/2 inches)		
	REMOVE (3) OXIDE	3:1 (H ₂ O:HF) until all oxide is removed R _s = _____ Ω/□ (Target value = 60 Ω/□)		
	CVD (4) SiO ₂	Deposit 5000 Å CVD oxide @ 850°C on back (numbered) side. Slow cool by reducing power very slowly (10 min.)		
	ETCH (5) SILICON	Mask CVD SiO ₂ with apeizon wax etch silicon on bare side, strip wax, H ₂ SO ₄ @ 90°C for 5 min. 44 cc HF + 26 cc HNO ₃ + 29 cc Acetic 5°C, Etch time = 5-10 sec Etch silicon between 5 to 8 μm deep Check Conductivity Type		
	CLEAN (6)	HF:H ₂ O (1 to 10 Ratio) dip 5 sec. H ₂ O ₂ - NH ₄ , H ₂ O ₂ - HCl		
	POCL ₃ (7) DIFFUSION	Diffusion Temp. 825°C Time 50 min. Source Temp. = 0°C Flow Rates 200 cc/min - N ₂ /Source: 1560 cc/min - N ₂ Carrier 62.5 cc/min O ₂ Slow cool by pulling 3 inches/5 min.		
	REMOVE (8) OXIDE	Strip deposition oxide 3:1 (H ₂ O:HF) Measure, R _s = _____ Ω/□ (Target value = 60 Ω/□)		
	CLEAN (9)	H ₂ SO ₄ : H ₂ O ₂ 87°C, 5 min. Strip all oxides in darkness with buffered HF. 10/1 H ₂ O/HF Dip 10 sec		
	METAL (10)	Top Side (side not numbered) only Ti 1500 Å 20 Å/sec Pd 500 Å 10 Å/sec Ag 20000 Å 40 Å/sec		
	PHOTO (11) RESIST	Mask #1 (contact grid) Waycoat IC, 4000 rpm, h = 1.7 μm Exposure time = 3 sec (I _d = 0.2 μa)		
	ETCH (12) METAL	Ag-20-60 H ₂ O ₂ & Ammonium Hydrox. -10-15 sec. Pd + 30 cc HCl + 10 cc HNO ₃ -5 sec Ti-150 cc H ₂ O + 60cc HCl + 30cc Ammonium Fl. 5 sec		
	CLEAN (13)	H ₂ SO ₄ at 75°C - 3 min Rinse in D.I. H ₂ O		
	METAL (14) BACK	Ti 1500 Å - Pd 500 Å Back side is numbered Ag 20 KA		
	SINTFR (15)	Temperature 550 °C Time 15 Min. Atmosphere = H ₂ , 500cc/min.		
	PHOTO- (16) RESIST	Mask #2 (Mesa) Waycoat SC, 7000 rpm, h - 4.0 μm Exposure time = 15 sec (I ₂ = 0.6 μa), Apiezon wax back side		
	ETCH (17) SILICON	44 cc HF + 26 cc HNO ₃ + 29 cc Acetic 5°C, Etch time = 5-10 sec Etch silicon between 5 to 8 μm deep, Talystep _____ μm.		
	TEST (18)			

original 6/3/77

Fig. 7. Solar Cell Run Sheet

ORIGINAL PAGE IS
OF POOR QUALITY

70621R RIBON 1003 RETEST W071 00 000
RIBON 10/20/77 AM1: P0=91.60MW/CM²

AR COATING

ID	ISC	VOC	IP	LOG(10)	N	K	FF	EFF	ODD
1R*	22.50	.549	20.11	-6.162	2.03	-.34	.712	9.30	.00
1B	31.00	.579	28.77	-8.419	1.40	.21	.765	14.51	15.60
2B	32.50	.583	30.19	-8.527	1.38	.28	.764	15.31	19.50
3B	31.00	.569	28.72	-8.216	1.42	.14	.763	14.24	12.35
4B*	23.90	.524	14.99	-4.686	2.86	10.86	.345	4.56	.00
5B.*	31.40	.547	28.90	-6.697	1.76	-1.67	.807	14.65	13.00
1K	30.40	.561	28.32	-8.950	1.26	.49	.762	13.75	9.10
5K	29.30	.542	26.72	-6.945	1.67	-.27	.746	12.53	4.94
6K	29.80	.539	26.94	-6.498	1.81	-.29	.732	12.44	1.82
8K	29.60	.538	24.92	-4.011	3.62	-2.73	.677	11.40	3.38

AVERAGES: 70621R BASELINE W071 00 000

	31.50	.577	29.23	-8.387	1.40	.21	.764	14.69	15.82
STD	.71	.006	.68	.129	.01	.06	.001	.45	2.92

70621R RIBON 1003 RETEST

	29.78	.545	26.72	-6.601	2.09	-.70	.729	12.53	4.81
STD	.40	.009	1.21	1.758	.90	1.22	.032	.83	2.71

PERCENT OF BASELINE

	94.5	94.5	91.4	121.3	149	*****	95.5	85.3	30.4
STDZ	3.4	2.6	6.4	22.5	67	814.2	4.3	8.5	25.9

Fig. 8 Sample Data Print-Out

been measured before and after a standard AR coating of 850 \AA of SiO_2 and the results indicate that the efficiency of the cell is increased by $41.2 \pm 2\%$. A cell with an AM1 efficiency of 10.2% uncoated, will thus yield a 14.4% cell when coated. Therefore, in order to facilitate comparison of our data with cell data from other sources, we will report cell efficiencies converted to AR coated values unless otherwise noted.

Several general conclusions can be stated from the data generated so far. First, within a cell fabrication run, data from a given dendritic web crystal clusters very tightly. This would indicate that solar cell parameters are a valid means for characterizing the web material. Cell data from a given crystal processed in different runs is somewhat more scattered, but still is representative of the crystal. Second, dendritic web can be processed into extremely good solar cells; some crystals yield devices with greater than 14% AM1 efficiency. Conversely, web samples chosen from crystals with obvious defects such as lineage or mosaic structure yield cells with only about 10.3% efficiency. Moderate quality material yields cells in the 12 to 13 percent range. Studies are now in progress to correlate solar cell performance with the structural perfection of the starting material.

The second aspect of the solar cell program is to develop processing techniques for dendritic web which will yield solar cells with higher efficiency. The current approach to this task is to consider that the processing of dendritic web is the same as for Czochralski material if due account is taken of the generally smaller thickness of the web. Studies so far indicate that the actual junction on the web is of extremely high quality. Attention is, therefore, being given to the matter of the back surface P^+ layer. Presently this is being fabricated by a boron diffusion process, which has an industry reputation for some variability. A process based on an aluminum doped back surface is under investigation. This process has the promise of greater reproducibility as well as possibly providing optical as well as electrical reflection

at the cell back surface. Since solar cells with greater than 14% efficiency have already been processed with the boron technique, enhanced optical reflectivity could bring this figure above 15%. Currently, equipment and materials are being set up to implement this process.

Facility Design and Construction

Design has been completed for a new web growth facility which will have dimensional capacity for web widths to four inches. Mechanical and electrical design of the system closely follows the concept of the most recent existing facility and is scaled up where needed to satisfy the greater dimensional requirements. The thermal design of the system is based upon thermal models and recent experience. Fabrication of components and assembly are in progress.

A conceptual design has been developed to permit, at some possible future time, conversion of the new facility from low frequency induction heating to more conventional and lower cost resistance heating.

The existing web growth facility is in the process of being modified to permit web growth of width up to three inches.

3. PLANS FOR THE NEXT PERIOD

Systematic changes in susceptor and lid configuration aimed at maximizing web width and minimizing thermally induced strain will be continued, utilizing guidance from the thermal modeling results.

The experimental effort to date has utilized 75 mm diameter crucibles. Crucibles of 100 mm diameter have been ordered and will be tested in the near future.

Thermal models of two new crucible/susceptor configurations will be completed and applied to the design of appropriate hardware. The first new design will be a circular crucible/susceptor with a 100 mm ID crucible. The second will be an elongated susceptor for use in the new web growth facility. The second thermal model (model of latent heat dissipation) will be applied to the problem of reducing curvature in the temperature profile in the web. The object will be to reduce possible thermal stress in the growing crystal.

Much of the characterization of the dendritic web will still be of a dimensional character. In addition, measurement of residual stress in appropriate sample will be continued to evaluate the effect of lid design. Similarly measurement of crystalline perfection will be continued and expanded. Solar cell fabrication to characterize the dendritic web material will be continued.

The new web growth facility will be completed and placed in operation. The existing facility will be modified to provide greater capacity.

4. NEW TECHNOLOGY

No new technology occurred during this reporting period.

5. REFERENCES

1. A. D. Morrison, et al., "Large Area Silicon Sheet by EFG," Annual Progress Report, ERDA/JPL 94355/76-11, Sept. 15, 1976.
2. D. L. Barrett, et al., "Growth of Wide, Flat Crystals of Silicon Web," J. Electrochem. Soc. 118, 952 (1971).
3. S. O'Hara, "Dislocations in Webs of Germanium and Silicon," J. Appl. Phys. 35, 409 (1964).
4. S. O'Hara and G. H. Schwuttke, "Dislocation Reactions in Silicon Web-Dendrite Crystals," J. Appl. Phys. 2475 (1965).
5. T. N. Tucker and G. H. Schwuttke, "Growth of Dislocation Free Silicon Web Crystals," Appl. Phys. Lett. 9, 219 (1966).
6. T. N. Tucker, "Topography of Silicon Web Crystal Surfaces," Electrochemical Technology 4, 546 (1966).
7. R. H. Hopkins, et al., "Silicon Materials Task of the Low Cost Solar Array Project: Fifth Quarterly Report and Summary," ERDA/JPL 954331-77/1, (1977).

6. APPENDIX

6.1 Growth Run Detail Summary for This Reporting Period

6.2 Complete Set of Design Drawings for Silicon Web Growth Facility

GROWTH RUN DETAIL SUMMARY

Run No.	Web No.	ΔT °C	Pull Rate cm/min	Length cm	Width mm	Thickness µm	Comments	
R-139		Dry run to test temperature stability and response time.						
R-140	1	4.4	2.2	75	12.5/16.7	203	Same configuration as R-138 116.3 gm Si 2 x 1017 DOPSIL pellet	
	2	4.8	2.2	18	14.2	190		
	3	4.7	2.2	16	12.5/14	168		
	4	5.4	2.2	32	13.5/15.1	147		
	5	-	2.2	13	14.2/15.2	145		
	6	5.9	2.1	81	13/17.4	152		
	7	4.5	2.0	134	11.7/13	145		
R-141	1	4.8	2.1	59	12.6/16.6	250	Same configuration as R-138 110.3 gm Si 2 x 1017 DOPSIL pellet	
	2	4.7	2.0	75	12.7/16.4	212		
	3	5.0	2.0	39	15/15.8	160		
	4	3.9	2.0	84	14.7/20.2	212		
R-142	1	5.2	2.0	28	12/14.2	183	0.95 cm high x 2.70 cm long after shields added along slot 114.9 gm Si 2 x 1017 DOPSIL pellet Plagued by oxide deposition	
	2	4.7	1.8	32	15/16.8	208		
R-143	Abort, inadequate power coil returned							
R-144	Power Failure							
								Lid dvg. 2612C82-07
								119.3 gm Si
								2 x 1017 DOPSIL pellet
								Same configuration as R-143
							119.6 gm Si	
							2 x 1017 DOPSIL pellet	

GROWTH RUN DETAIL SUMMARY

Run No.	Web No.	ΔT °C	Pull Rate cm/min	Length cm	Width mm	Thickness mm	Comments
R-147	1	4.7	1.7	42	8.3/9.8	108	Same configuration as R-143 118.2 gm Si 2 x 1017 DOPSIL Pellet
	2	4.8	1.7	41	8/9.2	115	
	3	*	1.7	77	9.2/13.7	133	
	4	*	1.5	101	8.9/14.3	145	
	5	*	1.5	136	8.6/15.7	150	
	6	*	1.5-4.0	102	-	10.7-20	
R-148	1	3.9	1.7	8	9.5	170	Same configuration as R-143 119.2 gm Si 2 x 1017 DOPSIL Pellet
	2	2.8	1.7	36	9.6/11.2	168	
	3	3.7	1.7	7	7.8	145	
	4	3.7	1.7	29	9/10.2	163	
	5	3.3	1.7	17	9.4/10.2	165	
	6	-	2.1	12	9.4	93	
	7	4.3	1.7	12	13.2/13.5	163	
	8	3.7	1.8	31	9.8/10.4	125	
	9	3.8	1.8	15	9.6/9.9	113	
	10	-	1.7	56	8.6/10.8	118	
R-149	1	*	1.9	220	10.7/21.1	113	Lid dwg. 2612C82-08 119.4 gm Si 2 x 1017 DOPSIL pellet
	2	*	1.8	201	10.8/18.5	135	
	3	3.6	1.8	11	-	100	
	4	-	1.7	117	8/14.3	125	
R-150	1	3.6	1.8	18	8.8/9.8	150	Same configuration as R-149 119.2 gm Si 2 x 1017 DOPSIL Pellet
	2	-	1.8	6	11.7	155	
	3	3.4	1.8	12	8.9/9.6	138	
	4	3.6	1.8	22	6/7	110	
	5	-	1.7	24	9.3/10.2	138	
	6	3.0	1.7	71	8.2/13.6	121	
	7	3.6	1.5-3.3	92	7/10.6	114-30	

Thickness vs. velocity run

* Strong drift of "hold" during growth.

GROWTH RUN DETAIL SUMMARY

Run No.	Web No.	AT °C	Pull Rate cm/min	Length cm	Width mm	Thickness µm	Comments
R-151	1	3.8	1.9	20	10.3/10.8	138	Six vent slots added to bottom of lid No.-08 119.8 gm Si 2 x 1017 DOPSIL Pellet
	2	3.9	1.8	7	9.8	163	
	3	4.1	1.8	9	10.6/11.0	145	
	4	2.9	1.8	40	9/11.2	150	
	5	2.9	1.8	127	8/18.6	124	
	6	2.4	1.8	41	11.6/14.6	138	
	7	2.5	1.8	89	11.4/18.0	111	
	8	2.5	1.7	6	8.9/9.3	109	
	9	2.5	1.7	132	10.5/20.3	123	
R-152	1	3.0	1.9	101	8.5/16.7	175	Slot beveled, .125 x .125 in. To lid No. -08. 119.9 gm Si 2 x 1017 DOPSIL Pellet
	2	3.4	1.9	126	10.5/18.4	150	
	3	4.8	1.9	13	13.4/14	150	
	4	6.0	1.9	145	8.8/11.8	118	
R-153	1	4.0	1.9	195	8.8/23.2	170	Same configuration as R-152 120-1 gm Si 2 x 1017 DOPSIL Pellet Thickness vs velocity run
	2	-	1.9	20	8.8/9.3	108	
	3	3.3	1.8	143	10/19.3	163	
	4	4.2	1.8-2.9	118	8.7/15.1	109-51	

ORIGINAL PAGE IS
OF POOR QUALITY

GROWTH RUN DETAIL SUMMARY

Run No.	Web No.	ΔT °C	Pull Rate cm/min	Length cm	Width mm	Thickness mm	Comments
R-154	1	3.9	1.9	111	8.8/16.5	150	Accumulate more growth experience on repeat of same configuration as R-152 119.9 gm Si 2 x 10 ¹⁷ DOPSIL pellet
	2	3.9	1.8	109	10.9/17.0	150	
	3	3.4	1.9/2.6	95	7.8/12.8	155/60	
	4	3.5	1.8	86	9.9/13.2	115	
	5		1.8	77	9.6/13.1	113	
	6	3.2	1.7/2.1	198	8.0/11.7	165/110	
R-155	1	5.5	2.0	41			Provide independent experience to 2nd furnace operator. Same configuration as R-152
	2	5.2	2.0	95	8.7/13.5	200	
	3		2.0				
	4		2.0				
	5		2.0	20	9.9/11.1	150	
	6		2.0	101	9.4/17.0	113	
R-156	1	3.4	1.9	65	8.4/11.4	160	Test new lot of crucibles in known configuration, same as R-152 119.5 gm Si 2 x 10 ¹⁷ DOPSIL pellet Oxide in slot
	2	3.7	1.9	67	9.7/13.0	162	
	3	2.7	1.9	57	10.4/13.3	146	
R-157	1	3.2	1.9	217	9.7/26.2	165	Gather more growth data Measure melt surface temperatures Same configuration as R-152 120.6 gm Si 2 x 10 ¹⁷ DOPSIL Pellet
	2	3.0	1.9	30	10/11.5	119	
	3	2.8	1.8	221	8.6/20.2	140	
	4	2.8	1.8/2.6	120	10.8/12.8	122/58	

ORIGINAL PAGE IS
OF POOR QUALITY

GROWTH RUN DETAIL SUMMARY

Run No.	Web No.	AT °C	Pull Rate cm/min	Length cm	Width mm	Thickness mm	Comments
---------	---------	----------	---------------------	--------------	-------------	-----------------	----------

R-158 No web growth - Dry run to measure susceptor temperatures for modeling input.

R-159 This run dedicated to measuring melt surface and melt bottom temperatures.
The introduction of oxide during these manipulations negated subsequent efforts to grow useful web.

P-160	1	4.7	2.1	88	11.8/18.4	210	Test growth with higher melt level Same configuration as R-152 134.7 gm Si 2 x 10 ¹⁷ DOPSIL Pellet
	2	4.6	1.9	182	11.5/25.2	165	
	3	2.7	1.8/1.5	167	9.4/18.5	170/220	
	4	3.1		Thickness vs. velocity run			

R-161	1	3.1	1.9	102	11.5/17.2	220	Repeat run with high melt level Same configuration as R-152 134.4 gm Si 2 x 10 ¹⁷ DOPSIL Pellet.
	2	3.4	1.9	74	10.7/14.5	183	
	3	3.8	1.9	45	10.2/12.9	163	
	4	3.9	1.9	22	13.1/14.2	145	
	5	3.8	1.9	101	7.7/13.3	138	

R-162 Run aborted due to power failure after melting.

Test new lid configuration.
Straight slot 6.67 cm long x 0.64 cm wide
Lid no. -10.

R-163	1	2.6	1.9	154	11.6/22.6	146	Repeat of R-162 133.2 gm. Si 2 x 10 ¹⁷ DOPSIL Pellet
	2	2.3	1.8	119	11.1/17.6	120	

Run aborted due to loss of power.

GROWTH RUN DETAIL SUMMARY

Run No.	Web No.	ΔT °C	Pull Rate cm/min	Length cm	Width mm	Thickness mm	Comments
R-164	Abort; Si touched lid during melt down						Repeat R-162 lid configuration
R-165	1	3.7	1.9	160	11.1/22.1	145	Repeat R-162 lid configuration
	2			128	10.5/15.3		135.2 gms Si
	3	3.4		82	11.3/14.4		2 x 10 ¹⁷ DOPSIL pellet
	a	-	1.4	-	-	165	
	b	-	1.9	-	-	86	
	c	-	2.6	-	-	48	
	4			112	12.2/14.6		
	5			32			
R-166	Abort; Si touched lid during melt down						
R-167	1		2.4	29	11.7	388	Test effect of 6.4 x 6.4 mm bevel (45°)
	2		2.6	24	10.2/10.8	263	on long straight slot of above lid
	3		2.4	11	9.9/10.4	300	121.6 gms Si
	4		2.6	27	10.6/11.1	-	2 x 10 ¹⁷ DOPSIL pellet
	5		2.4/3.4	72	-	283/125	
	6		2.4	24	12.9/13.7	238	
R-168	Abort; Si touched lid during melt down						
R-169	1		2.4	22	10.5/11.7	338	Repeat of R-167 configuration
	2		2.4	43	10.2/12.4	285	118.6 gms Si
	3		-	37	12.6/13.2		2 x 10 ¹⁷ DOPSIL pellet
	a		2.1			365	
	b		2.6			208	
	c		3.4			110	
	4		2.4	12	12.2/12/6	173	
	5		-	12	11.5	-	
	a		2.4	-	-	210	
	b		2.9	-	-	118	

ORIGINAL PAGE IS
OF POOR QUALITY

GROWTH RUN DETAIL SUMMARY

Run No.	Web No.	ΔT °C	Pul. Rate cm/min	Length cm	Width mm	Thickness μm	Comments
R-170	1	2.7	1.9	83	11.2/17.1	173	Test new lid configuration: 6.4 x 66.7 mm straight slot, beveled on ends only, beginning 9.5 mm from ends 118.9 gm Si 2 x 10 ¹⁷ DOPSIL pellet
	2	3.5	1.9	169	8.6/19.3	130	
	3	4.0	1.8	140	10.0/19.9	128	
	4	3.3	-	144	8.8/16.3	-	
	a	-	1.8	-	-	100	Bevel on above lid (R-170) slot extended additional 6.4 mm towards center 113.6 gm Si, 2 x 10 ¹⁷ DOPSIL pellet
	b	-	1.7	-	-	113	
	c	-	1.9	-	-	90	
	d	-	2.2	-	-	70	
R-171	1	3.2	1.9	107	10.3/13.3	163	Test effect of wider slot. Slot of above lid (R-171) widened to 7.4 mm
	2	4.8	1.9	99	13.3/16.6	148	
	3	4.1	1.9	122	13.5/20.5	150	
R-172	1	3.5	2.2	58	11.1/14.7	200	124.0 gm Si 2 x 10 ¹⁷ DOPSIL pellet
	2	6.0	2.2	53	14.5/16.8	155	
	3	4.5	2.2	89	13.1/17.6	140	
	4	4.9	2.0	132	13.5/21.6	160	
	5	5.3	1.8	Terminated		-	
	6	5.0	1.8	194	13.3/26.4	150	
R-173	1	4.4	2.0	39	11.5/14.3	273	Repeat of R-172 123.1 gm Si 2 x 10 ¹⁷ DOPSIL pellet
	2	3.4	2.0	212	11.5/27.2	165	
	3	4.8	2.2	18	13.3/14.3	130	
	4	4.3	2.2	174	12.7/23.4	113	
	5	3.9	1.9	181	9.4/22.0	113	

SILICON WEB PROCESS DEVELOPMENT

Research Memo 77-9C4-RIBON-M 4

DESIGN DRAWINGS FOR SILICON WEB GROWTH FACILITY
Date of Issue 22, September, 1977

C. S. Duncan

Contract No. 954654

This work was performed for the Jet Propulsion Laboratory, California Institute of Technology, under NASA Contract NAS7-100 for the U. S. Energy Research and Development Administration, Division of Solar Energy.

The JPL Low-Cost Silicon Solar Array Project is funded by ERDA and forms part of the ERDA Photovoltaic Conversion Program to initiate a major effort toward the development of low-cost solar arrays.



Westinghouse R&D Center
1310 Beulah Road
Pittsburgh, Pennsylvania 15235

ROUTING	FIREPROOF VAULT				
				ORIGINAL PAGE IS OF POOR QUALITY	

DRAWING LIST

INDEX	LINE	TITLE OF DRAWING	DRAWING NO.	PAGE		
	1	CHAMBER & FRAME ASS'Y	1289J18	1		
	2	GENERAL ASS'Y	1289J19	2		
	3					
	4	CHAMBER Box WELDM'T	639F477	3		
	5	FRAME DET	639F478	4		
	6					
	7	WORK COIL VERT ADJ DET'S	8504D76	5		
	8	WORK COIL HORIZ ADJ DET'S	8504D77	6		
	9	DETAILS	8506D61	7		
	10	RIBON GUIDE ROLL MECH	8507D32	8		
	11	COVER DETAILS	8508D18	9		
	12	BOX DETAILS	8519D87	10		
	13	COIL LIFT DET'S	8519D93	11		
	14	COIL LIFT DET'S	8519D94	12		
	15	COIL LIFT DET'S	8520D06	13		
	16	BOT. PL COIL LIFT SUB-ASS'Y	8520D12	14		
	17	DETAILS	8520D13	15		
	18	TAPE REEL DET'S	8520D14	16		
	19	TAPE REEL DET'S	8520D15	17		
	20	WEB WITHDRAWAL DUCT	8520D16	18		
	21	MID PL COIL LIFT SUB-ASS'Y	8520D17	19		
	22	SUB-ASS'Y	8520D18	20		
	23	DETAILS	8520D19	21		
	24	DETAILS	8520D31	22		
	25	RIBBON GUIDE DET'S	8520D34	23		
	26	DETAILS	8520D39	24		
	27	COIL DETAILS	8520D40	25		
	28	TOP PL COIL LIFT SUB-ASS'Y	8520D42	26		
	29	ROUND SUSCETOR DET	8520D49	27		

STOCK ORDER (1ST S.O. ON WHICH INF. HAS BEEN SENT TO SHOP)

IDENTIFYING DATA: IN SPECIFYING THIS D NO. ON A STOCK ORDER THE ENGINEER MUST GIVE: -

NAME OF APPARATUS

SILICON WEB FURNACE MOD-2

ENG'R S. DUNCAN

CHECKED BY AND DATE

W. SUMP MAN

9-22-77

DESIGN SPEC.

D 903066

SUB. LETTER

A

SUB. LETTER

SUB. LETTER

SUB. LETTER

SUB. LETTER

WESTINGHOUSE FORM 6541 J

PAGE

1 OF 3

SUB. LETTER

SUB. LETTER

SUB. LETTER

SUB. LETTER

SUB. LETTER

ROUTING	FIREPROOF VAULT				

DRAWING LIST

INDEX	LINE	TITLE OF DRAWING	DRAWING NO.	PAGE			
	1	TOP COVER PL DET	8520D50	28			
	2	OVAL SUSCEPTOR DET	8520D51	29			
	3	TOP ROLLER SYS DET	8520D52	30			
	4	DETAILS	8520D61	31			
	5	WEB GUIDE DET'S	8520D69	32			
	6	DETAILS	8520D78	33			
	7						
	8						
	9						
	10	KNOB DETAILS	257C034	34			
	11	ROD HOUSING SUB ASSY	257C074	35			
	12	BACK COVER WELDM'T	257C251	36			
	13	ROUGHING PUMP ASSY	257C261	37			
	14	BR'G SUPPORT FRAME	2613C30	38			
	15	STORAGE REEL WELDM'T	2613C34	39			
	16	STORAGE REEL DET	2613C35	40			
	17	STORAGE REEL DET	2613C36	41			
	18	VACUUM ELBOW WELDM'T	2613C43	42			
	19	ROUND WORK COIL DET	2613C50	43			
	20	TAP REEL BRACKETS	2613C61	44			
	21	OVAL WORK COIL DET	2613C64	45			
	22	SUPPORT PL DET	2613C70	46			
	23	ROUND SHIELD DET	2613C71	47			
	24	OVAL SHIELD DET	2613C82	48			
	25	OVAL SUPPORT PL DET	2613C83	49			
	26	ROUND WORK COIL ASSY	2613C98	50			
	27	WEB GUIDE SUB-ASSY	2614C09	51			
	28	ROUND TOP SHIELD DET	2614C18	52			
	29	ROUND SUSCEPTOR COVER	2614C19	53			

STOCK ORDER (LIST S.O. IN WHICH INFO. HAS BEEN SENT TO SHOP) IDENTIFYING DATA. IN SPECIFYING THIS D NO. ON A STOCK ORDER THE ENGINEER MUST GIVE: -

NAME OF APPARATUS

SILICON WEB FURNACE MOD-2

ENG'R S. DUNCAN

CHECKED BY AND DATE W. SUMPMAN 9-22-77					
DESIGN SPEC. D 903066	SUB. LETTER A	SUB. LETTER	SUB. LETTER	SUB. LETTER	SUB. LETTER
PAGE 2 OF 3	SUB. LETTER	SUB. LETTER	SUB. LETTER	SUB. LETTER	SUB. LETTER

ROUTING	FIREPROOF VAULT				

DRAWING LIST

INDEX	LINE	TITLE OF DRAWING	DRAWING NO.	PAGE		
	1	PUSH ROD ASS'Y	2614C20	54		
	2	OVAL WORK COIL ASS'Y	2614C23	55		
	3					
	4	ROUND CRUCIBLE DET	1689B31	56		
	5	BLANK COVER PL'S	1690B07	57		
	6	SENSOR HOLDER ASS'Y	1691B12	58		
	7	OVAL CRUCIBLE DET	1691B62	59		
	8					
	9	WORK COIL STANDOFF	6414A97	60		
	10	ADJ. SCR SUB-ASS'Y	6416A16	61		
	11	DUCT GUIDE ASS'Y	6417A44	62		
	12	ROUND CRUCIBLE	6417A57	63		
	13	OVAL TOP SHIELD	8521D13	64		
	14	OVAL SUSCEPTOR COVER DET.	8521D14	65		
	15	SILICON WEB FURNACE CONCEPTUAL DESIGN FOR		66		
	16	CONVERSION TO RESISTANCE HEATING				
	17					
	18					
	19					
	20					
	21					
	22					
	23					
	24					
	25					
	26					
	27					
	28					
	29					

STOCK ORDER (IST S.O. ON WHICH INF. HAS BEEN SENT TO SHOP) IDENTIFYING DATA: IN SPECIFYING THIS D NO. ON A STOCK ORDER THE ENGINEER MUST GIVE: -


NAME OF APPARATUS

SILICON WEB FURNACE MOD-2

ENG'R S. DUNCAN

CHECKED BY AND DATE W. SUMPMAN 9-22-77					
DESIGN SPEC. D 903066	SUB. LETTER A	SUB. LETTER	SUB. LETTER	SUB. LETTER	SUB. LETTER
WESTINGHOUSE FORM 6541 J	PAGE 3 OF 3	SUB. LETTER	SUB. LETTER	SUB. LETTER	SUB. LETTER


FOLDOUT FRAME



ORIGINAL PAGE IS
OF POOR QUALITY


1289J18

FOLDOUT FRAME 2



1289J18

FOLDOUT FRAME



APPROXIMATELY 10% OF THE TOTAL WEIGHT OF THE FRAME IS DUE TO THE WEIGHT OF THE FOLDOUT FRAME. THE WEIGHT OF THE FOLDOUT FRAME IS DETERMINED BY THE WEIGHT OF THE FOLDOUT FRAME. THE WEIGHT OF THE FOLDOUT FRAME IS DETERMINED BY THE WEIGHT OF THE FOLDOUT FRAME.

THE WEIGHT OF THE FOLDOUT FRAME IS DETERMINED BY THE WEIGHT OF THE FOLDOUT FRAME.

REF: GEN ASSY DWS 128°J19.

NO.	DESCRIPTION	QTY	UNIT
1	FLANGE	1	PC
2	FLANGE	1	PC
3	FLANGE	1	PC
4	FLANGE	1	PC
5	FLANGE	1	PC
6	FLANGE	1	PC
7	FLANGE	1	PC
8	FLANGE	1	PC
9	FLANGE	1	PC
10	FLANGE	1	PC
11	FLANGE	1	PC
12	FLANGE	1	PC
13	FLANGE	1	PC
14	FLANGE	1	PC
15	FLANGE	1	PC
16	FLANGE	1	PC
17	FLANGE	1	PC
18	FLANGE	1	PC
19	FLANGE	1	PC
20	FLANGE	1	PC
21	FLANGE	1	PC
22	FLANGE	1	PC
23	FLANGE	1	PC
24	FLANGE	1	PC
25	FLANGE	1	PC
26	FLANGE	1	PC
27	FLANGE	1	PC
28	FLANGE	1	PC
29	FLANGE	1	PC
30	FLANGE	1	PC
31	FLANGE	1	PC
32	FLANGE	1	PC
33	FLANGE	1	PC
34	FLANGE	1	PC
35	FLANGE	1	PC
36	FLANGE	1	PC
37	FLANGE	1	PC
38	FLANGE	1	PC
39	FLANGE	1	PC
40	FLANGE	1	PC
41	FLANGE	1	PC
42	FLANGE	1	PC
43	FLANGE	1	PC
44	FLANGE	1	PC
45	FLANGE	1	PC
46	FLANGE	1	PC
47	FLANGE	1	PC
48	FLANGE	1	PC
49	FLANGE	1	PC
50	FLANGE	1	PC
51	FLANGE	1	PC
52	FLANGE	1	PC
53	FLANGE	1	PC
54	FLANGE	1	PC
55	FLANGE	1	PC
56	FLANGE	1	PC
57	FLANGE	1	PC
58	FLANGE	1	PC
59	FLANGE	1	PC
60	FLANGE	1	PC
61	FLANGE	1	PC
62	FLANGE	1	PC
63	FLANGE	1	PC
64	FLANGE	1	PC
65	FLANGE	1	PC
66	FLANGE	1	PC
67	FLANGE	1	PC
68	FLANGE	1	PC
69	FLANGE	1	PC
70	FLANGE	1	PC
71	FLANGE	1	PC
72	FLANGE	1	PC
73	FLANGE	1	PC
74	FLANGE	1	PC
75	FLANGE	1	PC
76	FLANGE	1	PC
77	FLANGE	1	PC
78	FLANGE	1	PC
79	FLANGE	1	PC
80	FLANGE	1	PC
81	FLANGE	1	PC
82	FLANGE	1	PC
83	FLANGE	1	PC
84	FLANGE	1	PC
85	FLANGE	1	PC
86	FLANGE	1	PC
87	FLANGE	1	PC
88	FLANGE	1	PC
89	FLANGE	1	PC
90	FLANGE	1	PC
91	FLANGE	1	PC
92	FLANGE	1	PC
93	FLANGE	1	PC
94	FLANGE	1	PC
95	FLANGE	1	PC
96	FLANGE	1	PC
97	FLANGE	1	PC
98	FLANGE	1	PC
99	FLANGE	1	PC
100	FLANGE	1	PC


FOLDOUT FRAME

✓


1	PLATE	1289J18
2	PLATE	1289J18
3	PLATE	1289J18
4	PLATE	1289J18
5	PLATE	1289J18
6	PLATE	1289J18
7	PLATE	1289J18
8	PLATE	1289J18
9	PLATE	1289J18
10	PLATE	1289J18
11	PLATE	1289J18
12	PLATE	1289J18
13	PLATE	1289J18
14	PLATE	1289J18
15	PLATE	1289J18
16	PLATE	1289J18
17	PLATE	1289J18
18	PLATE	1289J18
19	PLATE	1289J18
20	PLATE	1289J18
21	PLATE	1289J18
22	PLATE	1289J18
23	PLATE	1289J18
24	PLATE	1289J18
25	PLATE	1289J18
26	PLATE	1289J18
27	PLATE	1289J18
28	PLATE	1289J18
29	PLATE	1289J18
30	PLATE	1289J18
31	PLATE	1289J18
32	PLATE	1289J18
33	PLATE	1289J18
34	PLATE	1289J18
35	PLATE	1289J18
36	PLATE	1289J18
37	PLATE	1289J18
38	PLATE	1289J18
39	PLATE	1289J18
40	PLATE	1289J18
41	PLATE	1289J18
42	PLATE	1289J18
43	PLATE	1289J18
44	PLATE	1289J18
45	PLATE	1289J18
46	PLATE	1289J18
47	PLATE	1289J18
48	PLATE	1289J18
49	PLATE	1289J18
50	PLATE	1289J18
51	PLATE	1289J18
52	PLATE	1289J18
53	PLATE	1289J18
54	PLATE	1289J18
55	PLATE	1289J18
56	PLATE	1289J18
57	PLATE	1289J18
58	PLATE	1289J18
59	PLATE	1289J18
60	PLATE	1289J18
61	PLATE	1289J18
62	PLATE	1289J18
63	PLATE	1289J18
64	PLATE	1289J18
65	PLATE	1289J18
66	PLATE	1289J18
67	PLATE	1289J18
68	PLATE	1289J18
69	PLATE	1289J18
70	PLATE	1289J18
71	PLATE	1289J18
72	PLATE	1289J18
73	PLATE	1289J18
74	PLATE	1289J18
75	PLATE	1289J18
76	PLATE	1289J18
77	PLATE	1289J18
78	PLATE	1289J18
79	PLATE	1289J18
80	PLATE	1289J18
81	PLATE	1289J18
82	PLATE	1289J18
83	PLATE	1289J18
84	PLATE	1289J18
85	PLATE	1289J18
86	PLATE	1289J18
87	PLATE	1289J18
88	PLATE	1289J18
89	PLATE	1289J18
90	PLATE	1289J18
91	PLATE	1289J18
92	PLATE	1289J18
93	PLATE	1289J18
94	PLATE	1289J18
95	PLATE	1289J18
96	PLATE	1289J18
97	PLATE	1289J18
98	PLATE	1289J18
99	PLATE	1289J18
100	PLATE	1289J18

ORIGINAL PAGE IS
OF POOR QUALITY


FOLDOUT FRAME









ORIGINAL PAGE IS
OF POOR QUALITY





STATION - 2304 THE STONY MOUNTAIN
ADDITION: 1000 STONY MOUNTAIN
STATION - 2304 THE STONY MOUNTAIN



ITEM	A	B	C	D
GS	362	335-001	86	162
II	473	4200-001	285	431

[illegible]




8507D3Z

[illegible]




THE SILON WEB FURNACE MODEL-2
SILICON LIFT DET'S. NO. 25

ITEM	DESCRIPTION	QTY	UNIT	PRICE	TOTAL
01	BASE PLATE	1	PC	12.00	12.00
02	ROD SUPPORT	2	PC	12.00	24.00
03	ROD	2	PC	12.00	24.00
04	ROD	2	PC	12.00	24.00
05	ROD SUPPORT	2	PC	12.00	24.00
06	ROD	2	PC	12.00	24.00
07	ROD	2	PC	12.00	24.00
08	ROD	2	PC	12.00	24.00
09	ROD	2	PC	12.00	24.00
10	ROD	2	PC	12.00	24.00
11	ROD	2	PC	12.00	24.00
12	ROD	2	PC	12.00	24.00
13	ROD	2	PC	12.00	24.00
14	ROD	2	PC	12.00	24.00
15	ROD	2	PC	12.00	24.00
16	ROD	2	PC	12.00	24.00
17	ROD	2	PC	12.00	24.00
18	ROD	2	PC	12.00	24.00
19	ROD	2	PC	12.00	24.00
20	ROD	2	PC	12.00	24.00
21	ROD	2	PC	12.00	24.00
22	ROD	2	PC	12.00	24.00
23	ROD	2	PC	12.00	24.00
24	ROD	2	PC	12.00	24.00
25	ROD	2	PC	12.00	24.00
26	ROD	2	PC	12.00	24.00
27	ROD	2	PC	12.00	24.00
28	ROD	2	PC	12.00	24.00
29	ROD	2	PC	12.00	24.00
30	ROD	2	PC	12.00	24.00
31	ROD	2	PC	12.00	24.00
32	ROD	2	PC	12.00	24.00
33	ROD	2	PC	12.00	24.00
34	ROD	2	PC	12.00	24.00
35	ROD	2	PC	12.00	24.00
36	ROD	2	PC	12.00	24.00
37	ROD	2	PC	12.00	24.00
38	ROD	2	PC	12.00	24.00
39	ROD	2	PC	12.00	24.00
40	ROD	2	PC	12.00	24.00
41	ROD	2	PC	12.00	24.00
42	ROD	2	PC	12.00	24.00
43	ROD	2	PC	12.00	24.00
44	ROD	2	PC	12.00	24.00
45	ROD	2	PC	12.00	24.00
46	ROD	2	PC	12.00	24.00
47	ROD	2	PC	12.00	24.00
48	ROD	2	PC	12.00	24.00
49	ROD	2	PC	12.00	24.00
50	ROD	2	PC	12.00	24.00
51	ROD	2	PC	12.00	24.00
52	ROD	2	PC	12.00	24.00
53	ROD	2	PC	12.00	24.00
54	ROD	2	PC	12.00	24.00
55	ROD	2	PC	12.00	24.00
56	ROD	2	PC	12.00	24.00
57	ROD	2	PC	12.00	24.00
58	ROD	2	PC	12.00	24.00
59	ROD	2	PC	12.00	24.00
60	ROD	2	PC	12.00	24.00
61	ROD	2	PC	12.00	24.00
62	ROD	2	PC	12.00	24.00
63	ROD	2	PC	12.00	24.00
64	ROD	2	PC	12.00	24.00
65	ROD	2	PC	12.00	24.00
66	ROD	2	PC	12.00	24.00
67	ROD	2	PC	12.00	24.00
68	ROD	2	PC	12.00	24.00
69	ROD	2	PC	12.00	24.00
70	ROD	2	PC	12.00	24.00
71	ROD	2	PC	12.00	24.00
72	ROD	2	PC	12.00	24.00
73	ROD	2	PC	12.00	24.00
74	ROD	2	PC	12.00	24.00
75	ROD	2	PC	12.00	24.00
76	ROD	2	PC	12.00	24.00
77	ROD	2	PC	12.00	24.00
78	ROD	2	PC	12.00	24.00
79	ROD	2	PC	12.00	24.00
80	ROD	2	PC	12.00	24.00
81	ROD	2	PC	12.00	24.00
82	ROD	2	PC	12.00	24.00
83	ROD	2	PC	12.00	24.00
84	ROD	2	PC	12.00	24.00
85	ROD	2	PC	12.00	24.00
86	ROD	2	PC	12.00	24.00
87	ROD	2	PC	12.00	24.00
88	ROD	2	PC	12.00	24.00
89	ROD	2	PC	12.00	24.00
90	ROD	2	PC	12.00	24.00
91	ROD	2	PC	12.00	24.00
92	ROD	2	PC	12.00	24.00
93	ROD	2	PC	12.00	24.00
94	ROD	2	PC	12.00	24.00
95	ROD	2	PC	12.00	24.00
96	ROD	2	PC	12.00	24.00
97	ROD	2	PC	12.00	24.00
98	ROD	2	PC	12.00	24.00
99	ROD	2	PC	12.00	24.00
100	ROD	2	PC	12.00	24.00

ROD SIZE AS
SPEC. EXCEPT
AS SHOWN





ORIGINAL PAGE IS
OF POOR QUALITY



WESTINGHOUSE ELECTRIC CORPORATION
THE SILON WEB FURNACE MODEL-2
SILICON LIFT DET'S. NO. 25
REV. 2/53
8519 D93

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100


THE 311500N WED FIVEONE THREE-2
CON GIFT DLT-3
END 051923Z WJZ



	66-7-0 79	
	DEPT OF JUSTICE	
2	66-7-0 79	
	DEPT OF JUSTICE	
	RECORDS	
1	790806	

WHE SILENCH WED PURCHASE MODEL-2
SIL. PL. COIL. LIFT 3-8 833F
REV. 1




REV	DATE	DESCRIPTION	BY	CHKD
01	10/10/83	ISSUED FOR FAB	WHE	
02	10/10/83	ISSUED FOR FAB	WHE	
03	10/10/83	ISSUED FOR FAB	WHE	
04	10/10/83	ISSUED FOR FAB	WHE	
05	10/10/83	ISSUED FOR FAB	WHE	
06	10/10/83	ISSUED FOR FAB	WHE	
07	10/10/83	ISSUED FOR FAB	WHE	
08	10/10/83	ISSUED FOR FAB	WHE	
09	10/10/83	ISSUED FOR FAB	WHE	
10	10/10/83	ISSUED FOR FAB	WHE	
11	10/10/83	ISSUED FOR FAB	WHE	
12	10/10/83	ISSUED FOR FAB	WHE	
13	10/10/83	ISSUED FOR FAB	WHE	
14	10/10/83	ISSUED FOR FAB	WHE	
15	10/10/83	ISSUED FOR FAB	WHE	
16	10/10/83	ISSUED FOR FAB	WHE	
17	10/10/83	ISSUED FOR FAB	WHE	
18	10/10/83	ISSUED FOR FAB	WHE	
19	10/10/83	ISSUED FOR FAB	WHE	
20	10/10/83	ISSUED FOR FAB	WHE	
21	10/10/83	ISSUED FOR FAB	WHE	
22	10/10/83	ISSUED FOR FAB	WHE	
23	10/10/83	ISSUED FOR FAB	WHE	
24	10/10/83	ISSUED FOR FAB	WHE	
25	10/10/83	ISSUED FOR FAB	WHE	
26	10/10/83	ISSUED FOR FAB	WHE	
27	10/10/83	ISSUED FOR FAB	WHE	
28	10/10/83	ISSUED FOR FAB	WHE	
29	10/10/83	ISSUED FOR FAB	WHE	
30	10/10/83	ISSUED FOR FAB	WHE	
31	10/10/83	ISSUED FOR FAB	WHE	
32	10/10/83	ISSUED FOR FAB	WHE	
33	10/10/83	ISSUED FOR FAB	WHE	
34	10/10/83	ISSUED FOR FAB	WHE	
35	10/10/83	ISSUED FOR FAB	WHE	
36	10/10/83	ISSUED FOR FAB	WHE	
37	10/10/83	ISSUED FOR FAB	WHE	
38	10/10/83	ISSUED FOR FAB	WHE	
39	10/10/83	ISSUED FOR FAB	WHE	
40	10/10/83	ISSUED FOR FAB	WHE	
41	10/10/83	ISSUED FOR FAB	WHE	
42	10/10/83	ISSUED FOR FAB	WHE	
43	10/10/83	ISSUED FOR FAB	WHE	
44	10/10/83	ISSUED FOR FAB	WHE	
45	10/10/83	ISSUED FOR FAB	WHE	
46	10/10/83	ISSUED FOR FAB	WHE	
47	10/10/83	ISSUED FOR FAB	WHE	
48	10/10/83	ISSUED FOR FAB	WHE	
49	10/10/83	ISSUED FOR FAB	WHE	
50	10/10/83	ISSUED FOR FAB	WHE	
51	10/10/83	ISSUED FOR FAB	WHE	
52	10/10/83	ISSUED FOR FAB	WHE	
53	10/10/83	ISSUED FOR FAB	WHE	
54	10/10/83	ISSUED FOR FAB	WHE	
55	10/10/83	ISSUED FOR FAB	WHE	
56	10/10/83	ISSUED FOR FAB	WHE	
57	10/10/83	ISSUED FOR FAB	WHE	
58	10/10/83	ISSUED FOR FAB	WHE	
59	10/10/83	ISSUED FOR FAB	WHE	
60	10/10/83	ISSUED FOR FAB	WHE	
61	10/10/83	ISSUED FOR FAB	WHE	
62	10/10/83	ISSUED FOR FAB	WHE	
63	10/10/83	ISSUED FOR FAB	WHE	
64	10/10/83	ISSUED FOR FAB	WHE	
65	10/10/83	ISSUED FOR FAB	WHE	
66	10/10/83	ISSUED FOR FAB	WHE	
67	10/10/83	ISSUED FOR FAB	WHE	
68	10/10/83	ISSUED FOR FAB	WHE	
69	10/10/83	ISSUED FOR FAB	WHE	
70	10/10/83	ISSUED FOR FAB	WHE	
71	10/10/83	ISSUED FOR FAB	WHE	
72	10/10/83	ISSUED FOR FAB	WHE	
73	10/10/83	ISSUED FOR FAB	WHE	
74	10/10/83	ISSUED FOR FAB	WHE	
75	10/10/83	ISSUED FOR FAB	WHE	
76	10/10/83	ISSUED FOR FAB	WHE	
77	10/10/83	ISSUED FOR FAB	WHE	
78	10/10/83	ISSUED FOR FAB	WHE	
79	10/10/83	ISSUED FOR FAB	WHE	
80	10/10/83	ISSUED FOR FAB	WHE	
81	10/10/83	ISSUED FOR FAB	WHE	
82	10/10/83	ISSUED FOR FAB	WHE	
83	10/10/83	ISSUED FOR FAB	WHE	
84	10/10/83	ISSUED FOR FAB	WHE	
85	10/10/83	ISSUED FOR FAB	WHE	
86	10/10/83	ISSUED FOR FAB	WHE	
87	10/10/83	ISSUED FOR FAB	WHE	
88	10/10/83	ISSUED FOR FAB	WHE	
89	10/10/83	ISSUED FOR FAB	WHE	
90	10/10/83	ISSUED FOR FAB	WHE	
91	10/10/83	ISSUED FOR FAB	WHE	
92	10/10/83	ISSUED FOR FAB	WHE	
93	10/10/83	ISSUED FOR FAB	WHE	
94	10/10/83	ISSUED FOR FAB	WHE	
95	10/10/83	ISSUED FOR FAB	WHE	
96	10/10/83	ISSUED FOR FAB	WHE	
97	10/10/83	ISSUED FOR FAB	WHE	
98	10/10/83	ISSUED FOR FAB	WHE	
99	10/10/83	ISSUED FOR FAB	WHE	
100	10/10/83	ISSUED FOR FAB	WHE	




WESTERN ENGINE COMPANY
1000 S. 10th St. Portland, OR 97204
TEL: 503/222-1111
FAX: 503/222-1111
E-MAIL: sales@western-engine.com
WWW: www.western-engine.com

9100021
8920017

UNIT		DATE		TIME		LOCATION		REMARKS	
NO.	NAME	DATE	TIME	LOCATION	REMARKS	NO.	NAME	DATE	TIME
1	ARMY	1954	10:00	ARMY	ARMY	2	ARMY	1954	10:00
2	ARMY	1954	10:00	ARMY	ARMY	3	ARMY	1954	10:00
3	ARMY	1954	10:00	ARMY	ARMY	4	ARMY	1954	10:00
4	ARMY	1954	10:00	ARMY	ARMY	5	ARMY	1954	10:00
5	ARMY	1954	10:00	ARMY	ARMY	6	ARMY	1954	10:00
6	ARMY	1954	10:00	ARMY	ARMY	7	ARMY	1954	10:00
7	ARMY	1954	10:00	ARMY	ARMY	8	ARMY	1954	10:00
8	ARMY	1954	10:00	ARMY	ARMY	9	ARMY	1954	10:00
9	ARMY	1954	10:00	ARMY	ARMY	10	ARMY	1954	10:00
10	ARMY	1954	10:00	ARMY	ARMY	11	ARMY	1954	10:00
11	ARMY	1954	10:00	ARMY	ARMY	12	ARMY	1954	10:00
12	ARMY	1954	10:00	ARMY	ARMY	13	ARMY	1954	10:00
13	ARMY	1954	10:00	ARMY	ARMY	14	ARMY	1954	10:00
14	ARMY	1954	10:00	ARMY	ARMY	15	ARMY	1954	10:00
15	ARMY	1954	10:00	ARMY	ARMY	16	ARMY	1954	10:00
16	ARMY	1954	10:00	ARMY	ARMY	17	ARMY	1954	10:00
17	ARMY	1954	10:00	ARMY	ARMY	18	ARMY	1954	10:00
18	ARMY	1954	10:00	ARMY	ARMY	19	ARMY	1954	10:00
19	ARMY	1954	10:00	ARMY	ARMY	20	ARMY	1954	10:00
20	ARMY	1954	10:00	ARMY	ARMY	21	ARMY	1954	10:00
21	ARMY	1954	10:00	ARMY	ARMY	22	ARMY	1954	10:00
22	ARMY	1954	10:00	ARMY	ARMY	23	ARMY	1954	10:00
23	ARMY	1954	10:00	ARMY	ARMY	24	ARMY	1954	10:00
24	ARMY	1954	10:00	ARMY	ARMY	25	ARMY	1954	10:00
25	ARMY	1954	10:00	ARMY	ARMY	26	ARMY	1954	10:00
26	ARMY	1954	10:00	ARMY	ARMY	27	ARMY	1954	10:00
27	ARMY	1954	10:00	ARMY	ARMY	28	ARMY	1954	10:00
28	ARMY	1954	10:00	ARMY	ARMY	29	ARMY	1954	10:00
29	ARMY	1954	10:00	ARMY	ARMY	30	ARMY	1954	10:00
30	ARMY	1954	10:00	ARMY	ARMY	31	ARMY	1954	10:00
31	ARMY	1954	10:00	ARMY	ARMY	32	ARMY	1954	10:00
32	ARMY	1954	10:00	ARMY	ARMY	33	ARMY	1954	10:00
33	ARMY	1954	10:00	ARMY	ARMY	34	ARMY	1954	10:00
34	ARMY	1954	10:00	ARMY	ARMY	35	ARMY	1954	10:00
35	ARMY	1954	10:00	ARMY	ARMY	36	ARMY	1954	10:00
36	ARMY	1954	10:00	ARMY	ARMY	37	ARMY	1954	10:00
37	ARMY	1954	10:00	ARMY	ARMY	38	ARMY	1954	10:00
38	ARMY	1954	10:00	ARMY	ARMY	39	ARMY	1954	10:00
39	ARMY	1954	10:00	ARMY	ARMY	40	ARMY	1954	10:00
40	ARMY	1954	10:00	ARMY	ARMY	41	ARMY	1954	10:00
41	ARMY	1954	10:00	ARMY	ARMY	42	ARMY	1954	10:00






SILICON WEB FURNACE MOD-2									
DETAILS									
ITEM	DESCRIPTION	QTY	UNIT	REVISION	DATE	BY	CHKD	APP'D	REMARKS
01	DOT COVER	1	PC						
02	BLANK COVER	1	PC						
03	FLANGE	1	PC						
04	ELBOW	1	PC						
05	PIN	1	PC						
06	SPACER	1	PC						










ORIGINAL PAGE IS
OF POOR QUALITY

A. FLOWLINE CORP. NEW CASTLE, PA









WESTINGHOUSE ELECTRIC CORPORATION		SILICON WEB FURNACE MOD-2		8520D19	
DATE: 12-1-57		BY: J. S. JONES		CHECKED: J. S. JONES	
APPROVED: J. S. JONES		DATE: 12-1-57		BY: J. S. JONES	
REVISIONS:		REVISIONS:		REVISIONS:	
1. 12-1-57		1. 12-1-57		1. 12-1-57	
2. 12-1-57		2. 12-1-57		2. 12-1-57	
3. 12-1-57		3. 12-1-57		3. 12-1-57	
4. 12-1-57		4. 12-1-57		4. 12-1-57	
5. 12-1-57		5. 12-1-57		5. 12-1-57	
6. 12-1-57		6. 12-1-57		6. 12-1-57	
7. 12-1-57		7. 12-1-57		7. 12-1-57	
8. 12-1-57		8. 12-1-57		8. 12-1-57	
9. 12-1-57		9. 12-1-57		9. 12-1-57	
10. 12-1-57		10. 12-1-57		10. 12-1-57	

[illegible]



SILICON WIRE FURNACE MOD-2
DETAILS
REV. 2

Item	Part Name	Qty.	Unit	Remarks	Material		Quantity		Remarks
					Part No.	Part Name	Qty.	Unit	
11	POST H&G								
12	FLANGE								
13	PIVOT BALL								
14	WASH PL								
15	POST								



WESTINGHOUSE ELECTRIC CORPORATION 700 S. CONNELL AVENUE MILWAUKEE, WISCONSIN 53212	TEL. 414-224-8000	85Z0D39
--	-------------------	---------

11 01-6	2	2
2	2	2
1	1	1




SECRET

26



WU SILICON WED FLANK MOD 2
SUSCEPTOR DET

Part	Part Name	Part Number	Part Description
01	SUSCEPTOR	228 541 214 1001	



100.24 (4.00) DIA. 1.25
DP ANKLES TO SP AS
SHOWN ON A 5.000
SUSCEPTOR DET

ITEM	A	B	C	D	E	F
01	100.24 (4.00) DIA. 1.25 DP ANKLES TO SP AS SHOWN ON A 5.000 SUSCEPTOR DET	100.24 (4.00) DIA. 1.25 DP ANKLES TO SP AS SHOWN ON A 5.000 SUSCEPTOR DET	100.24 (4.00) DIA. 1.25 DP ANKLES TO SP AS SHOWN ON A 5.000 SUSCEPTOR DET	100.24 (4.00) DIA. 1.25 DP ANKLES TO SP AS SHOWN ON A 5.000 SUSCEPTOR DET	100.24 (4.00) DIA. 1.25 DP ANKLES TO SP AS SHOWN ON A 5.000 SUSCEPTOR DET	100.24 (4.00) DIA. 1.25 DP ANKLES TO SP AS SHOWN ON A 5.000 SUSCEPTOR DET



NOTE: DIMENSIONS ENCLOSED BY I ARE IN MILLIMETERS

Westinghouse Electric Corporation

520 D-5









[illegible]

Washington Electric Corporation
720 COVER PLATE
SILICON WET BURNING
MAY 22 1961
A-1
052025

SILICON WELD FORMER, MOD-182

TOP ROLLER SHIM SET

Part No.	Part Name	Material	Quantity	Notes
01	TOP ROLLER	218 OF 200 GA TIECH	1	ABC'S 0427
02	ROLLER PL	218 OF 200 GA TIECH AL	1	100-0101 INT 303
03	ROLLER SHOT	218 OF 200 GA TIECH	1	700-0101 INT 303
04	ROLLER PLATE	218 OF 200 GA TIECH	1	700-0101 INT 303
05	ROLLER SHOT	218 OF 200 GA TIECH	1	700-0101 INT 303
06	ROLLER PLATE	218 OF 200 GA TIECH	1	700-0101 INT 303
07	ROLLER SHOT	218 OF 200 GA TIECH	1	700-0101 INT 303
08	ROLLER PLATE	218 OF 200 GA TIECH	1	700-0101 INT 303
09	ROLLER SHOT	218 OF 200 GA TIECH	1	700-0101 INT 303
10	ROLLER PLATE	218 OF 200 GA TIECH	1	700-0101 INT 303












WESTERN ELECTRIC CORPORATION
SILICON WELD FORMER, MOD-182
TOP ROLLER SHIM SET

WESTERN ELECTRIC CORPORATION
SILICON WELD FORMER, MOD-182
TOP ROLLER SHIM SET

WMA DIVISION WEB FURNACE MCD-2
WEB GUIDE LENS
REV 1

REV	DATE	DESCRIPTION	BY	CHKD	APP'D
01	1/15/00	11.000 OF ONE DIA. 5/16"			
02	1/15/00	17.500 OF ONE DIA. 5/16"			
03	1/15/00	9.500 OF ONE DIA. 5/16"			
04	1/15/00	4.375 OF ONE DIA. 5/16"			

WILLIAMS CO., INC. - POOL PA



WMA DIVISION WEB FURNACE MCD-2
WEB GUIDE LENS
REV 1


8520D69

17 CHANGES

1 903066

REV 123


-A- REID TOOL SUPPLY CO., MUSKEGON, MICH.
-B-PIC, PITTSBURGH, PA.




REV 143

ITEM	PART NAME	QTY	SIZE / INSTRUCTIONS	MATERIAL CODE PART NUMBER OR REF DIMS	GROUP NOTE					
					C	D	E	F	G	H
01	ROD HOUSING	SWS		B504 D76 H01						
02	HOUSING CAP	SWS		B504 D76 H02						
03	ROD	SWS		B504 D76 H03						
04 A	O-RING	BOS	CAT NO. 2-024 C557-70							
05 A	O-RING	BOS	CAT NO. 2-110 C557-70							
06	ROD HOUSING	SWS		B504 D77 H01						
07	HOUSING CAP	SWS		B504 D77 H02						
08	ROD	SWS		B504 D77 H03						


99	A O-RING	BOS CAT NO 2-01B	C557-70
10	A O-RING	BOS CAT NO 2-00B	C557-70
11	KNOB	DWG	257C034H01
12	CHAIN SPROCKET DWG		257C034H02
13	SCR	.080 - 40 X .25 SOC HD CAP SCR.	
14	KNOB	DWG	257C034H03
15	KNOB	DWG	257C034H04
16	SCR	.138 - 32 X .25 LG. STL.	257C034H05



GR. 01



GR.04



GR. 02


[illegible]

TITLE SILICON WEB FURNACE MODEL-1 & MODEL-2

BACK COVER WELDMENT

DWG 257C 251 REV-23

ITEM	QTY	PART NAME	DEF	(SEE) REFERENCE INFORMATION	MATERIAL CODE PART NUMBER CARTED DWG	GROUP
01	COVER	DWG			1490B07H01	1
02	BASE	DWG			8506D61H08	2




<p>Westinghouse Electric Corporation</p> <p>TITLE SILICON WEB FURNACE MODEL-1 & MODEL-2</p> <p>BACK COVER WELDMENT</p> <p>REV-23</p> <p>257C 251</p>	
<p>RESEARCH LABORATORIES CONTROL AND ATTACHMENT IN 1938 USE</p>	
<p>REVISIONS</p> <p>NO. 1</p> <p>DATE 10/1/53</p> <p>BY C. H. HANNA</p> <p>CHKD W. C. S.</p> <p>APPD</p> <p>DATE 10/1/53</p> <p>BY</p>	
<p>IDENTIFYING SYMBOLS</p> <p>SYMBOL</p> <p>DESCRIPTION</p> <p>1. 1/2-13 NPT</p> <p>2. 1/2-13 NPT</p> <p>3. 1/2-13 NPT</p> <p>4. 1/2-13 NPT</p> <p>5. 1/2-13 NPT</p> <p>6. 1/2-13 NPT</p> <p>7. 1/2-13 NPT</p> <p>8. 1/2-13 NPT</p> <p>9. 1/2-13 NPT</p> <p>10. 1/2-13 NPT</p> <p>11. 1/2-13 NPT</p> <p>12. 1/2-13 NPT</p> <p>13. 1/2-13 NPT</p> <p>14. 1/2-13 NPT</p> <p>15. 1/2-13 NPT</p> <p>16. 1/2-13 NPT</p> <p>17. 1/2-13 NPT</p> <p>18. 1/2-13 NPT</p> <p>19. 1/2-13 NPT</p> <p>20. 1/2-13 NPT</p> <p>21. 1/2-13 NPT</p> <p>22. 1/2-13 NPT</p> <p>23. 1/2-13 NPT</p> <p>24. 1/2-13 NPT</p> <p>25. 1/2-13 NPT</p> <p>26. 1/2-13 NPT</p> <p>27. 1/2-13 NPT</p> <p>28. 1/2-13 NPT</p> <p>29. 1/2-13 NPT</p> <p>30. 1/2-13 NPT</p> <p>31. 1/2-13 NPT</p> <p>32. 1/2-13 NPT</p> <p>33. 1/2-13 NPT</p> <p>34. 1/2-13 NPT</p> <p>35. 1/2-13 NPT</p> <p>36. 1/2-13 NPT</p> <p>37. 1/2-13 NPT</p> <p>38. 1/2-13 NPT</p> <p>39. 1/2-13 NPT</p> <p>40. 1/2-13 NPT</p> <p>41. 1/2-13 NPT</p> <p>42. 1/2-13 NPT</p> <p>43. 1/2-13 NPT</p> <p>44. 1/2-13 NPT</p> <p>45. 1/2-13 NPT</p> <p>46. 1/2-13 NPT</p> <p>47. 1/2-13 NPT</p> <p>48. 1/2-13 NPT</p> <p>49. 1/2-13 NPT</p> <p>50. 1/2-13 NPT</p> <p>51. 1/2-13 NPT</p> <p>52. 1/2-13 NPT</p> <p>53. 1/2-13 NPT</p> <p>54. 1/2-13 NPT</p> <p>55. 1/2-13 NPT</p> <p>56. 1/2-13 NPT</p> <p>57. 1/2-13 NPT</p> <p>58. 1/2-13 NPT</p> <p>59. 1/2-13 NPT</p> <p>60. 1/2-13 NPT</p> <p>61. 1/2-13 NPT</p> <p>62. 1/2-13 NPT</p> <p>63. 1/2-13 NPT</p> <p>64. 1/2-13 NPT</p> <p>65. 1/2-13 NPT</p> <p>66. 1/2-13 NPT</p> <p>67. 1/2-13 NPT</p> <p>68. 1/2-13 NPT</p> <p>69. 1/2-13 NPT</p> <p>70. 1/2-13 NPT</p> <p>71. 1/2-13 NPT</p> <p>72. 1/2-13 NPT</p> <p>73. 1/2-13 NPT</p> <p>74. 1/2-13 NPT</p> <p>75. 1/2-13 NPT</p> <p>76. 1/2-13 NPT</p> <p>77. 1/2-13 NPT</p> <p>78. 1/2-13 NPT</p> <p>79. 1/2-13 NPT</p> <p>80. 1/2-13 NPT</p> <p>81. 1/2-13 NPT</p> <p>82. 1/2-13 NPT</p> <p>83. 1/2-13 NPT</p> <p>84. 1/2-13 NPT</p> <p>85. 1/2-13 NPT</p> <p>86. 1/2-13 NPT</p> <p>87. 1/2-13 NPT</p> <p>88. 1/2-13 NPT</p> <p>89. 1/2-13 NPT</p> <p>90. 1/2-13 NPT</p> <p>91. 1/2-13 NPT</p> <p>92. 1/2-13 NPT</p> <p>93. 1/2-13 NPT</p> <p>94. 1/2-13 NPT</p> <p>95. 1/2-13 NPT</p> <p>96. 1/2-13 NPT</p> <p>97. 1/2-13 NPT</p> <p>98. 1/2-13 NPT</p> <p>99. 1/2-13 NPT</p> <p>100. 1/2-13 NPT</p>	

DATE 1927.252
PAGE 7103


DWD	COIL & HOUSING PART NO.		REV	SIZE REFERENCE INFORMATION		NATI. SIZE CODE PART NUMBER OR REF. DWD	GROUP NOTE	GROUP					
	PART NAME	DES		1	2			3	4	5	6		
2576261	COIL	DWG				3506356 KH		1					
	STAND-OFF	DWG				3506358 H12		24					
	FLANGE	DWG				3506361 H03			1				
	A 91" FITTING ELB	BOS				(FITTING TO SOLDER)			1				
	B 1 1/8" FITTING VALVE	BOS				1 1/8" PART # 354-B5126-313			1				
	B SILENTID VALVE	BOS				3.10 OF 1.125 OD x 1.000 ID CV			1				
	TUBING					1012-0112							

WILMINGTON, DE. P.O. BOX 1000 (SALES OFFICE)

2 - MARIAN IND EQ GR., EUCLID, OHIO



ORIGINAL PAGE IS
OF POOR QUALITY



GR-02


[illegible]

SILICON WEB FURNACE-MODEL-2 STORAGE REEL DETAIL WELDMENT


REV 1

DWG 2. 30

ITEM	QTY	PART NAME	REF	SIZE REFERENCE INFORMATION	MATL SIZ. FOR PART REFERENCE INFORMATION	GROUP
01	1	RIM		MAKE FROM AL.	7504-0101	1
02	1	RIB		34.00 X .387K AL.	6061-T651	1
03	1	HUB		4.25 OF 3.00 DIA. AL.	6061-T651	1



375-18TAP X .75 DR
6 HOLES EQ. SP. ON
A 34.500 B.C.





<p>Westinghouse Electric Corporation</p>		<p>2613 C 34</p>	
<p>TITLE: SILICON WEB FURNACE-MODEL-2 STORAGE REEL DETAIL WELDMENT</p>		<p>REV 1</p>	
<p>DATE: 12/29/19</p>		<p>2</p>	
<p>RESEARCH LABORATORIES CHEMICAL DIVISION</p>		<p>RESEARCH LAB</p>	

13C43

.281 DIA 12- HOLES
EQ SP AS SHOWN ON
A 5.250 DIA B.C.

7.5°



ITEM	"A"	"B"
01	6.75	9 SP @ ACB = 3.67

TITLE SILICON WEB FURNACE MOD-2
ROUND WORK COIL DETAIL

DWG 2613C50 REV-1







ITEM	NOTE	PART NAME	QTY	SIZE/REFERENCE INFORMATION	MATERIAL CODE PART NAME PART NUMBER	GROUP NOTE	PROCESS OR LINE NO	GROUP
01		WORK COIL	1	312 OD x .032 WALL CU	RED STAINLESS 7112-0701			

WESTINGHOUSE ELECTRIC CORPORATION TITLE SILICON WEB FURNACE MOD-2 ROUND WORK COIL DETAIL REV-1 2613C50		DRAWN BY CHECKED BY APPROVED BY DATE
DIMENSIONAL CHARACTERISTIC SYMBOLS FINISH TO BE UNLESS OTHERWISE SPECIFIED UNLESS OTHERWISE SPECIFIED TOLERANCES DECIMALS FRACTIONS ANGLES RADIUS DIAMETER HOLE TAP THREAD PITCH LEAD CHAMFER FILLET SPACING CENTER DISTANCE TOTAL PARTIAL CENTER DISTANCE TOTAL PARTIAL		REVISIONS NO. DESCRIPTION 1 2613C50

REV I

[illegible]


A-JOSEPH T. RYERSON & SON, INC., PGH.PA.



1	CHANGE
903066	

THE SILICON WEB FURNACE MOD-2
OVAL WORK COIL DETAIL
REV-1
DWG 2613C64


ITEM	DESCRIPTION	PART NAME	QTY	SIZE / REFERENCE INFORMATION	MATERIAL CODE PART NUMBER ON MAP DWG	CHECKED BY	GROUP
01	WORK COIL	MAY	312 OD x .032 WALL CL		R&D STK-6 7112 - 0701		



ITEM	A' RADIUS	B'	C'
01			



1	9903064	CHANGE										
<table border="1"> <tr> <td colspan="2">TOLERANCES</td> <td colspan="2">UNLESS OTHERWISE SPECIFIED</td> <td colspan="2">F. P. 005 G. P. 004 H. P. 003</td> <td colspan="2">FINISH TO BE UNLESS OTHERWISE SPECIFIED</td> <td colspan="2"> ELASTIC CHARACTERISTIC SYMBOLS A - 100% ELONGATION B - 200% ELONGATION C - 300% ELONGATION D - 400% ELONGATION E - 500% ELONGATION F - 600% ELONGATION G - 700% ELONGATION H - 800% ELONGATION I - 900% ELONGATION J - 1000% ELONGATION K - 1200% ELONGATION L - 1500% ELONGATION M - 2000% ELONGATION N - 2500% ELONGATION O - 3000% ELONGATION P - 3500% ELONGATION Q - 4000% ELONGATION R - 4500% ELONGATION S - 5000% ELONGATION T - 5500% ELONGATION U - 6000% ELONGATION V - 6500% ELONGATION W - 7000% ELONGATION X - 7500% ELONGATION Y - 8000% ELONGATION Z - 8500% ELONGATION AA - 9000% ELONGATION AB - 9500% ELONGATION AC - 10000% ELONGATION AD - 10500% ELONGATION AE - 11000% ELONGATION AF - 11500% ELONGATION AG - 12000% ELONGATION AH - 12500% ELONGATION AI - 13000% ELONGATION AJ - 13500% ELONGATION AK - 14000% ELONGATION AL - 14500% ELONGATION AM - 15000% ELONGATION AN - 15500% ELONGATION AO - 16000% ELONGATION AP - 16500% ELONGATION AQ - 17000% ELONGATION AR - 17500% ELONGATION AS - 18000% ELONGATION AT - 18500% ELONGATION AU - 19000% ELONGATION AV - 19500% ELONGATION AW - 20000% ELONGATION AX - 20500% ELONGATION AY - 21000% ELONGATION AZ - 21500% ELONGATION BA - 22000% ELONGATION BB - 22500% ELONGATION BC - 23000% ELONGATION BD - 23500% ELONGATION BE - 24000% ELONGATION BF - 24500% ELONGATION BG - 25000% ELONGATION BH - 25500% ELONGATION BI - 26000% ELONGATION BJ - 26500% ELONGATION BK - 27000% ELONGATION BL - 27500% ELONGATION BM - 28000% ELONGATION BN - 28500% ELONGATION BO - 29000% ELONGATION BP - 29500% ELONGATION BQ - 30000% ELONGATION BR - 30500% ELONGATION BS - 31000% ELONGATION BT - 31500% ELONGATION BU - 32000% ELONGATION BV - 32500% ELONGATION BW - 33000% ELONGATION BX - 33500% ELONGATION BY - 34000% ELONGATION BZ - 34500% ELONGATION CA - 35000% ELONGATION CB - 35500% ELONGATION CC - 36000% ELONGATION CD - 36500% ELONGATION CE - 37000% ELONGATION CF - 37500% ELONGATION CG - 38000% ELONGATION CH - 38500% ELONGATION CI - 39000% ELONGATION CJ - 39500% ELONGATION CK - 40000% ELONGATION CL - 40500% ELONGATION CM - 41000% ELONGATION CN - 41500% ELONGATION CO - 42000% ELONGATION CP - 42500% ELONGATION CQ - 43000% ELONGATION CR - 43500% ELONGATION CS - 44000% ELONGATION CT - 44500% ELONGATION CU - 45000% ELONGATION CV - 45500% ELONGATION CW - 46000% ELONGATION CX - 46500% ELONGATION CY - 47000% ELONGATION CZ - 47500% ELONGATION DA - 48000% ELONGATION DB - 48500% ELONGATION DC - 49000% ELONGATION DD - 49500% ELONGATION DE - 50000% ELONGATION DF - 50500% ELONGATION DG - 51000% ELONGATION DH - 51500% ELONGATION DI - 52000% ELONGATION DJ - 52500% ELONGATION DK - 53000% ELONGATION DL - 53500% ELONGATION DM - 54000% ELONGATION DN - 54500% ELONGATION DO - 55000% ELONGATION DP - 55500% ELONGATION DQ - 56000% ELONGATION DR - 56500% ELONGATION DS - 57000% ELONGATION DT - 57500% ELONGATION DU - 58000% ELONGATION DV - 58500% ELONGATION DW - 59000% ELONGATION DX - 59500% ELONGATION DY - 60000% ELONGATION DZ - 60500% ELONGATION EA - 61000% ELONGATION EB - 61500% ELONGATION EC - 62000% ELONGATION ED - 62500% ELONGATION EE - 63000% ELONGATION EF - 63500% ELONGATION EG - 64000% ELONGATION EH - 64500% ELONGATION EI - 65000% ELONGATION EJ - 65500% ELONGATION EK - 66000% ELONGATION EL - 66500% ELONGATION EM - 67000% ELONGATION EN - 67500% ELONGATION EO - 68000% ELONGATION EP - 68500% ELONGATION EQ - 69000% ELONGATION ER - 69500% ELONGATION ES - 70000% ELONGATION ET - 70500% ELONGATION EU - 71000% ELONGATION EV - 71500% ELONGATION EW - 72000% ELONGATION EX - 72500% ELONGATION EY - 73000% ELONGATION EZ - 73500% ELONGATION FA - 74000% ELONGATION FB - 74500% ELONGATION FC - 75000% ELONGATION FD - 75500% ELONGATION FE - 76000% ELONGATION FF - 76500% ELONGATION FG - 77000% ELONGATION FH - 77500% ELONGATION FI - 78000% ELONGATION FJ - 78500% ELONGATION FK - 79000% ELONGATION FL - 79500% ELONGATION FM - 80000% ELONGATION FN - 80500% ELONGATION FO - 81000% ELONGATION FP - 81500% ELONGATION FQ - 82000% ELONGATION FR - 82500% ELONGATION FS - 83000% ELONGATION FT - 83500% ELONGATION FU - 84000% ELONGATION FV - 84500% ELONGATION FW - 85000% ELONGATION FX - 85500% ELONGATION FY - 86000% ELONGATION FZ - 86500% ELONGATION GA - 87000% ELONGATION GB - 87500% ELONGATION GC - 88000% ELONGATION GD - 88500% ELONGATION GE - 89000% ELONGATION GF - 89500% ELONGATION GG - 90000% ELONGATION GH - 90500% ELONGATION GI - 91000% ELONGATION GJ - 91500% ELONGATION GK - 92000% ELONGATION GL - 92500% ELONGATION GM - 93000% ELONGATION GN - 93500% ELONGATION GO - 94000% ELONGATION GP - 94500% ELONGATION GQ - 95000% ELONGATION GR - 95500% ELONGATION GS - 96000% ELONGATION GT - 96500% ELONGATION GU - 97000% ELONGATION GV - 97500% ELONGATION GW - 98000% ELONGATION GX - 98500% ELONGATION GY - 99000% ELONGATION GZ - 99500% ELONGATION HA - 100000% ELONGATION HB - 100500% ELONGATION HC - 101000% ELONGATION HD - 101500% ELONGATION HE - 102000% ELONGATION HF - 102500% ELONGATION HG - 103000% ELONGATION HH - 103500% ELONGATION HI - 104000% ELONGATION HJ - 104500% ELONGATION HK - 105000% ELONGATION HL - 105500% ELONGATION HM - 106000% ELONGATION HN - 106500% ELONGATION HO - 107000% ELONGATION HP - 107500% ELONGATION HQ - 108000% ELONGATION HR - 108500% ELONGATION HS - 109000% ELONGATION HT - 109500% ELONGATION HU - 110000% ELONGATION HV - 110500% ELONGATION HW - 111000% ELONGATION HX - 111500% ELONGATION HY - 112000% ELONGATION HZ - 112500% ELONGATION IA - 113000% ELONGATION IB - 113500% ELONGATION IC - 114000% ELONGATION ID - 114500% ELONGATION IE - 115000% ELONGATION IF - 115500% ELONGATION IG - 116000% ELONGATION IH - 116500% ELONGATION II - 117000% ELONGATION IJ - 117500% ELONGATION IK - 118000% ELONGATION IL</td></tr></table>			TOLERANCES		UNLESS OTHERWISE SPECIFIED		F. P. 005 G. P. 004 H. P. 003		FINISH TO BE UNLESS OTHERWISE SPECIFIED		ELASTIC CHARACTERISTIC SYMBOLS A - 100% ELONGATION B - 200% ELONGATION C - 300% ELONGATION D - 400% ELONGATION E - 500% ELONGATION F - 600% ELONGATION G - 700% ELONGATION H - 800% ELONGATION I - 900% ELONGATION J - 1000% ELONGATION K - 1200% ELONGATION L - 1500% ELONGATION M - 2000% ELONGATION N - 2500% ELONGATION O - 3000% ELONGATION P - 3500% ELONGATION Q - 4000% ELONGATION R - 4500% ELONGATION S - 5000% ELONGATION T - 5500% ELONGATION U - 6000% ELONGATION V - 6500% ELONGATION W - 7000% ELONGATION X - 7500% ELONGATION Y - 8000% ELONGATION Z - 8500% ELONGATION AA - 9000% ELONGATION AB - 9500% ELONGATION AC - 10000% ELONGATION AD - 10500% ELONGATION AE - 11000% ELONGATION AF - 11500% ELONGATION AG - 12000% ELONGATION AH - 12500% ELONGATION AI - 13000% ELONGATION AJ - 13500% ELONGATION AK - 14000% ELONGATION AL - 14500% ELONGATION AM - 15000% ELONGATION AN - 15500% ELONGATION AO - 16000% ELONGATION AP - 16500% ELONGATION AQ - 17000% ELONGATION AR - 17500% ELONGATION AS - 18000% ELONGATION AT - 18500% ELONGATION AU - 19000% ELONGATION AV - 19500% ELONGATION AW - 20000% ELONGATION AX - 20500% ELONGATION AY - 21000% ELONGATION AZ - 21500% ELONGATION BA - 22000% ELONGATION BB - 22500% ELONGATION BC - 23000% ELONGATION BD - 23500% ELONGATION BE - 24000% ELONGATION BF - 24500% ELONGATION BG - 25000% ELONGATION BH - 25500% ELONGATION BI - 26000% ELONGATION BJ - 26500% ELONGATION BK - 27000% ELONGATION BL - 27500% ELONGATION BM - 28000% ELONGATION BN - 28500% ELONGATION BO - 29000% ELONGATION BP - 29500% ELONGATION BQ - 30000% ELONGATION BR - 30500% ELONGATION BS - 31000% ELONGATION BT - 31500% ELONGATION BU - 32000% ELONGATION BV - 32500% ELONGATION BW - 33000% ELONGATION BX - 33500% ELONGATION BY - 34000% ELONGATION BZ - 34500% ELONGATION CA - 35000% ELONGATION CB - 35500% ELONGATION CC - 36000% ELONGATION CD - 36500% ELONGATION CE - 37000% ELONGATION CF - 37500% ELONGATION CG - 38000% ELONGATION CH - 38500% ELONGATION CI - 39000% ELONGATION CJ - 39500% ELONGATION CK - 40000% ELONGATION CL - 40500% ELONGATION CM - 41000% ELONGATION CN - 41500% ELONGATION CO - 42000% ELONGATION CP - 42500% ELONGATION CQ - 43000% ELONGATION CR - 43500% ELONGATION CS - 44000% ELONGATION CT - 44500% ELONGATION CU - 45000% ELONGATION CV - 45500% ELONGATION CW - 46000% ELONGATION CX - 46500% ELONGATION CY - 47000% ELONGATION CZ - 47500% ELONGATION DA - 48000% ELONGATION DB - 48500% ELONGATION DC - 49000% ELONGATION DD - 49500% ELONGATION DE - 50000% ELONGATION DF - 50500% ELONGATION DG - 51000% ELONGATION DH - 51500% ELONGATION DI - 52000% ELONGATION DJ - 52500% ELONGATION DK - 53000% ELONGATION DL - 53500% ELONGATION DM - 54000% ELONGATION DN - 54500% ELONGATION DO - 55000% ELONGATION DP - 55500% ELONGATION DQ - 56000% ELONGATION DR - 56500% ELONGATION DS - 57000% ELONGATION DT - 57500% ELONGATION DU - 58000% ELONGATION DV - 58500% ELONGATION DW - 59000% ELONGATION DX - 59500% ELONGATION DY - 60000% ELONGATION DZ - 60500% ELONGATION EA - 61000% ELONGATION EB - 61500% ELONGATION EC - 62000% ELONGATION ED - 62500% ELONGATION EE - 63000% ELONGATION EF - 63500% ELONGATION EG - 64000% ELONGATION EH - 64500% ELONGATION EI - 65000% ELONGATION EJ - 65500% ELONGATION EK - 66000% ELONGATION EL - 66500% ELONGATION EM - 67000% ELONGATION EN - 67500% ELONGATION EO - 68000% ELONGATION EP - 68500% ELONGATION EQ - 69000% ELONGATION ER - 69500% ELONGATION ES - 70000% ELONGATION ET - 70500% ELONGATION EU - 71000% ELONGATION EV - 71500% ELONGATION EW - 72000% ELONGATION EX - 72500% ELONGATION EY - 73000% ELONGATION EZ - 73500% ELONGATION FA - 74000% ELONGATION FB - 74500% ELONGATION FC - 75000% ELONGATION FD - 75500% ELONGATION FE - 76000% ELONGATION FF - 76500% ELONGATION FG - 77000% ELONGATION FH - 77500% ELONGATION FI - 78000% ELONGATION FJ - 78500% ELONGATION FK - 79000% ELONGATION FL - 79500% ELONGATION FM - 80000% ELONGATION FN - 80500% ELONGATION FO - 81000% ELONGATION FP - 81500% ELONGATION FQ - 82000% ELONGATION FR - 82500% ELONGATION FS - 83000% ELONGATION FT - 83500% ELONGATION FU - 84000% ELONGATION FV - 84500% ELONGATION FW - 85000% ELONGATION FX - 85500% ELONGATION FY - 86000% ELONGATION FZ - 86500% ELONGATION GA - 87000% ELONGATION GB - 87500% ELONGATION GC - 88000% ELONGATION GD - 88500% ELONGATION GE - 89000% ELONGATION GF - 89500% ELONGATION GG - 90000% ELONGATION GH - 90500% ELONGATION GI - 91000% ELONGATION GJ - 91500% ELONGATION GK - 92000% ELONGATION GL - 92500% ELONGATION GM - 93000% ELONGATION GN - 93500% ELONGATION GO - 94000% ELONGATION GP - 94500% ELONGATION GQ - 95000% ELONGATION GR - 95500% ELONGATION GS - 96000% ELONGATION GT - 96500% ELONGATION GU - 97000% ELONGATION GV - 97500% ELONGATION GW - 98000% ELONGATION GX - 98500% ELONGATION GY - 99000% ELONGATION GZ - 99500% ELONGATION HA - 100000% ELONGATION HB - 100500% ELONGATION HC - 101000% ELONGATION HD - 101500% ELONGATION HE - 102000% ELONGATION HF - 102500% ELONGATION HG - 103000% ELONGATION HH - 103500% ELONGATION HI - 104000% ELONGATION HJ - 104500% ELONGATION HK - 105000% ELONGATION HL - 105500% ELONGATION HM - 106000% ELONGATION HN - 106500% ELONGATION HO - 107000% ELONGATION HP - 107500% ELONGATION HQ - 108000% ELONGATION HR - 108500% ELONGATION HS - 109000% ELONGATION HT - 109500% ELONGATION HU - 110000% ELONGATION HV - 110500% ELONGATION HW - 111000% ELONGATION HX - 111500% ELONGATION HY - 112000% ELONGATION HZ - 112500% ELONGATION IA - 113000% ELONGATION IB - 113500% ELONGATION IC - 114000% ELONGATION ID - 114500% ELONGATION IE - 115000% ELONGATION IF - 115500% ELONGATION IG - 116000% ELONGATION IH - 116500% ELONGATION II - 117000% ELONGATION IJ - 117500% ELONGATION IK - 118000% ELONGATION IL	
TOLERANCES		UNLESS OTHERWISE SPECIFIED		F. P. 005 G. P. 004 H. P. 003		FINISH TO BE UNLESS OTHERWISE SPECIFIED		ELASTIC CHARACTERISTIC SYMBOLS A - 100% ELONGATION B - 200% ELONGATION C - 300% ELONGATION D - 400% ELONGATION E - 500% ELONGATION F - 600% ELONGATION G - 700% ELONGATION H - 800% ELONGATION I - 900% ELONGATION J - 1000% ELONGATION K - 1200% ELONGATION L - 1500% ELONGATION M - 2000% ELONGATION N - 2500% ELONGATION O - 3000% ELONGATION P - 3500% ELONGATION Q - 4000% ELONGATION R - 4500% ELONGATION S - 5000% ELONGATION T - 5500% ELONGATION U - 6000% ELONGATION V - 6500% ELONGATION W - 7000% ELONGATION X - 7500% ELONGATION Y - 8000% ELONGATION Z - 8500% ELONGATION AA - 9000% ELONGATION AB - 9500% ELONGATION AC - 10000% ELONGATION AD - 10500% ELONGATION AE - 11000% ELONGATION AF - 11500% ELONGATION AG - 12000% ELONGATION AH - 12500% ELONGATION AI - 13000% ELONGATION AJ - 13500% ELONGATION AK - 14000% ELONGATION AL - 14500% ELONGATION AM - 15000% ELONGATION AN - 15500% ELONGATION AO - 16000% ELONGATION AP - 16500% ELONGATION AQ - 17000% ELONGATION AR - 17500% ELONGATION AS - 18000% ELONGATION AT - 18500% ELONGATION AU - 19000% ELONGATION AV - 19500% ELONGATION AW - 20000% ELONGATION AX - 20500% ELONGATION AY - 21000% ELONGATION AZ - 21500% ELONGATION BA - 22000% ELONGATION BB - 22500% ELONGATION BC - 23000% ELONGATION BD - 23500% ELONGATION BE - 24000% ELONGATION BF - 24500% ELONGATION BG - 25000% ELONGATION BH - 25500% ELONGATION BI - 26000% ELONGATION BJ - 26500% ELONGATION BK - 27000% ELONGATION BL - 27500% ELONGATION BM - 28000% ELONGATION BN - 28500% ELONGATION BO - 29000% ELONGATION BP - 29500% ELONGATION BQ - 30000% ELONGATION BR - 30500% ELONGATION BS - 31000% ELONGATION BT - 31500% ELONGATION BU - 32000% ELONGATION BV - 32500% ELONGATION BW - 33000% ELONGATION BX - 33500% ELONGATION BY - 34000% ELONGATION BZ - 34500% ELONGATION CA - 35000% ELONGATION CB - 35500% ELONGATION CC - 36000% ELONGATION CD - 36500% ELONGATION CE - 37000% ELONGATION CF - 37500% ELONGATION CG - 38000% ELONGATION CH - 38500% ELONGATION CI - 39000% ELONGATION CJ - 39500% ELONGATION CK - 40000% ELONGATION CL - 40500% ELONGATION CM - 41000% ELONGATION CN - 41500% ELONGATION CO - 42000% ELONGATION CP - 42500% ELONGATION CQ - 43000% ELONGATION CR - 43500% ELONGATION CS - 44000% ELONGATION CT - 44500% ELONGATION CU - 45000% ELONGATION CV - 45500% ELONGATION CW - 46000% ELONGATION CX - 46500% ELONGATION CY - 47000% ELONGATION CZ - 47500% ELONGATION DA - 48000% ELONGATION DB - 48500% ELONGATION DC - 49000% ELONGATION DD - 49500% ELONGATION DE - 50000% ELONGATION DF - 50500% ELONGATION DG - 51000% ELONGATION DH - 51500% ELONGATION DI - 52000% ELONGATION DJ - 52500% ELONGATION DK - 53000% ELONGATION DL - 53500% ELONGATION DM - 54000% ELONGATION DN - 54500% ELONGATION DO - 55000% ELONGATION DP - 55500% ELONGATION DQ - 56000% ELONGATION DR - 56500% ELONGATION DS - 57000% ELONGATION DT - 57500% ELONGATION DU - 58000% ELONGATION DV - 58500% ELONGATION DW - 59000% ELONGATION DX - 59500% ELONGATION DY - 60000% ELONGATION DZ - 60500% ELONGATION EA - 61000% ELONGATION EB - 61500% ELONGATION EC - 62000% ELONGATION ED - 62500% ELONGATION EE - 63000% ELONGATION EF - 63500% ELONGATION EG - 64000% ELONGATION EH - 64500% ELONGATION EI - 65000% ELONGATION EJ - 65500% ELONGATION EK - 66000% ELONGATION EL - 66500% ELONGATION EM - 67000% ELONGATION EN - 67500% ELONGATION EO - 68000% ELONGATION EP - 68500% ELONGATION EQ - 69000% ELONGATION ER - 69500% ELONGATION ES - 70000% ELONGATION ET - 70500% ELONGATION EU - 71000% ELONGATION EV - 71500% ELONGATION EW - 72000% ELONGATION EX - 72500% ELONGATION EY - 73000% ELONGATION EZ - 73500% ELONGATION FA - 74000% ELONGATION FB - 74500% ELONGATION FC - 75000% ELONGATION FD - 75500% ELONGATION FE - 76000% ELONGATION FF - 76500% ELONGATION FG - 77000% ELONGATION FH - 77500% ELONGATION FI - 78000% ELONGATION FJ - 78500% ELONGATION FK - 79000% ELONGATION FL - 79500% ELONGATION FM - 80000% ELONGATION FN - 80500% ELONGATION FO - 81000% ELONGATION FP - 81500% ELONGATION FQ - 82000% ELONGATION FR - 82500% ELONGATION FS - 83000% ELONGATION FT - 83500% ELONGATION FU - 84000% ELONGATION FV - 84500% ELONGATION FW - 85000% ELONGATION FX - 85500% ELONGATION FY - 86000% ELONGATION FZ - 86500% ELONGATION GA - 87000% ELONGATION GB - 87500% ELONGATION GC - 88000% ELONGATION GD - 88500% ELONGATION GE - 89000% ELONGATION GF - 89500% ELONGATION GG - 90000% ELONGATION GH - 90500% ELONGATION GI - 91000% ELONGATION GJ - 91500% ELONGATION GK - 92000% ELONGATION GL - 92500% ELONGATION GM - 93000% ELONGATION GN - 93500% ELONGATION GO - 94000% ELONGATION GP - 94500% ELONGATION GQ - 95000% ELONGATION GR - 95500% ELONGATION GS - 96000% ELONGATION GT - 96500% ELONGATION GU - 97000% ELONGATION GV - 97500% ELONGATION GW - 98000% ELONGATION GX - 98500% ELONGATION GY - 99000% ELONGATION GZ - 99500% ELONGATION HA - 100000% ELONGATION HB - 100500% ELONGATION HC - 101000% ELONGATION HD - 101500% ELONGATION HE - 102000% ELONGATION HF - 102500% ELONGATION HG - 103000% ELONGATION HH - 103500% ELONGATION HI - 104000% ELONGATION HJ - 104500% ELONGATION HK - 105000% ELONGATION HL - 105500% ELONGATION HM - 106000% ELONGATION HN - 106500% ELONGATION HO - 107000% ELONGATION HP - 107500% ELONGATION HQ - 108000% ELONGATION HR - 108500% ELONGATION HS - 109000% ELONGATION HT - 109500% ELONGATION HU - 110000% ELONGATION HV - 110500% ELONGATION HW - 111000% ELONGATION HX - 111500% ELONGATION HY - 112000% ELONGATION HZ - 112500% ELONGATION IA - 113000% ELONGATION IB - 113500% ELONGATION IC - 114000% ELONGATION ID - 114500% ELONGATION IE - 115000% ELONGATION IF - 115500% ELONGATION IG - 116000% ELONGATION IH - 116500% ELONGATION II - 117000% ELONGATION IJ - 117500% ELONGATION IK - 118000% ELONGATION IL				

[illegible]

NOTE:

1. DIMENSIONS ENCLOSED BY () ARE IN MILLIMETERS.

ITEM	A	B	C	D	E
O1	1674.749 DIA. 2 HOLES EQ. SP AS SHOWN ON A 5.625 (142.875) DIA. BC	125 (3.175) DIA. 196 (4.978) DIA. X .093 (2.362) DPC BORE 4 HOLES EQ. SP AS SHOWN ON A 5.000 (127.000) DIA. BC.	3.000 (76.200)	625 (15.875) DIA. 2 HOLES	300 (7.62) DIA.

[illegible]





SILICON WEB FURNACE
ROUND WORK COIL ASSY
2613C98 REV 1

ITEM	ELON	PART NAME	QTY	SIZE/REFERENCE INFORMATION	MATL SIZE CODE PART NUMBER OR SET QNG	GROUP NOTE PROJECT OR LINE NO	GROUP	QTY
------	------	-----------	-----	----------------------------	---	-------------------------------------	-------	-----

01		WORK COIL	DRG		2613C98H01		1	
02		STAND OFF	DRG		4414A97H01		40	
03	A	FAI POST	DRG		852004CH02		4	
04		KEY HUT		.138-32 STL			40	

A- USED FOR FIXTURING ONLY




DATE	BY	CHKD	APPD	REVISION
12/1/98	B			

DATE	BY	CHKD	APPD	REVISION
12/1/98	B			

DATE	BY	CHKD	APPD	REVISION
12/1/98	B			

DATE	BY	CHKD	APPD	REVISION
12/1/98	B			

Westinghouse Electric Corporation	2613C98
SILICON WEB FURNACE MODEL 2	
ROUND WORK COIL ASSY	
DATE: 12/1/98	REV: 1
BY: B	APPD: B
CHKD: B	APPD: B
DATE: 12/1/98	REV: 1



G	1156 (3222) DA 4-HOLES EQ SP ON A 5-688 (144.475) DIA 80
---	---

L DIMENSIONS ENCLOSED BY () ARE IN

SILICON WEB FURNACE MOD-2

UNITED STATES DEPARTMENT OF AGRICULTURE	WASHINGTON, D.C.
OFFICE OF THE SECRETARY	
ADVISORY BOARD ON THE STATUS OF WOMEN	
MEMBER	
NAME	
ADDRESS	
CITY	
STATE	
ZIP CODE	
DATE RECEIVED	
OTHERWISE SPECIFIED	


Westinghouse Electric Corporation

SILICON WEB FURNACE MOD-2

TOP SHIELD DET

130 073116 101

2614C18



56

1 2 3 4 5

1 2 3 4 5

1 2 3 4 5

1 2 3 4 5

1 2 3 4 5

1 2 3 4 5

1 2 3 4 5

1 2 3 4 5

1 2 3 4 5

1 2 3 4 5

1 2 3 4 5

1 2 3 4 5

1 2 3 4 5

1 2 3 4 5

1 2 3 4 5

1 2 3 4 5

1 2 3 4 5

1 2 3 4 5

1 2 3 4 5

1 2 3 4 5

1 2 3 4 5

1 2 3 4 5

1 2 3 4 5

1 2 3 4 5

1 2 3 4 5

1 2 3 4 5

1 2 3 4 5

1 2 3 4 5

1 2 3 4 5

1 2 3 4 5

1 2 3 4 5

1 2 3 4 5

1 2 3 4 5

1 2 3 4 5

1 2 3 4 5

1 2 3 4 5

1 2 3 4 5

1 2 3 4 5

1 2 3 4 5

1 2 3 4 5

1 2 3 4 5


1 2 3 4 5

1 2 3 4 5

TITLE SILICON WEB FURNACE MOD-2
SENSOR HOLDER
 DWG 1691B12 REV 1

ITEM	NO.	PART NAME	DEF	(SIZE) REFERENCE INFORMATION	MATL SIZE CODE PART NUMBER OR REF DWG	GROUP NOTE PROCESS OR LINE NO	GROUP				
01		CAP	DWG		8520D78H04		C1	C2	C3	C4	C5
02		SENSOR HLDR	DWG		8520D78H05						
03		A CONN.	BDS	SHAGELDK O-SEAL STRTD	B-200-1-OR						

A- PGR VALVE & FITTING CO, PLH, PA.



1 903066 CHANGE

WESTINGHOUSE ELECTRIC CORPORATION

TITLE SILICON WEB FURNACE MOD-2
SENSOR HOLDER ASSY
 DIMENSIONS IN INCHES-SCALE 1:1 REV 1

DATE C. H. H. 10-24 APP'D
 CHECK W.C.S. APP'D
 SUPV 1691B12 APP'D

RESEARCH LABORATORIES CHURCHILL WORKS PITTSBURGH PA 15136 U.S.A.



1 2 3 4 5

1289U18

REVISIONS

SYMBOL	DESCRIPTION	DATE
1	PLANNED	
2	DESIGNED	
3	ENGINEERED	
4	TESTED	
5	APPROVED	
6	RELEASED	
7	REWORKED	
8	REDESIGNED	
9	RETESTED	
10	REAPPROVED	
11	REDESIGNED	
12	RETESTED	
13	REAPPROVED	
14	REDESIGNED	
15	RETESTED	
16	REAPPROVED	
17	REDESIGNED	
18	RETESTED	
19	REAPPROVED	
20	REDESIGNED	
21	RETESTED	
22	REAPPROVED	
23	REDESIGNED	
24	RETESTED	
25	REAPPROVED	
26	REDESIGNED	
27	RETESTED	
28	REAPPROVED	
29	REDESIGNED	
30	RETESTED	
31	REAPPROVED	
32	REDESIGNED	
33	RETESTED	
34	REAPPROVED	
35	REDESIGNED	
36	RETESTED	
37	REAPPROVED	
38	REDESIGNED	
39	RETESTED	
40	REAPPROVED	
41	REDESIGNED	
42	RETESTED	
43	REAPPROVED	
44	REDESIGNED	
45	RETESTED	
46	REAPPROVED	
47	REDESIGNED	
48	RETESTED	
49	REAPPROVED	
50	REDESIGNED	
51	RETESTED	
52	REAPPROVED	
53	REDESIGNED	
54	RETESTED	
55	REAPPROVED	
56	REDESIGNED	
57	RETESTED	
58	REAPPROVED	
59	REDESIGNED	
60	RETESTED	
61	REAPPROVED	
62	REDESIGNED	
63	RETESTED	
64	REAPPROVED	
65	REDESIGNED	
66	RETESTED	
67	REAPPROVED	
68	REDESIGNED	
69	RETESTED	
70	REAPPROVED	
71	REDESIGNED	
72	RETESTED	
73	REAPPROVED	
74	REDESIGNED	
75	RETESTED	
76	REAPPROVED	
77	REDESIGNED	
78	RETESTED	
79	REAPPROVED	
80	REDESIGNED	
81	RETESTED	
82	REAPPROVED	
83	REDESIGNED	
84	RETESTED	
85	REAPPROVED	
86	REDESIGNED	
87	RETESTED	
88	REAPPROVED	
89	REDESIGNED	
90	RETESTED	
91	REAPPROVED	
92	REDESIGNED	
93	RETESTED	
94	REAPPROVED	
95	REDESIGNED	
96	RETESTED	
97	REAPPROVED	
98	REDESIGNED	
99	RETESTED	
100	REAPPROVED	

ITEM NO	A	B	C	D
01	2493	5.933	0.56	6.833



1	903066	CHANGE	IT																																																																																																																
<table border="1"> <tr> <td colspan="2">TOLERANCES UNLESS OTHERWISE SPECIFIED</td> <td colspan="2"> 3 P. DEC 3 P. DEC 3 P. DEC .001 .003 .005 .001 .001 .001 </td> </tr> <tr> <td colspan="4">FINISH TO BE UNLESS OTHERWISE SPECIFIED</td> </tr> <tr> <td colspan="4">GEOMETRIC CHARACTERISTICS</td> </tr> <tr> <td>1</td> <td>2</td> <td>3</td> <td>4</td> </tr> <tr> <td>5</td> <td>6</td> <td>7</td> <td>8</td> </tr> <tr> <td>9</td> <td>10</td> <td>11</td> <td>12</td> </tr> <tr> <td>13</td> <td>14</td> <td>15</td> <td>16</td> </tr> <tr> <td>17</td> <td>18</td> <td>19</td> <td>20</td> </tr> <tr> <td>21</td> <td>22</td> <td>23</td> <td>24</td> </tr> <tr> <td>25</td> <td>26</td> <td>27</td> <td>28</td> </tr> <tr> <td>29</td> <td>30</td> <td>31</td> <td>32</td> </tr> <tr> <td>33</td> <td>34</td> <td>35</td> <td>36</td> </tr> <tr> <td>37</td> <td>38</td> <td>39</td> <td>40</td> </tr> <tr> <td>41</td> <td>42</td> <td>43</td> <td>44</td> </tr> <tr> <td>45</td> <td>46</td> <td>47</td> <td>48</td> </tr> <tr> <td>49</td> <td>50</td> <td>51</td> <td>52</td> </tr> <tr> <td>53</td> <td>54</td> <td>55</td> <td>56</td> </tr> <tr> <td>57</td> <td>58</td> <td>59</td> <td>60</td> </tr> <tr> <td>61</td> <td>62</td> <td>63</td> <td>64</td> </tr> <tr> <td>65</td> <td>66</td> <td>67</td> <td>68</td> </tr> <tr> <td>69</td> <td>70</td> <td>71</td> <td>72</td> </tr> <tr> <td>73</td> <td>74</td> <td>75</td> <td>76</td> </tr> <tr> <td>77</td> <td>78</td> <td>79</td> <td>80</td> </tr> <tr> <td>81</td> <td>82</td> <td>83</td> <td>84</td> </tr> <tr> <td>85</td> <td>86</td> <td>87</td> <td>88</td> </tr> <tr> <td>89</td> <td>90</td> <td>91</td> <td>92</td> </tr> <tr> <td>93</td> <td>94</td> <td>95</td> <td>96</td> </tr> <tr> <td>97</td> <td>98</td> <td>99</td> <td>100</td> </tr> </table>				TOLERANCES UNLESS OTHERWISE SPECIFIED		3 P. DEC 3 P. DEC 3 P. DEC .001 .003 .005 .001 .001 .001		FINISH TO BE UNLESS OTHERWISE SPECIFIED				GEOMETRIC CHARACTERISTICS				1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
TOLERANCES UNLESS OTHERWISE SPECIFIED		3 P. DEC 3 P. DEC 3 P. DEC .001 .003 .005 .001 .001 .001																																																																																																																	
FINISH TO BE UNLESS OTHERWISE SPECIFIED																																																																																																																			
GEOMETRIC CHARACTERISTICS																																																																																																																			
1	2	3	4																																																																																																																
5	6	7	8																																																																																																																
9	10	11	12																																																																																																																
13	14	15	16																																																																																																																
17	18	19	20																																																																																																																
21	22	23	24																																																																																																																
25	26	27	28																																																																																																																
29	30	31	32																																																																																																																
33	34	35	36																																																																																																																
37	38	39	40																																																																																																																
41	42	43	44																																																																																																																
45	46	47	48																																																																																																																
49	50	51	52																																																																																																																
53	54	55	56																																																																																																																
57	58	59	60																																																																																																																
61	62	63	64																																																																																																																
65	66	67	68																																																																																																																
69	70	71	72																																																																																																																
73	74	75	76																																																																																																																
77	78	79	80																																																																																																																
81	82	83	84																																																																																																																
85	86	87	88																																																																																																																
89	90	91	92																																																																																																																
93	94	95	96																																																																																																																
97	98	99	100																																																																																																																
<div style="display: flex; justify-content: space-between;"> <div> <p>Westinghouse Electric Corporation</p> <p>TITLE SILICON WEB FURNACE MOD-2</p> <p>OVAL CRUCIBLE DET</p> <p>CHANGES IN INCREMENTAL REV-1</p> <p>DATE GRACED 5-22-77</p> <p>CHD W. C. 77</p> <p>SPD</p> </div> <div> <p>1691B62</p> </div> </div>																																																																																																																			
<div style="display: flex; justify-content: space-between;"> <div> <p>128918</p> </div> <div> <p>RECD</p> </div> </div>																																																																																																																			
<div style="display: flex; justify-content: space-between;"> <div> <p>Westinghouse Electric Corporation</p> <p>TITLE SILICON WEB FURNACE MOD-2</p> <p>OVAL CRUCIBLE DET</p> <p>CHANGES IN INCREMENTAL REV-1</p> <p>DATE GRACED 5-22-77</p> <p>CHD W. C. 77</p> <p>SPD</p> </div> <div> <p>1691B62</p> </div> </div>																																																																																																																			
<div style="display: flex; justify-content: space-between;"> <div> <p>128918</p> </div> <div> <p>RECD</p> </div> </div>																																																																																																																			
<div style="display: flex; justify-content: space-between;"> <div> <p>Westinghouse Electric Corporation</p> <p>TITLE SILICON WEB FURNACE MOD-2</p> <p>OVAL CRUCIBLE DET</p> <p>CHANGES IN INCREMENTAL REV-1</p> <p>DATE GRACED 5-22-77</p> <p>CHD W. C. 77</p> <p>SPD</p> </div> <div> <p>1691B62</p> </div> </div>																																																																																																																			
<div style="display: flex; justify-content: space-between;"> <div> <p>128918</p> </div> <div> <p>RECD</p> </div> </div>																																																																																																																			
<div style="display: flex; justify-content: space-between;"> <div> <p>Westinghouse Electric Corporation</p> <p>TITLE SILICON WEB FURNACE MOD-2</p> <p>OVAL CRUCIBLE DET</p> <p>CHANGES IN INCREMENTAL REV-1</p> <p>DATE GRACED 5-22-77</p> <p>CHD W. C. 77</p> <p>SPD</p> </div> <div> <p>1691B62</p> </div> </div>																																																																																																																			
<div style="display: flex; justify-content: space-between;"> <div> <p>128918</p> </div> <div> <p>RECD</p> </div> </div>																																																																																																																			
<div style="display: flex; justify-content: space-between;"> <div> <p>Westinghouse Electric Corporation</p> <p>TITLE SILICON WEB FURNACE MOD-2</p> <p>OVAL CRUCIBLE DET</p> <p>CHANGES IN INCREMENTAL REV-1</p> <p>DATE GRACED 5-22-77</p> <p>CHD W. C. 77</p> <p>SPD</p> </div> <div> <p>1691B62</p> </div> </div>																																																																																																																			
<div style="display: flex; justify-content: space-between;"> <div> <p>128918</p> </div> <div> <p>RECD</p> </div> </div>																																																																																																																			
<div style="display: flex; justify-content: space-between;"> <div> <p>Westinghouse Electric Corporation</p> <p>TITLE SILICON WEB FURNACE MOD-2</p> <p>OVAL CRUCIBLE DET</p> <p>CHANGES IN INCREMENTAL REV-1</p> <p>DATE GRACED 5-22-77</p> <p>CHD W. C. 77</p> <p>SPD</p> </div> <div> <p>1691B62</p> </div> </div>																																																																																																																			
<div style="display: flex; justify-content: space-between;"> <div> <p>128918</p> </div> <div> <p>RECD</p> </div> </div>																																																																																																																			
<div style="display: flex; justify-content: space-between;"> <div> <p>Westinghouse Electric Corporation</p> <p>TITLE SILICON WEB FURNACE MOD-2</p> <p>OVAL CRUCIBLE DET</p> <p>CHANGES IN INCREMENTAL REV-1</p> <p>DATE GRACED 5-22-77</p> <p>CHD W. C. 77</p> <p>SPD</p> </div> <div> <p>1691B62</p> </div> </div>																																																																																																																			
<div style="display: flex; justify-content: space-between;"> <div> <p>128918</p> </div> <div> <p>RECD</p> </div> </div>																																																																																																																			
<div style="display: flex; justify-content: space-between;"> <div> <p>Westinghouse Electric Corporation</p> <p>TITLE SILICON WEB FURNACE MOD-2</p> <p>OVAL CRUCIBLE DET</p> <p>CHANGES IN INCREMENTAL REV-1</p> <p>DATE GRACED 5-22-77</p> <p>CHD W. C. 77</p> <p>SPD</p> </div> <div> <p>1691B62</p> </div> </div>																																																																																																																			
<div style="display: flex; justify-content: space-between;"> <div> <p>128918</p> </div> <div> <p>RECD</p> </div> </div>																																																																																																																			
<div style="display: flex; justify-content: space-between;"> <div> <p>Westinghouse Electric Corporation</p> <p>TITLE SILICON WEB FURNACE MOD-2</p> <p>OVAL CRUCIBLE DET</p> <p>CHANGES IN INCREMENTAL REV-1</p> <p>DATE GRACED 5-22-77</p> <p>CHD W. C. 77</p> <p>SPD</p> </div> <div> <p>1691B62</p> </div> </div>																																																																																																																			
<div style="display: flex; justify-content: space-between;"> <div> <p>128918</p> </div> <div> <p>RECD</p> </div> </div>																																																																																																																			
<div style="display: flex; justify-content: space-between;"> <div> <p>Westinghouse Electric Corporation</p> <p>TITLE SILICON WEB FURNACE MOD-2</p> <p>OVAL CRUCIBLE DET</p> <p>CHANGES IN INCREMENTAL REV-1</p> <p>DATE GRACED 5-22-77</p> <p>CHD W. C. 77</p> <p>SPD</p> </div> <div> <p>1691B62</p> </div> </div>																																																																																																																			
<div style="display: flex; justify-content: space-between;"> <div> <p>128918</p> </div> <div> <p>RECD</p> </div> </div>																																																																																																																			
<div style="display: flex; justify-content: space-between;"> <div> <p>Westinghouse Electric Corporation</p> <p>TITLE SILICON WEB FURNACE MOD-2</p> <p>OVAL CRUCIBLE DET</p> <p>CHANGES IN INCREMENTAL REV-1</p> <p>DATE GRACED 5-22-77</p> <p>CHD W. C. 77</p> <p>SPD</p> </div> <div> <p>1691B62</p> </div> </div>																																																																																																																			
<div style="display: flex; justify-content: space-between;"> <div> <p>128918</p> </div> <div> <p>RECD</p> </div> </div>																																																																																																																			
<div style="display: flex; justify-content: space-between;"> <div> <p>Westinghouse Electric Corporation</p> <p>TITLE SILICON WEB FURNACE MOD-2</p> <p>OVAL CRUCIBLE DET</p> <p>CHANGES IN INCREMENTAL REV-1</p> <p>DATE GRACED 5-22-77</p> <p>CHD W. C. 77</p> <p>SPD</p> </div> <div> <p>1691B62</p> </div> </div>																																																																																																																			
<div style="display: flex; justify-content: space-between;"> <div> <p>128918</p> </div> <div> <p>RECD</p> </div> </div>																																																																																																																			
<div style="display: flex; justify-content: space-between;"> <div> <p>Westinghouse Electric Corporation</p> <p>TITLE SILICON WEB FURNACE MOD-2</p> <p>OVAL CRUCIBLE DET</p> <p>CHANGES IN INCREMENTAL REV-1</p> <p>DATE GRACED 5-22-77</p> <p>CHD W. C. 77</p> <p>SPD</p> </div> <div> <p>1691B62</p> </div> </div>																																																																																																																			
<div style="display: flex; justify-content: space-between;"> <div> <p>128918</p> </div> <div> <p>RECD</p> </div> </div>																																																																																																																			

Westinghouse Electric Corporation


RESEARCH LABORATORIES CHURCHILL BORO. PITTSBURGH. PA. 15233. U.S.A.

TITLE SILICON WEB FURNACE MOD-2

WORK COIL STAND-OFF DET

903066

REF DWG 2613095	TOLERANCES			FINISH TO BE <input checked="" type="checkbox"/> UNLESS OTHERWISE SPECIFIED	DIMENSIONS IN INCHES—SCALE	SUB. DATE 1 APRD	GROUP	GROUP
	2 PL DEC ± .02	3 PL DEC ± .005	ANGLES ± 0.5°					
ITEM	PART NAME	DEF	(SIZE) REFERENCE INFORMATION		MATL SIZE CODE PART NUMBER OR REF DWG	GROUP NOTE	PROCESS OR LINE NO.	GROUP
01	STAND OFF		2.75 OF .312 DIA BR		R&D STK NO 6105-0501	ASTM B-16		01 02 03 04 05




IT.NO.	A
01	1.40

6414 A97

Westinghouse Electric Corporation
 TITLE SILICON WEB FURNACE MOD-1&2
 ADJ. SCR. SUB ASSY.

RESEARCH LABORATORIES CHURCHILL BORO. PITTSBURGH, PA. 15233, U.S.A.

REF DWG	TOLERANCES			FINISH TO BE <input checked="" type="checkbox"/> UNLESS OTHERWISE SPECIFIED	DIMENSIONS IN INCHES—SCALE 2=1	GROUP NOTE	PROCESS OR LINE NO.	GROUP
	UNLESS OTHERWISE SPECIFIED	± PL. DEC.	3 PL. DEC.					
	±.02	±.005		±0.5°				
ITEM	NOTE	PART NAME	DEF	(SIZE) REFERENCE INFORMATION	MATL SIZE CODE PART NUMBER OR REF DWG R&D STK. NO.			
01		ALL THD.		1.88 OF .138-32 STL.	6506-0901		01	02
02		ACORN NUT		.138-32 STL.			01	04



RESEARCH LABORATORIES CHURCHILL BORO, PITTSBURGH, PA. 15133, U.S.A

RESEARCH LABORATORIES CHURCHILL WOOD, PITTSBURGH, PA. 15133, U.S.A.


TITLE SILICON WEB FURNACE MOD-2

DUCT GUIDE

REF 1289J19 DWG	TOLERANCES			FINISH TO BE ✓ UNLESS OTHERWISE SPECIFIED	DIMENSIONS IN INCHES—SCALE 1/16"
	UNLESS OTHERWISE SPECIFIED				
	2 PL. DEC.	3 PL. DEC.	ANGLES		
	±.02	±.003	± 0.5°		

ITEM	NOTE	PART NAME	DEF	(SIZE) REFERENCE INFORMATION	MATL SIZE CODE PART NUMBER OR REF DWG	GROUP PROCESS LINE
01		GUIDE HSG	DWG		8520D78H01	
02		GUIDE	DWG		8520D78H02	
03		GUIDE	DWG		8520D78H03	
04		GUIDE HSG	DWG		8520D78H06	

GROUP NOTE	GROUP					
	01	02	03	04	05	
PROCESS OR LINE NO.	1					
	2					
		2				
		1				



GR 01 & 02

6417A 44


Westinghouse Electric Corporation

RESEARCH LABORATORIES CHURCHILL BORO, PITTSBURGH, PA. 15233, U.S.A.

TITLE SILICON WEB FURNACE

CRUCIBLE

REF DWG	TOLERANCES			FINISH TO BE <input checked="" type="checkbox"/> UNLESS OTHERWISE SPECIFIED	DIMENSIONS IN INCHES—SCALE	SUB. DTM W. C.S. 72	APRD.	1	GROUP	GROUP		
	UNLESS OTHERWISE SPECIFIED	2 PL. DEC.	3 PL. DEC.								ANGLES	
	±.02	±.005		± 0.3°								
ITEM	NOTE	PART NAME	DEF	(SIZE) REFERENCE INFORMATION	MATL SIZE CODE PART NUMBER OR REF DWG	GROUP NOTE	PROCESS OR LINE NO.	01	02	03	04	05
01		CRUCIBLE	MKF	AMERSIL CFQ TOB								




ORIGINAL PAGE IS
OF POOR QUALITY

[illegible]

NOTES:-
1. DIMENSIONS ENCLOSED BY () ARE IN MILLIMETERS
2. POLISH & REMOVE ALL SHARP EDGES

ITEM	A	B	C	D	E	F	G	H	I	J	K	L
01	8.97 (2284)	3.34 (8443)	1.50 (3713)	5.04 (1274)	5.37 (1330)	36 (107) 34 (107.4)	140.4 140.4	154.5 154.5				

[illegible]



NOTES:
1 DIMENSIONS ENCLOSED BY () ARE IN MILLIMETERS
& DASHES & REMOVE ALL SHARP EDGES

RETURN TO: UNITED STATES DEPARTMENT OF JUSTICE FEDERAL BUREAU OF INVESTIGATION 400 ... WASHINGTON, D.C. 20535	
DATE: 10/10/74 TIME: 10:00 AM BY: SA [Name]	TO: SA [Name] FROM: SA [Name] SUBJECT: [Subject] RE: [Subject]
[Main body of the report containing text and possibly other forms]	
DISTRIBUTION: [List of recipients]	
APPROVED: [Signature] SPECIAL AGENT IN CHARGE	

