

DO NOT DESTROY
RETURN TO LIBRARY

**DOE/NASA MOD-0A
WIND TURBINE
PERFORMANCE**

T. R. Richards and H. E. Neustadter
National Aeronautics and Space Administration
Lewis Research Center

Work performed for
U.S. DEPARTMENT OF ENERGY
Office of Energy Technology
Division of Solar Energy

TECHNICAL PAPER to be presented at
Thirteenth Intersociety Energy
Conversion Engineering Conference
San Diego, California, August 20-25, 1978

13 JUL 1978
MCDONNELL DOUGLAS
RESEARCH & ENGINEERING LIBRARY
ST. LOUIS

M 78-15146

NOTICE

This report was prepared to document work sponsored by the United States Government. Neither the United States nor its agent, the United States Department of Energy, nor any Federal employees, nor any of their contractors, subcontractors or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

DOE/NASA/1004-78/13
NASA TM-78916

DOE/NASA MOD-0A
WIND TURBINE
PERFORMANCE

T. R. Richards and H. E. Neustadter
National Aeronautics and Space Administration
Lewis Research Center
Cleveland, Ohio 44135

Prepared for
U. S. Department of Energy
Office of Energy Technology
Division of Solar Energy
Washington, D. C. 20545
Under Interagency Agreement E(49-26)-1004

Thirteenth Intersociety Energy
Conversion Engineering Conference
San Diego, California, August 20-25, 1978

DOE/NASA MOD-0A WIND TURBINE PERFORMANCE

T. R. Richards and H. E. Neustadter

National Aeronautics and Space Administration
Lewis Research Center
Cleveland, Ohio 44135

ABSTRACT

As part of the national wind energy program under the direction of the Department of Energy, the NASA-Lewis Research Center has designed and built, and is now operating, a large wind turbine at Clayton, New Mexico. Designated the Mod-0A-1, this is the first of three identical 200 kW wind turbines to be operated on electric utility networks. This machine was installed at Clayton, New Mexico, in November 1977. This paper presents a comparison between its predicted and measured power versus wind speed performance.

BACKGROUND - As part of the Federal wind energy program under the direction of the Department of Energy, the NASA-Lewis Research Center (LeRC) is responsible for developing large, horizontal-axis wind turbines. Current projects at LeRC include turbine designs with rotor diameters ranging from 125 to 300 feet and generating capacities from 100 to 2500 kW.

The first of these designs to be built, the Mod-0 wind turbine (1),* consists of a two-bladed, 125-foot diameter rotor which drives a 100-kW capacity synchronous alternator through a step-up gearbox. This machine was built to provide early engineering data on the operation of large wind turbines and to serve as a testbed for various subsystems and components which held promise for reducing costs and increasing the reliability of later wind turbine designs.

The second of these designs, the Mod-0A wind turbine system, was derived directly from the Mod-0 design, with three minor modifications: stronger and heavier blades, an all-pipe truss tower as opposed to the Mod-0's pipe-and-channel tower design, and a larger capacity alternator and drivetrain. Although nearly identical in design to Mod-0, the Mod-0A machines are being built and tested for a different purpose; obtaining early operation and performance data and gaining experience while operating in typical utility environments (2). As such, the Mod-0A design was not developed under the stringent cost goals and constraints to which current designs are being subjected (3,4).

Of primary importance in the design of any wind turbine is the accurate prediction of energy output as a function of site wind characteristics. This prediction involves the combining of site wind duration curves and the power-versus-wind speed performance of the wind turbine. The wind

turbine's performance is determined by the product of two efficiencies: the aerodynamic efficiency of the rotor in converting from wind power to shaft power and the mechanical/electrical efficiency of the drivetrain/alternator system in converting shaft power to electrical power. This paper presents a comparison of predicted and measured performance for the Mod-0A wind turbine.

MOD-0A DESCRIPTION

The Mod-0A wind turbine has a 125-foot diameter, two-bladed rotor which drives a 200-kW capacity synchronous generator through a step-up gearbox. The rotor is positioned downwind of a 100-foot steel-truss tower, as pictured in Fig. 1. The rotor is designed to operate at a constant speed of 40 rpm and it drives a 60 Hz three-phase alternator at 1800 rpm. Constant rotor speed is maintained by controlling the blade pitch angle with a feedback control system. The rotor, alternator, transmission, and associated equipment are mounted on a bedplate, which is yawed to align the rotor with the wind. Power, instrumentation, and control connections to the ground are made through slip rings.

The Mod-0A wind turbine in Clayton, New Mexico, achieved first rotation in November 1977. Data reported here was recorded during the initial checkout phase of the Clayton installation, and corresponds to the normal operating mode of the Mod-0A wind turbine: synchronized to the utility network and utilizing a power feedback control loop for blade pitch control. The control system consists of integral control on power and feed-forward on wind speed. This control scheme is described in detail in Ref. 1.

COMPARISON OF PREDICTED AND ACTUAL PERFORMANCE

PREDICTIONS - The performance predictions for the Mod-0A wind turbine were calculated using an aerodynamic performance code PROP (5). This analysis is based on the blade element/momentum theory of rotor performance. Details of the Mod-0A blade geometry are given in Ref. 6, and the airfoil data used were NASA roughness. NASA roughness is defined as halfway between the smooth and standard roughness data found in Ref. 7.

DATA SYSTEM AND SITE LAYOUT - The data system used for recording Mod-0A performance data consists of approximately 85 measurement sensors,

*Numbers in parentheses designate References at end of paper.

Richards and Neustadter

three multiplexing devices, analog-to-digital converters, and recording of the data in both analog and digital form. The parameters recorded for determining performance are: alternator power output, meteorological tower wind speed at 100 feet, nacelle wind speed, and rotor shaft torque. The general layout of these sensors is shown in Fig. 2. The nacelle anemometer is located approximately 15 feet upwind of the plane of the rotor and 9 feet above the rotor centerline. The meteorological tower is located 500 feet from the wind turbine, and was upwind of the wind turbine when the data reported here were recorded.

MEASURED POWER VERSUS WIND SPEED - The process of correlating wind turbine performance with wind measurements is not completely straightforward. Two problems are encountered in making the correlation. First, wind measurements must be made close enough to the wind turbine to be representative of the "same" wind that drives the rotor, but far enough away to eliminate any interference effects. Second, an anemometer registers a wind value at a point, while the turbine responds to the wind that engulfs the entire disk swept by the blade.

The approach taken here to eliminate these problems is: (1) to provide a wind measurement as close to the rotor as possible, the average alternator power for each revolution of the rotor was correlated with the simultaneous measurement of nacelle wind speed. Figure 3 shows a sampling (1/20th) of the 1½ hours of data analyzed for this paper. (2) To eliminate the interference effects of the rotor and nacelle on the nacelle wind measurements, the 2-minute averages of wind speeds at the nacelle and meteorological tower at 100 feet are related. This is done by calculating the least squares best-fit straight line to the data. Two-minute averaging was chosen based on (unpublished) calculations of spectral content of the wind and results reported elsewhere (8). This data and the curve fit are shown in Fig. 4. Then, the wind measurements in the power-versus-nacelle wind relation are rescaled, using the equation of this best-fit line. The final result of alternator power versus free-stream wind speed is shown in Figs. 5(a) and (b).

The data shown in Figs. 5(a) and (b) are explained as follows: the upper portion of the figure shows the statistics of groups of the measured parameters - where the data are grouped into wind speed intervals of 3 mph each. The symbols depicting the statistics of each group are defined as: the top bar on each symbol represents the upper bound of 84 percent of the data in the group, two symbols (squares) indicate the 90 percent confidence interval about the mean, and the lower dash represents the upper bound of the 16th percentile. This method of reducing data scatter for comparisons with theory and Sandia's "method of bins" (9) share some common features, although this method retains more information. Both methods are applications of standard data analysis techniques (10). Figure 5(b) shows the total number of data values analyzed, as well as the percentage of this total included in each group.

The comparison in Fig. 5(a) shows general agreement between the theory (shown as the solid line) and measured performance of the Mod-OA wind

turbine. The deviation from theory (based on steady-state winds) near rated wind speed, that is, at the "sharp corner" of the curve, is well understood and has been discussed fully by Golding (11). It is due to the fluctuation of the wind about its "steady" value which is equivalent to the wind turbine retaining an averaging on the two sides of the "corner." To account for this smoothing, the corner of the theoretical curve can be rounded, as shown in Fig. 5(a).

CONCLUSIONS

Of primary importance in the design of any wind turbine is the accurate prediction of the machine's performance characteristics. This paper compares the predicted power-versus-wind speed performance of the Mod-OA wind turbine with predictions made using the PROP code. This comparison demonstrates that the Mod-OA wind turbine has power-versus-wind speed performance which closely matches predictions. Also, the method discussed here for processing the measured data is a valuable tool which enables design analyses to be verified by field measurements.

REFERENCES

1. R. L. Thomas and T. R. Richards, "ERDA/NASA 100-Kilowatt Mod-O Wind Turbine Operations and Performance." NASA TM-73825, Sep. 1977.
2. "200-kW Wind Turbine Project," Jan. 1978. (Unpublished information document).
3. "Design Study of Wind Turbines 50 kW to 3000 kW for Electric Utility Applications, Analysis and Design." General Electric Co., Philadelphia, PA, GE-SD-76SDS-H288, Vol. 2, Feb. 1976. (NASA CR-134935)
4. "Design Study of Wind Turbines 50 kW for Electric Utility Applications, Analysis and Design." Kaman Aerospace Corp., Bloomfield, Conn., R-1382, Feb. 1976. (NASA CR-194937)
5. R. E. Wilson and S. N. Walker, "A Fortran Program for the Determination of Performance, Loads, and Stability Derivatives of Wind Turbines." Oregon State Univ., Oct. 25, 1974.
6. A. W. Cherritt and J. A. Gaidelis, "A 100-kW Metal Wind Turbine Blade Basic Data, Loads and Stress Analysis." Lockheed California Co., Burbank, CA, June 1975. (NASA CR-134956)
7. H. Abbott, A. E. von Doenhoff, and L. S. Stivers, Jr., "Summary and Airfoil Data." NACA Rep. 824, 1945.
8. I. Van der Hoven, "Power Spectrum of Horizontal Wind Speed in the Frequency Range from 0.0007 to 900 Cycles per Hour." Journal of Meteorology, Vol. 14, Apr. 1957, pp. 160-164.
9. R. E. Akins, "Performance Evaluation of Wind Energy Conversion Systems Using the Method of Bins - Current Status." Sandis Labs., Albuquerque, N.M., SAND-77-1375, Mar. 1978.
10. J. W. Tukey, "Exploratory Data Analysis." Reading, Mass.: Addison-Wesley Publ. Co., 1977.
11. E. W. Golding, "The Generation of Electricity by Wind Power." New York, Philosophical Library, 1955.



Fig. 1 - Mod-OA

HEIGHT,
FT




Fig. 2 - Wind turbine and meteorological tower configuration




Fig. 3 - Alternator power output vs wind speed measured on the nacelle. Each point represents simultaneous 1-revolution (1.5 sec) averages




Fig. 4 - Simultaneous two-minute averages of meteorological tower wind speed at 100 feet vs nacelle wind speed. The line is the least squares best-fit line to the data




Fig. 5

1. Report No. NASA TM-78916		2. Government Accession No.		3. Recipient's Catalog No.	
4. Title and Subtitle DOE/NASA-MOD-0A WIND TURBINE PERFORMANCE				5. Report Date	
				6. Performing Organization Code	
7. Author(s) T. R. Richards and H. E. Neustadter				8. Performing Organization Report No. E-9654	
				10. Work Unit No.	
9. Performing Organization Name and Address National Aeronautics and Space Administration Lewis Research Center Cleveland, Ohio 44135				11. Contract or Grant No.	
				13. Type of Report and Period Covered Technical Memorandum	
12. Sponsoring Agency Name and Address U.S. Department of Energy Division of Solar Energy Washington, D.C. 20545				14. Sponsoring Agency Code Report No. DOE/NASA/1004-78/13	
15. Supplementary Notes Prepared under Interagency Agreement E(49-26)-1004. To be presented at the Thirteenth Inter-society Energy Conversion Engineering Conference, San Diego, California, August 20-25, 1978.					
16. Abstract As part of the national wind energy program under the direction of the Department of Energy, the NASA-Lewis Research Center has designed and built, and is now operating, a large wind turbine at Clayton, New Mexico. Designated the Mod-0A-1, this is the first of three identical 200 kW wind turbines to be operated on electric utility networks. This machine was installed at Clayton, New Mexico, in November 1977. This paper presents a comparison between its predicted and measured power versus wind speed performance.					
17. Key Words (Suggested by Author(s))				18. Distribution Statement Unclassified - unlimited STAR Category 49 DOE Category UC-60	
19. Security Classif. (of this report) Unclassified		20. Security Classif. (of this page) Unclassified		22. Price*	
				21. No. of Pages	

NATIONAL AERONAUTICS AND SPACE ADMINISTRATION
WASHINGTON, D.C. 20546

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE \$300

SPECIAL FOURTH-CLASS RATE

BOOK

POSTAGE AND FEES PAID
NATIONAL AERONAUTICS AND
SPACE ADMINISTRATION
451



22 AUG 78 C R. V. Brulle 341/32²/23575 17 JUN 1980 P

POSTMASTER: If Undeliverable (Section 158
Postal Manual) Do Not Return

McGONNELL DOUGLAS
RESEARCH & ENGINEERING LIBRARY
ST. LOUIS, MISSOURI

1200

11 JUL 1978