NASA TECHNICAL MEMORANDUM

NAS 3 TM-78277

AN EXPERIMENTAL INVESTIGATION OF CONVECTION IN A FLUID THAT EXHIBITS PHASE CHANGE

By D. E. Fitzjarrald Space Sciences Laboratory

(NASA-TM-78277) AN EXPERIMENTAL INVESTIGATION OF CONVECTION IN A FLUID THAT EXHIBITS PHASE CHANGE (NASA) 28 PHC A03/MF A01 CSCL 20D

N80-25613

Unclas G3/34 23531

May 1980

CO MILION TO THE PROPERTY OF T

NASA

George C. Marshall Space Flight Center Marshall Space Flight Center, Alabama

		TECHNIC	AL REPORT STAND		
1.	REPORT NO. NASA TM-78277	2. GOVERNMENT ACCESSION NO.	3. RECIPIENT'S C		
4.	TITLE AND SUSTITLE	L	5. REPORT DATE		
	An Experimental Investigation	on of Convection in a Fluid	May 1980		
	That Exhibits Phase Change		6. PERFORMING OR	IGANIZATION CODE	
7.	AUTHOR(S) D. E. Fitzjarrald*		8. PERFORMING ORG	ANIZATION REPORT	
9.	PERFORMING ORGANIZATION NAME AND ADDRESS		10. WORK UNIT, NO.		
	George C. Marshall Space Fla	ight Center	11. CONTRACT OR G	RANT NO.	
l	Marshall Space Flight Center				
12.	SPONSORING AGENCY NAME AND ADDRESS		13. TYPE OF REPOR	T & PERIOD COVERE	
			Technical M	emorandum	
ļ	National Aeronautics and Spa Washington, D. C. 20546	ace Administration	•		
	washington, b. c. 20040		14. SPONSORING AC	SENCY CODE	
15.	SUPPLEMENTARY NOTES	ahonetony Caiones and Prairie			
	Prepared by Space Sciences Laboratory, Science and Engineering *1979 Summer Faculty Fellow, Atmospheric Sciences Division, Space Sciences Laborator Current Affiliation: Geophysical Fluid Dynamics Institute, Florida State University Tallahassee, Florida 32306				
16.	ABSTRACT				
1		systematically observed in a			
	isothermal horizontal boundaries. The working fluid was a nematic liquid crystal, which exhibits a liquid-liquid phase change at which latent heat is released and the				
		on to ordinary Rayleigh-Benard			
	phase is present alone, then	re exist two distinct types of	convective mot	ions initiated	
		ference. When a thin layer of gons with downgoing centers ex			
		r of light fluid is brought on			
l	the hexagons have upshooting	g centers. In both cases, the	motions are ke	pt going	
l	once they are initiated by to of the results to applicable	the instability due to release	of latent heat	. Relation	
	of the results to applicable	e theories is discussed.			
l					
İ					
İ					
17.	KEY WORDS	I.a. DISTRIBUTION ST	ATEMENT	····	
				•	
		Unclass	ified Unlimite	d L	
		1 Down	W. Mill	7	
		10201	14 1 000		
19.	SECURITY CLASSIF, (of this report)	20. SECURITY CLASSIF. (of this page)	21. NO. OF PAGES	22. PRICE	
	Unclassified	Unclassified	28	NTIS	

ACKNOWLE DGMENTS

The author is grateful for the interest, encouragement, and help of the staff of the following institutions: Woods Hole Oceanographic Institution

Geophysical Fluid Dynamics Summer Program, University of California, Los

Angeles Institute of Geophysics and Planetary Physics, University of Colorado

Department of Astrogeophysics, University of California Davis Department of

Land, Air, and Water Resources, and NASA Marshall Space Flight Center Atmospheric

Sciences Division.

TABLE OF CONTENTS

		Page			
1.	INTRODUCTION	1			
2.	THERMAL CONVECTION IN A SINGLE PHASE	3			
	2.1. Nematodynamics	7			
	2.3 Thermal Convection in One Phase Alone	9			
3.	RAYLEIGH-TAYLOR INSTABILITY IN THE TWO-PHASE SYSTEM	13			
4.	COMBINATION OF RAYLEIGH-TAYLOR AND RAYLEIGH-BENARD				
	INSTABILITIES	18			
5.	SUMMARY AND CONCLUSIONS	20			
REFE	ERENCES	24			

1. INTRODUCTION

This report presents the results of a laboratory experiment in convection flow through a phase change, across which the density changes and latent heat is released. The working fluid is a nematic liquid crystal that undergoes a first-order phase change at convenient temperature and pressure. The addition of a first-order phase change to the convection flow makes the problem much more interesting, because in addition to the thermal buoyancy gβΔT there are two more sources of buoyant acceleration, i.e., the latent heat release and density difference across the phase boundary. Thus, in addition to the ordinary Rayleigh number $R_{_{\rm T\!P}}$ = $\Delta T \beta g$ $d^3/\nu \kappa,$ there are two other, very similar parameters. When the imposed temperature difference, AT, is replaced by the temperature that is characteristic of the latent heat release, $L/c_{_{\rm D}}$, the governing parameter is $R_L = (L/c_p)\beta g \ d^3/\nu\kappa$. And when the density difference across the phase boundary, $\Delta \rho$, is used, the parameter is $R_{\Delta \rho} = (\Delta \rho / \rho) \text{ g d}^3 / \nu \kappa$. In the above, β is the expansion coefficient, g is gravity, d is the layer depth, v and k are the diffusivities of momentum and heat, L is the latent heat, and $\mathbf{c}_{\mathbf{n}}$ is the specific heat at constant pressure.

The phase-change convection problem is further complicated by the fact that there are two possible geometries, even in the thermally unstable case (lower boundary hotter). When the lighter phase is present near the lower boundary, increases of both R_L and $R_{\Delta\rho}$ are destabilizing; i.e., an increase in either parameter is similar to an increase in R_T and brings the flow closer to the point of marginal stability. The latent heat effect is due to the release of latent heat in the hot updraft regions, and the density effect occurs because the basic state is statically unstable, i.e., the Rayleigh-Taylor geometry. When the heavier fluid lies near the hotter lower boundary, increasing R_L is now stabilizing, since in the updrafts latent heat is taken

44 °

in. Increasing R_{Ap} is destabilizing, since the phase boundary moves opposite to the vertical motion so that gravity, tending to flatten out the phase boundary, induces upward motion in the region of updraft. The latter effect was first shown by Busse and Schubert (1971), who demonstrated that the phase boundary in this case was not the barrier to motion that had been previously supposed (Knopoff, 1964). In the preceding descriptions, it is assumed that the latent heat is released when the fluid goes from the lighter (higher temperature or lower pressure) phase to the heavier one, so that the heavier-above case applies to laboratory experiments where compressibility effects are negligible and the heavier-below case to the geophysical flows where such effects dominate.

Convection flows in which a fluid is thermally driven (Rayleigh-Benard) and undergoes a phase change or in which two immiscible fluids are driven by a density discontinuity (Rayleigh-Taylor) have a number of interesting applications to geophysics, meteorology, and astrophysics. Thermal convection through a phase boundary has been used to look at the problem of mantle convection that occurs in the presence of an olivine-spinel phase change at 400 km (Schubert and Turcotte, 1971). The unstable two-fluid system has been used to explain the formation of geological structures such as salt domes (Whitehead and Luther, 1975). In meteorology the latent heat release due to phase change is a crucial part in the description of cumulus convection and in cellular convection over the ocean, especially the closed-cell hexagonal convection occurring in marine stratocumulus layers (Schubert, et al., 1979). In astrophysical flows the phase change process can be used to model convective flows in which heat is released from nuclear reactions or fluid properties changed due to ionization (Spiegel, 1972).

The experiments reported here are necessarily limited to the heavierabove case, so the lighter phase must be present at the hotter lower boundary.
Therefore, the conditions that can be examined are: thermal convection in
each phase separately, convection with negligible thermal gradient and unstable
phase boundary, and thermal convection including phase charge. The goal of
the work is to analyze the unique laboratory fluid flows obtained in the presence of a phase change. We will also see if the results, or other experiments
using these fluids, can be used to understand geophysical flows with phase
change.

We begin with thermal convection in each phase, also giving a brief review of the fluid dynamics of nematics, and then proceed to consider in turn each of the other cases possible in the laboratory.

THERMAL CONVECTION IN A SINGLE PHASE

The working fluid in the experiments described below exhibits a firstorder phase change, i.e., one in which the density changes and latent heat
is released. Above the phase-change temperature the material is an ordinary
isotropic fluid, and below it is a nematic liquid crystal. Since we are
interested primarily in the phase change, the experimental configuration and
operating conditions will be chosen to minimize the effect of the unique
anisotropies of the nematic phase. The single-phase experiments are presented both to provide a baseline with which to compare the two-phase results
and to illustrate that the nematic anisotropies do not greatly affect the
observed flows.

2.1 Nematodynamics

A nematic liquid crystal is an anisotropic liquid made of long, rod-like molecules that can be aligned along one direction, designated by a unit vector n.

No change in properties is observed when $\underline{n} \rightarrow \underline{n}$. When aligned, the direction of molecular orientation is easily determined, since the material is birefringent. The thermal and electrical conductivity, index of refraction, and viscosity all depend on the orientation of \underline{n} relative to the direction of propagation. Unlike isotropic fluids, nematics can resist torques elastically. The amount of static torque present in the fluid depends on the curvature of \underline{n} . The molecules can be aligned by imposing an electrical or magnetic field, by suitable treatment of the confining boundaries that is coupled to the interior by the static torques, or by shears in the fluid. It is the last method of orientation that will be of interest in the present case.

The stress tensor of nematic fluids contains four viscosity coefficients in addition to that of ordinary isotropic fluids. It is also a function of $\underline{\mathbf{n}}$ (see deGennes, 1974). The method of solution is to solve the ordinary Navier-Stokes equations for viscous flow, using the more complicated nematic stress tensor, together with an additional differential equation for n that is the result of adding the torques on the molecules due to imposed fields, static torques, and fluid shears. When there are only small deviations in n from the value determined by an imposed field, the analysis is considerably simplified, and a number of different flows have been solved. Shear instabilities (Dubois-Violette and Manneville, 1978) and thermal convection (Guyon and Pieranski, 1974) in thin horizontal layers with n parallel to the confining boundaries both give results that are unique to nematics. Thermal convection in a thin vertical slot when n is normal to the confining boundaries has been solved by Horn, et al. (1976) for the case when the orientation is due to static torques and by Fitzjarrald and Owen (1979) when an electrical field is imposed by a feedback circuit. The key to these successful solutions has been that the fluid exists in a thin layer so that there are only small deviations from a constant imposed \underline{n} .

٨

By contrast, the present experiments are in thick layers, i.e., too thick for orientation at the boundaries or external fields to affect the interior of the fluid. Thus, the only orienting mechanism left is that of shear, and the viscous torques (see deGennes, 1974) will align the molecules so that <u>n</u> is parallel to the direction of motion, i.e., normal to the shear. The primary effect of this orientation will be to specify the effective viscosity coefficient.

In simple shear flow there are three principal viscosities in a nematic, depending on the angle between \underline{n} and the shear. These are illustrated in Figure 1. Near the phase-change temperature a typical room-temperature nematic ν_a is approximately the same as ν_i , the isotropic value, while ν_b is about 25% less than this value and ν_c is nearly double. So at the onset of motion in a randomly oriented nematic, ν is slightly higher than in an isotropic fluid, since it is the average of the values for the three different orientations. As the motion starts, fluid shears are effective in orienting \underline{n} , so that the value of viscosity becomes very close to ν_b . Therefore, there must be a slight decrease in viscosity as the motions start.

The thermal diffusivity is also anisotropic in a nematic, with the value of $\kappa_{\parallel}/\kappa_{\parallel}\sim 1.5$ for room-temperature nematics. Here κ_{\parallel} and κ_{\parallel} are the diffusivities along and normal to n, respectively. It is clear that, because of the two anisotropic effects —lowering of the effective viscosity and heat focusing by the anisotropic thermal diffusivity— the onset of motion in a convective cell will be considerably different in a nematic than it is in an ordinary isotropic fluid. There should be a hysteresis, with motion continuing at lower R_t than that necessary for initiation of motion. Once the motion has started with R_t greater than the initiating value, however, the flow should be very similar to that of the isotropic phase. In this case the viscosity becomes very nearly ν_b , and since the convective heat transfer is greater than the conductive part, the conduction anisotropy is not a dominant effect.




Figure 1. Sketch of the three principal viscosities, $\nu_{a},~\nu_{b},~\nu_{c},~in~a~nematic.$

In the experiments to follow, the peculiarities of nematics will be avoided by concentrating on the finite-amplitude flows that exist once the flow is well established. It may be noted that the discussion given previously for a randomly oriented nematic is considerably different than for a well-oriented one. Then the molecules are initially oriented by an external field or surface treatment so that \underline{n} is parallel to the confining plates, the motion starts at R_t -1 instead of R_t -1700 for an isotropic fluid, because of the heat-focusing effect of the conductivity anisotropy. Coupling of the heat focusing to the thermal convection by means of changes in \underline{n} can also lead to oscillatory, or overstable convection because of the difference between the convection and orientation time scales (Guyon, et al., 1979). And when \underline{n} is initially normal to the plates, convective motions can occur when the fluid is heated from above (Guyon and Pieranski, 1974).

2.2 Description of Experiment

A sketch of the apparatus is shown in Figure 2. The fluid is confined by means of glass plates in a horizontal layer 45 mm diameter by 6.4 mm deep.

Water is circulated to keep the confining plates at constant temperature. Conductivity of the glass is approximately 6 times that of the working fluid, and the water flow rates are large enough so that nearly an isothermal boundary condition is maintained. The working fluid is a cyanobiphenyl, K-15 from BDH Chemicals. It is nematic from 22.5°C to 35°C and is very stable, being resistant to degradation by moisture, exposure to the atmosphere, and uv radiation. Unfortunately, not all the physical constants are known. The values should not be significantly different from those of other room-temperature nematics (such as MBBA--more widely studied, but much less stable), so that estimates




Figure 2. Sketch of convection cell.

based on such typical values should be applicable to K-15. The physical properties of interest that are known for K-15 are:

$$\rho = 1.02 \text{ gm/cm}^3 \text{ @ } 25^{\circ}\text{C}$$

$$\beta = 10^{-3} \text{ °C}^{-1} \text{ @ } 25^{\circ}\text{C}$$

$$n_e/n_o = 1.7/1.5 \text{ @ } 25^{\circ}\text{C}$$

$$L = 0.8 \text{ cal/gm},$$

where n and n are the extraordinary and rdinary indices of refraction. Properties of MBBA that should be approximately the same as K-15 are:

$$v_i = 0.3 \text{ cm}^2/\text{s}$$
 $\kappa_i = 10^{-3} \text{ cm}^2/\text{s}$
 $\Delta p/\rho = 2.10^{-3}$
 $c_n = 0.4 \text{ cal/gm}^\circ\text{C}$.

We see that $\Delta p/\rho$ and L/c_p both are approximately equal to a $2^{\circ}C$ change in fluid temperature. Using the preceding values, we find that $\Delta T = 2^{\circ}C$ is enough to make R_T -1700 and initiate thermal convection. We find that motion starts with ΔT -1.5°C in the isotropic Γ as just above the transition, so that the above values must be close to the true values. We intend to avoid the region near critical R_T , so that a more precise value of the constants is not necessary.

2.3 Thermal Convection in One Phase Alone

With only one phase present and an unstable temperature gradient, the familia. Rayleigh-Benard results are obtained. Convection rolls are observed when ΔT exceeds some critical value, and the rolls are circular because of the circular symmetry of the experiment with downflow near the outer edge. Upflow occurs at the center of the experiment with 3 waves across the diameter, corresponding to a wavelength $\lambda = 2.3$ d. However, the limited aspect ratio and the

necessity of having an integer number of waves in the experiment precludes making any general conclusions from this measurement of the wavelength. Flow visualization in the clear isotropic (lighter) phase is by shadowgraph and interferometer that show the temperature distribution in the layer. In the liquid crystal (heavier) phase, the birefringence allows observation of the fluid motions. As soon as motion starts, the molecules line up along the direction of motion due to the action of shear torques on n. Thus, the fluid appears clear in the regions where it is moving directly toward or away from the observer, i.e., the hottest and coldest part of the convection rolls. In the region where the fluid is moving normal to the direction of viewing, the fluid appears opaque.

A photograph of the transmitted light is shown in Figure 3 for the conditions when $\Delta T = 2^{\circ}C$ and the hotter temperature is just below the phase-change temperature, T. Upflow at the center and second ring with downflow at the first ring and the outer edge is confirmed by direct observation with a stereo microscope. With the same ΔT and the coldest temperature just above T_c , i.e., in the isotropic phase, the thermal pattern is seen to be just the same as for the heavier phase. A photograph of the interference pattern is shown in Figure 4, where the wider spacing between bright lines indicates colder temperatures. Careful observation of the interference pattern (and the associated shadowgraph) indicates that the diameter of the coldest part of the convection roll is just the same as for the other phase. A roll-like pattern is always observed in thermal convection in just one phase. When the rotational symmetry of the flow is disturbed by inverting the cell and shaking it, the roll pattern that occurs once the layer is returned to horizontal is no longer circular. Sinuous rolls with spacing \(\lambda_2\)d are observed that are, similar to the photographs of Willis and Somerville (1972) for convection in a rectangular geometry.

Figure 3. Thermal convection in liquid crystal phase alone. $\Delta T = 2^{\circ}C$. Transmitted light is shown. Brighter areas are due to birefringence of the liquid crystal. Molecules are oriented by the fluid shears. 11




Figure 4. Thermal convection in the isotropic phase alone. $\Delta T = 2^{\circ}C$. Wider spacing between the interference lines indicates cooler temperatures.

The circular thermal pattern of the convection rolls is first seen in the lighter phase when $\Delta T_{s}^{2}1.5^{\circ}C$. When $\Delta T = 2^{\circ}C$, the rolls are vigorous and the thermal pattern is quite distinct. In the heavier liquid-crystal phase the roll pattern is seen to start as ΔT is raised above $0.5^{\circ}C$ and to persist once started until ΔT is lowered to $0.3^{\circ}C$. It appears, therefore, that the anisotropies of the liquid-crystal phase have lowered the critical temperature slightly, but the two visualization techniques do not necessarily have the same threshold, so a definite conclusion cannot be made. The hysteresis that occurs in the liquid-crystal phase is very slight, being almost within the precision of the temperature measurement.

Certainly, the effects of anisotropy are not great and do not result in a qualitatively different flow as is the case for uniformly oriented liquid crystals. With $\Delta T = 2^{\circ}C$ the convection flow is the same in either phase, as nearly as can be determined. It is thus inferred that the liquid-crystal anisotropies have only a slight effect on the fluid motions to be described below.

3. RAYLEIGH-TAYLOR INSTABILITY IN THE TWO-PHASE SYSTEM

A statically unstable condition can be produced in a nearly isothermal layer, either by slightly elevating the lower temperature when the whole fluid layer is in the heavier phase just below T_c, or by slightly lowering the upper temperature when the whole fluid is just above T_c. In the first case a thin layer of lighter fluid forms at the bottom and in the second a thin layer of heavier fluid forms at the top. As the depth of the thin layer gets larger, the interface is seen to become distorted, finally leading to spouts of fluid shooting out of the thin layer. The spout of unstable fluid thus formed becomes the center of a cellular pattern that continues to have a convective flow. The flow is quasi-steady with new cells starting up and old ones dying out but always with approximately the same spacing.

Figure 5 is a photograph of the transmitted light of the cellular pattern formed when the lower temperature is 0.1°C above T_C. The bright circles are regions of upshooting out of the layer of clear, light fluid near the lower boundary. The slow return flow is along the boundaries of the cell. A parcel fluid thus starts in the light phase, shoots up in the center, spreads out along the slightly cooler top boundary changing to the heavy phase, and then returns to the center of the cell to commence another trip. Figure 6 is the corresponding photograph of the pattern when the upper boundary is 0.1°C lower than T, the darker circles now being the downshooting heavier fluid at the center of the cells.

A sketch of the flow patterns is presented in Figure 7, based on observations with the stereo microscope. It is seen that sinking motion is associated with changing from heavy to light (taking in latent heat), and rising motion with changing from light to heavy (giving off latent heat). This behavior is as expected in the qualitative discussion in the introduction and is confirmed by watching the phase-change process. When $\Delta T = 0$ and a parcel of fluid is changing from heavy to light (melting), it always sinks; and when it is changing from light to heavy (freezing), it always rises. Thus, spheres of heavy fluid that are becoming larger rise, and those that are becoming smaller sink, when $\Delta T = 0$.

The initiation of the cellular motions is described by the analysis of Whitehead and Luther (1975), who have analyzed the linear and finite-amplitude Reyleigh-Taylor problem. The linear results for a thin layer of unstable fluid when the viscosities are equal are that the wavenumber of maximum growth is $k = 2\pi/\lambda = 1.8/2h$, and the growth rate is n = 0.15 g $(\Delta \rho/\rho)$ h/v, where h is the dep. In the present case the calculated time for growth is




Figure 5. Buoyant motions due to unstable interface. Upshooting plumes from the thin layer of light fluid near the lower boundary create cellular motion. ΔT = 0.1°C.






Figure 6. Buoyant motions due to unstable interface. Downshooting plumes from the thin layer of heavy fluid near the upper boundary create cells with downgoing centers. $\Delta T = 0.1^{\circ}C$.

A ...



a. Thin layer near lower boundary



b. Thin layer near upper boundary

Figure 7. Sketch of cross section of fluid cells shown in Figures 5 and 6.

HIGH PAGE IS

5 min when h = 0.1 mm and 30 s when h = 1 mm. Thus, when the layer depth has grown to 1 mm, the instability should grow quickly, with a horizontal wavelength approximately equal to the depth of 6 mm. These are roughly the same values observed for both the upshooting and downshooting cells. The finite-amplitude analysis of Whitehead and Luther indicates that the planform of the motion should be hexagonal, with the sign of the motion so that the fluid jets out of the thin layer. This result is also confirmed by the present results.

Once the motion has been established by the unstable density interface (corresponding to the parameter $R_{\Delta\rho}$ discussed in the introduction), it continues without stopping. This is in contrast to the classic Rayleigh-Tavlor problem where the fluid spout necks down and becomes a bubble at the other boundary. The continuing flow must be due to the effect of latent heat release, which is of the proper sense and magnitude. But the fact that this latent-heat driven convection needs the finite-amplitude Rayleigh-Taylor flow to kick it off and a small temperature gradient to keep it going would surely complicate analysis of the flow.

4. COMBINATION OF RAYLEIGH-TAYLOR AND RAYLEIGH-BENARD INSTABILITIES

When an already-existing thermal convection flow in a single phase is altered by slightly changing the mean temperature (keeping ΔT the same) so that the phase change occurs at one of the boundaries, the planform of the convection is immediately altered. With the lower plate temperature just above T_c , the flow changes from rolls to cells with upshooting centers. This condition is shown in Figure 8 where $\Delta T = 2^{\circ}C$. Parcels of fluid go right through the phase boundary as discussed in Section 3, except with much greater speed. Because of the circular symmetry of the initial thermal convection flow the upshooting parts of the cells are arranged around the circle of up-flow and the center.

7




Figure 8. Thermal convection with phase change. Lower boundary is just above the phase-change temperature. Cells have upgoing centers. $\Delta T = 2^{\circ}C$.

When the upper plate temperature is just below T_c, the cells have downshooting centers and are arranged around the downflow ring of the initial flow. This is shown in Figure 9, where the dark line is approximately 2d. In both cases, the flows are steady state.

The changing of the convection planform from rolls to hexagons when something is present to disturb the vertical symmetry of the flow is akin to the work of Busse (1962) for vertical variations in properties and Krishnamurti (1968, 1975) for time variations and boundary suction. In each case the vertically symmetric rolls must give way to the asymmetric hexagons. When convection occurs in a liquid, for example, the hexagons must have upshooting centers so that the jet occurs in the low-viscosity, warm fluid. Gas hexagons go the other way, because the low viscosity is in the cold fluid. In the present case the Rayleigh-Taylor instability provides the asymmetry to cause the change in planform. The latent heat release is available to make the motion go faster, but since it is present in both updraft and downdraft, there is no contribution to asymmetry.

5. SUMMARY AND CONCLUSIONS

The laboratory experiments described here have explored the effect of phase change on buoyancy-driven flows in a horizontal layer. Thermal convection in each phase separately gave a basis with which to compare the two-phase results and showed that the anisotropies of the liquid-crystal working fluid did not greatly affect the results. When no appreciable thermal gradient was present and the phase boundary was unstable, the experimental results correspond to the analysis of Whitehead and Luther (1975). The continuation of flow after its initiation by the unstable phase boundary is a new result and is unique to these experiments. The release of latent heat as the fluid passes through




Figure 9. Thermal convection with phase thanks. Opper boundary is just below the phase-change temperature. Cells have downgoing centers. ΔT = 2°C. Length of dark bar is approximately twice the fluid depth.

the phase boundary must be the primary cause of this quasi-steady flow. When thermal convection exists in the presence of a phase change, the planform was observed to be cellular, instead of the rolls in thermal convection alone. The cause of this change in planform is the vertical asymmetry due to fluid shooting out from the thin layer across the density discontinuity of the interface.

The results have shown that a steady convection flow can exist right through a phase boundary, and that the flow is profoundly changed by presence of a change of phase. The limits of the laboratory and composite of the problem limit the applicability of these results to phase-change flows in geophysics, meteorology, and astrophysics, however. The geophysical case that may be applicable to mantle convection, where the heavy fluid lies below, cannot be attained in the laboratory. Geological flows such as salt domes and volcanism are perhaps better modeled by fluids with vastly different viscosities, as used by Whitehead and Luther. The meteorological case of cumulus convection driven by latent heat release is certainly an important one and has been the object of previous laboratory experiments. In such a case, the release of latent heat occurs only in the updraft regions, which is different from the fluid used here.

In marine stratocumulus layers that are driven by latent heat release the density interface, i.e., the boundary between the marine layer and the free atmosphere, is a stabilizing influence (in contrast to the mantle convection where latent heat is stabilizing and the density interface destabilizing). So the present results do not apply, because in each of these cases the principal driving forces are in the wrong sense relative to each other. It appears that the fluid used in these experiments cannot be used to directly model

geophysically relevant experiments. However, the results do show that the latent heat released in the phase change can keep the fluid in martin when it would ordinarily die out; and the density difference across the phase boundary can change the usual convection rolls to cells. Both these effects are similar to those that likely occur when phase change is present in geophysical or meteorological convection flows.

All the state of t

REFERENCES

- Busse, F.H., 1962. Das stabilitstaverhalten der zellularkanvektion bei endlicher amplitude Ph.D. thesis Ludwig-Maximilian Univ., Munich. (English translation by S.H. Davis Ref. LT-66-19 Rand. Corp. Santa Monica, 1966).
- Busse, F.H. and G. Schubert, 1971. Convection in a fluid with two phases. J. Fluid Mech. 46 801-812.
- Dubois-Violette, E. and P. Manneville, 1978. Stability of Couette flow in nematic liquid crystals. J. Fluid Mech. 89 273-303.
- Fitzjarrald, D.E. and E.W. Owen, 1979. Liquid crystal convection: a novel accelerometer. J. Physics E: Sci. Irstrum. 12 1075-1082.
- deGennes, P.G., 1974. The physics of liquid crystals (Oxford: Clarendon).
- Guyon, E. and P. Pieranski, 1974. Convective instabilities in nematic liquid crystals. Physica 73 184-194.
 - Guyon, E., P. Pieranski, and J. Salan, 1979. Overstability and inverted bifurcation in homeotropic nematics heated from below. J. Fluid Mech., 93, 65-31.
- Horn, D., E. Guyon, and P. Pieranski, 1976. Convection thermique dans des cellules nematiques inclinees. Revue Phys. Appl. 11 139-142.
 - Knopoff, L., 1964. The convection current hypothesis. Rev. Geophys. 2 89.
 - Krishnam ti, R., 1968. Finite amplitude convection with changing mean temperature. J. Fluid Mech. 33 445-463.
 - Krishnamurti, R., 1975. On cellular cloud patterns. J. Atmos. Sci. <u>32</u> 1353-1383.
 - Schubert, G. and D.L. Turcotte, 1971. Phase changes and mantle convection. J. Geophys. Res. 76 1424-1432.
 - Schubert, W.H., J.S. Wakefield, E.J. Steiner, and S.K. Cox. Marine Stratocumulus convection. J. Atmos. Sci. <u>36</u> 1286-1324.
- Speigel, E.A., 1972. Convection in stars. Am. Rev. Astronomy and Astrophysics 10, 261-304.
- Whitehead, J.A. and D.S. Luther, 1975. Dynamics of laboratory diapir and plume models. J. Geophys. Res. 80 705-717.
- Willis, G.E. and R.C.J. Somerville, 1972. Roll-diameter dependence in Rayleigh convection and its effect upon the heat flow. J. Fluid Mech. 54 351-367.

- i -

1

APPROVAL

AN EXPERIMENTAL INVESTIGATION OF CONVECTION IN A FLUID THAT EXHIBITS PHASE CHANGE

By D. E. Fitzjarrald

The information in this report has been reviewed for technical content. Review of any information concerning Department of Defense or nuclear energy activities or programs has been made by the MSFC Security Classification Officer. This report, in its entirety, has been determined to be unclassified.

GEORGE H. FICHTL

Chief, Fluid Dynamics Branch

WILLIAM W. VAUGHAN

Chief, Atmospheric Sciences Division

CHARLES A. LUNDQUIST

Director, Space Sciences Laboratory