NASA Contractor Report 181709 ICASE REPORT NO. 88-51

ICASE

NON-OSCILLATORY CENTRAL DIFFERENCING FOR HYPERBOLIC CONSERVATION LAWS

Haim Nessyahu

Eitan Tadmor

(NASA-CE-1817C9)NCN-CSCILLATCRY
CENTRALN89-10582LIFFERENCINGFCFEYFFFECLIC
CONSERVATIONN89-10582LAWSFinal
Report
(NASA)53FCSCLUnclasUnclasUnclasUnclas

G3/64 0166494

Contract Nos. NAS1-18107 and NAS1-18605 September 1988

INSTITUTE FOR COMPUTER APPLICATIONS IN SCIENCE AND ENGINEERING NASA Langley Research Center, Hampton, Virginia 23665

Operated by the Universities Space Research Association



Langley Research Center Hampton, Virginia 23665

-

ľ

• •

•

NON-OSCILLATORY CENTRAL DIFFERENCING FOR HYPERBOLIC CONSERVATION LAWS

Haim Nessyahu and Eitan Tadmor^{*} School of Mathematical Sciences Raymond and Beverley Sackler Faculty of Exact Sciences Tel Aviv University Tel Aviv, Israel and

Institute for Computer Applications in Science and Engineering NASA Langley Research Center Hampton, Virginia

ABSTRACT

Many of the recently developed high-resolution schemes for hyperbolic conservation laws are based on upwind differencing. The building block of these schemes is the averaging of an approximate Godunov solver; its time consuming part involves the field-by-field decomposition which is required in order to identify the "direction of the wind." Instead, we propose to use as a building block the more robust Lax-Friedrichs (LxF) solver. The main advantage is simplicity: no Riemann problems are solved and hence field-by-field decompositions are avoided. The main disadvantage is the excessive numerical viscosity typical to the LxF solver. We compensate for it by using high-resolution MUSCL-type interpolants. Numerical experiments show that the quality of the results obtained by such convenient central differencing is comparable with those of the upwind schemes.

^{*}This research was supported by the National Aeronautics and Space Administration under NASA Contract Nos. NAS1-18107 and NAS1-18605 while the second author was in residence at the Institute for Computer Applications in Science and Engineering (ICASE), NASA Langley Research Center, Hampton, VA 23665. Additional support was provided by U.S.-Israel BSF Grant No. 85-00346, and by NSF Grant No. DMS85-03294 while in residence at UCLA, Los Angeles, CA 90024.

• ŧ

INTRODUCTION

In this paper we present a family of non-oscillatory, second order, central difference approximations to non-linear systems of hyperbolic conservation laws. These approximations can be viewed as natural extensions of the first-order Lax-Friedrichs (LxF) scheme. In particular, total-variation and entropy estimates are provided in the scalar case, and unlike the upwind framework, no Riemann problems need to be solved in the case of systems of conservation laws. The use of second-order piecewise-linear approximants instead of the first-order piecewise-constant ones, compensates for the excessive LxF viscosity, and results in second-order resolution Riemann-solver-free family of central difference schemes.

The paper is organized as follows. In Section 2, we derive our family of high resolution central differencing schemes, using the LxF solver together with MUSCL-type interpolants. Thus, at each time-level we reconstruct from the piecewise constant numerical data, a nonoscillatory piecewise linear approximation of second order accuracy. We then follow the evolving solution to the next time level, and end up by projecting it back to a piecewise constant solution. The result is a family of schemes which takes an easily implemented predictor-corrector form. The resolution of our method hinges upon the choice of certain local <u>numerical derivatives</u> with which one reconstructs the piecewise-linear MUSCL-type interpolants from the piecewise-constant data

In Section 3, we concentrate on the scalar conservation law. We discuss a variety of choices for numerical derivatives, and prove that the resulting scalar family of schemes, under the appropriate CFL limitation, satisfies both the Total Variation Diminishing (TVD) property and a cell entropy inequality. These properties guarantee the convergence to the unique entropy solution, at least in the genuinely non-linear scalar case.

In Section 4, we describe several ways to extend our scalar family of central differencing schemes to systems of conservation laws. The main issue lies again in the choice of vectors of numerical derivatives. First, we describe a component-wise extension for the definition of these vectors, which share the simplicity of the scalar family of schemes. Next, we demonstrate the flexibility of our central differencing framework, which enables us to incorporate characteristic information-whenever available, into the definition of numerical derivatives. We continue, by using this characteristic-wise framework to isolate the contact wave where the Artificial Compression Method (ACM) is employed, while treating the more robust sound waves using the less expensive component-wise approach. We end up by presenting a corrective type ACM, which is implemented in a componentwise manner. This both improves the contact resolution, and retains the simplicity of the Riemann-solver-free scalar approach.

Finally, in Section 5 we present numerical experiments with our high-resolution non-

oscillatory central difference schemes, and compare the results with the corresponding upwind-based ones.

Both the quantitative and qualitative results for a representative sample of compressible flow problems governed by the Euler equations, are found to be in complete agreement with the resolution expected by the scalar analysis. Taking into account the ease of implementation, robustness and time performance, these results compare favorably with the results obtained by the corresponding upwind-based schemes.

2. A FAMILY OF HIGH-RESOLUTION CENTRAL DIFFERENCING METHODS

Many of the recently developed high-resolution schemes, which approximate the one dimensional system of conservation laws

$$\frac{\partial u}{\partial t} + \frac{\partial}{\partial x}(f(u)) = 0, \qquad (2.1)$$

are based on <u>upwind</u> differencing. The prototype of such upwind approximations is the Godunov scheme [4]; it computes a piecewise constant approximate solution over cells of width $\Delta x = x_{j+\frac{1}{2}} - x_{j-\frac{1}{2}}$, which is of the form,

$$\overline{v}(x,t) = v_j(t), \qquad x_{j-\frac{1}{2}} \le x \le x_{j+\frac{1}{2}}.$$
 (2.2)

To proceed in time, the Godunov scheme first evolves the piecewise constant solution, $\overline{v}(x,t)$, for a sufficiently small time step Δt . Initiated with $\overline{v}(x,t)$, equation (2.1) consists of a successive sequence of non-interacting Riemann problems. Their resulting solution at time level $t + \Delta t$, can be expressed in terms of the Riemann solver, $R(\frac{x}{t}; w_t, w_r)$,

$$v(x,t+\Delta t) = R(\frac{x-x_{j+\frac{1}{2}}}{\Delta t}; v_j(t), v_{j+1}(t)), \qquad x_j \le x \le x_{j+1}.$$
(2.3)

This solution is then projected back into the space of piecewise constant gridfunctions, see Fig. 2-1,

$$v_{j}(t + \Delta t) \equiv \overline{v}(x, t + \Delta t) = \frac{1}{\Delta x} \int_{x_{j-\frac{1}{2}}}^{x_{j+\frac{1}{2}}} v(y, t + \Delta t) dy, \qquad x_{j-\frac{1}{2}} \leq x \leq x_{j+\frac{1}{2}}.$$

$$(2.4)$$

$$v_{j-1}(t) \qquad v_{j}(t) \qquad v_{j}(t) \qquad v_{j+1}(t)$$

$$v_{j-1}(t) \qquad v_{j}(t) \qquad v_{j}(t) \qquad v_{j+1}(t)$$

Fig. 2-1

Integration of (2.1) over a typical cell $[x_{j-\frac{1}{2}}, x_{j+\frac{1}{2}}] \times [t, t + \Delta t]$ yields

 $v_j(t + \Delta t) = v_j(t) + \lambda [f(R(0^+; v_{j-1}(t), v_j(t)) - f(R(0^+; v_j(t), v_{j+1}(t))], \lambda \equiv \frac{\Delta t}{\Delta x}]$ (2.5) This shows the upwind property of the Godunov scheme. Namely, if the characteristic speeds throughout the relevant neighbouring cells, $[x_{j-1}, x_{j+1}]$, are all positive (respectively, negative), then (2.5) is simplified into $v_j(t + \Delta t) = v_j(t) - \lambda [f(v_j(t)) - f(v_{j-1}(t))]$ (respectively, $v_j(t + \Delta t) = v_j(t) - \lambda [f(v_{j+1}(t)) - f(v_j(t))]]$). However, a more complex situation occurs when there is a mixture of both rightgoing and leftgoing waves. In this case, the computation of Godunov's numerical flux in (2.5) requires us to identify the "direction of the wind," i.e., to distinguish between the left- and rightgoing waves inside the Riemann fan. The exact (or approximate) solution of the Riemann fan may be an intricate task, and in this context, we mention the field-by-field decomposition proposed by Roe [19], which intends to simplify this task.

Instead, in this section we propose a high resolution approximation of (2.1), which is based on the staggered form of the Lax-Friedrichs (LxF) scheme,

$$v_{j+\frac{1}{2}}(t+\Delta t) = \frac{1}{2}[v_j+v_{j+1}] - \lambda[f(v_{j+1}(t)) - f(v_j(t))].$$
(2.6)

The LxF scheme, [13], is a prototype of a central difference approximation, which offers a great simplicity over the upwind Godunov scheme (2.5). We observe that (2.6) can also be interpreted as a piecewise constant projection of successive non-interacting Riemann problems, which are integrated over a staggered grid, see Fig. 2-2,

$$v_{j+\frac{1}{2}}(t+\Delta t) \equiv \overline{v}(x,t+\Delta t) = \frac{1}{\Delta x} \int_{x_j}^{x_{j+1}} R(\frac{x-x_{j+\frac{1}{2}}}{\Delta t}; v_j, v_{j+1}) dx, \quad x_j \leq x \leq x_{j+1}.$$
(2.7)



Fig. 2-2

The robustness of the LxF scheme, (2.7), stems from the fact that unlike the Godunov case, here we integrate over the entire Riemann fan, taking into account both the leftand rightgoing waves. This enables us to ignore any detailed knowledge about the exact (or approximate) Riemann solver $R(\cdot;\cdot,\cdot)$. Unfortunately, the LxF staggered solver, (2.7), which results in the simple recipe (2.6), suffers from excessive numerical viscosity, which is evident from the viscous form [23]

$$v_{j}(t + \Delta t) = v_{j}(t) - \frac{1}{2}\lambda[f(v_{j+1}(t) - f(v_{j-1}(t))] + \frac{1}{2}[Q_{j+\frac{1}{2}}\Delta v_{j+\frac{1}{2}}(t) - Q_{j-\frac{1}{2}}\Delta v_{j-\frac{1}{2}}(t)], \quad \Delta v_{j+\frac{1}{2}}(t) \equiv v_{j+1}(t) - v_{j}(t).$$

$$(2.8)$$

Indeed, the class of upwind schemes is characterized by a numerical viscosity coefficient matrix $Q_{j+\frac{1}{2}}^{U} \sim \lambda |\overline{A}_{j+\frac{1}{2}}|$, (here $\overline{A}_{j+\frac{1}{2}}$ refers to an approximate average of the Jacobian of f(v(x,t)) over the cell $[x_j, x_{j+1}] \times [t, t + \Delta t]$, e.g., [22]). By the CFL limitation, this amount of numerical viscosity is always less than the amount of numerical viscosity present in the central LxF scheme, whose non-staggered form corresponds to $Q^{LxF} \equiv I$. Consequently, the upwind Godunov-like approximations have better resolution than the central LxF approximation, though they both belong to the same class of first-order accurate schemes. This is one of the main motivations for using upwind schemes as building blocks for the modern shock capturing methods of higher (than first-order) resolution, e.g. [7], [17], [24].

Alternatively, our proposed method will use the simpler central LxF solver as the building block for a family of high-resolution schemes. In this manner we shall retain the LxF main advantage of simplicity: no Riemann problems are solved and hence field-by-field decompositions are avoided. The main disadvantage of excessive numerical viscosity will be compensated by using high-resolution MUSCL interpolants, [24], instead of the first-order piecewise constant ones in (2.2).

To this end, at each time level we first reconstruct from (2.2) a piecewise linear approximation of the form

$$L_{j}(x,t) = v_{j}(t) + (x - x_{j}) \frac{1}{\Delta x} v'_{j}, \qquad x_{j-\frac{1}{2}} \leq x \leq x_{j+\frac{1}{2}}.$$
(2.9a)

This form retains conservation, i.e., (here the overbar denotes the $[x_j, x_{j+1}]$ - cell average),

$$\overline{L}_{j}(x,t) = \overline{v}(x,t) = v_{j}(t);$$

second-order accuracy is guaranteed if the so-called vector of numerical derivative, $\frac{1}{\Delta x}v'_{j}$, which is yet to be determined, satisfies

$$\frac{1}{\Delta x}v'_j = \frac{\partial}{\partial x}v(x=x_j,t) + O(\Delta x).$$
(2.9b)

Next, we continue with a second stage, similar to the construction of the central LxF recipe: we evolve the piecewise linear interpolant, (2.9), which is governed by the solution of successive sequences of noninteracting Generalized Riemann (GR) problems, [1], see Fig. 2-3,



$$v(x, t + \Delta t) = GR(x, t + \Delta t; L_j(x, t), L_{j+1}(x, t)), \quad x_j < x < x_{j+1}.$$

Fig. 2-3

Finally, the resulting solution is projected back into the space of staggered piecewiseconstant gridfunctions

$$v_{j+\frac{1}{2}}(t+\Delta t) = \overline{v}(x,t+\Delta t) \equiv \frac{1}{\Delta x} \int_{x_j}^{x_{j+1}} v(y,t+\Delta t) dy, \qquad x_j \leq x \leq x_{j+1}.$$
(2.10)

In view of the conservation law (2.1), the last integral equals

$$v_{j+\frac{1}{2}}(t+\Delta t) = \frac{1}{\Delta x} \left[\int_{x_j}^{x_{j+\frac{1}{2}}} L_j(x,t) dx + \int_{x_{j+\frac{1}{2}}}^{x_{j+1}} L_{j+1}(x,t) dx \right] \\ - \frac{1}{\Delta x} \left[\int_{\tau=t}^{t+\Delta t} f(v(x_{j+1},\tau)) d\tau - \int_{\tau=t}^{t+\Delta t} f(v(x_j,\tau)) d\tau \right].$$
(2.11)

The first two linear integrands on the right of (2.11), $L_j(x,t)$ and $L_{j+1}(x,t)$, are given by (2.9a) and can be integrated exactly. Moreover, if the CFL condition

$$\lambda \cdot \max_{x_j \leq x \leq x_{j+1}} \rho(A(v(x,t))) < \frac{1}{2}, \qquad (2.12)$$

is met, then the last two integrands on the right of (2.11), $f(v(x_j, \tau))$ and $f(v(x_{j+1}, \tau))$, are smooth functions of τ ; hence they can be integrated approximately by the midpoint rule at the expense of $O(\Delta t)^3$ local truncation error. Thus we arrive at

$$v_{j+\frac{1}{2}}(t+\Delta t) = \frac{1}{2}[v_j(t) + v_{j+1}(t)] + \frac{1}{8}[v'_j - v'_{j+1}] - \lambda[f(v(x_{j+1}, t+\frac{\Delta t}{2})) - f(v(x_j, t+\frac{\Delta t}{2}))].$$
(2.13)

By Taylor expansion and the conservation law (2.1),

$$v(x_j,t+\frac{\Delta t}{2})=v_j(t)-\frac{1}{2}\lambda f_j', \qquad (2.14)$$

may serve as our approximate midvalue, $v(x_j, t - \frac{\Delta t}{2})$, within the permissible second-order accuracy requirement. Here, $\frac{1}{\Delta x}f'_j$ stands for an approximate numerical derivative of the flux $f(v(x = x_j, t)),$

$$\frac{1}{\Delta x}f'_{j} = \frac{\partial}{\partial x}f(v(x=x_{j},t)) + O(\Delta x), \qquad (2.15)$$

which is yet to be specified.

We should emphasize that while using the central type LxF solver, we integrated over the entire Riemann fan, see $v(x, t + \Delta t)$ in (2.10), which consists of both the left- and rightgoing waves. On the one hand, this enabled us to ignore any detailed knowledge about the exact (or approximate) generalized Riemann solver $GR(\cdot; \cdot, \cdot)$; on the other hand, this enables us to accurately compute the numerical flux, $\int_{\tau=t}^{t+\Delta t} f(v(x,\tau))d\tau$, whose values are extracted from the <u>smooth</u> interface of two non-interacting Riemann problems.

In summary, our family of central differencing schemes takes the easily implemented predictor-corrector form,

$$v_j(t+\frac{\Delta t}{2}) = v_j(t) - \frac{1}{2}\lambda f'_j,$$
 (2.16a)

$$v_{j+\frac{1}{2}}(t+\Delta t) = \frac{1}{2}[v_j(t) + v_{j+1}(t)] + \frac{1}{8}[v_j' - v_{j+1}'] - \lambda[f(v_{j+1}(t+\frac{\Delta t}{2}) - f(v_j(t+\frac{\Delta t}{2}))]. \quad (2.16b)$$

Here the numerical derivatives of both gridfunctions, $\{v_j\}$ and $\{f_j\}$, should obey the accuracy constraints (2.9b) and (2.15). In this manner the second-order accurate corrector step (2.16b), augments the first-order accurate predictor step (2.16a), and results in a highresolution second-order central difference approximation of (2.1).

<u>Remarks</u>:

1. The choice $\frac{1}{\Delta x}v'_j \equiv \frac{1}{\Delta x}f'_j \equiv 0$ in (2.16), recovers the original first-order accurate LxF scheme (2.6).

2. If instead of (2.6) we use the non-staggered version of the LxF scheme,

$$v_{j}(t + \Delta t) = \frac{1}{2} [v_{j+1}(t) + v_{j-1}(t)] - \frac{\lambda}{2} [f(v_{j+1}(t)) - f(v_{j-1}(t))], \qquad (2.17)$$

and repeat the reconstruction, evolution and projection steps described above, then the resulting high resolution central differencing approximation amounts to

$$v_j(t + \frac{\Delta t}{2}) = v_j(t) - \frac{1}{2}\lambda f'_j,$$
 (2.18a)

$$v_{j}(t+\Delta t) = \frac{1}{2} [v_{j+1}(t) + v_{j-1}(t)] + \frac{1}{4} [v_{j-1}' - v_{j+1}'] - \frac{\lambda}{2} [f(v_{j+1}(t+\frac{\Delta t}{2}) - f(v_{j-1}(t+\frac{\Delta t}{2}))]. \quad (2.18b)$$

To guarantee the desired nonoscillatory property of these approximations, the two free ingredients at our disposal – the numerical derivatives $\frac{1}{\Delta x}v'_j$ and $\frac{1}{\Delta x}f'_j$, should be carefully chosen. This issue will be discussed in the next two sections.

3. THE SCALAR PROBLEM

In this section, we are concerned with non-oscillatory high- resolution central differencing approximations of the scalar conservation law

$$\frac{\partial u}{\partial t} + \frac{\partial}{\partial x}(f(u)) = 0.$$
(3.1)

Our family of high-resolution central differencing schemes (2.16) can be rewritten in the form

$$v_{j+\frac{1}{2}}(t+\Delta t) = \frac{1}{2}[v_j(t) + v_{j+1}(t)] - \lambda[g_{j+1} - g_j], \qquad (3.2a)$$

where the so-called modified numerical flux, g_j , [18], is given by

$$g_j = f(v_j(t+\frac{\Delta t}{2})) + \frac{1}{8\lambda}v'_j, \qquad v_j(t+\frac{\Delta t}{2}) = v_j(t) - \frac{1}{2}\lambda f'_j.$$
 (3.2b)

Here, $\frac{1}{\Delta x}v'_j$ is an approximate slope at the grid point x_j ,

$$\frac{1}{\Delta x}v'_j = \frac{\partial}{\partial x}v(x=x_j,t) + O(\Delta x), \qquad (3.3a)$$

and $\frac{1}{\Delta x}f'_j$ is the numerical derivative of the gridfunction $\{f_j\}$,

$$\frac{1}{\Delta x}f'_{j} = \frac{\partial}{\partial x}f(v(x=x_{j},t)) + O(\Delta x).$$
(3.3b)

The constraints (3.3) with smooth (= Lipschitz continuous) first order perturbations on their right, guarantee the second-order accuracy of the central differencing schemes (3.2).

In order to ensure that these schemes are also non-oscillatory in the sense to be described below, our numerical derivatives, $\frac{1}{\Delta x}w'_j$, should satisfy for every gridfunction $w = \{w_j\}$,

$$0 \le w'_j \cdot sgn(\Delta v_{j\pm\frac{1}{2}}) \le Const. \cdot |MinMod\{\Delta w_{j+\frac{1}{2}}, \Delta w_{j-\frac{1}{2}}\}|.$$
(3.4a)

Here, the $MinMod\{\cdot, \cdot\}$ stands for the usual limiter,

$$MM\{x,y\} \equiv MinMod\{x,y\} = \frac{1}{2}[sgn(x) + sgn(y)] \cdot Min(|x|,|y|), \quad (3.4b)$$

and can be similarly extended to include more (than two) variables. The constraint (3.4) is required in order to guarantee the Total Variation Diminishing (TVD) property for the family of central differencing schemes (3.2). We recall that TVD is a desirable property in the current setup, for it implies no spurious oscillations in our approximate solution v(x, t), [7].

However, it is well known, e.g. [7], [18], that one cannot satisfy both the accuracy requirement, (3.3), and the TVD requirement, (3.4), at the non-sonic critical gridvalues, v_j , where $\Delta v_{j+\frac{1}{2}} \cdot \Delta v_{j-\frac{1}{2}} < 0 \neq a(v_j)$. Therefore, the second-order accuracy requirement, (3.3), must be given up at these critical gridvalues. Difference schemes with (formal) second order of accuracy at all but these critical gridvalues may be classified as having second order resolution in the sense that the local truncation error is almost everywhere $O(\Delta x)^3$, and the overall second-order accuracy does not seem to be degraded in such cases, at least in the L^1 -norm.

We shall verify the TVD property of the central differencing schemes, (3.2), with the help of

Lemma 3.1: The scheme (3.2a) is TVD, if its modified numerical flux, g_j , satisfies the following generalized CFL condition,

$$\lambda |\frac{\Delta g_{j+\frac{1}{2}}}{\Delta v_{j+\frac{1}{2}}}| \leq \frac{1}{2}, \qquad \Delta g_{j+\frac{1}{2}} \equiv g_{j+1} - g_j. \tag{3.5}$$

Indeed, by (3.2a), the difference $v_{j+\frac{1}{2}}(t + \Delta t) - v_{j-\frac{1}{2}}(t + \Delta t)$ equals

$$v_{j+\frac{1}{2}}(t+\Delta t) - v_{j-\frac{1}{2}}(t+\Delta t) = \Delta v_{j+\frac{1}{2}}(\frac{1}{2} - \lambda \frac{\Delta g_{j+\frac{1}{2}}}{\Delta v_{j+\frac{1}{2}}}) + \Delta v_{j-\frac{1}{2}}(\frac{1}{2} + \lambda \frac{\Delta g_{j-\frac{1}{2}}}{\Delta v_{j-\frac{1}{2}}}).$$

Condition (3.5) tells us that the terms inside the parenthesis are positive and TVD follows along the lines of [7],

$$TV(v(t + \Delta t)) \equiv \sum_{j} |v_{j+\frac{1}{2}}(t + \Delta t) - v_{j-\frac{1}{2}}(t + \Delta t)| \le TV(v(t)).$$
(3.6)

Equipped with lemma 3.1 we turn to

Theorem 3.2: Let the numerical derivatives $\frac{1}{\Delta x}v'_j$ and $\frac{1}{\Delta x}f'_j$ in (3.3) be chosen such that the TVD requirement (3.4) holds, say,

$$0 \le v'_j \cdot sgn(\Delta v_{j\pm\frac{1}{2}}) \le Const_v \cdot |MM\{\Delta v_{j+\frac{1}{2}}, \Delta v_{j-\frac{1}{2}}\}|, \quad Const_v \equiv \alpha,$$
(3.7a)

$$0 \le f'_{j} \cdot sgn(\Delta v_{j\pm\frac{1}{2}}) \le Const_{f} \cdot |MM\{\Delta v_{j+\frac{1}{2}}, \Delta v_{j-\frac{1}{2}}\}|.$$
(3.7b)

Assume that the following CFL condition is satisfied

$$\lambda \cdot \max_{j} |a(v_{j})| \leq \beta, \qquad \beta \equiv \lambda \frac{Const_{f}}{Const_{v}} \leq \frac{1}{2\alpha} (\sqrt{4 + 4\alpha - \alpha^{2}} - 2).$$
 (3.8)

Then the family of high-resolution central differencing schemes (3.2), (3.3) is TVD.

Proof: By (3.2b) we have:

$$\lambda \left| \frac{\Delta g_{j+\frac{1}{2}}}{\Delta v_{j+\frac{1}{2}}} \right| \leq \lambda \left| \frac{f(v_{j+1}(t+\frac{\Delta t}{2})) - f(v_{j}(t+\frac{\Delta t}{2}))}{\Delta v_{j+\frac{1}{2}}} \right| + \frac{1}{8} \cdot \left| \frac{\Delta v'_{j+\frac{1}{2}}}{\Delta v_{j+\frac{1}{2}}} \right| \leq \\ \leq \lambda \left| \frac{f(v_{j+1}(t+\frac{\Delta t}{2})) - f(v_{j}(t+\frac{\Delta t}{2}))}{v_{j+1}(t+\frac{\Delta t}{2}) - v_{j}(t+\frac{\Delta t}{2})} \right| \cdot \left| \frac{v_{j+1}(t+\frac{1}{2}\Delta t) - v_{j}(t+\frac{\Delta t}{2})}{\Delta v_{j+\frac{1}{2}}} \right| + \frac{1}{8} \left| \frac{\Delta v'_{j+\frac{1}{2}}}{\Delta v_{j+\frac{1}{2}}} \right|.$$

$$(3.9)$$

Our CFL condition (3.8) implies that the first term on the right of (3.9) does not exceed

$$\lambda \left| \frac{f(v_{j+1}(t + \frac{\Delta t}{2})) - f(v_j(t + \frac{\Delta t}{2}))}{v_{j+1}(t + \frac{\Delta t}{2}) - v_j(t + \frac{\Delta t}{2})} \right| \le \beta.$$
(3.10)

Using the midvalue $v_j(t + \frac{\Delta t}{2})$ in (3.2b), we can estimate the second term on the right of (3.9),

$$\left|\frac{v_{j+1}(t+\frac{\Delta t}{2})-v_{j}(t+\frac{\Delta t}{2})}{\Delta v_{j+\frac{1}{2}}}\right| \le 1+\frac{\lambda}{2} \left|\frac{\Delta f'_{j+\frac{1}{2}}}{\Delta v_{j+\frac{1}{2}}}\right|, \quad \Delta f'_{j+\frac{1}{2}} \equiv f'_{j+1}-f'_{j}, \quad (3.11a)$$

where in view of (3.7b) and (3.8),

$$\left|\frac{\Delta f'_{j+\frac{1}{2}}}{\Delta v_{j+\frac{1}{2}}}\right| \le \max\left(\left|\frac{f'_{j}}{\Delta v_{j+\frac{1}{2}}}\right|, \left|\frac{f'_{j+1}}{\Delta v_{j+\frac{1}{2}}}\right|\right) \le Const_{f} \le \frac{1}{\lambda}\alpha\beta.$$
(3.11b)

Finally, the TVD requirement, (3.7a), gives us an upper bound for the third term on the right of (3.9),

$$|\frac{\Delta v'_{j+\frac{1}{2}}}{\Delta v_{j+\frac{1}{2}}}| \le \max(|\frac{v'_{j}}{\Delta v_{j+\frac{1}{2}}}|, |\frac{v'_{j+1}}{\Delta v_{j+\frac{1}{2}}}|) \le \alpha.$$
(3.12)

Using (3.10), (3.11) and (3.12), we find that (3.9) boils down to the quadratic inequality

$$eta(1+rac{1}{2}lphaeta)+rac{1}{8}lpha\leqrac{1}{2},$$

whose solution yields the CFL limitation (3.8).

<u>Remarks</u>:

- 1. The values α which permit a positive solution of (3.8), $\beta > 0$, are $0 \le \alpha < 4$.
- 2. The TVD constraints (3.7) with $\alpha = 0$ yields $v'_j \equiv f'_j \equiv 0$, which recovers the staggered LxF scheme (2.6) with the corresponding CFL condition $\beta \leq \frac{1}{2}$.
- 3. The CFL restriction (3.5) is a sufficient but not necessary condition for the TVD property. In practice one may use higher values of β , up to $\beta \leq \frac{1}{2}$.
- 4. A similar analysis carried out for the non-staggered form, (2.18), yields

$$\beta \leq \frac{1}{\alpha}(\sqrt{4+4\alpha-\alpha^2}-2)$$

instead of (3.8). In practice one may use $\beta \leq 1$ in this case.

We shall now discuss a few examples of numerical derivatives, which retain both the second order resolution constraint, (3.3), and the TVD constraints, (3.7). As our first example for the numerical derivative, v'_j , we choose

$$v'_{j} = MM\{\Delta v_{j+\frac{1}{2}}, \Delta v_{j-\frac{1}{2}}\}.$$
(3.13a)

This choice may oversmear a strong "discontinuity", where the order of accuracy is less significant. A preferable second choice, which allows for a steeper slope near such discontinuities and yet retains higher accuracy in smooth regions, is given by

$$v'_{j} = MM\{\alpha \Delta v_{j+\frac{1}{2}}, \frac{1}{2}(v_{j+1} - v_{j-1}), \ \alpha \Delta v_{j-\frac{1}{2}}\}.$$
(3.13b)

The limiting parameter α can range between the values $\alpha = 1$, which corresponds to the basic MinMod limiter in (3.13a), and up to $\alpha < 4$, which is permitted by the CFL condition (3.8). Similarly, the flux numerical derivative may be chosen as

$$f'_{j} = MM\{\Delta f_{j+\frac{1}{2}}, \Delta f_{j-\frac{1}{2}}\}, \qquad (3.14a)$$

which is a special case of

$$f'_{j} = MM\{\alpha \Delta f_{j+\frac{1}{2}}, \frac{1}{2}(f_{j+1} - f_{j-1}), \alpha \Delta f_{j-\frac{1}{2}}\}.$$
(3.14b)

A simpler alternative for (3.14) is given by

$$f'_{j} = a(v_{j})v'_{j},$$
 (3.15)

where v'_j is already computed by (3.13). We observe that this choice saves half the computation time of the MinMod operation; yet, it requires the computation of the Jacobian, $A(v_j)$, when dealing with systems of conservation laws.

The numerical derivative chosen in (3.13a), (3.14a) satisfies (3.7) with $\alpha = 1$, which implies the TVD property under the CFL limitation (3.8) with $\beta = \frac{1}{2}(\sqrt{7}-2) \approx 0.32$.

The numerical derivative chosen in (3.13b), (3.14b) clearly satisfies (3.7) and consequently the TVD property, for every permissible α , $0 \le \alpha < 4$. We summarize the above by stating

Corollary 3.3: Let the numerical derivative $\frac{1}{\Delta x}v'_j$ be chosen by

$$v'_{j} = MM\{\Delta v_{j+\frac{1}{2}}, \Delta v_{j-\frac{1}{2}}\}; \qquad (3.16a)$$

let the flux numerical derivative be chosen either by

$$f'_{j} = a(v_{j})v'_{j},$$
 (3.16b)

or

$$f'_{j} = MM\{\Delta f_{j+\frac{1}{2}}, \Delta f_{j-\frac{1}{2}}\}.$$
(3.16c)

Then the family of high resolution central differencing schemes (3.2), (3.16) is TVD under the CFL condition

$$\lambda \cdot max_j |a(v_j)| \leq eta, \qquad eta = rac{1}{2}(\sqrt{7}-2) pprox 0.32.$$

Similarily we have

Corollary 3.4: Let the numerical derivative $\frac{1}{\Delta x}v'_j$ be chosen by

$$v'_{j} = MM\{2\Delta v_{j+\frac{1}{2}}, \frac{1}{2}(v_{j+1} - v_{j-1}), 2\Delta v_{j-\frac{1}{2}}\}; \qquad (3.17a)$$

let the flux numerical derivative be chosen either by

$$f'_{j} = a(v_{j})v'_{j},$$
 (3.17b)

or

$$f'_{j} = MM\{2\Delta f_{j+\frac{1}{2}}, \frac{1}{2}(f_{j+1} - f_{j-1}), 2\Delta f_{j-\frac{1}{2}}\}.$$
(3.17c)

Then the family of high resolution central differencing schemes (3.2), (3.17) is TVD, under the CFL condition,

$$\lambda \cdot max_j |a(v_j)| \leq eta, \qquad eta := rac{1}{2}(\sqrt{2}-1) pprox 0.21.$$

Remarks:

- 1. We note that the CFL limitations in Corollaries 3.3 and 3.4 are not sharp. In the first case, (3.16), where a limiter parameter $\alpha = 1$ was used, the reconstruction step is a TVD operation; replacing the exact TVD evolution operator by the midpoint rule in (2.11) together with the final averaging step is also TVD, under the CFL limitation $\beta \leq \frac{1}{2}$. Similarly, one can argue that in the second case, (3.17), where a limiter parameter $\alpha = 2$ was used, the averaging step retains the TVD property (though not necessarily the entropy condition), as long as the CFL condition $\beta \leq \frac{1}{2}$ is met. Indeed, this CFL condition was verified as the stabilitiy limitation, by the numerical experiments reported in Section 5.
- Recently, non-oscillatory schemes were constructed, such that by sacrificing the TVD property, they achieve higher (than second-order) resolution including the critical gridvalues, e.g., the UNO scheme in [12] and the ENO class of approximations in [9]. To implement such ideas within our framework, one can borrow their definition of numerical derivative. For example, instead of the TVD choices (3.4), our central differencing scheme (3.2) may be augmented by the UNO choice (here Δ²v_j ≡ v_{j+1} 2v_j + v_{j-1}),

$$v'_{j} = MM\{\Delta v_{j-\frac{1}{2}} + \frac{1}{2}MM(\Delta^{2}v_{j-1}, \Delta^{2}v_{j}), \Delta v_{j+\frac{1}{2}} - \frac{1}{2}MM(\Delta^{2}v_{j}, \Delta^{2}v_{j+1})\}.$$
 (3.18)

Theorem 3.2 and its corollaries 3.3 and 3.4 demonstrate high-resolution central differencing methods which satisfy the non-oscillatory TVD property, and hence are convergent to a limit solution u(x,t). To guarantee that this limit solution is the unique entropy solution of the scalar conservation law (3.1), we shall appeal to the following cell entropy inequality, see [10],

$$U(v_{j+\frac{1}{2}}(t+\Delta t)) \leq \frac{1}{2}[U(v_j) + U(v_{j+1})] - \lambda[G_{j+1} - G_j].$$
(3.19)

Here U(u) is a convex entropy function and $G_j \equiv G(v_{j+1}, v_j, v_{j-1})$ is the numerical entropy flux which is consistent with the corresponding differential one

$$G(u,u,u) = F(u), \quad F(u) \equiv \int^u f'(u)U'(u).$$

We recall that Lax has verified such cell entropy inequality for the LxF scheme, [14]. Following Lax, we will continuously deform v_j into v_{j+1} ,

$$v(s) = sv_j + (1-s)v_{j+1}, \quad v(0) = v_{j+1}, v(1) = v_j,$$
 (3.20a)

and in a similar manner, we will further deform v(s) into v_{j+1} ,

$$v(r,s) = rv(s) + (1-r)v_{j+1}, \quad v(0,s) = v_{j+1}, v(1,s) = v(s).$$
 (3.20b)

In the Appendix we prove

Lemma 3.5: Let g(v) be a piecewise differentiable interpolant of the gridfunction $\{g_j\}$. Then the following identity holds,

$$U(v_{j+\frac{1}{2}}(t+\Delta t)) \equiv \frac{1}{2}[U(v_{j+1})+U(v_{j})] - \lambda \int_{v_{j}}^{v_{j+1}} U'(v)g'(v)dv - R_{j+\frac{1}{2}}^{U}(g(v)). \quad (3.21)$$

Here the residual term, $R_{j+\frac{1}{2}}(g) \equiv R_{j+\frac{1}{2}}^U(g(v))$, is given by,

$$R_{j+\frac{1}{2}}^{U}(g(v)) = (\Delta v_{j+\frac{1}{2}})^{2} \int_{0}^{1} \int_{0}^{1} sU''(v(r,s)) \cdot \left[\frac{1}{2} - \lambda g'(v(r,s))\right] \cdot \left[\frac{1}{2} + \lambda g'(v(s))\right] dsdr. \quad (3.22)$$

Adding and subtracting

$$\int_{v_j}^{v_{j+1}} U'(u)f'(u)du \equiv F(v_{j+1}) - F(v_j),$$

then after integration by parts, the right hand side of (3.21) will amount to:

$$\begin{split} U(v_{j+\frac{1}{2}}(t+\Delta t)) &= \frac{1}{2} [U(v_{j+1}) + U(v_j)] - \lambda [F(v_{j+1}) - F(v_j)] - \lambda U'(v) \cdot (g(v) - f(v))|_{v_j}^{v_{j+1}} \\ &+ \lambda \int_{v_j}^{v_{j+1}} U''(v) \cdot (g(v) - f(v)) dv - R_{j+\frac{1}{2}}^U(g(v)). \end{split}$$

Consequently, the inequality

$$\lambda \int_{v_j}^{v_{j+1}} U''(v) \cdot (g(v) - f(v)) dv - R_{j+\frac{1}{2}}^U(g(v)) \le 0, \qquad (3.23)$$

provides us with a sufficient condition for the family of central differencing schemes (3.2) to satisfy the cell entropy inequality, (3.19), with numerical entropy flux $G_j = F(v_j) + U'(v_j) \cdot (g(v_j) - f(v_j))$. This brings us to

Lemma 3.6: Let g(v) be the piecewise linear interpolant of the modified flux gridfunction $\{g_j\}$,

$$g(v) = \frac{\Delta g_{j+\frac{1}{2}}}{\Delta v_{j+\frac{1}{2}}}(v-v_j) + g_j, \quad \min(v_j, v_{j+1}) \le v \le \max(v_j, v_{j+1}). \tag{3.24}$$

Assume that the central differencing schemes (S.2), satisfy the TVD constraint (consult (S.7)),

$$0 \leq v'_{j} \cdot sgn(\Delta v_{j\pm\frac{1}{2}}) \leq Const_{v} \cdot |MM\{\Delta v^{+}_{j+\frac{1}{2}}, \Delta v^{+}_{j-\frac{1}{2}}\}|, \quad Const_{v} \equiv \alpha \leq 1, \qquad (3.25a)$$

where

$$\Delta v_{j+\frac{1}{2}}^{+} \equiv \Delta v_{j+\frac{1}{2}} \cdot [1 - \lambda \cdot (\max_{x} f''(v(x)) \cdot \Delta v_{j+\frac{1}{2}})^{+}]^{+}.$$
(3.25b)

The entropy dissipative limiter in (3.25b), is introduced in order to prevent the nonexpansive entropy violating rarefactions, consult [18, Section 8].

Moreover, assume that the flux numerical derivative satisfies the TVD constraint:

$$0 \le f'_{j} \cdot sgn(\Delta v_{j\pm\frac{1}{2}}) \le Const_{f} \cdot |MM\{\Delta v_{j+\frac{1}{2}}, \Delta v_{j-\frac{1}{2}}\}|, \quad \lambda \cdot \frac{Const_{f}}{Const_{v}} \equiv \beta, \qquad (3.25c)$$

so that the CFL condition (3.8) holds.

Then the following inequality holds

$$\lambda \int_{v_j}^{v_{j+1}} (g(v) - f(v)) dv - R_{j+\frac{1}{2}}^U(g(v)) \le 0, \qquad U(u) = \frac{1}{2}u^2. \tag{3.26}$$

<u>Remarks</u>:

- 1. We observe that in the Genuinely Non-Linear (GNL) case, where, say, f'' > 0, the entropy entropy (3.25b) becomes effective only in rarefaction cells where $\Delta v_{j+\frac{1}{2}} > 0$, in agreement with [18]. It retains the second-order resolution of the central differencing schemes (3.2), except for a finite number of critical cells which contain strong rarefactions, $(\Delta v_{j+\frac{1}{2}})^+ \sim 1$, where it reduces (3.2), (3.3) to the original LxF scheme.
- 2. Lemma 3.6 applies to choices of numerical derivatives, v'_j , subject to the TVD constraint (3.7a) with $0 < \alpha \le 1$. In practice, higher values, $\alpha > 1$, can be used.

Lemma 3.6 - which is proved in the appendix, shows that our central differencing TVD schemes (3.2), (3.7) fulfill the sufficient condition (3.23) and consequently the cell entropy inequality (3.19), with respect to the quadratic entropy function $U(u) = \frac{1}{2}u^2$. Thus, the limit solution of our central TVD schemes, u(x, t), satisfies

$$rac{\partial}{\partial t}(rac{1}{2}u^2)+rac{\partial}{\partial x}(F(u))\leq 0, \quad F(u)=\int^u uf'(u)du.$$

This singles out u(x,t) as the unique entropy solution of (3.1), at least in the GNL case [2]. We have shown

Theorem 3.7: Consider the GNL scalar conservation law (3.1). It is approximated by the family of high resolution central differencing schemes (3.2), (3.3) which satisfy the TVD and entropy constraints, (3.25). Then, if the CFL condition (3.8) holds, we have:

- 1. Second-order resolution;
- 2. Total Variation Diminishing property;
- 3. A consistent quadratic cell-entropy inequality;

and, as a consequence of 2. and 3.:

4. the corresponding central differencing schemes converge to the unique physically relevant solution of the GNL conservation law (3.1).

We shall close this section with some scalar numerical examples. We consider the approximate solution of the inviscid Burger's equation

$$u_t + (\frac{1}{2}u^2)_x = 0. ag{3.27}$$

using several of the previously mentioned central differencing schemes. They include:

- 1. The first-order LxF scheme in its non-staggered form (2.17).
- The second-order non-oscillatory central differencing scheme (2.18), (3.13a), (3.15). This is the ordinary <u>non-staggered</u> version of our central differencing which will be referred to as ORD.
- 3. The second-order non-oscillatory central differencing scheme (3.2), (3.13a), (3.15). This is the <u>staggered</u> version of our central differencing which will be referred to as STG.

Equation (3.27) is solved with two sets of initial conditions. In the first case, we have the smooth 1-periodic initial data,

$$u(x,0) = sin(\pi x);$$
 (3.28a)

in the second case we consider the Rieman initial data:

$$u(x,0) = \begin{cases} 1 & x < 0 \\ 0 & x \ge 0 \end{cases}.$$
 (3.28b)

The well known solution of (3.27), (3.28a), e.g. [15], develops a shock discontinuity at $t_c \approx 0.31$. Table 3.1 shows us the L_1 norm of the errors at the pre-shock time t = 0.15. It indicates the first order accuracy of the LxF scheme in contrast to the second order accuracy of our central differencing, ORD and STG.

Next, in Table 3.2 we recorded the same L_1 errors at the post-shock time t = 0.4. The presence of a shock discontinuity reduces the global L_1 error to first order. However, the

central differencing STG scheme performs somewhat better than the central differencing ORD scheme and they both have better resolution than the first-order LxF scheme in shock-free zones.

This behavior is amplified in the second case of solving the Rieman problem (3.27), (3.28b), see table 3.3 and Fig. 3.1. Once more, we observe that the STG scheme has somewhat better resolution then its non-staggered counterpart ORD. Yet, the CFL limitation in the non-staggered form, $\beta < 1$, results in a better time preformance than the STG scheme which is subject to the CFL limitation $\beta < \frac{1}{2}$. In either case, these easily implemented non-oscillatory central differencing outperform the first-order LxF one.

Rel.	STG	Rel.	ORD	Rel.	$\mathbf{L}\mathbf{x}\mathbf{F}$	NX
	.000859		.002620		.023702	40
3.70	000000	3.92	000005	1.93		
3.80	.000232	3.94	.000667	1 96	.012249	80
	.000061		.000169	1.50	.006246	160
3.81		3.93		1.97		
	.000016		.000043		.003158	320

<u>Table 3.1</u>: L_1 norm of the errors, Burger Equation, $u(x,0) = \sin(\pi x)$, t = 0.15.

<u>Table 3.2</u>: L_1 norm of the errors, Burger Equation, $u(x,0) = \sin(\pi x)$, t = 0.4.

Rel.	STG	Rel.	ORD	Rel.	\mathbf{LxF}	NX
	.000849		.003612		.044449	40
3.06		2.79		1.89		10
0 00	.000277	0.50	.001291		.023486	80
2.02	.000098	2.59	000498	2.06	011202	160
2.57		2.38	.000430	2.17	.011363	160
	.000038		.000209		.005235	320

<u>Table 3.3</u>: L_1 norm of the errors, Burger Equation, u(x, 0) given in (3.28b), t = 0.3.

Rel.	STG	Rel.	ORD	Rel.	$\mathbf{L}\mathbf{x}\mathbf{F}$	NX
1.00	.010921	1.00	.014044		.021956	50
1.99	.005461	1.99	.007027	1.94	.011315	100
2.00	.002730	2.00	.003513	1.99	.005685	200
2.14	.001274	2.00	.001756	1.99	.002843	400

ORIGINAL PAGE IS OF POOR QUALITY



4. SYSTEMS OF CONSERVATION LAWS

In this section, we describe how to extend our scalar family of central differencing schemes to the one-dimensional system of conservation laws,

1 (•

$$\frac{\partial u}{\partial t} + \frac{\partial}{\partial x}(f(u)) = 0. \tag{4.1}$$

Here u(x,t) is the unknown N-vector of the form

$$u=(u_1(x,t),u_2(x,t),\ldots,u_N(x,t))^T,$$

and f(u) is the flux vector,

$$f(u) = (f_1(u), f_2(u), \ldots, f_N(u))^T,$$

with an $N \times N$ Jacobian matrix,

$$A_{pq}(u_1,\ldots,u_N) = \left(rac{\partial f_p}{\partial u_q}
ight) \quad p,q=1,\ldots,N.$$

Our approximate solution at the gridpoint x_j is given by the N-vector

$$v_j = (v_{j,1}, v_{j,2}, \ldots, v_{j,N})^T,$$

and the corresponding vector of differences, $\Delta v_{j+\frac{1}{2}} = v_{j+1} - v_j$, consists of N-components denoted by $\Delta v_{j+\frac{1}{2},k} = v_{j+1,k} - v_{j,k}$.

Equipped with these notations, our family of high-resolution central differencing schemes (3.2), (3.3), takes the form,

$$v_{j+\frac{1}{2}}(t+\Delta t) = \frac{1}{2}[v_j(t)+v_{j+1}(t)] - \lambda[g_{j+1}-g_j], \qquad (4.2a)$$

where the modified numerical flux, g_j , is given by

$$g_j = f(v_j(t + \frac{\Delta t}{2})) + \frac{1}{8\lambda}v'_j, \quad v_j(t + \frac{\Delta t}{2}) = v_j(t) - \frac{1}{2}\lambda f'_j.$$
 (4.2b)

As before, the computation of g_j and $v_j(t + \frac{\Delta t}{2})$ requires the numerical derivatives of the gridfunctions $\{v_j\}$ and $\{f_j\}$. This time we have to choose two N-vectors of numerical derivatives,

$$\frac{1}{\Delta x}v'_{j} = (v'_{j,1}, v'_{j,2}, \cdots, v'_{j,N})^{T}, \qquad (4.3a)$$

$$\frac{1}{\Delta x}f'_{j} = (f'_{j,1}, f'_{j,2}, \cdots, f'_{j,N})^{T}.$$
(4.3b)

In the rest of this section, we shall describe the pros and cons of several choices for these vectors of numerical derivatives.

Our first choice is a component-wise extension of the scalar definition in Section 3. To this end we may use either (4.4a),

$$v'_{j,k} = MM\{\Delta v_{j+\frac{1}{2},k}, \Delta v_{j-\frac{1}{2},k}\}, \quad k = 1, \dots, N,$$
(4.4a)

or the more general (4.4b),

$$v_{j,k}' = MM\{\alpha \Delta v_{j+\frac{1}{2},k}, \frac{1}{2}(v_{j+1,k} - v_{j-1,k}), \ \alpha \Delta v_{j-\frac{1}{2},k}\}, \quad k = 1, \dots, N,$$
(4.4b)

or instead, use the UNO-like numerical derivative in (3.18),

$$v'_{j,k} = MM\{ \Delta v_{j-\frac{1}{2},k} + \frac{1}{2}MM(\Delta^2 v_{j-1,k},\Delta^2 v_{j,k}),$$

$$\Delta v_{j+\frac{1}{2},k} - \frac{1}{2}MM(\Delta^2 v_{j,k},\Delta^2 v_{j+1,k})\}, \quad k = 1, \dots, N.$$
(4.4c)

A possible choice for the vector of numerical flux derivative may be

$$f'_j = A(v_j)v'_j. \tag{4.5}$$

1. -

This approach involves multiplication of the Jacobian matrix by the vector of derivatives, v'_j . This multiplication may be avoided if we use a component-wise definition for the vector of numerical flux derivatives, f_j , in analogy to (3.14). For example, we may use (4.6a)

$$f'_{j,k} = MM\{\Delta f_{j+\frac{1}{2},k}, \ \Delta f_{j-\frac{1}{2},k}\}$$
(4.04)

or alternatively,

$$f'_{j,k} = MM\{\alpha \Delta f_{j+\frac{1}{2},k}, \frac{1}{2}(f_{j+1,k} - f_{j-1,k}), \alpha \Delta f_{j-\frac{1}{2},k}\}$$
(4.6b)

We observe that the Jacobian Free Form (JFF), (4.4), (4.6) avoids the use of the Jacobian matrix A(v) required by (4.4), (4.5), at the expense of carrying out the MinMod operation

twice. The resulting central differencing schemes, (4.2), which are based upon the componentwise definition of the numerical derivatives in (4.4)-(4.6), share the simplicity of the scalar framework. Namely, no Riemann problems are solved and consequently characteristic decompositions-required in order to distinguish between the left and rightgoing waves inside the Riemann fan, are avoided. At the same time, our central differencing approach is flexible enough so that it enables us to incorporate characteristic information, whenever available, in order to achieve improved resolution.

available, in order to accure the provided of the numerical derivatives. To this end we shall employ a Roe Matrix, definition of the numerical derivatives. To this end we shall employ a Roe Matrix, $\hat{A}_{j+\frac{1}{2}} = A(v_j, v_{j+1})$, namely, an averaged Jacobian, $\hat{A}_{j+\frac{1}{2}}$, satisfying, e.g. [11], [19], $f(v_{j+1}) - f(v_j) = \hat{A}_{j+\frac{1}{2}} \cdot (v_{j+1} - v_j)$, (4.7) and having complete real eigensystem $\{\hat{a}_{j+\frac{1}{2},k}, \hat{R}_{j+\frac{1}{2},k}\}, k = 1, ..., N$. Let us project the vector of differences $\Delta v_{j+\frac{1}{2}}$ onto $\{\hat{R}_{j+\frac{1}{2}}\}$, i.e. we use the characteristic decomposition

$$\Delta v_{j+\frac{1}{2}} = \sum_{k} \hat{\alpha}_{j+\frac{1}{2},k} \cdot \hat{R}_{j+\frac{1}{2},k}, \quad k = 1, \dots, N, \qquad (4.8a)$$

where

$$\hat{\alpha}_{j+\frac{1}{2},k} = \hat{L}_{j+\frac{1}{2},k} \cdot \Delta v_{j+\frac{1}{2}}, \quad \hat{L}_j \cdot \hat{R}_j = \delta_{ij}, \quad k = 1, \dots, N.$$
(4.8b)

Then the corresponding projection of the flux vector of differences is given by

$$\Delta f_{j+\frac{1}{2}} = \sum_{k} \hat{\alpha}_{j+\frac{1}{2},k} \hat{a}_{j+\frac{1}{2},k} \hat{R}_{j+\frac{1}{2},k}.$$
(4.9)

Now, a possible characteristic-wise choice for the numerical derivatives in analogy with (4.4), may be (here $\hat{R}_{j,k}$ is denotes the averaged eigenvector centered at $x = x_j$),

$$v'_{j,k} = \sum_{k} MM\{\hat{\alpha}_{j+\frac{1}{2},k}, \hat{\alpha}_{j-\frac{1}{2},k}\}\hat{R}_{j,k}, \qquad (4.10)$$

and the numerical flux derivatives can be calculated as

$$f'_{j} = \hat{A}_{j+\frac{1}{2}}v'_{j}. \tag{4.11}$$

Once again we can use the JFF and avoid the multiplication of Roe's matrix by the vector of numerical derivatives, if instead of (4.11) we employ, consult (4.9),

$$f'_{j,k} = \sum_{k} MM\{\hat{\alpha}_{j+\frac{1}{2},k}\hat{a}_{j+\frac{1}{2},k}, \hat{\alpha}_{j-\frac{1}{2},k}\hat{a}_{j-\frac{1}{2},k}\}\hat{R}_{j,k}.$$
(4.12)

As an example, let us consider the Euler equations,

$$\frac{\partial}{\partial t} \begin{bmatrix} \rho \\ m \\ E \end{bmatrix} + \frac{\partial}{\partial x} \begin{bmatrix} m \\ \rho u^2 \\ u(E+p) \end{bmatrix} = 0, \quad p = (\gamma - 1) \cdot (E - \frac{1}{2}\rho u^2). \tag{4.13}$$

Here $\rho, u, m = \rho u, p$ and E are respectively the density, velocity, momentum, pressure and total energy. The corresponding Roe matrix, $\hat{A}(v_j, v_{j+1})$, is associated with the eigensystem $\{\hat{a}_{j+\frac{1}{2},k}, \hat{R}_{j+\frac{1}{2},k}\}$, where the eigenvalues $\hat{a}_{j+\frac{1}{2},k}$ are given by

$$\hat{a}_{j+\frac{1}{2},1} = \hat{u}_{j+\frac{1}{2}} - \hat{c}_{j+\frac{1}{2}}, \quad \hat{a}_{j+\frac{1}{2},2} = \hat{u}_{j+\frac{1}{2}}, \quad \hat{a}_{j+\frac{1}{2},3} = \hat{u}_{j+\frac{1}{2}} + \hat{c}_{j+\frac{1}{2}}, \quad (4.14)$$

and the right eigenvectors are given by

$$\hat{R}_{j+\frac{1}{2},1} = \begin{bmatrix} 1\\ \hat{u} - \hat{c}\\ \hat{H} - \hat{u}\hat{c} \end{bmatrix}_{j+\frac{1}{2}} \hat{R}_{j+\frac{1}{2},2} = \begin{bmatrix} 1\\ \hat{u}\\ \frac{1}{2}\hat{u}^2 \end{bmatrix}_{j+\frac{1}{2}} \hat{R}_{j+\frac{1}{2},3} = \begin{bmatrix} 1\\ \hat{u} + \hat{c}\\ \hat{H} + \hat{u}\hat{c} \end{bmatrix}_{j+\frac{1}{2}}.$$
 (4.15)

The average quantities on the right of (4.14)-(4.15) given in [19] are,

$$\hat{u} = \frac{\langle \sqrt{\rho}u \rangle}{\langle \sqrt{\rho} \rangle}, \ \hat{H} = \frac{\langle \sqrt{\rho}H \rangle}{\langle \sqrt{\rho} \rangle}, \ \hat{c} = \sqrt{(\gamma - 1)(\hat{H} - \frac{1}{2}\hat{u}^2)}, \quad H_j = \frac{E_j + p_j}{\rho_j},$$
 (4.16)

where $\langle w \rangle = \frac{1}{2}(w_j + w_{j+1})$ denotes the usual arithmetic mean. This brings us to the characteristic decomposition (4.8), where the characteristic projections,

$$\hat{\alpha}_{j+\frac{1}{2},1} = \frac{1}{2}(\eta_1 - \eta_2), \quad \hat{\alpha}_{j+\frac{1}{2},2} = \hat{\rho}_{j+\frac{1}{2}} - \eta_1, \quad \hat{\alpha}_{j+\frac{1}{2},3} = \frac{1}{2}(\eta_1 + \eta_2), \quad (4.17a)$$

are expressed in terms of η_1, η_2 , which are given by

$$\eta_{1} = (\gamma - 1) \cdot (\hat{E}_{j + \frac{1}{2}} + \frac{1}{2} \hat{\rho}_{j + \frac{1}{2}} \hat{u}_{j + \frac{1}{2}}^{2} - \hat{u}_{j + \frac{1}{2}} \hat{m}_{j + \frac{1}{2}}) / \hat{c}_{j + \frac{1}{2}}^{2}, \qquad (4.17b)$$

$$\eta_2 = (\hat{m}_{j+\frac{1}{2}} - \hat{\rho}_{j+\frac{1}{2}} \hat{u}_{j+\frac{1}{2}}) / \hat{c}_{j+\frac{1}{2}}.$$
(4.17c)

We note that the second contact field associated with $\hat{R}_{j+\frac{1}{2},2}$ is independent of the square root which is required only in the computation of the mean value sound speed $\hat{c}_{j+\frac{1}{2}}$. Since this field is a linearly degenerate, it lacks the strong entropy enforcement typical to the other two genuinely non-linear field, and therefore, is usually smeared by numerical schemes. In our next choice of numerical derivatives, we incorporate only partial characteristic information. Namely, we isolate the less expensive (i.e., square root-free) characteristic projection on the contact field, and use the component-wise approach for the other two fields.

Thus, we first separate the contact field,

$$\begin{bmatrix} \Delta \tilde{\rho}_{j+\frac{1}{2}} \\ \Delta \tilde{m}_{j+\frac{1}{2}} \\ \Delta \tilde{E}_{j+\frac{1}{2}} \end{bmatrix} \equiv \begin{bmatrix} \Delta \rho_{j+\frac{1}{2}} \\ \Delta m_{j+\frac{1}{2}} \\ \Delta E_{j+\frac{1}{2}} \end{bmatrix} - \hat{\alpha}_{j+\frac{1}{2},2} \cdot \begin{bmatrix} 1 \\ \hat{u} \\ \frac{1}{2} \hat{u}^2 \end{bmatrix}_{j+\frac{1}{2}}, \qquad (4.18)$$

and then define the vector of numerical derivative as

$$\begin{bmatrix} \rho'_{j} \\ m'_{j} \\ E'_{j} \end{bmatrix} = MM\{\hat{\alpha}_{j+\frac{1}{2},2}, \hat{\alpha}_{j-\frac{1}{2}}\} \cdot \begin{bmatrix} 1 \\ <\hat{u} > \\ <\frac{1}{2}\hat{u}^{2} > \end{bmatrix}_{j} - MM\begin{bmatrix} \Delta\rho_{j+\frac{1}{2}}, \Delta\rho_{j-\frac{1}{2}} \\ \Delta\tilde{m}_{j+\frac{1}{2}}, \Delta\tilde{m}_{j-\frac{1}{2}} \\ \Delta\tilde{E}_{j+\frac{1}{2}}, \Delta\tilde{E}_{j-\frac{1}{2}} \end{bmatrix}.$$
(4.19)

Similarly, computing the numerical flux derivative with a characteristic approach applied only to the isolated contact wave,

$$\begin{bmatrix} \Delta \tilde{f}_{j+\frac{1}{2},1} \\ \Delta \tilde{f}_{j+\frac{1}{2},2} \\ \Delta \tilde{f}_{j+\frac{1}{2},3} \end{bmatrix} \equiv \begin{bmatrix} \Delta f_{j+\frac{1}{2},1} \\ \Delta f_{j+\frac{1}{2},2} \\ \Delta f_{j+\frac{1}{2},3} \end{bmatrix} - \hat{\alpha}_{j+\frac{1}{2},2} \cdot \hat{a}_{j+\frac{1}{2},2} \cdot \begin{bmatrix} 1 \\ \hat{u} \\ \frac{1}{2} \hat{u}^2 \end{bmatrix}_{j+\frac{1}{2}}, \qquad (4.20)$$

amounts to

$$\begin{bmatrix} f'_{j,1} \\ f'_{j,2} \\ f'_{j,3} \end{bmatrix} = MM(\hat{\alpha}_{j+\frac{1}{2},2}\hat{a}_{j+\frac{1}{2},2}, \hat{\alpha}_{j-\frac{1}{2},2}\hat{a}_{j-\frac{1}{2},2}) \cdot \begin{bmatrix} 1 \\ <\hat{u} > \\ <\frac{1}{2}\hat{u}^2 > \end{bmatrix}_{j} - MM\begin{bmatrix} \Delta \tilde{f}_{j+\frac{1}{2},1}, \Delta \tilde{f}_{j-\frac{1}{2},1} \\ \Delta \tilde{f}_{j+\frac{1}{2},2}, \Delta \tilde{f}_{j-\frac{1}{2},2} \\ \Delta \tilde{f}_{j+\frac{1}{2},3}, \Delta \tilde{f}_{j-\frac{1}{2},3} \end{bmatrix}.$$

$$(4.21)$$

The latter approach enables us to use effectively the Artificial Compression Method (ACM) on the isolated contact field, e.g. [6], [7]. To this end, the contact wave isolated in (4.19) is modified by

$$\begin{bmatrix} \rho'_{j} \\ m'_{j} \\ E'_{j} \end{bmatrix} = \begin{bmatrix} MM\{\hat{\alpha}_{j+\frac{1}{2},2}, \hat{\alpha}_{j-\frac{1}{2},2}\} + \theta_{j}r_{j} \end{bmatrix} \cdot \begin{bmatrix} 1 \\ \hat{u} \\ \frac{1}{2}\hat{u}^{2} \end{bmatrix}_{j} - MM\begin{bmatrix} \Delta \tilde{\rho}_{j+\frac{1}{2}}, \Delta \tilde{\rho}_{j-\frac{1}{2}} \\ \Delta \tilde{m}_{j+\frac{1}{2}}, \Delta \tilde{m}_{j-\frac{1}{2}} \\ \Delta \tilde{E}_{j+\frac{1}{2}}, \Delta \tilde{E}_{j-\frac{1}{2}} \end{bmatrix}, \quad (4.22a)$$

where θ_j and r_j are given by

$$\theta_{j} = \frac{|\hat{\alpha}_{j+\frac{1}{2},2} - \hat{\alpha}_{j-\frac{1}{2},2}|}{|\hat{\alpha}_{j+\frac{1}{2},2}| + |\hat{\alpha}_{j-\frac{1}{2},2}|}, \qquad (4.22b)$$

$$r_{j} = MM\left\{\frac{1}{2}(1-\lambda\hat{u}_{j+\frac{1}{2}})^{2}\cdot\hat{\alpha}_{j+\frac{1}{2},2}, \frac{1}{2}(1-\lambda\hat{u}_{j-\frac{1}{2}})^{2}\cdot\hat{\alpha}_{j-\frac{1}{2},2}\right\}.$$
(4.22c)

Finally, we shall mention an alternative approach to the characteristic implementation of the ACM in (4.22). To this end, the Artificial Compression is implemented as a further corrector step to the component-wise approach presented in (4.2a)-(4.2b). This corrective type ACM takes the form,

$$v_{j}^{*}(t + \Delta t) = v_{j}(t + \Delta t) - \epsilon (W_{j+\frac{1}{2}} - W_{j-\frac{1}{2}}), \quad 0 \le \epsilon \le 1.$$
 (4.23a)

Here, the compression coefficient, ϵ , and W_j are given by

$$W_{j+\frac{1}{2}} = \begin{cases} w_{j}, & \Delta w_{j+\frac{1}{2}} \cdot \Delta v_{j+\frac{1}{2}} > 0, \\ & & \\ &$$

where v_{RL} is related to subcell resolution information (Harten, private communication, [8]),

$$v_{RL} = |v_{j+1}(t+\Delta t) - v_{j-1}(t+\Delta t) - \Delta x_{j+\frac{1}{2}}(\delta_{j+1}+\delta_{j-1})|, \ \delta_j = MM\{\Delta v_{j-\frac{1}{2}}, \Delta v_{j+\frac{1}{2}}\}. \ (4.23c)$$

The result is the central differencing scheme (4.2), appended by the component-wise definitions of numerical derivatives in (4.10) - (4.12), and complemented by the ACM

corrector step (4.23). This scheme, unlike the characteristic-wise implementation of the ACM in (4.22), enjoys the simplicity of the component-wise approach, and at the same time, enables us to deal effectively with the delicate contact wave. We remark that one should be careful not to overcompress discontinuities using such corrective type Artificial Compression: it should be implemented after the rarefaction waves have evolved using an appropriately chosen compression coefficient ϵ .

5. NUMERICAL EXAMPLES

In this section, we will present numerical examples which demonstrate the performance of our family of high resolution central differencing schemes for systems of conservation laws. We consider the approximate solution of the Euler equations of gasdynamics, see section 4,

$$\frac{\partial}{\partial t} \begin{bmatrix} \rho \\ m \\ E \end{bmatrix} + \frac{\partial}{\partial x} \begin{bmatrix} m \\ \rho u^2 \\ u(E+p) \end{bmatrix} = 0, \quad p = (\gamma - 1) \cdot (E - \frac{1}{2}\rho u^2), \quad m = \rho u. \tag{5.1}$$

We experiment with the following members from our family of high- resolution central differencing schemes:

- 1. The central differencing scheme (4.2), (4.4a), (4.5). This is the component-wise extension of the scalar STG scheme presented in Section 3 and is therefore referred to by the same abbreviation.
- 2. The central differencing scheme (4.2), (4.4b), (4.5) with a limiter value $\alpha = 2$. This scheme is referred to as STG2.
- 3. The component-wise UNO-type version of our scheme, (4.2), (4.4c), (4.5). It is referred to as STGU.
- 4. The scheme STG with the addition of the corrective type ACM described by (4.23) is referred to as STGC.

All the above examples use component-wise definitions for the vectors of numerical derivatives, and are based on the staggered grid formulation. Our last example is based on non-staggered LxF scheme, namely,

5. The central differencing scheme (2.18), (4.4a), (4.5). This is the component-wise extension of the scalar ORD scheme presented in section 3 and is therefore referred to by the same abbreviation.

For the purpose of performance comparison we include here the results of several well known upwind and central schemes as well. These schemes include:

- 1. The first order central non-staggered LxF scheme, (2.17), [13].
- 2. The first order accurate Godunov-type scheme of Roe, e.g. [7].
- 3. Harten's second order accurate upwind ULT1 scheme, [7].
- 4. Harten's second order accurate upwind ULT1C scheme, [7], where Artificial Compression is added to ULT1 in the linearily degenerate contact field. It is referred to as ULTC.

We solve the system (5.1) with three sets of initial conditions. Our first example is the Riemann problem proposed by Sod [21] (abbreviated hereafter as RIM1), which consists of initial data

$$v(x,0) = \begin{cases} v_{\ell}, & x < 0, \quad v_{\ell} = (1,0,2.5)^{T} \\ v_{r}, & x > 0, \quad v_{r} = (0.125,0,0.25)^{T}. \end{cases}$$
(5.2)

Table 5.1 shows the L_1 norm of the errors. Though the results are field dependent, the "quantitative picture" is favourable with the central differencing schemes. Table 5.2 shows the time performance of the various schemes. All the schemes have time performances of order $O(NX)^2$, where NX is the number of spatial cells. Figures 5.1-5.4 include a comparison between the numerical solution and the exact solution (shown by the solid line), e.g. [3], [20], at t = 0.1644. As expected, the overall resolution of the first order schemes is outperformed by the second order schemes.

We observe that our second order staggered schemes, STG, STG2, and STGU, and similarily, the second order upwind ULT1 scheme, smear the shock discontinuity over two cells. The contact discontinuity, however, is more delicate: here we observe smearing of about 5-6 cells by the second order schemes, both in the central and upwind cases. We can also observe the over- and undershoots generated by both the upwind ULT1 and central ORD. These unsatisfactory results suggest to introduce ACM in the contact field. For this purpose we present the upwind ULTC scheme and the central component-wise STGC scheme in Fig. 5.4. We note that the ACM is applied in STGC only at the last 10% of the time steps with the compression coefficient $\varepsilon = 0.625$. This results in 2 cells resolution of the contact wave, and somewhat better resolution in the other waves as well. Yet, small over- and undershoots which are due to overcompression, still remain.

Our second Riemann test problem (abbreviated hereafter as RIM2), is the one proposed by Lax [5]. It is initiated with,

$$v_{\ell} = (0.445, 0.311, 8.928)^T, \quad v_r = (0.5, 0, 1.4275)^T,$$
(5.3)

and the results at t = 0.16 can be found in Fig. 5.5 - 5.8. The density profile in RIM2 lacks the monotonicity we had in RIM1, and therefore, it is more difficult for "non-oscillatory" numerical schemes to recover the contact wave and the intermediate "plateau" which follows. Consequently, the upwind schemes perform here somewhat better than the central schemes: ULTC resolution is better than STGC which has more over- and undershoots than before. We note that STG2 has better resolution and L_1 errors than STGU in all fields. This is due to the fact that STG2 has steeper slope near discontinuities, consult Section 2.

Finally, the results of the nonstaggered central difference scheme ORD for both RIM1 and RIM2 problems are presented in Figure 5.9. We recall that the CFL limitation in the staggered case, $\beta < \frac{1}{2}$, is now doubled to be $\beta < 1$, consult Section 3. Moreover, a component-wise reconstruction of the vector of numerical derivatives, enabled us to avoid any Riemann solver in this nonstaggered case. Consequently, the ORD scheme is twice faster than the staggered central versions based on STG, as well as the upwind scheme ULT1 which necessitates the (approximate) solution of a Riemann problem at each cell. However, the resolution of this nonstaggered version, ORD, deteriorates, when compared to the staggered versions and the upwind methods.

Our third problem, discussed by Woodward-Collela in [25], consists of initial-data,

$$u(x,0) = \begin{cases} v_{\ell} & 0 \le x < 0.1, \\ v_{m} & 0.1 \le x < 0.9, \\ v_{r} & 0.9 \le x < 1, \end{cases}$$
(5.4)

where $\rho_{\ell} = \rho_m = \rho_r = 1$, $m_l = m_m = m_r = 0$, $p_{\ell} = 100$, $p_m = 0.01$, $p_r = 100$. A solid wall boundary conditions (reflection) is applied to both ends. The results are compared with the fourth order ENO scheme [9], in Fig. 5.10-5.12.² The continous line is the result of the ENO scheme with 800 cells. We present the results of STG2 and ULT1 with 400 cells in Fig. 5.13-5.15 at t = 0.01, t = 0.03, and t = 0.038 respectively. We observe that the upgrade from the first order LxF scheme to the second order STG2, results in a substantial improvement of resolution, see Fig. 5.10-5.15; moreover, STG2 compares favourably with the second order upwind ULT1 scheme.

In summary, we may conclude that when strong discontinuities are present, STG2 seems to offer the best results, STGC can be tuned to obtain sharp resolution at the expense of overcompression, and ORD version was found to be the most economical. Further extensive numerical experiments done along these lines are reported in [16].

²We thank A. Harten for allowing us to use his ENO results in [9].

	ULT1/C	STG	ROE	ORD	\mathbf{LxF}	STGC	STGU	STG2	NX
RIM1								<u></u>	<u>IIA</u>
	1.23	1.23	0.74	0.69	0.22	1.43	1.47	1 37	50
	4.93	4.75	2.92	2.71	0.85	5.67	5.88	5 42	100
	19.81	19.32	11.68	10.71	3 37	22 74	0.00	01.40	100
				10111	0.01	22.14	23.49	21.66	200
RIM2									
	2.87	2.74	1.72	1.55	0.48	3 94	2 25	2.07	
	11.54	10.02	6 00	0.10	1.00	0.24	3.35	3.07	50
	40.04	10.39	0.03	0.10	1.90	12.88	13.30	12.22	100
	46.34	43.50	27.27	24.40	7.52	51.46	53.20	48.83	200

<u>Table 5.1</u>: Computation time of Riemann problems, results at t = 1.0.

<u>Remarks</u>:

- 1. Due to our method of implementation, ULT1 and ULTC have the same computation time. In fact ULT1 is somewhat faster then ULTC.
- 2. All the above schemes use a CFL number of 0.95, except for the versions, STG*, which use a CFL number of 0.475.

Density					Velocity		Pressure		
Nv	50	100	200	50	100	200	50	100	200
				<u> </u>					
Scheme			Riema	an Probl	em - RIN	11, t = 0	.1644		
LvF	03121	.02460	.01769	.06651	.04583	.02814	.03602	.02458	.01582
DAL	010121	01308	.00836	.03224	.02090	.01145	.01762	.01109	.00666
ADD	01868	01026	00578	.03315	.01807	.00959	.01630	.00861	.00460
OND STC	.01800	00741	00409	.02812	.01105	.00550	.01232	.00581	.00294
	.01430	00806	00437	.02933	.01177	.00820	.01285	.00736	.00362
	.01330	00610	00207	02449	.01132	.00494	.01019	.00487	.00228
SIGZ	.01241	.00019	00231	02300	00816	.00403	.00961	.00432	<u>.00216</u>
STGU	<u>.01146</u>	.00544	.00291	01004	00491	00276	00705	00270	.00153
STGC	<u>.00982</u>	<u>.00322</u>	<u>.00172</u>	.01994	.00461	.00210	01002	00735	00362
ULTC	.01269	.00715	.00361	.02923	.01761	.00804	.01283	.00733	.00302

<u>Table 5.2</u>: Riemann problems, L_1 norm errors.

Rieman Problem - RIM2, t = 0.16

T v F	12162	09044	.06165	.13523	.09294	.05557	.15860	.10767	.06537
DAF	.12102	04334	02827	07397	.04144	.02192	.08399	.04826	.02655
RUL	.00030	.04004	02021	07158	03623	.01709	.07836	.04056	.01995
ORD	.06791	.03024	.02251	.07100	02/16	01307	05118	.02669	.01426
STG	.04972	.02903	.01/70	.04392	.02410	01004	06075	02841	01206
ULT1	.04518	.03572	.01477	.05570	.02603	.01094	00010	02011	00088
STG2	.03473	.02129	.01151	.03369	<u>.01655</u>	.00849	.03930	.02037	01101
STGU	.03668	.02152	.01302	<u>.03323</u>	.01657	.01046	<u>.03907</u>	.02031	.01121
STGC	.02764	<u>.01291</u>	<u>.00647</u>	<u>.02285</u>	<u>.01356</u>	<u>.00836</u>	<u>.02355</u>	<u>.01409</u>	.00873
ULTC	.03001	.01566	.00872	.05504	.02545	.01074	.05997	.02784	.01183
· · · ·									

<u>Remarks</u>:

- 1. All the above schemes use CFL number of 0.95, except for the staggered versions, STG*, which use a CFL number of 0.475.
- 2. The underlined results indicate the smallest L_1 norm errors in every column.





Fig. 5-2



32

*1 I







Fig. 5-6



Fig. 5-7

ORIGINAL PAGE IS OF POOR QUALITY DENSITY DENSITY RIM2 BY STCC 200 RIM2 BY ULIC 200 ſ VE1 OC I 1 Y VELOCITY RIM2 BY 0.10200 RIM2 BY STOC 200 ٠ PRESSURE PRESSURE ---!a -RIM2 BY STCC 200 RIM2 BY ULTE 200







Fig. 5-10







•

I₽



Fig. 5-13

ORIGINAL PAGE IS OF POOR QUALITY



Fig. 5-14



ORIGINAL PAGE IS OF POOR QUALITY

APPENDIX: ON A CELL ENTROPY INEQUALITY

In this section, we provide the promised proofs for Lemmatta 3.7 and 3.8, which verify the cell entropy inequality for our scalar family of high-resolution central difference methods.

We begin with a proof of Lemma 3.7.

Let $R_{j+\frac{1}{2}}(g)$ denote the difference,

$$R_{j+\frac{1}{2}}(g) = \frac{1}{2}[U_{(v_{j+1})} + U_{(v_j)}] - \lambda \int_{v_j}^{v_{j+1}} U'(v)g'(v)dv - U(v_{j+\frac{1}{2}}(t+\Delta t))). \tag{A.1}$$

We now continuously deform $v_j(s) \equiv v(s) = sv_j + (1-s)v_{j+1}$, between $v_j = v(0)$ and $v_{j+1} = v(1)$, see (3.20a). With this in mind, $R_{j+\frac{1}{2}}(g)$ may be rewritten in the form

$$R_{j+\frac{1}{2}}(g) = \int_0^1 \frac{d}{ds} [RHS] ds.$$
 (A.2)

From (3.2a) we may find the dependence of $v_{j+\frac{1}{2}}(t + \Delta t)$ on the continuation parameter s (for simplicity we omit the explicit dependence on time):

$$v_{j+\frac{1}{2}}(s) = \frac{1}{2}[v(s) + v_{j+1}] - \lambda[g_{j+1} - g(v(s))], \qquad (A.3)$$

which in view of

$$\frac{d}{ds}v(s) = -\Delta v_{j+\frac{1}{2}},\tag{A.4}$$

yields

$$\frac{d}{ds}U(v_{j+\frac{1}{2}}(s)) = -U'(v_{j+\frac{1}{2}}(s))[\frac{1}{2} + \lambda g'(v(s))] \cdot \Delta v_{j+\frac{1}{2}}.$$
(A.5)

In a similar manner, we have

$$\frac{d}{ds}U(v(s)) = -U'(v(s)) \cdot \Delta v_{j+\frac{1}{2}}, \qquad (A.6)$$

and Leibnitz rule gives us

$$\frac{d}{ds}[-\lambda \int_{v(s)}^{v_{j+1}} U'(v)g'(v)dv] := -\lambda U'(v(s))g'(v(s)) \cdot \Delta v_{j+\frac{1}{2}}.$$
(A.7)

Substitution of (A.5), (A.6), and (A.7) into (A.2) yields

$$R_{j+\frac{1}{2}}(g) = -\Delta v_{j+\frac{1}{2}} \int_0^1 \left[\frac{1}{2} + \lambda g'(v(s))\right] \cdot \left[U'(v(s)) - U'(v_{j+\frac{1}{2}}(s))\right] ds. \tag{A.8}$$

Next, we use the continuation $v(r,s) = rv(s) + (1-r)v_{j+1}$ in (3.20b) in order to express the last difference on the right as

$$U'(v(s)) - U'(v_{j+\frac{1}{2}}(s)) = \int_0^1 \frac{d}{dr} U'(v_{j+\frac{1}{2}}(r,s)) dr.$$
 (A.9)

This equality comes about as follows: in view of (3.20b), (3.2a), $v_{j+\frac{1}{2}}(r,s)$ is given by

$$v_{j+\frac{1}{2}}(r,s) = \frac{1}{2}[v(s) + v(r,s)] - \lambda[g(v((r,s)) - g(v(s)))]; \qquad (A.10)$$

hence, $v_{j+\frac{1}{2}}(1,s) = v(s)$, $v_{j+\frac{1}{2}}(0,s) = v_{j+\frac{1}{2}}(s)$ and (A.9) follows.

Noting that

$$\frac{d}{dr}v(r,s) = -\Delta v_{j+\frac{1}{2}} \cdot s, \qquad (A.11)$$

then by carrying out the differentiaton on the RHS of (A.9) we obtain,

$$\frac{d}{dr}U'(v_{j+\frac{1}{2}}(r,s)) = -U''(v_{j+\frac{1}{2}}(r,s)) \cdot \left[\frac{1}{2} - \lambda g'(v(r,s))\right] \cdot s \Delta v_{j+\frac{1}{2}}.$$
 (A.12)

Substituting (A.9), (A.11) and (A.12) into (A.8), we will end up with the desired identity $(3.22)\square$.

We close this section with the proof of Lemma 3.8.

The piecewise linear interpolant of the gridfunction, $\{g_j\}$, chosen in (3.24),

$$g(v) = \frac{\Delta g_{j+\frac{1}{2}}}{\Delta v_{j+\frac{1}{2}}}(v-v_j) + g_j \qquad (A.13)$$

has a fixed slope at each cell:

$$g'(v(r,s)) = g'(v(s)) = \frac{\Delta g_{j+\frac{1}{2}}}{\Delta v_{j+\frac{1}{2}}}.$$
 (A.14)

From (A.14) and (3.22) we obtain that in the case of quadratic entropy function where $U'' \equiv 1$,

$$R_{j+\frac{1}{2}}(g) = \frac{1}{2} (\Delta v_{j+\frac{1}{2}})^2 \left[\frac{1}{4} - \left(\lambda \frac{\Delta g_{j+\frac{1}{2}}}{\Delta v_{j+\frac{1}{2}}} \right)^2 \right].$$
(A.18)

Moreover, the difference g(v) - f(v) between two neighboring values v_j and v_{j+1} , covers an area of size,

$$\lambda \int_{v_j}^{v_{j+1}} (g(v) - f(v)) dv = \frac{\lambda}{2} [g_{j+1} + g_j] \Delta v_{j+\frac{1}{2}} - \lambda \int_{v_j}^{v_{j+1}} f(v) dv. \qquad (A.16)$$

Thus, in view of (A.15) and (A.16), the desired inequality, (3.26), boils down to

$$\frac{\lambda}{2}[g_{j+1}+g_j]\cdot\Delta v_{j+\frac{1}{2}}-\lambda\int_{v_j}^{v_{j+1}}f(v)dv+\frac{1}{2}(\lambda\frac{\Delta g_{j+\frac{1}{2}}}{\Delta v_{j+\frac{1}{2}}})^2-\frac{1}{8}(\Delta v_{j+\frac{1}{2}})^2\leq 0.$$
(A.17)

To verify the inequality (A.17), we recall that by (3.2a), (3.2b) we have

$$g_m = f(v_m(t + \frac{\Delta t}{2})) + \frac{1}{8\lambda}v'_m = f(v_m(t) - \frac{\lambda}{2}f'_m) + \frac{1}{8\lambda}v'_m, \ m = j, j + 1, \qquad (A.18)$$

and Taylor's expansion yields

$$g_m = f_m + \frac{1}{8\lambda} v'_m (1 - 4\beta^2) + O(\Delta v_{j+\frac{1}{2}})^2, \quad \beta \equiv \lambda a(v_{j+\frac{1}{2}}(t)). \tag{A.19}$$

This enables us to write the first two terms on the left of (A.17) as

$$\frac{\lambda}{2}[g_{j+1}+g_j]\cdot\Delta v_{j+\frac{1}{2}}-\lambda\int_{v_j}^{v_{j+1}}f(v)dv=\frac{1}{8}(1-4\beta^2)\cdot(\frac{v_{j+1}'+v_j'}{2\Delta v_{j+\frac{1}{2}}})\cdot(\Delta v_{j+\frac{1}{2}})^2+O(\Delta v_{j+\frac{1}{2}})^3.$$
(A.20)

Consider now the third term on the left of (A.17): by (A.19) we have

$$\lambda \Delta g_{j+\frac{1}{2}} = \lambda \Delta f_{j+\frac{1}{2}} + \frac{1}{8} (1 - 4\beta^2) \cdot (\frac{\Delta v'_{j+\frac{1}{2}}}{\Delta v_{j+\frac{1}{2}}}) \cdot \Delta v_{j+\frac{1}{2}}; \qquad (A.21a)$$

inserting $\lambda \Delta f_{j+\frac{1}{2}} = \beta \Delta v_{j+\frac{1}{2}} + O(\Delta v_{j+\frac{1}{2}})^2$ into (A.21a), squaring the result and rearranging we obtain

$$\frac{1}{2} (\lambda \Delta g_{j+\frac{1}{2}})^2 = \frac{\beta^2}{2} (\Delta v_{j+\frac{1}{2}})^2 + \frac{\beta}{8} (1 - 4\beta^2) \cdot (\frac{\Delta v_{j+\frac{1}{2}}}{\Delta v_{j+\frac{1}{2}}}) \cdot (\Delta v_{j+\frac{1}{2}})^2 + \frac{1}{128} (1 - 4\beta^2)^2 \cdot (\frac{\Delta v_{j+\frac{1}{2}}}{\Delta v_{j+\frac{1}{2}}})^2 \cdot (\Delta v_{j+\frac{1}{2}})^2 + O(\Delta v_{j+\frac{1}{2}})^3.$$
(A.21b)

We note that the cubic term on the right of (A.20), (A.21b), consists of the error in the trapezodial rule

$$\frac{\lambda}{2}[f(v_{j+1})+f(v_j)]\Delta v_{j+\frac{1}{2}}-\lambda\int_{v_j}^{v_{j+1}}f(v)dv=\frac{\lambda}{12}f''(v(\overline{x}))\cdot(\Delta v_{j+\frac{1}{2}})^3,$$

as well as additional contributions which are of the same order of magnitude

$$O(\Delta v_{j+\frac{1}{2}})^3 < \lambda \cdot [f''(v(\overline{x}))] \cdot (\Delta v_{j+\frac{1}{2}})^3.$$
(A.22)

Inserting (A.20), (A.21b), and (A.22) into the inequality (A.17) gives us

$$\frac{1-4\beta^{2}}{8}(\Delta v_{j+\frac{1}{2}})^{2} \cdot \left[\frac{v_{j+1}'+v_{j}'}{2\Delta v_{j+\frac{1}{2}}}-1+\beta\frac{\Delta v_{j+\frac{1}{2}}}{\Delta v_{j+\frac{1}{2}}}\right] + \frac{1-4\beta^{2}}{16}\left(\frac{\Delta v_{j+\frac{1}{2}}'}{\Delta v_{j+\frac{1}{2}}}\right)^{2} + \lambda \cdot \max_{\mathbf{x}}[f''(v(\mathbf{x}))] \cdot (\Delta v_{j+\frac{1}{2}})^{3} \leq 0.$$
(A.23)

Finally, since v'_j and v'_{j+1} agree in sign with $\Delta v_{j+\frac{1}{2}}$, the expression inside the left brackets can be upper bounded by

$$[\cdots] \leq \left[\frac{1}{\Delta v_{j+\frac{1}{2}}} \left(\frac{v_{j+1}' + v_{j}'}{2} \pm \left| \frac{v_{j+1}' - v_{j}'}{2} \right| \right) - 1 + (\beta - \frac{1}{2}) \left| \frac{\Delta v_{j+\frac{1}{2}}}{\Delta v_{j+\frac{1}{2}}} \right| + \frac{1 - 4\beta^2}{16} \left| \frac{\Delta v_{j+\frac{1}{2}}}{\Delta v_{j+\frac{1}{2}}} \right| \right].$$
(A.24)

By the CFL limitation, $\beta < \frac{1}{2}$, the sum of the last two terms is nonpositive, and we are left with the inequality

$$\left[\max\left(rac{v_j'}{\Delta v_{j+rac{1}{2}}},rac{v_{j+1}'}{\Delta v_{j+rac{1}{2}}}
ight)-1
ight]+\lambda\cdot\max_x[f''(v(x))]\cdot\Delta v_{j+rac{1}{2}}\leq 0,$$

which is met by the choice of entropy satisfying limiter in (3.25a), (3.25b).

References

- Ben-Arzi, M. and Falcovitz, J., "An Upwind Second-Order Scheme for Compressible Duct Flows," SIAM J. Sci. Stat. Comput., Vol. 7, No. 3, July 1986.
- [2] DiPerna, R. J., "Convergence of Approximate Solutions to Conservation Laws," Arch. Rat. Mech. Anal., Vol. 82, 1983, pp. 27-70.
- [3] Dutt, P., "A Riemann Solver Based on a Global Existence Proof for the Riemann Problem," ICASE Report No. 86-3, January 1986.
- [4] Godunov, S. K., "A Finite Difference Method for the Numerical Computation of Discontinuous Solutions of the Equations of Fluid Dynamics," Mat. Sb., Vol. 47, 1959, pp. 271-290, in Russian.
- [5] Harten, A., "The Method of Artificial Compression: I. Shocks and Contact Discontinuities," Research Develop. Report, COU-3077.50, Courant Institute, N.Y.U., June 1974
- [6] Harten, A., "The Artificial Compression Method for Computation of Shocks and Contact Discontinuities, III. Self-Adjusting Hybrid Schemes," Math. Comput., Vol. 32, New York, 1978, pp. 363-389.
- [7] Harten, A., "High Resolution Schemes for Hyperbolic Conservation Laws," J. Comput. Physics, Vol. 49, 1983, pp. 357-393.
- [8] Harten, A., "ENO Schemes with Subcell Resolution," ICASE Report No. 87-56, August 1987.
- [9] Harten, A., Engquist, B., and Osher, S., and Chakravarthy, S. R. "Uniformly High Order Accurate Essentially Non-Oscillatory Schemes III," ICASE Report No. 86-22, April 1986.
- [10] Harten, A., Hyman, J. M., and Lax, P. D., "On Finite Difference Approximations and Entropy Conditions for Shocks," Commun. Pure Appl. Math., Vol. 29, 1976, pp. 297-322.
- [11] Harten, A. and Lax, P. D., "A Random Choice Finite Difference Scheme for Hyperbolic Conservation Laws," SIAM J. Num. Anal., Vol. 18, 1981, pp. 289-315.

- [12] Harten, A. and Osher, S., "Uniformly High Order Accurate Non-Oscillatory Scheme I," MRC Technical Summary Report No. 2823, May 1985, to appear in SINUM.
- [13] Lax, P. D., "Weak Solutions of Non-Linear Hyperbolic Equations and Their Numerical Computations," Commun. Pure Applied Math., Vol. 7, 1954, pp. 159-193.
- [14] Lax, P. D., "Shock Waves and Entropy in Contributions to Nonlinear Functional Analysis," Editor E. A. Zarantonello, Academic Press, New York, Vol. 31, 1971, pp. 611-613.
- [15] Lax, P. D., "Hyperbolic Systems of Conservation Laws and the Mathematical Theory of Shock Waves," Regional Conf. Series in Appl. Math., 1973, SIAM, Phila.
- [16] Nessyahu, H., "Non-Oscillatory Second Order Central Type Scheme for Systems of Non-Linear Hyperbolic Conservation Laws," M.Sc. Thesis, Tel-Aviv University, 1987.
- [17] Osher, S., "Riemann Solvers, The Entropy Condition and Difference Approximating," SIAM J. Num. Anal., Vol. 21, 1984, pp. 217-235.
- [18] Osher, S. and Tadmor, E., "On the Convergence of Difference Approximations to Scalar Conservation Laws," ICASE Report No. 85-28, May 1985.
- [19] Roe, P. L., "Approximate Riemann Solvers, Parameter Vectors, and Difference Schemes," J. Comput. Phys., Vol. 43, 1981, pp. 357-372.
- [20] Smoller, J., "Shock Waves and Reaction-Diffusion Equations," Springer Verlag, N.Y., 1983.
- [21] Sod, G. A., "A Survey of Several Finite Difference Methods for Systems of Nonlinear Hyperbolic Conservation Laws," J. Comp. Phys., Vol. 27, 1978, pp. 1-31.
- [22] Tadmor, E., "The Large Time Behaviour of the Scalar, Genuinely Nonlinear Lax-Friedrichs Scheme," Math. Comp., Vol. 43, 1984, pp. 353-368.
- [23] Tadmor, E., "Numerical Viscosity and the Entropy Condition for Conservative Difference Schemes," Math. Comp., Vol. 43, 1984, pp. 369-382.
- [24] Van Leer, B., "Towards the Ultimate Conservative Difference Scheme V.A. Second-Order Sequel to Godunov's Method," J. Comp. Phys., Vol. 32, 1979, pp. 101-136.
- [25] Woodward, P. and Collella P., "The Numerical Simulation of Two-Dimensional Fluid Flow with Strong Shocks," J. Comp. Phys., Vol. 54, 1984, pp. 115-173.

	Report Docum	entation Pag	ρ			
brake Administration						
NASA CR-181709 ICASE Report No. 88-51	2. Government Access	ion No.	3. Recipient's Cata	alog No.		
4. Title and Subtitle			5. Report Date			
NON-OSCILLATORY CENTRAL HYPERBOLIC CONSERVATION	DIFFERENCING FOR LAWS		September	1988		
		6. Performing Organization Code				
7. Author(s)			8 Performing Orga	Dization Report No.		
Haim Nessyahu and Eitan	Tadmor		88-51			
			10. Work Unit No.			
9. Performing Organization Name and Add			505-90-21-	01		
Institute for Computer A	nnlightigne in C		11. Contract or Gran	nt No.		
and Engineering	pprications in So	lence	NAC1 19107	NAGI 1000		
Mail Stop 132C, NASA Lang	gley Research Cer	iter	NAS1-18107	, NASI-18605		
Hampton, VA 23665-5225 12. Sponsoring Agency Name and Address			13. Type of Report and Period Covered			
National Aeronautics and	Space Administra	tion	Contractor	Report		
Langley Research Center Hampton, VA 23665-5225	1		14. Sponsoring Ager	ncy Code		
15. Supplementary Notes			J			
Langley Technical Monitor Richard W. Barnwell	-:	Submitted Phys.	to SIAM J. Con	np.		
Final Report						
16. Abstract						
Many of the recently servation laws are based schemes is the averaging of involves the field-by-fiel the "direction of the wind more robust Lax-Friedrichs Riemann problems are solve The main disadvantage is solver. We compensate fo Numerical experiments show venient central differencir	developed high- on upwind diffe of an appropriate d decomposition d." Instead, we s (LxF) solver. ed and hence fie the excessive p r it by using h that the quali- ng is comparable	resolution so rencing. Th Godunov solve which is requ propose to us The main adv d-by-field d numerical visco righ-resolution ty of the resu with those of	themes for hype building bl er; its time c uired in order se as a build vantage is sime compositions cosity typical n MUSCL-type is ults obtained the upwind scl	perbolic con- ock of these onsuming part to identify ing block the plicity: no are avoided. to the LxF interpolants. by such con- hemes.		
17. Key Words (Suggested by Author(s))		18 Distribution Cart				
central differencing, non-o approximations, high resolu	scillatory tion	64 - Numeric	al Analysis			
		Unclassified	- unlimited			
19. Security Classif. (of this report)	20. Security Classif. (of th	is page)	21. No. of pages	22. Price		
Unclassified	Unclassi	fied	52	A04		

ī