

NASA- CR- 187,590

**NASA Contractor Report 187590**

NASA-CR-187590  
19910021434

**USER MANUAL FOR TWO SIMPLE POSTSCRIPT  
OUTPUT FORTRAN PLOTTING ROUTINES**

**T. X. Nguyen**

**RESEARCH TRIANGLE INSTITUTE  
Research Triangle Park, North Carolina**

**Contract NAS1-18925  
August 1991**




National Aeronautics and  
Space Administration

**Langley Research Center**  
Hampton, Virginia 23665-5225



NF00789



**FOR OFFICE USE ONLY**

100-207-247-247-247-247

RTI/4500/004-01I

## **USER MANUAL FOR TWO SIMPLE POSTSCRIPT OUTPUT FORTRAN PLOTTING ROUTINES**

By T.X. Nguyen

**INTERIM REPORT  
NASA Contract NAS1-18925  
Task Assignment No. 4**

Prepared for

**Langley Research Center  
National Aeronautics and Space Administration  
Hampton, VA 23665**

Prepared by

**Electromagnetics Research Department  
Center for Systems Engineering  
Research Triangle Institute  
Research Triangle Park, NC 27709**



## **TABLE OF CONTENTS**

List of Figures.....	v
1.0 Introduction.....	1
2.0 Overview of the Programs.....	3
3.0 Program Structures.....	5
4.0 Input File Format.....	7
5.0 Interactive Input.....	9
6.0 Program Output.....	15
7.0 Acknowledgment.....	17
8.0 References .....	19
9.0 Appendices .....	21
Appendix A.....	23
Appendix B.....	33



## **LIST OF FIGURES**

	<u>Page</u>
1. A sample X-Y plot (not true size).	12
2. A sample twinplot (not true size).	13



## **1.0 INTRODUCTION**

Graphics is one of the important tools in engineering analysis and design. However, plotting routines that generate output on high quality laser printers normally come in graphics packages, which tend to be expensive and system dependent. These factors become important for small computer systems or desktop computers, especially when only some form of a simple plotting routine is sufficient. With the Postscript language becoming popular, there are more and more Postscript laser printers now available. Simple, versatile, low cost plotting routines that can generate output on high quality laser printers, are needed and standard Fortran language plotting routines using output in Postscript language seems logical. The purpose of this report is to explain the use of two simple Fortran plotting routines that generate output in Postscript language.



## 2.0 OVERVIEW OF THE PROGRAMS

The listing of two Fortran plotting programs, PSPLXY.FOR and PSTWINPLOT.FOR, is in the appendices. The first program generates plots in X-Y format. A sample output is shown in figure 1. The second program generates two plots on the same page (called twinplot). A possible and popular application for the second program is to display both phase and magnitude for a set of complete data on the same page. A sample plot in this format is shown in figure 2.

These two routines can generate multiple curves (a maximum of 4) on the same plot with different line styles. Users have options to label curves, label the axes, and title the plot. In addition, two lines of comments can be included. Furthermore, the routine can automatically list the plot date and the time the plots are generated. However, this option is system dependent and it makes the programs nonportable. Users have the option to include this feature at the cost of code portability. This is described in section 5.0 in detail.

The two programs and their inputs are similar, thus the instructions for their use can be combined.



### **3.0 PROGRAM STRUCTURES**

The main program is very simple. It makes two calls to the subroutines. The first call is to subroutine DATAIN to read data to be plotted. The second call is to subroutine PPLOT to generate the plot. The calls to these subroutines are repeated for multiple plots

The subroutine that reads in the data requires that the data be formatted in one of two specific formats. These formats are explained in section 4.0.

The second subroutine generates all the plots, labels, etc. The explanation of this subroutine requires some knowledge of the Postscript language [1], which is beyond the scope of this report, and will be skipped.



## 4.0 INPUT FILE FORMAT

The subroutine that reads data to be plotted is named DATAIN. The data should be stored in a file in one of the two following formats:

### Format 1:

```
NPTS, XMIN, DX  
AM(1), PH(1)  
AM(2), PH(2)  
AM(3), PH(3)
```

...

The first line represents the number of data points, NPTS, the starting X value, XMIN, and the increment DX between successive values of X. This format assumes data are equally spaced in the X coordinate with XMIN being X(1).

The input lines following the first represent the amplitude, AM, and phase, PH, values of the data. AM and PH are values in the vertical coordinates. AM and PH represent Amplitude and Phase arrays, respectively (although the data may be something else if the users wish). For XY plots (PSPLOTXY FOR), only the AM array is used in plotting. However, the PH array is still required in the input to maintain input file compatibility for both programs PSPLOTXY.FOR and PSTWINPLOT.FOR.

### Format 2:

```
NPTS  
X(1), AM(1), PH(1)  
X(2), AM(2), PH(2)  
X(3), AM(3), PH(3)
```

...      ...      ...

The first line represents the number of points, NPTS.  
The following lines represent the X values for the horizontal axis  
and the AM and PH values for the vertical axis. For XY plots  
(PSPLOYXY FOR), only the X and AM arrays are used. However, the  
users must specify dummy PH values for the data to be read  
properly.

## 5.0 INTERACTIVE INPUT

Program users compile and run codes just like any other Fortran program. The programs prompt the users for input. The procedure is very self-explanatory. For completeness, the inputs are explained below:

### Input 1: NPLOTS

NPLOTS is the number of curves to be plotted on the same plot; the maximum number of curves to be plotted is four.

### Input 2: IDEF

IDEF is the axis label indicator.

- IDEF = 0 For automatic axis labeling of Magnitude vs.  
Frequency,
- = 1 For automatic axis labeling of Magnitude vs Angle  
plots,
- = 2 For the program to prompt users to input axis labels,
- = 9 To change plot size and prompt for axis labels.

The default plot size is 8.0 X 5.5 inches for XY plot (figure 1) and 5.688 x 3.438 inches for each plot on the twinplot (figure 2).

### Input 3: IFI

IFI indicates which format the data is in, as explained previously

### Input 4: INFILE

Input data file name. The file must have the format specified by Input 3.

Input 4a:

If IDEF = 2 users are prompted for axis labels for horizontal and vertical axis.

If IDEF = 9 users are prompted for a new plot size and axis labels.

Input 5: XMIN, XMAX, XINC

After displaying the minimum and maximum values of X array, users are prompted for the lower (XMIN) and upper (XMAX) limits of plot, and the X increment (XINC) between adjacent tic marks for the horizontal axis.

Input 6: YMIN, YMAX, YINC

Users are prompted for lower and upper limits of the vertical axis. YINC is the vertical axis increment between the ticmarks on the plot.

Input 6a: PHMIN, PHMAX, PHINC (Twinplots only)

For the program that generates twin plots (PSTWINPLOT.FOR), additional inputs for the vertical axis of the upper plot (usually the phase plot as in figure 2) are needed. PHMIN, PHMAX are the lower and upper limits of vertical axis, and PHINC is the coordinate increment between the ticmarks.

Input 7: TITLE

Input title for plot, 60 characters maximum. However, to avoid overlapping problems, a maximum of 35 characters is recommended for the twinplot case.

Input 8: Input first line of comments.

Users can input two lines of comments. In addition, the program has an option to automatically put the date and time under the comment lines (see figures 1,2). This option is system dependent as can be seen on program line labeled 23 in subroutine PPLOT (program PSTWINPLOT.FOR) and in subroutine PPLOXY (program PSPLXY.FOR). Thus the users are recommended to change the program line to their own system call. The program line is currently commented out to make the code portable.

Input 9: Input second line of comments

Input 9a: Input next data file name (if multiple plots).

Input 10: PLOTLAB

Input labels for the curves. Users are prompted to type in labels for each of the NPLOTS curves.

The numerical labels at each of the ticmarks on the output plot is written with Fortran format F6.1. Program users can change this format to suit their need by changing appropriate parameters on program lines labeled 2002 and 2006 in subroutine PPLOT or PSPLXY.FOR and lines labeled 2002, 2006 and 2007 in subroutine PPLOT of PSTWINPLOT.FOR. Line labeled 2002 is for the horizontal axis. Line labeled 2006 is for formating numerical labels at the ticmarks of the vertical axis on the X-Y plot and for the vertical axis of amplitude plot on a twinplot. Line labeled 2007 is for the vertical axis of the phase plot in the twinplot case.

# MAGNITUDE VS. ANGLE

COMMENT LINE 1

COMMENT LINE 2

28-NOV-1990 08 49 30 47

PLOT NUMBER 1  
PLOT NUMBER 2  
PLOT NUMBER 3  
PLOT NUMBER 4

12




Figure 1: A sample X-Y plot (not true size)

## MAGNITUDE VS. ANGLE

comment line 1  
comment line 2  
28-NOV-1990 08 59 30 03

Plot number 1  
Plot number 2  
Plot number 3  
Plot number 4





Figure 2: A sample twinplot (not true size).



## **6.0 PROGRAM OUTPUT**

The programs generate postscript output files named either "RECPLOT.ps" for a X-Y plot program or "TWINPLOT.ps" for a twinplot program.



## **7.0 ACKNOWLEDGMENT**

The author wishes to give special thanks to Ali Moaghaddar at Ohio State University for the skeleton twinplot program, which is the basis for the two described computer programs and to Karen Gray for her assistance in formatting this report.



## **8.0 REFERENCES**

- [1] Adobe Systems Incorporated: "POSTSCRIPT Language Tutorial and Cookbook." Addison-Wesley Publishing Company, 1990



## **APPENDICES**



**APPENDIX A**

**Program PSPLXY!FOR**



```

C*****
C THIS PROGRAM GENERATES PLOTS IN XY COORDINATE.
C THE OUTPUT FILE IS IN POSTSCRIPT LANGUAGE.
C
C -NUMERICAL LABELS AT THE TIC MARKS ARE WRITTEN
C WITH FORMAT "F6.1" ON LINE LABEL 2002 AND 2006 IN
C SUBROUTINE PPLOTXY. USER MAY WISH TO MODIFY THAT FORMAT
C IF NEEDED.
C
C -MAXIMUM ARRAY SIZE IS 2000. TO INCREASE, CHANGE BOTH
C PARAMETERS "NDIM" IN MAIN AND "NMAX" IN PPLOTXY
C
C -MAXIMUM 4 CURVES ON THE PLOT
C
C -LINE LABEL 23 IN SUBROUTINE PPLOTXY MAKES CALL TO A SYSTEM
C DEPENDENT FUNCTION TO GET DATE AND TIME. USER SHOULD REPLACE
C THIS LINE WITH A FUNCTION THAT WORKS ON THEIR SYSTEM.
C FOR PORTABILITY THIS STATEMENT IS TEMPORARILY COMMENTED OUT.
C
C -THE CONTENTS OF DATA FILES SHOULD BE IN ONE OF THE TWO
C FOLLOWING FORMATS:
C   1. FORMAT 1:
C     - First line : Npts, X(1), Xinc
C       where Npts = Number of Points,
C             X(1) = First data X value
C             Xinc = X increment (equally spaced data)
C     - Following lines:
C       Y(1), PH(1)
C       Y(2), PH(2)
C       Y(3), PH(3)
C
C       ...
C       Where PH array is a dummy array (could be set to zero)
C       to maintain data files compatibility between PSPLXY.FOR
C       and PSPLTAMPH.FOR
C
C   2. FORMAT 2:
C     - First line : Npts
C       where Npts = Number of Points,
C     - Following lines:
C       X(1), Y(1), PH(1)
C       X(1), Y(2), PH(2)
C       X(1), Y(3), PH(3)
C
C       ...
C       Where PH array is a dummy array (could be set to zero)
C       to maintain data files compatibility between PSPLXY.FOR
C       and PSPLTAMPH.FOR
C
C
C*****
C
C
C*****
```

PROGRAM PSPLXY

NPLOTS : NUMBER OF CURVES ON ONE PLOT

PARAMETER (NDIM=2000)

REAL\*4 AM(NDIM), PH(NDIM), X(NDIM)

WRITE(6,\*)

WRITE(6,91) 'HOW MANY CURVES ON PLOT (4 MAX)? '

```

      READ(5,*)NPLOTS
      IF(NPLOTS.LE.0) WRITE(6,*)'ERROR NPLOTS' '
C   TYPES OF PLOTS:
      WRITE(6,*)
      WRITE(6,*)'AXIS LABELS: '
      WRITE(6,*)'    IDEF=0 : FREQ. SCAN (MAG VS FREQ) '
      WRITE(6,*)'    IDEF=1 : AZIM. SCAN (MAG VS ANGLE) '
      WRITE(6,*)'    IDEF=2 : PROMPT FOR AXIS LABELS '
      WRITE(6,*)'    IDEF=9 : PROMPT FOR PLOT SIZE & AXIS LABELS '
      WRITE(6,*)'          (DEFAULT SIZE = 8.0 X 5.5 INCHES) '
      WRITE(6,91)'Input IDEF: '
      READ(5,*) IDEF
      WRITE(6,*)
      WRITE(6,99)
      WRITE(6,100)
      WRITE(6,101)
99      FORMAT(1X,'TYPES OF INPUT DATA FORMAT (PH is dummy var): ')
100     FORMAT(1X,'    IFI = 1 :: header: N,XMIN,DX ; data: Y,PH')
101     FORMAT(1X,'          = 2 :: header: N           ; data: X,Y,PH')
91      FORMAT ( 1X, A, $ )
      WRITE(6,91)'Input IFI: '
      READ(5,*) IFI

      DO 10 N=1,NPLOTS
      CALL DATAIN(NPTS,NDIM,X,AM,PH,IFI)
      CALL PPLOTXY(NPTS,NDIM,X,AM,PH,IDEF,NPLOTS,N,3)
10      CONTINUE

      STOP
      END

C+++++
CCC THIS IS INPUT READ FILE
CCC
      SUBROUTINE DATAIN(NPTS,NDIM,X,AM,PH,IFI)
      COMMON/HEADING/INFILE,LINE1,LINE2,LINE3
      REAL           X(NDIM), AM(NDIM), PH(NDIM)
      CHARACTER*60 LINE1,LINE2,LINE3
      CHARACTER*36 INFILE
7      FORMAT (A36)
91      FORMAT ( 1X, A, $ )
      WRITE(6,91)'ENTER (next) FILE NAME TO BE PLOTTED>... '
      READ(5,7) INFILE
      OPEN(UNIT=1,NAME=INFILE,STATUS='OLD')

C   FILE FORMAT READ:
      IF (IFI.EQ.1) THEN
        READ(1,*)NPTS,P_LO,P_INC
        READ(1,*)( AM(I),PH(I), I=1,NPTS )
        DO 10 I=1,NPTS
          X(I)=P_LO+(I-1.0)*P_INC
10      CONTINUE
      ELSE IF (IFI.EQ.2) THEN
        READ(1,*)NPTS
        READ(1,*)( X(I),AM(I),PH(I),I=1,NPTS )
      ENDIF
      CLOSE(UNIT=1,STATUS='KEEP')

```

```
RETURN  
END
```

```
C _____  
C SUBROUTINE PPLOTXY(NPTS,NDIM,X,AM,PH,IDEF,NPLOTS,NCOUNT,IGRID)  
  
C NPTS : INPUT NO. OF POINTS IN X AND Y ARRAY  
C XX : INPUT REAL ARRAY X COORDINATES [1..NPTS]  
C AM : INPUT REAL ARRAY OF AMPLITUDES [1..NPTS]  
C PH : INPUT REAL ARRAY OF PHASE DATA [1..NPTS]  
C IDEF : INPUT INTEGER, IDEF=0 : FREQ. SCAN  
C IDEF=1 : AZIM. SCAN  
C IDEF=2 : CHANGE AXIS LABELS  
C IDEF=9 : CHANGE X AND Y SIZE OF PLOT.  
C NPLOTS : TOTAL NUMBER OF CURVES ON PLOTS  
C IGRID : 0: NO GRID (NOT INCORPORATED)  
C 1: HORIZONTAL GRID ONLY (NOT INCORPORATED)  
C 2: VERTICAL GRID ONLY (NOT INCORPORATED)  
C 3: BOTH HORIZONTAL AND VERTICAL GRID  
C NCOUNT: N th CURVE ON THE PLOT  
  
COMMON/HEADING/INFILE,LINE1,LINE2,LINE3  
PARAMETER (NMAX=2000)  
REAL X(NDIM), AM(NDIM), PH(NDIM)  
REAL XX(NMAX), XAM(NMAX), XPH(NMAX)  
CHARACTER*30 XLABEL, AMLABEL, PHLABEL  
CHARACTER*30 ADASH(4), PLOTLAB(4), ATHICK  
CHARACTER*60 LINE1,LINE2,LINE3,TITLE  
CHARACTER*23 DATETIME  
CHARACTER*36 INFILE  
SAVE XMIN,XMAX,YMIN,YMAX,AMMAX,AMMIN,PHMAX,PHMIN  
SAVE XLENGTH,YLENGTH  
  
C CALL TO GET SYSTEM DATE & TIME:  
23 IF(NCOUNT.EQ.1) CALL LIB$DATE_TIME(DATETIME)  
  
C SET DASH TYPES:  
ADASH(1)= ' [] 0 setdash '  
ADASH(2)= ' [4 2] 0 setdash '  
ADASH(3)= ' [6 4 2 4] 0 setdash '  
ADASH(4)= ' [2 4] 0 setdash '  
ATHICK= '.6 setlinewidth '  
C TRANSFER THE VARIABLES, SO THE ROUTINE RETURNS THE ORIGINAL VARS  
DO 17 I=1,NPTS  
XX(I)=X(I)  
XAM(I)=AM(I)  
XPH(I)=PH(I)  
17 CONTINUE  
  
C FOR MULTIPLE PLOT, GO TO 300  
IF(NCOUNT.GT.1) GOTO 300  
  
C SET UP DEFAULT PLOT SIZE IN INCHES:  
C XLENGTH=5.688  
C YLENGTH=3.438  
C XLENGTH=8.000  
C YLENGTH=5.500  
C SET UP AXIS LABELS:
```

```

IF (IDEF.EQ.0) THEN
    XLABEL = '          FREQUENCY IN GHZ'
    AMLABEL= '          MAGNITUDE IN DB'
ELSEIF (IDEF.EQ.1) THEN
    XLABEL = '          ANGLE IN DEGREES'
    AMLABEL= '          MAGNITUDE IN DB'
ELSEIF (IDEF.EQ.2) THEN
    WRITE(6,*)
    WRITE(6,102)' Enter the X label: '
    READ(5,101) XLABEL
    WRITE(6,102)' Enter the Y label: '
    READ(5,101) AMLABEL
ELSEIF (IDEF.EQ.9) THEN
    WRITE(6,*)
    WRITE(6,102)' Enter the physical size of X coord. (inch)'
    READ(5,*) XLENGTH
    WRITE(6,102)' Enter the physical size of Y coord. (inch)'
    READ(5,*) YLENGTH
    WRITE(6,102)' Enter the X label: '
    READ(5,101) XLABEL
    WRITE(6,102)' Enter the Y label: '
    READ(5,101) AMLABEL
ELSE
    XLABEL = '          X      '
    AMLABEL= '          Y      '
END IF
101   FORMAT(30A)
102   FORMAT ( 1X, A, $ )

CX     IF (XLENGTH.GT.6) XLENGTH=6.0
CX     IF (YLENGTH.GT.4) YLENGTH=4.0
IF (XLENGTH.GT.8.2) XLENGTH=8.2
IF (YLENGTH.GT.6.0) YLENGTH=6.0
CALL AMINMAX(XX,NPTS,NDIM,AMAX,AMIN)
WRITE(6,*)
WRITE(6,*) ' XMIN= ', AMIN,' XMAX= ', AMAX
WRITE(6,*)' Enter Xmin, Xmax, Xinc for horizontal scaling '
READ(5,*) XMIN,XMAX,XINC
NXTIC= INT((XMAX-XMIN)/XINC)

CALL AMINMAX(XAM,NPTS,NDIM,AMAX,AMIN)
WRITE(6,*) ' AMP_MIN= ', AMIN,' AMP_MAX= ', AMAX
WRITE(6,*)' Enter Ymin, Ymax, Yinc for magnitude.'
READ(5,*) AMMIN,AMMAX,AMINC
NAMTIC= INT((AMMAX-AMMIN)/AMINC)
100   FORMAT(A20)
C     END IF

C CONTINUE HERE FOR MULTIPLE PLOTS
300   CONTINUE

C NORMALIZE THE ARRAY VALUES TO PHYSICAL DEVICE COORDS.
TEMPX=XMAX-XMIN
TEMPAM=AMMAX-AMMIN
DO 1 I=1,NPTS
    IF (XX(I).GT.XMAX) XX(I)=XMAX
    IF (XX(I).LT.XMIN) XX(I)=XMIN
    XX(I)=((XX(I)-XMIN)/TEMPX) * XLENGTH

```

```

        IF (XAM(I).GT.AMMAX) XAM(I)=AMMAX
        IF (XAM(I).LT.AMMIN) XAM(I)=AMMIN
        XAM(I)=((XAM(I)-AMMIN)/TEMPAM)*YLENGTH
        XX(I)=XX(I)*72.0
        XAM(I)=XAM(I)*72.0
1      CONTINUE
XPHYINC = (XINC/TEMPX)*XLENGTH
AMPHYINC = (AMINC/TEMPAM)*YLENGTH

IF (NCOUNT.GT.1) GOTO 305

C TRANSFER TO PHYSICAL DEVICE COORDS MAX X AXIS 6 INCH MAX Y 7 INCH

      OPEN( UNIT = 22,FILE = 'RECPLT.ps' ,
+           RECL = 128, STATUS = 'UNKNOWN' )

      WRITE(22,FMT='(A)') '%!PS-Adobe'
      WRITE(22,FMT='(A)') '/#copies 1 def'
      WRITE(22,FMT='(A)') '/inch {72 mul} def'
      WRITE(22,FMT='(A)') ' 8.50 inch 0 inch translate'
      WRITE(22,FMT='(A)') ' 90 rotate '
      WRITE(22,FMT='(A)') ' 1 inch 0.75 inch translate gsave'
      WRITE(22,FMT='(A)') '/box{exch dup 0'
      WRITE(22,FMT='(A)') ' rlineto exch dup 0 exch rlineto'
      WRITE(22,FMT='(A)') ' neg exch neg 0 rlineto'
      WRITE(22,FMT='(A)') ' 0 exch rlineto closepath} def'
      WRITE(22,FMT='(A)') '.5 setlinewidth'

      WRITE(22,1000)NXTIC
1000  FORMAT(1X,'/nxtic ',I3, ' def')
      WRITE(22,1001)NAMTIC
1001  FORMAT(1X,'/namtic ',I3, ' def')
      WRITE(22,1002)XLENGTH
1002  FORMAT(1X,'/xsize ',f7.4, ' inch def')
      WRITE(22,1003)YLENGTH
1003  FORMAT(1X,'/ysize ',f7.4, ' inch def')
      WRITE(22,1004)XPHYINC
1004  FORMAT(1X,'/xinc ',f7.4, ' inch def')
      WRITE(22,1005)AMPHYINC
1005  FORMAT(1X,'/aminc ',f7.4, ' inch def')
      WRITE(22,1006)NPTS
1006  FORMAT(1X,'/npts ',I4, ' def')
      WRITE(22,1007)DELY
1007  FORMAT(1X,'/dely ',f7.3, ' inch def')

      WRITE(22,FMT='(A)') '/ticsize 7 def'
      WRITE(22,FMT='(A)') '/do_x_tic {0 ticsize neg rlineto '
      WRITE(22,FMT='(A)') ' 0 ticsize rmoveto} def '
      WRITE(22,FMT='(A)') '/do_x_axis {0 1 3 -1 roll'
      WRITE(22,FMT='(A)') '{do_x_tic currentpoint'
      WRITE(22,FMT='(A)') ' exch xinc add exch moveto}for} def'
      WRITE(22,FMT='(A)') '/do_y_tic {ticsize neg 0 rlineto '
      WRITE(22,FMT='(A)') ' ticsize 0 rmoveto} def '
      WRITE(22,FMT='(A)') '/do_ver_grid { 1 sub 1 1 3 -1 roll'
      WRITE(22,FMT='(A)') '{currentpoint exch',
&           ' xinc add exch moveto currentpoint ysize add lineto '
      WRITE(22,FMT='(A)') ' currentpoint ysize sub moveto',

```

```

&      ' for stroke} def'
WRITE(22,FMT='(A)') '/do_am_grid { 1 sub 1 1 3 -1 roll'
WRITE(22,FMT='(A)') '{currentpoint ',
&      ' aminc add moveto currentpoint exch xsiz add exch lineto'
WRITE(22,FMT='(A)') ' currentpoint exch xsiz sub ',
&      'exch moveto }for stroke} def'

WRITE(22,FMT='(A)') '/do_am_axis {0 1 3 -1 roll'
WRITE(22,FMT='(A)') '{do_y_tic currentpoint'
WRITE(22,FMT='(A)') ' aminc add moveto}for} def'
WRITE(22,FMT='(A)') '/do_alabel {currentpoint 3 -1 roll dup '
WRITE(22,FMT='(A)') ' stringwidth pop -2 div 0 rmoveto show'
WRITE(22,FMT='(A)') ' moveto }def'
WRITE(22,FMT='(A)') '/Cor_point{4.5 inch xsiz 2 div sub '
WRITE(22,FMT='(A)') '.5 inch} def'
WRITE(22,FMT='(A)') '/Cor_point2{Cor_point ysize add 1.125 '
WRITE(22,FMT='(A)') ' inch add} def'
WRITE(22,FMT='(A)') '/Corner {Cor_point moveto} def'
WRITE(22,FMT='(A)') '/Corner2 {Cor_point2 moveto} def '

WRITE(22,FMT='(A)') ' Corner xsiz ysize box stroke'
WRITE(22,FMT='(A)') ' Corner nxtic do_x_axis stroke'
WRITE(22,FMT='(A)') ' Corner 0 ysize ticsize add rmoveto '
WRITE(22,FMT='(A)') ' nxtic do_x_axis stroke'
WRITE(22,FMT='(A)') ' Corner namtic do_am_axis stroke'
WRITE(22,FMT='(A)') ' Corner xsiz ticsize add 0 rmoveto'
WRITE(22,FMT='(A)') ' namtic do_am_axis stroke'

WRITE(22,FMT='(A)') ' Corner 0 ticsize -2.5 mul rmoveto '
WRITE(22,FMT='(A)') '/Helvetica findfont 10 scalefont '
WRITE(22,FMT='(A)') 'setfont '
XTEMP=XMIN
DO I=1,NXTIC+1
  WRITE (22,2002) XTEMP
2002 FORMAT('(',F6.1,') do_alabel xinc 0 rmoveto ')
  XTEMP=XTEMP+XINC
END DO

WRITE(22,FMT='(A)') 'gsave Cor_point translate 90 rotate'
WRITE(22,FMT='(A)') '0 0 moveto 0 ticsize 1.5 mul rmoveto '
XTEMP=AMMIN
DO I=1,NAMTIC+1
  WRITE (22,2006) XTEMP
2006 FORMAT('(',F6.1,') do_alabel aminc 0 rmoveto ')
  XTEMP=XTEMP+AMINC
END DO
WRITE(22,FMT='(A)') '/Helvetica findfont 16 scalefont '
WRITE(22,FMT='(A)') 'setfont 0 0 moveto'
WRITE(22,FMT='(A)') 'ysize 2.0 div 3.5 ticsize mul rmoveto'
WRITE(22,2003) AMLABEL

WRITE(22,FMT='(A)') ' grestore '
WRITE(22,FMT='(A)') '/Helvetica findfont 16 scalefont setfont'
WRITE(22,FMT='(A)') ' Corner xsiz 2.0 div -5.5 ticsize mul '
WRITE(22,FMT='(A)') 'rmoveto '
WRITE(22,2003) XLABEL
2003 FORMAT(' ', A30 , ' ) do_alabel ')

```

```

305      CONTINUE

C PLOT LABEL, THREE COMMENT LINES & LINE STYLE MARKERS
IF((NPLOTS.EQ.1).OR.(NCOUNT.EQ.NPLOTS)) THEN
WRITE(6,91)' Enter TITLE (60 chars max): '
READ(5,9) TITLE
9      FORMAT(A60)
91     FORMAT( 1X, A, $ )
WRITE(6,*) 'TWO LINES OF COMMENTS (DATE-TIME FOR LINE 3):'
WRITE(6,91)'INPUT COMMENTS LINE 1>...'
READ(5,9) LINE1
WRITE(6,91)'      COMMENTS LINE 2>...'
READ(5,9) LINE2
WRITE(6,91)'      COMMENTS LINE 3>...DATE-TIME '
C      READ(5,9) LINE3
WRITE(6,*)
WRITE(22,FMT='(A)') '/Helvetica findfont 16 scalefont setfont'
WRITE(22,FMT='(A)')'Corner -.6 inch ysize .8 inch add rmoveto'
WRITE(22,2005)TITLE
WRITE(22,FMT='(A)') '/Helvetica findfont 11 scalefont setfont'
WRITE(22,FMT='(A)')'Corner -.6 inch ysize .6 inch add rmoveto'
WRITE(22,2004)LINE1
WRITE(22,FMT='(A)')'Corner -.6 inch ysize .45 inch add rmoveto'
WRITE(22,2004)LINE2
WRITE(22,FMT='(A)')'Corner -.6 inch ysize .30 inch add rmoveto'
WRITE(22,2011)DATETIME
C      WRITE(22,2004)LINE3
2004   FORMAT(' (', A60 , ' )show ')
2005   FORMAT(' (', A38 , ' )show ')
2011   FORMAT(' (', A23 , ' )show ')

C***** LINE STYLE MARKER *****
C
DO 111 I=1,NPLOTS
WRITE(6,113) I
113    FORMAT(1X,'Input LABEL for PLOT ',1X,I3,: '$)
READ(5,114)PLOTLAB(I)
114    FORMAT(A30)
111    CONTINUE

C  WRITE THE PLOT LABEL
WRITE(22,FMT='(A)') '/Helvetica findfont 11 scalefont setfont'
DO 115 I=1,NPLOTS
WRITE(22,1201) ATHICK
WRITE(22,1201) ADASH(I)
IF(I.EQ.1)THEN
WRITE(22,FMT='(A)')'Corner 5.5 inch ysize .77 inch add rmoveto'
ELSE IF(I.EQ.2)THEN
WRITE(22,FMT='(A)')'Corner 5.5 inch ysize .62 inch add rmoveto'
ELSE IF(I.EQ.3)THEN
WRITE(22,FMT='(A)')'Corner 5.5 inch ysize .47 inch add rmoveto'
ELSE IF(I.EQ.4)THEN
WRITE(22,FMT='(A)')'Corner 5.5 inch ysize .32 inch add rmoveto'
ENDIF
WRITE(22,FMT='(A)')' 0.5 inch 0 rlineto stroke'
115    CONTINUE
WRITE(22,FMT='(A)') '/Helvetica findfont 11 scalefont setfont'
DO 117 I=1,NPLOTS

```

```

C      WRITE(22,1201) ADASH(I)
IF(I.EQ.1)THEN
WRITE(22,FMT='(A)')'Corner 5.5 inch ysize .75 inch add rmoveto'
ELSE IF(I.EQ.2)THEN
WRITE(22,FMT='(A)')'Corner 5.5 inch ysize .60 inch add rmoveto'
ELSE IF(I.EQ.3)THEN
WRITE(22,FMT='(A)')'Corner 5.5 inch ysize .45 inch add rmoveto'
ELSE IF(I.EQ.4)THEN
WRITE(22,FMT='(A)')'Corner 5.5 inch ysize .30 inch add rmoveto'
ENDIF
WRITE(22,FMT='(A)')' 0.4 inch 0   rmoveto'
WRITE(22,2005)PLOTLAB(I)
117    CONTINUE

C*****END LINE STYLE MARKER*****
ENDIF

      WRITE(22,FMT='(A)') ' gsave Cor_point translate '

C   TO SELECT DASH TYPES:
      WRITE(22,1201) ATHICK
      WRITE(22,1201) ADASH(NCOUNT)
1201    FORMAT(1X,A30)

      WRITE(22,3000) XX(1),XAM(1)
3000    FORMAT(2(F8.3,2x) ' moveto ')
      WRITE(22,*) (XX(I),XAM(I),' lineto ',I=2,NPTS)
      WRITE(22, FMT = '(A)') 'stroke grestore'

      IF ((NPLOTS.EQ.1).OR.(NCOUNT.EQ.NPLOTS)) THEN
      WRITE(22,FMT='(A)') '[1 5]6 setdash .2 setlinewidth '
      WRITE(22,FMT='(A)') ' Corner ntic do_ver_grid '
      WRITE(22,FMT='(A)') ' Corner namtic do_am_grid '
      WRITE(22, FMT = '(A)') 'showpage'
      CLOSE( 22 )
      WRITE(6,*)
      WRITE(6,*) 'YOUR OUTPUT FILE IS "REC PLOT.ps" '

      END IF
      RETURN
      END

C _____
C   Finds min and max in an array of size NPTS

      SUBROUTINE AMINMAX(X,NPTS,NDIM,AMAX,AMIN)
      REAL X(NDIM)
      AMAX=-1000.0
      AMIN=1000.0
      DO 1 I=1,NPTS
          IF(X(I).GT.AMAX) AMAX=X(I)
          IF(X(I).LT.AMIN) AMIN=X(I)
1       CONTINUE
      RETURN
      END

CC _____

```

**APPENDIX B**

**Program PSTWINPLOT.FOR**



```

***** THIS PROGRAM GENERATES TWO PLOTS ON THE SAME PAGE (AM VS X AND
C THIS PROGRAM GENERATES TWO PLOTS ON THE SAME PAGE (AM VS X AND
C PH VS X). THE OUTPUT FILE IS IN POSTSCRIPT LANGUAGE.
C
C -NUMERICAL LABELS AT THE TIC MARKS ARE WRITTEN
C WITH FORMAT "F6.1" ON LINE LABEL 2002, 2006 AND 2007 IN
C SUBROUTINE PPLOT. USER MAY WISH TO MODIFY THAT FORMAT
C IF NEEDED.
C
C -MAXIMUM ARRAY SIZE IS 1024. TO INCREASE, CHANGE BOTH
C PARAMETERS "NDIM" IN MAIN AND "NMAX" IN PPLOT
C
C -MAXIMUM 4 CURVES ON THE PLOT
C
C -LINE LABEL 23 IN SUBROUTINE PPLOT MAKES CALL TO A SYSTEM
C DEPENDENT FUNCTION TO GET DATE AND TIME. USER SHOULD REPLACE
C THIS LINE WITH A FUNCTION THAT WORKS ON THEIR SYSTEM.
C FOR PORTABILITY THIS STATEMENT IS TEMPORARILY COMMENTED OUT.
C
C -THE CONTENTS OF DATA FILES SHOULD BE IN ONE OF THE TWO
C FOLLOWING FORMATS:
C     1. FORMAT 1:
C         - First line : Npts, X(1), Xinc
C             where Npts = Number of Points,
C                   X(1) = First data X value
C                   Xinc = X increment (equally spaced data)
C         - Following lines:
C             Y(1), PH(1)
C             Y(2), PH(2)
C             Y(3), PH(3)
C             ...
C
C     2. FORMAT 2:
C         - First line : Npts
C             where Npts = Number of Points,
C         - Following lines:
C             X(1), Y(1), PH(1)
C             X(1), Y(2), PH(2)
C             X(1), Y(3), PH(3)
C             ...
C
C ***** PROGRAM PSPLT
C Plot Amp. and Phase data to the postscript printer
C NPLOTS      : NUMBER OF CURVES ON ONE PLOT
C PARAMETER (NDIM=1024)
C REAL*4       AM(NDIM),PH(NDIM),X(NDIM)

        WRITE(6,*)
        WRITE(6,*) 'THIS PROGRAM PLOTS TWIN PLOTS (MAG & PHASE) '
        WRITE(6,91)'HOW MANY CURVES ON PLOT (4 MAX)? '
        READ(5,*)NPLOTS
        IF(NPLOTS.LE.0) WRITE(6,*)'ERROR NPLOTS! '

C TYPES OF PLOTS:
        WRITE(6,*)
        WRITE(6,*) 'AXIS LABELS: '

```

```

      WRITE(6,*)'      IDEF=0 : FREQ. SCAN (MAG VS FREQ) '
      WRITE(6,*)'      IDEF=1 : AZIM. SCAN (MAG VS ANGLE) '
      WRITE(6,*)'      IDEF=2 : PROMPT FOR AXIS LABELS '
      WRITE(6,*)'      IDEF=9 : PROMPT FOR PLOT SIZE & AXIS LABELS '
      WRITE(6,*)'                      (DEFAULT SIZE= 5.688 X 3.438 INCHES)'
      XLENGTH=5.688
      YLENGTH=3.438

      WRITE(6,91)'Input IDEF: '
      READ(5,*) IDEF
      WRITE(6,*)
      WRITE(6,99)
      WRITE(6,100)
      WRITE(6,101)

99    FORMAT(1X,'TYPES OF INPUT DATA FORMAT : ')
100   FORMAT(1X,'    IFI = 1 :: header: N,XMIN,DX ; data: Y,PH')
101   FORMAT(1X,'        = 2 :: header: N           ; data: X,Y,PH')
91    FORMAT ( 1X, A, $ )
      WRITE(6,91)'Input IFI: '
      READ(5,*) IFI
      DO 10 N=1,NPLOTS
      CALL DATAIN(NPTS,NDIM,X,AM,PH,IFI)
      CALL PPLOT(NPTS,NDIM,X,AM,PH,IDEF,NPLOTS,N,3)
10     CONTINUE

      STOP
      END

C+++++
CCC THIS IS INPUT READ FILE
CCC

      SUBROUTINE DATAIN(NPTS,NDIM,X,AM,PH,IFI)
      COMMON/HEADING/INFILE,LINE1,LINE2,LINE3
      PARAMETER (NMAX=1024)
      REAL          X(NDIM), AM(NDIM), PH(NDIM)
      CHARACTER*60  LINE1,LINE2,LINE3
      CHARACTER*36  INFILE
7     FORMAT (A36)
91    FORMAT ( 1X, A, $ )
      WRITE(6,91)'ENTER (next) FILE NAME TO BE PLOTTED>... '
      READ(5,7) INFILE
      OPEN(UNIT=1,NAME=INFILE,STATUS='OLD')

C      FILE FORMAT READ:
      IF (IFI.EQ.1) THEN
        READ(1,*)NPTS,P_LO,P_INC
        READ(1,*)( AM(I),PH(I), I=1,NPTS )
        DO 10 I=1,NPTS
          X(I)=P_LO+(I-1.0)*P_INC
10     CONTINUE
      ELSE IF (IFI.EQ.2) THEN
        READ(1,*)NPTS
        READ(1,*)( X(I),AM(I),PH(I),I=1,NPTS )
      ENDIF
      CLOSE(UNIT=1,STATUS='KEEP')

      RETURN
      END

```

```

C _____
C SUBROUTINE PPLOT(NPTS,NDIM,X,AM,PH,IDEF,NPLOTS,NCOUNT,IGRID)

C NPTS : INPUT NO. OF POINTS IN X AND Y ARRAY
C XX : INPUT REAL ARRAY X COORDINATES [1..NPTS]
C AM : INPUT REAL ARRAY OF AMPLITUDES [1..NPTS]
C PH : INPUT REAL ARRAY OF PHASE DATA [1..NPTS]
C IDEF : INPUT INTEGER, IDEF=0 : FREQ. SCAN
C IDEF=1 : AZIM. SCAN
C IDEF=2 : CHANGE AXIS LABELS
C IDEF=9 : CHANGE X AND Y SIZE OF PLOT.
C NPLOTS : TOTAL NUMBER OF CURVES ON PLOTS
C IGRID : 0: NO GRID (NOT INCORPORATED)
C 1: HORIZONTAL GRID ONLY (NOT INCORPORATED)
C 2: VERTICAL GRID ONLY (NOT INCORPORATED)
C 3: BOTH HORIZONTAL AND VERTICAL GRID
C NCOUNT: N th CURVE ON THE PLOT

COMMON/HEADING/INFILE,LINE1,LINE2,LINE3
PARAMETER (NMAX=1024)
REAL X(NDIM), AM(NDIM), PH(NDIM)
REAL XX(NMAX), XAM(NMAX), XPH(NMAX)
CHARACTER*30 XLABEL, AMLABEL, PHLABEL
CHARACTER*30 ADASH(4), PLOTLAB(4)
CHARACTER*60 LINE1, LINE2, LINE3, TITLE
CHARACTER*23 DATETIME
CHARACTER*36 INFILE
SAVE XMIN, XMAX, YMIN, YMAX, AMMAX, AMMIN, PHMAX, PHMIN
SAVE XLENGTH, YLENGTH

C CALL TO SYSTEM TO GET DATE & TIME
23 IF (NCOUNT.EQ.1) CALL LIB$DATE_TIME(DATETIME)

C SET DASH TYPES:
ADASH(1)= ' [] 0 setdash '
ADASH(2)= ' [4 2] 0 setdash '
ADASH(3)= ' [6 4 2 4] 0 setdash '
ADASH(4)= ' [2 4] 0 setdash ' ;

C TRANSFER THE VARIABLES, SO THE ROUTINE RETURNS THE ORIGINAL VARS
DO 17 I=1,NPTS
    XX(I)=X(I)
    XAM(I)=AM(I)
    XPH(I)=PH(I)
17 CONTINUE

IF (NCOUNT.GT.1) GOTO 300

CXX
C SET UP DEFAULT PLOT SIZE IN INCHES:
XLENGTH=5.688
YLENGTH=3.438
C XLENGTH=8.000
C YLENGTH=5.500
C SET UP AXIS LABELS:
IF (IDEF.EQ.0) THEN
    XLABEL = ' FREQUENCY IN GHZ'
    AMLABEL= ' MAGNITUDE IN DB'

```

```

      PHLABEL= '          PHASE IN DEGREES'
ELSEIF (IDEF.EQ.1) THEN
      XLABEL = '          ANGLE IN DEGREES'
      AMLABEL= '          MAGNITUDE IN DB'
      PHLABEL= '          PHASE IN DEGREES'
ELSEIF (IDEF.EQ.2) THEN
      WRITE(6,*)
      WRITE(6,102)' Enter the X label: '
      READ(5,101) XLABEL
      WRITE(6,102)' Enter the AM (amplitude) label: '
      READ(5,101) AMLABEL
      WRITE(6,102)' Enter the PH (phase) label: '
      READ(5,101) PHLABEL
ELSEIF (IDEF.EQ.9) THEN
      WRITE(6,*)
      WRITE(6,102)' Enter the physical size of X coord. (inch)'
      READ(5,*) XLENGTH
      WRITE(6,102)' Enter the physical size of Y coord. (inch)'
      READ(5,*) YLENGTH
      WRITE(6,102)' Enter the X label: '
      READ(5,101) XLABEL
      WRITE(6,102)' Enter the AM (amplitude) label: '
      READ(5,101) AMLABEL
      WRITE(6,102)' Enter the PH (phase) label: '
      READ(5,101) PHLABEL
ELSE
      XLABEL = '          X'
      AMLABEL= '          MAGNITUDE IN DB'
      PHLABEL= '          PHASE IN DEGREES'
END IF
101  FORMAT(30A)
102  FORMAT ( 1X, A, $ )

IF (XLENGTH.GT.6) XLENGTH=6.0
IF (YLENGTH.GT.4) YLENGTH=4.0
CALL AMINMAX(XX,NPTS,NDIM,AMAX,AMIN)
WRITE(6,*)
WRITE(6,*) ' XMIN= ', AMIN, ' XMAX= ', AMAX
WRITE(6,*) 'Enter Xmin, Xmax, Xinc for horizontal scaling'
READ(5,*) XMIN,XMAX,XINC
NXTIC= INT((XMAX-XMIN)/XINC)

CALL AMINMAX(XAM,NPTS,NDIM,AMAX,AMIN)
WRITE(6,*) ' AMP_MIN= ', AMIN, ' AMP_MAX= ', AMAX
WRITE(6,*) ' Enter min, max, inc for magnitude.'
READ(5,*) AMMIN,AMMAX,AMINC
NAMTIC= INT((AMMAX-AMMIN)/AMINC)
CALL AMINMAX(XPH,NPTS,NDIM,AMAX,AMIN)
WRITE(6,*) ' PH_MIN= ', AMIN, ' PH_MAX= ', AMAX
WRITE(6,*) ' Enter min, max, inc for phase.'
READ(5,*) PHMIN,PHMAX,PHINC
NPHTIC= INT((PHMAX-PHMIN)/PHINC)
100   FORMAT(A20)

C  CONTINUE HERE FOR MULTIPLE PLOTS
300   CONTINUE

C  NORMALIZE THE ARRAY VALUES TO PHYSICAL DEVICE COORDS.

```

```

TEMPX=XMAX-XMIN
TEMPAM=AMMAX-AMMIN
TEMPPH=PHMAX-PHMIN
DO 1 I=1,NPTS
    IF (XX(I).GT.XMAX) XX(I)=XMAX
    IF (XX(I).LT.XMIN) XX(I)=XMIN
    XX(I)=((XX(I)-XMIN)/TEMPX) * XLENGTH
    IF (XAM(I).GT.AMMAX) XAM(I)=AMMAX
    IF (XAM(I).LT.AMMIN) XAM(I)=AMMIN
    XAM(I)=((XAM(I)-AMMIN)/TEMPAM) * YLENGTH
    IF (XPH(I).GT.PHMAX) XPH(I)=PHMAX
    IF (XPH(I).LT.PHMIN) XPH(I)=PHMIN
    XPH(I)=((XPH(I)-PHMIN)/TEMPPH) * YLENGTH
    XX(I)=XX(I)*72.0
    XAM(I)=XAM(I)*72.0
    XPH(I)=XPH(I)*72.0
1 CONTINUE
XPHYINC = (XINC/TEMPX)*XLENGTH
AMPHYINC = (AMINC/TEMPAM)*YLENGTH
PHPHYINC = (PHINC/TEMPPH)*YLENGTH

IF (NCOUNT.GT.1)GOTO 305

```

C TRANSFER TO PHYSICAL DEVICE COORDS MAX X AXIS 6 INCH MAX Y 7 INCH

```

OPEN( UNIT = 22, FILE = 'TWINPLOT.ps',
+      STATUS = 'UNKNOWN' )

WRITE(22,FMT='(A)') '%PS-Adobe'
WRITE(22,FMT='(A)') '/#copies.1 def'
WRITE(22,FMT='(A)') '/inch {72 mul} def'
WRITE(22,FMT='(A)') ' 1 inch 1 inch translate gsave'
WRITE(22,FMT='(A)') '/box{exch dup 0'
WRITE(22,FMT='(A)') ' rlineto exch dup 0 exch rlineto'
WRITE(22,FMT='(A)') ' neg exch neg 0 rlineto'
WRITE(22,FMT='(A)') ' 0 exch rlineto closepath} def'
WRITE(22,FMT='(A)') '.5 setlinewidth'

1000 WRITE(22,1000)NXTIC
FORMAT(1X,'/nxtic ',I3, ' def')
WRITE(22,1001)NAMTIC
1001 FORMAT(1X,'/namtic ',I3, ' def')
WRITE(22,1009)NPHTIC
1009 FORMAT(1X,'/nphtic ',I3, ' def')
WRITE(22,1002)XLENGTH
1002 FORMAT(1X,'/xsize ',f7.4, ' inch def')
WRITE(22,1003)YLENGTH
1003 FORMAT(1X,'/ysize ',f7.4, ' inch def')
WRITE(22,1004)XPHYINC
1004 FORMAT(1X,'/xinc ',f7.4, ' inch def')
WRITE(22,1005)AMPHYINC
1005 FORMAT(1X,'/aminc ',f7.4, ' inch def')
WRITE(22,1008)PHPHYINC
1008 FORMAT(1X,'/phinc ',f7.4, ' inch def')
WRITE(22,1006)NPTS
1006 FORMAT(1X,'/npts ',I4, ' def')
WRITE(22,1007)DELY

```

```

1007 FORMAT(1X,'/dely ',f7.3, ' inch def')

      WRITE(22,FMT='(A)') '/ticsize 7 def'
      WRITE(22,FMT='(A)') '/do_x_tic {0 ticsize neg rlineto '
      WRITE(22,FMT='(A)') ' 0 ticsize rmoveto} def '
      WRITE(22,FMT='(A)') '/do_x_axis {0 1 3 -1 roll'
      WRITE(22,FMT='(A)') ' {do_x_tic currentpoint'
      WRITE(22,FMT='(A)') ' exch xinc add exch moveto}for} def'
      WRITE(22,FMT='(A)') '/do_y_tic {ticsize neg 0 rlineto '
      WRITE(22,FMT='(A)') ' ticsize 0 rmoveto} def '
      WRITE(22,FMT='(A)') '/do_ver_grid { 1 sub 1 1 3 -1 roll'
      WRITE(22,FMT='(A)') '{currentpoint exch',
      & ' xinc add exch moveto currentpoint ysize add lineto '
      WRITE(22,FMT='(A)') ' currentpoint ysize sub moveto',
      & ' for stroke} def'
      WRITE(22,FMT='(A)') '/do_am_grid { 1 sub 1 1 3 -1 roll'
      WRITE(22,FMT='(A)') '{currentpoint ',
      & ' aminc add moveto currentpoint exch xsize add exch lineto'
      WRITE(22,FMT='(A)') ' currentpoint exch xsize sub ',
      & ' exch moveto }for stroke} def'
      WRITE(22,FMT='(A)') '/do_ph_grid { 1 sub 1 1 3 -1 roll'
      WRITE(22,FMT='(A)') '{currentpoint ',
      & ' phinc add moveto currentpoint exch xsize add exch lineto'
      WRITE(22,FMT='(A)') ' currentpoint exch xsize sub ',
      & ' exch moveto }for stroke} def'

      WRITE(22,FMT='(A)') '/do_am_axis {0 1 3 -1 roll'
      WRITE(22,FMT='(A)') '{do_y_tic currentpoint'
      WRITE(22,FMT='(A)') ' aminc add moveto}for} def'
      WRITE(22,FMT='(A)') '/do_ph_axis {0 1 3 -1 roll'
      WRITE(22,FMT='(A)') '{do_y_tic currentpoint'
      WRITE(22,FMT='(A)') ' phinc add moveto}for} def'
      WRITE(22,FMT='(A)') '/do_alabel {currentpoint 3 -1 roll dup '
      WRITE(22,FMT='(A)') ' stringwidth pop -2 div 0 rmoveto show'
      WRITE(22,FMT='(A)') ' moveto }def'
      WRITE(22,FMT='(A)') '/Cor_point{3.5 inch xsize 2 div sub '
      WRITE(22,FMT='(A)') ' .5 inch} def'
      WRITE(22,FMT='(A)') '/Cor_point2{Cor_point ysize add 1.125 '
      WRITE(22,FMT='(A)') ' inch add} def'
      WRITE(22,FMT='(A)') '/Corner {Cor_point moveto} def'
      WRITE(22,FMT='(A)') '/Corner2 {Cor_point2 moveto} def '

      WRITE(22,FMT='(A)') ' Corner xsize ysize box stroke'
      WRITE(22,FMT='(A)') ' Corner nxtic do_x_axis stroke'
      WRITE(22,FMT='(A)') ' Corner 0 ysize ticsize add rmoveto '
      WRITE(22,FMT='(A)') ' nxtic do_x_axis stroke'
      WRITE(22,FMT='(A)') ' Corner namtic do_am_axis stroke'
      WRITE(22,FMT='(A)') ' Corner xsize ticsize add 0 rmoveto'
      WRITE(22,FMT='(A)') ' namtic do_am_axis stroke'

      WRITE(22,FMT='(A)') ' Corner2 xsize ysize box stroke'
      WRITE(22,FMT='(A)') ' Corner2 nxtic do_x_axis stroke'
      WRITE(22,FMT='(A)') ' Corner2 0 ysize ticsize add rmoveto '
      WRITE(22,FMT='(A)') ' nxtic do_x_axis stroke'
      WRITE(22,FMT='(A)') ' Corner2 nphtic do_ph_axis stroke'
      WRITE(22,FMT='(A)') ' Corner2 xsize ticsize add 0 rmoveto'
      WRITE(22,FMT='(A)') ' nphtic do_ph_axis stroke'

```

```

      WRITE(22,FMT='(A)') ' Corner 0 ticsize -2.5 mul rmoveto '
      WRITE(22,FMT='(A)') '/Helvetica findfont 10 scalefont '
      WRITE(22,FMT='(A)') 'setfont '
      XTEMP=XMIN
      DO I=1,NXTIC+1
        WRITE (22,2002)XTEMP
      2002   FORMAT('(',F6.1,') do_alabel xinc 0 rmoveto ')
        XTEMP=XTEMP+XINC
      END DO
      WRITE(22,FMT='(A)') ' Corner2 0 ticsize -2.5 mul rmoveto '
      XTEMP=XMIN
      DO I=1,NXTIC+1
        WRITE (22,2002)XTEMP
        XTEMP=XTEMP+XINC
      END DO

      WRITE(22,FMT='(A)') 'gsave Cor_point translate 90 rotate'
      WRITE(22,FMT='(A)') '0 0 moveto 0 ticsize 1.5 mul rmoveto '
      XTEMP=AMMIN
      DO I=1,NAMTIC+1
        WRITE (22,2006)XTEMP
      2006   FORMAT('(',F6.1,') do_alabel aminc 0 rmoveto ')
        XTEMP=XTEMP+AMINC
      END DO
      WRITE(22,FMT='(A)') '/Helvetica findfont 16 scalefont '
      WRITE(22,FMT='(A)') 'setfont 0 0 moveto'
      WRITE(22,FMT='(A)') 'ysize 2.0 div 3.5 ticsize mul rmoveto'
      WRITE(22,2003)AMLABEL

      WRITE(22,FMT='(A)') 'grestore Cor_point2 translate 90 rotate'
      WRITE(22,FMT='(A)') '0 0 moveto 0 ticsize 1.5 mul rmoveto '
      XTEMP=PHMIN
      DO I=1,NPHTIC+1
        WRITE (22,2007)XTEMP
      2007   FORMAT('(',F6.1,') do_alabel phinc 0 rmoveto ')
        XTEMP=XTEMP+PHINC
      END DO
      WRITE(22,FMT='(A)') '/Helvetica findfont 16 scalefont '
      WRITE(22,FMT='(A)') 'setfont 0 0 moveto'
      WRITE(22,FMT='(A)') 'ysize 2.0 div 3.5 ticsize mul rmoveto'
      WRITE(22,2003)PHLABEL
      WRITE(22,FMT='(A)') ' grestore '

      WRITE(22,FMT='(A)') '/Helvetica findfont 16 scalefont setfont'
      WRITE(22,FMT='(A)') ' Corner xsize 2.0 div -5.5 ticsize mul '
      WRITE(22,FMT='(A)') 'rmoveto '
      WRITE(22,2003)XLABEL
      2003   FORMAT('(', A30 ,') do_alabel ')
      WRITE(22,FMT='(A)') ' Corner2 xsize 2.0 div -5.5 ticsize mul '
      WRITE(22,FMT='(A)') 'rmoveto '
      WRITE(22,2003)XLABEL

      305   CONTINUE

C PLOT LABEL, THREE COMMENT LINES & LINE STYLE MARKERS
      IF((NPLOTS.EQ.1).OR.(NCOUNT.EQ.NPLOTS)) THEN
      WRITE(6,*)
      WRITE(6,91)' Enter TITLE (40 chars max): '

```

```

9      READ(5,9) TITLE
91     FORMAT (A60)
      FORMAT ( 1X, A, $ )
      WRITE(6,*)
      WRITE(6,91)'TWO LINES OF COMMENTS (DATE-TIME FOR LINE 3):'
      WRITE(6,91)'INPUT COMMENTS LINE 1>...'
      READ(5,9) LINE1
      WRITE(6,91)'      COMMENTS LINE 2>...'
      READ(5,9) LINE2
      WRITE(6,91)'      COMMENTS LINE 3>...DATE-TIME '
C      READ(5,9) LINE3
      WRITE(6,*)
      WRITE(22,FMT='(A)') '/Helvetica findfont 16 scalefont setfont'
      WRITE(22,FMT='(A)')'Corner2 -.6 inch ysize .8 inch add rmoveto'
      WRITE(22,2005)TITLE
      WRITE(22,FMT='(A)') '/Helvetica findfont 11 scalefont setfont'
      WRITE(22,FMT='(A)')'Corner2 -.6 inch ysize .6 inch add rmoveto'
      WRITE(22,2004)LINE1
      WRITE(22,FMT='(A)')'Corner2 -.6 inch ysize .45 inch add rmoveto'
      WRITE(22,2004)LINE2
      WRITE(22,FMT='(A)')'Corner2 -.6 inch ysize .30 inch add rmoveto'
C      WRITE(22,2004)LINE3
      WRITE(22,2011)DATETIME
2004   FORMAT(' (', A60 ,')show ')
2005   FORMAT(' (', A38 ,')show ')
2011   FORMAT(' (', A23 ,')show ')

C***** LINE STYLE MARKER *****
C
      DO 111 I=1,NPLOTS
      WRITE(6,113) I
113     FORMAT(1X,'Input LABEL for PLOT ',1X,I3,: '$')
      READ(5,114)PLOTLAB(I)
      FORMAT(A30)
111     CONTINUE

C  WRITE THE PLOT LABEL
      WRITE(22,FMT='(A)') '/Helvetica findfont 11 scalefont setfont'
      DO 115 I=1,NPLOTS
      WRITE(22,1201) ADASH(I)
      IF(I.EQ.1)THEN
      WRITE(22,FMT='(A)')'Corner2 3.5 inch ysize .77 inch add rmoveto'
      ELSE IF(I.EQ.2)THEN
      WRITE(22,FMT='(A)')'Corner2 3.5 inch ysize .62 inch add rmoveto'
      ELSE IF(I.EQ.3)THEN
      WRITE(22,FMT='(A)')'Corner2 3.5 inch ysize .47 inch add rmoveto'
      ELSE IF(I.EQ.4)THEN
      WRITE(22,FMT='(A)')'Corner2 3.5 inch ysize .32 inch add rmoveto'
      ENDIF
      WRITE(22,FMT='(A)')' 0.5 inch 0 rlineto stroke'
115     CONTINUE

      WRITE(22,FMT='(A)') '/Helvetica findfont 11 scalefont setfont'
      DO 117 I=1,NPLOTS
      WRITE(22,1201) ADASH(I)
      IF(I.EQ.1)THEN
      WRITE(22,FMT='(A)')'Corner2 3.5 inch ysize .75 inch add rmoveto'
      ELSE IF(I.EQ.2)THEN
      WRITE(22,FMT='(A)')'Corner2 3.5 inch ysize .60 inch add rmoveto'

```

```

ELSE IF(I.EQ.3)THEN
WRITE(22,FMT='(A)')'Corner2 3.5 inch ysize .45 inch add rmoveto'
ELSE IF(I.EQ.4)THEN
WRITE(22,FMT='(A)')'Corner2 3.5 inch ysize .30 inch add rmoveto'
ENDIF
WRITE(22,FMT='(A)')' 0.4 inch 0 rmoveto'
WRITE(22,2005)PLOTLAB(I)
117    CONTINUE

C*****END LINE STYLE MARKER*****
ENDIF

        WRITE(22,FMT='(A)') ' gsave Cor_point translate '

C   TO SELECT DASH TYPES:
        WRITE(22,1201) ADASH(NCOUNT)
1201    FORMAT(1X,A30)

3000    WRITE(22,3000) XX(1),XAM(1)
        FORMAT(2(F8.3,2x) ' moveto ')
        WRITE(22,*) (XX(I),XAM(I),' lineto ',I=2,NPTS)
        WRITE(22, FMT = '(A)') 'stroke grestore'

        WRITE(22,FMT='(A)') ' gsave Cor_point2 translate '
C   TO SELECT DASH TYPES:
        WRITE(22,1201) ADASH(NCOUNT)
        WRITE(22,3000) XX(1),XPH(1)
        WRITE(22,*) (XX(I),XPH(I),' lineto ',I=2,NPTS)
        WRITE(22, FMT = '(A)') 'stroke grestore '

        IF ((NPLOTS.EQ.1).OR.(NCOUNT.EQ.NPLOTS)) THEN
        WRITE(22,FMT='(A)') '[1 5]6 setdash .2 setlinewidth '
        WRITE(22,FMT='(A)') ' Corner nxtic do_ver_grid '
        WRITE(22,FMT='(A)') ' Corner2 nxtic do_ver_grid '
        WRITE(22,FMT='(A)') ' Corner namtic do_am_grid '
        WRITE(22,FMT='(A)') ' Corner2 nphtic do_ph_grid'
        WRITE(22, FMT = '(A)') 'showpage'
        CLOSE( 22 )
        WRITE(6,*)
        WRITE(6,*)"THE OUTPUT FILE IS "TWINPLOT.ps" '
        END IF
        RETURN
        END

C
C   Finds min and max in an array of size NPTS

SUBROUTINE AMINMAX(X,NPTS,NDIM,AMAX,AMIN)
REAL      X(NDIM)
AMAX=-1000.0
AMIN=1000.0
DO 1 I=1,NPTS
     IF(X(I).GT.AMAX) AMAX=X(I)
     IF(X(I).LT.AMIN) AMIN=X(I)
1      CONTINUE
      RETURN
      END

```



## Report Documentation Page

1 Report No <b>NASA CR-187590</b>	2 Government Accession No	3 Recipient's Catalog No
4 Title and Subtitle <b>User Manual For Two Simple Postscript Output Fortran Plotting Routines</b>		5 Report Date <b>August 1991</b>
		6 Performing Organization Code
7 Author(s) T. X. Nguyen		8 Performing Organization Report No <b>RTI 4500 004-01I</b>
9 Performing Organization Name and Address Research Triangle Institute P.O. Box 12194 Research Triangle Park, NC 27709		10 Work Unit No <b>505-64-70-01</b>
		11 Contract or Grant No <b>NAS1-18925</b>
12 Sponsoring Agency Name and Address National Aeronautics and Space Administration Langley Research Center Hampton, VA 23665-5225		13 Type of Report and Period Covered <b>Contractor Report (Interim Report)</b>
		14 Sponsoring Agency Code
15 Supplementary Notes Langley Contract Monitor: Lyle C. Schroeder Interim Report Task 4 Langley Technical Task Monitor: Fred Beck		
16 Abstract Graphics is one of the important tools in engineering analysis and design. However, plotting routines that generate output on high quality laser printers normally come in graphics packages, which tend to be expensive and system dependent. These factors become important for small computer systems or desktop computers, especially when only some form of a simple plotting routine is sufficient. With the Postscript language becoming popular, there are more and more Postscript laser printers now available. Simple, versatile, low cost plotting routines that can generate output on high quality laser printers, are needed and standard Fortran language plotting routines using output in Postscript language seems logical. The purpose of this report is to explain the use of two simple Fortran plotting routines that generate output in Postscript language.		
17 Key Words (Suggested by Author(s)) Postscript Fortran Graphics		18 Distribution Statement <b>Unclassified - Unlimited</b> Subject Category 61
19 Security Classif (of this report) <b>Unclassified</b>	20 Security Classif (of this page) <b>Unclassified</b>	21 No of pages <b>47</b>
		22 Price <b>A03</b>

**End of Document**