

N92-139397

RESEARCH ON INVERSE, HYBRID AND OPTIMIZATION PROBLEMS  
IN ENGINEERING SCIENCES WITH EMPHASIS ON TURBOMACHINE  
AERODYNAMICS: REVIEW OF CHINESE ADVANCESGao-Lian Liu, Professor  
Laboratory of Turbomachinery Aerodynamics  
Shanghai Institute of Mechanical Engineering  
516 Jun-Gong Rd, Shanghai 200093, China

## ABSTRACT

A brief review of advances in the inverse design and optimization theory in the following engineering fields in China is presented: I) Turbomachine aerodynamic inverse design: including mainly: (1) two original approaches—image-space approach and variational approach, (2) improved mean-streamline (stream surface) method, (3) optimization theory based on optimal control. II) Other engineering fields: inverse problem of heat conduction, free-surface flow, variational cogeneration of optimal grid and flow field, optimal meshing theory of gears.

## I. INTRODUCTION

Up to now, most(over 95%) of the technical literature deals only with the direct (analysis) problem due to possibly the fact that the inverse(design) problem(finding the unknown boundary shape) is, in general, much more difficult to formulate as well as to solve than the direct one, though the inverse problem is more important for, and directly related to, practical design. As a result, for instance, almost all turbomachine bladings are still designed by repeated use of direct problem methods in a cut-and-try manner, which is of course not only inconvenient and time-consuming, but also incapable of providing very good results. So in the 1950's in China we have tried to apply the mean-streamline method for inverse problem of Wu & Brown[30] to cascade design and some improvements of this method were suggested[2]. In the 1960's a new image-plane approach to the inverse problem was proposed [5]. It was realized, however, that also the inverse problem can not be successfully used for practical blade design, because it often leads to blade configurations that are either unfeasible from consideration of stress, vibration, cooling and technology or even unrealizable(e.g. giving profiles unclosed or with negative thickness). Therefore the traditional direct and inverse problems can not keep up with the development of modern turbomachinery(TM) and it was suggested in Refs.[18,56] to extend the scope of aerodynamic problems and reclassify them into four categories: direct, inverse, hybrid and optimization problems. Then the image-plane approach was extended to hybrid problem in Refs.[6,56], and another new approach to inverse and hybrid problems based on variational principles (VPs) was also suggested in Refs. [18,21]. Since then, a lot of variants of the image-plane approach, the variational approach and the mean-streamline method have been developed in China and extended to 3-D case.

The Chinese research on the optimization problem of bladings started with the problem of optimal radial distribution of flow parameters in TM with long twisted blades in 1963[52]. Later, advances in this area are characterized and facilitated considerably by the introduction of modern optimal control theory.

## II. RECLASSIFICATION OF ENGINEERING PROBLEM SETTING

Generally speaking, any problem of engineering sciences can be posed in different ways, resulting in four problem categories: direct, inverse, hybrid and optimization problems. Specifically, for the aerodynamic problem of blade cascades these problems are defined conceptually in Table I. The aerodynamic problem for  $S_2$ -stream surface can be classified similarly as shown in Table II.

The hybrid problem is a unification as well as a generalization of the direct and inverse problems, encompasses a wide variety of types (see Table III for cascades on arbitrary streamsheet of revolution) and hence is very flexible and capable of meeting various design requirements. It provides design engineers with a series of new rational versatile ways for blade design. In addition, the inverse and hybrid problems also constitute an important ingredient of the optimization problem.

Table I. Problem Classification of Cascade Flow

	problem	Given	To be sought
1	Direct (D)	cascade geometry	velocity field
2	Inverse (I)	surface velocity distribution	cascade geometry
3	Hybrid (H)	'partly geometric conditions' & 'partly flow condition'	the remaining unknown geometry & flow field
4	Optimization (Opt)	1) objective functional 2) design inequality constraints	optimal cascade geometry & flow field

Table II. Problem Classification of  $S_2$ -Flow

problem		Given	
		on $S_2$	on hub & casing
Direct	complete	Shape	geometry
	semi-		pressure distribution
Inverse	complete	$V_{\phi r}$	pressure distribution
	semi-		geometry
Hybrid		Shape or $V_{\phi r}$	'partly geometry' + 'partly pressure distribution'
Optimization		1) objective function, 2) inequality design constraints	

Table III. Hybrid Problem Types of Cascades

Types	Given conditions	
	geometric	aerodynamic
$H_A$	part of airfoil form	velocity distribution along the remaining part of profile contour
$H_B$	airfoil thickness distribution	blade loading distribution ( $p_p - p_s$ )
$H_C$	airfoil thickness distribution	velocity distribution along the suction surface
$H_D$	airfoil thickness distribution	distribution of velocity difference ( $W_s - W_p$ )

Since the hybrid problem of fully 3-D flow may have a wide variety of types, depending on the manner in which the boundary conditions (B.C.) on the blade surface are combined with those on the annular walls, it is necessary to employ some properly defined compound symbols to designate them as proposed in Refs. [46, 47]. For instance, the symbol ( $I \times H_A$ ) designates such a hybrid problem type in which an inverse problem is posed on the blade surface, while a  $H_A$ -problem is posed on the annular walls (Fig. 1a). In other words, the symbol before 'X' characterizes the problem type on the blade surface, while the symbol behind 'X'---that on the annular walls. It is easy to see that the scope of possible hybrid problem types can be made even much broader by posing different problem types on different portions of the blade (and/or annular) walls (Fig. 1b).

### III. INVERSE & HYBRID PROBLEMS OF BLADE-TO-BLADE FLOW IN TURBOMACHINES

The research on inverse and hybrid problems in China has been going basically along the following three lines: (i) universal approach based on image-plane concept; (ii) unified approach based on variational principles (VPs) and the related finite element method (FEM); (iii) improvement of the mean-streamline method and of other well-known methods.

#### 1) Universal Approach Based on Image-Plane Concept

Two different image planes  $\xi\psi$  and  $\xi\eta$  have been introduced:

##### 1-1. Methods based on image-plane $\xi\psi$ .

The first universal image-plane method for solving the inverse problem of 2-D compressible cascade flow was suggested by Liu in 1964 [5] and extended to cascades on arbitrary streamsheet of revolution by Liu & Tao in 1967 [6] and to hybrid problem  $H_A$  by Liu & Tao in 1981 [6]. The main difficulty is the treatment of unknown boundary (blade surface) and was successfully overcome by introducing a nonorthogonal curvilinear (streamline) coordinate system (von-Mises coordinates) defined by (Fig. 2, where  $\eta$  should be replaced by  $\psi$ )

$$\left. \begin{aligned} \xi &= l \quad [\text{or: } \xi = f(l)] \\ \psi &= \psi(l, \varphi) \end{aligned} \right\} \quad (1)$$

where the stream function  $\psi$  is defined by

$$\frac{\partial \psi}{\partial \xi} = -\tau \rho \Lambda_\varphi, \quad \frac{\partial \psi}{\partial \varphi} = \tau r \rho \Lambda_\xi \quad (2)$$

It is expedient to regard Eq.(1) as a mapping, which transforms the original irregular periodic flow domain with some unknown boundary (AB in  $H_A$ -problem, Fig.2a) on the physical stream surface into a simple rectangular one with fully known boundary in the image plane (Fig.2b). Moreover, the following four alternative formulations were derived in Ref. [5,6]:

- i) first-order partial differential equation (PDE) system
- ii) second-order PDE
- iii) integro-differential equation
- iv) integral equation system,

of which only the integro-differential formulation for homentropic flow is given here for reference [6]:

$$\oint_{(\delta C)} \frac{1}{\tau \rho} \left\{ \left[ 1 + \left( r \frac{\partial \varphi}{\partial \xi} \right)^2 \right] \left( r \frac{\partial \varphi}{\partial \psi} \right)^{-1} d\xi + r \frac{\partial \varphi}{\partial \xi} d\psi \right\} = L_1 \quad (3)$$

where

$$\frac{\partial \varphi}{\partial \xi} = \Lambda_\varphi / (r \Lambda_\xi), \quad \frac{\partial \varphi}{\partial \psi} = 1 / \tau r \rho \Lambda_\xi \quad (4)$$

$$\rho = p^{1/\kappa} = \left\{ 1 - \frac{1}{2m} (\Lambda^2 - \Lambda_u^2) \right\}^m \quad (5)$$

$$L_1 = \frac{-2\omega B}{a_0} \iint_{(\delta A)} r \sin \sigma \frac{\partial \varphi}{\partial \psi} d\xi d\psi.$$

Here  $\Lambda (=w/a_0)$  and  $\Lambda_u (= \omega r/a_0)$  are dimensionless relative velocity and blade speed respectively;  $m = (\kappa - 1)^{-1}$ ;  $a_0$  --- reference speed of sound;  $\omega$  --- rotor angular speed;  $\delta C$  --- the contour abcd of a finite area  $\delta A$  (Fig.2b).

A  $H_A$ - and an inverse problems of a cascade on a general streamsurface of revolution have been solved by this method by Chen et al. in Ref. [7].

This method was then improved considerably by Liu [8] via introducing a new moment function  $\Omega$  defined by

$$\frac{\partial \Omega}{\partial \xi} = \tau r \frac{p}{\kappa}, \quad \frac{\partial \Omega}{\partial \psi} = -(\Lambda_\varphi + \Lambda_u) r \quad (6)$$

The moment function has some special features, for instance: (i) its increment around any closed contour enclosing an airfoil  $\Delta \Omega$  is just equal to the aerodynamic moment  $M_z$  exerted on airfoil:

$$\Delta \Omega = M_z = \Gamma \cdot \Delta \psi \quad (7)$$

This is just a generalization of the well-known Kutta's lift theorem for 2-D flow, showing that  $M_z$  is proportional to both absolute circulation around airfoil  $\Gamma$  and flow rate through an interblade channel  $\Delta \psi$ . (ii) the pressure  $p$  can be computed directly from Eq.(5), resulting in two advantages: first, no density ambiguity [80] appears; second, for the inverse problem the B.C. (i.e. the distribution of  $\Omega$ ) on the airfoil contour is of the Dirichlet's type and hence easy to deal with. Also in this case the four alternative formulations mentioned above are possible, of which only the second-order PDE formulation is given below:

$$A \frac{\partial^2 \Omega}{\partial \xi^2} + 2B \frac{\partial^2 \Omega}{\partial \xi \partial \psi} + C \frac{\partial^2 \Omega}{\partial \psi^2} + D \frac{\partial \Omega}{\partial \xi} + E \left( \frac{\partial \Omega}{\partial \psi} \right)^2 = F, \quad (8)$$

where A, B, C, D, E are functions of Mach number,  $\rho$ ,  $\tau$  and  $\zeta$  (Fig. 2); F is a function of the gradients of entropy and rothalpy. In Ref. [8] an inverse problem of a cascade on a conical streamsurface taken from Ref. [78] was solved and the result is given in Fig. 3.

Later, a number of methods using this image plane  $\xi\psi$  have been also published in Refs [9-12], differing from one another, however, by different choice between the four above-mentioned formulations and by different iterative strategies. Thus, in contrast to Refs. [5, 6], Shen & Ma [9] solved the  $H_A$ - and  $H_C$ -problems of 2-D transonic cascade flow by employing the 1st-order PDE formulation and Jameson's rotated difference scheme, while Chen & Zhang [10], using the second-order PDE formulation for the dependent variable  $\varphi(\xi, \psi)$ , presented a numerical method for solving direct, inverse and hybrid  $H_A$ -problems along with three numerical inverse problem examples, of which the one for a tandem cascade is given in Fig. 4. Some difference between the calculated and original profiles might be attributed to the use of the measured velocity distribution as input for the calculation. This method has been modified by Sun et al. in Ref. [11] by using a boundary-fitted coordinate  $\eta$  (see Eq. (9)) instead of  $\varphi$ . The numerical result of a supercritical cascade together with its modified design is shown in Figs. 5 & 6. In Ref. [12] a method similar to Ref. [10] for  $H_C$ - & I-problems was presented for rotational flow, and a method for removing the density ambiguity is also given. In addition, a rational cascade design procedure consisting of successive use of  $H_C$ - and I-problems is proposed.

1-2. Methods based on image-plane  $\xi\eta$ .

All methods using image-plane  $\xi\psi$  suffer from the shortcoming that singularities appear in the vicinity of blunt leading and trailing edges due to local multivaluedness of the mapping Eq. (1). To circumvent this difficulty, another method for hybrid problems was suggested by Liu [13], where a new image-plane  $\xi\eta$  defined by (Fig. 2)

$$\left. \begin{aligned} \xi &= l \quad [\text{or: } \xi = f(l)] \\ \eta &= \frac{\eta_p - \eta_s}{\varphi_p - \varphi_s} (\varphi - \varphi_s) + \eta_s \end{aligned} \right\} \quad (9)$$

was introduced, where  $\eta_p$  and  $\eta_s$  (the  $\eta$ -values on suction & pressure sides) are given constants. Also in this case four alternative formulations can be derived, but only the integro-differential formulation is given here for reference (Fig. 2b):

$$\oint_{(bc)} \frac{1}{\tau \rho} \left\{ \text{tg} \gamma \frac{\partial \psi}{\partial \xi} - \frac{\sec^2 \gamma}{H_\eta} \frac{\partial \psi}{\partial \eta} \right\} d\xi + \left( H_\eta \frac{\partial \psi}{\partial \xi} - \text{tg} \gamma \frac{\partial \psi}{\partial \eta} \right) d\eta = 2 \frac{\Lambda_u}{r} \Delta \eta \int_{(ab)} H_\eta \sin \zeta \cdot d\xi. \quad (10)$$

$$\frac{\partial \psi}{\partial \xi} = \tau \rho (\Lambda_l \text{tg} \gamma - \Lambda_\varphi), \quad \frac{\partial \psi}{\partial \eta} = \tau \rho H_\eta \Lambda_l \quad (11)$$

$$\rho = \left[ 1 - \frac{1}{2m} (\Lambda^2 - \Lambda_u^2) \right]^m \quad (12)$$

where  $\text{tg} \gamma$  is the slope of the  $\xi$ -coordinate line;  $H_\eta = r \delta \varphi / (\eta_p - \eta_s)$  is the scale factor of the coordinate  $\eta$ ;  $\delta \varphi = \varphi_p - \varphi_s$  is the angular width of the blade channel. We can see that this new image-plane method is particularly advantageous for solving those hybrid prob-

lems with given airfoil thickness (and hence  $H_\eta$  is also known).

Other methods based on  $\xi\eta$ -image plane, using, however, the following second-order PDE formulation, have been presented by Chen et al. [14, 15] and Ge [16]:

$$A_1 \frac{\partial^2 \psi}{\partial \xi^2} + A_2 \frac{\partial^2 \psi}{\partial \xi \partial \eta} + A_3 \frac{\partial^2 \psi}{\partial \eta^2} + A_4 \frac{\partial \psi}{\partial \xi} + A_5 \frac{\partial \psi}{\partial \eta} = B_1 \quad (13)$$

where  $A_1, A_2, A_3, A_4, A_5$  are functions of  $\rho$  and the metric tensor  $g_{22}, g_{23}$ ;  $B_1$  depends on the gradients of entropy and rothalpy, velocity,  $\omega$ ,  $\bar{c}$  and viscous forces. In Ref. [14] the  $H_A$ -problem of potential flow is solved and one of the numerical examples is given in Fig. 7. The figures 8 & 9 taken from the viscous inverse problem solutions of Refs. [15] & [16] respectively show that for the same inlet and outlet flow angles the airfoil in viscous flow is more strongly curved than that in inviscid flow.

## 2) Unified Approach Based on Variational Principles

Basically there have been developed two completely different variational approaches, following a systematic way suggested by Liu [17].

### 2-1. Approach based on VPs in the image plane $\xi\psi$ (Fig. 2)

In Ref. [18] Liu established two families of VPs and generalized VPs in terms of the moment function  $\Omega$  and angular function respectively for the  $H_A$ - and  $H_B$ -problems in the image plane  $\xi\psi$ , which were modified by Liu & Yao to give the VPs for the  $H_C$ -problem in Ref. [19]. Only one of these VPs is given below:

$$J_1(\Omega) = \iint_{(A)} \left\{ \Lambda_u^2 + 2m \left[ 1 - \left( \frac{\kappa}{\tau r} \frac{\partial \Omega}{\partial \xi} \right)^{\frac{1}{\kappa m}} \right] - \left( \frac{1}{r} \frac{\partial \Omega}{\partial \psi} + \Lambda_u \right)^2 \right\} d\xi d\psi + L_\Omega \quad (14)$$

where the boundary integral term  $L_\psi$  takes different form for different problem types. Based on these VPs involving  $\Omega$ , some finite element (FE) solutions to  $H_A$ - and  $H_B$ -problems have been presented in Ref. [20] by Yao et al., from which Figs. 10 & 11 for a cascade on a conical stream surface [78] are taken.

### 2-2. Approach based on VPs with variable domain.

Making use of the functional variation with variable domain, Liu was able to establish three families of VPs and generalized VPs for  $H_A$ -,  $H_B$ - and  $H_C$ -problems in terms of the potential and stream functions  $\Phi$  &  $\psi$  for potential and rotational flows in Refs. [21, 22] and extended them to transonic flow with shocks in Ref. [24]. Moreover, variable-domain VPs using Clebsch variables have been also developed for 2-D transonic rotational channel flow by Liu [25].

Numerical solutions to  $H_A$ - and  $H_C$ -problems based on VPs of Refs. [21, 22] have been obtained by Yan & Liu [22, 23] by means of a new finite element with self-adjusting nodes for numerical realization of the functional variation with variable domain (Figs. 12 & 13).

Perhaps a very attractive merit of this variable-domain approach is that it can be straightforwardly extended to fully 3-D flow.

## 3) The Mean-Streamline Method (MSLM).

This method originally suggested by Wu & Brown [30] was improved in many aspects in China. A survey of this development before 1984 has been presented by Cai [2]. Recent research includes Cai's paper [3] and Wang's paper [4].

## 4) Miscellaneous Approaches.

Several known approaches to inverse design of cascades were improved or modified in China.

### 4-1. Iterative method based on direct problem solver.

Such a method is suggested by Wang in Ref. [26] to solve inverse and various hybrid problems (including  $H_A$  &  $H_C$ ) and extended to viscous flow in Ref. [27] by incorporating a boundary layer solver of integral type. Based on this method, Wang et al. proposed a

quasi-3-D design procedure for impellers [28, 29].

#### 4-2. Time-dependent method.

Starting from the integral form of aerodynamic equations, a finite-volume method for inverse cascade problem is given by Zhou & Zhu [31].

#### 4-3. Hodograph method.

It was improved in the transonic region by incorporating some analytical nozzle solutions and generalized to cascade flow along general streamsheet of revolution independently by Chen [32] and Yao [33].

### IV. INVERSE & HYBRID PROBLEMS OF $S_2$ -FLOW IN TURBOMACHINES

Similarly to  $S_1$ -flow, the image-plane approach and the VP-based approach mentioned above can be applied to  $S_2$ -flow as well.

#### 1) Unified VP-Based Approach.

Starting from the basic equations of Wu's  $S_2$ -flow model [1, 79], first complete VPs and generalized VPs for the semi-inverse problem were established by Liu [34] and the corresponding FE solutions were obtained by Qin et al. [35]. Inverse and hybrid problems of  $S_2$ -flow were formulated in a unified manner by VPs with variable domain by Liu [36] and by VPs in an image-plane  $\xi\psi$  by Cai & Liu [37], which have been generalized to flow of pure substance by Xu [38]. In Ref. [39] VPs for hybrid problems of axisymmetric channel flow were derived by Tao & Liu.

#### 2) Universal Image-Plane Approach.

Using an image plane  $\xi\psi$  and given a distribution of circulation  $V_\phi r$  on  $S_2$ -surface, Ge presented a method for solving the complete inverse problem and a hybrid problem (with unknown hub (or casing) wall, see Table II), thereby a second-order PDE for  $r(\xi, \psi)$  was derived and solved [40].

### V. INVERSE & HYBRID PROBLEMS OF FULLY 3-D ROTOR-FLOW

For these problems three approaches have been developed in China.

#### 1) Method of Mean-Stream Surface.

It was originally suggested by Wu in 1952 [1] by a Taylor-series expansion of flow parameters in the azimuthal direction as an extension of MSLM [30, 2]. It was improved, numerically elaborated and applied to design by Zhao et al. in Refs. [41, 42], where an annular constraint condition is set up, which must be satisfied to ensure that the hub/casing walls are axisymmetric.

#### 2) Universal Image-Space Approach.

In Ref. [43] Liu developed a universal image-space theory of hybrid problems for fully 3-D potential flow, which is a generalization of the image-plane approach of Ref. [13]. Applying tensor calculus and Stokes theorem, the basic flow equations are transformed into the following integro-differential equation system for the stream functions  $\psi_1$  and  $\psi_2$  in the image space  $\xi^1 \xi^2 \xi^3$  (Fig. 14b):

$$\oint_{(c)} \left( g_{ij} V^j + \Lambda_u r \frac{\partial \varphi}{\partial \xi^i} \right) d\xi^i = 0 \quad (15)$$

$$\sqrt{g} \rho \{V^1, V^2, V^3\} = \left\{ \frac{\partial(\psi_1, \psi_2)}{\partial(\xi^2, \xi^3)}, \frac{\partial(\psi_1, \psi_2)}{\partial(\xi^3, \xi^1)}, \frac{\partial(\psi_1, \psi_2)}{\partial(\xi^1, \xi^2)} \right\} \quad (16)$$

and Eq.(5), where  $V^i$  are the contravariant components of the velocity  $\vec{A}$  in a body-fitted

nonorthogonal curvilinear coordinate system  $\xi^i$  (Fig.16a). Similarly, a corresponding potential function formulation by integro-differential equations of this theory has been also presented by Liu et al. [44].

A similar method for solving 3-D hybrid problems was put forth by Chen et al. [45], using, however, a second-order PDE formulation:

$$\frac{\partial}{\partial \xi^i} \left( \sqrt{g} \rho g^{ij} \frac{\partial \Phi}{\partial \xi^j} \right) - \frac{\partial}{\partial \xi^2} \left( \sqrt{g} g^{22} \rho \Lambda_u \right) = 0 \quad (17)$$

This equation was solved numerically by the method AF2, the multigrid technique and the artificial density in the transonic region. To greatly simplify the numerical solution, the inverse problem is modified in such a way that the physical contravariant velocity components  $A^i$  (assuming that  $\xi^1$ -coordinate is the streamlike line) rather than the fully velocity  $A$  is prescribed on the blade surface. An axial compressor rotor was redesigned and improved by this method as shown in Figs.15 & 16.

### 3) Unified Variable-Domain Variational Approach

The variable-domain variational approach [21, 22] has been extended by Liu to hybrid problems for fully 3-D incompressible [46], compressible [47] and transonic [48] flows in rotors. Only one of the VPs is given below for reference:

$$J_2(\Phi, A_b^{**}, A_{2d}) = \frac{1}{\kappa} \iiint_{(V)} \left\{ 1 - \frac{1}{2m} \left[ (\nabla \Phi)^2 - \frac{2\Lambda_u}{r} \frac{\partial \Phi}{\partial \varphi} \right] \right\}^{xm} dV + L. \quad (18)$$

where the boundary integral term  $L$  takes different form for different problem type. Note that the variable-domain variation of  $J_2$  should be taken at the unknown boundaries  $A_b^{**}$  (blade surface) and  $A_{2d}$  (free trailing vortex sheet). Corresponding numerical solutions to incompressible ( $H_A \times D$ )-problem of Mizuki's centrifugal compressor [51] and to compressible ( $[H_c + D] \times D$ )-problem of an axial turbine stator have been obtained by a novel FE with self-adjusting nodes in Refs. [49] and [50] respectively and are shown partly in Figs.17 & 18.

## VI. OPTIMIZATION OF AERODYNAMIC DESIGN OF BLADING.


### 1) Optimization of $S_2$ -Flow.

A basic and very important problem in this context is the optimal flow type (i.e. optimal radial distribution of flow) in bladings. This problem was first studied by a variational method by Liu [52] and later by Xue [53] and Lu [54]. Recently, this problem was treated by an optimal control method by Gu & Miao [55], so that various inequality design constraints can be accounted for.

### 2) Optimization of 2-D Cascades.


Theory of optimization of cascade profile shape can be founded on the basis of one of the following flow models.

#### i) Simplified model (LeFoll, Citavy)





ii) Refined model (Liu[57-59])



Perhaps, a third, most accurate flow model based on Navier-Stokes equations incorporating some turbulence models should be also tried.

Two possible mathematical models (formulations) can be used here, namely: a) mathematical programming problem, b) optimal control problem.

2-1. Optimization based on the simplified flow model.

The problem of determining the optimal velocity distribution along the suction side was formulated as an optimal control problem with some inequality design constraints (e.g. separation-free, maximum or minimum velocity limit, etc) and solved by a heuristic grapho-analytical method by Liu[56,63]. This approach is followed by Wang[60] in the design of an axial ventilator. Having calculated the optimal velocity distribution along suction side and specified a reasonable airfoil thickness distribution, a Hc-problem was solved by the image-plane method given in Refs. [5,6] to yield the optimal airfoil shape. A similar method, with some modifications, for optimizing 2-D compressor cascade was presented by Hua & Chen[61], where a method for estimating the airfoil circulation was given and the optimal airfoil shape was obtained by MSLM[20,30].

The optimal velocity distribution along the suction side on a general streamsheet of revolution was obtained by Zou[62], using Mager's transformation of turbulent boundary layer.

In Ref. [63] some generalizations of the LeFoll's optimization theory of blades were given by Liu & Wu to accommodate different objective functionals with more general constraints.

2-2. Optimization based on refined model.

In Refs. [57,59] Liu suggested a new theory of optimal 2-D cascades based on the above-mentioned refined flow model, in which this problem has been formulated as an optimal control problem with multiple inequality design constraints on control- and phase-spaces. Two typical optimal control problems were considered: cascade with minimal losses and cascade with maximal loading (circulation), and a duality theorem between them has been proved theoretically, so that it is sufficient to study only the cascade with minimal losses. This theory has been generalized to 2-D compressible flow and to a 3-D axial-flow rotor by Liu[58]. The essential feature of this theory lies in its capability of handling a wide variety of practical design constraints (from stress, vibrational, cooling and technological considerations) in a unified manner so as to make the optimal solution surely feasible and suitable for use in practice.

2-3. Local optimization of transonic cascades

Jiang et al. suggested a numerical method for weakening shocks in transonic cascades by local optimization of airfoil shape[64]. The airfoil contour segment near the shock is represented by a cubic parabola with free coefficients  $a_1, a_2, a_3, a_4$ . Then the Mach number just before the shock  $M_s$  is minimized with respect to  $a_i$ .

3) Optimal Design of Diffusers.

The optimal design of 2-D diffusers was considered by Gu & Ji[66] using optimal

control for searching optimal wall shape that maximizes the pressure recovery of diffuser. A more general optimization problem of diffuser was put forth by Liu et al. in Ref. [65], where not only the wall shape but also the wall suction distribution that maximize the pressure recovery without boundary layer separation are sought by optimal control method.

An 1-D optimal design method for turbine annular axial-radial exhaust diffuser was presented by Ling & Jin [67] based on an approximate loss model. The pressure recovery coefficient of an optimal diffuser designed in this way has been shown higher than the conventional one by 7% by experiment.

#### 4) Other Optimization Problems.

Making use of the Parson's number and the concept of optimal reaction degree, Yao presented a method for optimizing aerothermodynamic parameters in one-and multi-stage steam turbine design. Some guidelines for optimal design of long twisted blades are given.

In Ref. [69], based on the diffusion factor and equivalent diffusion ratio, the optimal solidity problem of 2-D compressor cascades is formulated by Liu as nonlinear programming problems, whose analytical solution in form of simple formulae is very convenient for practical use.

A simple approximate method for determining the optimal relative azimuthal position of two blade rows in tandem cascades is suggested by Wu & Feng [70] using a simple total pressure loss model.

### VII. MISCELLANEOUS INVERSE, HYBRID & OPTIMIZATION PROBLEMS IN ENGINEERING SCIENCES

In Ref. [71] the finite element method is generalized by Liu & Zhao via variable-domain variations in such a way that the nodes are movable. It allows both optimal grid and flow field to be cogenerated simultaneously and naturally using directly the VPs of aerodynamic problems.

The inverse problem of heat conduction with unknown boundary was handled by Liu & Zhang [72] using Ritz's and FEM based on Variable-domain VPs. An alternative method for solving this problem was suggested by Liu [73] by introducing an image plane  $T\psi'$  ( $T$  and  $\psi'$  stand for transformed temperature and heat stream function respectively). An interesting invariance property of the nonlinear inverse problem solution with respect to variable conductivity is pointed out. An example is solved by FEM based on a pair of complementary extremum principles.

The inverse and hybrid problems of free surface flow under gravity over a dam are posed and handled by Liu via VPs in an image-plane  $\xi\psi$  [74] and VPs with variable domain in the physical plane [75, 76].

In Ref. [77] Liu suggested a novel problem in gear theory—optimal meshing (i.e. optimal tooth profile) of spur gears and its variational theory. An analytical solution to the optimal meshing with minimal friction losses has been obtained and it has been revealed that the cycloidal gearing with radial tooth profile on the lower half tooth height used widely in watches and clocks can be regarded approximately as a practical gearing with maximal efficiency.

### VIII. CONCLUDING REMARKS

Research on inverse, hybrid and optimization problems is of great theoretical as well as practical importance in engineering sciences. To our experiences, the three new approaches (image-space approach and VP-based approach, especially its variable-domain variational variat, for inverse and hybrid problems; optimization approach based on optimal control) suggested and intensively developed in China in the last two decades have proved to be efficient tools for inverse design and optimization not only in turbomachinery aerodynamics in particular but also in engineering sciences in general and deserve further development and application to practice. Design engineers and industry will surely benefit a lot from them, if a complete set of computer codes based on these

approaches can be finished and organized into a computerized automated interactive design system (something like that of Ref. [8]).

## REFERENCES

- [1] Wu, Chung-Hua, A general theory of 3-D flow in subsonic and supersonic turbomachines of axial-, radial- and mixed-flow types, NACA TN 2604(1952)
- [2] Cai, R., A summary of developments of the mean-streamline method in China, ASME J. Engrg for GT & Power, 106(1984) pp.300-305
- [3] Cai, R., An engineering method for solving axial flow cascade inverse problem, ASME paper 87-GT-147(1987)
- [4] Wang, Zhengming, A method for aerodynamic design of blades in quasi-3D calculation of turbomachines, ASME J. of Turbomachinery, 110, (1988) pp.181-186
- [5] Liu, Gao-Lian, A universal computer method for solving inverse cascade flow problem with prescribed velocity distribution (in Chinese), Research Report, Institute of Mechanics of Chinese Academy of Sciences, Beijing, China, 1964.
- [6] Liu, Gao-Lian & Tao, Cheng, A universal image-plane method for inverse & hybrid problems of compressible cascade flow on arbitrary streamsheet of revolution: Part I--Theory, Numerical Methods in Laminar & Turbulent Flow, Vol. 6, C. Taylor et al. (ed.), Pineridge Press, U.K., 1989, pp. 1343-1354. (or: Power Engrg (China), No. 2 (1981) pp. 20-29).
- [7] Chen, Kang-min et al., A universal image-plane method for inverse and hybrid problems of compressible cascade flow on arbitrary streamsheet of revolution: Part II--Num. Solution. *ibid*, pp.1355-1366.
- [8] Liu, Gao-Lian & Zhang, Dao-Fang, The moment function formulation of inverse & hybrid problems for blade-to-blade compressible viscous flow along axisymmetric streamsheet. Numerical Methods in Laminar & Turbulent Flow, Vol.6, C. Taylor et al. (ed.) Pineridge Press, U.K., 1989, pp.1289-1300. (or: Liu, Gao-Lian, Chinese J. of Engrg Thermophys. 3 (1982) pp.138-144 (in Chinese))
- [9] Shen, M.Y. & Ma, Y.L., Direct-inverse problem of 2-D cascades in transonic flow (in Chinese), Acta Mechanica Sinica, 15, 1 (1983) pp.1-6.
- [10] Chen, Naixing, Zhang Fengxian, A generalized numerical method for solving direct, inverse and hybrid problems of blade cascade flow by using streamline-coordinate equation, ASME Paper 87-GT-29(1987).
- [11] Sun, X.Y. et al., A unified method for solving aerodynamic cascade design problems on an arbitrary surface of revolution, ASME Paper 88-GT-118(1988)
- [12] Ge, Manchu et al., A method for solving transonic  $S_q$ -Stream surface with a stream function equation (in Chinese), Chinese J. Engrg Thermophys. 8(1987) pp.31-38.
- [13] Liu, Gao-Lian, A new approach to some hybrid aerodynamic problems of airfoil cascades on a general streamsheet of revolution (in Chinese), Chinese J. Engrg Thermophysics. 5, 1(1984) pp.27-32.
- [14] Chen, Naixing & Li Weihong, A new method for solving aerodynamic hybrid problem of profile cascade on S stream surface of revolution by employing stream function equation expressed with non-orthogonal coordinate system. Int'l J. Num. Methods in Engrg, 22, (1986) pp.456-479.
- [15] Chen, Naixing et al., A inverse problem solution method for the blade cascade flow on streamsurface of revolution, ASME Paper 86-GT-159(1986)
- [16] Ge, Manchu et al., A method for solving subsonic and transonic viscous inverse problem of cascade with stream function equations (in Chinese), Chinese J. Engrg Thermophys. 8(1987) pp.243-245.
- [17] Liu, Gao-Lian, A systematic approach to the search and transformation for VPs in fluid mechanics with emphasis on inverse and hybrid problems, Chinese J. Engrg Thermophysics (English ed.) 2, 4(1990), Allerton Press, New York.
- [18] Liu, Gao-Lian, VPs and generalized VPs for the hybrid aerodynamic problem of airfoil

- cascade on an arbitrary streamsheet of revolution: Part(I), *Scientia Sinica*, 23, 10 (1980) pp. 1339-1347; Part(II), *Chinese J. of Engrg Thermophysics*, 2, 4(1981) pp.335-342.
- [19] Liu, Gao-Lian & Yao, Zheng., VPs & Generalized VPs for the hybrid aerodynamic problem of airfoil cascades on an arbitrary stream sheet of revolution: Part(III), *Proc. 6th Int'l Symp. FEM in flow Problems*, Antibes, France, June 1986, pp.137-142.
  - [20] Yao, Zheng et al., Variational FE calculation for hybrid aerodynamic problem of cascades on an arbitrary streamsheet of revolution, *Comput'l Methods in Turbomachinery*, IMechE, 1984, U.K. pp.237-245.
  - [21] Liu, Gao-Lian, VP families for hybrid problems of blade-to-blade flow along axisymmetric streamsheet: A unified variable-domain approach(in Chinese), *Acta Aerodynamica Sinica*, 3, 3(1985) pp.24-32.
  - [22] Liu, Gao-Lian & Yan, Shan, A unified variable-domain variational approach to hybrid problems of compressible blade-to-blade flow, *ASME Paper 91-GT-169*(1991)
  - [23] Yan, Shan & Liu, Gao-Lian, Variational FEM with variable domain for solving type 'A' hybrid problem of blade-to-blade compressible flow along an arbitrary streamsheet of revolution, *Exper'l & Comput'l Aerothermodynamics of Internal Flow* (Proc. 1st Int'l Symp.) N.X.Chen & H.D.Jiang (ed.) World publ. Corp., Beijing, China, pp.457-463
  - [24] Liu, Gao-Lian, VPs for hybrid problems of transonic cascade flow along axisymmetric streamsheet: A unified variable-domain approach. *Proc. 4th Int'l Symp. on Refined Flow Modeling and Turbulence Measurements*, Sept. 1990, Wuhan, pp. 175-181.
  - [25] Liu, Gao-Lian, A variable-domain variational theory using Clebsch variables for hybrid problems of 2-D transonic rotational flow: Pt I ---Planar Channel design. *Proc.Int'l Conf. on Fluid Mechanics*, July 1977, Beijing, China, pp. 314-319.
  - [26] Wang, Zhengming, Inverse design calculations for transonic cascades, *ASME Paper 85-GT-6* (1985)
  - [27] Wang, Zhengming, A numerical method for solving the inverse problem of cascade viscous flow, *Proc. 1st ISAIF*, July, 1990, Beijing, China, pp.482-488.
  - [28] Wang, Zhengming et al., An improved method for aerodynamic design of centrifugal impeller blades, *ASME Paper 91-GT-76* (1991)
  - [29] Wang, Zhengming et al., A quasi-3D design method of transonic compressor blades with the function of improving velocity distribution. *ISABE Paper 89-7089*, the 9th Int'l Symp. on Air-Breathing Engines(1989).
  - [30] Wu, Chung-hua & Brown, C.A., A theory of the direct and inverse problems of compressible flow past cascade of arbitrary airfoils, *J.A.S.*, 19, 3(1952).
  - [31] Zhou, Xinhai & Zhu Fangyuan, Finite volume method to solve the inverse problem for transonic flow in cascades(in Chinese), *Chinese J. Engrg Thermophys.*, 6, 4 (1985) pp. 331-335.
  - [32] Chen, Zuoyi, The hodograph method for design of transonic turbine cascade in revolutionary surface(in Chinese), *Chinese J. Engrg Thermophys.*, 3, 4 (1982) pp.353-356.
  - [33] Yao, Zheng, A hodograph-based FEM for 2-D transonic cascades and its generalization to cascades on arbitrary streamsheet of revolution (in Chinese). Master Thesis, Shanghai Inst. of Mech. Engrg, 1982.
  - [34] Liu, Gao-Lian, VPs and generalized VPs for semi-inverse problem of compressible flow along S2-stream surface in axial-flow Turbomachinery, *J. Shanghai Institute of Mechanical Engrg*, 3, 1 (1981) pp.1-14.
  - [35] Qin, Ren, et al., A new variational FE computation for the aerodynamic inverse problem in turbines with long blades, *ASME J. Turbomachinery*, 110, 4 (1988) pp.545-548.
  - [36] Liu, Gao-Lian, A unified variable-domain variational theory of hybrid problems for compressible S-flow in mixed-flow turbomachinery, *Proc. 1987 Tokyo Int'l Gas Turbine Congress*, Oct. 1987, Japan, Vol.II, pp. 259-264.(Paper 87-Tokyo-IGTC-34).
  - [37] Cai, Rong-Qian & Liu, Gao-Lian, Families of VPs for inverse & H hybrid problems of an S2 streamsheet in mixed-flow turbomachines, *Int'l J.Heat and Fluid Flow*, 9, 3(1988) pp.302-307.
  - [38] Xu, Hong-Yi, Families of VPs for semi-inverse and H hybrid problems on a S2-

- streamsheet for fluids of pure substance (in Chinese). *Acta Aerodynamica Sinica*, 8, 1 (1990) pp.98-103.
- [39] Tao, Cheng & Liu, Gao-Lian, VPs for hybrid problem of axisymmetric compressible channel flow using an image plane, *Proc. 3rd Japan-China Joint Conf. on Fluid Machinery*, April 1990, Osaka, Japan.
  - [40] Ge, Manchu et al., A new approach to the calculation of S2 stream surface with full inverse and hybrid methods for turbomachine, *ASME Paper 88-GT-262*(1988).
  - [41] Zhao, Xiao-lu et al., A simple method for solving 3-D inverse problems of turbomachine flow and the annular constraint condition, *ASME J. of Engrg for Power*, 107 (1985) pp.293-300.
  - [42] Zhao, Xiao-lu, Qin Li-Sen, An approximate 3-D aerodynamic design method for centrifugal impeller blades, *ASME Paper 89-GT-73*(1989).
  - [43] Liu, Gao-Lian, A general image-space theory of hybrid problems for fully 3-D compressible flow in turbo-rotors:(I) stream-function formulation, *Comput'l Methods in Flow Analysis* (Proc. of Int'l Conf., Okayama, Japan, Sept. 1988), H.Niki and M. Kawahara (ed.), Okayama univ. of Science, pp. 936-942. (or: *Chinese J. Engrg Thermophysics*, 6, 1(1985) pp.40-45)
  - [44] Liu, Gao-Lian et al., Ditto, Part (II) Axial-flow, potential function formulation(in Chinese), *Chinese J. Engrg Thermophys.*, 9, 4(1988) pp. 331-333.
  - [45] Chen, Naixing et al., A numerical method for solving aerodynamic hybrid problem of fully 3-D flow in turbomachinery, *Proc. 1st Int'l Symp. on Exper'l & Comput'l Aerothermodynamics of Internal Flows*, July 1990, Beijing, China, pp. 441-448.
  - [46] Liu, Gao-Lian, A unified theory of hybrid problems for fully 3-D incompressible rotor flow based on VPs with variable domain, *ASME J. Engrg for GT & Power*, 108, 2(1986) pp.254-258.
  - [47] Liu, Gao-Lian, A variational theory of hybrid problems for fully 3-D compressible rotor-flow: A unified variable-domain approach, *Comput'l Fluid Dynamics*, G. d. V. Davis & C. Fletcher, (ed.), North-Holland, 1988, pp.473-480.
  - [48] Liu, Gao-Lian, Variational formulation of hybrid problems for fully 3-D transonic flow with shocks in rotor, *Proc.3rd Int'l Conf. on Inverse Design Concepts and Optimization in Engrg Sciences*, Oct.1991, Washington, D.C., USA.
  - [49] Yan, Shan & Liu, Gao-Lian, Variational FEM with variable domain for solving hybrid problems of 3-D incompressible rotor flow, *Exper'l & Comput'l Aerothermodynamics of Internal Flow*(Proc. 1st Int'l Symp.), Chen, N.X. & Jiang, H.D.(ed.), World Publ. Corp., Beijing, China, 1990, pp.449-456.
  - [50] Yan, Shan and Liu, Gao-Lian, Variable-domain FEM based on VPs for solving hybrid problems of fully 3-D compressible rotor-flow, *Proc. 1991 Yokohama Int'l Gas Turbine Congress*, Sept. 1991, Japan.
  - [51] Mizuki, S. et al., Investigation concerning the blade loading of centrifugal impeller, *ASME Paper 74-GT-143*(1974)
  - [52] Liu, Gao-Lian, On the optimal type of flow pattern in turbomachinery (in Chinese), *Research Note*, Institute of Mechanics of Chinese Academy of Sciences, Beijing, China, 1963.
  - [53] Xue, Ming-lun, Optimum aerodynamic design problem of axial turbomachines(in Chinese), *Research Report*, Institute of Mechanics of Chinese Academy of Sciences, Beijing, China, 1975.
  - [54] Lu, Wen-can, The theory and experiment of optimum flow distribution for low pressure axial fans, *Proc. 2nd China-Japan Joint Conf. on Fluid Machinery*, Oct. 1987, Xi'an China, pp.481-489.
  - [55] Gu, Chuan-Gong & Miao, Yong-Miao, Blade design of axial-flow compressors by the method of optimal control theory, *ASME Pap.* 86-GT-182, 86-GT-183(1986)
  - [56] Liu, Gao-Lian & Wang, Jiasheng, *Fundamentals of Aerodynamic Theory of Turbomachinery* (in Chinese), Machinery Press, Beijing, China, 1980.
  - [57] Liu, Gao-Lian, A new theory of 2-D cascades optimized aerodynamically via a generalized maximum principle: Pt(I) & Pt(II) (in Chinese), *Acta Mechanica Sinica*,

- 12, 4(1980) pp.337-346; 14, 2(1982) pp.122-128.
- [58] Liu, Gao-Lian, Aerodynamic optimization theory of a 3-D axial-flow rotor-blading via optimal control. Proc. 6th Int'l Symp. on Air-Breathing Engines, June 1983, Paris, pp. 313-318 (AIAA Paper 83-7037)
- [59] Liu, Gao-Lian, Aerodynamic theory of 2-D cascades optimized via optimal control, Numerical Methods in Laminar and Turbulent Flow, Vol.5, C.Taylor et al.(ed.), Pineridge Press, U.K. 1987. pp.1739-1749.
- [60] Wang, Xue-Jin, Optimal design method for cascades in an axial ventilator(in Chinese), Master Thesis, North-East University of Technology, China, 1983.
- [61] Hua, Yaonan & Chen Naixing, Optimization of the plane compressor blade aerodynamic design, Proc. 6th Int'l Symp. on Air-Breathing Engines, June 1983, Paris, pp.487-495.
- [62] Zou, Zi-xiong, Method of calculation of optimal velocity distribution on arbitrary stream surface of revolution for compressible flow in cascades of turbomachinery. Chinese J. Engrg Thermophysics, 1, 4(1980) pp.341-347.
- [63] Wu, Bao-ren & Liu, Gao-Lian, Progress in aerodynamic optimization theory of turbomachine blading(in Chinese), Advances in Mechanics, 14, 2(1984) pp.161-174.
- [64] Jiang, H.X. et al., A numerical method to weaken shocks in transonic cascades. Proc. 1983 Tokyo Int'l Gas Turbine Congress, Japan.
- [65] Liu, Gao-Lian et al., Theory of optimum design of 2-D diffusers with optimal boundary layer control, Proc.6th Int'l Symp. FEM in Flow Problems, Antibes, France, June, 1986, pp.39-43.
- [66] Gu, Chuan-gang, Ji Yong-ming, Theoretical analysis of the optimal shape for 2-D diffuser with incompressible flow. Proc. 2nd China-Japan Joint Conf. on Fluid Machinery, Oct. 1987, Xi'an, China, pp.416-422.
- [67] Ling, Zhiguang & Jin Juanqian, Design optimization of turbine annular axial-radial exhaust diffuser and experimental verification(in Chinese), Chinese J. Engrg Thermophys., 6, 3 (1985) pp.245-248.
- [68] Yao, F.S, Method of calculating optimal parameters of through-flow components in stream turbines(in Chinese), Chinese J. Mech. Engrg, (1979) No.2
- [69] Liu, Gao-Lian, Simple formulae for optimal solidity of 2-D compressor cascades based on diffusion concept. ASME Paper 91-GT-308 (1991)
- [70] Wu, GuoChuan & Feng, Qi, Optimization of the arrangement of the front & rear blade rows of a tandem blade cascade, Paper 87-Tokyo-IGTC-19(1987)
- [71] Liu, Gao-Lian & Zhao, Yi-Hua, Generalized FEM via variable-domain variations: Cogeneration of optimal grid and flow field, Proc. 4th National Conf. on Fluid Mechanics, April 1989, Beijing, China.
- [72] Liu, Gao-Lian & Zhang, Dao-Fang, Numerical methods for solving inverse problem of heat conduction with unknown boundary based on VPs with variable domain, Num.Methods in Thermal Problems, Vol. 5, R.W.Lewis et al.(ed.), Pineridge Press, U.K., 1987.
- [73] Liu, Gao-Lian, A Novel variational formulation of inverse problem of heat conduction with free boundary on an image plane, Num. Methods in Thermal Problems, Vol.6, R.W. Lewis et al.(ed.), Pineridge press, U.K., 1989, pp.1712-1720.
- [74] Liu, Gao-Lian, New VP families for direct, inverse and hybrid problems of free surface gravity flow over a spillway. Turbulence Measurements & Flow Modeling, C.J. Chen et al.(ed.), Hemisphere, Washington, 1987. pp.323-332.
- [75] Liu, Gao-Lian, The hybrid problem of free-surface gravity spillway flow treated by VPs with variable domain: (I) Potential function formulation, Proc. 3rd Int'l Symp. Refined Flow Modeling & Turbulence Measurements, July 1988, Tokyo, Japan.
- [76] Liu Gao-Lian, The hybrid problem of free-surface gravity spillway flow treated by VPs with variable domain: (II) Stream function formulation, Proc. 7th Int'l Conf. on FEM in Flow Problem, 1989, Alabama, USA.
- [77] Liu, Gao-Lian, A variational theory of optimal meshing of spur gears (in Chinese), J. of Shanghai Institute of Mech. Engrg, 2, 2(1980) pp.25-42
- [78] Wilkinson, D.H., Calculation of Blade-to-Blade flow in a turbomachinery by stream-line curvature, ARC RM 3704 (1970)

- [79] Wu, Chung-Hua, 3-D turbomachine flow equations expressed with respect to nonorthogonal curvilinear coordinates and methods of solution, Proc. Third Int'l Symp. on Air-Breathing Engines, München, Germany, (1976) pp. 233-252.
- [80] Hefez, M., Lovell, D., Numerical solution of transonic stream function equation, AIAA-J., 21 (1983) pp.327-335.
- [81] Thomas, K.M. & Piendel, J.J., An automated interactive design system for advanced gas turbines, ASME, Paper 74-GT-82(1974).




Fig.1 Definition of Symbols for fully 3-D hybrid problems




Fig.2 Cascade flow and its image plane




Fig.3 Image-plane solution by  
moment function




Fig.4 Tandem cascade profiles by an  
inverse solution




Fig.5 Modified distribution of  
Mach number




Fig.7 Cascade profile obtained by  $H_A$ -  
problem solution




Fig.6 Comparison of profiles corresponding  
to Fig.5




Fig.8 Viscous effect on airfoil shape






Fig. 9 Viscous effect on airfoil shape






Fig. 10 FE solution of  $H_A$ -problem



(a)



(b)

Fig. 11 FE solution of  $H_B$ -problem




Fig. 12 Airfoil shape by FE solution of  
a  $H_C$ -problem






Fig. 13 Airfoil shape by FE solution of  
a  $H_A$ -problem



a) Physical space



b) Image space

Fig.14 3-D rotor flow and its image space







Fig.15 Distribution of  $V^1$  over blade surface

Fig.16 The shape of the blade after and before the modification

Fig.17 FE solution of  $(H_A \times D)$ -problem of a centrifugal compressorFig.18 FE solution of  $[(H_c + D) \times D]$ -problem of an axial turbine statorORIGINAL DATA IS  
OF POOR QUALITY

