

NASA Technical Memorandum 105420

1N-32
68744
p.5

Advanced Communication Technology Satellite (ACTS) Multibeam Antenna Analysis and Experiment

Roberto J. Acosta, Jeffrey M. Larko, and Adabelle Narvaez
*Lewis Research Center
Cleveland, Ohio*

and

Alan R. Lagin
*Analex Corporation
Brook Park, Ohio*

Prepared for the
1992 AP-S International Symposium
sponsored by the Institute of Electrical and Electronic Engineering
Chicago, Illinois, July 18-25, 1992



(NASA-TM-105420) ADVANCED COMMUNICATION
TECHNOLOGY SATELLITE (ACTS) MULTIBEAM
ANTENNA ANALYSIS AND EXPERIMENT (AAE) 1992
C10L 171

1992-17147

Unclass

6/12

ADVANCED COMMUNICATION TECHNOLOGY SATELLITE (ACTS) MULTIBEAM ANTENNA ANALYSIS AND EXPERIMENT

Roberto J. Acosta, Jeffrey M. Larko and Adabelle Narvaez
National Aeronautics and Space Administration
Lewis Research Center
Cleveland, Ohio 44135

Alan R. Lagin
Analex Corporation
Brook Park, Ohio 44142

Abstract

One of the most important aspects of a satellite communication system design is the accurate estimation of antenna performance degradation (Pointing error, end coverage gain, peak gain degradation, etc. are of main concern). The thermal or dynamic distortions of a reflector antenna structural system can affect the far-field antenna power distribution in at least four ways. 1. The antenna gain is reduced, 2. The main lobe of the antenna can be mispointed thus shifting the destination of the delivered power away from the desired locations 3. The main lobe of the antenna pattern can be broadened thus spreading the RF power over a larger area than desired 4. The antenna pattern sidelobes can increase thus increasing the chances of interference among adjacent beams of a multiple beam antenna system or with antenna beams of other satellites. The in-house developed NASA Lewis Research Center thermal/structural/RF analysis program was designed to accurately simulate the ACTS in-orbit thermal environment and predict the RF antenna performance. The program combines well established computer programs (TRASYS, SINDA and NASTRAN) with a dual reflector-physical optics RF analysis program. The ACTS multibeam antenna configuration is analyzed and several thermal cases are presented and compared with measurements (pre-flight).

Introduction

The ACTS multibeam antenna system (figure 1.) consists of a separate Ka-band (30/20 GHz) antennas, each with horizontal and vertical polarization subreflectors. The offset Cassegrain antenna system provides two hopping spot beam families (east and west) plus three fixed spot beams. The east and west beam families are discriminated by polarization. The east family of beams comprises an east scan sector and additional spot beams for isolated-location coverage outside the sector. The west family comprises a west scan sector, additional spot beams for isolated-location coverage outside the sector, and a steerable spot beam. Within the beams access will be by demand-assigned multiple access (DAMA) using time division multiple access (TDMA) transmission. The multibeam communication center package provides the means for receiving, processing, switching, amplifying, and transmitting signals that carry high-speed digital communication traffic.

ACTS Multibeam Antenna Configuration (transmitting case)

The ACTS dual reflector (front sub-reflector) geometry (figure 2) is analyzed. This configuration consists of parabolic main reflector with a focal length of 132 inches, and hyperbolic sub-reflector (cassegrian configuration). The feed is located at the Cleveland spot beam. The feed is modeled with measured E and H plane far-field antenna pattern.

Discussion and Results

The ACTS MBA transmitting configuration was simulated using the thermal/structure/dual reflector-physical optics computer program. Several cases are presented and its antenna performance calculated. One of the limitation of our model is that it does not include the grided characteristics of the front sub-reflector. It assumes that the sub-reflector is a solid perfect conductor. Also the points generated by thermal/structure portion of the analysis program are interpolated by using either polynomial spline algorithm (3th order) or a 4th order polynomial. The ideal far-field antenna performance for the Cleveland spot beam (case 1) is shown in figure 3. The surface points were generated using analytic equations. Its calculated peak directivity is 55.45 db. Figure 4 shows the simulated pre-flight (case 2) antenna far-field pattern. In this case the surface points are measured with a main reflector rms of 5 mils. The calculated directivity was 54.45 db. Case 3 simulates an in-orbit case representing the spacecraft max cold thermal cycle. The antenna performance is presented in figure 5. The calculated directivity is 54.01 db. For comparison purposes the measured pre-flight antenna pattern for the Cleveland spot beam is presented in figure 6.

All the antenna pattern are very similar in shape to the measured pattern, slight differences in gain (less 0.5 db) and sidelobe level (1-3db) are observed. The discrepancies are mainly due to sub-reflector modeling, feed modeling and surface errors interpolation. The overall simulation results were in agreement with the measurements. The thermal/structure/RF analysis program could provide an indirect means of verifying in-orbit antenna performance.

References

1. Acosta, R.J.; Active Feed Array Compensation for Reflector Antenna Surface Distortions, NASA TM-100826, June 1988.
2. Sharp, G.R.; Acosta R.J.; Bobisnsky, E.A. and Shaker, F.J.; A Conceptual System Design for Antenna Thermal and Dynamic Distortion Compensation Using Phased Array Feed. Second NASA/DOD Control/Structures Interaction Technology Conference, Colorado Spring, CO, November 17-19, 1987.




Figure 1. The ACTS multibeam antenna system




Figure 2. ACTS MBA transmitting reflector geometry




Figure 3. Simulated ideal case far-field antenna pattern




Figure 4. Simulated pre-flight antenna far-field antenna pattern




Figure 5. Simulated Thermal distortion case far-field antenna pattern




Figure 6. Measured pre-flight antenna case far-field antenna pattern

REPORT DOCUMENTATION PAGE

Form Approved

OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE 1992	3. REPORT TYPE AND DATES COVERED Technical Memorandum	
4. TITLE AND SUBTITLE Advanced Communication Technology Satellite (ACTS) Multibeam Antenna Analysis and Experiment			5. FUNDING NUMBERS WU-679-40-00	
6. AUTHOR(S) Roberto J. Acosta, Alan R. Lagin, Jeffrey M. Larko, and Adabelle Narvaez				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) National Aeronautics and Space Administration Lewis Research Center Cleveland, Ohio 44135-3191			8. PERFORMING ORGANIZATION REPORT NUMBER E-6835	
9. SPONSORING/MONITORING AGENCY NAMES(S) AND ADDRESS(ES) National Aeronautics and Space Administration Washington, D.C. 20546-0001			10. SPONSORING/MONITORING AGENCY REPORT NUMBER NASA TM-105420	
11. SUPPLEMENTARY NOTES Prepared for the 1992 AP-S International Symposium sponsored by the Institute of Electrical and Electronic Engineering, Chicago, Illinois, July 18-25, 1992. Roberto J. Acosta, Jeffrey M. Larko, and Adabelle Narvaez, NASA Lewis Research Center; Alan R. Lagin, Analex Corporation, 3001 Aerospace Parkway, Brook Park, Ohio 44142. Responsible person, Roberto J. Acosta, (216) 433-6640.				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Unclassified - Unlimited Subject Category 32			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) One of the most important aspects of a satellite communication system design is the accurate estimation of antenna performance degradation (Pointing error, end coverage gain, peak gain degradation, etc. are of main concern). The thermal or dynamic distortions of a reflector antenna structural system can affect the far-field antenna power distribution in at least four ways. 1. The antenna gain is reduce, 2. The main lobe of the antenna can be mispointed thus shifting the destination of the delivered power away from the desired locations 3. The main lobe of the antenna pattern can be broadened thus spreading the RF power over a larger area than desired 4. The antenna pattern sidelobes can increase thus increasing the chances of interference among adjacent beams of a multiple beam antenna system or with antenna beams of other satellites. The in-house developed NASA Lewis Research Center thermal/structural/RF analysis program was designed to accurate simulate the ACTS in-orbit thermal environment and predict the RF antenna performance. The program combines well establish computer programs (TRASYS, SINDA and NASTAN) with a dual reflector-physical optics RF analysis program. The ACTS multibeam antenna configuration is analyzed and several thermal cases are presented and compared with measurements (pre-flight).				
14. SUBJECT TERMS Reflector antenna; Antenna measurements; Multibeam antenna			15. NUMBER OF PAGES 4	
			16. PRICE CODE A02	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT	

National Aeronautics and
Space Administration

Lewis Research Center
Cleveland, Ohio 44135

Official Business
Penalty for Private Use \$300

FOURTH CLASS MAIL

ADDRESS CORRECTION REQUESTED



Postage and Fees Paid
National Aeronautics and
Space Administration
NASA 451

NASA
