


1N-20

5321

p. 15

Human Lunar Mission Capabilities Using SSTO, ISRU and LOX-Augmented NTR Technologies—A Preliminary Assessment

Stanley K. Borowski
*Lewis Research Center
Cleveland, Ohio*



Prepared for the
31st Joint Propulsion Conference and Exhibit
cosponsored by AIAA, ASME, SAE, and ASEE
San Diego, California, July 10-12, 1995



National Aeronautics and
Space Administration

(NASA-TM-107095) HUMAN LUNAR
MISSION CAPABILITIES USING SSTO,
ISRU AND LOX-AUGMENTED NTR
TECHNOLOGIES: A PRELIMINARY
ASSESSMENT (NASA. Lewis Research
Center) 15 p

N96-12353

Unclass

G3/20 0071561

HUMAN LUNAR MISSION CAPABILITIES USING SSTO,
ISRU AND LOX-AUGMENTED NTR TECHNOLOGIES
--A PRELIMINARY ASSESSMENT

Stanley K. Borowski *
NASA Lewis Research Center
Cleveland, OH 44135

ABSTRACT

The feasibility of conducting human missions to the Moon is examined assuming the use of three "high leverage" technologies: (1) a single-stage-to-orbit (SSTO) launch vehicle, (2) *"in-situ" resource utilization* (ISRU)--specifically "lunar-derived" liquid oxygen (LUNOX), and (3) LOX-augmented nuclear thermal rocket (LANTR) propulsion. Lunar transportation system elements consisting of a LANTR-powered lunar transfer vehicle (LTV) and a chemical propulsion lunar landing / Earth return vehicle (LERV) are configured to fit within the "compact" dimensions of the SSTO cargo bay (diameter: 4.6 m/length: 9.0 m) while satisfying an initial mass in low Earth orbit (IMLEO) limit of ~60 t (3 SSTO launches). Using ~8 t of LUNOX to "reoxidize" the LERV for a "direct return" flight to Earth reduces its size and mass allowing delivery to LEO on a single 20 t SSTO launch. Similarly, the LANTR engine's ability to operate at any oxygen/hydrogen mixture ratio from 0 to 7 with high specific impulse (~940 to 515 s) is exploited to reduce hydrogen tank volume, thereby improving packaging of the LANTR LTV's "propulsion" and "propellant modules". Expendable and reusable, piloted and cargo missions and vehicle designs are presented along with estimates of LUNOX production required to support the different mission modes. Concluding remarks address the issue of lunar transportation system costs from the launch vehicle perspective.

INTRODUCTION

Future human exploration missions to the Moon will require an "economical" lunar transportation system (LTS) providing efficient "access to and through space." Utilizing locally available resources--specifically "iron oxide (FeO)-

rich" mare soils and impact / volcanic glass-- to produce LUNOX will also be key to minimizing IMLEO, the size and number of LTS elements, and the cost for each lunar mission. At present, NASA is focusing considerable resources on the construction of the international space station (ISS) and on development and demonstration of a reusable, single-stage-to-orbit (SSTO) vehicle¹ to replace the current Space Shuttle in the post-2005 timeframe. It is envisioned that an industry-developed and-operated SSTO would have an average flight rate of ~40 missions per year with ~50% of these flights procured by NASA to provide logistics resupply to the ISS.

Planning future human missions to the Moon and Mars is also beginning anew--albeit in a less dramatic fashion than the previous Space Exploration Initiative²--in response to the "Human Exploration and Development of Space" (HEDS) component of NASA's just released strategic plan.³ Activities are focusing on the development of key "high leverage" technologies and systems, their demonstration on precursor missions, and on the identification of viable mission architectures that could be supported by NASA in the future given the expected tight budgets and the trends toward commercialization.

This paper addresses the feasibility of conducting human lunar missions using SSTO, ISRU and LOX-augmented nuclear thermal rocket (LANTR) technologies/systems. For "access to space," the lure of the SSTO is its full reusability, improved operability, high flight rate and reduced launch costs estimated at ~40 M\$ per flight.⁴ Its lift capability is limited, however, and varies from ~25 klbm (~11.3 t) to 45 klbm (~20.4 t) depending on the

*Ph.D./Nuclear Engineering, Senior Member AIAA

low Earth orbit (LEO) altitude and its inclination. The SSTS's cargo bay volume is also small (~50 to 75% that of the current Space Shuttle) which makes packaging of payload and LTS elements a particular challenge.

The development of LUNOX production, storage and tanker transport / transfer technologies and systems for "reoxidizing" expendable lunar landing/Earth return vehicles (LERVs) initially, and then reusable, lunar landing and transfer vehicles (LLVs and LTVs) is expected to dramatically reduce IMLEO requirements, the number of SSTS launches and the cost of delivering payload to the lunar surface. For example, with ~7 kilograms of mass required in LEO for each kilogram of mass landed on the lunar surface, the ability to reoxidize an LERV with ~8 tons of LUNOX for a "direct Earth return" mission would save three 20 t-class SSTS launches compared to an "all Earth-supplied" mission requiring twice that number.

To improve "access through space," a LANTR-based LTV mission scenario has been assumed. The ability to alter the engine's thrust and specific impulse (Isp) by varying the liquid oxygen-to-liquid hydrogen (LOX/LH₂) mixture ratio (MR) in LANTR's "LOX-afterburner" nozzle leads to small engines (both in terms of physical size and reactor power output) capable of providing "big engine" performance. Supersonic combustion of LOX with reactor preheated hydrogen emerging from the engine's sonic throat also results in higher Isp values than LOX/LH₂ chemical engines operating at the same mixture ratio (~100 s at MR = 6). Lastly, the increased use of high-density LOX in place of low-density LH₂ reduces hydrogen tank volume and improves LTV component packaging within the "volume-constrained" SSTS cargo bay.

This paper describes results of preliminary system and mission analysis conducted by Lewis Research Center for NASA Headquarters' Advanced Concepts Office over the past two months. The paper first discusses the relevant technologies and describes their characteristics. Mission and transportation system ground rules and assumptions are then presented along with a description of the reference lunar mission scenario. Next, a comparison of different LTS element options--both for the LERV and LTV--is provided and the requirements/performance gains from transitioning from an expendable to reusable LTS architecture are discussed. The paper concludes with a discussion of lunar transportation system and launch vehicle costs.

SSTS, LUNOX, AND LANTR TECHNOLOGY DESCRIPTION

The SSTS Reusable Launch Vehicle

In January 1993, NASA initiated a comprehensive "in-house" study called "Access to Space." The goals of the study were to identify attractive options for the next generation of U.S. launch vehicles which would: (1) allow major reductions in the cost of space transportation (by at least 50%); (2) provide an order of magnitude increase in crew flight safety; and (3) substantially improve overall system operability. The study examined three major architectural options which included: retaining and upgrading the current Space Shuttle and expendable launch vehicle fleet (Option 1); developing new expendable vehicles using conventional technologies (Option 2); and developing new reusable vehicles using advanced technology (Option 3). A conservative "launch needs" mission model was defined and used in the study.⁴ It included all U.S. civilian (NASA), defense and commercial missions anticipated during the period 1995 through 2030, but did not consider future human missions to the Moon and Mars--a major omission.

In its final summary report⁴ issued in January 1994, NASA concluded that a fully reusable, pure-rocket SSTS (SSTS-R) launch vehicle was the most attractive/beneficial option for development. The preferred Option 3 reference vehicle described in the "Access to Space Study" Summary Report⁴ is shown in Figure 1. It is a vertical takeoff, horizontal-landing winged concept with a circular cross-section fuselage for structural efficiency (other configurations are presently being examined under NASA-supported industry contracts). It uses aluminum-lithium (Al/Li) cryotanks, graphite composite material for all non-pressurized primary structure and a tripropellant (LOX/LH₂/RP) propulsion system employing seven RD-704 engines. The payload bay is located horizontally between the forward LOX tank and the LH₂ tank positioned in the vehicle's midsection. The crew cabin is situated on top of the vehicle next to an airlock/work-station area which provides crew access to both the payload bay and the ISS through an overhead hatch. A "LOX/LH₂" version of the SSTS-R would have an overall length and diameter ~15% larger than its tripropellant counterpart and a gross liftoff weight (GLOW) of ~2.48 million pounds (~1125 t).

The reference SSTS-R cargo bay is 15 feet (~4.6 m) in diameter and 30 feet (~9.15 m) long. A




Fig. 1 Characteristics of Reference SSTO Launch Vehicle (Ref. 4)

“stretched” tripropellant vehicle configuration with a 45 foot (13.7 m) long payload bay and capable of delivering ~20 t to LEO (185 km/28.5 degrees inclination) was also developed. Because of the tripropellant vehicle’s smaller LH₂ tank, the 45 foot bay could also be placed longitudinally in the vehicle. The 45 foot SSTO-R design could also

accommodate the larger DOD Titan IV-class payloads. As a result, this vehicle option showed the lowest annual operating costs (~1.4 B\$/year), as well as cost per launch (~38 M\$) and per pound of payload to LEO (~920 \$/lbm) of the three options examined (see Table 1).

Table 1. Summary of Launch Vehicle Option Costs (Ref. 4)


* Current Space Shuttle capability (no ASRM)
 ** In the out-years
 • Constant FY94 dollars; no “new ways of doing business.”

	Current Program	Option 1 (Retrofit + ELV Fleet)	Option 2 (Lg. + Sm. Veh. + Delta)	Option 3	
				(SSTO-R, 30-ft Bay + Titan)	(SSTO-R, 45-ft Bay)
Technology	0	Incl. in DDT&E	\$0.4B	\$0.9B	\$0.9B
DDT&E (Incl. Technology)	0	\$2.4B	\$11.1B	\$17.6B	\$18B
Production	0	\$5.6B	\$2.0B	\$18.1B	\$18.7B
Operations (Out-Years)	\$6.4B/yr	\$6.1B/yr	\$4.0B/yr	\$2.6B/yr	\$1.4B/yr
Life-Cycle Costs	\$233B	\$230B	\$192B	\$198B	\$169B
Average \$/Launch (Shuttle Replacement)	\$322M (STS)*	\$293M (STS)*	\$85M (Sm.) \$205M (Lg.)	\$41M	\$38M
\$/lb of Payload (Fleet Average for Mission Model)	\$7,488/lb	\$6,814/lb	\$6,100/lb	\$3,900/lb	\$2,100/lb
\$/lb of Payload (Full Veh., to LEO, 28°)	\$6,850/lb (STS)*	\$6,234/lb (STS)*	\$3,900/lb (Sm.) \$1,600/lb (Lg.)	\$980/lb	\$920/lb
\$/lb of Payload (to the Space Station)	\$12,880/lb	\$11,720/lb	\$3,700/lb (Lg.)	\$1,600/lb	\$1,500/lb

LUNOX Production and Utilization

Lunar -derived oxygen (LUNOX) has been identified⁵ as the most promising initial resource to be developed on the lunar surface. A local source of LOX could replenish life support systems, and fuel cells used to power electric surface vehicles. Most importantly, the ability to provide the LERV's "oxygen-rich" chemical rocket engines (which typically operate at MR=6) with a source of return propellant oxidizer reduces the size and mass of the LERV, as well as, the LTV which delivers it to low lunar orbit (LLO). This "feedback effect" can cut the required mission IMLEO by a factor of 2.

Oxygen is also attractive as a resource because it is abundant in the lunar regolith (~45% by mass)⁵ and can be extracted using a variety of techniques.⁶ Two of the more promising concepts for oxygen production involve hydrogen reduction of ilmenite (FeTiO_3) in high-titanium mare soil and ferrous iron in volcanic glass.⁷ Oxygen production via hydrogen reduction is a two step process. First, the iron oxide (FeO) in ilmenite or volcanic glass is reduced and oxygen is liberated to form water:



Next, the water vapor is electrolyzed to regenerate the hydrogen reactant and oxygen resource. The hydrogen is recycled back to react with more lunar feedstock while the oxygen is liquified and stored in "well-insulated" storage tanks.

Reduction experiments⁷ on samples of high-titanium mare soil and iron-rich volcanic glass collected during the Apollo 17 mission to the Taurus-Littrow region of the Moon have produced significant amounts of oxygen. Yields of ~3.0 weight percent (wt %) have been measured for ilmenite-rich, titanium soil at a reduction temperature of ~1050 C after 3 hours. Using the iron-rich "orange" volcanic glass, a yield of ~5.1 wt % was achieved at ~1100 C over the same time period. These experimental results suggest that iron- and titanium-rich soils and iron-rich glasses, in particular, would be attractive feedstocks for lunar oxygen production. In addition to each existing in large quantities on the Moon, both are fine grained and friable and could be used with little or no processing prior to reduction. This is very important because reduced mining and beneficiation of bulk regolith can lower the mass and power requirements of a LUNOX production plant.

Because the lunar mission architecture

examined here assumes that LUNOX is available to support the first piloted mission, cargo missions will be required in advance to establish the necessary mining infrastructure on the lunar surface. It is envisioned⁸ that initial cargo flights will deliver the LUNOX production plant and nuclear power supply. A reactor system is preferred because it allows operation during the lunar night and is less massive than a photovoltaic system with energy storage. The reactor would be mounted on a small teleoperated cart and transported a safe distance away from the LUNOX facility before power generation begins. Subsequent flights would deliver high duty-cycle, electric vehicles for loading and handling regolith and transporting LUNOX from the production site to the LERV (see Figure 2).

The mass and power requirements for a lunar ilmenite reduction facility producing ~24 t of LUNOX per year (enough for 3 piloted missions) have been estimated^{8,9} at ~17.3 to 20.7 t, and ~40 to 80 kW_e, respectively, with system mass and power variations depending on specific assumptions. A breakdown of system element masses for Jooston's⁸ 20.7 t estimate includes the LUNOX plant (7.3 t), and nuclear reactor system (5.1 t), 2 regolith loaders (3.5 t), and haulers (1.9 t), and 2 LUNOX tanker vehicles (2.9 t).

The LOX-Augmented NTR (LANTR)

The recently proposed LANTR propulsion concept^{10,11} represents an innovative combination of conventional LH₂-cooled NTR and supersonic combustion ramjet (scramjet) technologies. The LANTR engine (see Figure 3) utilizes the large divergent section of the NTR nozzle as an "afterburner" into which LOX is injected and supersonically combusted with reactor-heated hydrogen emerging from the LANTR's choked sonic throat--"scramjet propulsion in reverse". By varying the LOX- to- LH₂ mixture ratio (MR), the LANTR engine can operate over a wide range of thrust and Isp values while the reactor produces a relatively constant power output. As the MR varies from 0 to 7, the engine thrust - to - weight ratio for a 15 klbf NTR increases by ~ 440%--from 3 to 13--while the Isp decreases by only ~45%--from 940 to 515 seconds.

The ability to vary LANTR engine performance with MR also results in important engine-, vehicle-, and mission-benefits. Thrust augmentation allows "big engine" performance to be obtained using smaller, more affordable, easier to test NTR engines. Burn times are also shortened which extends engine life and improves "life cycle costs"--an important consideration in reusable mission architectures.




Fig. 2 "LUNOX" Facility and Teleoperated Support Vehicles




Fig. 3 Schematic/Characteristics of LOX-Augmented NTR

Increasing the MR reduces the hydrogen mass and volume and decreases the LH₂ tank size and mass. This feature provides important flexibility to vehicle designers allowing small LANTR-based transfer stages to be configured to accommodate "mass-and/or volume-constrained" launch vehicles. Compactness is especially important for LANTR deployment using the SSTO because of its small cargo bay dimensions.

Finally, once LUNOX becomes available in LLO to reoxidize the LANTR LTV, transition to a "reusable" mission architecture can occur, with formerly expendable vehicles delivering significant quantities of payload to LLO on each round trip cargo, as well as piloted mission. These capabilities are discussed in detail in the sections which follow.

LUNAR MISSION / TRANSPORTATION SYSTEM GROUND RULES AND ASSUMPTIONS

The ground rules and assumptions for the reference lunar mission examined in this study are summarized in Table 2. Provided are details on outbound and return payloads, parking orbits, mission velocity change (ΔV) requirements and duration, and SSTO characteristics. In addition to

the primary ΔV maneuvers indicated, midcourse correction maneuvers are also performed using a storable, bipropellant RCS system. Table 3 details assumptions for the LANTR LTV on primary and auxiliary propulsion, cryogenic tankage, thermal protection and boiloff rates, primary structure, and contingency factors used in this study.

An aluminum-lithium alloy "Weldalite" ($F_{tu} = 111$ ksi, $\rho = 0.0976$ lbm/in³ = 2700 kg/m³) has been used for the cryogenic LOX and LH₂ tanks and a graphite/epoxy composite IM7/977-2 ($F_{tu} = 91$ ksi, $\rho = 0.057$ lbm/in³ = 1577 kg/m³) for non-pressurized primary structure in accordance with assumptions used for the SSTO-R reference configuration. Wall thicknesses for the LH₂ tanks were calculated based on a 35 psi internal pressure and included hydrostatic loads using a "4 g" load factor along with a safety factor of 1.5. A 2.5% ullage was also assumed in this study. A 50 psi internal pressure was assumed for LOX tanks with wall thicknesses of ~0.05 inches.

A two inch helium-purged, multilayer insulation (MLI) system (at 50 layers per inch) is assumed for thermal protection of the LANTR's LOX

Table 2. Reference Lunar Mission Ground Rules and Assumptions

• Payload Outbound:	17.4-18.2 t	"Wet" LERV	} "expendable mode" *
	0.6 t	Crew (3) & suits	
	1.0-0.2 t	Surface payload	
	6.8 t	LTV crew module	} "reuse mode" **
	0.8 t	Crew (4) & suits	
	2.0 t	Surface payload	
• Payload Inbound:	6.8 t	LTV crew module	
	0.8 t	Crew (4) & suits	
	0.5 t	Lunar samples	
	0.1 t	LERV lunar samples	
• Parking Orbits:	185-407 km	Circular (Earth departure)	
	300 km	Circular (lunar arrival/departure)	
• Trans-lunar injection / Earth orbit capture ΔV : 3155 m/s + g-losses / 3100 m/s			
• Lunar orbit capture / trans-Earth injection ΔV : 915 m/s			
• Lunar descent / direct ascent and Earth return ΔV : 2000 m/s / 2900 m/s and capsule entry			
• Lunar orbit disposal ΔV : 860 m/s (for expendable LANTR scenario)			
• Mission duration: ≤ 54 days* (2 in LEO, 7 in transit, ≤ 45 days at Moon)			
• Launch vehicle type / payload capability: SSTO / 20 t to 185 km circular			
• LTS assembly scenario: 3 SSTO launches with EOR&D (IMLEO ≤ 60 t)			

* "Wet" LERV carries return fuel but requires LUNOX for direct ascent/Earth return

** In "reuse mode" surface-based LLV picks-up/returns crew & payload/sample

Table 3. LANTR Transportation System Assumptions

• LANTR System:	Propellants	= Cryogenic hydrogen and oxygen	
	Isp	= 940 s (@ O/F MR = 0.0 / LH ₂ only)	
		= 607 s (@ O/F MR = 4.0)	
		= 545 s (@ O/F MR = 6.0)	
	External Shield Mass	= 2.84 kg/MWt of reactor power	
	Flight Reserve	= 1% of total tank capacity	
	Residuals	= 1.5% of total tank capacity	
	Cooldown (effective)	= 3% of usable LH ₂ propellant	
	• RCS System:	Propellant	= N ₂ O ₄ /MMH
		Isp	= 320 s
Tankage		= 5% of total RCS propellants	
• Cryogenic Tankage:	Material	= "Weldalite" Al/Li alloy	
	Diameter	= 2.7 m (LOX)/4.6 m (LH ₂)	
	Geometry	= Cylindrical tank with 2/2 domes	
	Insulation	= 2 inches MLI + micrometeoroid debris shield	
	LH ₂ /LOX Boiloff*	= 1.31/2.44 kg/m ² /month (LEO @ ~ 240 K)	
	= 0.56/0.90 kg/m ² /month (in-space @ ~ 172 K)		
	= 1.91/3.68 kg/m ² /month (LLO @ ~ 272 K)		
• Primary Structure:	Material	= Graphite/Epoxy Composite	
• Contingency:	Engine, shield, and stage dry mass = 15%		
<hr/>			
• Assumes 3 x "Lockheed Eqn" heat flux estimates for MLI Δt ~ 2 inches			

and LH₂ cryogenic tanks. This insulation thickness exceeds the "ground hold" thermal protection requirements for "wet-launched" LH₂ tanks which need a minimum of 1.5 inches of helium-purged insulation.¹² The installed density of the "2 inch MLI system" is ~2.62 kg/m², and the resulting LH₂ boiloff rate in LEO is ~1.31 kg/m²/month (based on an estimated heat flux of ~0.22 W/m² at a LEO sink temperature of ~240 K). In lunar orbit, where the sink temperature and heat flux are estimated to be ~272 K and 0.32 W/m², respectively, the LH₂ boiloff rate increases by ~46% to 1.91 kg/m²/month. The corresponding boiloff rates for LOX are also shown in Table 3. Finally, a 0.25 mm thick sheet of aluminum (corresponding to ~0.682 kg/m²) is included in the total tank weight estimates to account for micrometeoroid protection.

LUNAR MISSION ARCHITECTURE DESCRIPTION

The reference lunar scenario examined in this study assumes a split mission architecture involving both cargo and piloted missions operating initially in an "expendable mode." The piloted mission employs a "lunar direct" flight profile and assumes the availability of LUNOX for lander refill and Earth return.^{8,13} The mission flight profile is illustrated in Figure 4. Three SSTO flights, each with a payload

capability of ~20 t, are used to deliver the LTS elements consisting of the LANTR-powered LTV and its payload--the piloted lunar landing / Earth return vehicle (LERV) to LEO. Here the elements are assembled into an integrated spacecraft via a series of rendezvous and docking maneuvers (see Figures 4 and 5b).

After 2 days in LEO for system checkout, a "single burn" trans-lunar injection (TLI) maneuver is performed which sends the coupled LTV/LERV on a trajectory to the Moon. Following a 3.5 day transit, the LANTR engine performs a second burn to achieve lunar orbit insertion (LOI). After a brief waiting period in LLO for proper landing site phasing, the LERV with its 3 person crew separates from the LANTR stage, deorbits and lands on the lunar surface. Shortly afterwards, the LANTR performs a short (~0.6 minute) final burn to depart LLO and send the spent stage on a "long-term disposal" trajectory into heliocentric space.

The LERV consists of a "scaled-up" Apollo capsule mounted atop a combination service module/lander vehicle which uses either LOX/LH₂ or LOX/liquid methane (CH₄) chemical engines. It lands on the lunar surface with its LOX tanks essentially "empty" but carries sufficient fuel (LH₂ or




Fig. 4 Reference Piloted Mission Scenario Using SSTO, LANTR and LUNOX Technologies

CH₄) for the return trip to Earth. Because of the limited life support capabilities of the LERV, the crew is sustained for extended periods by a surface habitation facility delivered on earlier cargo missions, as are the LUNOX production equipment and surface exploration equipment.⁸ Near the end of the surface stay, the crew uses the surface tanker to transport and refill the LERV's LOX tank with ~8 t of LUNOX supplied by the production facility. Once reoxidized, the LERV, with crew and samples, ascends to a temporary lunar phasing orbit, then performs the trans-Earth injection (TEI) burn for the trip back. Near Earth, the lander stage is jettisoned and the crew module reenters ballistically.

LTS VEHICLE DESCRIPTIONS / COMPARISONS

The relative size and mass of various NTR/LANTR-powered LTV and chemical LERV combinations are shown in Figure 5. Table 4 summarizes LERV system assumptions and its mass breakdown both in low lunar orbit (IMLLO) and on the lunar surface (IMLS) prior to Earth return. The

mass elements include the 3 crew, surface-landed payload (SP/L), the LERV's return crew capsule (LERC), and lunar landing stage, and returned lunar samples/payload (RP/L). The required amounts of LOX and fuel (either LH₂ or CH₄) for landing, as well as, quantities of LUNOX and fuel for ascent and Earth return are also shown.

To provide a point of comparison with the reference SSTO-launched and LANTR-powered vehicles, Figure 5a shows a LOX/LH₂ LERV and "all LH₂" NTR LTV configuration that uses the Space Shuttle orbiter and a Titan IV launch vehicle, respectively, for their delivery to LEO. The LERV's "wet" lander stage and crew capsule have a combined mass of 20 t and are carried in the orbiter's payload bay "side-by-side." Once in orbit the capsule is installed atop the lander and the integrated LERV's systems are checked out.

Next, a 20 t "all LH₂" NTR-powered LTV is launched to LEO for Earth orbit rendezvous and docking (EOR&D) with the LERV. A Titan IV booster, with an 86 foot (~26.2 m) long payload fairing, is




Fig. 5 Relative Size/Mass of NTR, LANTR and LERV Vehicles

Table 4. LERV System Assumptions and Characteristics

• Propellant:	LOX/LH ₂	LOX/LH ₂	LOX/CH ₄
• MR / Isp:	6.0 / 465 s	6.0 / 465s	3.5 / 375 s
• IMLLO / IMLS:	16.0 / 16.8 t	19.0 t	18.5 t
• Crew (3) & suits:	0.6 t	0.6 t	0.60 t
• M _{SPL} :	0.4 t	1.04 t	0.20 t
• M _{LERC} :	5.0 t	6.29 t	5.60 t
• M _{stage} :	3.0 t (15% IMLEO)	2.85 t (15% IMLS)	1.85 t (10% IMLS)
• M _{LOX} :	5.0 t	5.93 t	6.82 t
• M _{fuel} :			
- landing	0.84 t	0.99 t	1.14 t
- ascent / return	1.16 t	1.31 t	2.30 t
• M _{LUNOX} :	6.95 t	7.85 t	8.05 t
• M _{RPL} :	0.10 t	0.10 t	0.10 t

used to accommodate the 18.7 m long NTR stage. Total vehicle length after EOR&D is ~25 meters (see Figure 6). In contrast to the reference scenario, the NTR LTV performs a single 28 minute TLI burn only, leaving the LERV to accomplish the LOI burn. The added LOX/LH₂ propellant consumption results in a lower initial mass in low lunar orbit (IMLO) of ~16 t (see Table 4) and a reduced capability crew cab weighing ~5.0 t. The LERV lander stage mass is set at 15% of the "wet" LERV mass in LEO. The same mass fraction and mission approach was proposed by General Dynamics¹⁴ in 1993 except that their scenario used a "Centaur-derived" TLI stage with a new, single 35 klbf LOX/LH₂ chemical engine. It also

assumed a lighter weight "2 person" crew capsule (at ~3.3 t) and had a total IMLEO in excess of the "40 t limit" because of the use of a chemical TLI stage and the absence of LUNOX utilization.

The "all LH₂" NTR TLI stage uses a single 15 klbf engine, dual turbopumps for improved reliability, and ternary carbide fuel elements. At the hydrogen exhaust temperature and nozzle inlet pressure of 2900 K and 2000 psia, respectively, the specific impulse is ~940 s using a nozzle expansion ratio of 300 to 1. Other elements of the NTR TLI stage include: (1) an external radiation shield for crew protection; (2) a 4.6 m diameter by 12.4 m long LH₂ tank; (3) a forward cylindrical adaptor housing the RCS system, avionics and auxiliary power, and docking system; (4) forward and aft cylindrical band skirts; and (5) a conical thrust structure. The TLI stage "dry" mass is ~7.0 t which includes ~3.64 t for the 15 klbf NTR and shield. The RCS and LH₂ propellant loads total ~13 t. Included in this total is propellant to perform a small (~30 m/s) "trailing edge" lunar swingby maneuver for stage disposal after LERV separation.

Because of the high launch cost estimates for the Titan IV (~190-375 M\$) and the Space Shuttle (~450-550 M\$) systems, future lunar transportation costs could be substantially reduced if LTS elements can be efficiently packaged within the SSTO cargo bay. The most restrictive configuration is the 30 ft cargo bay. Figure 5b shows a "3 element" vehicle configuration. The first SSTO flight delivers the "propulsion module" consisting of a small LANTR engine (producing 15 klbf at MR = 0) and a LOX tank which is 2.7 m in diameter and 3.0 m long and has a maximum capacity of ~15 t. The propulsion module also contains: (1) a forward conical adaptor section (housing half of the total RCS propellant and hardware required for the lunar mission, modest avionics and auxiliary power, and docking system); (2) two cylindrical band skirts; and (3) aft thrust structure. The propulsion module "dry" mass is ~5.0 t and consists primarily of the LANTR engine at ~2.7 t and its external radiation shield at ~1.1 t. The propulsion module total mass and length are ~20 t and 9.0 m, respectively. By contrast, a propulsion module with a LH₂ tank the same size as the LOX tank would contain only ~1 t of LH₂ and thus be far less mass-efficient than the present design.

The second SSTO launch one week later, delivers a 20 t "propellant module" to LEO containing the LH₂ tank, its forward and aft adaptors and docking systems, and the remainder of the RCS, avionics and auxiliary power. To stay within the "9 m length limit" of the SSTO, the remaining oxygen




Fig. 6 NTR LTV and LERV Dimensions Using Shuttle and Titan IV Launch Vehicles

required for the mission is contained within a "double-walled" and insulated internal LOX tank the same length as that of the LH₂ tank at ~8.0 m. Its diameter is only 1.3 m, however, compared to 4.6 m for that of the LH₂ tank. The LH₂ and internal LOX tanks contain ~6.5 t and 10.0 t of fuel and oxidizer, respectively, but can accommodate up to ~7.3 t of LH₂ and ~11.1 t of LOX depending on mission requirements. The 9 m long "propellant module" has a dry mass of ~3.3 t and RCS, LH₂ and LOX propellant loads of 0.3, 6.5, and 9.9 t, respectively.

After successful rendezvous and docking between the propulsion and propellant modules, the third and final SSTO launch delivers the LERV and its crew. Because of volume constraints, a LOX/CH₄ LERV is utilized and launched with the crew capsule positioned sideways next to the lander. Its maximum mass is limited to ~18.5 t to stay within the payload delivery capability of the LANTR-powered LTV and the total "mission-mass-limit" of 60 t. The LERV's LOX/CH₄ engines operate at a MR = 3.5 and Isp = 375 s (see Table 4), and although their performance is less than the LOX/LH₂ system, methane is more easily stored on the Moon implying less boiloff and tank insulation mass. The LERV transports ~2.3 t of "return methane" to the lunar surface and refills its LOX tank with just over 8 t of LUNOX to return the LERV with its 5.6 t crew capsule and ~0.7 t of crew and lunar samples back to Earth. The same LANTR LTV and LERV landing stage can deliver ~8.7 t of lunar surface payload on "1-way" cargo missions.

When the crew capsule is mounted to the landing stage and the LERV mated to the LANTR LTV, the total spacecraft length and mass is ~24.2 m and 58.5 t, respectively (see Figure 7). The LANTR engine operates at a MR = 4 (Isp ~607 s) which increases the thrust output by a factor of ~3.2--from 15klbf (at MR = 0) to ~48.4 klbf. With this "enhanced" engine thrust-to-weight capability, g-losses drop to less than 50 m/s and the TLI burn duration is ~11.2 minutes compared to ~28 minutes for the "all LH₂" NTR system (Figure 5a). In fact, the total burn duration for the TLI, LOI and LLO disposal maneuvers is just over 14 minutes --half that of the "all LH₂" NTR TLI stage.

Because the reactor fuel lifetime in the LANTR engine is ~5 hours at a hydrogen exhaust temperature of 2900 K, the LANTR LTV is capable of performing many lunar missions in its lifetime, thereby reducing LTS recurring costs. Once LUNOX becomes available in LLO to "reoxidize" the expendable LANTR LTV (Figure 5b), the mission architecture can transition to a "reusable mode" with the same LANTR-powered LTV transporting a 6.8 t




Fig. 7 LANTR LTV and LERV Dimensions Using "9 m Cargo Bay" SSTO

crew module plus 2 t of surface payload to LLO (see Figure 5c). Crew and cargo would then be ferried to the lunar surface by reusable LLVs that are now maintained and refueled at an established lunar outpost. In the "cargo-delivery mode," the crew capsule would be removed allowing the LANTR LTV to deliver ~12 t of cargo and "Earth-supplied LH₂" to LLO on each round trip mission. The required IMLEO for the reusable cargo mission is ~52.4 t.

In the "reuse mode," the LANTR engine operates with a MR=6 (Isp~545 s and thrust~61 klbf) both outbound and back to stay within the LOX and LH₂ propellant limits of the LTV again demonstrating the versatility of the LANTR concept. The piloted and cargo vehicles would require refilling in LLO with

~17.1 and 9.7 t of LUNOX, respectively, before returning to Earth. Also with total mission burn times for the piloted and cargo missions of ~15.2 and 12.9 minutes, respectively, the LANTR-powered LTV would be able to perform ~20 round trip piloted and or cargo missions over its reactor operational lifetime thereby improving lunar transportation costs. Refueling and reoxidizing of the LANTR LTV in LEO would be accomplished at a propellant depot resupplied by a "tanker version" of the SSTD.

Figure 5d shows an alternative expendable piloted configuration possible using the "45 ft cargo bay" SSTD option. With ~13.5 m of available length to work with instead of 9 m, the supplemental LOX




Fig. 8 LANTR LTV and LERV Dimensions Using "13.5 m Cargo Bay" SSTD

tank in the propellant module can be removed from inside the LH₂ tank improving safety and simplifying the design, construction and cost of the propellant module. The propellant module length is ~11 m and includes a 7 m long LH₂ tank and an ~2.5 m long LOX tank at the same diameter as the propulsion module LOX tank. The LANTR LTV has an overall length ~2m longer than the configuration shown in Figure 5b but it is slightly lighter since the "double-walled" internal LOX tank is replaced by a single-walled version. The larger payload bay also makes it possible to deploy a larger, more capable LOX/LH₂ LERV carrying a 6.3 t crew capsule (see Figure 8) while staying within the 60 t IMLEO limit. On "1-way" cargo missions, the LOX/LH₂ lander stage can deliver ~9.2 t of surface payload which is sufficient to accommodate all of the envisioned surface elements⁸ needed to support the piloted mission.

CONCLUDING REMARKS ON TRANSPORTATION SYSTEM COSTS

While detailed LTS system (LANTR LTV and LERV) and operational costs are not yet available for determining the economics of the transportation system discussed here, some preliminary statements can be made on the basis of launch vehicle options and costs. Because LANTR engine use provides flexibility in packaging the LTV, it appears that viable human lunar missions are possible using SSTD and modest orbital assembly (Earth orbit rendezvous and docking of no more than three SSTD payloads). If SSTD launch costs of ~40M\$ can be truly realized, then 3 SSTD launches costing ~120 M\$ could support higher performance lunar missions than the 2 launch scenario using the Space Shuttle and Titan IV vehicles costing ~640 M\$--a factor of 5 reduction in costs. With past studies⁸ showing cost of payload to the lunar surface at ~100 k\$/kg (~8 times higher than the cost to LEO), it can be inferred that delivery costs to the lunar surface of ~20 k\$/kg may be possible using SSTD, ISRU and LANTR technologies. It can also be easily argued that quoted SSTD costs are only estimates at this time while the the cost for Shuttle and Titan IV reflect actual operational costs. The technology challenges of the SSTD are substantial but so are the economic rewards. Without it, human lunar missions still appear possible using Shuttle, Titan IV, ISRU and NTR / LANTR technologies but at substantially higher costs.

ACKNOWLEDGEMENTS

The author wishes to express his thanks to management (Joe Nieberding and Don Palac) for their support during the course of this study and to John Mankins at NASA Headquarters' Advanced

Concepts Office. His challenge to fit a LANTR-based system in the SSTO to support human lunar missions was the basis for this work. The author would also like to express his gratitude to Len Dudzinski (NASA Lewis) for converting the author's pencil drawings / layouts into the clear vehicle illustrations depicted in this paper and to Kent Joosten (NASA JSC) for use of the artwork depicted in Figure 2.

REFERENCES

1. R. E. Austin and S. A. Cook, "SSTO Rockets: Streamlining Access to Space," Aerospace America, Vol. 32, (November 1994), pp. 34-38.
2. America at the Threshold--America's Space Exploration Initiative, Report of the Synthesis Group, Available from the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C. 20402 (June 1991).
3. NASA Strategic Plan, National Aeronautics and Space Administration, (May 1994).
4. Access to Space Study--Summary Report, Office of Space Systems Development, National Aeronautics and Space Administration, (January 1994).
5. T. S. Sullivan and D. S. McKay, Using Space Resources, NASA Johnson Space Center (1991).
6. L. A. Taylor and W. D. Carrier III, "The Feasibility of Processes for the Production of Oxygen on the Moon," in Engineering, Construction and Operations in Space III, New York, 1992, pp. 752-762.
7. C. C. Allen, R. V. Morris, and D. S. McKay, "Experimental Reduction of Lunar Mare Soil and Volcanic Glass," Journal of Geophysical Research, 99, 23, 173 (November 1994).
8. B. K. Joosten and L. A. Guerra, "Early Lunar Resource Utilization: A Key to Human Exploration," AIAA-93-4784, American Institute of Aeronautics and Astronautics (September 1993).
9. E. L. Christiansen, et al., "Conceptual Design of a Lunar Oxygen Pilot Plant," Eagle Engineering Report No. 88-182, Eagle Engineering, Inc., Houston, Texas (July 1, 1988).
10. S. K. Borowski et al., "A Revolutionary Lunar Space Transportation System Architecture Using Extraterrestrial LOX-Augmented NTR Propulsion," AIAA-94-3343, American Institute of Aeronautics and Astronautics (June 1994).
11. S. K. Borowski, D. W. Culver, and M. J. Bulman, "Human Exploration and Settlement of the Moon Using LUNOX-Augmented NTR Propulsion," in Proc. 12th Symposium on Space Nuclear Power and Propulsion, AIP Conf. Proc. No. 324, January 1995, Vol. 1, pp. 409-420.
12. R. H. Knoll, R. J. Stochl, and R. Sanabria, "A Review of Candidate Multilayer Insulation Systems for Potential Use of Wet-Launches LH₂ Tankage for the Space Exploration Initiative Lunar Mission," AIAA-91-2176, American Institute of Aeronautics and Astronautics (June 1991).
13. R. M. Zubrin, "The Design of Lunar and Mars Transportation Systems Utilizing Extraterrestrial Resources," IAA-92-0161, 43rd Congress of the International Astronautical Federation, Washington, DC, (August 28-September 5, 1992).
14. J. M. Lenorovitz, "GD Goal: Lower Cost Manned Lunar Missions," Aviation Week and Space Technology, (January 18, 1993), pp. 42-45.

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE October 1995	3. REPORT TYPE AND DATES COVERED Technical Memorandum		
4. TITLE AND SUBTITLE Human Lunar Mission Capabilities Using SSTO, ISRU and LOX-Augmented NTR Technologies—A Preliminary Assessment		5. FUNDING NUMBERS WU-242-10-01		
6. AUTHOR(S) Stanley K. Borowski				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) National Aeronautics and Space Administration Lewis Research Center Cleveland, Ohio 44135-3191		8. PERFORMING ORGANIZATION REPORT NUMBER E-9973		
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) National Aeronautics and Space Administration Washington, D.C. 20546-0001		10. SPONSORING/MONITORING AGENCY REPORT NUMBER NASA TM-107095 AIAA-95-2631		
11. SUPPLEMENTARY NOTES Prepared for the 31st Joint Propulsion Conference and Exhibit cosponsored by AIAA, ASME, SAE, and ASEE, San Diego, California, July 10-12, 1995. Responsible person, Stanley K. Borowski, organization code 6850, (216) 977-7091.				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Unclassified - Unlimited Subject Categories 16 and 20 This publication is available from the NASA Center for Aerospace Information, (301) 621-0390.		12b. DISTRIBUTION CODE		
13. ABSTRACT (Maximum 200 words) The feasibility of conducting human missions to the Moon is examined assuming the use of three "high leverage" technologies: (1) a single-stage-to-orbit (SSTO) launch vehicle, (2) "in-situ" resource utilization (ISRU)--specifically "lunar-derived" liquid oxygen (LUNOX), and (3) LOX-augmented nuclear thermal rocket (LANTR) propulsion. Lunar transportation system elements consisting of a LANTR-powered lunar transfer vehicle (LTV) and a chemical propulsion lunar landing/Earth return vehicle (LERV) are configured to fit within the "compact" dimensions of the SSTO cargo bay (diameter: 4.6 m/length: 9.0 m) while satisfying an initial mass in low Earth orbit (IMLEO) limit of ~60 t (3 SSTO launches). Using ~8 t of LUNOX to "reoxidize" the LERV for a "direct return" flight to Earth reduces its size and mass allowing delivery to LEO on a single 20 t SSTO launch. Similarly, the LANTR engine's ability to operate at any oxygen/hydrogen mixture ratio from 0 to 7 with high specific impulse (~940 to 515 s) is exploited to reduce hydrogen tank volume, thereby improving packaging of the LANTR LTV's "propulsion" and "propellant modules". Expendable and reusable, piloted and cargo missions and vehicle designs are presented along with estimates of LUNOX production required to support the different mission modes. Concluding remarks address the issue of lunar transportation system costs from the launch vehicle perspective.				
14. SUBJECT TERMS LOX-augmented NTR; LANTR; LUNOX; Single-stage-to-orbit; SSTO; ISRU; Lunar transportation system; Lunar landing/Earth return vehicle; LERV; LTV		15. NUMBER OF PAGES 15		
		16. PRICE CODE A03		
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT	