

Design of Electrical Systems for Rocket Propulsion Test Facilities at the John C. Stennis Space Center

Stennis Space Center


**Space Shuttle Main Engine Test
@ A2 Test Stand**



**RS-68 650 klbf
@ B1 Test Stand**




**Fastrac 60 klbf
@ B2 Test Stand**






Design of Electrical Systems for Rocket Propulsion Test Facilities at the John C. Stennis Space Center



Stennis Space Center

- ◆ NASA/SSC's Mission in Rocket Propulsion Testing Is to Acquire Test Performance Data for Verification, Validation and Qualification of Propulsion Systems Hardware
 - Accurate
 - Reliable
 - Comprehensive
 - Timely
- ◆ Data Acquisition in a Rocket Propulsion Test Environment Is Challenging
 - Severe Temporal Transient Dynamic Environments
 - Large Thermal Gradients
 - Vacuum to 15k psi pressure regimes
- ◆ SSC Has Developed and Employs DAS, Control Systems and Robust Instrumentation that Effectively Satisfies these Challenges
- ◆ The Following Presentation Reviews SSC's Data Acquisition and Controls Architectures




Agenda

Stennis Space Center


- ◆ Background – SSC EE Org & Test Facilities
- ◆ High/Low Speed Data Acquisition Systems
- ◆ Control Systems
- ◆ Data Acquisition and Control Systems Lab
- ◆ Unique Sensor Development Activities



ENGINEERING & SCIENCE DIRECTORATE



ENGINEERING & SCIENCE DIRECTORATE



Full Time	84
Part Time	1
Co-Op	2
IPA	3



Design & Analysis Division



Stennis Space Center



- Configuration Management
- Records Retention DB Management

Mechanical and Component Systems

- Cryogenic Propellant Systems
- Storable Propellant Systems & HPIW
- Hydraulics/pneumatics Systems
- Press Gas/Purge Systems (TBA)
- Components
- Materials
- Ancillary Systems
 - TMS, Measurement Uncertainty
 - Standards & Specifications

Electrical Systems & Software

- Data Acquisition
- Instrumentation & Signal Conditioning
- Controls & Simulation
- DACS Lab Management
- Data Systems Management
- Ancillary Systems/Electrical Power

Systems Analysis & Modeling

- Modeling and Analysis development and integration into RPT
- Fluid Mechanics/Thermal Analysis of Propellant Systems
 - Liquid
 - Gas
- CFD
- Structures/Loads Analysis
- Thermal/Heat Transfer Analysis

Organization Goal:

- **Develop and maintain propulsion test systems and facilities engineering competencies**
 - Unique and focused technical knowledge across respective engineering disciplines applied to rocket propulsion testing. e.g.,
 - Materials selection and associated database management
 - Piping, electrical and data acquisition systems design for cryogenic, high flow, high pressure propellant supply regimes
 - Associated analytic modeling and systems analysis disciplines and techniques

RELEASED - Printed documents may be obsolete; validate prior to use. Corresponding digital structural, thermal, and electrical engineering disciplines



SSC Test Facilities



Stennis Space Center



A-1

Full Scale Engine Devt. & Cert

A-2

J-2X

SSME

AB-Complex



B-1/B-2

Full Scale Engine/Stage
Devt. & Cert


RS-68/ARES

Components
...Engines
... Stages



E-Complex

Stennis Space Center



E-1
Cells 1, 2, 3

High Press., Full Scale
Engine Components

J-2X

E-2
Cell 1

High Press.
Mid-Scale
& Subscale

J-2X



E-2 Cell 2
Low Press. Mid-Scale
& Subscale, Stage


TGV

High Press. Small-Scale
Subscale

E-3


Cell 1

RELEASED - Printed documents may be obsolete; validate prior to use.



E-3


Cell 2





Test Facility Layout

Stennis Space Center



Test Control Center

Signal Conditioning Bldg

Test Article



Test Control Centers

Stennis Space Center



A2 TCC



Test Conductor's Station



E2 TCC



Signal Conditioning Buildings (SCB)

Stennis Space Center




E1 SCB
Signal
Conditioning
Rack



E2 Cell 1
SCB 1
Controls
Racks




E2
SCB's
1 & 2






Typical Test Articles



Stennis Space Center

Integrated Powerhead Demonstrator




LR-89

Test Facility Electrical Systems

Stennis Space Center

- ◆ Communications System
- ◆ **Control System**
- ◆ Facility Fire Alarm System
- ◆ Fire & Gas Leak Detect System
- ◆ Grounding System
- ◆ **High Speed Data Acquisition System**
- ◆ Lighting System
- ◆ Lightning Protection System
- ◆ **Low Speed Data Acquisition System**
- ◆ Oral Warning System
- ◆ Power Distribution System
- ◆ Uninterruptible Power System
- ◆ Video System



Stennis Space Center

High Speed Data Acquisition Systems (HSDAS)

Mark Hughes



High Speed Data Acquisition System

Stennis Space Center

- The High Speed Data Acquisition System is used to record rocket engine or component data from a variety of dynamic sensors.

- Sampling rates normally range from 5.12K to 204.8K samples per second (For Comparison, the Low Speed Data Acquisition System ranges from 1 to 250 samples per second.)
- High speed data provides the Analyst with information about the dynamic environment/condition of a test article. The data feeds models that characterize the performance of the test article or allows the analyst to help determine the health of the hardware.
- Challenges to recording good high speed data include the environment (high temperatures, vibration, high flow, cryogenic temperatures, high pressure), proper cabling, appropriate sensor selection, and numerous other considerations.



High Speed

Data Acquisition Systems

Stennis Space Center


- ◆ **RACAL (Obsolete)** - 100,000 Samples Per Second (**Decimal Sampling**)
 - AB-Complex (SSME)
 - E-Complex (TGV)
- ◆ **MIDDAS (SSME Only)**- 51,200 Samples Per Second (**Binary Sampling**)
 - A Complex (SSME Only)


NOTE: This System is being replaced.

- ◆ **DataMAX II (New)**- 204,800 Samples Per Second (**Binary & Decimal Sampling**)
 - AB Complex (RS-68, J-2X)
 - E Complex



Typical HSDAS Bandwidth Usage






RACAL HSDAS

- **Obsolete**-Being Replaced by DataMAX II HSDAS
- Decimal Sampling Only
- AB-Complex Use Ends in 2007, E-Complex by 2010

Specifications

- 128 Channels
- 100K Samples Per Second
- 45.5 KHz Bandwidth
- 16 Bit Delta-Sigma A/D Conversion
- 0.5, 1, 2, 5, 10, 20 50 Volts Peak





RACAL HSDAS


Stennis Space Center



Tape Transport Unit



Signal Processing Unit



Handheld Controller



Direct-to-Disk System





MIDDAS HSDAS

Stennis Space Center

- SSME Use Only
- Binary Sampling
- Backed up by a DataMAX II
- Used for Quick Turnaround Data


Specifications

- 128 Channels
- 51.2K Samples Per Second
- 23 KHz Bandwidth
- 16 Bit Delta-Sigma A/D Conversion
- .1, .2, .5, 1, 2, 5, 10, 20 Volts Peak

No SCB
Hardware

Results in Cable Lengths
of around 1700 FT

TCC





MIDDAS HSDAS



Stennis Space Center

MIDDAS in Standalone Configuration



128 Channel MIDDAS System





DataMAX II HSDAS

Stennis Space Center


- Mirrored Data Recording
- Binary & Decimal Sampling
- Rates up to 204.8 K SPS
- Fast Turnaround and Archive Data

Specifications

- 192 Channels
- 204.8K Samples Per Second
- 90 KHz Bandwidth
- 16 Bit Delta-Sigma A/D Conversion
- 1, 4, 10, 40 Volts Peak

SCB


TCC



Redundant Data Storage




DataMAX II HSDAS



Stennis Space Center

Mirrored Drives in the TCC



32 Channel

RELEASED - Printed documents may be obsolete; validate prior to use.


Records



DataMAX II Planned for B2 Test Complex



Stennis Space Center




Test Facility



DataMAX II Planned for B2 Test Complex

Stennis Space Center




Test Control Center





Typical High Speed Data Acquisition System Instrumentation

Stennis Space Center




Typical High Speed DAS Instrumentation



Typical High Speed Data Acquisition System Instrumentation



Stennis Space Center



Strain



Dynamic Pressure



Accelerometer




Speed

RELEASED - Printed documents may be obsolete; validate prior to use.




E-Complex High Speed Data Processing System

Stennis Space Center





E-Complex High Speed Data Processing System




Stennis Space Center

HP J6750 Unix Workstations

- ❑ Twin 875 MHz RISC Processors
- ❑ 4 GB RAM
- ❑ 72 GB Storage





Stennis Space Center

Low Speed Data Acquisition Systems Dawn Davis



SSC's Low Speed

Data Acquisition Systems

Stennis Space Center


- ◆ **Data acquisition, recording, real time display**
- **Data types:** Low frequency Analog Data, Discrete (event) Data, Pulse Data from flow meters and speed sensors
 - ◆ **E-Complex Tustin** - 250 samples per second
 - ◆ **AB-Complex PreSys 1000** - 250 samples per second



E-Complex Low Speed Data Acquisition System Architecture



Stennis Space Center






E-Complex Low Speed Data Acquisition System Architecture



Stennis Space Center

- ◆ The E-Complex consists of three test stands
 - E1
 - ◆ Contains four separate data systems: facility, Cell 1, Cell 2, Cell 3
 - ◆ Each system contains 512 analog input channels and 320 discrete channels
 - ◆ Two systems run during a test: Facility and cell
 - E2
 - ◆ Contains two separate data systems: Cell 1 and Cell 2
 - ◆ Each system contains 400 analog input channels and 420 discrete channels
 - ◆ Systems include both facility and test cell measurements
 - E3
 - ◆ Contains one data systems for both cells
 - ◆ System contains 400 analog input channels and 312 discrete channels



E-Complex

Low Speed Data Acquisition System



Stennis Space Center

Tustin Data System



◆ Fully populated analog box

- 128 analog input channels


◆ Fully populated discrete box

- 320 digital input channels



E-Complex

Low Speed Data Acquisition System



Stennis Space Center

Pacific Instruments Signal Conditioners

- ◆ Model 9355

- Programmable

- ◆ Gain, filter, excitation

- Automated Calibration

- ◆ Voltage Insertion
- ◆ Shunt
- ◆ Rcal

- Various Completion Cards

- ◆ Full Bridge, Half Bridge
- ◆ Internal or external shunt resistors
- ◆ ICP

- Measurements

- ◆ RTD's
- ◆ Pressure Transducers
- ◆ Strain Gauges





E-Complex

Low Speed Data Acquisition System



Stennis Space Center

Pacific Instruments Amplifiers

Model 70A

- **Manual Settings**
 - ◆ Gain, filter
- **Calibrations**
 - ◆ Automated through use of additional hardware
- **Measurements**
 - ◆ TC's
 - ◆ Transmitters
 - ◆ Require no excitation






E-Complex Low Speed Data Acquisition System



Stennis Space Center

Calibration Bus





E-Complex

Low Speed Data Acquisition System



Stennis Space Center

Software

- ◆ All of the E-Complex Low Speed DAS software is developed in LabVIEW
 - LSDAS Control Software
 - Display Screens
 - Calibration Software
 - Measurement System Analysis (MSA's) Software





E-Complex


Low Speed Data Acquisition System



Stennis Space Center

Software

- ◆ Low Speed DAS Control Software
 - Used for operation and configuration of the LSDAS Hardware
 - Capability to place system in various modes: Standby, Test, Pre-test, Post-test, Display
 - Saves data to hard-drive
 - Distributes data for remote display





E-Complex


Low Speed Data Acquisition System



Stennis Space Center

Software


- ◆ Low Speed DAS Display Software
 - Tabular and numerical display of measurements
 - Analog and digital data





E-Complex

Low Speed Data Acquisition System



Stennis Space Center

Software

◆ Calibration Software

- ◆ Voltage insertion, shunt calibration
- ◆ Calibrate to a tolerance
- ◆ All or subset of channels
- ◆ Generates Report

◆ Additional Functions

- ◆ Setup of programmable amplifiers : gain, filter, excitation
- ◆ Auto-balance
- ◆ Single Channel Diagnostics



E-Complex


Low Speed Data Acquisition System




Stennis Space Center

Software

◆ Calibration Software



Main Page



Single Channel Operations



E-Complex

Low speed Data Acquisition System



Stennis Space Center

Software

◆ Calibration Software

Channel Diagnostics


Report

RELEASED - Printed documents may be obsolete; validate prior to use.



E-Complex

Low Speed Data Acquisition System



Stennis Space Center

Software

◆ Measurement System Analysis Software

- ◆ Purpose is to quantify a system precision for the LSDAS by evaluating the drift over time of the data system.
- ◆ It consists of a two point calibration performed every hour during an eight hour time span. This is to simulate the maximum time between a pre-test calibration and a test.
- ◆ MSA is performed every thirty days.
- ◆ Reports are generated and data is stored in database.
- ◆ Data from previous runs are used to generate the system precision and to maintain a history of the data system's response.



E-Complex


Low Speed Data Acquisition System



Stennis Space Center

Software

- ◆ Measurement System Analysis Software



Main Screen

RELEASED - Printed documents may be obsolete; validate prior to use.



E-Complex

Low Speed Data Acquisition System

Stennis Space Center

Software

- ◆ Measurement System Analysis Software

Measurement System Analysis *...in progress*


Hour	Complete	Last Cal Time 9:48:21 AM										Next Cal Time 10:48										Taking Data
9355-1-001	0	6406	6412	25583	25589	9355-1-018	17	6407	6404	25592	25590	9355-1-036	35	6404	6404	25600	25602	6404				
9355-1-002	1	6401	6404	25597	25600	9355-1-019	18	6404	6410	25605	25611	9355-1-039	38	6398	6402	25595	25597	6398				
9355-1-003	2	6392	6398	25584	25589	9355-1-020	19	6396	6401	25585	25590	9355-1-040	39	6407	6406	25594	25612	6406				
9355-1-004	3	6394	6399	25568	25573	9355-1-021	20	6391	6399	25569	25576	9355-1-041	40	6398	6403	25581	25585	6403				
9355-1-005	4	6403	6406	25586	25589	9355-1-022	21	6404	6406	25596	25616	9355-1-043	42	6397	6399	25578	25578	6399				
9355-1-006	5	6394	6400	25578	25585	9355-1-023	22	6402	6404	25584	25588	9355-1-044	43	6406	6404	25587	25585	6404				
9355-1-007	6	6400	6400	25587	25587	9355-1-024	23	6394	6416	25591	25585	9355-1-049	48	6401	6407	25604	25610	6407				
9355-1-008	7	6400	6403	25578	25580	9355-1-025	24	6398	6422	25598	25589	9355-1-050	49	6376	6379	25552	25554	6379				
9355-1-009	8	6397	6402	25586	25592	9355-1-026	25	6396	6404	25581	25580	9355-1-051	50	6402	6406	25597	25600	6406				
9355-1-010	9	6396	6400	25579	25582	9355-1-027	26	6396	6396	25582	25578	9355-1-052	51	6400	6406	25600	25606	6406				
9355-1-011	10	6402	6405	25579	25581	9355-1-028	27	6395	6399	25581	25585	9355-1-053	52	6397	6402	25592	25596	6402				
9355-1-012	11	6398	6404	25592	25598	9355-1-029	28	6395	6400	25577	25581	9355-1-055	54	6403	6413	25596	25586	6413				
9355-1-013	12	6404	6410	25596	25601	9355-1-030	29	6402	6405	25578	25582	9355-1-056	55	6392	6397	25575	25580	6397				
9355-1-014	13	6394	6397	25569	25573	9355-1-032	31	6398	6405	25597	25598	9355-1-057	56	6400	6405	25596	25600	6405				
9355-1-015	14	6396	6403	25587	25595	9355-1-033	32	6400	6405	25594	25601	9355-1-058	57	6398	6401	25590	25594	6401				
9355-1-016	15	6394	6397	25578	25581	9355-1-034	33	6397	6399	25589	25591	9355-1-059	58	6384	6394	25558	25585	6394				
9355-1-017	16	6398	6394	25588	25586	9355-1-035	34	6400	6406	25602	25604	9355-1-060	59	6406	6403	25566	25590	6403				

RELEASED - Printed documents may be obsolete; validate prior to use. Hourly Report



E-Complex

Low Speed Data Acquisition System



Stennis Space Center

Software

- ◆ Measurement System Analysis Software




AB-Complex Architecture

Low Speed Data Acquisition System



Stennis Space Center



Primary Difference with E-Complex
 Redundant Data Recording (2nd A/D)



AB-Complex Architecture Low Speed Data Acquisition System




Stennis Space Center

- ◆ The AB-Complex consists of four test stands
 - A1, A2, B1, B2 (B1/B2 one structure with two distinct sides)
 - ◆ Systems contain 512 analog input channels and 736 digital input channels
 - ◆ Each system contains a primary and secondary system for redundancy. Data from the secondary system is only processed if a problem occurs on the primary system.



AB-Complex Architecture Low Speed Data Acquisition System



Stennis Space Center

PreSys 1000



- ◆ Fully populated analog box
 - 256 analog input channels
- ◆ Fully populated discrete box
 - 480 digital input channels




AB-Complex Architecture Low Speed Data Acquisition System



Stennis Space Center

Preston Amplifiers

- ◆ Model 8300
 - Programmable
 - ◆ Gain, filter, excitation
 - Automated calibration
 - ◆ Voltage Insertion
 - ◆ Shunt
 - ◆ Rcal
 - Various Mode Cards
 - ◆ Strain Gauge
 - ◆ Full Bridge , Half Bridge
 - ◆ RTD
 - ◆ Thermocouple
 - Measurements
 - ◆ Strain Gauges
 - ◆ Pressure Transducers
 - ◆ RTD's
 - ◆ Thermocouples



RELEASED - Printed documents may be obsolete; validate prior to use.




AB-Complex Architecture Low Speed data acquisition System



Stennis Space Center

Calibration Control





AB-Complex Architecture Low Speed Data Acquisition System



Stennis Space Center

Software

- ◆ Software consists of :
 - Signal Conditioning Setup
 - Measurement Calibration
 - Data Acquisition and Real-time Display
 - Measurement System Analysis



AB-Complex Architecture Low Speed Data acquisition System

Stennis Space Center

- ◆ **Software**
 - ◆ Software written in Microsoft Visual Basic provides computer controlled setups and calibration of the Preston signal conditioners and amplifiers
- ◆ **Signal Conditioning Setup – Set8300**
 - Select gain, filter
 - Setup and adjustment of individual signal conditioners and amplifiers
- **Calibration – CalMon**
- Automatic calibrations on any number of selected signal conditioners
- Calibrate all active measurements pre-test
- Calibration Types
 - ◆ Shunt Calibration
 - ◆ Voltage Substitution
 - ◆ Excitation Power Supply Calibration



AB-Complex Architecture Low Speed Data Acquisition System

Stennis Space Center

Software

◆ Data Acquisition and Real-time Display – DDAS

- ◆ Provides for the control of the data acquisition process and the distribution of data for real-time display
- ◆ Combines both the analog and discrete data

◆ Measurement System Analysis


- ◆ Software originally developed by Rocketdyne
- ◆ Purpose is to quantify a system precision for the LSDAS by evaluating the drift over time of the data system.
- ◆ It consists of a two point calibration performed every hour during an eight hour time span. This is to simulate the maximum time between a pre-test calibration and a test.



Typical Low Speed Data Acquisition System Instrumentation



Stennis Space Center



- **Standard Instrumentation - Not always in the Catalog**
- **Special Ranges (Cryogenics, Hundreds of Degrees F)**
- **Special temperature compensation circuits**
- **Special Materials**
- **Extremely High Pressures**



Typical Low Speed Data Acquisition System Instrumentation




Stennis Space Center

Pressure



Transmitter



Delta P

Temperature



Thermocouples



RTD's

FLOW

Pressure



Transmitter


Strain



Venturi Flowmeter

Speed






Stennis Space Center

Control Systems

John Bakker



Control Systems

Stennis Space Center

- The **Control System** manages the test complex and rocket engine or component systems during day-to-day operations and testing while maintaining a safe environment allowing for orderly test shutdown and making facility systems safe in emergency situations.
 - Programmable Logic Controllers (PLCs) form the backbone of the SSC Control Systems.
 - PLCs primary functions are to sequence rocket engine or component tests and maintain daily operations.
 - Hard-wired controls are provided as a backup to the



Control Systems Functions

Stennis Space Center

- ◆ **Day to Day Operations**
 - Unloading cryogenics/propellants (Oxygen, Hydrogen, Nitrogen, Methane, etc.)
 - Propellant transfers from storage to run tanks
 - Pumping up bottle pressures (Nitrogen, hydrogen, helium etc.)
 - Gas leak and fire detection.
 - Engine drying
 - Facility Readiness Test (FRTs)
 - Redline cut checks (Redlines are measurements that are monitored by the PLC for the purpose of initiating an immediate shut down when out of tolerance.)



Control Systems Functions

Stennis Space Center

◆ Test Day Operations

- Propellant Transfers
- Engine chill down and prep
- Greenline monitoring (Permissives to start test.)
- Test stand valve sequencing and control during hot fire test
- Redline monitoring during hot fire test
- Performs a controlled shutdown of the engine
 - ◆ Critical valves are also wired to a backup PLC or relays



E1 Test Stand Control System


Stennis Space Center

- ◆ **Three Independent Test Cells**
 - Can support three different test programs simultaneously
 - All test cells share the same propellant run tanks, high pressure bottles, Control System etc.
 - Control system must be flexible enough to switch between test cells in twenty four hours
- ◆ **Most Generic PLC (Ladder Logic) of Any Test Facility**
 - System is configured entirely through Excel
 - Excel tables can be configured in advance and downloaded on test day.
 - Excel tables can be archived for historical reference



E1 Control System Layout


Stennis Space Center





E1 PLC Network Design

Stennis Space Center



Control Room

SCB






Typical E1 SLC Programmable Logic Controller (PLC) Installation



Stennis Space Center

E1 A-B SLC PLC Cabinet

- Dedicated STE PLC for Cell 2
 - 64 DO 80 AI
 - 12 AO 128 DI
- Shared Display PLC
 - 80 AI
 - 32 DI






E1 PLC Architecture with Parallel SLC Input/Output (I/O) Cards



Stennis Space Center



**Advantage: Fast Throughput
Multiple Processors**


Disadvantages:


**Only three racks of I/O per processor
Parallel cables are short**



Test Stand E2 Cell 1 Signal Conditioning Bldg 1 Controls I/O


Stennis Space Center





A/B/E2 PLC Architecture

Stennis Space Center



Advantages: One Processor
Much larger I/O count

Disadvantages:
Throughput slowed by serial
communications




SSC PLC Architecture Changes



Stennis Space Center

- **Migration to faster PLCs in a Distributed Architecture outside the E1 Test Facility**


- A-Complex Redline System
- A-Complex Fire & Gas Leak Detect System
- B-Complex Redline System
- B-Complex Fire & Gas Leak Detect System in design
- E3 Redline System




Control Logix 5000 PLC



Test Control Center with Human Machine Interface (HMI) Screens



Stennis Space Center




Hard Wired
Controls

Controls
HMI



InTouch by Wonderware HMI

Stennis Space Center






Stennis Space Center

Data Acquisition & Control Systems Lab (DACs Lab)

Scott Jensen



DACS Lab

Stennis Space Center

- The DACS Lab is a facility designed to provide an off-stand capability for developing data acquisition and control systems in support of testing.
- Safe and controlled environment allows verification and development without impacting project schedules or compromising pre-existing test hardware, software, networks or configurations.
- Useful in the identification and resolution of significant issues with equipment and configuration functionality prior to activation.
- Servo valve control capability and personnel's expertise have been utilized to expedite mission critical valve integrity checks prior to field installation.
- Helps to eliminate facility downtime and test delays.
- Provides for hands-on training, qualifying spares, market evaluations, minor equipment repairs, and familiarization with data acquisition and controls equipment



DACS Lab


Stennis Space Center



DAS Station



Controls Station




RELEASED - Printed documents may be obsolete; validate prior to use.

Controls Checkout Cart



Sensor Workstation



Stennis Space Center

Sensor Development



Wireless Sensor Development



Stennis Space Center

Sensors Needed to Monitor Valve Health

High-Geared Ball Valves

- Torsional shaft strain
- Total valve cycles
- Cryogenic valve cycles
- Inlet temperature
- Outlet temperature
- Body temperature



Linearly Actuated Valves

- Linear bonnet strain
- Total linear travel
- Total directional changes
- Valve preload position
- Inlet temperature
- Outlet temperature
- Body temperature





Wireless Sensor Development



Stennis Space Center

Confined Locations

- **Sensor Size**
2½ X 3 X 4 inch
- **Wireless**
35 foot transmission
radius
Added data security
902-928 MHz band
Compliance with FCC
- **Battery powered**
Two battery packs
with two 9 Volts
supplies





Wireless Sensor Development




Stennis Space Center

◆ NEC Class I Division II B Hazardous Environment

- Compliance with NEC article 501
- Enclosed in Potting

Blue-epoxy flame retardant 832FRB
M.G. Chemicals

- Internal temperature monitoring
Shutdown 150° F
- No exposed arcing points
- Limited operational power
9 Volts at 250 milliamp
- No exposed cavities





Wireless Sensor Development





Stennis Space Center

- ◆ **Power Conservative**
 - **One-Way Communications**
Linx HP3 transmitter and receiver modules
 - **Microprocessor Sleep Mode**
 - **Piezoelectronic Wake-Up Circuitry**
Measurement Specialties LDT series

◆ **Accurate Data Synchronization**

- **IRIG-B Timing Module**
Facility correlation
- **Communication Bus**
Internal data correlation





Wireless Sensor Development



Stennis Space Center

◆ **Automatic and Manual Data Access**

- **Memory storage Network capable**



Compact flash card memory access
ARMA Design Inc.

- **Network capable**

Ethernet broadcast I-7188E
ICS DataCom Inc.

◆ **Setup and Maintenance**

- **Simple Human interface**
Switch and Indicator light
- **On-board programmer interface**
Serial communications
Software updates





Wireless Sensor Development



Stennis Space Center

◆ The K-Type thermocouples sensor

(for inlet, outlet, and body temperature monitoring)


- Monolithic thermocouple amplifier from Analog Devices
- Uses cold junction compensation

◆ The strain instrumentation sensor


(for bonnet and torsional strain monitoring)

- Axial Strain by a Vishay precision quarter bridge
- Biaxial Strain by a Vishay precision half bridge
- Shear Strain by a Vishay precision full bridge


Uniaxial Pattern



Biaxial Pattern



Shear Pattern



Wireless Sensor Development



Stennis Space Center

◆ Limit switch sensor

(for monitoring number of cycle)


- 6 magnetic reed switches
- 4 input with wake-up abilities

◆ Signal interface sensor

(for Linear Voltage Differential Transformer (LVDT) monitoring)

- 4 to 20 milliamp current loop signal
 - Giant Magneto Resistive (GMR) from Unobtrusively monitors magnetic fields
- 0 to 10 volts Direct Current (DC) signal
 - Basic voltage follower circuit

Giant Magneto Resistive






Cryogenic Sensor Development


Stennis Space Center

- ◆ Developed improved bonding techniques for strain gauges and thermocouples used in cryogenic service






Cryogenic Sensor Development




Stennis Space Center

- ◆ Developed calibration curves for foil and fiber optic strain gauges at cryogenic temperatures

Fiber Optic Strain Gauge Curve



Foil Strain Gauge Curve






Speed Sensor Signal Conditioning Development




Stennis Space Center

- Developed a frequency to voltage converter for determining rotational speed of turbopumps during rocket engine testing - improved the response to complex waveforms recorded from speed sensors

Existing Speed Detection Logic




Experimental Speed Detection Logic






Stennis Space Center


Speed Sensor Signal Conditioning Development



Breadboard



Populated Board (top)




Populated Board (bottom)






Piezoelectric Sensor Health



Stennis Space Center

- ◆ Developing the techniques to evaluate the health of piezoelectronic sensors

Breadboard of Piezoelectric Sensor Tester





Summary

Stennis Space Center

- ◆ NASA/SSC's Mission in Rocket Propulsion Testing Is to Acquire Test Performance Data for Verification, Validation and Qualification of Propulsion Systems Hardware
 - Accurate
 - Reliable
 - Comprehensive
 - Timely

- ◆ Data Acquisition in a Rocket Propulsion Test Environment Is Challenging
 - Severe Temporal Transient Dynamic Environments
 - Large Thermal Gradients
 - Vacuum to 15 ksi pressure regimes

- ◆ SSC Has Developed and Employs DAS, Control Systems and Robust Instrumentation that Effectively Satisfies these Challenges