#### **Designing for Our Future in Space**

Janis Connolly, M. Arch.
NASA Johnson Space Center – Habitability and Human Factors Office

NASA Rhode Island Space Grant Consortium Spring Symposium: NASA in Rhode Island April 28, 2007


#### Abstract

Over the past several years, the disciplines of architecture and human factors have been increasingly recognized as specialties that have focused upon "human-centered design" in the development of spacecraft and surface habitats. These specialties have been instrumental in the conceptual design of overall spacecraft configurations and layouts, as well as habitability outfitting hardware, such as the galley, hygiene facility, sleep quarters, or the layout of displays and controls.

From the human-centered perspective, this approach to design assists in the mitigation of risk when designing for an extreme environment such as space. It takes into account the human's physical and cognitive capabilities and limitations, the human's performance in the context of human space flight, the human's interaction with machines that are both physically and cognitively complex, the activities required of the human to accomplish the goals of missions, and the use of design practices that promote products to enable human activity.


It is this latter aspect – the use of design practices that promote products to enable human activity – that is the focus of the approach used by the Rhode Island School of Design (RISD) in collaboration with the Habitability and Human Factors Branch (HHFB) at the NASA Johnson Space Center (JSC). During the past few years, there has been a growing recognition of the value added by utilizing industrial designers to further the conceptual development of space hardware, that when used in conjunction with architecture and human factors, provides a robust solution to the design challenge.

The "Design for Extreme Environments" Studio at RISD has taken suggested design topics from the NASA JSC HHFB and asked the students to investigate solutions to these challenges. The topics have demanded that the student pay particular attention to a variety of aspects of the space environment and understand how the human responds to each. The student must then adapt the design to these responses. The studio environment has been one way to introduce these challenges, but providing for an "in-residence" opportunity at JSC has given the students a broader vision and set of experiences. The accompanying presentation highlights the studio as well as in-residence work that has been accomplished.





April 28, 2007 Spring Symposium: NASA in Rhode Island **NASA Rhode Island Space Grant Consortium** 







continues to take steps further from its cradle...








Designing for the human in space design from a "human-centered" needs to draw not only on engineering, but must approach perspective...






"Design

#### Respiratory Support Pack Design Project



- 1. Medical Equipment is covered up & hidden from the viewer.
- 2. Medical equipment is not laid out according to order of use.
- 3. Equipment is not clearly labeled.
- 4. No instruction booklet.
- 5. Equipment inside is too cluttered.

concerns with existing RSP....






### Respiratory Support Pack



### RESPIRATORY SUPPORT PACK CUE CARD #1



### UNCONSCIOUS PATIENT

- Deploy RSP, ALSP, and Defibrillator
- Remove metal dustcap from regulator supply hose and connect to (02) supply (\*\* If CHeCs is unavailable, use PBA)
- Set Autovent BPM knob = dot (●)
- Caution: Use WHITE indicator Line Set Regulator flow rate = 12
- attach (o2) tubing to RSP Regulator hose barb 12 Attach Patient Valve to ILMA Retrieve blue Ambu Bag from ALSP and
- Place Ambu Bag on patient and give 1 breath every 5 sec while preparing ILMA in ALSP.

- Insert ILMA using ILMA cue card in IAK
- Caution: Use WHITE indicator line Set Regulator flow rate = 0
- Set Autovent BPM = 12
- 10 Set Autovent Tidal Volume = 800
- on to of patient valve and feel for (o2) flow. 11 Check for movement of green indicator
- 13 Contact Flight Surgeon. Monitor Patient.

#### CONSCIOUS PATIENT

- Deploy RSP, ALSP, and Defibrillator
- Remove metal dustcap from Regulator supply hose and connect to (o2) supply (\*\* if CHeCs is unavailable, use PBA)
- Set Autovent BPM knob = dot (●)

- (Caution use WHITE indicator line) Set Regulator flow rate = 12
- Remove Low Flow Mask from RSP lid pocket and attach (o2) tubing to Regulator hose barb
- Put mask on patient
- Contact Flight Surgeon. Monitor Patient

## Wireless Crew Communication Project



Challenges with Existing Headsets








Limits usability range, wire tangle, obstruction, bulky headsets, needs simplicity, needs versatility.....


### Wireless Crew Communication Project












ATU COMMUNICATION LOOPS




ATU COMMUNICATION LOOPS


#### NCC Loops #1

I nese diagrams illustrate different possibilities for communication configurations from the space station to ground, via the ATU. They were used to help communicate ideas between the differing diagram formats used by Human Factors designers, and Electrical Engineers on the WCC team, and were updated and modified weekly to better mesh the two different styles of

### Project Wireless Crew Communication







Configuration C


## Wireless Crew Communication Project









Our work on WCC
Started with study of
the research and
concept development
that our RISD
colleagues had already
put together, as well as
the work of Mr. Li Hua
of NASA and the
research on available
commercial wireless
headsets done by
NASA's UTAF Lab.
This work provided a
foundation for our



Precedent Imagery on Wireless COM Project (J. Flahrety, L. Hua, C. Conlee)

# living in isolation/confinement and how the analog affects the designs..... And using Earth "analogs" to help us understand





# For the next journeys to the Moon....



