MSFC-205_ABSTRACT

ABSTRACT OF PRESENTATION

TITLE: Welding Development at Marshall Space Flight Center

This paper presents the basic understanding of the friction stir welding process. It covers process description, pin tool operation and materials, metal flow theory, mechanical properties, and materials welded using the process. It also discusses the thermal stir welding process and the differences between thermal stir and friction stir welding. MSFC weld tools used for development are also presented.

MSFC-205_PRESENTATION



National Aeronautics and Space Administration
George C. Marshall Space Flight Center
Materials, Processes and Manufacturing Department

WELDING DEVELOPMENT

MARSHALL SPACE FLIGHT CENTER

Jeff Ding

Metallic Materials & Processing

R. Jeffrey Ding
Robert.J.Ding@nasa.gov

AGENDA

- Introduction
- Conventional FSW Process:
  - Description
  - Microstructure
  - Hardness
  - Mechanical Properties
- Self Reacting FSW

R. Jeffrey Ding
Robert.J.Ding@nasa.gov

Friction Stir Welding and Processing
Ed. R.S. Mishra and M.W. Mahoney
2007, ASM International

1. Introduction (R. Mishra-UMR & M. Mahoney-Rockwell Scientific Co.)
2. FSW Tooling (C. Fuller- Rockwell Scientific Co.)
3. Metal Flow and Temperature Distribution (J. Schneider-MSU)
4. Microstructural Evolution in Al Alloys (A. Reynolds-USC)
5. Mechanical Properties of FSWed Al. Alloys (M. Mahoney-Rockwell Scientific Co.)
6. FSWing of Ferrous and Nickel Alloys (C. Sorensen & T. Nelson-BYU)
7. Microstructure & Mechanical Prop. of FSW Ti Alloys (T. Lienert-LANL)
8. Microstructures & Mechanical Prop. of Cu Alloys (T. McNelley-NPS)
9. Corrosion Properties of FSW Al. Alloys (J. Lumsden - Rockwell Scientific Co.)
10. Process Modeling (A.Askari & S. Silling-Cambridge)
11. Robots & Machines for FSW/FSP (C. Smith-Friction Stir Link, Inc.)
12. Friction Stir Spot Welding (H. Badarinarayan, F. Hunt, K. Okamoto - Hitachi)
13. Application of FSW & Related Applications (W. Arbegast-SDSMM)
14. Friction Stir Processing (R. Mishra-UMR & M. Mahoney-Rockwell Scientific Co.)
15. Future Outlook for FSW/FSP (R. Mishra-UMR & M. Mahoney-Rockwell Scientific Co.)

R. Jeffrey Ding
Robert.J.Ding@nasa.gov

Background
Friction Stir Welding

- Jeff Ding brought FSW to the NASA agency in 1995.
- Patented by The Weld Institute (TWI) Cambridge, U.K in 1991.
- Solid state (non-melting) joining process using frictional heat to raise temperature into the metals plastic state.
- Recognized as significant advancements in welding technology.

R. Jeffrey Ding
Robert.J.Ding@nasa.gov

FSW Metallography



Macro transverse section of FSW



Macro transverse section of VPPA

NASA
George C. Marshall Space Flight Center
June 27, 2007

R. Jeffrey Ding
Robert.J.Ding@nasa.gov

Conventional FSW Process



Chapter 1: Introduction

- **Tool serves 3 primary functions:**
  - **Heat: Heating of workpiece**
  - **Stir: Movement of material to product the joint**
  - **Forge: Containment of material**

R. Jeffrey Ding
Robert.J.Ding@nasa.gov

Conventional FSW Process Parameters



Chapter 2: FSW Tooling: Tool Materials & Design

NASA
George C. Marshall Space Flight Center
June 27, 2007

R. Jeffrey Ding
Robert.J.Ding@nasa.gov

FSW of 1" thick panels



AVI file. Click to Run Movie.

NASA
George C. Marshall Space Flight Center
June 27, 2007

R. Jeffrey Ding
Robert.J.Ding@nasa.gov

Temperature Distribution in FSW





Chapter 3: Temperature Distribution and Resulting Metal Flow

NASA
George C. Marshall Space Flight Center
June 27, 2007

R. Jeffrey Ding
Robert.J.Ding@nasa.gov

Mechanical Properties



Hardness AA2219



TIG vs FSW Hardness



R. Jeffrey Ding
Robert.J.Ding@nasa.gov

FSW properties independent of material thickness

	(MPa)	ksi	(MPa)	ksi	(mm)	
	570	82.7	460	67.0	6.1	
	225	32.6	97.0	66.6	4	
	270	39.2	410	59.5	8.1	
	251	36.4	401	58.2		
	249	36.1	399	57.9	8.1	
	209	30.3	357	51.8	16.5	
	217	31.4	367	53.4	25.4	

R. Jeffrey Ding
Robert.J.Ding@nasa.gov

FSW Benefits

R. Jeffrey Ding
Robert.J.Ding@nasa.gov

FSW Limitations

- Exit hole left after withdrawing tool.
- Significant down force and traversing forces required.
- Lacks the flexibility of manual and arc processes.

R. Jeffrey Ding
Robert.J.Ding@nasa.gov

Production Benefits Obtained with FSW

- The formation of low distortion, solid-phase, welds of repeatable high quality and mechanical properties, which could improve existing products and lead to a substantial number of new product design opportunities, hitherto not possible, in many different industries.
- Low welding operation costs due to the low welding power requirement and the elimination of filler wires, weld pool shielding gases and the special joint edge preparations required by fusion welding techniques.
- The machine tool operation, once correctly set, does not require operator skill and the machine settings can be easily monitored to provide in-process weld quality assurance.
- The process is clean and does not produce any major safety hazards, such as welding fume or radiation.

R. Jeffrey Ding
Robert.J.Ding@nasa.gov

Two basic components of weld tool



Generally the shoulder is twice as wide as the pin.

NASA
George C. Marshall Space Flight Center
June 27, 2007

R. Jeffrey Ding
Robert.J.Ding@nasa.gov

Basic shoulder geometries

Cross sections of pin tool



Concave smooth shoulder



Flat shoulder with scrolls



View showing scrolls on shoulder

NASA
George C. Marshall Space Flight Center
June 27, 2007

ey Ding
Robert.J.Ding@nasa.gov

Weld Tool Pin Configurations

Threaded features on either cylindrical or tapered pin

R. Jeffrey Ding
Robert.J.Ding@nasa.gov

Weld Tool Shoulder Features







R. Jeffrey Ding
Robert.J.Ding@nasa.gov



Theorized Metal Flow Paths in FSW

Workpiece/Pin Tool Interaction

NASA
George C. Marshall Space Flight Center
June 27, 2007

R. Jeffrey Ding
Robert.J.Ding@nasa.gov

Kinematic mathematical model approach defines the theoretical flow fields and resultant currents in the neighborhood of the conventional FSW tool



Shear texture bands are observed in the weld nugget

Similar texture has been reported in weld nuggets, independent of the initial PM texture



1000 mm



(6063) DP Field, et. al., 2001.
(1100) K.V., Jata, S.L. Semiatin, 2000.

'A' fiber texture

{111} <hkl>

2195-T8



Schneider, J.A., Nunes, Jr., A.C., *Met. Trans. B*, 2004.

FSW Microstructure





Retreating side



Advancing side.

R. Jeffrey Ding
Robert.J.Ding@nasa.gov

Sharp boundary exists between parent grains and recrystallized nugget grains

RS



OIM

2195-T8

Optical light Micrograph of weld nugget



Studies were conducted to trace variations in the metal flow paths



Based on position and process parameter

Force (lbf)	*Travel (ipm)*	*Rotation (rpm)*
6500	*3*	*150*
7000	*4.5*	*200*
8000	*6*	*300*

Study produced:
117 each 6.5 " welds

- **Tungsten wire: 0.001" dia**
- **Al 2219 plates: 0.25" thick**

Colligan, Welding Journal, 1999.

Seidel & Reynolds, Met. & Mat. Trans. A, 2001.

NASA
George C. Marshall Space Flight Center
June 27, 2007

R. Jeffrey Ding
Robert.J.Ding@nasa.gov

Strain experienced by the metal can be determined from a wire marker spacing



0.026" length

Optical image

Initial dia. = 0.0025"
Final dia. = 0.0024"



$$\Delta L \approx r \frac{\sigma_{tungsten\_wire}}{\sigma_{weld\_metal}}$$

NASA
George C. Marshall Space Flight Center
June 27, 2007

R. Jeffrey Ding
Robert.J.Ding@nasa.gov

The rotating plug of metal contains the Maelstrom current



Nunes, Automotive Alloys and Joining Aluminum, TMS, 2001.

R. Jeffrey Ding
Robert.J.Ding@nasa.gov

Summary of metal flow variation with entrance into weld zone



C05
8000 lbf /200 RPM /4.5 ipm



C20
7000 lbf /300 RPM /4.5 ipm





C22
7000 lbf /300 RPM /4.5 ipm





R. Jeffrey Ding
Robert.J.Ding@nasa.gov



Self Reacting Friction Stir Welding (SR-FSW)

NASA
George C. Marshall Space Flight Center
June 27, 2007

R. Jeffrey Ding
Robert.J.Ding@nasa.gov

SR-FSW
2001- PRESENT







Purpose of Development:
- Natural/Logical evolutionary step.
- Goal is implementation on External Tank and other Large-Scale Aluminum cryogenic tanks.

Advantages over Conventional FSW:
- No Anvil Required – Simplified Tooling.
- Lowers Potential for Creating Defects (LOP).
- Faster Travel Rates.

Similar Macro Transverse Sections in SR-FSW and C-FSW



Macro transverse section of SR-FSW



Macro transverse section of FSW

NASA
George C. Marshall Space Flight Center
June 27, 2007

R. Jeffrey Ding
Robert.J.Ding@nasa.gov



FSW Weld Tools

NASA
George C. Marshall Space Flight Center
June 27, 2007

R. Jeffrey Ding
Robert.J.Ding@nasa.gov

Conventional FSW Development

Panel Welding Development

27.5' ET Hydrogen Barrel #1 Demonstration at MSFC



Vertical Weld Tool Bldg. 4705



NASA-MSFC Vertical Weld Tool

External Tank FSW Barrel Implementation



Two Longitudinal FSW Cryotank Barrel Welders At the Michoud Assembly Facility

Self-Reacting FSW Development



Panel Welding



14' Ring Welding Technology Demonstrations at NASA-MSFC Circumferential Weld Tool



Circumferential Weld Tool

Full Scale Self-Reacting FSW 0.320" Implementation



External Tank Tooling for Circumferential SR-FSW

Full Scale Self-Reacting FSW 27.5' diameter Demonstration



MSFC Building 4707
Horizontal Weld Tool





Horizontal Weld Tool Platform

Full Scale Self-Reacting Gore to Gore Demonstration





Complex Curvature Friction Stir Welder at MAF

Full Scale Self-Reacting Chord to Gore Demonstration





Complex Curvature Friction Stir Welder at MAF

Full Scale Self-Reacting
Dome Cap to Dome Body Demonstration





Complex Curvature Friction Stir Welder at MAF

Complex Curvature Friction Stir Welder at MAF

Thermal Stir Welding (TSW)

- A new solid state welding process similar to friction stir welding (FSW) but with independent stirring, heating and forging function controls.
- Joins similar and dissimilar metals.
- More degrees of freedom for greater process control and optimization.
- Provides mechanical means to produce localized superplastic material in high melting alloys, i.e., titanium.

R. Jeffrey Ding
Robert.J.Ding@nasa.gov

Thermal Stir Welding Process Description



NASA
George C. Marshall Space Flight Center
June 27, 2007

R. Jeffrey Ding
Robert.J.Ding@nasa.gov

Thermal Stir Welding

- Key-hole close out
- Joining of dissimilar metals
- Elimination of backside anvil
- Optional inert processing environment
- Complex joint designs

NASA
George C. Marshall Space Flight Center
June 27, 2007

R. Jeffrey Ding
Robert.J.Ding@nasa.gov

Thermal Stir Welding

Prototype System





NASA
George C. Marshall Space Flight Center
June 27, 2007

R. Jeffrey Ding
Robert.J.Ding@nasa.gov

Comparison Between FSW and TSW Microstructure



Macro transverse section of TSW



Macro transverse section of conventional FSW

NASA
George C. Marshall Space Flight Center
June 27, 2007

R. Jeffrey Ding
Robert.J.Ding@nasa.gov