

# Statistical Properties of SEE Rate Calculation in the Limits of Large and Small Event Counts


Ray Ladbury  
Radiation Effects and Analysis Group  
NASA Goddard Space Flight Center

To be presented by Ray Ladbury at the IEEE Nuclear and Space Radiation Effects Conference (NSREC), July 23-27, 2007 and to be published on <http://rahome.gsfc.nasa.gov>

1

## Motivation for a Statistical Approach

- Goal of SEE rate calculation is to bound the SEE rate
  - by how much?
- Estimated rate depends on the fit to the  $\sigma$  vs. LET curve
  - Should the fit be a “Best” fit or a conservative worst-case fit
  - Does the answer depend on error bars



To be presented by Ray Ladbury at the IEEE Nuclear and Space Radiation Effects Conference (NSREC), July 23-27, 2007 and to be published on <http://rahome.gsfc.nasa.gov>

2

## Outline


- Understanding errors on SEE cross sections
- Methodology: Maximum Likelihood and confidence Contours
- Tests with Simulated data
- Applications

To be presented by Ray Ladbury at the IEEE Nuclear and Space Radiation Effects Conference (NSREC), July 23-27, 2007 and to be published on <http://rahome.gsfc.nasa.gov>

3

## Cross sections and Errors

$$\sigma(\text{LET}_i) = \sigma_{\text{lim}} \times (1 - \exp(-((\text{LET}_i - \text{LET}_0)/w)^s))$$



To be presented by Ray Ladbury at the IEEE Nuclear and Space Radiation Effects Conference (NSREC), July 23-27, 2007 and to be published on <http://rahome.gsfc.nasa.gov>

4

## Maximum Likelihood and Confidence

- Likelihood  $\mathcal{L}$  is the product of the probabilities of all our data
  - Probabilities of our observations are driven by Poisson fluctuations, so

$$\mathcal{L} = \prod_{i=1}^n P(x_i, \mu) = F_i \times \sigma_{lim} \times \left[ 1 - \exp \left\{ - \left( \frac{LET - LET_0}{W} \right)^s \right\} \right]$$

- Values of  $(LET_0, \sigma_{lim}, w \text{ and } s)$  that maximize  $\mathcal{L}$  give a best fit to data
  - Must be done numerically
- Advantage of Maximum Likelihood is that the ratio of the likelihood for different parameter values gives a measure of their relative probability

$$\log(\mathcal{L}(\{LET_0^*, \sigma_{lim}^*, w^*, s^*\}) / \mathcal{L}(\{LET_0, \sigma_{lim}, w, s\}_{bf})) \geq -0.5 \chi^2(P, k)$$

- This allows construction of confidence contours around our best-fit values
- The highest SEE rate for parameters within a confidence contour will be the WC rate consistent with our data at that confidence level.
  - Use Figure of merit (FOM) to select parameter sets  $FOM = C \times \sigma_{lim} / LET_{0.25}^2$

To be presented by Ray Ladbury at the IEEE Nuclear and Space Radiation Effects Conference (NSREC), July 23-27, 2007 and to be published on <http://rahome.gsfc.nasa.gov>

5

## Example with Simulated Data

Sample Data: Generated with  $LET_0=26, \sigma_{lim}=3.13 \times 10^{-4}, w=70$  and  $s=2.5$

LET <sub>EFF</sub>	7.8	11.03	15.6	28.8	40.73	53.1	57.6	75.1	106.2
Cross Section	0.0E+00	0.0E+00	0.0E+00	1.0E-07	6.3E-06	2.8E-05	4.0E-05	1.1E-04	2.4E-04
Events Observed	0	0	0	1	50	100	100	100	100
Effective Fluence	1.0E+07	1.0E+07	1.0E+07	1.0E+07	8.0E+06	3.6E+06	2.5E+06	9.5E+05	4.2E+05

LET <sub>0</sub> \ $\sigma_{lim}$	20	21	22	23	24	25	26	27	28
2.13E-04	-20.41	-15.29	-12.74	-12.82	-15.57	-21.10	-29.51	-41.02	-56.28
2.63E-04	-33.21	-21.23	-12.18					-13.17	-23.93
3.13E-04	-62.62	-43.77	-28.22	-16.01	-7.19				-8.19
3.63E-04	-103.68	-77.97	-55.92	-37.57	-22.96	-12.15			
4.13E-04	-153.39	-120.81	-92.26	-67.77	-47.37	-31.11	-19.05	-11.37	-8.65
4.63E-04	-209.75	-170.30	-135.26	-104.63	-78.44	-56.73	-39.56	-27.08	-19.86

To be presented by Ray Ladbury at the IEEE Nuclear and Space Radiation Effects Conference (NSREC), July 23-27, 2007 and to be published on <http://rahome.gsfc.nasa.gov>

6

## Example with Simulated Data (Cont'd)

Slice in w-s for best fit cross section and onset LET

W \ S	2.1	2.2	2.3	2.4	2.5	2.6	2.7	2.8	2.9
60	-88.4	-67.1	-49.6	-35.7	-24.8	-16.7	-11.2	-7.9	-6.7
62	-71.1	-51.7	-36.2	-24.1	-15.2	-9.0			
64	-56.5	-39.0	-25.4	-15.2	-8.2				
66	-44.2	-28.6	-16.9	-8.6					-8.1
68	-34.1	-20.3	-10.5						-12.8
70	-25.8	-13.9			0.0			-11.1	-19.1
72	-19.2	-9.2					-9.5	-17.2	-26.9
74	-14.1					-7.9	-15.2	-24.6	-36.1
76	-10.4					-13.1	-22.1	-33.2	-46.3
78	-7.9				-11.0	-19.3	-30.0	-42.8	-57.5
80				-9.2	-16.6	-26.6	-38.9	-53.3	-69.6
82			-7.9	-14.0	-23.1	-34.7	-48.6	-64.6	-82.4

To be presented by Ray Ladbury at the IEEE Nuclear and Space Radiation Effects Conference (NSREC), July 23-27, 2007 and to be published on <http://rahome.gsfc.nasa.gov>

7

## Example with Simulated Data (Cont'd)

LET <sub>EFF</sub>	7.8	11.03	15.6	28.8	40.73	53.1	57.6	75.1	106.2
Cross Section	0.0E+00	0.0E+00	0.0E+00	1.0E-07	6.3E-06	2.8E-05	4.0E-05	1.1E-04	2.4E-04
Events Observed	0	0	0	1	2	4	4	4	4
Effective Fluence	1.0E+07	1.0E+07	1.0E+07	1.0E+07	8.0E+06	3.6E+06	2.5E+06	9.5E+05	4.2E+05

LET <sub>0</sub>	20	21	22	23	24	25	26	27	28
1.13E-04	-6.94						-7.22	-8.89	-11.71
2.13E-04	-8.89								
3.13E-04	-15.57	-10.74	-6.85						
4.13E-04	-24.29	-17.52	-11.96	-7.55					
5.13E-04	-34.16	-25.45	-18.22	-12.40	-7.92				
6.13E-04	-44.76	-34.12	-25.22	-17.98	-12.32	-8.16			

To be presented by Ray Ladbury at the IEEE Nuclear and Space Radiation Effects Conference (NSREC), July 23-27, 2007 and to be published on <http://rahome.gsfc.nasa.gov>

8


## Example with Simulated Data (Cont'd)

W \ S	1.7	1.9	2.1	2.3	2.5	2.7	2.9	3.1	3.3	3.5	3.7	3.9	4.1
45	-43.2	-28.5	-19.4	-13.6	-9.9	-7.6							
50	-34.0	-21.1	-13.2	-8.4									
55	-27.0	-15.6	-8.9										
60	-21.6	-11.5											-7.4
65	-17.4	-8.5										-7.9	-9.8
70	-14.1										-8.2	-10.3	-12.6
75	-11.5									-8.2	-10.5	-13.0	-15.6
80	-9.5								-8.0	-10.5	-13.1	-15.9	-18.7
85	-8.0							-7.4	-10.1	-12.8	-15.8	-18.8	-21.9
90	-6.8						-6.7	-9.4	-12.2	-15.3	-18.5	-21.8	-25.1
95							-8.4	-11.3	-14.5	-17.8	-21.2	-24.8	-28.4
100						-7.2	-10.1	-13.3	-16.7	-20.3	-24.0	-27.7	-31.6
105						-8.7	-11.9	-15.4	-19.0	-22.8	-26.7	-30.7	-34.7
110						-7.1	-10.2	-13.7	-17.4	-21.3	-25.3	-29.4	-33.6
115						-8.4	-11.7	-15.5	-19.4	-23.5	-27.7	-32.0	-36.4
120						-9.7	-13.3	-17.2	-21.4	-25.7	-30.1	-34.6	-39.2
125						-7.6	-11.0	-14.8	-19.0	-23.4	-27.9	-32.5	-37.2
130						-8.6	-12.3	-16.4	-20.7	-25.3	-30.0	-34.8	-39.7
135						-9.7	-13.6	-17.9	-22.4	-27.2	-32.1	-37.0	-42.1
140						-7.3	-10.8	-14.9	-19.4	-24.1	-29.0	-34.1	-39.2

To be presented by Ray Ladbury at the IEEE Nuclear and Space Radiation Effects Conference (NSREC), July 23-27, 2007 and to be published on <http://rahome.gsfc.nasa.gov>

9


## SEE Rate Confidence Contour vs. Event Count



To be presented by Ray Ladbury at the IEEE Nuclear and Space Radiation Effects Conference (NSREC), July 23-27, 2007 and to be published on <http://rahome.gsfc.nasa.gov>

10

## How Event Count affects Estimation



To be presented by Ray Ladbury at the IEEE Nuclear and Space Radiation Effects Conference (NSREC), July 23-27, 2007 and to be published on <http://rahome.gsfc.nasa.gov>

11

## Applications

- Determination of part-to-part and lot-to-lot variability
  - Poisson errors sometimes give an impression of variability
  - Variability is established at significance  $1-\alpha$  if the contours for  $CL = \alpha$  do not overlap
- Test planning—although we don't know a priori how a test will perform, we can simulate over a range of possible distributions to determine the worst-case dependence of rate error on event count
  - Can be used to ensure efficient allocation of test time and resources
    - What ions to use?
    - How much time for each ion?
    - For destructive errors, how many parts to sacrifice at each ion?
  - Estimate derating factors as a function of # of events and confidence level.
- Dividing the data set in post-processing
  - Often events of interest to the application emerge only in post-processing
    - Example: Some SEFI may pose system-level problems, while others do not
    - Example: Only transients larger than a minimum amplitude and longer than a certain duration may pose a threat

To be presented by Ray Ladbury at the IEEE Nuclear and Space Radiation Effects Conference (NSREC), July 23-27, 2007 and to be published on <http://rahome.gsfc.nasa.gov>

12

## Example: Ultra-long Transients for OP293

- Testing on Analog Devices OP293 revealed transients up to 1 ms long
  - Boards were already populated and there was no easy replacement
  - Circuit analysis revealed concern only for transients  $>120\ \mu\text{s}$  and  $>2\text{V}$

LET <sub>EFF</sub> (MeVcm <sup>2</sup> /mg)	Total transients	Transients ( $>120$ ms, $>2\text{ V}$ )	Cross Section (cm <sup>2</sup> )
19.5	751	1	$1 \times 10^{-7}$
28	525	3	$3 \times 10^{-7}$
43	679	5	$5 \times 10^{-7}$
49.5	1303	0	0
87.5	477	2	$2 \times 10^{-7}$


- Testing on Analog Devices OP293 revealed transients up to 1 ms long
  - Boards were already populated and there was no easy replacement
  - Circuit analysis revealed concern only for transients  $>120\ \mu\text{s}$  and  $>2\text{V}$

To be presented by Ray Ladbury at the IEEE Nuclear and Space Radiation Effects Conference (NSREC), July 23-27, 2007 and to be published on <http://rahome.gsfc.nasa.gov>

13

## Possible Extensions of the Method

- This work dealt with Poisson errors, where mean  $\sigma$  follows a Weibull
  - Method can also be extended to model other error including systematic errors



- If we can model it, we can apply this method
  - Errors on fluence, deviations from RPP, Weibull form for  $\sigma$ , and so on.

To be presented by Ray Ladbury at the IEEE Nuclear and Space Radiation Effects Conference (NSREC), July 23-27, 2007 and to be published on <http://rahome.gsfc.nasa.gov>

14

## Conclusions

- Maximum Likelihood methods allow us to bound the SEE rate for a given confidence level IF we can model the errors on  $\sigma$  vs. LET curve
  - If event counts are high systematic errors will dominate
  - Otherwise errors are Poisson
- Allows unambiguous determination of a bounding rate for a given confidence level and data set.
- Applications include
  - Determination of part-to-part and lot-to-lot variability
  - Test Planning
  - Determination of bounding rates for marginal data (e.g. divided data sets)
- Technique can be generalized to include any error we can model
  - Other random errors (including part-to-part variations)
  - Systematic errors if we can characterize and model them

To be presented by Ray Ladbury at the IEEE Nuclear and Space Radiation Effects Conference (NSREC), July 23-27, 2007 and to be published on <http://rahome.gsfc.nasa.gov>

15