

secutive radar profiles are offset slightly (by amounts much less than  $\Delta r$ ) with respect to each other according to the relative change in geodetic altitude. As a consequence, in a case in which the surface area under examination is homogeneous (e.g., an ocean surface), a sequence of consecutive radar profiles of the surface in that area contains samples of the surface response with range resolution ( $\Delta\rho$ ) much finer than the range-increment ( $\Delta\rho \ll \Delta r$ ).

Once the high-resolution surface response has thus become available, the profile of surface clutter can be accurately estimated by use of a conventional maximum-correlation scheme: A trans-

lated and scaled version of the high-resolution surface response is fitted to the observed low-resolution profile. The translation and scaling factors that optimize the fit in a maximum-correlation sense represent (1) the true position of the surface relative to the sampled surface peak and (2) the magnitude of the surface backscatter.

The performance of this algorithm has been tested on CloudSat data acquired over an ocean surface. A preliminary analysis of the test data showed a surface-clutter-rejection ratio over flat surfaces of >10 dB and a reduction of the contaminated altitude over ocean from about 1 km to about 0.5 km (over the ocean).

The algorithm has been embedded in CloudSat L1B processing as of Release 04 (July 2007), and the estimated flat surface clutter is removed in L2B-GEOPROF product from the observed profile of reflectivity (see CloudSat product documentation for details and performance at <http://www.cloudsat.cira.colostate.edu/dataSpecs.php?prodid=1>).

*This work was done by Simone Tanelli, Kyung Pak, Stephen Durden, and Eastwood Im of Caltech for NASA's Jet Propulsion Laboratory.*

*The software used in this innovation is available for commercial licensing. Please contact Karina Edmonds of the California Institute of Technology at (626) 395-2322. Refer to NPO-44873.*

---

## ➤ MODIS Atmospheric Data Handler

*Stennis Space Center, Mississippi*

A number of science data sets are derived from the observations of the Moderate Resolution Imaging Spectroradiometer (MODIS) instrument onboard NASA's Terra and Aqua satellites. These data typically contain information on retrieval techniques, quality-control flags, and geo-referencing information. These datasets, distributed in HDF (Hierarchical Data Format), must be further processed to extract relevant information for weather analysis studies and numerical models input. The MODIS-Atmosphere Data Handler software converts the HDF data to ASCII format, and outputs: (1) atmospheric profiles

of temperature and dew point and (2) total precipitable water. Quality-control data are also considered in the export procedure.

The package currently consists of programs to process the MOD05 and MOD07 data products from MODIS. The software is written using the C programming language and contains Makefiles for easier compilation and installation. The MODIS-ADH software helps ease the overhead involved in data processing so that the numerical modelers may concentrate on their science and modeling tasks rather than manipulating data for their models.

*This program was written by Valentine Anantharaj and Patrick Fitzpatrick of the Northern Gulf Institute at Mississippi State University for Stennis Space Center.*

*Inquiries concerning rights for its commercial use should be addressed to:*

*Mississippi State University  
Northern Gulf Institute  
BLDG 1103, Room 233  
Stennis Space Center, MS 39529  
Phone No.: (228) 688-1157  
Fax: (228) 688-7100  
E-mail: val@gri.msstate.edu*

*Refer to SSC-00267, volume and number of this NASA Tech Briefs issue, and the page number.*

---

## ➤ Multibeam Altimeter Navigation Update Using Faceted Shape Model

**The model is applicable to a body having almost any complex shape.**

*NASA's Jet Propulsion Laboratory, Pasadena, California*

A method of incorporating information, acquired by a multibeam laser or radar altimeter system, pertaining to the distance and direction between the system and a nearby target body, into an estimate of the state of a vehicle upon which the system is mounted, involves the use of a faceted model to represent the shape of the target body. In the original intended application, the vehicle would be a spacecraft and the target body would be an asteroid, comet, or similar body that the spacecraft was required to approach. The method could

also be used in navigating aircraft at low altitudes over terrain that is rough and/or occupied by objects of significant structure.

Fundamentally, what one seeks to measure is the distance from the vehicle to the target body. The present method is the product of a generalization of a prior method of altimetry, in which the target body has a simple shape represented by a spherical or ellipsoidal model. In principle, the estimate of distance or altitude obtained by use of a multibeam altimeter can be more robust

than that obtained by use of a single-beam altimeter, but if the surface of the target body has a complex and/or irregular shape, then it becomes more difficult to define the distance and compute the distance from readings of a multibeam altimeter.

The faceted shape model of the present method facilitates the definition and computation of distance to a target object having almost any shape, no matter how irregular and complex. The use of faceted shape models to represent complex three-dimensional objects is com-