#### UPDATE ON DOE ADVANCED IGCC/H2 GAS TURBINE

Ray Chupp GE Energy Greenville, South Carolina



### GE Energy

# Update on DOE Advanced IGCC/H2 Gas Turbine

DE-FC26-05NT42643

Ray Chupp

### 2008 NASA Seal/Secondary Air System Workshop November 18-19, 2008

- 1. This material is based upon work supported by the Department of Energy under Award Number DE-FC26-05NT42643
- 2. This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.



### **Acknowledgements**

GE would like to extend a special thanks to the US Department of Energy National Energy Technology Laboratory and the following individuals for their past and continued support on the DOE/GE "Advanced IGCC/Hydrogen Gas Turbine Development Program"

#### **Rich Dennis**

Turbine Technology Manager
Office of Fossil Energy
U.S. Department of Energy
National Energy Technology Laboratory



### Ron Harp

Project Manager
Power Systems Division
U.S. Department of Energy
National Energy Technology Laboratory





# **IGCC - H<sub>2</sub> Gas Turbine Landscape**

### **Objective**

**Approach** 

Capability

Cleaner Energy from Coal

via

IGCC with Carbon Capture

#### Today

**GE** existing products:

7FB-H2

- · High-H2 GT fleet
- · Successful operation
- Diffusion flame
- Diluent for NOx



#### **Future**

**Technology Advances** 

- Reduced NOx (2ppm)
- Increased Performance (+3-5pts)
- DOE Program Increased Output
  - Reduced Cost

Combustion v

**Turbine** 

**Materials Systems** 

#### **Program Timeline**

2010 2011 2013 - TBD 2006 Phase III (Not Yet Awarded) Phase I (CPT) Phase II (Awarded, In Progress) Concept Design **Detailed Design & Component Validation Test** Final Design & Field Evaluation




### **Combustion Technology:**

Modeling
Subscale testing
Limited full scale, multi nozzle testing

Phase I... focus on fundamentals

- 'Chemistry' evaluation fuels, mixing, residence time, EGR
- Benchmark existing NG designs on high H2 fuels
- Evaluate 1<sup>st</sup> Gen prototypes (based on traditional designs)
- Evaluate 2<sup>nd</sup> Gen prototypes (more 'out-of-the-box'
   designed specifically for high H2)



#### Phase I Goal Complete: Select top two concepts for further evaluation in Phase II



Phase II... design optimization

- Optimize designs for resistance to flashback, flameholding, dynamics
- Obtain data to minimize risk
- Validate the technology

Status: Initial full can/larger scale testing of down selected concepts providing promising results, continuing to drive down emissions and extend operability




### **Materials Technology:**

Phase I... characterization and development

- Characterizing the environment
- Identification of candidate material/coating systems
- Development of screening tests for material systems (corrosion, erosion, impact)
- CMC/EBC development



#### Phase I Goal Complete: Screened list of candidate material systems for Phase II





Phase II... enabling turbine technology improvements


- Validation of material systems at component level
- Field testing of components where applicable

**Status:** Interim down select completed with significant capability improvements, line of sight to program targets

### **Turbine Technology:**

Phase I... identifying turbine technology improvements

#### Phase I Goal Complete: Technology development plan for Phase II



#### **Phase II Goal**: Validated technologies at the component level




# **Turbine - Aerodynamics**


### **Advanced Design**

- work splits, reaction, and airfoil counts.
- 3-D Aero & Endwall Contouring

### **Turbine Rig Testing**

Learning, Validation








### **Turbine - Mechanical**

### **Turbine Goal:**

Higher component efficiency with higher flow rates

### **Turbine Efforts Launched:**

- Conceptual design studies on different turbine concepts – aerodynamic and mechanical
- Advanced technology development to <u>reduce</u> <u>parasitic leakages</u>
  - Transition Piece/Stage 1 nozzle seal
  - Turbine interstage beneath nozzle
- Advanced technology dev. to address turbine blade durability
  - Damping effect on aeromechanics
  - Fretting and wear





Fretting & Wear Test





6

## **Turbine – Heat Transfer/Sealing Plans**

#### Cooling Flow Reduction:

- Focus on <u>improving turbine hot gas path part cooling</u> <u>efficiency</u>
- Applicable to current metallic turbine components and synergistic with advance materials
- Address challenges of IGCC/hydrogen fuel environment (for example, possible cooling hole plugging)

#### Leakage Flow Reduction:

- Focus on <u>decreasing turbine parasitic leakages</u>, i.e. between static-to-static, static-to-rotating, and rotating-to-rotating turbine parts
- Develop improved seal designs in a variety of important areas

#### • Purge Flow Reduction:

- Focus on <u>decreasing required flows</u> to keep rotor disk cavities within temperature limits
- Develop improved sealing at the cavity rims and modified flow geometries to minimize hot gas ingestion and aerodynamic impact









### Cooling—Advanced Film Cooling

Diffuser and Chevron shaped film cooling hole geometries\*

Shaped "Baseline" Chevron 1 "Flat"

Chevron 2 "Tent"

Chevron 3 "Arcuate"

**Example geometries for shallow** trench film cooling\*













- 0.66 mm diameter · 30-deg to surface tangent
- · 20-deg lateral diffuser
- 10-deg laidback

· 0.46 mm diameter "chevron" edge troughs

Results to date show:

- Some hole/trench configurations provide up to 20% higher average film effectiveness than diffuser shaped holes.
- Aerodynamic mixing losses were also measured





#### **Blowing Ratio or Pressure Ratio**


Low **Moderate** High






**Shaped Holes** 

**Chevron Holes** 






Full-surface film effectiveness data for diffuser shaped holes and chevron holes.



\* Hole shapes based on US patents: 7,328,580, 6,234,755, 6,234,755, and 2008/0057271A1.

#### Laterally averaged film effectiveness curves




Distance Downstream of Holes / Hole Diameter

2008 NASA Seal/Secondary Air System Workshop, No. 18, 2008, Ohio Aerospace Institute (OAI)—Copyright 2008 General Electric Company

### **Advanced Sealing—Four Focus Locations**


#### **Transition Piece/Stage 1 Nozzle Seal**





- New flow fixture built to test engine size seals.
- Relative axial movement modeled.
- Leakage through various paths measured.
- Current and new seal designs tested to optimize seal design


#### **Turbine Interstage Seal**




- New seal approaches investigated.
- · Initial testing on 5-in flow rig.
- Intermediate size rig being built


#### **Angel Wing Seal**







#### **High Pressure Packing Seal**



- Passive retractable brush seal design based on successful GE steam turbine retractable seals
- Testing at full pressure conditions

- Identified optimum abradable geometry/material vs. location
- Flow resistance quantified via. CFD
- Honeycomb → good flow restriction for engine radial closures
- Studying aluminizing honeycomb material to increase oxidation resistance







12

### Purge Flow—Transonic Annular Cascade Screening Tests

Regional static pressure distributions, Infrared surface temperature maps, trench and buffer cavity cooling effectiveness.






- Annular sector cascade rig run to gather data on rim seal region pressures, temperatures, and hot gas ingestion for various geometries.
- Data used to validate detailed CFD model analysis.
- Potential improved rim seal configurations being tested.



### Purge Flow—Rotating Wheelspace Rig Development



Wheelspace Rig Schematic

**Test Section Features** 

- Scaled baseline geometry with flexibility to model other engine configurations
- Features to allow testing variations.
- Rotating and static instrumentation
- · Configurations will be tested to achieve optimum designs.
- Data will be used to validate detailed CFD models with rotation.



# **Summary and Conclusions**

- 1. Strong program structured to meet DOE goals on efficiency, emissions, and capital cost
- 2. Phase I completed all milestones met and significant progress made:
  - Obtained near-entitlement NOx emissions at temperatures of interest for this program
  - Turbine technologies identified to achieve DOE goals development will expand in Phase II

### 3. Phase II Underway:

- Combustion focus narrowed to two concepts
- <u>Materials</u> focus on optimization of materials/coating systems for environment
- Heavier turbine effort on mechanical and aero aspects plus:
  - > Cooling—initially looking at advanced film cooling
  - > Sealing—focusing on four key leakage areas
  - > Purge flow—initially using a cascade rig to screen configurations & validate CFD, rotating rig being developed

