

sion of polychromatic light, it would be possible to utilize broader wavelength ranges, maintain high transmissivity through use of wavelengths farther from the edges of the photonic bandgaps, take advantage of the reduction in non-linearity to simplify the positioning of optical components, and take advantage of larger crystal spatial periods to further simplify fabrication. The design parameters that could be varied to obtain the desired properties include the angle

of incidence, the angle of the exit surface, and the thicknesses of the layers.

One-dimensional photonic crystal superprisms for visible and infrared wavelengths could be fabricated on semiconductor wafers and, hence, could be integrated monolithically with other miniature optical components. In one example of this approach, a 1D photonic crystal superprism would be fabricated by patterning and anisotropic etching of one of two silicon layers of a silicon-on-in-

ulator substrate (see Figure 2). In this case, the insulator ( $\text{SiO}_2$ ) would not only provide structural support, because the index of refraction of  $\text{SiO}_2$  is lower than that of Si, the  $\text{SiO}_2$  layer would also act as an optical cladding layer to confine light to the 1D photonic crystal.

*This work was done by David Z. Ting of Caltech for NASA's Jet Propulsion Laboratory. Further information is contained in a TSP (see page 1). NPO-30594*

---

## Rapid Analysis of Mass Distribution of Radiation Shielding

*Lyndon B. Johnson Space Center, Houston, Texas*

Radiation Shielding Evaluation Toolset (RADSET) is a computer program that rapidly calculates the spatial distribution of mass of an arbitrary structure for use in ray-tracing analysis of the radiation-shielding properties of the structure. RADSET was written to be used in conjunction with unmodified commercial computer-aided design

(CAD) software that provides access to data on the structure and generates selected three-dimensional-appearing views of the structure. RADSET obtains raw geometric, material, and mass data on the structure from the CAD software. From these data, RADSET calculates the distribution(s) of the masses of specific materials about any user-specified

point(s). The results of these mass-distribution calculations are imported back into the CAD computing environment, wherein the radiation-shielding calculations are performed.

*This program was written by Edward Zapp of Lockheed Martin Corp. for Johnson Space Center. Further information is contained in a TSP (see page 1). MSC-23935*

---

## Modeling Magnetic Properties in EZTB

*NASA's Jet Propulsion Laboratory, Pasadena, California*

A software module that calculates magnetic properties of a semiconducting material has been written for incorporation into, and execution within, the Easy (Modular) Tight-Binding (EZTB) software infrastructure. [EZTB is designed to model the electronic structures of semiconductor devices ranging from bulk semiconductors, to quantum wells, quantum wires, and quantum dots. EZTB implements an empirical tight-binding mathematical model of the underlying physics.]

This module can model the effect of a magnetic field applied along any direction and does not require any adjustment of model parameters. The module has thus far been applied to study the performances of silicon-based quantum computers in the presence of magnetic fields and of miscut angles in quantum wells. The module is expected to assist experimentalists in fabricating a spin qubit in a Si/SiGe quantum dot. This software can be executed in almost any Unix operating

system, utilizes parallel computing, can be run as a Web-portal application program. The module has been validated by comparison of its predictions with experimental data available in the literature.

*This program was written by Seungwon Lee and Paul von Allmen of Caltech for NASA's Jet Propulsion Laboratory.*

*This software is available for commercial licensing. Please contact Karina Edmonds of the California Institute of Technology at (626) 395-2322. Refer to NPO-44782.*

---

## Deep Space Network Antenna Logic Controller

*NASA's Jet Propulsion Laboratory, Pasadena, California*

The Antenna Logic Controller (ALC) software controls and monitors the motion control equipment of the 4,000-metric-ton structure of the Deep Space Network 70-meter antenna. This program coordinates the control of 42 hydraulic pumps, while monitoring several interlocks for personnel and equipment safety. Remote operation of the ALC runs via the Antenna Monitor &

Control (AMC) computer, which orchestrates the tracking functions of the entire antenna.

This software provides a graphical user interface for local control, monitoring, and identification of faults as well as, at a high level, providing for the digital control of the axis brakes so that the servo of the AMC may control the motion of the antenna. Specific

functions of the ALC also include routines for startup in cold weather, controlled shutdown for both normal and fault situations, and pump switching on failure.

The increased monitoring, the ability to trend key performance characteristics, the improved fault detection and recovery, the centralization of all control at a single panel, and the simplifi-