

cludes chemical models developed at JPL. The products are synthetic images and spectra for comparison with Spitzer measurements.

Radiative transfer in a protostellar disk is primarily affected by absorption and emission processes in the dust and in molecular gases such as H₂, CO, and HCO. The magnitude of the optical absorption and emission is determined by the population of the electronic, vibrational, and rotational energy levels. The population of the molecular level is in turn determined by the intensity of the

radiation field. Therefore, the intensity of the radiation field and the population of the molecular levels are interdependent quantities.

To meet the computational challenges of solving for the coupled radiation field and electronic level populations in disks having wide ranges of optical depths and spatial scales, the tool runs in parallel on the JPL Dell Cluster supercomputer with C++ and Fortran compiler with a Message Passing Interface. Because this software has been developed on a distributed com-

puting platform, the modeling of systems previously beyond the reach of available computational resources is possible.

This program was written by Paul Von Allmen and Neal Turner of Caltech for NASA's Jet Propulsion Laboratory. Further information is contained in a TSP (see page 1).

The software used in this innovation is available for commercial licensing. Please contact Karina Edmonds of the California Institute of Technology at (626) 395-2322. Refer to NPO-44467.

Composite Pulse Tube

Axial leakage of heat is reduced.

Lyndon B. Johnson Space Center, Houston, Texas

A modification of the design of the pulse tube in a pulse-tube cryocooler reduces axial thermal conductance while preserving radial thermal conductance. It is desirable to minimize axial thermal conductance in the pulse-tube wall to minimize leakage of heat between the warm and cold ends of the pulse tube. At the same time, it is desirable to maximize radial thermal conductance at the cold end of the pulse tube to ensure adequate thermal contact between (1) a heat exchanger in the form of a stack of copper screens inside the pulse tube at the cold end and (2) the remainder of the cold tip, which is the object to which the heat load is applied and from which heat must be removed. The modified design yields a low-heat-leak pulse tube that can be easily integrated with a cold tip.

A typical pulse tube of prior design is either a thin-walled metal tube or a metal tube with a nonmetallic lining. It

is desirable that the outer surface of a pulse tube be cylindrical (in contradistinction to tapered) to simplify the design of a regenerator that is also part of the cryocooler. Under some conditions, it is desirable to taper the inner surface of the pulse tube to reduce acoustic streaming. The combination of a cylindrical outer surface and a tapered inner surface can lead to unacceptably large axial conduction if the pulse tube is made entirely of metal. Making the pulse-tube wall of a nonmetallic, low-thermal-conductivity material would not solve the problem because the wall would not afford the needed thermal contact for the stack of screens in the cold end.

The modified design calls for fabricating the pulse tube in two parts: a longer, nonmetallic part that is tapered on the inside and cylindrical on the outside and a shorter, metallic part that is cylindrical on both the inside and the

outside. The nonmetallic part can be made from G-10 fiberglass-reinforced epoxy or other low-thermal-conductivity, cryogenically compatible material. The metallic part must have high thermal conductivity in the cryogenic temperature range and would typically be made of pure copper to satisfy this requirement. The metallic part is bonded to the nonmetallic part with epoxy. Copper screens are inserted in the metallic part to form the cold-end heat exchanger, then the assembled pulse tube is inserted in the cold tip.

This work was done by Jerry L. Martin and Jason H. Cloyd of Mesoscopic Devices, LLC for Johnson Space Center. For further information, contact:

*Jerry L. Martin
Mesoscopic Devices, LLC
510 Compton Street, Suite 106
Broomfield, CO 80020
Phone No.: (303) 466-6968
Refer to MSC-23522*

Photometric Calibration of Consumer Video Cameras

In imaging of point sources, dynamic ranges can be extended beyond saturation levels.

Marshall Space Flight Center, Alabama

Equipment and techniques have been developed to implement a method of photometric calibration of consumer video cameras for imaging of objects that are sufficiently narrow or sufficiently distant to be optically equivalent to point or line sources. Heretofore, it has been difficult to calibrate consumer video cameras,

especially in cases of image saturation, because they exhibit nonlinear responses with dynamic ranges much smaller than those of scientific-grade video cameras. The present method not only takes this difficulty in stride but also makes it possible to extend effective dynamic ranges to several powers of ten beyond saturation

levels. The method will likely be primarily useful in astronomical photometry. There are also potential commercial applications in medical and industrial imaging of point or line sources in the presence of saturation.

This development was prompted by the need to measure brightnesses of de-