



# Status of Kilowatt-Class Stirling Power Conversion Using a Pumped NaK Loop for Thermal Input

*Maxwell H. Briggs*  
*QinetiQ North America, Cleveland, Ohio*

*Steven M. Geng*  
*Glenn Research Center, Cleveland, Ohio*

*Malcolm G. Robbie*  
*QinetiQ North America, Cleveland, Ohio*

## NASA STI Program . . . in Profile

Since its founding, NASA has been dedicated to the advancement of aeronautics and space science. The NASA Scientific and Technical Information (STI) program plays a key part in helping NASA maintain this important role.

The NASA STI Program operates under the auspices of the Agency Chief Information Officer. It collects, organizes, provides for archiving, and disseminates NASA's STI. The NASA STI program provides access to the NASA Aeronautics and Space Database and its public interface, the NASA Technical Reports Server, thus providing one of the largest collections of aeronautical and space science STI in the world. Results are published in both non-NASA channels and by NASA in the NASA STI Report Series, which includes the following report types:

- **TECHNICAL PUBLICATION.** Reports of completed research or a major significant phase of research that present the results of NASA programs and include extensive data or theoretical analysis. Includes compilations of significant scientific and technical data and information deemed to be of continuing reference value. NASA counterpart of peer-reviewed formal professional papers but has less stringent limitations on manuscript length and extent of graphic presentations.
- **TECHNICAL MEMORANDUM.** Scientific and technical findings that are preliminary or of specialized interest, e.g., quick release reports, working papers, and bibliographies that contain minimal annotation. Does not contain extensive analysis.
- **CONTRACTOR REPORT.** Scientific and technical findings by NASA-sponsored contractors and grantees.

- **CONFERENCE PUBLICATION.** Collected papers from scientific and technical conferences, symposia, seminars, or other meetings sponsored or cosponsored by NASA.
- **SPECIAL PUBLICATION.** Scientific, technical, or historical information from NASA programs, projects, and missions, often concerned with subjects having substantial public interest.
- **TECHNICAL TRANSLATION.** English-language translations of foreign scientific and technical material pertinent to NASA's mission.

Specialized services also include creating custom thesauri, building customized databases, organizing and publishing research results.

For more information about the NASA STI program, see the following:

- Access the NASA STI program home page at <http://www.sti.nasa.gov>
- E-mail your question via the Internet to [help@sti.nasa.gov](mailto:help@sti.nasa.gov)
- Fax your question to the NASA STI Help Desk at 443-757-5803
- Telephone the NASA STI Help Desk at 443-757-5802
- Write to:  
NASA Center for AeroSpace Information (CASI)  
7115 Standard Drive  
Hanover, MD 21076-1320



# Status of Kilowatt-Class Stirling Power Conversion Using a Pumped NaK Loop for Thermal Input

*Maxwell H. Briggs*  
*QinetiQ North America, Cleveland, Ohio*

*Steven M. Geng*  
*Glenn Research Center, Cleveland, Ohio*

*Malcolm G. Robbie*  
*QinetiQ North America, Cleveland, Ohio*

Prepared for the  
Seventh International Energy Conversion Engineering Conference (IECEC)  
sponsored by the American Institute of Aeronautics and Astronautics  
Denver, Colorado, August 2-5, 2009

National Aeronautics and  
Space Administration

Glenn Research Center  
Cleveland, Ohio 44135

## Acknowledgments

This work was performed for the NASA Exploration Technology Development Project and the Fission Surface Power Project. The authors wish to acknowledge the technical contributions of Barry Penswick of Penswick Consulting and Rodger Dyson of GRC for their support relative to the design of the NaK heater heads for the 1-kWe Stirling power convertors. In addition, the authors wish to thank Dave Shade of Sunpower, Inc., for technical support during the design and assembly phases of this project.

This report contains preliminary findings,  
subject to revision as analysis proceeds.

Trade names and trademarks are used in this report for identification  
only. Their usage does not constitute an official endorsement,  
either expressed or implied, by the National Aeronautics and  
Space Administration.

*Level of Review:* This material has been technically reviewed by technical management.

Available from

NASA Center for Aerospace Information  
7115 Standard Drive  
Hanover, MD 21076-1320

National Technical Information Service  
5301 Shawnee Road  
Alexandria, VA 22312

Available electronically at <http://gltrs.grc.nasa.gov>

# **Status of Kilowatt-Class Stirling Power Conversion Using a Pumped NaK Loop for Thermal Input**

Maxwell H. Briggs  
QinetiQ North America  
Cleveland, Ohio 44135

Steven M. Geng  
National Aeronautics and Space Administration  
Glenn Research Center  
Cleveland, Ohio 44135

Malcolm G. Robbie  
QinetiQ North America  
Cleveland, Ohio 44135

## **Abstract**

Free-piston Stirling power conversion has been identified as a viable option for potential Fission Surface Power (FSP) systems on the Moon and Mars. Proposed systems consist of two or more Stirling convertors, in a dual-opposed configuration, coupled to a low-temperature uranium-dioxide-fueled, liquid-metal-cooled reactor. To reduce developmental risks associated with liquid-metal loop integration, a test rig has been built to evaluate the performance of a pair of 1-kW free-piston Stirling convertors using a pumped sodium-potassium (NaK) loop for thermal energy input. Baseline performance maps have been generated at the Glenn Research Center (GRC) for these 1-kW convertors operating with an electric heat source. Each convertor was then retrofitted with a custom-made NaK heater head and integrated into a pumped NaK system at the Marshall Space Flight Center (MSFC). This paper documents baseline testing at GRC as well as the progress made in integrating the Stirling convertors into the pumped NaK loop.

## **Introduction**

Free-piston Stirling power conversion has been identified as a viable option for potential fission surface power (FSP) systems on the Moon and Mars (Refs. 1 to 4). Recent studies have focused on the use of Stirling convertors coupled to a low-temperature (<900 K), uranium-dioxide-fueled, liquid-metal-cooled reactor for potential lunar application in year 2020 (Refs. 2 and 3). The system is considered a low development risk based on the use of terrestrial-derived reactor technology and conventional materials. In addition, all materials and components are compatible with the lunar and Martian environments. Therefore, Mars-based power conversion system designs are expected to be very similar to lunar designs in configuration, set-up, and operations (Ref. 4).

One of the key technical hurdles identified in the development of such a system is the integration of the liquid-metal-pumped loop with a multi-kilowatt Stirling power conversion system (Ref. 4). While earlier Glenn Research Center (GRC) efforts (Ref. 5) have clearly demonstrated the application of liquid metals as a heat transport medium for a Stirling cycle convertor, it is important to note that these heat exchangers utilized two-phase heat pipes in the energy transfer process. The heat transfer characteristics of condensing liquid-metal vapor in heat pipe applications differ substantially from those expected in the single-phase liquid-metal to gas heat exchangers used for heat addition in FSP applications. To reduce developmental risks associated with integrating these liquid-metal to gas heat exchangers into a Stirling power conversion system, a pair of 1-kWe Stirling convertors have been integrated into a pumped NaK loop at the Marshall Space Flight Center (MSFC). The 1-kWe Stirling convertors were built by Sunpower of Athens, Ohio. The performance of these Stirling convertors will be compared with the baseline

performance data taken at GRC and described herein. These comparisons will serve as a proof of concept of kilowatt-level Stirling power conversion using single-phase pumped NaK for thermal input.

## Baseline Testing

### Test Setup

A test rig was built at GRC to measure the baseline performance of these converters using electric cartridge heaters for thermal input. Testing was conducted in the Stirling Research Laboratory at GRC from March through May 2008. The test rig, shown in Figure 1 and represented schematically in Figure 2, consists of two variacs (one per engine), two free-piston Stirling converters in a dual-opposed configuration, a cold-end water chiller, a helium fill station, two AC power supplies (used for piston control), and a data acquisition system.

Power is provided to the electrical heating elements through two variacs that receive 208 VAC from the facility power grid. Piston frequency and amplitude, as well as convertor synchronization were controlled using two AC power supplies that apply an AC voltage across the alternator of each convertor. Electric power produced by the alternators was dissipated using  $39.7 \Omega$  load resistors. Waste heat was rejected to a circulating water loop that is cooled by a Neslab HX-300 recirculating chiller. Hot-end, cold-end, and alternator housing temperatures, as well as all coolant inlet and exit temperatures were monitored using type-N thermocouples. Cooling water flow rates were measured using turbine flow meters on the cooling supply line. Piston and displacer amplitudes were calculated from Fast Linear Displacement Transducer (FLDT) position sensor measurements.



Figure 1.—The 1-kW dual-opposed Stirling test rig as assembled at GRC.




Figure 2.—The 1-kW dual-opposed Stirling test rig schematic.

## Method

Baseline performance map testing involved measuring power output and gross thermal efficiency (Ref. 6) of each convertor over a matrix of hot-end and cold-end temperatures and a range of piston amplitudes. These convertors were designed to operate at a charge pressure of 450 psia, a hot-end temperature of 550 °C, and a cold-end temperature of 50 °C, at a piston amplitude of 10 mm. During performance map testing, the convertor hot-end temperature was varied between 400 and 550 °C, in increments of 50 °C, at cold-end temperatures of 30, 40, 50, and 70 °C. At the design hot-end and cold-end temperatures, the intended power piston amplitude test range was 6 to 11 mm (1 mm increments). At all other hot-end and cold-end temperatures, the intended power piston amplitude test range was 9 to 11 mm (1 mm increments).

Constraints on the maximum voltage across the cartridge heaters limited the maximum piston amplitude to 10.5 mm during 550 °C hot-end tests. Constraints on the minimum power factor limited the maximum piston amplitude to 9 mm during all 30 °C cold-end tests. This constraint also limited maximum piston amplitude to 9 mm during 40 °C cold-end tests at hot-end temperatures of 400 and 450 °C. For all tests in which power factor constraints prevented the acquisition of data beyond a 9 mm piston amplitude, data was acquired at a piston amplitude of 8 mm to expand the data range.

## Results

Each datapoint shown in the performance maps shown in Figures 3 and 4 is the average of 30 measurements taken at ten-second intervals over a 5-min period. Each 5-min period began when the alternator gas temperature (the last temperature to reach steady-state) changed at a rate of no more

than 1 °C over a 5-min period. Manufacturer’s data shows that the actual cold-end temperature can be 2 to 6 °C warmer than the cooling water temperature. The cold-end temperatures reported are estimated from correlations based on manufacturer’s data, *not* the cooling water temperature. The legends shown in Figures 3 and 4 indicate the hot and cold-end temperatures of the convertors in °C.




Figure 3.—Total power output versus piston amplitude at various operating conditions.




Figure 4.—Average convertor efficiency versus piston amplitude at various operating conditions.



The total power output is the sum of the individual power output of each convertor, and is shown in Figure 3 at various operating conditions. As expected, the total power output increases with both increasing temperature ratio and increasing piston amplitude. The maximum total power of 2240 W<sub>e</sub> was produced at a 550 °C hot-end, 40 °C cold-end temperature with a piston amplitude of 10.5 mm. This power level was achieved at a system gross thermal efficiency of 28.6 percent. At this operating point, the maximum piston amplitude of 11 mm could not be achieved because of the constraints on maximum voltage across the electric resistance heaters described above.

The ratio of the total electrical power output of both convertors to the total electrical input to the cartridge heaters is defined as the gross thermal efficiency (Ref. 6) and is plotted in Figure 4 at various operating conditions. As expected, the gross thermal efficiency increases with increasing temperature ratio. For a given set of hot-end and cold-end temperatures, the maximum gross thermal efficiency occurs between 8 and 9 mm piston amplitude. The maximum gross thermal efficiency declines at piston amplitudes above 9 mm most likely due to heater head heat transfer limitations at the higher piston amplitudes. In the cases where the temperature ratio is approximately equal (i.e., 500 °C hot-end/50 °C cold-end and 550 °C hot-end/70 °C cold-end) the efficiency versus piston amplitude curves are very similar. The maximum gross thermal efficiency of 30.0 percent was achieved at operating temperatures of 550 °C hot-end, and 30 °C cold-end and a piston amplitude of 9 mm. At this operating point, the total power was 1820 W<sub>e</sub>.

## **Current Convertor Configuration**

### **Heater Head Modification**

The design process for the NaK heater heads began with considering several fluid housing geometries. The desire to have a uniform fluid flow while minimizing circumferential temperature distribution led to the geometry shown in Figure 5. A more detailed discussion of candidate geometries and the selection process was reported by Dyson (2008) (Ref. 7). The chosen design consists of an inlet plenum in which NaK impinges on the dome of the hot end of the Stirling convertor, then flows axially across the Stirling acceptor region before accumulating in a torus, which drains the NaK outlet. Once this general geometry was selected, a more detailed fluid flow and structural analysis was performed. The key design parameters of the NaK heater head are: (1) capable of transferring approximately 4500 W of thermal energy into the Stirling convertor, (2) NaK inlet temperature of 825 K, (3) designed for optimal performance at a NaK flow rate of 0.55 kg/s, (4) NaK velocities are below 1 m/s, and (5) the pressure drop between the inlet and outlet is less than 1 psi.

The region of interest, structurally, is the weld which attaches the NaK head to the Stirling convertor. Detailed finite element analysis, focused on this region, was conducted to verify that this weld will maintain structural integrity throughout testing, taking into account rupture, fatigue, and creep.

Fabrication of the NaK heater heads and assembly of the heads onto the Stirling convertors offered unique challenges to the manufacturing community. Welding components to finished goods was difficult. The challenge was further complicated by the need to limit distortions to thousandths of an inch on high value hardware. As a resolution to these issues, a micro TIG (tungsten inert gas) welding technique was selected. The final head had minimal distortion (0.002 in.) and passed dye penetration, hydro, and helium leak tests.

### **NaK Loop Integration**

Following fabrication and integration of the NaK heater heads onto the Stirling convertor, the modified 1-kW convertors were installed in a pumped NaK loop test facility at MSFC. This loop consists of an upper and lower reservoir to accommodate NaK expansion during heating, a custom built Annular Linear Induction Pump (ALIP), an electrically powered NaK heater, a gas cooler, and a custom flow meter. The Stirling convertors were plumbed in immediately downstream of the NaK heater and upstream of the gas cooler. A more complete description of the NaK loop is described by Garber (2008) (Ref. 8). Figure 6 shows the Stirling convertors as installed at MSFC.




Figure 5.—NaK heater head installed on 1-kWe Stirling power convertor.




Figure 6.—Stirling convertors as installed in the MSFC pumped NaK loop test facility.

## Conclusion

A baseline performance map has been established for a pair of 1-kW Stirling convertors that used electrical resistance heating elements for thermal input. The electrical resistance heating elements used during the baseline tests have been replaced with NaK-compatible heater heads and the convertors have been integrated into the pumped-NaK loop at the Marshall Space Flight Center. Comparison between the current test data and data to be taken using a NaK pumped loop for thermal input, will provide valuable information about NaK heater head design and overall power conversion unit design. This information will be crucial to the development of free-piston Stirling technology for use in fission surface power applications.

## References

1. Mason, L.S., "A Comparison of Fission Power System Options for Lunar and Mars Surface Applications," NASA/TM—2006-214120, 2006.
2. Mason, L.S., "A Practical Approach to Starting Fission Surface Power Development," NASA/TM—2006-214366, 2006.
3. Mason, L.S., Poston, D., Qualls, L., "System Concepts for Affordable Fission Surface Power," NASA/TM—2008-215166, 2008.
4. Geng, S.M., Mason, L.S., Dyson, R.W., Penswick, L.B., "Overview of Multi-Kilowatt Free-Piston Stirling Conversion Research at GRC," NASA/TM—2008-215061, 2008.
5. Dhar, M., "Stirling Space Engine Program," NASA/CR—1999-209164/VOL1, 1999.
6. Crowley, J.L., "Efficiency Terms for Stirling Engine Systems," ORNL/CON—131, 1983.
7. Dyson, R.W., Penswick, L.B., Robbie, M.G., and Geng, S.M., "Investigation of Liquid Metal Heat Exchanger Designs for Fission Surface Power," *6<sup>th</sup> International Energy Conversion Engineering Conference (IECEC)*, AIAA-2008-5733, Cleveland, OH, 2008.
8. Garber, A., "Modifications to the Fission Surface Power Primary Test Circuit," *International Congress on Advances in Nuclear Power Plant*, Paper 8254.

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188		
<p>The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.</p> <p>PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.</p>					
<b>1. REPORT DATE (DD-MM-YYYY)</b> 01-06-2010		<b>2. REPORT TYPE</b> Technical Memorandum		<b>3. DATES COVERED (From - To)</b>	
<b>4. TITLE AND SUBTITLE</b> Status of Kilowatt-Class Stirling Power Conversion Using a Pumped NaK Loop for Thermal Input			<b>5a. CONTRACT NUMBER</b>		
			<b>5b. GRANT NUMBER</b>		
			<b>5c. PROGRAM ELEMENT NUMBER</b>		
<b>6. AUTHOR(S)</b> Briggs, Maxwell, H.; Geng, Steven, M.; Robbie, Malcolm, G.			<b>5d. PROJECT NUMBER</b>		
			<b>5e. TASK NUMBER</b>		
			<b>5f. WORK UNIT NUMBER</b> WBS 463169.04.03.04.01.01		
<b>7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)</b> National Aeronautics and Space Administration John H. Glenn Research Center at Lewis Field Cleveland, Ohio 44135-3191			<b>8. PERFORMING ORGANIZATION REPORT NUMBER</b> E-17040-1		
<b>9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)</b> National Aeronautics and Space Administration Washington, DC 20546-0001			<b>10. SPONSORING/MONITOR'S ACRONYM(S)</b> NASA		
			<b>11. SPONSORING/MONITORING REPORT NUMBER</b> NASA/TM-2010-216265		
<b>12. DISTRIBUTION/AVAILABILITY STATEMENT</b> Unclassified-Unlimited Subject Category: 20 Available electronically at <a href="http://gltrs.grc.nasa.gov">http://gltrs.grc.nasa.gov</a> This publication is available from the NASA Center for AeroSpace Information, 443-757-5802					
<b>13. SUPPLEMENTARY NOTES</b>					
<b>14. ABSTRACT</b> Free-piston Stirling power conversion has been identified as a viable option for potential Fission Surface Power (FSP) systems on the Moon and Mars. Proposed systems consist of two or more Stirling convertors, in a dual-opposed configuration, coupled to a low-temperature uranium-dioxide-fueled, liquid-metal-cooled reactor. To reduce developmental risks associated with liquid-metal loop integration, a test rig has been built to evaluate the performance of a pair of 1-kW free-piston Stirling convertors using a pumped sodium-potassium (NaK) loop for thermal energy input. Baseline performance maps have been generated at the Glenn Research Center (GRC) for these 1-kW convertors operating with an electric heat source. Each convertor was then retrofitted with a custom-made NaK heater head and integrated into a pumped NaK system at the Marshall Space Flight Center (MSFC). This paper documents baseline testing at GRC as well as the progress made in integrating the Stirling convertors into the pumped NaK loop.					
<b>15. SUBJECT TERMS</b> Stirling; Power conversion; NaK; Nuclear					
<b>16. SECURITY CLASSIFICATION OF:</b>			<b>17. LIMITATION OF ABSTRACT</b>  UU	<b>18. NUMBER OF PAGES</b> 13	<b>19a. NAME OF RESPONSIBLE PERSON</b> STI Help Desk (email:help@sti.nasa.gov)
<b>a. REPORT</b> U	<b>b. ABSTRACT</b> U	<b>c. THIS PAGE</b> U			<b>19b. TELEPHONE NUMBER (include area code)</b> 443-757-5802



