

Probe Station and Near-Field Scanner for Testing Antennas

Multiple antennas on the same substrate can be evaluated quickly and inexpensively.

John H. Glenn Research Center, Cleveland, Ohio

A facility that includes a probe station and a scanning open-ended waveguide probe for measuring near electromagnetic fields (see figure) has been added to Glen Research Center's suite of antenna-testing facilities, at a small fraction of the cost of the other facilities. This facility is designed specifically for nondestructive characterization of the radiation patterns of miniaturized microwave antennas fabricated on semiconductor and dielectric wafer substrates, including active antennas that are difficult to test in traditional antenna-testing ranges because of fragility, smallness, or severity of DC-bias or test-fixturing requirements. By virtue of the simple fact that a greater fraction of radiated power can be captured in a near-field measurement than in a conventional far-field measurement, this near-field facility is convenient for testing miniaturized antennas with low gains.


This facility makes it possible to test a complete set or any subset of a multiplicity of antennas on the same substrate in one session. The multiple antennas can all be of the same design or different designs. Unlike in prior antenna-testing facilities, there is no need for wafer-level dicing or packaging to isolate individual antennas from a multiple-antenna substrate before testing, and no need for special test fixtures. Hence, alternative prototype antenna designs can be evaluated in rapid succession to converge on an optimum design in less time (and, hence, at less

cost) than in prior antenna-testing facilities.

In this facility, radio-frequency (RF) signals and DC bias voltages and currents are supplied to an antenna under test (AUT) through RF and DC probes, respectively, that are parts of the probe station. The equipment in this facility includes a commercially available RF probe station, a coplanar-waveguide ground-signal-ground microwave probe that makes contact with the AUT, the aforementioned scanning open-ended waveguide probe, an automatic network analyzer (more specifically, a vector network analyzer)/microwave receiver, and a computer.

The mechanisms for scanning the open-ended waveguide probe are a three-axis slide mechanism and a rotation mechanism that, under computer control, positions this probe for acquisition of data at prescribed grid points on a plane very close to the AUT. This near-field scanning scheme enables capture of a maximum amount of energy radiated by one or multiple small antennas while they are DC-biased, without need for any special fixture.

The system is controlled by user-friendly operational, data-acquisition, and data-analysis software. The dimensions of the near-field scan area and the distance between grid points are specified by the user via the computer keyboard as inputs to a software-generated control panel. After each scan, the data-analysis software processes the measurement data and displays the far-field radiation pattern of the AUT,



The Open-Ended Waveguide Probe Is Scanned in a plane slightly above the AUT and is operated in conjunction with an RF contact probe and the vector network analyzer to gather data on the near radiation field.

computed from the near-field measurements.

This work was done by Afroz Zaman, Richard Q. Lee, William G. Darby, Philip J. Barr, and Félix A. Miranda of **Glenn Research Center**; and Kevin Lambert of **Analex Corp.** Further information is contained in a TSP (see page 1).

Inquiries concerning rights for the commercial use of this invention should be addressed to NASA Glenn Research Center, Innovative Partnerships Office, Attn: Steve Fedor, Mail Stop 4-8, 21000 Brookpark Road, Cleveland, Ohio 44135. Refer to LEW-17877-1.

Photodetector Arrays for Multicolor Visible/Infrared Imaging

Separate optical trains would not be needed for different wavelength bands.

NASA's Jet Propulsion Laboratory, Pasadena, California

Monolithic focal-plane arrays of photodetectors capable of imaging the same scenes simultaneously in multiple wavelength bands in the visible and infrared spectral regions have been proposed. In prior visible/infrared imaging systems, it has been standard practice to use separate optical trains to form images in visible and infrared wavelength bands on separate visible- and infrared-photodetector arrays. Be-

cause the proposal would enable the detection of images in multiple wavelength bands on the same focal plane, the proposal would make it unnecessary to use multiple optical trains. Hence, multispectral imaging systems could be made more compact and the difficulties of aligning multiple optical trains would be eliminated.

Each pixel in an array according to the proposal would contain stacks of sev-

eral photodetectors. The proposal is a logical extension of prior concepts of arrays of stacked photodetectors for imaging in two or three wavelength bands. For example, such an array was described in "Three-Color Focal-Plane Array of Infrared QWIPs" (NPO-20683), *NASA Tech Briefs*, Vol. 24, No. 5 (May 2000), page 26a.

In one proposed design, (see figure), each pixel would be divided into four