



### Collaborative Clustering for Sensor Networks

**This technique can be used in sensor networks such as those for volcano and earthquake monitoring, intruder detection, target tracking, and data mining in cell phone networks.**

*NASA's Jet Propulsion Laboratory, Pasadena, California*

Traditionally, nodes in a sensor network simply collect data and then pass it on to a centralized node that archives, distributes, and possibly analyzes the data. However, analysis at the individual nodes could enable faster detection of anomalies or other interesting events, as well as faster responses such as sending out alerts or increasing the data collection rate. There is an additional opportunity for increased performance if individual nodes can communicate directly with their neighbors.

Previously, a method was developed by which machine learning classification algorithms could collaborate to achieve high performance autonomously (without requiring human intervention). This method worked for supervised learning algorithms, in which labeled data is used to train models. The learners collaborated by exchanging labels describing the data. The new advance enables clustering algorithms, which do not use labeled data, to also collaborate. This is achieved by defining a new language for collaboration that uses pair-wise constraints to en-

code useful information for other learners. These constraints specify that two items must, or cannot, be placed into the same cluster. Previous work has shown that clustering with these constraints (in isolation) already improves performance.

In the problem formulation, each learner resides at a different node in the sensor network and makes observations (collects data) independently of the other learners. Each learner clusters its data and then selects a pair of items about which it is uncertain and uses them to query its neighbors. The resulting feedback (a "must" and "cannot" constraint from each neighbor) is combined by the learner into a consensus constraint, and it then re-clusters its data while incorporating the new constraint. A strategy was also proposed for "cleaning" the resulting constraint sets, which may contain conflicting constraints; this improves performance significantly. This approach has been applied to collaborative clustering of seismic and infrasonic data collected by the Mount Erebus Volcano Observatory in Antarctica.

Previous approaches to distributed clustering cannot readily be applied in a sensor network setting, because they assume that each node has the same "view" of the data set. A view is the set of features used to represent each object. When a single data set is partitioned across several computational nodes, distributed clustering works; all objects have the same view. But when the data is collected from different locations, using different sensors, a more flexible approach is needed. This approach instead operates in situations where the data collected at each node has a different view (e.g., seismic vs. infrasonic sensors), but they observe the same events. This enables them to exchange information about the likely cluster membership relations between objects, even if they do not use the same features to represent the objects.

*This work was done by Kiri L. Wagstaff of Caltech, Jillian Green of California State University of Los Angeles, and Terran Lane of University of New Mexico for NASA's Jet Propulsion Laboratory. For more information, contact [iaoffice@jpl.nasa.gov](mailto:iaoffice@jpl.nasa.gov). NPO-47491*

### Teleoperated Marsupial Mobile Sensor Platform Pair for Telepresence Insertion Into Challenging Structures

**This configuration adds more flexibility to robotic rescue operations.**

*John H. Glenn Research Center, Cleveland, Ohio*

A platform has been developed for two or more vehicles with one or more residing within the other (a marsupial pair). This configuration consists of a large, versatile robot that is carrying a smaller, more specialized autonomous operating robot(s) and/or mobile repeaters for extended transmission. The larger vehicle, which is equipped with a ramp and/or a robotic arm, is used to operate over a more challenging topography than the smaller one(s) that may have a more limited inspection area to traverse. The intended use of this con-

cept is to facilitate the insertion of a small video camera and sensor platform into a difficult entry area. In a terrestrial application, this may be a bus or a subway car with narrow aisles or steep stairs.

The first field-tested configuration is a tracked vehicle bearing a rigid ramp of fixed length and width. A smaller six-wheeled vehicle approximately 10 in. (25 cm) wide by 12 in. (30 cm) long resides at the end of the ramp within the larger vehicle. The ramp extends from the larger vehicle and is tipped up into the air. Using video feedback from a

camera atop the larger robot, the operator at a remote location can steer the larger vehicle to the bus door. Once positioned at the door, the operator can switch video feedback to a camera at the end of the ramp to facilitate the mating of the end of the ramp to the top landing at the upper terminus of the steps. The ramp can be lowered by remote control until its end is in contact with the top landing. At the same time, the end of the ramp bearing the smaller vehicle is raised to minimize the angle of the slope the smaller vehicle has to climb, and fur-