

laser pulse duration. Ions of different masses are then spatially dispersed along the focal plane of the magnetic sector of the miniature mass spectrometer and measured in parallel by a modified CCD (charge-coupled device) array detector capable of detecting ions directly. Compared to conventional scanning techniques, simultaneous measurement of the ion pulse along the focal plane effectively offers a 100% duty cycle over a wide mass range. LA-MMS offers a more quantitative assessment of elemental composition than techniques that detect laser-ionized species produced directly in the abla-

tion process because the latter can be strongly influenced by matrix effects that vary with the structure and geometry of the surface, the laser beam, and the ionization energies of the elements. The measurement of high-precision isotopic ratios and elemental composition of different rock minerals by LA-MMS method has been demonstrated. The LA-MMS can be applied for the absolute age determination of rocks. There is no such instrument available presently in a miniaturized version that can be used for NASA space missions. Work is in progress in the laboratory for geochronology of rocks using LA-MMS

that is based on K-Ar radiogenic dating technique.

Besides the MMS that has a double focusing focal plane geometry and a modified-CCD array ion-detector, the major components of the instrument include the laser, pumping, and its housing subsystem. These have been miniaturized for other NASA missions and when combined with the LA-MMS, make the instrument deployable on a rover or lander.

This work was done by Mahadeva P. Sinha, Michael H. Hecht, and Joel A. Hurowitz of Caltech for NASA's Jet Propulsion Laboratory. For more information, contact iaoffice@jpl.nasa.gov. NPO-48250

Physics Mining of Multi-Source Data Sets

Goddard Space Flight Center, Greenbelt, Maryland

Powerful new parallel data mining algorithms can produce diagnostic and prognostic numerical models and analyses from observational data. These techniques yield higher-resolution measures than ever before of environmental parameters by fusing synoptic imagery and time-series measurements. These techniques are general and relevant to observational data, including raster, vector, and scalar, and can be applied in all Earth- and environmental-science domains. Because they can be highly automated and are parallel, they scale to large spatial domains and are well suited to change and gap detection. This makes it possible to analyze spatial and temporal gaps in information, and facilitates within-mission re-planning to optimize the allocation of observational resources.

The basis of the innovation is the extension of a recently developed set of algorithms packaged into MineTool to multi-variate time-series data. MineTool is

unique in that it automates the various steps of the data mining process, thus making it amenable to autonomous analysis of large data sets. Unlike techniques such as Artificial Neural Nets, which yield a blackbox solution, MineTool's outcome is always an analytical model in parametric form that expresses the output in terms of the input variables. This has the advantage that the derived equation can then be used to gain insight into the physical relevance and relative importance of the parameters and coefficients in the model. This is referred to as "physics-mining of data." The capabilities of MineTool are extended to include both supervised and unsupervised algorithms, handle multi-type data sets, and parallelize it.

The innovations include: (1) Physics mining algorithms, enabling derivation of analytical relations and physical models from observational data; (2) Automated, parallel algorithms, enabling a high degree of automation and paral-

lization, scaling to large spatial domains well-suited to change and gap detection; (3) Local versus global modeling, to generate locally optimal models appropriate to a specific geospatial region accounting for the unique setting and conditions; (4) Fusion of multi-source, multi-type data that yield higher-resolution measures than ever before by fusing synoptic imagery and independent time-series measurements; and (5) Calculation of Palmer's Drought Severity Index Analogue.

Successful completion of this project will lead to a major breakthrough in the climate study in particular, and to analysis of multi-source data as applied to the hydrologic cycle affecting climate change impacts and resource management.

This work was done by John Helly, Homa Karimabadi, and Tamara Sipes of SciberQuest, Inc. for Goddard Space Flight Center. Further information is contained in a TSP (see page 1). GSC-15802-1

Photogrammetry Tool for Forensic Analysis

This acquires visual crime and accident scene data for later processing.

John F. Kennedy Space Center, Florida

A system allows crime scene and accident scene investigators the ability to acquire visual scene data using cameras for processing at a later time. This system uses a COTS digital camera, a photogrammetry calibration cube, and 3D

photogrammetry processing software.

In a previous instrument developed by NASA, the laser scaling device made use of parallel laser beams to provide a photogrammetry solution in 2D. This device and associated software work well under

certain conditions. In order to make use of a full 3D photogrammetry system, a different approach was needed.

When using multiple cubes, whose locations relative to each other are unknown, a procedure that would merge the