Ice Growth Measurements from Image Data
to Support Ice-Crystal and Mixed-Phase Accretion Testing

This paper describes the imaging techniques as well as the analysis methods used to measure the ice thickness and growth rate in support of ice-crystal icing tests performed at the National Research Council of Canada (NRC) Research Altitude Test Facility (RATFac). A detailed description of the camera setup, which involves both still and video cameras, as well as the analysis methods using the NASA Spotlight software, are presented. Two cases, one from two different test entries, showing significant ice growth are analyzed in detail describing the ice thickness and growth rate which is generally linear. Estimates of the bias uncertainty are presented for all measurements. Finally some of the challenges related to the imaging and analysis methods are discussed as well as methods used to overcome them.

Ice Growth Measurements from Image Data
to Support Ice-Crystal and Mixed-Phase Accretion Testing

- **Peter M. Struk**
- *NASA Glenn Research Center, Cleveland, Ohio*

- **Christopher J. Lynch**
- *Wyle Information Systems, Cleveland, Ohio, 44135*

Outline

- **Introduction**
- **Imaging setup**
  - Primary views
  - Camera Setup November 2010
  - Camera Setup March 2011
- **Image Analysis**
  - Measurement process
  - Image to physical size scaling
  - Uncertainty estimate
- **Results**
- **Discussion**
- **Conclusions**
- **Acknowledgements**

Introduction

- **Experiments underway to understand fundamentals of mixed-phase and ice crystal icing in jet engines**

    - NASA & NRC collaborations have had 3 test entries:

        - Nov 2010

        - Mar 2011

        - Mar & Apr 2012

- **Traditional methods of recording ice shapes (e.g. tracings and castings) were not easily adaptable to this experiment**

- **Experiments have gathered numerous still & video imagery**

    - Goal is to extract 2D and 3D shapes from imagery

    - As a first step, leading edge ice-growth measured and is the focus of this paper

Test Facility

- **Tests conducted in an icing cascade tunnel located in NRC Research Altitude Test Facility (RATFac) altitude chamber.**


Rectangular inlet bellmouth

Connection to exhauster

SEA multi-wire probe

Airfoil

Large front window

J-strip

Image Views

Leading Edge

Nov. 2010
(Still Camera)

Leading Edge

Nov. 2010
(HD Camera)

Camera Setup – November 2010

Front Perspective Still Camera

Airfoil

Side View Still Camera

Airfoil (w/ grid overlay)

Top-Down HD Video Camera

Top- Down Still Camera

Front Perspective Still Camera

Airfoil

Front Perspective View

Side View

Top Down View

Camera Setup – March 2011

Top-down HD Camera View

Front Perspective HD Video Camera

**Side HD Video Cameras**

HD Video Cameras:

Sony FCB-H11 (1280x720P)

Iconix HD-RH1 (1280x720 P)

Panasonic AK-HC1500 (1280x720 P)

Image Analysis

Objective: Measured leading edge ice thickness as a function of time

$$G = \frac{G_{pix}}{S \cdot \cos(\alpha + \beta)}$$

# Measurement Process (1 of 2)

- **Region of interest (ROI) definition**
  - 11 pix spanwise x 200 pix chordwise
  - Single or multiple ROIs used
  - Measurement (red cross **+**) constrained to spanwise midpoint of a given ROI

- **Edge Detection**
  - Needed to determine threshold grey level corresponding to ice edge
  - Linear contrast stretch enhancement in ROI (see next slide)
  - Used constant intensity for most cases
 - Typically looked for edge from right to left

- **Automated Analysis**
  - At 60 fps → 10,800 frame in 3 min.
  - Software would proceed frame by frame until it failed to detect an edge
  - Can watch analysis in graphically

Measurement Process (2 of 2)

- **Multiple ROIs effective for non-uniform spanwise accretion cases**

- **Obscuration issue due to water or ice runback:**
  - Create masking ROI to cover airfoil
  - Larger contrast adjustment region was required.
  - Looked for edge from left to right
 - In one case (thus far), manual measurements were required

Leading Edge

Masking ROI

Contrast Adj. ROI

Runback ice or water along window

Image to Physical Size Scaling (Nov – 2010)

- **Scale factor S**

  - Image units (pixels) to physical units (mm)

  - Perspective effect

    - Not primary view

    - ~36° (20°+6°+ ~10°) between imaging plane & airfoil cover

    - Square pixels

  - Calculated S at ½ ice thickness

    - Not precisely same plane as ice growth

    - Contributes to uncertainty

$$S = \frac{l_p}{l_a}$$

pixel length

actual length

Camera

20°

75.91 mm = 980 pixels ($l_{p,min}$)

136 pixels

75.91 mm = 987 pixels (l_p)

75.91 mm = 994 pixels ($l_{p,max}$)

Leading Edge

Imaginary Ice Thickness

Flow Direction

Line A

Line B

75.91 mm = 1051 pixels

$$S = 13.003 \pm 0.093 \frac{pix}{mm}$$

Image to Physical Size Scaling (Mar – 2011)

Camera

– **Grid overlay used**
  - Printed on transparency
  - 220±0.4 mm = 43 squares
  - Each grid 5.12 ± 0.01 mm

$$S = \frac{l_p}{l_a}$$

– **Perspective effect**
  - Now video primary view
  - Ice growth plane & imaging plane parallel
  - ~20° between imaging plane & airfoil cover

– **Used S at leading edge**
  - 631 ± 2 pixels
  - 66.56 ± 0.13 mm

$$S = 9.480 \pm 0.035 \frac{pix}{mm}$$

Grid Number

Leading Edge

Y = 354

Flow Direction

X =055

X =585

X =960

Uncertainty Calculation

$$G = \frac{G_{pix}}{S \cdot \cos(\alpha + \beta)} \longrightarrow dG = \left(\left[\frac{\partial G}{\partial G_{pix}} dG_{pix} \right]^2 + \left[\frac{\partial G}{\partial S} dS \right]^2 + \left[\frac{\partial G}{\partial \alpha} d\alpha \right]^2 + \left[\frac{\partial G}{\partial \beta} d\beta \right]^2 \right)^{\frac{1}{2}}$$

$$\frac{\partial G}{\partial G_{pix}} = \frac{1}{S \cdot \cos(\alpha + \beta)} \qquad \frac{\partial G}{\partial S} = \frac{-t_{pix}}{S^2 \cdot \cos(\alpha + \beta)} \quad \cdots \quad \longleftarrow \text{Sensitivity Coefficients}$$

| Parameter	Date	Case	Value	Uncertainty
G_{pix}	Nov. 2010	All	0-200 pixels	±2 pixels
	Mar. 2011	All	0-200 pixels	±2 pixels
S	Nov. 2010	144	13.003 pix/mm	± 0.093 pix/mm
	Mar. 2011	Mar. 8	9.480 pix/mm	± 0.035 pix/mm
α	Nov. 2010	All	0 or 6°	± 0.2°
	Mar. 2011	All	0 or 6°	± 0.2°
β	Nov. 2010	All	+10°	± 10°
	Mar. 2011	All	-6°	± 3°

Uncertainty Estimate

Reported uncertainty is due to measurement bias
Run-to-run variation yet to be determined

Results (1 of 2, Nov 2010)

- **One case from Nov 2010 & Mar 2011**
  - Similar but not identical conditions
- **Origin at water or ice flow initiation**
  - Manual activation, ice growth delay
- **Probe inserted ~ 1 min. near end**

- **Flashes (Nov 2010) only.**
- **Thickness ~13.04 $\pm$ 0.69 mm @ 298 s.**
- **Linear curve fit ~0.0482$\pm$0.0025 mm/s**
- **Camera zoom out $\rightarrow$ changes in scale**

Results (2 of 2, Mar 2011)

- **Thickness 15.49 ± 0.22 mm @198 s.**
  - Less bias uncertainty in Mar 2011 (1.4%) compared to Nov 2010 (5.3 %)

- **Linear fit 0.0788 ± 0.0015 mm/s**
  - Uncertainty comparison Mar 2011 (~2%) compared to Nov 2010 (~5 %)

- **No camera zoom during test**

Discussion

- **Factors affecting results**

- **Camera orientation:**
  - Perspective effective can be difficult to interpret
  - More optimal angle between ice growth plane and imager in Mar 2011
  - Contributes to the bias uncertainty in measurement

- **Camera zoom**
  - Trade off between large field of view and resolution

- **Window obscuration**
  - Ice and water contamination on windows
  - Can complicate analysis but can be overcome in most cases

- **Lighting / illumination**
  - Various orientations were experimented with lessons learned

Conclusions

- **Experiments gathering image data for ice accretion**
  - Not amenable to traditional ice growth measurement techniques
  - Three test entries thus far; each entry improved imaging techniques

- **1D leading-edge ice growth measurement technique presented**
  - Used NASA Spotlight software to measure ice edge within defined ROI
  - Described scale factor for conversion from image to physical units
  - Estimated uncertainly due to measurement bias

- **Presented results, one case from Nov 2010 & Mar 2011**
  - Similar but not identical conditions leading to large ice growths

- **Bias uncertainty estimate allows case-to-case comparison**

- **Results offer a new parameter, growth rate, not previously available for icing research**

Acknowledgements

- **Collaboration between NASA and the NRC**
  - NASA funding comes from the Atmospheric Environment Safety Technologies (AEST) / NASA's Aviation Safety Program.
  - Funding for the NRC work comes from the Federal Aviation Administration and Transport Canada.
- **NASA team members:**
  - Dr. Jen-Ching Tsao
 - Dr. Mario Vargas
  - Dr. Andy Broeren
- **NRC team members:**
  - Dr. Tom Currie
  - Mr. Dan Fuleki
  - Dr. Danny Knezevici
- **Special thanks for support of this work:**
  - Mr. Jim MacLeod
  - Mr. Thomas Bond

Questions

Ice Growth Measurements from Image Data

BACKUP SLIDES

Image to Physical Size Scaling (Mar – 2011)