



MIRA Architecture

saging Service (AMS), and the Delay Tolerant Network (DTN) standards into a single integrated protocol system.

The ultimate goal of the MIRA project is to develop an application stack for all robotics, even complex ones. It will be capable of status and control of three different cameras on the Exposed Facility (the porch) of the ISS JEM Module from MCC. Each successive phase will add incremental capabilities such as the capability of handling Human Factors and Performance (HFP), and automatic/semiautomatic change detection from imagery of spaceflight vehicles and equip-

ment. In later project phases, it will include ground control of robotic assets over Earth-Moon-Mars time delays, and remote sensing of planetary surfaces and surface navigation.

This project seeks to develop a new standard for robotics such that interoperability with crewed as well as non-crewed elements is provided, assuring cost effective collaboration between NASA and the international space community. The evolution of the proposed standard will be coordinated through the CCSDS International Standards community. The confluence of the

MIRA, SM&C/AMS/DTN standards, the robustness of DTN capability, and remote connectivity to ISS and ground assets (interoperability) will assure the JSC/MCC will be the hub of human, human precursor, and robotic missions where the mission components can be seamlessly integrated with other locations without excessive reconfiguration and integration costs that would render the MCC non-competitive.

The MIRA initial results have demonstrated robotic camera control that is applicable to near-Earth or distant applications where the DTN provides the bridge across the time delay impacts. The MIRA, SM&C/AMS/DTN standards-based status and control system software and protocol could be hardened, and expanded into the next-generation MCC protocol supporting human, robotic, and human-robotic missions. As such, this simple robotic camera prototype is a significant first step in the integration of robotic and human missions into true distant independent building blocks for future missions.

This work was done by Lindolfo Martinez, Thomas Rich, Steven Lucord, Thomas Diegelman, James Mireles, and Pete Gonzalez of Johnson Space Center. Further information is contained in a TSP (see page 1). MSC-25164-1

➤ Particle Filtering for Model-Based Anomaly Detection in Sensor Networks

Experiments on test stand sensor data show successful detection of a known anomaly in the test data.

Stennis Space Center, Mississippi

A novel technique has been developed for anomaly detection of rocket engine test stand (RETS) data. The objective was to develop a system that post-processes a csv file containing the sensor readings and activities (time-series) from a rocket engine test, and detects any anomalies that might have occurred during the test. The output consists of the names of the sensors that show anomalous behavior, and the start and end time of each anomaly.

In order to reduce the involvement of domain experts significantly, several data-driven approaches have been proposed where models are automatically acquired from the data, thus bypassing the cost and effort of building system

models. Many supervised learning methods can efficiently learn operational and fault models, given large amounts of both nominal and fault data. However, for domains such as RETS data, the amount of anomalous data that is actually available is relatively small, making most supervised learning methods rather ineffective, and in general met with limited success in anomaly detection.

The fundamental problem with existing approaches is that they assume that the data are iid, i.e., independent and identically distributed, which is violated in typical RETS data. None of these techniques naturally exploit the temporal information inherent in time series data

from the sensor networks. There are correlations among the sensor readings, not only at the same time, but also across time. However, these approaches have not explicitly identified and exploited such correlations. Given these limitations of model-free methods, there has been renewed interest in model-based methods, specifically graphical methods that explicitly reason temporally. The Gaussian Mixture Model (GMM) in a Linear Dynamic System approach assumes that the multi-dimensional test data is a mixture of multi-variate Gaussians, and fits a given number of Gaussian clusters with the help of the well-known Expectation Maximization (EM) algorithm. The parameters thus learned

are used for calculating the joint distribution of the observations. However, this GMM assumption is essentially an approximation and signals the potential viability of non-parametric density estimators. This is the key idea underlying the new approach.

Since this approach was model-based, it was possible to automatically learn a model of nominal behavior from tests that were marked nominal. Particle filtering and machine learning were applied to capture the model of nominal operations, and voting techniques were used in conjunction with particle filter-

ing to detect anomalies in test runs. Experiments on test stand sensor data show successful detection of a known anomaly in the test data, while producing almost no false positives.

A novel combination of particle filtering, machine learning, and voting techniques was developed to detect anomalies in sensor network data. Although most of the subsystems are tightly integrated into the system, the following two subsystems can also be used as standalone for extraneous tasks. A novel, efficient (but approximate) correlation clustering method that is currently used for sensor

selection was developed, but it can also be used to visualize sensor correlations as an aid to manual analysis. Sensors are detected that are overactive (large variance) or underactive (low variance) between commands, which effectively give a high-level map of the effect of commands on sensor groups. This may be used as an aid to visual/manual analysis.

This work was done by Wanda Solano of Stennis Space Center, and Bikramjit Banerjee and Landon Kraemer of The University of Southern Mississippi. For more information, call the SSC Center Chief Technologist at 228-688-1929. Refer to SSC-00379.