

THREE-DIMENSIONAL UNSTEADY SIMULATION OF AERODYNAMICS AND HEAT TRANSFER IN A MODERN HIGH PRESSURE TURBINE STAGE


Unsteady 3-D RANS simulations have been performed on a highly loaded transonic turbine stage and results are compared to steady calculations as well as to experiment. A low Reynolds number $k-\epsilon$ turbulence model is employed to provide closure for the RANS system. A phase-lag boundary condition is used in the tangential direction. This allows the unsteady simulation to be performed by using only one blade from each of the two rows. The objective of this work is to study the effect of unsteadiness on rotor heat transfer and to glean any insight into unsteady flow physics. The role of the stator wake passing on the pressure distribution at the leading edge is also studied. The simulated heat transfer and pressure results agreed favorably with experiment. The time-averaged heat transfer predicted by the unsteady simulation is higher than the heat transfer predicted by the steady simulation everywhere except at the leading edge. The shock structure formed due to stator-rotor interaction was analyzed. Heat transfer and pressure at the hub and casing were also studied. Thermal segregation was observed that leads to the heat transfer patterns predicted by steady and unsteady simulations to be different.



Three-Dimensional Unsteady Simulation of Aerodynamics and Heat Transfer in a Modern High Pressure Turbine Stage

Vikram Shyam
Student Trainee
NASA Glenn Research Center/ The Ohio State University


Ali Ameri
Research Scientist
NASA Glenn Research Center/ The Ohio State University



2009 Annual Meeting
Fundamental Aeronautics Program
Subsonic Fixed Wing Project
September 29-October 1, 2009

NASA Subsonic Transport System Level Metrics

.... technology for dramatically improving noise, emissions, & performance



CORNERS OF THE TRADE SPACE	N+1 (2015) ^{***} Technology Benefits Relative to a Single Aisle Reference Configuration	N+2 (2020) ^{***} Technology Benefits Relative to a Large Twin Aisle Reference Configuration	N+3 (2025) ^{***} Technology Benefits
Noise (cum below Stage 4)	- 32 dB	- 42 dB	- 71 dB
LTO NOx Emissions (below CAEP 6)	-60%	-75%	better than -75%
Performance: Aircraft Fuel Burn	-33% ^{**}	-40% ^{**}	better than -70%
Performance: Field Length	-33%	-50%	exploit metroplex* concepts

^{***} Technology Readiness Level for key technologies = 4-6

^{**} Additional gains may be possible through operational improvements

^{*} Concepts that enable optimal use of runways at multiple airports within the metropolitan areas

SFW Approach

- Conduct Discipline-based Foundational Research
- Investigate Advanced Multi-Discipline Based Concepts and Technologies
- Reduce Uncertainty in Multi-Disciplinary Design and Analysis Tools and Processes
- Enable Major Changes in Engine Cycle/Airframe Configurations

About this work...



- 3-D URANS simulations performed on highly loaded transonic turbine stage using TURBO (Chen et al.)
- Results are compared to steady calculations as well as experiment (Tallman, Haldemann et al. at OSU GTL).
- Effect of unsteadiness studied
 - shock structure
 - rotor heat flux
 - hub and casing heat flux
 - thermal segregation

Background



- HPT flow is unsteady due to wake passage and shock-wake interactions
- Stagnation point on rotor moves away from LE
- Shock moves from rotor crown to leading edge as wake passes (Denos et al., Paniagua et al.)
- Thermal segregation could occur (Shang and Epstein, Ameri et al., Kerrebrock and Mikolajczak)


Segregation





Velocity diagrams in the wake.
 $T_{\text{time_average}} < T_{\text{steady}}$

Rotor-Stator interface

Steady



Unsteady wake




Lower temperature in wake directs cooler gas to suction side

- Upwind Roe scheme with Newton sub iterations
 - No artificial dissipation
- Fully parallelized to use MPI
- Only need one blade per row using Phase lag
- Phase lag - ideal for single-stage simulation (Van Zante et al.)
- Uses low Re k - ϵ turbulence model
- Heat transfer simulation made possible by incorporating isothermal BC

Phase lag

Uses blade count of
neighboring blade row to
determine frequency

The Grid




Rotor grid.

Rotor Features

- 2.1% tip clearance
- blade speed ~ 9000 rpm
- $Re \sim 3 \times 10^6 / m$


**Convergence
determined using mass
flow and surface heat
transfer**

- 38 Stators, 72 rotor blades
- ~2.5M cells (very fine grid)
- $y^+ < 1$ (at first point off wall)
- Coarser grids have shown satisfactory results (e.g. Green et al.)



Relative stator-rotor positioning for unsteady case and boundary conditions

Simulations



- Steady
 - Used circumferentially averaged vane exit total pressure and temperature profiles as rotor inlet profiles.
 - Periodic BC used in tangential direction
- Unsteady
 - Stator inlet total pressure and temperature, rotor exit static pressure specified
 - Phase lag BC in tangential direction
 - 50 steps per period stored
 - Sliding interface BC at stator-rotor interface





RESULTS

Shock Function at 15% span



$$SF = \vec{V} \cdot \nabla p$$

- Boundaries of red regions are shocks

(Large pressure gradient is in direction of flow velocity)




Shock Function at Mid-Span



**Vane trailing edge
shock sweeps
across crown and LE
of rotor**

**Minimum
unsteadiness on
suction side of rotor**

Comparison with Schlieren




**Dotted lines are
reflected shocks**

**De la Loma, Paniagua, Verrastro, Adami,
GT2007-27101**


Shock Function at 90% Span




**Vane trailing edge
shock interacts with
rotor trailing edge
shock**



Mid-span Pressure and Mach Number





Pressure



Mach no.

Pressure Profiles



Unsteady envelope widest near LE,
narrows towards TE


Rotor
trailing
edge shock

Pressure Profiles


b) 50%

P/P_{ref}

c) 90%




Stag. Point
moved to
pressure
side




- No shock near
tip
- Thin envelope

Stanton Number Profiles




$$St = - \left[\frac{dT}{dn} \right]_{wall} \cdot \left[\frac{\mu_{wall}}{(\rho V)_{inlet}} \right] \cdot \frac{1}{Re_{ref} \cdot Pr}$$




Stanton Number Profiles




b) 50%



$$St = - \left[\frac{dT}{dn} \right]_{wall} \left[\frac{\mu_{wall}}{(\rho V)_{inlet}} \right] \frac{1}{Re_{ref} \cdot Pr}$$




Streamlines



Streamlines of relative velocity over suction side of rotor blade with rotor blade showing Stanton number contours.

Surface Heat Flux




Comparison between steady and time-averaged Stanton number distribution on rotor blade pressure side.

Snapshots of Unsteady Heat Flux



time →




In the Tip Gap

Stanton number on blade

$$\theta = \tan^{-1}\left(\frac{u}{w}\right)$$

$$\text{Isosurface} : x - z \tan(\theta) = c$$





$$V_{\text{plane}} = u \sin(\theta) + w \cos(\theta)$$




V_{plane} is positive (yellow through red colors) if flow is separated. This is only valid in the tip gap, where flow separation can be measured in the z-x plane

V_{plane} on Iso planes of c

In the Tip Gap – Plane 1




In the Tip Gap – Plane 1 - Unsteady



Shock function

tip_shock3.avi


In the Tip Gap – Plane 2




Casing Heat Transfer



Steady




Time-averaged



Corresponds to
separation

Hub Heat Transfer




Percent difference between steady and time-averaged Stanton number on rotor hub.



Conclusions


- Over most of blade surface, steady simulation is accurate
- Thermal wake causes unsteady heat transfer over most of the blade to be higher than steady heat transfer except at leading edge.
- At the leading edge the effect of unsteadiness is most prominent
- Thermal redistribution was observed at the hub and on the blade surface
- Pressure and heat transfer distribution over blade is highly 3D






Backup slides


Time averaged P and Shock @ 50% span



0.498
0.370
0.242
0.115





0.873
0.222
-0.429
-1.079



- ## Fundamental Aeronautics Program Subsonic Fixed Wing Project

Pressure and Temperature Profile at Interface



Stanton No. Derivation



$$St = \frac{h}{c_p \cdot \rho \cdot V} \quad \text{since } h = \frac{q_{wall}}{T_{wall} - T_{ref}}, \text{ and knowing } \dot{m} = \rho \cdot A \cdot V$$

$$St = \frac{q_{wall}}{\left(\frac{\dot{m}}{A}\right) \cdot c_p \cdot [T_{wall} - T_{ref}]}$$

$$St = \frac{1}{\rho \cdot V \cdot C_p} \cdot \frac{-k \cdot \frac{dT}{dn}|_{wall}}{T_{wall} - T_{ref}} \quad \text{knowing:}$$

$$Pr = \frac{\mu_{wall} \cdot C_p}{k}$$

$$\mu_{wall} = \frac{Pr \cdot k}{C_p}$$

$$\mu_{wall} = \rho_{wall} \cdot \nu_{wall}$$

multiply and divide by μ_{wall} and simplify to obtain:

$$St = \frac{-\frac{dT}{dn}|_{wall}}{T_{wall} - T_{ref}} \cdot \frac{\mu_{wall}}{\rho \cdot V} \cdot \frac{1}{Pr}$$


An expression in nondimensional terms:

$$St = - \left[\frac{\frac{dT}{dn}|_{wall}}{\bar{T}_{wall} - \bar{T}_{ref}} \right] \cdot \left[\frac{\bar{\mu}_{wall}}{\bar{\rho} \cdot \bar{V}} \right] \cdot \left[\frac{1}{Pr} \right] \cdot \left[\frac{\mu_{ref}}{\rho_{ref} x_{ref} a_0} \right]$$


Rotor Hub Surface Heat Transfer - Steady



TURBO predictions




Stanton No. Comparisons




Rotor Tip Heat Transfer – Steady



TURBO predictions




Stanton No. Comparisons




Rotor Casing Surface Heat Transfer - Steady



TURBO predictions



No data available for comparison



Statistics – Steady



Results	TURBO vs. Tacoma	TURBO vs. Experimental
Vane Surface Pressure	Good	Good
Vane Surface Heat Transfer	Good	Good
Blade Surface Pressure	Good	Good
Blade Surface Heat Transfer	Fair	16.3% difference (max: 25%)
Rotor Hub Surface Heat Transfer	13.4% difference	13.1% greater
Rotor Tip Heat Transfer	10.5% difference	15.5% greater
	Iterations	Estimated CPU Time
Stator	30,000	60 Hours
Rotor	40,000	120 Hours