



Chemical Microsensor Development for Aerospace Applications

*Jennifer C. Xu, Gary W. Hunter, Dorothy Lukco,
Liangyu Chen, and Azlin M. Biaggi-Labiosa*

Jennifer C. Xu

University of Illinois at Urbana-Champaign, 1998, Ph.D.

Case Western Research University, 1998-2000, Post Doctoral

Sensor Development Co., Inc. 1999-2002, Material Scientist


NASA Glenn Research Center: 2002-present, Electronics Engineer



Chemical Sensor Development at NASA GRC



- **Microsensors and platforms**
 - * H_2 , CH_4 , C_2H_4 , C_3H_6 , CO_2 , CO , O_2 , NO_x , N_2H_4 , HCl , HCN , and HF
 - * Schottky diodes, resistors, and electrochemical cells
- **Approaches**
 - * Smart sensor system: sensor arrays, signal processing and conditioning components, power and telemetry
 - * “Lick and Stick” for full-field view of environment
 - * Nanotechnology and batch microfabrication
 - * Small size, low weight, cost, and power consumption
- **Applications**
 - * Propulsion system, fuel depot leak detection
 - * Low false alarm fire detection.
 - * Harsh environment engine emissions monitoring
 - * Human health monitoring and potential astronaut health evaluation
- **Sensor to be presented**
 - * **CO_2 sensors:** Electrochemical cells: amperometric and metal oxide nanomaterial modified, potentiometric sensors and resistors
 - * **H_2/C_xH_y Schottky diode sensors:** Diodes and diodes with contact pads
 - * **O_2 sensors:** High temp and room temp
 - * **NO sensor:** metal oxide resistor based
- * **Metal oxide nanomaterials**



NASA GRC Sensors and Electronics Branch cleanroom





NASA GRC


Solid Electrolyte Carbon Dioxide Microsensors (NASA GRC)

Side view of microfabricated CO₂ sensor



(Simplified with a pair of two electrodes)



SEM image of a fabricated CO₂ sensor




Testing Results of Solid Electrolyte Carbon Dioxide Sensor






Addition of Tin Oxide Nanocrystallines Improves Solid Electrolyte Carbon Dioxide Sensor Performance

Tin oxide nanocrystalline layer added






K. Obata et al. / Sensors and Actuators B 76 (2001) 639-643


Sensors without tin oxide sol gel addition





Sensors with tin oxide sol gel addition




Potentiometric CO₂ Microsensors Developed



1%, 2%, 3%, 4% CO₂ gases in air
at 500°C, air for baseline



Working



Reference

Development of Diode Sensors with Contact Pads




Fig. 1. A single metal/PdO_x/SiC based diode for H₂/C_xH_y detection.




Fig. 2. a) Schottky diode with contact pad fabrication process. b). Image of a Pd/PdO_x/SiC diode with a Au/Ti contact pad. The dark area surrounding the sensor-pad is SiO₂




Fig. 2. c) 400 x micrograph of Pt/Ti connect on diode; b) 1000x micrograph. The white area is metal silicide while the dark area is SiC





Fig 4. a). Sensor with interconnect contact pad responses to 50 ppm, 100 ppm, 150 ppm, and 200 ppm H₂ gases; b). Sensor responses to 50 ppm, 25 ppm, and 20 ppm H₂ gases, at 300°C, 1V.









Fig. 5. Sensor with interconnect contact pad response to 0.5% H₂ at 500°C, 1V

Developed Room Temperature Potentiometric Oxygen Sensors

Totally different structure: one of its kind




Development of Nitric Oxide and Oxygen Sensors


Pt interdigitated electrodes fabricated on a 2-inch alumina wafer




**Gas testing chamber:
Probe contact**




Electrode structure and schematic of gas testing setup





High Temperature YSZ Oxygen Sensor Testing Results





(Linear fitting from 0.5% to 16%)



Testing Results




Sputtered ITO Microsensor Response to Nitric Oxide Gas





- * Low concentration (ppb to low ppm): adsorption
- * High concentration (ppm): adsorption and NO oxidation reaction:

O_2 , NO from air grab electrons from ITO surface, deplete ITO surface





Metal Oxide Nanomaterials for Reducing Gas Sensing





SnO_x nanocrystallines by sol gel process



Increased nano grain boundary contact



Single crystal nanorods by CVD



Polycrystal SnO_x nanofibers by electrospun process



Left: Palladium Doped SnO_x Nanofibers Detect Hydrogen and Hydrocarbons

Summary

- **A variety of chemical microsensors development for aerospace applications**
- **Different sensor structures and sensing mechanisms were used in the sensor designs**
- **Carbon dioxide sensors, oxygen sensors, Schottky diode sensors, nitric oxide sensors, and nanomaterials discussed**
- **Small size, batch fabrication, low cost and power consumption, and harsh environment applications**
- **Applications: fire detection, engine emission and health monitoring, and environmental monitoring. In ambient and harsh environments**

Acknowledgements

Mike Artale, Jose Gonzalez, Peter Lampard, Drago Androjna, Christopher Hampton, Beth Osborn, and Michelle Mrdenovich

Lawrence Matus and Mary Zeller

NASA Sensors and Electronics Branch members

NASA Aviation Safety Program/IVHM Project

NASA ETDP/Space Fire Prevention Task