



Mini-Membrane Evaporator for Contingency Spacesuit Cooling

Janice V. Makinen, NASA JSC

Grant Bue, NASA JSC

Aaron Colunga, Matthew Vogel, Jacobs Technology

TFAWS 2014

August 7, 2014

Introduction-Advanced PLSS



- A new Portable Life Support System is being developed at NASA JSC.
- Includes new technology development hardware;
 - Spacesuit Water Membrane Evaporator for heat rejection
 - High-speed ventilation fan
 - Primary and Secondary oxygen regulators
 - Rapid-Cycle Amine (CO₂ removal)
- Integrated PLSS testing completed at a breadboard level in 2011 (PLSS 1.0)
- Packaging the PLSS into 'backpack' began in 2013 (PLSS 2.0)



PLSS 1.0 Testing

Introduction



- The current Extravehicular Mobility Unit (EMU) utilizes a secondary oxygen vessel (SOV) for contingency breathing oxygen and cooling of the crewmember during an EVA anomaly.
 - Sublimator failure
 - Power failure
- The SOV flows high pressure oxygen through the LCVG to cool the crewmember.
- Some drawbacks of the SOV include:
 - Very high pressure charge: 6000 psi
 - Primary oxygen vessel (POV) is charged only to 3000 psi and is smaller
 - Cannot be recharged on orbit after use—must be returned for service
 - Provides only 30 minutes of get-back time

Introduction-PLSS 2.0



- During packaging analyses for PLSS 2.0, it became clear that more space was needed to package all of the components
- A proposed solution was to eliminate the SOV and replace it with a smaller tank, identical to the POV.
 - Rely on new, smaller SOV for contingency breathing oxygen only
 - Create an Auxiliary Cooling Loop (ACL), which relies on a small membrane evaporator for heat rejection.
- Advantages to identical Primary and Secondary oxygen tanks include;
 - More available volume inside of PLSS package
 - Component similarity
 - Rechargeable on-orbit

Auxiliary Cooling Loop Overview



- Auxiliary Cooling Loop consists of:
 - Small Membrane Evaporator, Mini-ME, utilizing same technology as the primary heat rejection device for the PLSS, the Spacesuit Water Membrane Evaporator (SWME)
 - Independent pump
 - Independent power supply
 - Independent LCVG tubing in the vest area only
 - Independent feedwater assembly
 - Independent controller
- Advantages of the ACL
 - Can be recharged on orbit
 - Can provide more get-back time
 - Completely independent system


Auxiliary Cooling Loop Overview



- Mini-ME is an evaporative cooler
 - 8000 porous microfibers
 - 300 microns in diameter

Process

- Water in LCVG absorbs body heat while circulating
- Warm water pumped through Mini-ME
- Valve is opened
- Mini-ME evaporates water vapor, while maintaining liquid water
 - Cools water
- Cooled water is then recirculated through LCVG.
- LCVG water lost due to evaporation (cooling) is replaced from feedwater




ACL & Mini-ME




- Proposed operation of ACL
 - During a contingency event, the crewmember will turn-on the ACL via a switch on the Display Control Module (DCM)
 - The switch will turn on the independent controller
 - The pump will start
 - The valve will fully open, exposing fibers to vacuum, rejecting heat
- Goals for first generation of hardware:
 - Accommodate a 1200 BTU/hr crewmember metabolic rate
 - Provide 60 minutes of heat rejection
 - Package into PLSS 2.0—rectangular cross section preferred
- The dimensions for the first Mini-ME were dictated by available volume in the PLSS.

First Generation Mini-ME



- A rectangular membrane evaporator was designed and constructed in-house.
- A clear, acrylic housing was chosen in order to evaluate membrane integrity
- The fiber cartridge was constructed with 8000 fibers, utilizing a new, layered technique
- Gate valve with small stepper motor
 - Gate valve chosen due to volumetric constraints within the PLSS volume.




Mini-ME Fabrication

Preliminary Mini-ME testing




- Two units were constructed.
- Preliminary testing results showed heat rejection performance of 95-110W (325-375 BTU/hr) at 50kg/hr flow rate with a 10 degree Celsius outlet temperature.
- Approximately ~10 W of heat leak was observed across the closed gate valve
 - This could cause fiber freezing and loss of feedwater during system standby
- Following preliminary testing, one Mini-ME was installed into the PLSS 2.0 backpack.




Completed Mini-ME unit

PLSS 2.0



PLSS 2.0



Mini-ME (left), RVP SWME (right)

Subsequent Mini-ME Testing




- Following the preliminary testing of Mini-ME, a study was conducted to:
 - investigate ideal fiber density and packaging in terms of heat rejection
 - Determine smallest valve throat area needed to reject at full capability
- 9 Fiber Density Test Articles (FDTA's) were constructed with different fiber densities and with replaceable valve throat areas.
- Each unit was tested for a total of 24 hours.
- Data from these tests allowed analysts to correlate models to data
- Ideal configuration: 16 bundles of 6 layers (9413 fibers), which produced 165W of heat rejection with a 55kg/hr flow rate

Fiber Density Test Article (FDTA)	Bundle Count	Layers	Nominal Fiber Count	Day 4, 0.75 in ² Orifice Plate, 10°C Outlet Heat Rejection (W)	FDTA Outlet Water Mass Flow (kg/hr)	Normalized (10°C Tout, 55 kg/hr mdot) FDTA Day 4, 0.75 in ² Orifice Plate Heat Rejection (W)
2	16	5	7844	127	55.05	127
5	14	6	8236	127	54.95	127
1	16	6	9413	164	54.3	166
3	16	6	9413	158	55.55	156
8	12	7	8236	118	55.2	118
6	14	7	9609	138	54.25	140
4	16	7	10982	158	54.5	159
9	12	8	9413	148	55.2	147
7	14	8	10982	135	54.4	136
Nominal bundle width (in)		1.85				
Nominal fiber density (fibers/inch)		53				
Nominal fiber exposed length (in)		2.25				


FDTA Analysis



- Valve throats of 0.75in^2 , 1 in^2 and 4in^2 were investigated.
 - No difference between 0.75in^2 and 4 in^2
- Fiber density and packaging:
 - Most data points show that fewer layers yield greater heat rejection for same fiber count
 - Strongly suggests optimum packaging is higher bundle count and fewer layers
 - Limits of this approach would require additional testing



FDTA



Fiber Density Test Article (FDTA)

Forward Work



- The Mini-ME and ACL will be tested as an integrated system in PLSS 2.0, beginning in September.
- The next generation of Mini-ME hardware (Mini-ME2) is currently being designed.
 - Goals:
 - New valve with 0W heat leak
 - More heat rejection (350W)
- Mini-ME2 will be tested independently, and ultimately integrated into the next round of PLSS testing (PLSS 2.5).

Acknowledgments



- Grant Bue
- Matt Vogel
- Aaron Colunga
- Colin Campbell
- Carly Watts
- Ian Anchondo