

Initial Thrust Measurements of Marshall's Ion-ion Thruster

Natalie R. Schloeder¹, Tyler Scogin², Thomas M. Liu³, and Mitchell L.R. Walker⁴
Georgia Institute of Technology, Atlanta, GA 30332

Kurt A. Polzin⁵ and John W. Dankanich⁶
NASA George C. Marshall Space Flight Center, Huntsville, AL 35811

and

Ane Aanesland⁷
Laboratoire de Physique des Plasmas (LPP), CNRS-Ecole Polytechnique, 91128 Palaiseau Cedex, France

Electronegative ion thrusters are a variation of tradition gridded ion thruster technology differentiated by the production and acceleration of both positive and negative ions. Benefits of electronegative ion thrusters include the elimination of lifetime-limiting cathodes from the thruster architecture and the ability to generate appreciable thrust from both charge species. Following the continued development of electronegative ion thruster technology as exhibited by the PEGASES (Plasma Propulsion with Electronegative GASES) thruster, direct thrust measurements are required to push interest in electronegative ion thruster technology forward. For this work, direct thrust measurements of the MINT (Marshall's Ion-ion Thruster) will be taken on a hanging pendulum thrust stand for propellant mixtures of Sulfur Hexafluoride and Argon at volumetric flow rates of 5-25 sccm at radio frequency power levels of 100-600 watts at a radio frequency of 13.56 MHz. Acceleration grid operation is operated using a square waveform bias of ± 300 volts at a frequency of 25 kHz.

Nomenclature

α	=	Electronegativity
d_s	=	Beamlet Diameter
γ	=	Thrust Correction Factor
I_{sp}	=	Specific Impulse
J_{ions}	=	Ion Current Density
l_e	=	Sheath Thickness
l_g	=	Grid Gap
M	=	Adjusted Mass of Propellant Mixture
\dot{m}_i	=	Ion Mass Flow Rate
n_i	=	Ion Number Density
P_{in}	=	Total Power Input
Q	=	Volumetric Flow Rate
$T_{e,i}$	=	Electron/Ion Temperature
T_{MAX}	=	Maximum Thrust

¹ Graduate Student Researcher, School of Aerospace Engineering, nschloeder3@gatech.edu, Student Member AIAA

² Graduate Student Researcher, School of Aerospace Engineering, tscogin@gatech.edu, Student Member AIAA

³ Research Engineer, School of Aerospace Engineering, thomas.liu@ae.gatech.edu, Member AIAA

⁴ Associate Professor, School of Aerospace Engineering, mitchell.walker@ae.gatech.edu, Associate Fellow AIAA

⁵ Propulsion Research Engineer, Propulsion Research and Technology Applications Branch, Propulsion Systems Department, kurt.a.polzin@nasa.gov, Associate Fellow AIAA

⁶ Program Manager, Technology Development and Transfer Office, john.dankanich@nasa.gov, Associate Fellow AIAA

⁷ Researcher, CNRS – Ecole Polytechnique, ane.aanesland@lpp.polytechnique.fr, Member AIAA