



# Preliminary Findings of Inflight Icing Field Test to support Icing Remote Sensing Technology Assessment

Prepared by:

Michael King & Andy Reehorst

*National Aeronautics and Space Administration, Glenn Research Center*

Dave Serke

*National Center for Atmospheric Research, Research Applications Laboratory*

June 22-25, 2015



# Presentation Overview

- Background
- Icing remote sensing systems
  - NASA Icing Remote Sensing System
  - NASA Terminal Area Icing Remote Sensing System
- In-situ atmospheric sounding systems
  - Weather Balloon Systems
  - Anasphere SLWC Sensor
  - SLWC Calculation
- Selected winter 2015 system comparisons
  - Forecasting and Release Decision Criteria
  - March 17, 2015
  - March 20, 2015
  - March 26, 2015
- Summary



# Background


- Icing accidents continue to occur despite advances in all aspects of icing related technologies
- The spatial and temporal variability of icing severity is a major challenge to providing pilots and controllers with actionable icing hazard information
- The need for direct detection and measurement of hazardous icing conditions is still significant despite improvements to weather models over the past decade
- NASA has teamed with NCAR for the last 10 years to develop a ground-based remote icing hazard detection algorithm test bed to address this need
- The result of this effort is the NASA Icing Remote Sensing System (NIRSS)
- NASA carried out a weather balloon campaign during winter 2015 using a new supercooled liquid water (SLWC) sensor to generate the database necessary to validate NIRSS



# Icing Remote Sensing Systems:

## *NASA Icing Remote Sensing System (NIRSS)*

- The NIRSS remotely detects hazardous icing conditions using ground based meteorological instrumentation
  - Vertical icing condition severity product is derived from calculated supercooled liquid water content estimated by the NIRSS algorithm
  - Includes 3 vertically pointing instruments: a Radiometrics Radiometer, a Vaisala Ceilometer and a METEK Ka-Band Cloud Radar System
  - System shown to agree well with the Aviation Weather Center (AWC) Current Icing Product (CIP) and Pilot Reports (PIREP)
    - Johnston, Christopher J., et al., “Comparison of In-Situ, Model and Ground Based In-Flight Icing Severity”, NASA/TM—2011-217141, Dec. 2011
- An acknowledged shortcoming of NIRSS is that it only produces a vertical profile of the icing conditions
  - To help fully protect a terminal area and provide information that accounts for the temporal and spatial variability of icing conditions, a volumetric remote measurement capability is required




Reehorst & Serke, “A Terminal Area Icing Remote Sensing System”, NASA/TM-2014-218417, Nov 2014




# Icing Remote Sensing Systems:

## *NASA Terminal Area Icing Remote Sensing System*

- The terminal area system was developed to address the shortcomings of NIRSS
  - Produces icing condition severity classification along defined airport approach and departure paths every minute based on most recent measurements
  - Icing hazard is output in 9 boxes centered along each runway approach path, from the airport center to 25 Km out
- Terminal Area System builds upon the existing capability of NIRSS
  - Includes NIRSS instrumentation, an additional pointable radiometer and ingests NEXRAD radar data
  - In addition to NIRSS vertical condition fields, the system ingests :
    - Radiometer slant elevation ILW measurements along airport runway headings
    - NEXRAD reflectivity and ground surface wind data to advect the measured fields into the 3-D volume



Reehorst & Serke, "A Terminal Area Icing Remote Sensing System", NASA/TM-2014-218417, Nov 2014




Radiometrics Radiometer on top of IRT roof with NEXRAD radar and KCLE airport in background



# In-situ Atmospheric Sounding Systems:

## *Weather Balloon Systems*

- Weather balloons used to obtain in-situ measurements characterizing conditions aloft
  - Instrument package carried specialized, disposable sensor to measure supercooled liquid water content in addition to standard meteorological radiosonde
- Weather balloon operations were carried out from the NASA Glenn Research Center hangar ramp
  - Balloon release location is 0.25 Km from ground instrumentation and within 1 Km of airport center
  - Coordination with Cleveland Hopkins Airport Air Traffic Control established to ensure safe operations
- 24 instrumented balloons released for 12 different icing events between Jan. 22 and Apr. 23, 2015




Instrument Package: InterMet iMet-1-RSNB Radiosonde and Anasphere SLWC Sensor



# In-situ Atmospheric Sounding Systems:

## *Supercooled Water Content Sensor*


- Balloon-borne SLWC sensor
  - Anasphere, Inc., through a NASA contract, developed a new, prototype sensor based on work by Hill and Woffinden
    - Hill & Woffinden, "A Balloon-borne Instrument for the Measurement of Vertical Profiles of Supercooled Liquid Water Concentration," Journal of Applied Meteorology, 1980
- Measurement principle is based on the reduction in natural vibration frequency of a wire due to ice accretion
  - Natural frequency decreases with increasing ice accretion along the wire
  - SLWC is calculated using time history of natural frequency
- Frequency measurements obtained every 3 seconds, nominally
  - Wire is periodically perturbed by magnet attached to a servomotor
  - Natural vibration frequency determined using Fast Fourier Transform



Anasphere, Inc. SLWC Sensor: Wire Vibration Video Loop



# SLWC Calculation



March 17, 2015, Balloon 002 frequency profile showing characteristic frequency depression due to ice accretion on wire

$$SLWC = \frac{C}{\epsilon D \omega} \frac{df}{dt}$$

General form of the equation to calculate SLWC from Hill, "Analysis of Supercooled Liquid Water Measurements Using Microwave Radiometer and Vibrating Wire Devices," J. Atmo. & Oceanic Tec., Vol. 6, 1989.

- **SLWC** is calculated using the frequency profile
  - The time derivative of the frequency, **df/dt**, is the driving term
  - The coefficient **C** is model, assumption specific
  - The terms **ε**, **D** and **ω** are collection efficiency, wire diameter and ascent speed, respectively
- Outliers in the frequency are removed and the profile is smoothed prior to calculation
  - Robust local regression using weighted linear least squares and a second degree polynomial (Matlab: LOESS)



# Case Studies:

## *Forecasting and Release Decision Criteria*

- Long-Range Forecast
  - Long-range icing forecasting was provided by NCAR
    - Weather systems of interest identified in advance
- Next-Day Forecast
  - NCAR provided next-day forecast specifying period of interest
    - Notice to Airmen (NOTAM) submitted for forecast specified period of time
    - Coordination with NASA GRC Hangar personnel
- Short-Range Forecast
  - Coordination with NCAR on conditions during period of interest for release decision
  - Radiometer-derived ILW used as final release decision criterion
    - $ILW > 0.3\text{mm}$
  - Coordination with Cleveland Air Traffic Control for permission to release
    - Class B Airspace



# Case Studies:


March 17, 2015 (Remote Sensing and PIREP)



PIREP Map for March 17, 2015

|   | Aircraft Type | Time [UTC] | Flight Level [Ft] | Icing Report |
|---|---------------|------------|-------------------|--------------|
| 1 | E145          | 1423       | 5200-6000         | Light Clear  |
| 2 | B712          | 1520       | 4000              | Light Rime   |
| 3 | B712          | 1552       | 4000              | Mod. Rime    |

PIREP Summary for March 17, 2015 for period of interest




NIRSS icing severity product output for March 17, 2015

[Note: Markers only indicate corresponding time and altitude and do not represent transection of aircraft with the NIRSS sample volume]



# Case Studies:

## March 17, 2015 Balloon 002 (Comparison)




Skew-T, Log-P Diagram (left), Frequency Profile (middle), and SLWC Profile (right) for March 17, 2015, 1447 UTC



# Case Studies:

*March 20, 2015 (Remote Sensing & PIREP)*




NIRSS icing severity product output for March 20, 2015

- No icing PIREPs were issued within 90 Km of CLE during the period of interest (1300 to 1800 UTC) on March 20, 2015



# Case Studies:

## March 20, 2015 Balloon 001 (Comparison)



Skew-T, Log-P Diagram (left), Frequency Profile (middle), and SLWC Profile (right) for March 20, 2015, 1500 UTC



# Case Studies:


March 26, 2015 (Remote Sensing and PIREP)



PIREP Map for March 26, 2015

|   | Aircraft Type | Time [UTC] | Flight Level [Ft] | Icing Report            |
|---|---------------|------------|-------------------|-------------------------|
| 1 | E145          | 1428       | 12000             | No Icing Below 12000 Ft |
| 2 | E145          | 1439       | 13000             | Mod. Rime               |
| 3 | C525          | 1650       | 14000             | Light Rime              |
| 4 | C56X          | 1836       | 10500             | No Icing                |
| 5 | C510          | 1910       | 15500             | Light Mixed             |

PIREP Summary for March 26, 2015 for period of interest




NIRSS icing severity product output for March 26, 2015

[Note: Markers only indicate corresponding time and altitude and do not represent transection of aircraft with the NIRSS sample volume]



# Case Studies:

## March 26, 2015 Balloon 003 (Comparison)



Skew-T, Log-P Diagram (left), Frequency Profile (middle), and SLWC Profile (right) for March 26, 2015, 1659 UTC



# Summary

- A successful weather balloon campaign utilizing a new SLWC sensor was conducted out of NASA Glenn Research Center from Jan. 22 to Apr. 23, 2015
  - A database of 24 balloon soundings for 12 different icing weather events was generated that can be used to validate and improve the NIRSS and Terminal Area Systems
- Initial results between the remote sensing and in-situ systems show agreement in several cases
  - The altitude of significant SLWC and general distribution SLWC aloft agree in several cases
  - The ILW between NIRSS and the weather balloon soundings agree in several cases
  - Disagreement between NIRSS and the weather balloons system may be attributed to spatial and temporal sampling differences