




# **Subscale Validation of the Subsurface Active Filtration of Exhaust (SAFE) Approach to NTP Ground Testing**

William M. Marshall  
NASA Glenn Research Center

Presented at AIAA Propulsion and Energy Forum  
27-29 July 2015



# Acknowledgements

## Co-authors:

- Stanley K. Borowski from NASA Glenn Research Center
- Mel Bulman and Russell Joyner from Aerojet Rocketdyne
- Charles R. Martin from National Securities Technologies, LLC

The authors are grateful for the contributions of the numerous team members on the NTP program. The team thanks the Department of Energy for their contributions in discussion of the regulatory environment for a ground test campaign.





# Overview

- Introduction
- Brief History of NTP
- Ground Test Options
- Validation Plans for SAFE Concept
- Alternative SAFE Concepts
- Recent Assessments
- Summary



# Introduction

- Nuclear Thermal Propulsion (NTP) is an attractive propulsion method for crewed Mars Transit
- NASA DRA 5.0 identified NTP as the preferred approach for a Mars mission
  - High thrust (~10's klbf)
  - High  $I_{sp}$  (875-950 s)
- Benefits of NTP include
  - A propulsion system that can reduce transit times
  - Reduce initial mass to low Earth orbit (IMLEO)
  - Permit greater shielding from cosmic rays for crew safety
- Goals of NTP Program
  - Development of fuel materials (ZrC composite) or ( $UO_2$  cermet)
  - Design of NTR engine (7.5 klbf, 16.4-klbf SNRE, 25 klbf, etc.)
  - Lab testing of fuel elements in non-radiation environment
  - *Ground testing of NTR engine at full power and duration (~ 1 hr.)*




# Brief History of NTP

- Project Rover
  - Began in 1950's by Los Alamos Scientific Labs (now Los Alamos National Labs) and ran until 1970's
  - Tested a series of nuclear reactor engines of varying size at Nevada Test Site (now Nevada National Security Site)
  - Ranged in scale from 111 kN (25 klbf) to 1.1 MN (250 klbf)
  - Included Nuclear Furnace-1 tests for materials and fuel element testing
  - Demonstrated the viability and capability of a nuclear rocket engine test program
  - One of Kennedy's 4 goals during famous moon speech to Congress
- Nuclear Engines for Rocket Vehicle Applications (NERVA)
  - Atomic Energy Commission and NASA joint venture started in 1964
  - Parallel effort to Project Rover
  - Was focused on technology demonstration
  - Tested XE' engine, a 245-kN (55-klbf) engine to demonstrate startup/shutdown sequencing


# Results of Rover/NERVA

- Largely successful programs
  - Demonstrated 800+ seconds of specific impulse
  - Achieved TRL 6 level of development
  - Much of present design and understanding of NTP are heritage from Rover/NERVA
- Identified mid-band corrosion issue in fuel elements
  - Due to high temperature, high pressure hydrogen, fuel elements were susceptible to corrosion & cracking
  - Coatings were used to minimize corrosion effect, but insufficient to mitigate entirely
- Ultimately cancelled in 1973






# Background on Nuclear Thermal Propulsion



NERVA Concept Engine





16.4-kIbf SNRE Reactor Core



Fuel Elements

Tie-Tube Bundles



NTR Engine Cycle



# Challenges to Ground Testing NTR

- Hot-hydrogen stream is passed directly through fuel elements
  - Potential for radioactive material to be eroded into gaseous fuel flow as identified in previous programs
  - NERVA and Project Rover (1950's-70's) were able to test in open atmosphere
    - Similar to conventional rocket engine test stands today
    - Nuclear Furnace-1 tests employed a full scrubber system
- Increased government and environmental regulations prohibit the modern testing in open atmosphere
  - Since the 1960's, there's been an increasing cessation on open air testing of nuclear material
  - Political and national security concerns further compound the regulatory environment






# Ground Test Options

- Open Air Testing
  - Least expensive method and used during Rover/NERVA
  - Preferably at remote site (such as NNSS)
  - Environmental, political and regulatory concerns rule out as possibility for future test series
  
- Above Ground Scrubbers
  - Used during Nuclear Furnace-1 (NF-1) testing
  - Exhaust still expelled to atmosphere, but after series of filters & heat exchangers
  - Remaining hydrogen is flared off and burned




From: AIAA 2011-5849



From: AIAA 1989-2386

# Ground Test Options


- Full-Containment
  - Similar to above-ground scrubber concept
  - Hydrogen exhaust is burned with oxygen to create steam, cooled, condensed and collected
  - Filters and particle traps capture any condensable nuclides
  - Exhaust water is then held in retention tanks and slowly filtered for evaporation
  - Non-condensable gases (e.g. oxygen) are collected, filtered and vented off



From: NETS2015-5146

# Ground Test Options


- Sub-surface Active Filtration of Exhaust (SAFE)
  - Conceptualized by Steve Howe, CSNR in 1998
  - Uses the alluvium soil of NNSS to act as natural filter
  - Uses existing “boreholes” at NNSS left over from below ground nuclear weapons testing
  - Envisioned as being a cost-effective option since costs for infrastructure (e.g. scrubbers and filters) are reduced, and existence of boreholes at NNSS
  - Water spray would help cool and condense the exhaust
  - One of leading ground test options for NTP project




Source: Steve Howe, CSNR

# Validation Plans for SAFE Concept

- Before SAFE concept can be utilized on a full-scale nuclear engine, must be validated
  - Several studies and models have investigated the soil characteristics and concept of tests at NNSS.
  - Physical tests need to be conducted to validate model predictions
- Plans are to utilize a non-nuclear rocket engine to produce high temperature exhaust at NNSS borehole
  - Tests will utilize Aerojet Rocketdyne Liquid oxygen Augmented Nuclear Thermal Rocket (LANTR) simulator
    - Hydrogen-Oxygen test article with oxygen afterburner
    - Simulates exhaust products expected from full-scale testing with water cooling
  - Will seed exhaust with Xenon or Krypton to measure nuclide migration through soil




From: AIAA 2012-3743





# Alternative SAFE Concepts

- Security regulations and HEU quantities for SNRE may pose increased costs for above ground SAFE tests
  - Alternative concepts being investigated based upon SAFE concept
- U1-A site at NNSS attractive due to below ground tunnels and soil characteristics
  - Would allow for quick entombment of engine should release incident occur
  - Temporary hot-cell could be located in parallel drift tunnel
- P-Tunnel site at NNSS attractive due to solid rock features in mountain tunnels
  - Could be attractive to reduce hydrogen diffusion through tunnel complexes and reduce water cooling requirements
  - Would use heat exchangers, filters & flare stack to vent to atmosphere and regulate pressure in tunnel



From: NETS2015-5146



# Recent Assessments

- Numerous studies have reviewed ground test programs over history of NTP
  - Various engine sizes ranging from 7 kbf to 75 klbf were used as baseline from studies
    - Difficult to complete an “apples-to-apples” comparison due to varying scales and program direction
    - Ex: Recent review by ARES studied a 222-kN (50-klbf) engine vs. the 73-kN (16.4-klbf) scale engine under current investigation. Also considered a 25 year life-cycle
    - Difference in scales impact consumables, infrastructure requirements, security and regulatory requirements, etc.
    - Cost inflation since 1980’s/1990’s further compound comparisons
  - Most recent assessments conducted by NSTec in 2011
    - Full-power/duration tests at NNSS
      - Based upon 1999 Bechtel Nevada estimates and included inflation
    - Sub-scale SAFE validation tests
      - “Clean-sheet” cost assessment
      - Included costs of preparation of test site (holes, berms, trailers, etc.)
- Despite previous estimate activities, continual discussion of what cost drivers impact ground testing cost & schedule
- NASA and DOE stakeholders currently engaged to understand ground test requirements and impacts



# Summary

- Nuclear Thermal Propulsion is an enabling technology for fast crewed Mars missions, but requires ground test facility
- A number of ground test options are possible
  - Sub-surface Active Filtration of Exhaust (SAFE) concept is one of the approaches for ground testing being examined
- SAFE concept requires a sub-scale, non-nuclear validation
  - Alternative methods based on SAFE concept would utilize below ground tunnels at NNSS for additional security/safety
- On-going discussions with NASA and DOE stakeholders reviewing regulatory and programmatic requirements for best path forward for ground testing