



Keeping the universe connected.

Design of a K/Q-band Beacon Receiver for the Alphasat TDP#5 Experiment

Jacquelynne R. Morse
NASA Glenn Research Center
Cleveland, OH

July 7th, 2014

Presentation Overview




1. Technical Motivation
2. Site Information
3. Receiver Design
4. Receiver Performance
5. Measurement Resolution
6. Initial Results
7. Conclusions & Future Work

Technical Motivation




Propagation studies at a given site are valuable in designing efficient, cost effective ground stations without sacrificing performance or availability.^[1]



Attenuation measurements characterize the attenuation of a link due to rain, clouds, and gases in the troposphere.^[7] The total attenuation can be measured on the ground via a beacon receiver.

The beacon transmits a signal, and the power is measured on the ground. This power measurement will fluctuate with atmospheric conditions, yielding a characterization of the total atmospheric attenuation.

Site Information



Milan, Italy		
Site	Installation Date	April 2014
	Latitude	45.4787° N
	Longitude	9.2327° E
	Altitude	121 m
Satellite	Name	Alphasat
	Elevation	48.6°
	Azimuth	170.2°
	Beacon Freqs.	19.701 GHz 39.402 GHz




This work was performed as part of the development of a beacon receiver terminal deployed to **Milan**, Italy in collaboration with the Politecnico di Milano.

Receiver Design



System Specifications	
Downconversion (Ka)	3-step down to 455 kHz
Downconversion (Q)	4-step down to 455 kHz
Sampling Rate	1.111 MHz
Number of Points	2^{17}
Integration Time	125 ms
Time Series Output Rate	8 Hz
Dynamic Range	35 dB



Receiver Performance



Laboratory Performance


System Performance		
	Ka	Q
System Temperature	504K	720K
Dynamic Range at 1 Hz	58dB	58dB
Dynamic Range at 8 Hz	48dB	48dB

Actual Performance

System Performance		
	Ka	Q
System Temperature	504K	720K
Dynamic Range at 1 Hz	40dB	40dB
Dynamic Range at 8 Hz	37dB	37dB

In laboratory testing the system achieved a dynamic range of 58/48dB for the 1Hz and 8Hz measurements. This was based on the link budget calculations that estimated the power at the flange to be ~ -115 dB. The actual power is lower than expected reducing the dynamic range, additionally the phase stability of the satellite is worse than expected. The phase instability made the 1Hz measurements noisy due to the long integration time. The 1Hz measurements are now made by averaging the 8Hz measurements over the 1Hz integration time further reducing the dynamic range.

Measurement Resolution




The above figure shows the system performance in clear sky conditions. The measurement resolution of the system during this condition is .009dB root-mean-square (RMS) at 10Hz and .005dB RMS at 1Hz


Initial Results



Measured Attenuation 6/4/2014



Measured Rain Rate 6/4/2014



Data collection officially began 6/1/2014. It is too soon for full statistical analysis but several major rain events have been recorded by the system.

Conclusions/Future Work



The AlphaSat terminal was installed in Milan Italy in April of 2014 with the official data collection starting on June 1st, 2014. The goals of the campaign will be to study the atmospheric effects at Ka/Q band and to investigate site diversity at these frequencies using a second terminal located in Spino d'Adda, Italy approximately 30km away.

Current Plans:

- **Continued Data Collection**
 - ≥ 5 years per site

Long-Term Goals:

- **Adaptive Compensation Techniques**
- **New Frequency Bands**
 - *Q/V/W Band*
- **Additional Sites**

References



- [1] A.R. Thompson, J.M. Moran, and G.W. Swenson, *Interferometry and Synthesis in Radio Astronomy*, Second Edition, John Wiley & Sons, 2001.
- [2] D. H. Rogstad, A. Mileant, and T. T. Pham, *Antenna Arraying Techniques in the Deep Space Network*. Pasadena, CA, Hoboken, NJ: Wiley, 2003.
- [3] J. A. Nessel and R. J. Acosta, "Predicting Sparse Array Performance From Two-Element Interferometer Data," *IEEE Trans. Antennas Propag.*, vol. 60, no. 2, pp. 886-894, Feb. 2012.
- [4] R. J. Acosta, et al., "Simultaneous Ka-Band Site Characterization: Goldstone, CA, White Sands, NM, and Guam, USA," in 17th Ka and Broadband Communications Conference, Palermo, Italy, 2011.
- [5] "The Proposer's Guide for the Green Bank Telescope," National Radio Astronomy Observatory, 2013.
- [6] C. Salter, "An Astronomer's Guide to the Arecibo 305-m Telescope," National Astronomy and Ionosphere Center, 2012.
- [7] J.-R. Cook, "Historic Deep Space Network Antenna Starts Major Surgery," Jet Propulsion Laboratory Press Release, 2010.
- [8] R. K. Crane, "Propagation Phenomena Affecting Satellite Communication System Operating in the Centimeter and Millimeter Wavelength Bands," *Proc. IEEE*, vol. 59, no. 2, pp. 173-188, Feb. 1971.
- [9] P. Hariharan, *Basics of Interferometry*, 2nd ed. Burlington, MA: Elsevier, 2007.
- [10] R. J. Acosta, B. D. Frantz, J. A. Nessel, and D. D. Morabito, "Goldstone Site Test Interferometer," in 13th Ka and Broadband Communications Conference, Turin, Italy, 2007.
- [11] R. J. Acosta, M. J. Zemba, J. R. Morse, and J. A. Nessel, "Two Years of Simultaneous Ka-Band Measurements: Goldstone, CA; White Sands, NM; and Guam, USA," in 18th Ka and Broadband Communications Conference, Ottawa, Canada, 2012.
- [12] R. J. Acosta, J. R. Morse, M. J. Zemba, and J. A. Nessel, "Two Years of Site Diversity Measurements in Guam," in 18th Ka and Broadband Communications Conference, Ottawa, Canada, 2012.
- [13] R. J. Acosta, J. A. Nessel, and D. D. Morabito, "Data Processing for Atmospheric Phase Interferometers," in 14th Ka and Broadband Communications Conference, Matera, Italy, 2008.
- [14] C. Peat. (2013, Aug.) Heavens Above - ANIK F2 Orbit. <http://www.heavens-above.com/orbit.aspx?satid=28378&lat=0&lng=0&loc=Unspecified&alt=0&tz=CET>
- [15] Mathworks. (2013, Aug.) MATLAB Polynomial Curve Fitting. <http://www.mathworks.com/help/matlab/ref/polyfit.html>
- [16] A. Kolmogorov, "The Local Structure of Turbulence in Incompressible Viscous Fluid for Very Large Reynolds Numbers," *Proc. USSR Academy of Sciences*, vol. 30, pp. 229-303, 1941.
- [17] G. I. Taylor, "The Spectrum of Turbulence," *Proc. Roy. Soc. Lond. A*, vol. 164, no. 919, pp. 476-490, 1938.
- [18] S. Radford and M. A. Holdaway, "Atmospheric Conditions at a site for submillimeter Wavelength Astronomy," *Proc. SPIE*, vol. 3357, 1998.
- [19] F. Davarian, "Uplink Arrays for the Deep Space Network," *Proc. IEEE*, vol. 95, no. 10, pp. 1923-1930, Oct. 2007.
- [20] B. J. Butler and S. J. E. Radford, "Atmospheric Phase Stability at Chajnantor and Pampa la Bola," *NRAO ALMA Memo*. No. 365, 2001.
- [21] R. E. Hills, R. J. Kurz, and A. B. Peck, "ALMA: Status Report on Construction and Early Results from Commissioning," *Joint ALMA Observatory*, 2012.



Appendix / Backup Slides