



## Technical Note

## Re: Penetration behavior of opposed rows of staggered secondary air jets depending on jet penetration coefficient and momentum flux ratio

James D. Holdeman<sup>1</sup>

NASA Glenn Research Center, Cleveland, OH 44135, USA

## ARTICLE INFO

## Article history:

Received 12 May 2016

Accepted 14 June 2016

## Keywords:

Solid waste incinerator

Staggered jets

Momentum-flux ratio

Jet penetration coefficient

Jets in crossflow

Gas turbine combustors

Dilution jets

Empirical model

Correlations

Conserved scalar

Temperature distribution

JIC

## ABSTRACT

The purpose of this article is to explain why the extension of the previously published  $C = (S/H_o)\sqrt{J}$  scaling for opposed rows of staggered jets wasn't directly successful in the study by Choi et al. (2016).

It is not surprising that staggered jets from opposite sides do not pass each other at the expected  $C$  value, because  $H_o/D$  and  $\sqrt{J}$  are much larger than the maximum in previous studies. These, and large  $x/D$ 's, tend to suggest development of 2-dimensional flow.

Although there are distinct optima for opposed rows of in-line jets, single-side injection, and opposed rows of staggered jets based on  $C$ , opposed rows of staggered jets provide as good or better mixing performance, at any  $C$  value, than opposed rows of in-line jets or jets from single-side injection.

© 2016 The Author. Published by Elsevier Ltd. This is an open access article under the CC BY-NC-ND license (<http://creativecommons.org/licenses/by-nc-nd/4.0/>).

## 1. Introduction

The extensive studies of rows of non-reacting jets in crossflow (JIC) that are summarized in Ref. [1] were motivated by mixing of dilution jets in conventional gas turbine combustors.

The orifice spacing,  $S/H_o$  and  $S/D$ , the density ratio,  $DR$ , and the jet-to-mainstream mass-flow ratio,  $MR$ , in Ref. [2] are within the range of the experiments in Ref. [1]. However, the jet-to-mainstream momentum-flux ratio,  $J = (\rho_j V_j^2)/(\rho_m U_m^2)$ , and the reciprocal of the orifice size,  $H_o/D$ , are substantial extrapolations. The minimum  $J$  in Ref. [2] is approximately an order of magnitude greater than the maximum in Ref. [1] ( $J \simeq 100$ ), and the holes in Ref. [2] are much smaller than the minimum size in Ref. [1] (i.e.  $1/(H_o/D) = 0.125$ ).

Since both  $J$  and  $H_o/D$  are significantly larger in the application that motivated Ref. [2] than they are in gas turbine combustors, it is not surprising that the jets from opposite sides cannot pass each other without interacting as is required for optimum mixing of opposed rows of staggered jets.

The purpose of this article is to investigate why the extension of the  $C = (S/H_o)\sqrt{J}$  scaling in Ref. [1] wasn't quantitatively successful for the application that motivated Ref. [2].

From the experimental results in Ref. [1], it is apparent that midplane values approach centerplane values (the mean flow becomes more 2-dimensional) as the momentum-flux ratio,  $J$ , and the dimensionless downstream distance,  $x/D = (x/H_o)(H_o/D)$ , increase.

## 2. History and previous usage of the NASA empirical model for confined JIC's

The effect of high momentum-flux ratio and small orifice size can be shown for conditions similar to those in Ref. [2] using the NASA JIC empirical model. This model was used in Refs. [3,4] to represent data obtained in the 1970s and 1980s. The original Applesoft® BASIC code (in Appendixes A and B of Ref. [5]) was subsequently rendered in an Excel® spreadsheet (unchanged – except for correction of known errors) in Refs. [5–8] using the correlation equations in Appendix C of Ref. [5]. (These correlations are the same as those in Ref. [1], but with the curvature effect equations in Ref. [1] deleted). The NASA JIC spreadsheet was also used in

<sup>1</sup> Present address: 5228 Meadow Moss Ln, N Ridgeville, OH 44039, USA.

E-mail address: [jjdholdeman@aol.com](mailto:jjdholdeman@aol.com)

### Nomenclature

|       |   |            |  |
|-------|---|------------|--|
| $C$   | $(S/H_o)(\sqrt{J})$   | $T$        | local scalar variable  |
| $C_d$ | orifice discharge coefficient = (effective area)/(physical area)  | $T_j$      | jet exit scalar variable   |
| $D$   | actual orifice diameter   | $T_m$      | unmixed mainstream scalar variable   |
| $DR$  | jet-to-mainstream density ratio, $\rho_j/\rho_m$ (for an incompressible flow, and for gases of the same chemical composition, this ratio is approximately equal to the mainstream-to-jet temperature ratio, $T_m/T_j$ ) | $U_m$      | velocity of unmixed mainstream   |
| $H_o$ | duct height at center of row of holes (called $H$ in several previous publications)   | $V_j$      | jet exit velocity  |
| $J$   | jet-to-mainstream momentum-flux ratio   | $x$        | downstream coordinate; $x = 0$ at center of the row of orifices                            |
| $MR$  | jet-to-mainstream mass-flow ratio   | $y$        | cross-stream coordinate  |
| $S$   | lateral spacing between equivalent locations of adjacent orifices, e.g. between orifice centerplanes  | $y_c/H_o$  | scalar trajectory = location of maximum scalar difference ratio in centerplane, $\theta_c$ |
| $S/D$ | ratio of orifice spacing to orifice diameter  | $z$        | lateral coordinate; $z = 0$ at centerplane   |
|       |   | $\theta$   | $(T_m - T)/(T_m - T_j)$  |
|       |   | $\theta_c$ | maximum scalar difference ratio, defines location of scalar trajectory, $y_c/H_o$          |

Ref. [9] for opposed rows of both aligned and staggered jets. (actually Refs. [9,10] are both subsets of Ref. [7].)

The several versions of the spreadsheet published to date are all capable of performing previous calculations, so the one included with Ref. [8] can duplicate all the results shown in Refs. [5–10] and is the version used in this paper.

Note that the NASA JIC spreadsheet assumes Gaussian profiles on both sides of the jet trajectory. Thus it should not be used if the jet trajectory exceeds  $H_o$ , i.e. if  $y_c/H_o > 1$ .

The NASA JIC spreadsheet doesn't have  $C = (S/H_o)\sqrt{J}$  scaling "hardwired" so it should give a fair and adequate representation of the results in Ref. [2]. Although it returns results, the spreadsheet should not be used upstream of the trailing edge of the orifices ( $x/D = 0.5$  ( $x/H_o = 0.5/(H_o/D)$ )).

### 3. Results

Profile and contour plots from the NASA JIC spreadsheet are shown in Figs. 1–7 for the conditions in Table 1 in the present communication. The conditions for Figs. 3–6 are the same as those in Table 1 in Ref. [2].

The parameter shown in the profile and contour plots is  $\theta = (T - T)/(T_m - T_j)$ , where  $T_m$  is the mainstream temperature,  $T_j$  is the jet temperature, and  $T$  is the local temperature. Note that  $\theta = 1$  for pure jet fluid,  $\theta = 0$  for pure mainstream fluid, and  $\theta = MR/(MR + 1)$  at the fully mixed condition. Although temperature is used here, any conserved scalar is acceptable.

The profile and contour plots in this paper always cover a span of two orifices on each side. Thus, the physical distance shown will vary with orifice spacing.

The conditions for  $C = 1.3$  in Fig. 1 (column 1) represent an optimum mixer for opposed rows of aligned jets. The results shown in

Fig. 1 suggest that the flow becomes 2-dimensional very quickly, which is not surprising given the high  $J$ , high  $x/D$ , small orifice size, and small orifice spacing.

Nonetheless, the results in Fig. 1 agree with the  $C = (S/H_o)\sqrt{J}$  scaling in Ref. [1]. Although the jets on top and bottom are aligned, results for in-line and staggered jets are indistinguishable for high  $C$  values at the  $C$  value that is optimum for opposed rows of in-line jets.

The conditions in column 2 for  $C = 2.6$  are nearly optimum for one-side injection, and have been changed from the staggered case in Ref. [2] to one-side injection at the jet-to-mainstream mass-flow ratio used in Ref. [2]. Note that the diameter of the orifices is double that for each row of the single-side jets in column 2 (and Fig. 2) because there are only half as many orifices per row and only half as many rows in the single-side configuration in column 2.

The one-side injection in Fig. 2 is also in approximate agreement with the  $C$  scaling in Ref. [1], but note that the jet penetration also depends significantly on downstream distance.


The results in Fig. 2 are very similar to the results for the upper jets in Fig. 1 when the  $x/H_o$  for single-side injection (Fig. 2) is twice that in opposed rows of in-line jets (Fig. 1) since the "effective" mixing height for opposed rows of in-line jets is  $H_o/2$ . Thus, better mixing is obtained at a specified downstream distance ( $x/H_o$ ) with opposed rows of jets.

The results for staggered jets at  $C = 2.6, 3.5, 5.7$  and  $9.4$  shown in Figs. 3–6 essentially agree with the results in Ref. [2].

Fig. 3 has the same  $C$  value as Fig. 2 ( $C = 2.6$ ), but the configuration in Fig. 3 is opposed rows of staggered jets. Note that the orifices are smaller than for single-side injection since there are twice as many rows, but the orifice spacing ( $S/H_o$ ) and  $MR$  are the same.

**Table 1**  
Parameters for cases calculated with the NASA JIC spreadsheet.

| Figure  | 1    | 2    | 3    | 4    | 8    | 6    | 7    |
|---------|------|------|------|------|------|------|------|
| $C$     | 1.3  | 2.6  | 2.6  | 3.5  | 5.7  | 9.4  | 18.8 |
| $DR$    | 1    | 1    | 1    | 1    | 1    | 1    | 1    |
| $J$     | 800  | 800  | 800  | 800  | 800  | 800  | 800  |
| $H_o/D$ | 70.6 | 35.3 | 49.9 | 42.4 | 32.8 | 24.4 | 17.3 |
| $S/H_o$ | .045 | .091 | .091 | .125 | .200 | .333 | .667 |
| $C_d$   | 1    | 1    | 1    | 1    | 1    | 1    | 1    |
| $S/D$   | 3.2  | 3.2  | 4.5  | 5.4  | 6.6  | 8.2  | 11.5 |
| $D/H_o$ | .014 | .028 | .02  | .024 | .031 | .041 | .058 |




**Fig. 1.** Profile and contour plots from NASA JIC Excel<sup>®</sup> spreadsheet for opposed rows of in-line jets at  $C = 1.3$ :  $DR = 1$ ,  $J = 800$ ,  $H_0/D = 70.6$ ,  $S/H_0 = 0.045$  ( $S/D = 3.2$ ), and  $C_d = 1$ .

Fig. 3 shows equivalent mixing to that in Fig. 2 at the  $C$  value that is optimum for single-side injection. However, opposed rows of staggered jets fill in the gaps, and are less sensitive to variations in downstream distance.

The profiles and contours in Figs. 4 and 5 show that the jets from opposite sides do not pass each other. Although optimum

penetration for opposed rows of staggered jets was expected for  $C = 5.7$  (Fig. 5), this probably does not occur because the high  $J$  and  $H_0/D$  values promote jet interaction and 2-dimensional flow.


The profiles and contours for  $C = 9.4$  in Fig. 6 suggest that the jets from opposite sides are trying to pass, as the initial profiles are similar to the initial ones in sequence 18 in the slideshow in the



**Fig. 2.** Profile and contour plots from NASA JIC Excel<sup>®</sup> spreadsheet for single-side injection at  $C = 2.6$ ;  $DR = 1$ ,  $J = 800$ ,  $H_0/D = 35.3$ ,  $S/H_0 = 0.091$  ( $S/D = 3.2$ ), and  $C_d = 1$ .

Appendix of Ref. [6] and in Figs. 12 and 13 of Ref. [7] and Figs. 7 and 8 of Ref. [9]. However, further penetration is masked by 2-dimensional flow. However, the mixing is quite uniform at  $x/H_0 = 0.5$ .


The conditions for  $C = 18.8$  in column (and Fig. 7) are not possible in the facility used in Ref. [2], but are included here to show what might be expected for a further increase in  $C$ . Here



**Fig. 3.** Profile and contour plots from NASA JIC Excel<sup>®</sup> spreadsheet for opposed rows of staggered jets at  $C = 2.6$ :  $DR = 1$ ,  $J = 800$ ,  $H_0/D = 49.9$ ,  $S/H_0 = 0.091$  ( $S/D = 4.5$ ), and  $C_d = 1$ .


$S/H_0 = 0.667$  which seems acceptable, but it is unlikely that a jet would spread laterally more than in the direction of jet penetration so care must be taken to insure that  $S/H_0 \leq 1$ .

Fig. 7 shows jets from opposite sides that pass each other, as shown in Fig. 12 of Ref. [7] and Fig. 7 of Ref. [9]. Apparently the high momentum-flux ratio jets are finally spaced far enough apart



**Fig. 4.** Profile and contour plots from NASA JIC Excel<sup>®</sup> spreadsheet for opposed rows of staggered jets at  $C = 3.5$ :  $DR = 1$ ,  $J = 800$ ,  $H_o/D = 42.8$ ,  $S/H_o = 0.125$  ( $S/D = 5.4$ ), and  $C_d = 1$ .






**Fig. 5.** Profile and contour plots from NASA JIC Excel<sup>®</sup> spreadsheet for opposed rows of staggered jets at  $C = 5.7$ :  $DR = 1$ ,  $J = 800$ ,  $H_o/D = 32.8$ ,  $S/H_o = 0.2$  ( $S/D = 6.6$ ), and  $C_d = 1$ .

that jets from opposite sides can pass each other without interacting. Distributions from the JIC spreadsheet are not shown farther downstream than  $x/H_o = 0.1$  as the jet trajectory exceeds  $H_o$ , and significant mass is “lost” (i.e. the profiles are truncated).

Although calculating  $S/D$  ( $= (S/H_o)(H_o/D)$ ) is straight-forward,  $S/D$  values are included in Table 1 and the titles of Figs. 1–7 as they highlight the importance of  $S/D$  spacing.

No matter what the application is, the absolute minimum spacing that allows staggered jets from opposite sides to pass each other




**Fig. 6.** Profile and contour plots from NASA JIC Excel<sup>®</sup> spreadsheet for opposed rows of staggered jets at  $C = 9.4$ :  $DR = 1$ ,  $J = 800$ ,  $H_0/D = 24.4$ ,  $S/H_0 = 0.333$  ( $S/D = 8.2$ ), and  $C_d = 1$ .

is  $S/D = 2$ , provided that the opposed rows are perfectly staggered and the jets do not diffuse as they proceed downstream. Of course,

this won't happen, and the minimum  $S/D$  will increase as  $J$  increases.





**Fig. 7.** Profile and contour plots from NASA JIC Excel<sup>®</sup> spreadsheet for opposed rows of staggered jets at  $C = 18.8$ :  $DR = 1$ ,  $J = 800$ ,  $H_o/D = 17.3$ ,  $S/H_o = 0.667$  ( $S/D = 11.5$ ), and  $C_d = 1$ .

In the application that motivated Ref. [2], the optimum  $S/D$  for opposed rows of staggered jets appears to be approximately  $S/D = 10$ . Thus,  $C = ((S/D)/(H_o/D))\sqrt{J} = 283/(H_o/D)$  for  $J = 800$ ; if  $H_o/D \approx 20$ , then  $C \approx 15$ . Note that in Fig. 7 of Ref. [9],  $S/D = 8$ ,  $H_o/D = 8$ , and  $J = 26.4$ , so  $C = 5.14$ , but if  $J$  were 800,  $C$  would be 28.3 for  $S/H_o = 1$ .

#### 4. In Conclusion

Since  $H_o/D$  and  $\sqrt{J}$  are approximately both 3 times larger than the maximum in previous studies, and these, and large  $x/D$ 's show 2-dimensional flow, it is not surprising that staggered jets from opposite sides do not pass each other at the expected  $C$  value.

There are distinct optima for opposed rows of in-line jets, single-side injection, and opposed rows of staggered jets based on  $C$ . However, opposed rows of staggered jets provide as good or better mixing performance as opposed rows of in-line jets or jets from single-side injection at any  $C$  value.

#### Acknowledgements

The author would particularly like to thank Mr. Richard E. Walker (Aerojet Liquid Rocket Company, ret.) and Dr. Ram Srinivasan (then of Garrett Turbine Engine Company) for their early contributions to the NASA JIC empirical model. The author would also like to thank Professor William E. Lear, Jr. of the University of Florida for suggesting that the original computer code could be converted to an Excel<sup>®</sup> spreadsheet and for directing its development, and to Mr. James R. Clisset who did the initial Excel<sup>®</sup> programming as an undergraduate student at UF. Also, Messrs. Timothy D. Smith and Jeffrey P. Moder of the NASA Glenn Research Center contributed significantly to development and demonstration of the spreadsheet. Finally, the author would like to thank Dr. Clarence T. Chang of the Combustion Branch at the NASA Glenn Research Center for providing funding for the Open Access publication and color printing of this paper.

## References

- [1] James D. Holdeman, Mixing of multiple jets with a confined subsonic crossflow, *Prog. Energy Combust. Sci.* 19 (June 1991) 31–70, [http://dx.doi.org/10.1016/0360-1285\(93\)90021-6](http://dx.doi.org/10.1016/0360-1285(93)90021-6). similar to AIAA Paper 91-2458 and NASA TM 104412.
- [2] Chonggun Choi, Woosung Choi, Jun Hyuk Choi, Donghoon Shin, Penetration behavior of opposed rows of staggered secondary air jets depending on jet penetration coefficient and momentum flux ratio, accepted for publication, *Int. J. Heat Mass Transfer* (2016), <http://dx.doi.org/10.1016/j.ijheatmasstransfer.2016.04.088>.
- [3] J.D. Holdeman, Perspectives on the mixing of a row of jets with a confined crossflow, AIAA Paper 83-1200 (also NASA TM.83457), 1983, <http://dx.doi.org/10.2514/6.1983-1200>.
- [4] J.D. Holdeman, R. Srinivasan, Perspectives on dilution jet mixing, AIAA Paper 86-1611 (also NASA TM 887294), 1986.
- [5] James D. Holdeman, Timothy D. Smith, James R. Clisset, William E. Lear Jr., A spreadsheet for the mixing of a row of jets with a confined crossflow, NASA/TM-2005-213137, 2005.
- [6] James D. Holdeman, James R. Clisset, Jeffrey P. Moder, William E. Lear Jr., On the mixing of single and opposed rows of jets with a confined crossflow, NASA/TM-2006-214226, 2006.
- [7] James D. Holdeman, James R. Clisset, Jeffrey P. Moder, Spreadsheet Calculations for Jets in Crossflow: Opposed Rows of Inline and Staggered Holes and Single and Opposed Rows With Alternating Hole Sizes, NASA/TM-2010-216100, 2010.
- [8] James D. Holdeman, James R. Clisset, Jeffrey P. Moder, Spreadsheet calculations for jets in crossflow: opposed rows of slots slanted at 45°, NASA/TM-2011-215980, 2011.
- [9] James D. Holdeman, James R. Clisset, Jeffrey P. Moder, Spreadsheet calculations of jets in crossflow: opposed rows of inline and staggered round holes, *Heat Mass Transfer* 48 (2) (February 2012) 412–424, <http://dx.doi.org/10.1007/s00231-011-0913-6>.
- [10] J.D. Holdeman, J.R. Clisset, J.P. Moder, Spreadsheet calculations for jets in crossflow from single and opposed rows with alternating hole sizes, *J. Eng. Gas Turbines Power* 132 (2010) 64502-1–64502-7, <http://dx.doi.org/10.1115/1.40001>.