AERONAUTICS

Airspace Technology Demonstration 2 (ATD-2)

Integrated Surface and Airspace Simulation – Experiment Plan

> Joint Workshop for KARI-NASA Research Collaboration May 23 - 25, 2017





Airspace Technology Demonstration 2 (ATD-2)

Integrated Surface and Airspace Simulation (ISAS)

March 7th- 9th







- ATD-2 project overview
- Objectives of the HITL
- ATD-2 capabilities tested in the HITL
- Tools used in the HITL
- What to expect during testing?
- Participants
- Roles and responsibilities
- Schedule





ATD-2 Project Overview

Operational Environment for the ATD-2 Concept



ATC: Phase 1: Baseline IADS Demonstration





- CLT ATCT control positionsBaseline electronic flight data
- Baseline electronic flight data capability via TFDM EFD



- AAL ramp controller and manager positions
- Tactical pushback advisories via RTC/RMTC display



- All positions as neededPredictive mode: strategic
- metering info for situational awareness and analysis

Surface Components

Interfaces to external systems via SWIM plus ATD-2 SWIM extensions



Phase 1 Demonstration Goals

- Evaluate the Baseline IADS capability
- Enhance American Airlines CLT "departure sequencing" procedure with ATD-2 surface tactical metering
- Demonstrate improved compliance for a significant percentage of tactical TMIs
- Mature strategic Surface CDM capability via operational use, analysis, and feedback
- Reduce ATCT workload by replacing paper strips with EFD



CLT ATCT TMU position
Tactical departure scheduling capability via STBO display



- ZDC TMU
- Tactical departure scheduling via modified TBFM/IDAC

Airspace Components







ISAS HITL Objectives





- Evaluate operational procedures and information requirements for the following:
 - Tactical Surface Metering Tool
 - Evaluate the level of gate holds and its impact on runway queue
 - Evaluate the impact of EOBT accuracy level on the advisories
 - APREQ/CFR procedures between ATC Tower and Center
 - Data exchange elements between Ramp and ATC Tower
- Obtain feedback for Phase 1 Freeze decisions
 - Software
 - Procedures
 - Training





ATD-2 capabilities tested in the HITL



Surface Metering Concept



- Estimates capacity of current and future runway resources
- Builds an efficient runway schedule based on readiness, EOBT and RBS
- Calculates spot advisories that support the metered runway schedule
- Provides push back advisories from gates that support the spot advisories



Trajectory prediction and constraint modeling

RBS = Ration By Schedule











- Based on legacy PDRC currently deployed at DFW ATC tower
 - Improves the insertion of the flight into the overhead stream
 - Automates the process of getting a flow time (i.e., wheelsup time) from the Center that was traditionally handled via phone calls
- Provides Surface trajectory based OFF times to TBFM scheduler
- Integrates IDAC/IDST into the STBO (Surface Trajectory Based Operations)
- Shows the slots on STBO Timeline and allows automated APREQs

PDRC = Precision Departure Release capability APREQ = Approval Request or CFR = call for release TBFM = Time Based Flow Management IDAC= Integrated Departure and Arrival Capability IDST = Integrated Departure Scheduling Tool STBO = Surface Trajectory Based Operations



STBO Client Timeline











- Metering Time Based Metering
- Pushback and Surveillance information
- APREQ/CFR
- MIT flights
- EDCT flights
- Gate Conflicts
- Change runway utilization
- Runway assignments operational necessity only
- Long on board (LOB) common awareness
- Runway closures

EDCT = Expected Departure Clearance Time MIT = Miles in Trail





Tools used in the HITL





- ATC Tower
 - Mini Tower showing CLT ATC tower out-the-window view (270 degree view) using 8 monitors
 - STBO Client: Surface Trajectory Based Operations
 - Emulation of ASDE-X display (STBO map)
 - Flight Strips
- AAL Ramp
 - 360 degree Simulator at FutureFlight Central (FFC)
 - Tactical Surface Scheduler (Ramp Tool)
 - Ramp Traffic Console (RTC) & Ramp Manager Traffic Console (RMTC)
- CLT TRACON
 - Emulation of STARS displays
 - Operational TBFM (ZTL arrival metering)
 - Remote view of STBO
- Washington Center (ZDC)
 - TBFM (ZDC Departure scheduling)
 - Remote view of STBO Client
 - Emulation of Traffic Situational Display (TSD)



AAL CLT Ramp Tower - FFC







ATCT Panoramic View







CLT Tower TMC with STBO















Pseudo-pilot working with ATG





ATG = Airspace Traffic Generator





- STBO Client : Surface Trajectory Based Operations (ATC Tower Tool)
- RTC: Ramp Traffic Console (Ramp Tool)
- RMTC: Ramp Manager Traffic Console (Ramp Tool)
- TBFM Trajectory based Flow Management (ZDC & TRACON Tool)
- MACS- Multi Aircraft Control System (TRACON & En route Tool)
- ATG: Airspace Traffic Generator (Tower Pseudo Pilot Tool)

Surface Trajectory Based Operations (STBO) Client



 \odot

18R/36L

Toolbar STBO Toolbar - sms \odot Settings TM Actions Create Show Window Search NEW (.... RAMAY 15 MIT 19:26:46 North_Departures_Normal 🖸 💿 Timeline: Runway 23/05 18L/36R \odot \otimes 🛓 💿 STBO Map 1 - sms 🛞 🖪 💽 Timeline: Runway 18C/36C 18R/36L File View Action Help Runwav Runway 18L/36R 🛕 D 🔍 Q 😡 🐹 🕲 💢 🕲 🦯 🗄 36C 23 18L 5 36L 18R 18C 36R 8-8-Map 4862 E12 4866060 KILNS A12 APREO G ASH6 -JIA511783 (CONS CS MIT -13 -JIA5119 KWEEN E19 -AAL1802 B14 -JIA5218 BEAVY E21 -AAL852 B11 -TCF3328 BARMY A5 JIA5 427 KILNS E33 APREQ Current time: 19:26:47 GMT Configuration: D 36C 36R A 36L 36C 36R Scenario: North Departures Normal - Visuals All; Results: 548 total, 19:26 GMT \odot Close 🌱 🐺 🗃 🖽 🖽 Search Spot B Flight ID Dest AC Type Mtrd On Ti... Etms Eta RwyOpNec Rwy Time Status 21/18.59 21/18.26 Enroute_Dep Ramp A... Gate E SOUTH E15 IIA5365 CRI9 21/18:31 21/18:28 In E21/19:46 Scheduled_Out \$9W 21/18:28 – 🖇 RPA4573 KILNS C3 APREQ 🖕 IIA5372 E_NORTH E20 RIC 21/20:31 S24 IIA5376 CLT CRJ9 21/18:44 21/18:45 21/18:45 E_SOUTH E17 S27E In JIA5379 CLE CRJ9 21/19:44 21/18:44 Enroute_Dep E_NOR... E25 S2 4 JIA5386 CRJ9 E_NORTH E26 BW 21/21:15 E21/20:10 Scheduled_Out JIA5386 CRJ9 21/18:26 21/18:29 21/18:27 In E_SOUTH ESA 527E 21/18:50 Enroute_Dep JIA5387 E_NORTH E8 CRIS 21/19:49 BW IIA5388 CRI9 22/00:36 E_SOUTH E17 527E Scheduled_In IIA5388 E21/19:36 Out E NORTH E32 BDL 21/21:04 S2.4 1145400 CLT CRI7 E_SOUTH E3 \$2.7E Scheduled_In RWY 23/05 19:26:46 RWY 18L/36R RWY 18C/36C 19:26:47 1145401 CRJ7 21/21:51 Scheduled_In E SOUTH E17 S27E JIA5 403 CLT CRJ9 21/23:55 Scheduled_In E_SOUTH E17 S9W JIA5 403 CRJ9 E21/21:34 Scheduled_Out E_SOUTH E15 CHA 52.4 Ĩ. ► 105408 IND CRIS 21/21:03 F21/19:48 Scheduled Out F FAST F18 \$24

Timeline

Flights Table

Timeline

RWY 18R/36L



Ramp Traffic Console (RTC)







Ramp Manager Traffic Console (RMTC) Setting Metering Modes







ZDC TBFM TGUI and PGUI









What to expect during testing?





- Time Based Metering
 - Amount of delay propagated to surface (AMA and Ramp area) vs. Gate
 - Different levels of gate hold
 - Earliest Off-block Times (EOBTs)
 - Perfect EOBTs for all carriers
 - Phase1 EOBT: Higher accuracy for AAL and regionals, and current day accuracy for non AAL Flights
- Runway Configurations
 - North flow
 - South flow
- Various Data Exchange Exercised
 - APREQs, EDCTs, MITs
 - Runway Utilization (arrivals and departures)
 - Runway Assignments
 - Gate Conflicts

Charlotte Douglas International Airport (CLT)





South Dual Converging Operations







North Operations (Triple)









Scenarios – Bank Analysis Actual On and OUT









- South Dual Converging Operation (92 arr & 80 dep per hour)
- Triple North Operation (75 arr & 65 dep per hour)
- No wind, clear visibility, but IFR rules in effect (can't fly visual in this sim)
- No GA, No Cargo flights
- Duration 65 70 min
- Banks: matching heavy banks (2nd and 6th)
 - 47-48 arrivals on RWY 36L/18R
 - 31-30 arrivals on RWY 36R/23
 - 36-25 departures on RWY 36C/18C
 - 33-38 departures on RWY 36R/18L
- TMIs:
 - ZDC requesting CLT APREQ departures to DCA, EWR, LGA, JFK and PHL
 - ZDC requesting CLT 15 MIT on BARMY and KILNS excluding APREQs
 - EDCTs



Demand Profile at CLT Gate OUT / IN Events





- CLT has highly dynamic departure and arrival demand
- Other airports in NAS have similarly dynamic demand profiles
- Need for metering at such airports can be intermittent and must be informed by both departure and *arrival* demand predictions





- En route traffic to DC metro and NY metro.
- Departures from CLT, GSO, RDU, RIC, DCA, IAD, BWI
- TMIs
 - ZDC requesting CLT APREQ departures to DCA, EWR, LGA, JFK and PHL
 - ZDC requesting CLT 15 MIT on BARMY and KILNS excluding APREQs
- BWI, CLT DCA, IAD, RIC, RDU will send electronic APREQ requests





Airspace



ZDC Airspace and Meter Points













Arrival Airspace (South Flow)









Simulation Artifacts



- Approaches in burgundy
- Arrivals in blue
- Departures in red
- MACS ATG handoff boundary

7nm away from the RWY threshold

2nm away from the RWY threshold



Operational constraints: Arrivals will be established on the approach before transferring to Tower (ATG). Departures will be on a RWY heading until they are transferred to TRACON (MACS). We are not using divergent heading).





Participants/Positions





- 2 Local and 2 Ground Controllers
- 1 Tower TMC
- 2 AAL Ramp Controllers
- 2 Retired Controllers
- 1 Ramp Manager
- 1 Clearance Delivery confederate
- 1 TRACON TMC
- 1 ZDC TMC
- 1 ZTL TMC as observer
- 2 Ghost En route Controllers
- 1 ZDC other Towers- confederate
- 4 Arrival controllers
- 2 Departure controllers
- 18 pseudo pilots

Note: Positions in the Ramp, ATC Tower and TRACON will rotate.





- Manage traffic as usual
- Provide an accurate assessment of workload during the simulation runs
- Fill in Post Run surveys online
- Fill in Post Study surveys
- Will rotate positions in the Ramp, ATC Tower and TRACON





Roles and Responsibilities





- ATC-T TMC
 - Enter the APREQs and MITs into STBO Client
 - Evaluate nominal and reschedule process for APREQ flights
 - Evaluate the RWY Off-times predictions and APREQ compliance
 - Evaluate that the information presented on STBO Client is adequate to handle ramp operations
 - Evaluate the data exchange items for procedures and information such as runway utilization, metering modes, and others
 - Evaluate how the gate holds are impacting operations in the AMA
- ATC-T GC/LC
 - Manage traffic as usual
 - Ensure that flights with TMIs meet their scheduled wheels-up time with the compliance windows (-2/+1 min for APREQ and +5/-5 min for EDCT)
 - Evaluate how difficult or easy it was to comply to the wheels-up times
 - Evaluate how the gate holds are impacting operations in the AMA





- Ramp Controllers / Ramp Manager
 - Adhere to the metering advisories as much as possible
 - Evaluate the advisories on TMI and non-TMI flights
 - Ensure flights with APREQ have a flow time before they are sent to the spot
 - Evaluate the level of gate holds and how they impact ramp operations
 - Evaluate that information presented on RTC/RMTC is adequate
 - Evaluate the data exchange items for procedures and information such as runway utilization, metering modes, and more
 - Ramp Manager assess and point out times when metering should be turned on or off





- CLT TRACON
 - Controllers to provide vectors to arrivals and departures, as well as required minimal separation as usual
 - Pre-arranged coordination between departures and arrivals.
 - Departures controllers are responsible to separate departures from arrivals
 - Arrival controllers must point out arrivals to departures. This is indicated in the SOP
 - Two final sectors
 - Final West controls East and Center RWY
 - Final East controls the East and crossing RWY
 - Feeder sectors enter scratchpad entries for RWY assignments.
 - East arrivals are assigned to East RWY
 - West arrivals are assigned to West RWY

South	North
18L =L 18C = C 23 = X	36L = NL 36C = NC 36R = NR





- TRACON TMC
 - Use both TBFM arrival metering TGUI and STBO as information input on traffic flow
 - Determine the use of Center RWY (18C/36C)
 - TRACON TMC decides which arrivals go to the Center RWY.
 - Determine in-trail spacing for En-route feed to the TRACON airspace, as needed
 - MIT and APREQ from CLT
 - STBO displays which departures have an APREQ and which have an MIT
 - Departure controllers will also know which destination the flights are flying via the datablock





- TRACON TMC
 - Evaluate STBO demand prediction for RWY utilization
 - Evaluate RWY Off-times and APREQ compliance
- Time permitting
 - Evaluate that information presented on STBO Client is adequate to handle ramp operations
 - Evaluate the data exchange items for procedures and information such as runway utilization, metering modes, and more
 - Evaluate how the gate holds are impacting operations in the AMA





- ZDC Center TMC
 - Schedule all departures to ZDC's Meter Points on the phone or electronically
 - TBFM EDC is used to schedule <u>all</u> stream classes going to NY and DC metro, including EWR and PHL (will be handled by CFR)
 - Center TMC will have STBO for situational awareness about CLT
 - Evaluate the APREQ nominal and reschedule process with IDAC
 - Evaluate usefulness of information presented on STBO Client for TMC operations





- Data source:
 - SDSS and ATG data logs
 - Audio and video recording of each station
 - Workload (prompts every 5 min during the scenario)
 - Post-run and Post-Simulation surveys
- Metrics (Not exhaustive list):
 - Both real time and post analysis
 - Queue size, Gate holds, Taxi Times, compliance to TMI, Throughput, Efficiency and predictability metrics
 - Subjective assessments of: Workload, Situation Awareness, usability, acceptability



Schedule



Time			
	Run No.	Condition/Description	Scenario
0830	Pm 100	Wolcomo/Briofing	
0830		Brook	
0920		Dieak	
0930	Rm 100 FFC AOL	Classroom training	
1020	Rm 100	Data Exchange & Integration	
1050		Break	
1100	TR1	Training Run – No metering/ Time Based Metering	
1200		Lunch	
1300	Run 1	Time Based Metering	North flow
1405		Questionnaire	
1410		Break	
	Run 2	Time Based Metering	
1425			South flow
1530		Questionnaire	
1535		Break	
1540		Debrief	
1630		End	



Back up slides





Functional Architecture





ATC- Tower Sectors





CLT Ramp Sectors





Accessing Surveys



1. In the AOL: On the lower menu bar (extreme bottom left corner) on your screen, open Internet Explorer with a double click on the icon. It will open on the survey page. In the FFC: The correct page will be brought up for you automatically at the right time.

AOL Surveys	
The following surveys are available:	
CLT Tower ATD2 ISAS HITL – Feb 2017	2. Double click on the
Please contact Vick Kelkar (vaibhav.kelkar@nasa.gov) for further assistance.	green survey title in the middle of the survey
English 🛟	page
powered by ČLimeSurvey The Online Survey Tool - Free & Open Source	

CLT Tower ATD2 ISAS HITL – March 2017

Please answer as many of the questions below as you can. Don't think about any of them for too long, we'd like your first impressions.

There are 61 questions in this survey.

Next >>

Exit and clear survey

3. Click "next>>" on the bottom right of the start page & the first question page will open.

Answer questions by clicking in the buttons or boxes, or place your cursor in the white boxes and use the regular keyboard to type a written answer.

You may need to scroll down to see all the questions & will need to click "next>>" to move from one page to the next & "submit" at the end to save your answers.



FFC Workload Assessment Keypad (WAK) (to indicate your level of mental workload)









lot-Config: view(Disabled) ATC-Sector: ZKC_90(E WINDOWS ATC / DST TOOLS	inabled) ADRS: reunion.arc.nasa.gov (CONNECTED) 232 17:51:15 1	2 3 4 5		OAC	O MULTI 🛛 🖲 DSR	Ö STARS
T DYNAMIC BOUNDA				KEYS	SUP -	
398 NEXT UPDATE 00:02:2 COUNT DOWN OUTC	Workload	Rating Se	cale Off	ST TIM	HS VS P V-SEP	
			ACA279 NWA149	11 5 11 5	2 Ø	



WINDOWS	ATC/DST TOOLS	17:57:48		OAIC	OMULTI	• DSR O STAF
	T DYNAMIC BOUNDARY -	T RNG LIST COL R -	T 110 CNFL	KEY	's sup	
	COUNT DOWN OUTC		2 12 LBL UNT	TIME H-S	EP V-SEP	vs
M _{SE}	BOUNDARY PRE	Workload Rating S	cale On 🛛 🛓	6 Ø	Ø	3
-		\sim				

Workload Scale will randomly prompt you for your current workload level

When keypad lights up press a key to indicate your workload at that time Trackball PICK or hit F1-F6 key on keyboard for appropriate rating number Rating Scale will turn dark until next prompt







After a key is pressed, feedback is given until the end of the 20 sec time At the end of 20sec whether or not a key is pressed, the screen reverts back to its quiet state



AT Workload Rating Scale – on tablet or station



Workload: All the physical and mental effort you must exert to do your job, including maintaining the "picture," planning, coordinating, decision making, communicating, and whatever else is required to maintain safe and expeditious traffic flow.



- Time on Hands 1 - very low workload - very little traffic - hardly anything to do – time to talk
 - 2 low workload light traffic time to give best routes time to talk

In the Groove

Overloaded

- 3 moderate workload in the groove firm grasp of the flick proactively looking for conflicts still provide services
- 4 high workload mostly in the groove still have the flick proactive most of the time but focusing more on the separation management over providing services or other tasks with less priority
- 5 high workload having trouble keeping the flick working reactively instead of proactively mode - falling behind in routine tasks – cannot take on any additional tasks

Remember that your rating is intended to reflect your workload at the moment you are prompted, not your general appraisal of workload for the whole scenario

Workload is a very important measure for data analysis please try to respond to every prompt