Small Satellite Conference 2017

Lunar and Lagrangian Point L1/L2 CubeSat Communication and Navigation Considerations

Scott Schaire, Yen F Wong, Serhat Altunc, George Bussey, Marta Shelton, Dave Folta, Cheryl Gramling Goddard Space Flight Center

> Peter Celeste, Mike Anderson, Trish Perrotto Booz Allen Hamilton

> > Ben Malphrus, Jeff Kruth Morehead State University

Presenter Scott H Schaire Scott.H.Schaire@NASA.gov

EM-1 CubeSats & Lunar IceCube Mission Overview

- NASA's EM-1 will be the maiden voyage of the Space Launch System (SLS), ushering NASA into a new era of solar system exploration
 - SLS, supporting human exploration beyond Low Earth Orbit (LEO), will also serve as a platform to launch small satellites flying onboard as secondary payloads
 - EM-1 will launch thirteen CubeSats that will perform science investigations that address NASA Strategic Knowledge Gaps
 - CubeSat missions will also demonstrate a variety of enabling technologies, including communication and ranging
- Lunar IceCube will be one of the CubeSats to be launched from EM-1
 - Lunar IceCube is a partnership between Morehead State University (MSU), GSFC, JPL, the Busek Company, and Vermont Technical College
 - Lunar IceCube will prospect for water in solid, liquid, and vapor forms and other lunar volatiles from a ~100 km lunar orbit
 - Lunar IceCube will be deployed by the SLS at Bus Stop One, at a distance of approximately 25,000km



Secondary CubeSat payloads on the adapter between the SLS upper stage and the Orion spacecraft



Lunar CubeSat Spacecraft

Lunar IceCube: Communication & Navigation Needs

- Lunar IceCube navigation and communication poses challenges:
 - Precise orbit determination after deployment is required for lunar flyby maneuver planning
 - Establishing communication links given limited onboard power

To meet these challenges a large aperture on the ground is required

- DSN will be the primary network
- MSU will manage ground operations for all phases and utilize their 21-m antenna to provide significant gain and link margin
- The NEN, as a significant addition, can provide comprehensive tracking and telemetry services from facilities around the globe

- Lunar IceCube navigation will be performed by the GSFC Flight Dynamics Facility (FDF)
 - GSFC will provide navigation and maneuver planning
 - FDF will provide planning, ephemeris generation, tracking evaluation, operational products, and data archiving

Required tracking data and related accuracies vary over the transfer trajectory

- Frequency of tracking will vary from every opportunity to ever few days depending on the phase of the mission
- Navigation accuracies of <100 m in position and <0.1 cm/s in velocity are required

Lunar IceCube: Radiation Requirements

- GSFC radiation branch performed an analysis for Lunar IceCube
 - The radiation environment is harsh from a Galactic (Heavy Ion) Radiation perspective
 - Trips through the Van Allen belts early in the mission will expose Lunar IceCube to Total Ionizing Dose (TID) Radiation
- Lunar Ice Cube Radiation Tolerance Requirements:
 - Direct Radiative Effect (DRE) Electrical, Electronic, and Electromechanical (EEE) Parts shall meet Linear Energy Transfer Threshold (LETth) of > 37 MeV-cm2/mg for soft errors from single events (SEU, Single Event Transients, etc.)
 - DRE EEE Parts shall meet LETth of > 75 MeV-cm2/mg for potential destructive events (SEL, SEB, SEGR, etc.)
 - DRE EEE Parts shall meet 5 krads (Si) Total Ionizing Dose (TID) assuming 50 mils Al shielding



Lunar IceCube Dose – Depth at 95% Confidence

NASA Near Earth Network Project Overview

Near Earth Network (NEN) is composed of stations distributed throughout the world. The NEN supports orbits in the Near Earth region from Earth to 2 million kilometers



Sample CubeSat Radios For Lunar and L1/L2 Missions

Freq.	Vendor / Name	Size (cm)	Mass (g)	Flight Heritage	Max Data Rate	NASA Network Compatibility*	
S-Band	Innoflight / SCR-100	8.2x8.2x3.2	300	Sense NanoSat	4.5 Mbps Tx	NEN, SN, DSN	
	Tethers Unlimited / SWIFT- SLX	10x10x3.5	380	None	15 Mbps Tx	NEN, SN, DSN	
	Clyde Space / S-Band TX (STX)	9.6x9.0x1.6	< 80	UKube-1	2 Mbps Tx	Partially NEN	
	Microhard / MHX-2420	8.9x5.3x1.8	75	RAX	230 kbps Tx 115 kbps Rx	Partially NEN	
	Quasonix / nano TX	3.3x3.3x3.3	<200	CPOD	46 Mbps Tx	NEN	
	LASP & GSFC / X-band Radio	9.8x9x2	500	None	12.5 Mbps Tx 50 kbps Rx	NEN	
B	Syrlinks / X-band Transmitter	9x9.6x2.4	225	None	5 Mbps Tx	NEN	
X-Banc	Marshall / X-band Tx	10.8x10.8x7.6	<1000	FASTSat2	150 Mbps Tx 50 kbps Rx	NEN	
	Tethers Unlimited / SWIFT- XTS	8.6x4.5 (0.375U)	500	None	300 Mbps Tx	NEN, SN, DSN	
	JPL / Iris Transponder	0.4U	400	INSPIRE	256 kbps Tx 8 kbps Rx	DSN, Partially NEN	
Ka-Band	Canopus Systems / Ames Ka-band Tx	18x10x8.5	820	None	125 Mbps Tx	NEN, SN, DSN	
	Tethers Unlimited / SWIFT-KTX	8.6x4.5 (0.375U)	500	None	300 Mbps Tx	NEN, SN, DSN	





Innoflight SCR-100



nanoTX™

Quasonix S- Band Transmitter



Tethers Unlimited SWIFT-SLX

Sample CubeSat Antennas For Lunar and L1/L2 Missions

Antenna Vendor	Antenna Type	Band	Antenna Gain (dBi)	Dimensions	Mass (g)
Antenna Development Corporation	Low-Gain Patch Antenna (LGA)	S	2	(4 x 4x0.25)"	115
Haigh Farr S-band Patch	Patch	S	2	(94x76x4) mm	62
University of Southern California's Information Sciences Institute Space Engineering Research Center (SERC)	Deployable High Gain Antenna	S/X	>24	50 cm	760
BDS Phantom Works	Deployable High Gain Antenna	S	18	50 cm	1000
Antenna Development Corporation	Patch	х	9	(1.85x1.85x0.55)"	300
BDS Phantom Works Deployable High Gain X- band Antenna	Deployable High Gain Antenna	х	25	50 cm	1000
Canopus System Horn	Horn	Ka	25	18 cm	820



University of Southern California's Information Sciences Institute Space Engineering Research Center (SERC)



Ant Dev. Corp: Medium Gain Xband Patch Array Antenna

Lunar IceCube Communication System / Iris Transponder



- 4 custom design X-band patch antennas
- Iris transponder without a diplexer

Patch Antenna performance characteristics:

- Receive Band: 7.145-7.190 GHz
- Transmit Band: 8.400-8.450 GHZ
- Gain: 6 dBi

Iris transponder features:

- Modular design allows user to select layers necessary to meet needs, be it S-band, X-band, Tx, Rx
- The transponder is radiation tolerant up to 15 Krads and its memory modules are all radiation tolerant

- Iris transponder features continued:
 - Switchable discrete data rates
 - Telemetry rates ranging from 62.5 bps up to 256 kbps; Lunar IceCube is exploring telemetry data rates of 16, 32, 64, 128 kbps
 - Command rates ranging from 62.5 bps up to 8 kbps, in powers of two
 - Lunar IceCube plans to use the power efficient Turbo 1/6 code



Patch antennas and Iris transponder

Lunar IceCube NASA NEN Ground Station Coverage

- DSN/MSU will provide prime support to Lunar IceCube during all phases, but the NEN would be able to provide additional comprehensive support
 - MSU has visibility for the 8-hour event following deployment, but not for the next three cruise events
 - DSN/MSU will have lengthy periods where only one site has coverage
- As a significant addition, the NEN could ensure a minimum of two sites in view at all times and provide supplemental and backup support

- Based on current NEN locations, four X-band capable equatorial sites would be required to provide full global coverage to Lunar lceCube based on its trajectory
 - The commercial sites SSC Hawaii and Australia are the only NEN stations currently capable of X-band uplink and would be ideal due to their larger antennas (13-m) and equatorial location
 - The NASA owned Wallops site has an 11-m X-band system and is located to complement the coverage provided by the Hawaii and Australia sites
 - The addition of the commercial site in Hartebeesthoek, South Africa, which has a 10-m system, would ensure full global coverage
 - Note: Sites would require modification for Lunar IceCube compatibility

Achievable Ranging and Data Rates

- Lunar IceCube had considered the use of either sequential tone ranging or Pseudo-Noise (PN) ranging, but has decided to use sequential ranging
- Lunar IceCube implementation of sequential ranging will use two modes for uplink and one mode for downlink
 - Ranging data channel having a major tone for uplink
 - Command data channel modulating a subcarrier
 - A single tone ranging channel directly phase modulating the RF carrier for downlink

- A NEN link analysis was performed to evaluate NEN Xband support for Lunar IceCube science data downlink
 - Achievable data rate will vary depending on the distance to the Earth during different phases

NEN Achievable Data Rates at a Range of 400,000 km

Station	X-band G/T (dB/K)*	Achievable Rate
Wallops	35.4	16 kbps
Australia	37.7	32 kbps
Hawaii	37.7	32 kbps
Hartebeesthoek	30.5	8 kbps

* Clear sky and 10° elevation angle

Note: The achievable data rate is 64 kbps at a 400,000 km range for the MSU 21-m antenna

NEN Coverage During Lunar IceCube Deployment Phase - Video





Wallops Coverage (128 kbps)

7 oct 2018 15:39:56.961

E e e

49 • • • • • •

NEN Coverage During Lunar IceCube Deployment Phase



Note: Coverage times are based on line of site coverage and do not guarantee commitment of asset(s) for service. All NEN coverage times assume a 10 degree minimum elevation for RX, Tx, and Trk. DSN/MSU assumes a 6 degree minimum elevation for Rx and a 10 degree minimum elevation for Tx and Trk.

Morehead State Ground Station Modifications and Further Enhancements

- The MSU 21-m antenna system is being upgraded under the support of NASA's Advanced Exploration Services (AES) to be integrated into the DSN as an auxiliary station to support SmallSat missions
 - This MSU upgrade project serves as a test case to define a path for integration of other ground stations to support SmallSat missions
- > The ultimate deliverables of the two-year effort, to be completed in 2018, will be:
 - 1. Design that includes hardware and software upgrades necessary to provide deep space telemetry, tracking, and command functions compliant with CCSDS SLE specifications
 - 2. Demonstration of the MSU 21-m antenna as a DSN-compatible operational node
 - 3. Demonstration of ground system capabilities in demodulating and decoding CubeSat telemetry data, accepting and transmitting commands to CubeSats, and providing Doppler and ranging data for CubeSat deep space navigation strategies and processes
 - 4. Compatibility with uplink and downlink processes implemented in NASA's Advanced Multi-Mission Operations System (AMMOS)



Potential NEN Enhancements and Benefits

- NEN commercial stations at Hawaii and Dongara, Australia have X-band uplink capability that could support EM-1 missions with some minor modifications to these stations
 - Addition of a tunable up converter and IF distribution system between the Cortex modem and the up converter
- NEN is considering adding X-band uplink capability to other NASA NEN stations
 - Addition of X-band uplink will help with frequency crowding in S-band
- NEN Cortex modem enhancements with 1/6 Turbo code and sequential ranging/PN ranging for compatibility with EM-1 CubeSats missions carrying the Iris transponder is potentially under consideration
- NEN ground system enhancements to achieve compatibility with missions carrying an Iris transponder would enable benefits in the form of coverage and larger beamwidth

NEN Benefits For EM-1 CubeSat Missions: Coverage

- NEN NASA-owned and commercial ground systems are positioned around the globe and are able to provide significant to full coverage to CubeSats in lunar orbit or beyond
 - Four select NEN stations could provide ~99.8% coverage at 25,000 km, the approximate distance where Lunar IceCube will separate
 - Full coverage, 100%, could be achievable at ~35,000 km and beyond, assuming four stations

NEN <u>Four</u> Station Architecture Providing <u>99.8%</u> Coverage at 25,000 km



NEN <u>Four</u> Station Architecture Providing <u>100%</u> Coverage at 35,000 km and beyond



NEN Benefits For EM-1 CubeSat Missions: Beamwidth

• The NEN's use of smaller apertures provides a larger beamwidth, compared to larger apertures, which could benefit Lunar CubeSats with uncertain ephemeris data

WG1 11m

• SSC Hawaii and Australia 13m would cover over 2.5x the area of a DSN 34m

MSU 21m

- WG1 11m would cover 3.10x the area of a DSN 34m
- Assumptions:
 - Frequency: 8450 MHz
 - The Moon's angular diameter is 0.5 degrees
- 3 dB Beamwidth for Varying Antenna Diameter*
 - 10m = 0.250 degrees (half of Moon angular diameter)
 - 11m = 0.226 degrees
 - 13m = 0.191 degrees
 - 21m = 0.118 degrees
 - 34m = 0.073 degrees



* Not all antenna diameters depicted in graphic

DSN 34m

NEN Lunar And L1/L2 Support Without Any Enhancement

- NEN NASA owned and commercial stations support S, X and Ka frequency bands
- The station Cortex modem supports a variety of modulation and coding schemes, including power and bandwidth efficient low-density paritycheck (LDPC) code, but requires a license upgrade for Turbo coding
- A majority of the EM-1 CubeSats will use the Iris transponder with Turbo coding
- COTS S- and X-band Software Designed Radio (SDR) radios are available for use by CubeSats in lunar and L1/L2 orbit
- NEN is capable, without any enhancements, of supporting CubeSats using COTS radios in lunar and L1/L2 orbit and current Cortex modems
- Tradeoffs can be accomplished between CubeSat transmitting power and signal design, for instance Turbo vs LDPC coding, to achieve the desired downlink data rate
- NEN station S-band uplink can be used today to support CubeSat commanding

NASA NEN Initiatives For Better Support Of CubeSat Community

- In addition to enhancement of ground stations, the NEN is focusing multiple initiatives to meet future needs of the CubeSat community
 - NASA missions can obtain services on NASA-owned antennas for free
 - NEN can broker commercial services for NASA missions
 - NEN is investigating partnering with other agencies/universities to integrate new antennas into the NEN that may offer lower costs and greater coverage
- NASA missions are required to pay for mission planning, integration, and testing (MPI&T), including compatibility and end-toend testing
 - NEN and GSFC Network Integration Management Office (NIMO) completed a Lean Six Sigma Project that explored ways to reduce MPI&T costs
 - The project identified savings that could total 60%
- > NEN is also investigating ways to streamline NEN scheduling
 - As the number of missions increase, so does complexity
 - NEN is investigating ways to handle the increased load without increasing scheduling staff

Conclusion

- The NEN is ready today to support lunar and L1/L2 CubeSats
- Potential enhancements to Morehead State University and NEN ground stations will increase the science return from CubeSats and traditional non-CubeSat missions
- A relatively small investment in NEN ground station equipment could payoff over tens or hundreds of future missions
- Advancements in flight hardware will also increase data rates and science return
- The challenges for lunar and L1/L2 missions for communication and navigation are much greater than for LEO missions, but are not insurmountable
- NEN ground systems could benefit lunar and L1/L2 CubeSat missions, including the EM-1 CubeSat missions



NASA

EM-1 Secondary Payloads



Lunar Ice Cube Mission Design



Lunar IceCube Trajectory



NEN Coverage During Lunar IceCube Deployment Phase #3

Event Start: 9 Oct 2018 11:56:19 Event Stop: 9 Oct 2018 21:56:19



Site	Capability	Coverage Times						
Hawaii	Rx/Tx/Tracking							1:16
Australia	Rx/Tx/Tracking	1:06						
Wallops	Rx					6:00		
Hart.	Rx		6:57					
NEN Sites	-	Dual	Single		Dual	5	Single	Dual
DSN/MSU (6º) Sites	Rx		Single		Dual	Triple		Dual
DSN/MSU (10º) Sites	Rx/Tx/Tracking		Single		Dual	Triple	Triple Dual	

Note: Coverage times are based on line of site coverage and do not guarantee commitment of asset(s) for service. All NEN coverage times assume a 10 degree minimum elevation for RX, Tx, and Trk. DSN/MSU assumes a 6 degree minimum elevation for RX and a 10 degree minimum elevation for Tx and Trk.

NEN Coverage During Lunar IceCube Deployment Phase #4

Event Start: 11 Oct 2018 03:07:24 Australia AOS Event Stop: 11 Oct 2018 13:07:24 Hawaii AOS Hart. AOS Hawaii LOS NEN Rx/Tx/Trk 10:00 Site Max Range Achievable Rate Hawaii 378,162 km 32 kbps Australia 385,862 km 32 kbps Wallops Hart. 381.111 km 4 kbps Site **Coverage Times** Capability Hawaii Rx/Tx/Tracking 3:18 Rx/Tx/Tracking Australia Wallops Rx Hart. Rx 5:24 NEN Sites Dual Single Dual DSN/MSU (6º) Sites Rx D Single D Single Single Single DSN/MSU (10°) Sites Rx/Tx/Tracking

Note: Coverage times are based on line of site coverage and do not guarantee commitment of asset(s) for service. All NEN coverage times assume a 10 degree minimum elevation for RX, Tx, and Trk. DSN/MSU assumes a 6 degree minimum elevation for Rx and a 10 degree minimum elevation for Tx and Trk.

NEN Coverage During Lunar IceCube Outbound Lunar Flyby



Note: Coverage times are based on line of site coverage and do not guarantee commitment of asset(s) for service. All NEN coverage times assume a 10 degree minimum elevation for RX, Tx, and Trk. DSN/MSU assumes a 6 degree minimum elevation for Rx and a 10 degree minimum elevation for Tx and Trk.

NEN Coverage During Lunar IceCube Science Phase



NEN Coverage at Lunar Distances



NEN Three Station Architecture Providing 89% Lunar Coverage

NEN Four Station Architecture Providing 100% Lunar Coverage



Morehead State 21-m Station Performance Measure Pre- and Post-Upgrade Targets

Performance Measure	Current Values	Post-Upgraded Targets			
X-Band Frequency Range	7.0 – 7.8 GHz	7.0 – 8.5 GHz			
LNA Temperature	70 K	< 20 K			
System Temperature Tsys	215 K	<100 K			
Antenna Gain	62.0 dBi (@ 7.7 GHz)	62.7 dBi (@8.4 GHz)			
System Noise Spectral Density	-175 dBm/Hz	<-178 dBm/Hz			
G/T at 5° Elevation	37.5 dBi/K	40.4 dBi/K			
Time Standard	GPS (40-ns)	MASER 3.3 E-14 over 100 secondspse)			
SLE Compliant	No	Yes			
CCSDS Capable	No	Yes			