

Colleen A. Wilson-Hodge^a, P.S. Ray^b, K. Gendreau^c, Z. Arzoumanian^c, D. Chakrabarty^d, R. Remillard^d, M. Feroci^e, T. Maccarone^f, K. Wood^g, and P. Jenke^h for the STROBE-X team

^aNASA/MSFC, ^bNRL, ^cNASA/GSFC, ^dMIT, ^eINAF-IAPS/INFN, ^fTexas Tech, ^gPraxis/NRL, ^hUAH

ABSTRACT: We describe a probe-class mission concept that provides an unprecedented view of the X-ray sky, performing timing and 0.2-30 keV spectroscopy over timescales from microseconds to years. The Spectroscopic Time-Resolving Observatory for Broadband Energy X-rays (STROBE-X) comprises three primary instruments. The first uses an array of lightweight optics (3-m focal length) that concentrate incident photons onto solid state detectors with CCD-level (85-130 eV) energy resolution, 100 ns time resolution, and low background rates to cover the 0.2-12 keV band. This technology is scaled up from NICER, with enhanced optics to take advantage of the longer focal length of STROBE-X. The second uses large-area collimated silicon drift detectors, developed for ESA's LOFT, to cover the 2-30 keV band. These two instruments each provide an order of magnitude improvement in effective area compared with its predecessor (NICER and RXTE, respectively). Finally, a sensitive sky monitor triggers pointed observations, provides high duty cycle, high time resolution, high spectral resolution monitoring of the X-ray sky with ~20 times the sensitivity of the RXTE ASM, and enables multi-wavelength and multi-messenger studies on a continuous, rather than scanning basis.

For the first time, the broad coverage provides simultaneous study of thermal components, non-thermal components, iron lines, and reflection features from a single platform for accreting black holes at all scales. The enormous collecting area allows detailed studies of the dense matter equation of state using both thermal emission from rotation-powered pulsars and harder emission from X-ray burst oscillations. The combination of the wide-field monitor and the sensitive pointed instruments enables observations of potential electromagnetic counterparts to LIGO and neutrino events. Additional extragalactic science, such as high quality spectroscopy of clusters of galaxies and unprecedented timing investigations of active galactic nuclei, is also obtained.

Mission Overview

The Spectroscopic Time-Resolved Observatory for Broadband X-rays




Figure 1: (Left) Notional deployed configuration of the STROBE-X spacecraft. (Right) Effective area for the current baseline configuration of 90 Large Area Detector (LAD) modules and 128 X-ray Concentrator (XRC) units. This configuration has ~10m² of effective area in the critical iron line region.

INSTRUMENTS: X-ray Concentrator Array (XRCA)

- Low background, low cost, light weight single bounce foil concentrators developed for NICER. Much simpler and cheaper than traditional X-ray optics
- Focal length 3 m with 2' focal spots for enhanced throughput >2.5 keV (relative to NICER). Set of 107 nested foil shells with diameters between 3 and 28 cm
- Energy range: 0.2-12 keV
- Energy resolution: 85-175 eV FWHM
- Effective area @ 1.5 keV: 3.4 m² (128 XRC units)
- Time resolution: 100ns




Figure 2: (Left) XACT (larger) and NICER (smaller) X-ray concentrator optics. STROBE-X XRCs will have approximately the diameter and focal length of the XACT optic. (Right) Amptek SDD detectors with and without the TO-8 cap. The thin silicon-nitride entrance window is built into the cap. NICER XRCs and detectors are now flight qualified.

INSTRUMENTS: Wide Field Monitor (WFM)

- Coded Mask imager similar to that employed on several previous missions. Based on LOFT m-class design.
- Energy range: 2-50 keV
- Energy resolution: 300 eV FWHM @6 keV, using SDDs similar to LAD
- Effective area/ camera pair: 364 cm²
- Sky coverage: 1/3 of the sky (instantaneous)
- Position accuracy: 1 arcmin




Figure 4: (Left) Detailed view of a single WFM camera. (Center) Configuration of the WFM on LOFT. (Right) Combined FOV of the WFM on the sky for LOFT, for a typical galactic center pointing.

Mission Study Parameters

- STROBE-X is part of a NASA funded 18-month study of Probe-class Missions for the 2020 decadal survey. Mission and Instrument studies will be performed at GSFC
- Orbit: LEO, 500-600 km altitude, as low inclination as possible
- Launcher: Falcon 9 FT
- Cost: <\$1B including launch

Key Science Goals

- Probe stationary spacetimes near black holes to explore the effects of strong field general relativity and measure the masses and spins of BHs
- Map the geometry of BH accretion flows, using X-ray reverberation, across all mass scales from stellar mass BHs in our galaxy to supermassive BH in AGN
- Fully determine the ultradense matter equation of state by measuring the neutron star mass-radius relation using >20 pulsars over an extended mass range.
- Continually survey the dynamic X-ray sky with large duty cycle and high spectral and time resolution to enable multi-wavelength and multi-messenger studies through cross-correlation with high cadence surveys at other wavelengths and in gravitational waves and neutrinos.

INSTRUMENTS: Large Area Detector (LAD)

- Lightweight MCP collimators enable an order of magnitude increase in area over RXTE. Developed for the European LOFT M-class mission
- Energy range: 2-30 keV
- Energy resolution: 200-240 eV FWHM (CCD quality)
- Effective area @10 keV ~7.6 m² (90 LAD modules)
- Time resolution: 10 μs




Figure 3: (Left) The assembled LAD module as well as the exploded view of its components, (Center) Lead-glass micro-capillary plate (MCP) collimator tile in its transport frame. (Right) A large area SDD developed for the European LOFT mission.