On the Development of the Marshall Grazing Incidence X-ray Spectrograph (MaGIXS) Mirrors

SPIE Astronomical Telescopes & Instrumentation 2018

Patrick Champey (NASA MSFC), Amy Winebarger (NASA MSFC), Ken Kobayashi (NASA MSFC), Sabrina Savage (NASA MSFC), Brian Ramsey (NASA MSFC), Jeff Kolodziejczak (NASA MSFC), Charlie Griffith (NASA MSFC), Tom Kester (NASA MSFC), Tomasz Lis (NASA MSFC/UAH), Mark Young (Jacobs ESSSA), Peter Cheimets (Smithsonian Astrophysical Observatory), Edward Hertz (Smithsonian Astrophysical Observatory), Leon Golub (Smithsonian Astrophysical Observatory)

Abstract

The Marshall Grazing Incidence X-ray Spectrograph (MaGIXS) is a sounding rocket experiment that will obtain spatially resolved soft X-ray spectra of the solar corona from 0.5 – 2 keV. The optical system comprises a Wolter-I telescope mirror, a slit spectrograph, and a CCD camera. The spectrograph has a finite conjugate paraboloid pair, which re-images the slit, and a varied line-space planar reflection grating. Both the Wolter-I mirror and paraboloid pair are being fabricated at the NASA Marshall Space Flight Center (MSFC), using nickel replication. The MaGIXS mirror mandrels have been diamond turned, polished, and have yielded a set of engineering mirrors. Unlike other grazing incidence instruments, such as FOXSI, ART-XC, and IXPE, the MaGIXS prescriptions have large departure from a cone. This property exacerbates challenges with conventional lap polishing techniques and interferometric metrology. Here we discuss the progression of the optical surfaces of the mandrels through lap polishing, X-ray data from the replicated shells obtained in the MSFC Stray Light Facility (SLF), and our transition to using the *ZEEKO* computer numerical controlled (CNC) polisher for figure correction.