

MATURATION OF DYNAMIC POWER CONVERTORS FOR RADIOISOTOPE POWER SYSTEMS

Scott Wilson, Sal Oriti


NASA Glenn Research Center

February 26, 2019

Nuclear and Emerging Technologies for Space (NETS) 2019

Maturation of Dynamic Power Convertors


- **Radioisotope Power Systems Program** implemented maturation model developed for other projects
 1. Established a Surrogate Mission Team (SMT) to provide clear mission pull and requirements context
 2. Execute the evaluation model to mature available technologies to a TRL that is suitable for flight development
- **Surrogate Mission Team (SMT)** developed the multi-mission requirements used in the technology maturation contracts
- **Risk Informed Life Testing (RILT)** model
 - Was designed to quantify the likelihood that components and subassemblies will meet life goal with margin
 - Is being used to identify components and materials that need improved life data
- **Integrated Product Team (IPT)** formed by the project
 - To monitor contract progress to identify risk of insufficient margin
 - Identify potential testing or analysis to address risks



Requirements & Environments

Item	Description
Design Life	20 years continuous operation at full power
Power	Suitable for a 200 to 500 W_e generator
Efficiency	$\geq 24\%$ at $T_{\text{cold-end}} \geq 100\text{ }^\circ\text{C}$
Specific Power	20 W_e/kg (convertor only)
Degradation	Output power changes $< 0.5\%$ per year
Partial power	Maintains 20% conversion efficiency at 50% heat input
Atmosphere compatibility	Earth, Mars, Titan, vacuum, Argon
Hot-End Temp	$< 1000\text{ }^\circ\text{C}$
Cold-End Temp	Capable of 20 to $175\text{ }^\circ\text{C}$
Random Vibe	Launch spectrum for 1 min in each axis
Static Accel	20 g for 1 minute, 5 g for 5 days
Tolerance to Loss of Load	Survive a loss of electrical load for 10 seconds while at full power
EMI	$< 100\text{ nT}$ at 1 m while at full power
Radiation	No degradation after exposure to 300 krad
Autonomy	No external commands needed
Transmitted Forces	Enables generator with less than 10 N transmitted forces to spacecraft
Size	Enables generator for shipping cask

- Surrogate Mission Team (SMT) membership from major robotic mission centers and agency partners (RPS Program, DOE, GRC, JHU-APL, GSFC, JPL)
- SMT used target environments as basis for requirements development



DPC Contracts


- Formulation

Phase	Duration	Contractor Work	Government Work
1	6 months	Design	Review Risk Informed Life Testing analysis
Decision Gate 1 (move to gate 2?)			
2	18 months	Fabrication & Test	Review IV&V Plan, test facility preparation
Decision Gate 2 (recommend for flight development?)			
3	12 months	Support	IV&V testing and analysis Model validation
Potential Decision Gate n			

Dynamic Power Convertors for RPS Contracts


Flexure-Isotope Stirling Convertor (FISC)

- American Superconductor Corp (AMSC)
- Flexure bearing
- TDC derivative
- **Engineering challenges:**
 - Close clearance non-contacting seals, high-cycle fatigue, high-temp creep, high-temperature rejection
- **Status:** Production in progress, 50% through Phase 2




Turbo-Brayton Convertor (TBC)

- Creare
- Hydrodynamic gas bearing
- Cryocooler derivative
- **Engineering challenges:**
 - Close clearance non-contacting seals, high-performance heat exchangers, high-temp creep, high-temperature rejection
- **Status:** Production in progress, 50% through Phase 2





Sunpower Robust Stirling Convertor (SRSC)

- Hydrostatic gas bearing (Sunpower Inc.)
- ASC derivative
- **Engineering challenges:**
 - Close clearance non-contacting seals, high-cycle fatigue, high-temp creep, high-temperature rejection
- **Status:** Production in progress, 40% through Phase 2



Flexure Isotope Stirling Convertor (FISC)





Notional 250 W generator concept with 100% converter redundancy (4 required, 8 installed, 4 GPHS's)

Design Parameters

Hot-end Temp	650 °C
Cold-end Temp	20 to 175 °C
Efficiency	31% @ $T_{\text{COLD}}=100^{\circ}\text{C}$
Power Output	70 W_{ac}
Mass	3.3 kg ($>20W_e/\text{kg}$)

- Flexure-bearing based free-piston Stirling convertor
- Derivative of Technology Demonstration Convertor (TDC) from a 1990's SBIR and SRG-110 project
- **Design deltas relative to TDC to improve the following:**
 - Higher radial stiffness flexures, overstroke tolerance, hot-end temperature margin
 - Independently verifiable subassemblies
 - Higher efficiency alternator, higher cold-end temp capability

Turbo-Brayton Converter (TBC)





Notional 337 W generator concept with 100% convertor redundancy (1 required, 2 installed, 6 GPHS's)

Design Parameters

Turbine Inlet Temp (Hot-end)	730 °C
Compressor Inlet Temp (T _{cold})	20 to 175 °C
Efficiency	26% @ T _{COLD} =100°C
Power Output	337 W _{ac}
Mass	16.5 kg (>20W _e /kg)

- Closed Brayton continuous flow cycle with recuperation to achieve high efficiency
- Scaled-down from previous designs
- Leverages heritage from Creare's Hubble Space Telescope NICMOS cooler
- Two counter-rotating units permits redundancy, and nullifies angular momentum

Sunpower Robust Stirling Convertor (SRSC)



Notional 255 W generator concept with 50% convertor redundancy (4 required, 6 installed, 4 GPHS's)

Design Parameters

Hot-end Temp	640°C
Cold-end Temp	20 to 175 °C
Efficiency	30% @ $T_{\text{COLD}}=100^{\circ}\text{C}$
Power Output	64 W_{ac}
Mass	1.6 kg (> 20 W_e/kg)

- Gas-bearing based free-piston Stirling convertor
- Derivative of Advanced Stirling Convertor (ASC) from ASRG Project
- **Design deltas relative to ASC to improve the following:**
 - Higher radial gas bearing load capacity, higher cold-end temperature capability
 - Regenerator robustness improvements, debris tolerance
 - Overstroke tolerance, passive collision prevention system, bumpers, encapsulated magnets

Prototype Testing and Analysis

- **Phase I - Complete**

- Analysis completed to determine margin (against requirements and for hot thin-walled pressure barriers, joint analysis, temperature limits for various materials, etc.)

- **Phase II – In progress (~50% complete)**

- Beginning of phase for final analysis for any revised features, production readiness
- Prototype fabrication
- Test prior to delivery (required temperatures, 50% heat input, start/stop, temporary loss of load)


- **Phase III – Next**

- **Government IV&V Testing**


Independent Validation & Verification Testing

- **Demonstrate robustness to critical environments**
 - Ground operations
 - Horizontal orientation in different quadrants
 - Start/stop cycling
 - Thermal cycling
 - Steady operation
 - Random vibration simulates launch environment
 - Constant acceleration
 - Simulates potential spin stabilization for short period (days)
 - Simulates spacecraft entry into an atmosphere (entry, decent, and landing or EDL)
- **Inspecting data and hardware to verify robustness**
 - Steady operation period before and after each critical test
 - Partial disassembly desired to enable inspection of running surfaces

Ground Operations




Launch System



Cruise



Spin Stabilization and EDL



GRC Dynamic Power Test Facilities

- GRC's Stirling Research Laboratory (SRL)
 - Able to test dynamic convertors, controllers, and electrically heated generators
 - Unattended 24/7 operation to acquire life & reliability data, automated data collection and archiving, safety provisions for graceful shutdown in case of fault or power outage
 - **1,000,000 hours** of free-piston Stirling convertor operation achieved on October 24, 2018
 - Current record holder for longest operating free-piston Stirling convertor accumulated over 13.2 years of operation
 - Longest running free-piston Stirling convertor after launch vibration has accumulated 9.1 years of operation
 - Longest running free-piston Stirling convertor on engineering unit controller accumulated 4.9 years of operation
- Dedicated thermal vacuum facility for relevant environment tests
 - Over 25,000 hours of convertor operation in vacuum
- Performs tactical and durability tests for IV&V




Generator Extended Operation



Performance Testing & Extended Operation



Centrifuge Test Facility at CWRU



Vibe Testing at GRC Structural Dynamics Laboratory


Stirling Convertor Extended Operation

- Currently 12 convertors are on extended operation testing in the GRC SRL
- **TDC #13 started operation in June 2003 and is the longest running Stirling convertor**


Project & Provider	Test Article	Hrs of Operation
SRG 110 Infinia, Corp.	TDC #13	116,058 (13.2 yrs)
	TDC #15 & #16	108,212 each
	SES #2* (SRG-110 eng unit)	8,820
ASRG Sunpower, Inc.	ASC-E3 #4* , #9	34,210 / 20,253
	ASC-E3 #6* , #8	27,035 / 22,887
	ASC-0 #3*	79,284 (9.1 yrs)
	ASC-L*	42,492 (4.9 yrs)

Cumulative Per-Convertor Runtime as of Feb 24, 2019

*Have undergone random vibrate
(20 years = 175,000 hrs)



TDC #13 Extended Operation




ASC-E3 Pair Extended Operation Test Article


Recent Hardware Assessments

- **TDC #14 inspection after 105,620 hrs of operation (12 years)**
 - No sign of flexure degradation
 - Signs of oxidation on expected surfaces – likely from early non-hermetic operation
 - Geometric stability verified via Coordinate Measuring Machine (CMM)
 - Evidence of oxide residue/dust in various areas – did not degrade functionality of alternator or flexure bearings
- **Random Vibration & Centrifuge Testing of SES #2**
 - Engineering Unit convertor from SRG-110 project successfully passed launch simulation and constant acceleration while operating
 - **Vibration testing:** 10.35 grms profile formulated by SMT, encompasses wide span of launch vehicles, 2 min duration at full random vibrate level
 - » Reduce piston amplitude for axial exposure (expected), temporary reduction in power output during lateral axes exposures (expected)
 - **Centrifuge testing:** Static acceleration exposure up to 5g axial and 20g lateral successfully completed in April 2018
 - SES #2 now operating continuously at full power, 8,820 hrs accumulated


TDC #14 displacer after 12 years of operation




TDC #14 aft flexure stack after 12 years of operation



SES #2 undergoing launch vibration exposure



Centrifuge facility for static acceleration testing of SES #2



Conclusion

- DPC contracts started in late 2017 and are about half way through Phase 2 now
- Fabrication is in progress and first operation is anticipated in late summer
- Contracts have resulted in promising designs thus far
- Research continues at NASA GRC utilizing existing hardware to identify relevant risks
- NASA GRC is preparing for DPC prototype IV&V testing in 2020
- Dynamic Power Convertor for RPS
 - **SMT identified requirements**
 - **Contracts being used to develop conversion technologies**
 - **Government IV&V testing will verify prototypes meet requirements**
 - **Decision Gate 2 could result in recommendation for flight development**



Special thanks to:

- **RPS Program and DRPS Project**
- **Stirling Research Laboratory Team**

Thank you for attending