

Gradient-Based Propeller Optimization with Acoustic Constraints

AIAA 2019-1219

Daniel Ingraham¹ Justin Gray¹ Leonard V. Lopes²

¹NASA Glenn Research Center

²NASA Langley Research Center

AIAA Aviation Forum
June 17th–21st, 2019

This work was supported by NASA's Transformational Tools and
Technologies (TTT) Project.




Urban Air Mobility Represents a New Challenge for Aircraft Acoustics




What We'd Like To Do

Develop toolchain for large-scale **optimization** of a tilt wing turboelectric UAM concept from Johnson et al.[1], with coupled structural, aerodynamics, acoustics, propulsion, thermal, and trajectory disciplines.



What We've Done Here: Propeller Optimization With Fixed Relative Observer (Essentially Wind Tunnel Configuration)



Mid-Fidelity Models, Gradient-Based Optimization Enable Large-Scale Analysis


- ▶ Mid-fidelity aerodynamic models:
 - ▶ Blade element momentum theory (BEMT): Gur and Rosen[2, 3], Wisniewski et al.[4].
 - ▶ Vortex lattice: Miller and Sullivan[5].
- ▶ High-fidelity aerodynamic models:
 - ▶ Computational Fluid Dynamics: Pagano et al.[6, 7].
- ▶ Most examples use some form of the Ffowcs-Williams Hawking (FWH) approach[8] for the acoustic model.

Methods for this work

BEMT and FWH, all with analytic derivatives. Focusing on developing tool chain.




Propeller Aerodynamics: Blade Element Momentum Theory



BEMT Limitations


- ▶ No interaction between blade elements, so spanwise flow not captured (so no blade sweep).
- ▶ Here, used steady, level flight, so predicted loads will be steady (not changing with propeller rotation).
- ▶ OK for steady, forward flight. Probably not adequate for VTOL.

BEMT Implementation: OpenBEMT




- ▶ Initially developed by Hwang and Ning[9] to study the X-57 Maxwell concept.
- ▶ Uses OpenMDAO framework[10] to propagate outputs and their derivatives through each stage of the calculation for gradient-based optimization.

Propeller Acoustics: Ffowcs-Williams Hawking Approach



- Uses distributed flow properties on surface (e.g., propeller blade surface) to calculate source term strengths, and then the acoustic pressure time history at a specified location (“acoustic observer”).

Compact F1A




- ▶ Acoustic prediction method used here: compact version[11] of Farassat's 1A formulation[12, 13] of the FWH approach.
- ▶ Needed inputs directly correspond to BEMT outputs, and about the same computational expense as BEMT.
- ▶ Limitations & Assumptions
 - ▶ Steady loading configuration captures only steady acoustic sources.
 - ▶ Elongated surface in lifting line direction.
 - ▶ Assumes acoustic observer distance much larger than blade thickness.

FWH Implementation: ANOPP2

- ▶ Compact F1A calculation is implemented in NASA Langley's second generation Aircraft Noise Prediction Program[14] (ANOPP2).
- ▶ ANOPP2 is a comprehensive noise prediction framework, much more than just F1A.
- ▶ The Compact F1A implementation has been differentiated for use with gradient-based optimization, and is used in this work.




XDSM Diagram: Optimization Overview



- ▶ D_{hub} : hub diameter
- ▶ $\vec{v}_\infty$: free-stream velocity
- ▶ c_i : chord
- ▶ Y_i : blade element location
- ▶ T : thrust
- ▶ D_{prop} : propeller diameter
- ▶ $\vec{x}$: observer location
- ▶ θ_i : twist
- ▶ $\vec{f}_i$: blade element loading
- ▶ η : efficiency



XDSM Diagram: ANOPP2 Detail



Test Case: X-57 Cruise Propeller Properties

Test case parameters were taken from the NASA's X-57 Maxwell[15] cruise propellers:



Test Case: X-57 Cruise Propeller Properties

Test case parameters were taken from the NASA's X-57 Maxwell[15] cruise propellers:

Property	Value
Altitude	10 m
Cruise speed	77.2 m/s
Diameter	1.5 m
Hub diameter	0.3 m
Airfoil	MH117
Blade count	3



Two Optimization Cases

Multi-objective optimization: **maximize propeller efficiency** for **constant thrust**, with **OASPL constraint** systematically reduced to form a Pareto frontier.

	Variable	Lower Bound	Upper Bound
maximize	efficiency		
with respect to	chord	1 cm	20 cm
	twist	20 deg	90 deg
	Case 2 only: diameter¹	75 cm	150 cm
	Case 2 only: RPM	None	None
subject to	total thrust = 700. N		
	sideline OASPL	x Δ dB	x Δ dB

¹Optimizer chose upper bound for each run.



Optimizations are Pretty Quick

Itns	Major	Minors	Step	nCon	Feasible	Optimal	MeritFunction	L+U	BSwap	nS	cond	ZHZ	Penalty		
10	0	10		1	3.3E-02	5.5E-03	-9.3427573E-01	4		9	1.9E+00			-	r
11	1	1	1.7E-01	3	2.8E-02	4.8E-03	-9.3413416E-01	4		9	1.8E+00	1.2E-01		-	r
12	2	1	1.7E-01	5	2.4E-02	1.8E-01	-9.3408573E-01	4		9	1.7E+00	1.8E-01		-	s
13	3	1	4.3E-02	7	2.4E-02	4.4E-02	-9.3401303E-01	4	1	9	2.6E+00	2.9E-01		-	
14	4	1	2.5E-01	9	2.0E-02	5.1E-02	-9.3403539E-01	4		9	3.6E+00	2.9E-01		-	
16	5	2	7.3E-02	11	1.9E-02	1.1E-01	-9.3403816E-01	4		10	4.5E+00	2.9E-01		-	
18	6	2	1.0E+00	12	2.0E-03	4.6E-02	-9.3394566E-01	4		9	4.8E+00	5.9E-01		-	
20	7	2	1.0E+00	13	1.1E-03	3.9E-03	-9.3397863E-01	4	1	10	7.4E+00	5.9E-01		-	
21	8	1	1.0E+00	14	6.6E-05	1.4E-02	-9.3397529E-01	4		10	7.6E+00	8.4E+00		-	
22	9	1	1.0E+00	15	7.0E-05	3.7E-02	-9.3398045E-01	4		10	8.7E+00	2.9E+00		-	
23	10	1	1.0E+00	16	2.6E-05	2.8E-02	-9.3398412E-01	4		10	6.2E+00	2.9E+00		-	
24	11	1	1.0E+00	17	1.5E-04	2.0E-02	-9.3398490E-01	4		10	7.6E+00	2.9E+00		-	
25	12	1	1.0E+00	18	1.0E-05	2.7E-02	-9.3398664E-01	4		10	1.0E+01	2.9E+00		-	
26	13	1	2.3E-01	20	1.2E-05	1.8E-02	-9.3398804E-01	4		10	8.3E+00	2.9E+00		-	
27	14	1	1.0E+00	21	3.5E-06	1.9E-03	-9.3398892E-01	4		10	1.2E+01	2.9E+00		-	
28	15	1	1.0E+00	22	1.8E-05	5.8E-03	-9.3398934E-01	4		10	1.3E+01	2.9E+00		-	
29	16	1	1.0E+00	23	1.5E-05	3.0E-04	-9.3398972E-01	4		10	1.5E+01	2.9E+00		-	
30	17	1	1.0E+00	24	(3.3E-07)	1.4E-04	-9.3398994E-01	4		10	1.7E+01	2.9E+00		-	
31	18	1	1.0E+00	25	(1.0E-07)	3.3E-03	-9.3399005E-01	4		10	2.2E+01	2.9E+00		-	
32	19	1	1.0E+00	26	1.0E-06	4.2E-04	-9.3399037E-01	4		10	3.8E+01	2.9E+00		-	

Itns	Major	Minors	Step	nCon	Feasible	Optimal	MeritFunction	L+U	BSwap	nS	cond	ZHZ	Penalty		
34	20	2	1.0E+00	27	1.1E-06	4.4E-03	-9.3399069E-01	4		9	2.1E+01	2.9E+00		-	
35	21	1	1.0E+00	28	(8.3E-07)	4.8E-03	-9.3399109E-01	4		9	2.0E+01	2.9E+00		-	
36	22	1	1.0E+00	29	(7.2E-07)	1.6E-04	-9.3399126E-01	4		9	1.9E+01	2.9E+00		-	
37	23	1	1.0E+00	30	(3.1E-08)	4.5E-04	-9.3399127E-01	4		9	1.8E+01	2.9E+00		-	
38	24	1	1.0E+00	31	(1.6E-09)	4.0E-05	-9.3399127E-01	4		9	4.1E+01	2.9E+00		-	
39	25	1	1.0E+00	32	(9.1E-09)	2.1E-04	-9.3399127E-01	4		9	5.5E+01	2.9E+00		-	
40	26	1	1.0E+00	33	(1.3E-09)	2.2E-04	-9.3399127E-01	4	1	9	6.0E+01	2.9E+00		-	
41	27	1	1.0E+00	34	(1.6E-09)	1.2E-04	-9.3399127E-01	4		9	5.7E+01	2.9E+00		-	
42	28	1	1.0E+00	35	(6.0E-10)	2.1E-05	-9.3399127E-01	4		9	4.9E+01	2.9E+00		-	
43	29	1	1.0E+00	36	(2.9E-10)	3.7E-05	-9.3399127E-01	4		9	5.3E+01	2.9E+00		-	
44	30	1	1.0E+00	37	(1.7E-10)	5.9E-05	-9.3399127E-01	4		9	6.1E+01	2.9E+00		-	
45	31	1	1.0E+00	38	(4.2E-10)	5.3E-05	-9.3399127E-01	4		9	5.8E+01	2.9E+00		-	
46	32	1	1.0E+00	39	(3.6E-10)	2.4E-05	-9.3399127E-01	4		9	4.8E+01	2.9E+00		-	
47	33	1	1.0E+00	40	(7.2E-11)	2.8E-06	-9.3399127E-01	4		9	4.7E+01	2.9E+00		-	
48	34	1	1.0E+00	41	(2.8E-12)	(6.7E-07)	-9.3399127E-01	4		9	4.8E+01	2.9E+00		-	


1

SNOPTC EXIT 0 -- finished successfully
 SNOPTC INFO 1 -- optimality conditions satisfied


Time for MPS input 0.00 seconds
 Time for solving problem 9.54 seconds
 Time for solution output 0.00 seconds
 Time for constraint functions 9.54 seconds
 Time for objective function 0.00 seconds




Significant Difference Between the Two Pareto Frontiers




Slower Propellers Are Quiet Propellers




Case 1 Strategy: Shift Chord Inboard to Quiet Propeller




Case 2 Strategy: Increase Chord to Maintain Thrust



Case 1 Strategy: Shift Twist Inboard to Quiet Propeller




Case 2 Strategy: Increase Twist to Maintain Thrust²




²Decreased RPM+increased pitch reminiscent of Berton & Nark[16]


Case 1: Move Axial Loading Inboard




Case 2: Maintain Axial Loading



Case 1: Chord and Twist Impact Circumferential Loading



Case 2: More Chord and Twist Increase Circum. Loading



Conclusions & Future Work

- ▶ Propeller aerodynamics and acoustics codes were combined within an MDAO framework and exercised on two test cases.
- ▶ Near-term next steps:
 - ▶ fixed-observer case with trajectory optimization
 - ▶ Goal is to extend Berton & Nark's[16] recent idea of reducing the noise of a hypothetical propeller-driven electrified GA aircraft through pitch control.
 - ▶ Replace BEMT with higher-fidelity approach
- ▶ Ultimate goal: include this tool chain in a larger UAM optimization (trajectory, power generation, vehicle weight).



References I

- [1] Wayne Johnson, Christopher Silva, and Eduardo Solis. “Concept Vehicles for VTOL Air Taxi Operations”. In: *AHS Specialists’ Conference on Aeromechanics Design for Transformative Vertical Flight*. San Francisco, California: American Helicopter Society, 2018.
- [2] Ohad Gur and Aviv Rosen. “Multidisciplinary Design Optimization of a Quiet Propeller”. In: *14th AIAA/CEAS Aeroacoustics Conference (29th AIAA Aeroacoustics Conference)*. American Institute of Aeronautics and Astronautics, 2008. DOI: 10.2514/6.2008-3073.
- [3] Ohad Gur and Aviv Rosen. “Optimization of Propeller Based Propulsion System”. In: *Journal of Aircraft* 46.1 (2009), 95–106. DOI: 10.2514/1.36055.



References II

- [4] Charles F. Wisniewski et al. “Designing Small Propellers for Optimum Efficiency and Low Noise Footprint”. In: *33rd AIAA Applied Aerodynamics Conference*. American Institute of Aeronautics and Astronautics, 2015. ISBN: 9781624103636. DOI: 10.2514/6.2015-2267.
- [5] C. J. Miller and J. P. Sullivan. *Noise constraints effecting optimal propeller designs*. Tech. rep. NASA-TM-86967. Soc. of Automotive Engr. Gen. Aviation Aircraft Meeting and Exposition; 16-19 Apr. 1985; Wichita, KS; United States. NASA Lewis Research Center, Jan. 1985.
- [6] Antonio Pagano et al. “Tonal and Broadband Noise Calculations for Aeroacoustic Optimization of Propeller Blades in a Pusher Configuration”. In: *15th AIAA/CEAS Aeroacoustics Conference (30th AIAA Aeroacoustics Conference)*. American Institute of Aeronautics and Astronautics, 2009. DOI: 10.2514/6.2009-3138.



References III

- [7] Antonio Pagano et al. “Tonal and Broadband Noise Calculations for Aeroacoustic Optimization of a Pusher Propeller”. In: *Journal of Aircraft* 47.3 (2010), 835–848.
DOI: 10.2514/1.45315.
- [8] J. E. Ffowcs Williams and D. L. Hawkings. “Sound Generation by Turbulence and Surfaces in Arbitrary Motion”. In: *Philosophical Transactions of the Royal Society of London. Series A, Mathematical and Physical Sciences* 264.1151 (1969), pp. 321–342.
- [9] John T. Hwang and Andrew Ning. “Large-scale multidisciplinary optimization of an electric aircraft for on-demand mobility”. In: *2018 AIAA/ASCE/AHS/ASC Structures, Structural Dynamics, and Materials Conference*. American Institute of Aeronautics and Astronautics, 2018.
DOI: 10.2514/6.2018-1384.



References IV

- [10] Justin Gray, Kenneth Moore, and Bret Naylor. “OpenMDAO: An Open Source Framework for Multidisciplinary Analysis and Optimization”. In: *13th AIAA/ISSMO Multidisciplinary Analysis Optimization Conference*. American Institute of Aeronautics and Astronautics, 2010. DOI: 10.2514/6.2010-9101.
- [11] Leonard V. Lopes. “Compact Assumption Applied to Monopole Term of Farassat’s Formulations”. In: *Journal of Aircraft* 54.5 (2017), 1649–1663. DOI: 10.2514/1.c034048.
- [12] F. Farassat. “Linear Acoustic Formulas for Calculation of Rotating Blade Noise”. In: *AIAA Journal* 19.9 (1981), pp. 1122–1130. ISSN: 0001-1452. DOI: 10.2514/3.60051.
- [13] F. Farassat. *Derivation of Formulations 1 and 1A of Farassat*. Tech. rep. NASA/TM 2007-214853. Hampton, VA, United States: NASA Langley Research Center, 2007.



References V


- [14] L. V. Lopes and C. L. Burley. *ANOPP2 User's Manual: Version 1.2*. Tech. rep. NASA TM-2016-219342. Hampton, VA, United States: NASA Langley Research Center, Oct. 2016.
- [15] Nicholas K. Borer et al. "Design and Performance of the NASA SCEPTOR Distributed Electric Propulsion Flight Demonstrator". In: *16th AIAA Aviation Technology, Integration, and Operations Conference*. American Institute of Aeronautics and Astronautics, 2016. ISBN: 9781624104404. DOI: 10.2514/6.2016-3920.
- [16] Jeffrey J. Berton and Douglas M. Nark. "Low-Noise Operating Mode for Propeller-Driven Electric Airplanes". In: *24th AIAA/CEAS Aeroacoustics Conference*. American Institute of Aeronautics and Astronautics, 2018.



Compact F1A

- ▶ Acoustic prediction method used here: compact version[11] of Farassat's 1A formulation[12, 13] of the FWH approach.
- ▶ **Compact** F1A: integration surface is replaced with spanwise lifting line.

$$p(t) = \frac{1}{4\pi} \int \left[\rho_{\infty} \Lambda C_{1A} + \frac{1}{c_{\infty}} \left(\dot{F}_i D_{1A,i} + F_i E_{1A,i} \right) \right]_{\text{ret}} dl$$



C_{1A} , D_{1A} , E_{1A} are function of blade motion only, **large in regions where blade motion is high.**