





Flow Boiling and Condensation Experiment Flight Hardware Development

35th Annual Meeting of the American Society for
Gravitational and Space Research

November 22, 2019

Monica C. Guzik
Henry K. Naha
Jesse H. deFiebre
NASA Glenn Research Center






Flow Boiling and Condensation Experiment (FBCE)

PI Team: Dr. Issam Mudawar, Purdue University
 Dr. Mojib Hasan, NASA GRC
GRC Project Manager: Andrew Suttles, NASA GRC
GRC Project Scientist: Dr. Henry Nahra, NASA GRC
Customers/Adopters (Push): AP1, TSES1, Nuclear Power/Propulsion,
 Thermal Control/Life Support, Chilldown for Cryo Propellant Management

Right to left: Flow Boiling Imaging (Horizontal orientation, 1g); Flow Boiling Imaging (vertical up-flow orientation, low g-Aircraft); Integrated FBCE system on FIR optics bench; Flow Boiling Module Teat Assembly



Objectives

- Develop an integrated two-phase flow boiling/condensation facility for the International Space Station (ISS) to serve as primary platform for obtaining two-phase flow and heat transfer data in microgravity.
 - Obtain flow boiling and flow condensation databases in long-duration microgravity environment.
 - Develop experimentally validated, mechanistic model for microgravity flow boiling critical heat flux (CHF) and flow condensation and dimensionless criteria to predict minimum flow velocity required to ensure gravity-independent CHF.

Experimental Approach

- Study influence of microgravity on two-phase transport phenomena.
- Control variables: temperature, pressure, flow rate.
- Diagnostics: Pressure transducers, thermocouples, high-speed imagery.

Relevance/Impact

- The Rankine cycle is one of the most viable options for space application because of its high power output per unit mass or unit volume.
- TSES1: Conduct research to address issues for active two phase flow relevant to thermal management.
- AP1: Reduced-gravity multiphase flows, cryogenics and heat transfer database and modeling, including phase separation and distribution (i.e.. flow regimes), phase-change heat transfer, pressure drop and multiphase system stability.

Project Development Approach

- Protoflight flight hardware – Flight-functional ground unit for development testing.
- Fluids Integrated Rack (FIR) Subrack Payload Facility.
- Developed, integrated, and operated in-house by GRC Engineering.

Estimated ISS Resource Requirements

Accommodation (carrier)	Fluid Integrated Rack (FIR)
Upmass (kg) (w/o packing factor)	165 kg (estimated - dry)
Volume (m³) (w/o packing factor)	0.2 m ³ (estimated)
Power (kw) (peak)	2500W (estimated)
Crew Time (hrs) (installation/operations)	8 hrs for install (estimated) runs autonomous / Inc 65-69
Autonomous Operation	12 months
Launch/Increment	First Available in Increment 62



Flight FBCE test module in assembly

Award	SCR	RDR	PDR	CDR	FHA	Ops
6/15/2011	11/2011	2/2014	3/2015	1/2018	5/2019	9/2020




FBCE System Overview

FBCE Modules:

- **BHM** – Bulk Heater Module
- **FSMU** – Fluids System Module - Upper
- **FSML** – Fluids System Module - Lower
- **RDAQM 1** – Remote Data Acquisition Module 1
- **RDAQM 2** – Remote Data Acquisition Module 2
- **TMA** – Test Module Assembly (1 of 2 installed):
 - **FBM** – Flow Boiling Module
 - **CM-HT** – Condensation Module - Heat Transfer

FIR Provided Hardware:

- **SAMS** – Space Acceleration Measurement System
- **CCU** – Confocal Control Unit (on back of rack)
- **IPSU-CL** – Imaging Processing Storage Unit – Camera Link (on back of rack)






Fluid Integration Rack


Environmental Control (ECS)

- Air Thermal Control
- Fire Detection & Suppression
- Water Thermal Control
- Gas Interfaces (GN₂, VES, VRS)







FBCE Fluid System Overview






FBCE Fluid System Module - Lower






Fluid System Module - Upper

- Mass flow controller drives a gear pump to provide flow throughout the closed loop system
- Multiple controls in place to prevent over-pressurization
- Degassing contactor removes dissolved gases from test fluid when membrane exposed to vacuum





FBCE Fluid System Module - Upper






Bulk Heater Module



- Primary source of heating to condition test fluid to required test section inlet conditions
- Three 120V primary heaters and three 28V booster heaters can be operated at any time, with backup heaters available
- Multiple safety devices in place to prevent overheating of the test fluid

Color Key:
 Test fluid (nPFH)






FBCE Bulk Heater Module






Test Module Assemblies

Condensation Module - Heat Transfer (CM-HT)






Flow Boiling Module (FBM)

Color Key:	
Test fluid (nPFH)	Water







FBCE Flow Boiling Module






Remote Data Acquisition Modules

Remote Data Acquisition Module 1 (RDAQM1)



**UEI Data Cubes
[Thermocouple
Signal
Conditioning]**

Remote Data Acquisition Module 2 (RDAQM2)




**UEI Data Cube and Custom Sensor
Supply Printed Circuit Board
[Signal Conditioning and Power
Distribution]**





Future Work: Environmental Testing



FBCE in EMI Test Chamber



FBCE System Capabilities and Constraints*

- Capabilities:
 - Test Fluid: normal Perfluorohexane (nPFH)
 - Flow Rate to Test Section: 2 g/s – 40 g/s
 - 2 – 14 g/s for flow condensation experiments
 - 2 – 40 g/s for flow boiling experiments
 - Heat Delivery: up to 1540 W (BHM)
 - FBM additional heat delivery up to 340 W
 - Water Cooling to Test Section: up to 27 g/s
 - Water Inlet Temperature: 16 – 18°C (approximate)
 - Water Return Temperature: 40 – 49°C
 - Test Fluid Degassing Capability
 - Test Fluid Delivery to Test Section: subcooled, saturated, or two-phase mixture
- Constraints:
 - Available power to test section
 - Water cooling to test section limited by system pressure drop and flow required through condenser
 - Volume constraint: 91.44x121.92x48.28 cm³ (36x48x19 in³)

**NOTE: system capability numbers subject to change based on achieving finalized integrated system test results*



Acknowledgements



- Andrew Suttles, Project Manager
- Dr. Issam Mudawar, Principal Investigator
- Dr. Mojib Hasan, Principal Investigator
- Dr. Henry Nahra, Project Scientist
- William Taylor, Chief Engineer
- David Bittner, Chief Safety Officer
- Timothy Schuler, Lead Systems Engineer
- Mark Lefebvre, Assembly, Integration, and Test Lead
- Mark Sorrells, Verification and Validation Lead
- Jesse deFiebre, Fluids Discipline Lead
- Dr. Jeffrey Mackey, Optics and TMA Lead
- Rochelle May, Software Lead
- Daniel Gedeon and Christopher Detardo, Mechanical Technicians
- Robert Paulin, Gary Gorecki, Tiffany Vanderwyst, and Andrew Fausnaugh, Electrical Technicians
- FBCE Engineering Team
- FBCE Project Support Team

