




Preliminary Aeroacoustic Measurements from the AART in the NFAC 40-by 80-Foot Wind Tunnel

Natasha L. Schatzman and Benny Cheung

Spring 2020 Acoustics Technical Working Group Virtual Meeting

April 7-8, Hampton, VA



Outline



- **Introduction**
- **AART wing configurations**
- **Microphone locations**
- **Processing technique**
- **Data Quality**
 - Background noise (no wing, half wing, full wing)
 - Repeatability
 - Point-to-Point
 - Signal to Noise (Full wing and No wing)
- **Data**
 - No wing vs. Half wing vs. Full wing
- **Concluding Remarks**



Introduction



Aerodynamic & Acoustic Rotorprop Testing (AART) Program

- The primary objective: determine the aerodynamics and acoustics related to an auxiliary propulsor mounted behind an isolated wing in the National Full Scale Aerodynamic Complex 40-by 80-Foot Wind Tunnel
- The primary data points match test conditions for in-flow stereo PIV measurements completed in the Ames 7x10 in 2018.
- The propeller consists of a Sensenich L26H commercial off the shelf blade set and hub, with a 26 inch diameter; propeller performance is measured with an internal balance integrated in the test stand
- The wing is a NACA 0015 with a 12 inch chord; 58.5 inches in height for full wing configuration; 40.5 inches in height for the half wing configuration;




Full Wing Configuration

AART Wing Configuration




- Three configuration (no wing, half wing, and full wing) for Army portion of testing, with conditions to include variation of M_{tip} (tip Mach number), M_{tunn} (tunnel Mach number), and yaw.


No Wing



Half Wing




Full Wing





Microphone Locations

- 8 microphones total
- 40AC 1/2" G.R.A.S free-field microphone with G.R.A.S. RA0020 nosecone




Mic #	Dimensional Distance from Rotor Center [inches]			Radial Distance From Rotor Center	
	X	Y	Z	[inches]	[feet]
Mic #6	-6.4	120.6	-110.2	163.4	13.6
Mic #7	101.8	100.4	2.0	143.0	11.9
Mic #8	-6.7	-120.1	-110.3	163.2	13.6
Mic #9	-120.4	124.4	1.4	173.1	14.4
Mic #10	-191.1	71.0	1.8	203.8	17.0
Mic #11	-119.8	-123.6	1.7	172.1	14.3
Mic #12	-4.6	-186.8	3.8	186.9	15.6
Mic #13	101.5	-100.1	1.4	142.6	11.9

NOTE: All measurements referenced to the tip of the bullet-type cap on each mic.

Processing techniques



2048/Rev




*1250 revolutions of data

♦ Frequency range: 0 – 106,680 Hz ($\Delta \sim 100$ Hz), for 6,250 RPM

Outline



- Introduction
- AART wing configurations
- Microphone locations
- Processing technique
- **Data Quality**
 - Background noise (no wing, half wing, full wing)
 - Repeatability
 - Point-to-Point
 - Signal to Noise (Full wing and No wing)
- **Data**
 - No wing vs. Half wing vs. Full wing
- **Concluding Remarks**



Background Noise: $M_{TUN} = 0.204$ (Spectrum)



Aerotares

$M_{TUN} = 0.204$


$M_{TIP} = 0.636$

$C_T = 0.0$

Yaw = 0°

Pitch = 0°

R21 P19 (No wing) ———
 R19 P27 (Half wing) - - -
 R20 P19 (Full wing) - - -



Minimal differences between each configuration are shown for background noise

Background Noise: $M_{TUN} = 0.204$ (Spectrum)



Aerotares


$M_{TUN} = 0.204$

$M_{TIP} = 0.636$


$C_T = 0.0$

Yaw = 0°


Pitch = 0°



Mic#12: 74.3 / 74 / 72.3 dB



Mic#11: 75.7 / 74.3 / 76.7 dB



R21 P19 (No wing) —
R19 P27 (Half wing) - - -
R20 P19 (Full wing) . . .

Minimal differences
between each
configuration are
shown for background
noise

For this presentation,
only Mics 11 (out-of-
plane) and 12 (in-plane)
will be shown from this
point on

Repeatability: Point-to-Point (Spectrum)



Blades on
No Wing


$M_{TUN} = 0.204$

$M_{TIP} = 0.636$


$C_T = 0.05$

Yaw = 0°

Pitch = 0°




Mic#12: 94.2 / 94.3 / 94.1 / 94.2 dB



Run 23 Point 21 ----
Run 23 Point 26 - - - -
Run 23 Point 31 - - - -
Run 25 Point 15 - - - -

Mic#11: 93.7 / 93.8 / 94.1 / 94 dB



**OASPL less than 2
dB variation for this
conditions**

Signal-to-Noise: No wing (Spectrum)




No Wing

$M_{TUN} = 0.204$


$M_{TIP} = 0.636$

Yaw = 0°

Pitch = 0°




Mic#12: 72.4 / 94.4 dB



Run 21 Point 24 (Aerotare) —
Run 37 Point 29 (Blades on) - - -

Mic#11: 74.8 / 93.9 dB



	1st BPF (Δ dB)	2nd BPF (Δ dB)	3rd BPF (Δ dB)
Mic #6	32.4	24.4	22.9
Mic #7	28.4	28.0	2.9
Mic #8	55.4	24.0	25.9
Mic #9	28.9	17.9	13.6
Mic #10	33.3	9.9	11.7
Mic #11	37.9	16.2	16.1
Mic #12	32.5	40.6	26.8
Mic #13	27.4	19.7	16.3

Signal-to-Noise: Full wing (Spectrum)





Full Wing

$M_{TUN} = 0.204$

$M_{TIP} = 0.636$


Yaw = 5°

Pitch = 0°



Run 16 Point 19 (Aerotare) —

Run 34 Point 24 (Blades on) - - -



	1st BPF (Δ dB)	2nd BPF (Δ dB)	3rd BPF (Δ dB)
Mic #6	32.4	24.4	22.9
Mic #7	28.4	28.0	2.9
Mic #8	55.4	24.0	25.9
Mic #9	28.9	17.9	13.6
Mic #10	33.3	9.9	11.7
Mic #11	37.9	16.2	16.1
Mic #12	32.5	40.6	26.8
Mic #13	27.4	19.7	16.3

Adequate S/N for all mics and first three BPF for this condition

Signal-to-Noise: Full wing (Time History)





Full Wing

$M_{TUN} = 0.204$


$M_{TIP} = 0.636$

Yaw = 5°

Pitch = 0°



Run 16 Point 19 (Aerotare) ———
Run 34 Point 24 (Blades on) - - - - -




Mic #11 (out-of-plane)
reveals wing wake
interaction (impulsive)

Outline



- Introduction
- AART wing configurations
- Microphone locations
- Processing technique
- Data Quality
 - Background noise (no wing, half wing, full wing)
 - Repeatability
 - Point-to-Point
 - Signal to Noise (Full wing and No wing)
- Data
 - No wing vs. Half wing vs. Full wing
- Concluding Remarks



No wing vs. Half wing vs. Full Wing (Spectrum)



Blades on


$$M_{TUN} = 0.204$$

$$M_{TIP} = 0.636$$


$$C_T = 0.06$$

$$\text{Yaw} = 5^\circ$$

$$\text{Pitch} = 0^\circ$$




Mic#12: 95.8 / 92.5 / 97.1 dB



Run 36 Point 23 (No Wing) —
Run 31 Point 25 (Half Wing) ···
Run 34 Point 24 (Full wing) ····

Mic#11: 94.3 / 95.8 / 98.9 dB



Frequency (Hz)

Addition of the wing compared to no wing resulted in increase in OASPL

No wing vs. Half wing vs. Full Wing (Time History)



Blades on


$$M_{TUN} = 0.204$$

$$M_{TIP} = 0.636$$


$$C_T = 0.06$$

$$\text{Yaw} = 5^\circ$$

$$\text{Pitch} = 0^\circ$$




Mic#12: 95.8 / 92.5 / 97.1 dB



Run 36 Point 23 (No Wing) ———
Run 31 Point 25 (Half Wing)
Run 34 Point 24 (Full wing)

Mic#11: 94.3 / 95.8 / 98.9 dB



Time history reveals
significance peak-to-peak
difference of no wing
compared to half and full
wing



- Background noise for wing configurations are consistent and minimal.
- Data is repeatable for the 4 selected points
- S/N adequate for further analysis, especially for wing/prop configurations
- Addition of wing and half-wing produced anticipated changes in the unsteady loading noise of the propeller

Further analysis to be completed