



Dynamic Radioisotope Power Systems Status and Path to Flight

Conference on Advanced Power Systems for Deep Space
Exploration

October 29, 2020

Salvatore Oriti
NASA Glenn Research Center
Thermal Energy Conversion Branch

Project Goal

Utilize dynamic energy conversion technology to manifest a next-generation Radioisotope Power System (RPS) for Planetary Sciences

- Conversion efficiency (thermal-to-electric) up to 40% has been demonstrated
- Non-contacting bearings and seals (enables long-life continuous operation)
- Zero degradation via elimination of wear mechanisms
- Macroscopic engineering challenges (high-temp materials, high-cycle fatigue)
- Long-life, maintenance-free capability demonstrated in laboratory:



Electrically-heated DRPS test station at NASA GRC

Test Article	Years of Operation
TDC #13	14.0
TDC #14	12.1
TDC #15	13.9
TDC #16	13.9
SES-2	1.8

Test Article	Years of Operation
ASC-0 #3	10.6
ASC-E3 #4	5.4
ASC-E3 #9	3.8
ASC-L	6.3

Cumulative runtimes on various Stirling convertors at NASA GRC

Left – Flexure Bearing Designs
Right – Gas Bearing Designs

Multi-Mission DRPS Requirements

- Requirements were previously in draft form, and have recently been officiated
- Developed via an interagency team representing mission designers, and Department of Energy
- May be tailored for a 1st mission (i.e. Lunar application design life is only 2 years)


Category	Requirement
Power Output	100 to 500 W_e at Beginning of Life (BOL)
Design Life	17 years (3 yrs storage + 14 yr mission)
Mission Capability	Deep space, Lunar, Mars, Titan, Europa, Enceladus
Efficiency	>20% at $T_{cold} > 100^\circ C$
Specific Power	2 W_e/kg
Fault Tolerance	Single fault tolerant
Degradation	<1.3% per year
Random Vibe	Per GEVS (< 14.1 g_{rms} , depends on mass)
Static Accel	20g for 1 minute, 5g for 5 days
Radiation	100 krad TID



Europa



Titan



Lunar

(Far side & South Aitken Basin)




Recent Generator Design Progress

Three ongoing dynamic conversion development contracts recently produced several viable generator designs

Flexure Isotope Stirling Convertor (FISC)



QTY
6




American Superconductor, Inc. with Teledyne Energy Systems




Power	223 W _e
Efficiency	22%
Mass (w/o power conditioner)	66 kg
# of GPHS	4
Redundancy	50%

Recent Generator Design Progress

Sunpower Robust Stirling Converter (SRSC)




QTY
6



Sunpower, Inc. with Aerojet Rocketdyne	
Power	238 W _e
Efficiency	24%
Mass (w/o power conditioner)	49 kg
# of GPHS	4
Redundancy	50%

Recent Generator Design Progress

Turbo-Brayton Converter (TBC)



Create, LLC. with Aerojet Rocketdyne	
Power	319 W _e
Efficiency	21 %
Mass	133 kg
# of GPHS	6
Redundancy	100%

DRPS Sources Sought Notice

DOE released a Sources Sought Notice for DRPS providers August 2019
Industry Day Q&A held October 2019

- Purpose : Identify system contractors that could provide a DRPS with draft requirements, tailored for the Lunar mission application
- Interagency team evaluated responses, and determined 4 entities to be qualified bidders
- Requests for proposal will be sent to these qualified bidders in the near future
- **System integration contract will build and verify an electrically heated qualification unit**

Lunar mission is a good choice for first use of DRPS

- Short cruise, short design life, RPS enables lunar night survival
- However, Lunar equatorial is perhaps the most tortuous thermal condition
- Commercial Lunar Payload Services (CLPS) mission cadence offers several opportunities
- Tech Demo missions are viable
- DRPS could be used for lander power, or for the science payload, or both
- A system capable of a Lunar mission will likely be capable of all other planetary science missions

NASA GRC's In-house DRPS Testbed


The Thermal Energy Conversion Branch is building a DRPS testbed with in-hand Stirling convertors, to demonstrate the latest system topology

- Will utilize available spare Stirling-cycle machines
- Will enable compelling range of tests not previously possible, that would not be possible until well into a system-development contract:
 - Balancing of the radial array of convertors
 - Disabling one pair and throttling up the other pair (convertor-level redundancy)
 - Convertor redundancy is a critical and compelling feature to encourage the 1st use of dynamic energy conversion on a NASA mission
 - Radiant coupling of heat source to convertors
- Schedule:
 - March 2021: Design review, begin fabrication
 - November 2021: Assembly begins
 - March 2022: Testing begins


NASA GRC's In-house DRPS Testbed

Requirements

- Radial array of free-piston Stirling convertors
- Allows integration of 2 to 4 Stirling convertors
- Centrally located electrical heat source, simulating 2 or 3 GPHS modules
- Radiant heat transfer coupling between electric heat source and convertors
- Maintains the cold-end convertor operating temperature below 100°C, with ambient natural convection
- The inner volume of the housing can be evacuated or filled with an inert cover gas
- Radiator fins are detachable
- Capable of attachment of passive balancers for the two in-plane axes



DRPS testbed



DRPS testbed section view


Controller Development

Dynamic energy convertor output requires power conditioning, and development of this hardware continues

- The recently developed DRPS requirements include new controller fault handling behavior to better mimic RTG characteristics
- Efforts focused on demonstrating availability of control designs that can be used for upcoming DRPS qualification unit contract

Dual Convertor Controller (DCC)

- Engineering unit hardware exists
- Predecessor has operated with Stirling machine for > 6 years
- Currently being upgraded to improve efficiency
- Status: Awaiting upgrades by APL



High Voltage Convertor Controller (HVCC)


- Enables DRPS with higher voltage convertor output (i.e. 50 V_{rms})
- Will incorporate latest fault tolerance requirements
- Status: Breadboard being designed

NASA Analog Controller (NAC)

- In-house GRC design
- Analog components for simplicity and robustness
- Achieves most recent fault tolerance requirements
- Status: Hardware ready for laboratory testing with Stirling convertor




DRPS Notional Schedule




Summary

- DRPS has demonstrated viability for NASA missions via laboratory testing
- Ongoing dynamic energy conversion development contracts have produced system designs, in addition to their multiple conversion prototypes
- System integration contractors have been qualified via a Sources Sought Notice
- An RFP will soon be released to these qualified organizations
- The design phase of a Lunar DRPS contract will begin in FY21
- NASA GRC is designing and building a DRSP testbed to demonstrate the proposed topology and latest operational features being pursued
- Controller methods and hardware continue to be developed for future use in DRPS designs



2x DRPS on concept Lunar ISRU lander



2x DRPS on concept Lunar ISRU lander