



# **In-situ Measurements using a Configurable Architecture Additive Testbed System**

Joseph N. Zalameda,

Samuel J. A. Hocker, Joshua M. Fody, Peter W. Spaeth, Erik Frankforter

Wesley A. Tayon, and Brodan Richter

NASA Langley Research Center

NASA Langley Transformational Tools and Technologies Sub-project Lead

Ed Glaessgen

MOST-AM Consortium Meeting May 5, 2022



# Outline

*TACP - Transformational Tools & Technologies Project*







- Introduction/Motivation
- Configurable Architecture Additive Testbed (CAAT)
  - Overall Description for Selective Laser Melting
  - Calibration of Near Infrared (NIR) Camera
- Measurement Results
  - Melt Pool Imaging on Ti-6Al-4V Plate
  - Comparison to Optical Microscopy
- Recent Efforts
  - Part Builds with In-situ Measurements using Upgraded Cameras
  - Registration and Comparison to Ex-situ X-ray CT
- Summary



# NASA Transformational Tools and Technologies (TTT) Project Introduction



TACP - Transformational Tools & Technologies Project





# Subproject: Materials and Structures



TACP - Transformational Tools & Technologies Project

## Objectives:

Reduce the total Life Cycle Costs by:

### 1. Enabling Certification by Analysis to reduce surprises during flight tests

- Develop and validate eddy resolving methods for airframe and propulsion system applications
- Design and execute CFD validation experiments
- Develop pressure & temperature sensitive paints to support dynamic measurements
- Develop applicable velocimetry techniques for time-resolved unsteady flow

### 2. Increase manufacturing rate and reduce weight of materials during production

- Develop computational validation of additive and other advanced manufacturing processes
- Advance rapid manufacturing of composite unitized structures
- Develop advanced materials and structural concepts

### 3. Decreasing the amount of required maintenance during Operations and Maintenance Phase

- Enable predictive maintenance methods through advances in data fusion methods and techniques






# NASA Transformational Tools and Technologies Project Additive Manufacturing (Metals)



TACP - Transformational Tools & Technologies Project





# In-situ Measurements using Configurable Architecture Additive Testbed (CAAT)



*TACP - Transformational Tools & Technologies Project*

## Objectives



- Investigate the use of a low cost in-situ near infrared (NIR) sensor for real time measurement of the thermal history for improved additive manufactured builds.
- Calibrate the NIR sensor and investigate the measured melt pool size based on varying process parameters.
- Compare the melt pool width with microscopy measurements.

## Payoffs

- Additively manufactured parts must be certified for broad application onto aircraft structures. By documenting the thermal history, process parameters for microstructure can be evaluated and real time inspections can be performed during the AM build. These results can be used to validate thermal models and build process parameters.


# CAAT System Layout

TACP - Transformational Tools & Technologies Project




# Co-axial NIR Optical Path

TACP - Transformational Tools & Technologies Project



Basler acA640-750um





- NIR camera has 640 x 480 FPA, maximum frame rate = 751 Hz, pixel pitch is 4.8 x 4.8 um, configured with focusing optics and 880 nm narrow bandpass filter (875-884nm), resolution approximately 8.55 microns, ROI for images 144 x144, and provides frame rate of approximately 2,000 Hz.



# Effective Radiance and Calibration

TACP - Transformational Tools & Technologies Project

$$Radiance = \frac{1}{2} \int_{\lambda_1}^{\lambda_2} \frac{c_1}{\lambda^5 (e^{\frac{c_2}{\lambda(T+273.15)}} - 1)} * sensor(\lambda) * filter(\lambda) * d\lambda \quad \text{where } c_1 = 2 * h * c^2 \quad \text{and} \quad c_2 = \frac{h * c}{k}$$



NIR Camera


Calibration Source

- Spectral band 875 to 884 nm defined by the 880 nm narrow bandpass filter.
- Camera frame rate approximately 2,000. Hertz with ROI pixel array size of 144x144.
- Temperatures used were 900, 1000, 1100, 1200, 1300, 1400, and 1500 degrees C for integration times were varied 59, 75, 100, 150, 300, 500, 700, 900, 1200, and 1500 micro-seconds.


# NIR Camera Calibration from Blackbody Radiation Source

TACP - Transformational Tools & Technologies Project

### NIR Camera Response




### Calibration Equation from Fit



# In-situ NIR Melt Pool Imaging Results

TACP - Transformational Tools & Technologies Project






# Requirements for Measurement of Melt Pool Width

*TACP - Transformational Tools & Technologies Project*

- Radiometric calibration for interpretation of camera imagery.
- Thermal camera pixel resolution – Measured Pixel Resolution Approximately 8.55 microns.
- Solidus temperature value – 1605 Degrees C (Ti-6Al-4V).
- Blurring due to movement of laser beam vs. camera integration time.
- Surface emissivity value (vary with material, surface geometry and temperature).
- Accurate destructive measurements using microscopy.

# Melt Pool Imagery (Laser Scanning 500 mm/sec) for Various Emissivity Values Compared to Optical Microscopy – Blurring Uncorrected


TACP - Transformational Tools & Technologies Project





# Melt Pool Imagery (Laser Scanning 750 mm/sec) for Various Emissivity Values Compared to Optical Microscopy – Blurring Uncorrected

TACP - Transformational Tools & Technologies Project





# Removal of Blurring using Inverse Filtering

TACP - Transformational Tools & Technologies Project

- Laser velocity of 500 and 750 mm/sec combined with camera integration time (200 microseconds) results in ~ 12 pixel and ~ 18 pixel blur respectively.
- Use Weiner inverse filtering technique to remove camera blur.


$$W(u, v) = \frac{H^*(u, v)}{|H(u, v)|^2 + K(u, v)}$$

$$\text{Deblurred Image } (u, v) = W(u, v) \text{ Blurred Image } (u, v)$$




# Melt Pool Imagery (Laser Scanning 500 mm/sec) for Various Emissivity Values Compared to Optical Microscopy – Blurring Corrected

TACP - Transformational Tools & Technologies Project



# Melt Pool Imagery (Laser Scanning 750 mm/sec) for Various Emissivity Values Compared to Optical Microscopy – Blurring Corrected

TACP - Transformational Tools & Technologies Project




- Inverse deblurring filter helps with agreement, however other factors might be contributing to these errors such as plume effects, calibration errors, sensor blooming, etc.


## Width

TACP - Transformational Tools & Technologies Project

Top Down Image



Melt Pool Width  
by Cross Section  
133.4  $\mu\text{m}$







# Finite Element Modeling of Surface Temperature

TACP - Transformational Tools & Technologies Project

1727 Celsius



Cross Section Measurement of Melt Pool





Model Temperature > 1600 Celsius is Estimated

227 Celsius

- The COMSOL model uses a volumetric heat source and was calibrated to the optical microscopy measurements. The gray center in the middle shows the melt pool and semi-solid regions.

# Preliminary Comparison of Measured Radiance to Model for Melt Pool Width



Model Temperature  
> 1605 Celsius  
is Estimated

- Comparison of in-situ measured melt pool width to model predictions is progressing.
- Radiometric calibration allows for initial comparisons to models however, emissivity, plume effects, powder splatter, varying melt properties, etc. can make things challenging.


# Most Recent Results

TACP - Transformational Tools & Technologies Project

- Higher speed cameras installed for improved temporal and spatial imaging.
- Registration of in-situ measurements to X-ray CT.
- Future work: continue/refine comparison of melt pool width measurements to FEM models for given process parameters.



Photron Nova S6




NIR Camera 1

NIR Camera 2

# Recent Fabrication using CAAT System

TACP - Transformational Tools & Technologies Project

Designed Part



Built Example



- Disk slices represent different build parameters denoted by circumferential numbering scheme.




# In-situ Monitoring Mapping of Built Part

TACP - Transformational Tools & Technologies Project


As built example part

Build mapped with in-situ monitoring measurements

Melt-pool image mean [counts]



Melt pool image, 3kHz sampling rate @ 12bit




Mean = 112.4 counts




# Registered X-ray CT to In-situ Measurements

TACP - Transformational Tools & Technologies Project

Build mapped with in-situ monitoring measurements



Porosity segmented X-Ray computed tomography





# Summary

*TACP - Transformational Tools & Technologies Project*

- A low cost NIR camera was calibrated and used to measure the width of the melt pool on a Ti-6Al-4V plate.
- Blurring effects, due to relatively long integration time, was reduced by inverse filtering.
- Optical microscopy measurements were used to compare the NIR melt pool width with marginal agreement. Need to investigate error in optical microscopy measurements to validate NIR melt pool width measurements.
- CAAT system operational for building AM parts with high-speed cameras used for in-situ measurements.
- Registered in-situ infrared measurements with X-ray CT for volume comparisons.